



## RTEMS - 5.0.0-m2003 Release Notes

04 March 2020

### RTEMS 5 Series Release Notes

These notes cover the dot releases:

5.1


5.0

## 5.1 (open)

### Statistics

Total	754
Fixed	654
Invalid	11
Works for me	8
Duplicate	12
Won't fix	33

### Distribution



### Summary

- #1247 RTEMS does not implement locks needed by multithreaded newlib
- #1394 scandir() fails due to MAXNAMELEN is incorrect
- #1662 termios.c: semaphore not deleted, consequently resulting in failure of rtems\_termios\_open
- #1747 Heap extend allows discontinuous memory regions.
- #1971 Memory leak in tmpfile()
- #2132 <rtems/score/basedefs.h> superfluously includes <limits.h>
- #2133 <rtems/score/basedefs.h> superfluously includes <string.h>
- #2135 times() and \_times() are subject to integer overflows
- #2173 Potential integer overflow problem in EDF scheduler
- #2176 fishy behavior in termios tx task mode
- #2198 Automate doxygen build
- #2207 RTEMS tar does not overwrite.
- #2213 Decreased performance for whetstone benchmark using GCC >=4.5
- #2261 Add coverage report generation support to rtems-tools
- #2266 Move bsp\_pretasking\_hook() into files named bsppretaskinghook.c
- #2284 h8300 gets error linking dl0\* tests
- #2289 rtems\_ada\_self is broken on SMP
- #2305 sp07 needs to be split into an user extensions and a notepad test
- #2306 powerpc/mvme5500/vectors/exceptionhandler.c uses task variables
- #2308 Change uniprocessor INIT task mode to preempt.
- #2325 Broken console driver infrastructure for SPARC
- #2344 Second argument of ualarm() is ignored
- #2350 One watchdog ticks header per scheduler instance
- #2354 Replace red-black tree implementation, change API
- #2355 SPARC: Several shared drivers are not SMP ready
- #2363 SPARC: Silent FP context corruption possible
- #2366 Create a Public API for the Atomic Operations
- #2367 Documentation of User Extensions needs more information
- #2377 rtems\_waf: Tools without a version are not supported
- #2385 Warning from commit "bsps/arm: Do not use \_\_ARM\_ARCH\_7A\_\_"
- #2407 Enable function and data sections
- #2408 Linker set based initialization
- #2412 Improved priority inheritance implementation
- #2420 RSB %source file fails
- #2423 rtems\_iterate\_over\_all\_threads lacks user callback private pointer pass through
- #2428 Add 4.12 Tool Target Configurations to RSB
- #2441 lpc1768 variants fail to build with error in gpio.c
- #2442 Remove avrttest BSP
- #2443 Remove AVR Architectural Port
- #2444 Remove m68k/mvme136 BSP
- #2445 Remove m68k/sim68000 BSP
- #2446 Remove M32R Architectural Port
- #2447 Remove m32r/m32rsim
- #2448 Remove mips/mongoose BSP
- #2449 Remove arm/gba BSP
- #2450 Remove arm/nds
- #2451 Remove arm/gp32 BSP
- #2452 Remove H8300 Architectural Port
- #2453 Remove h8300/h8sim BSP
- #2454 Warning in threadqops.c
- #2455 Warning in spsimplsched02
- #2457 Remove powerpc/ep1a BSP
- #2458 Remove powerpc/score603e BSP
- #2459 Add rtems\_chain\_get\_first\_unprotected() to chain API
- #2464 RSB: Tool patches use the RTEMS version
- #2468 Add Thread Local Storage (TLS) support on x86
- #2477 Remove <rtems/debug.h>
- #2487 Should <https://devel.rtems.org/wiki/TBR/Delete/SpecBuilder> be Deleted?
- #2488 Vagrant Scripts
- #2490 RSB: Use SHA512 instead of MD5
- #2493 Remove notepads
- #2494 Remove task variables
- #2503 mvme5500 BSP: Exception Handler uses deprecated Notepads.
- #2509 Should "[https://devel.rtems.org/wiki/TBR/Delete/BSP\\_Template](https://devel.rtems.org/wiki/TBR/Delete/BSP_Template)" be replaced?
- #2513 Remove m68k/idp BSP
- #2514 Make POSIX API mandatory (except signals and the sporadic server)
- #2515 i386 score/libcpu API Layering Violation
- #2527 Move pc386/tools/bin2boot to rtems-tools
- #2529 BSP for the Atmel SAM V71/V70/E70/S70 chip platform
- #2536 RSB allows use of insecure hash algorithms like MD5 and SHA1
- #2537 Use Newlib exec\*() variants and remove RTEMS versions
- #2542 Review cxx\_iostream size change per function-section changes
- #2543 Obsolete gen68302 BSP
- #2544 Obsolete m68k/ods68302
- #2545 Obsolete mbx8xx BSP

- #2546 Obsolete idp BSP
- #2553 [mvme3100] boot\_card() broken by 37030e38
- #2554 New watchdog handler implementation
- #2555 Eliminate the Giant lock
- #2556 Implement the O(m) Independence-Preserving Protocol (OMIP)
- #2557 Add word splitting to print output
- #2559 Delete the EXTERN pattern
- #2560 smdk2410 is broken due to gp32 removal
- #2562 RSB Docs Quick Start version number
- #2576 arm/lpc176x: linker script update (add KEEP() sections)
- #2606 alarm() uses seconds watchdog and thus is affected by clock changes
- #2608 POSIX Condition Variables Clock Attribute Support
- #2617 rtems\_heap\_allocate\_aligned\_with\_boundary() body and prototype inconsistent
- #2624 Fix the year 2038 problem
- #2625 Use one lookup tree per-thread for the POSIX keys
- #2626 Unify thread cancel/join and delete
- #2627 Fix CPU time used for threads on SMP
- #2628 Avoid home-grown condition variable implementation in the Classic Regions
- #2631 Use an ISR lock to protect the state of Classic Rate Monotonic objects
- #2632 rtems-tester failure
- #2633 waf build failed for rtems-libbsd
- #2634 New warning in pc386 VESA driver
- #2638 pc386: ld -r issue with per function sections
- #2641 configure: enable-rtemsbsp doesn't warn if bsp does not exist
- #2644 sis does not run on gdb 7.11 but does on gdb 7.9
- #2649 RSB remove 4.11, 4.10 and 4.9 from the master branch.
- #2663 pc386 BSP has complex dependencies
- #2664 spclock\_err02
- #2669 Update OpenRISC toolchain in 4.12
- #2672 After latest patches with Objects\_Get\_by\_name rtems-master not compiling without --enable-posix
- #2674 CORE spinlock implementation is next to be useless
- #2676 Obsolete clock\_get() directive
- #2680 Add pthread\_setconcurrency() and pthread\_getconcurrency()
- #2684 rtems/c/src/lib/libbsp/sparc/leon3/clock/ckinit.c:122: duplicate if
- #2685 c/src/lib/libbsp/arm/atsam/network/if\_atsam.c:409: possible bad if statement
- #2689 POSIX key destructors must be called during thread restart
- #2692 User extensions execution order must be clarified
- #2693 Update doc to reflect obsoleting rtems\_clock\_get()
- #2694 linking issue for htonl, etc when using -std=c99
- #2695 Add libatomic for RTEMS
- #2696 Unpredictable errno value returned by sem\_wait() in case of semaphore deletion
- #2698 GCC 6.1 is broken for microblaze
- #2700 cpukit/libfs/src/nfsclient/src/rpcio.c:524: (style) Suspicious condition
- #2701 Rename asm file with .S(upper case) ext. name
- #2702 Remove descriptor objects for POSIX message queues
- #2706 Buffer allocation of capture engine is broken on SMP configurations
- #2707 Unsafe use of current processor index in capture engine
- #2714 A pthread\_detach() does not lead to a resource reclamation
- #2718 Blocking \_CORE\_message\_queue\_Submit() may lead to unpredictable results
- #2722 SEM\_VALUE\_MAX is unusually small on RTEMS
- #2723 CPUINFO command to report per-processor information
- #2725 Classic binary semaphores without a locking protocol can be released by everyone
- #2726 grasc.c: Questionable use of binary semaphore
- #2727 FAT file systems use wrong semaphore for mutual exclusion
- #2728 Pipes use wrong semaphore for mutual exclusion
- #2729 TFTP client uses wrong semaphore for mutual exclusion
- #2732 Add clock\_nanosleep()
- #2734 pthread\_setschedprio() is missing
- #2735 pthread\_setschedparam() sets the priority not according to POSIX
- #2736 pthread\_getschedparam() returns wrong priority values
- #2737 Add CLOCK\_DRIVER\_USE\_ONLY\_BOOT\_PROCESSOR
- #2740 Suboptimal type for Timestamp\_Control
- #2741 New warning from printf plugin changes
- #2742 New warning in SHM driver
- #2745 Use clock from pthread\_condattr in pthread\_cond\_timedwait
- #2748 Move RTEMS-specific socket wake-up to RTEMS-specific <rtems/rtems\_bsdnet.h>
- #2749 rtems\_task\_set\_scheduler() has insufficient parameters
- #2750 Compile Error When Multiprocessing Enabled
- #2751 Thread dispatch via interrupt is broken at least on ARM and PowerPC
- #2752 Relax execution environment for thread begin extensions
- #2754 no .strtab section
- #2765 Application level deadlocks may lead to SMP lock level deadlocks
- #2768 untar does not keep permissions correctly.
- #2769 rtems-syms does not clean up temp files.
- #2770 Missing documentation for RTEMS\_LINKER\_ROSET\_CONTENT and RTEMS\_LINKER\_RWSET\_CONTENT
- #2771 Empty C++ file with just <rtems.h> does not compile with HEAD.
- #2775 ARM CP15 arm\_cp15\_set\_translation\_table\_entries fails if TTB in read-only memory
- #2776 SPI Framework
- #2777 Remove librtems++
- #2784 Add function to get the current priority of a task by scheduler instance
- #2788 RTEMS I2C API only defines Standard-mode (Sm) speed as a default.
- #2790 Linker sets broken with GCC 7
- #2795 Overrun Handling for general real-time models
- #2797 Add ability to add/remove processors to/from a scheduler instance
- #2798 Fix POSIX timer interval
- #2800 qorIQ variants failing to build
- #2802 Test "libdl (RTL) 5" fails on SPARC targets
- #2803 Get rid of CPU\_BIG\_ENDIAN and CPU\_LITTLE\_ENDIAN
- #2805 Use SPRGO on PowerPC for current per-CPU control (SMP only)
- #2807 rtems-docs repository is not known to trac
- #2808 Conditionally provide rtems\_interrupt\_frame
- #2809 Reduce interrupt latency on SMP configurations during thread dispatch
- #2810 Remove sparc/sis BSP variant
- #2811 More robust thread dispatching on SMP and ARM Cortex-M
- #2816 Many ARM BSPs have Static Assert
- #2817 All Blackfin BSPs do not Compile on Master
- #2818 NIOS2 Does Not Compile on Master
- #2819 powerpc-ss555 does not compile on master
- #2820 All SPARC64 BSPs do not Build on master
- #2821 No BSPs Build on Master

- #2822 m32csm does not build on master
- #2823 Nearly all m68k BSPs do not Build on Master
- #2824 arm/lpc23xx\_tti800 no longer links tar01
- #2825 Improve the fatal error handling chapter of the user manual
- #2826 arm\_cp15\_get\_translation\_table\_base\_control\_register warning.
- #2829 xz git URL in README is broken
- #2835 Ada support is broken on SMP configurations
- #2836 Add posix\_devctl()
- #2838 Termios task driven mode should use mutex for device operations
- #2839 Add new interrupt server driven Termios mode
- #2840 Use self-contained mutexes for Termios framework
- #2841 Add NXP SC16IS752 serial device driver
- #2843 Use self-contained objects instead of Classic API for drivers and support libraries
- #2844 JFFS2: Add IO controls to get filesystem instance information and force a garbage collection
- #2845 Add I2C framework documentation
- #2849 ATA/IDE support in RTEMS is out-dated
- #2850 Driver manual covers non-existent Analog Driver
- #2851 Driver manual covers non-existent Discrete Driver
- #2853 Driver manual covers non-existent Non-Volatile Memory Driver
- #2858 Add user defined thread names
- #2859 Implement POSIX Shared Memory Objects
- #2862 docs.rtems.org Add support to ReST format releases.
- #2863 Update POSIX 1003.1 Compliance Guide for ReST
- #2864 docs.rtems.org Automatic update of branches content when a rtems-doc.git change is made.
- #2865 Coverage installed when building the docs repeats catalogue.xml entries
- #2867 Fix exclude rule in rtems-test-check
- #2868 src/c/src/lib/libbsp/arm/smdk2410/smc/smc.c: 3 \* pointless local variables ?
- #2873 src/c/src/lib/libbsp/arm/raspberrypi/i2c/i2c.c:320: defective error checking ?
- #2874 src/c/src/lib/libbsp/powerpc/beatnik/marvell/gt\_timer.c: 4 \* pointless check ?
- #2877 DHCP client fails on complex networks
- #2878 src/c/src/lib/libbsp/sparc/shared/can/occan.c:1573: broken error checking ?
- #2879 src/cpukit/libdebugger/rtems-debugger-server.c: four problems
- #2880 src/cpukit/libfs/src/jffs2/src/readinode.c:189: faulty logic
- #2883 src/c/src/lib/libbsp/arm/tms570/console/tms570-sci.c:248: strange expression ?
- #2885 Fix rtems\_rate\_monotonic\_postponed\_job\_count() prototype
- #2889 RTEMS\_STACK\_CHECKER\_EXTENSION has incomplete definition
- #2890 \_RBTree\_Initialize\_node generates warnings
- #2893 Remove CONFIGURE\_SMP\_APPLICATION
- #2894 Rename CONFIGURE\_SMP\_MAXIMUM\_PROCESSORS to CONFIGURE\_MAXIMUM\_PROCESSORS
- #2895 Prefix the confdefs.h internal defines with an underscore
- #2896 RSB requirements are missing pax
- #2897 Update termios.h to match the latest FREEBSD definitions
- #2905 Merge LEON
- #2906 rtems-doc waf configure does not detect sphinxcontrib.bibtex status
- #2909 xz: Support for 64-bit CRC is build although XZ\_USE\_CRC64 is not defined
- #2912 libdebugger: control reaches end of non-void function
- #2916 termios: Change receive callback invocation to enable select() and poll() support
- #2917 termios: Make write POSIX compatible
- #2922 libdl unresolved externals that use more than one block or multiple entries corrupts.
- #2923 Questionable Code in resource\_snapshot.c
- #2924 Warnings in SPARC BSPs
- #2925 Warnings in rti-obj-cache.c on some targets
- #2930 Coverity Reports Out of Bounds Read in drvmgr\_print.c
- #2933 Flexibleassignto is broken on new ticket page.
- #2935 Termios task driven mode not compatible with SMP
- #2941 building rsb freezes
- #2942 rtems building error
- #2943 rtems building error
- #2945 Many failures on LEON3 with SMP disabled
- #2946 Add a top level global testsuite configuration file (.tcfg) and a 'user-input' test state.
- #2949 Questionable patch organization in RTEMS tools and RSB
- #2951 Error path in rtems-gcc-6.3.0-newlib-2.5.0.20170228-1.cfg
- #2954 ARM: Optimize context switch
- #2957 Shared memory support internal locking is broken
- #2958 Add some popular benchmark programs to the testsuite
- #2959 arm/libdl: C++ exception index tables may not be ordered correctly
- #2962 Set test configurations to reflect test results.
- #2963 Add a testsuite top level configuration file that is common to all tests.
- #2965 bootstrap sort inconsistent with sb-bootstrap for acinclude
- #2967 ARM: Change ABI to not use short enums
- #2968 newlib inttypes.h is missing some methods
- #2969 qoriq BSPs depend on mkimage which is not always available
- #2976 warnings in rtems-debugger-server.c
- #2977 warnings in Dhrystone Benchmark
- #2980 pc586-sse does not compile fsjffs2gc01
- #2981 testdata excludes on included tcfg files does not work
- #2982 LibBSD broken with GCC+RTEMS changes
- #2983 Create <rtems/inttypes.h> to consolidate extensions to <inttypes.h>
- #2984 Changing Trac milestone page fails.
- #2990 RTEMS Source Builder Fails on Windows Builds
- #2992 Long path crashes the RSB when listing a directory.
- #2993 SMP assert in \_Thread\_Executing in libdebugger
- #2994 tar01 XZ error
- #2995 Missing bsets
- #2997 Monitor config command does not handle unlimited objects.
- #2998 RTEMS User Manual Quick Start does not cover releases.
- #2999 sb-check on Cygwin
- #3000 Setting interrupt level in the mode arg on SMP returns RTEMS\_UNSATISFIED
- #3001 SMP build of RTEMS Testsuite does not set CONFIGURE\_MAXIMUM\_PROCESSORS
- #3003 FAT does not support clusters bigger than 32K
- #3006 SPARC LEON3 BSP SMP build is broken.
- #3007 ARM caching issues
- #3008 missing pax causes install failures
- #3009 Provide invalid link handler for docs.rtems.org so old docs can be removed.
- #3010 src/cpukit/posix/src/mmap.c:189]: (style) Suspicious condition
- #3011 Error compiling xilinx\_zynq\_zedboard.
- #3012 Global C++ IO streams are broken (cout, cin, cerr)
- #3013 ProgrammingError: (1064, "You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'sid='nikolaykomashinskiy' AND authenticated=1 AND name='force\_change\_passwd' at line 1")
- #3014 interrupt vector indexing is assuming BSP\_INTERRUPT\_VECTOR\_MIN = 0 for this code.

- #3015 Add support for IBM PPC 750 chip
- #3016 missing a couple register names + a #ifndef \_\_ASM\_\_ around serial.h inclusion
- #3017 improvement in pci.h
- #3018 RSB cannot compile tool chain in CentOS 7.
- #3023 Parameter of CPU\_COPY() are in wrong order
- #3025 m32c/m32csim does not build linpack-pc.c
- #3027 RTEMS source builder fails when building gcc documentation with newer versions of gcc
- #3032 CPU\_NAND\_S() implementation is not in line with FreeBSD
- #3036 CPU\_CMP() implementation is not in line with FreeBSD
- #3040 Cannot use RTEMS mailing list archive for patches
- #3043 4.11/rtems-nios2 does not build on Windows.
- #3046 4.12/rtems-moxie missing release number.
- #3047 Remove docs directory from the RSB
- #3049 Warnings in libdebugger
- #3052 RSB: powerpc GDB build broken on Apple Darwin
- #3054 gdb 7.12.1 on RSB 4.12 branch fail to build on Archlinux
- #3056 Add EDF SMP scheduler
- #3057 Add a workaround for the LEON3FT store-store errata
- #3059 Add a simple processor affinity support to the EDF SMP scheduler including 'unistd.h' in C++ does not build.
- #3063 Make the EDF scheduler the default SMP scheduler
- #3069 Add rtems\_scheduler\_ident\_by\_processor()
- #3070 Add rtems\_scheduler\_ident\_by\_processor\_set()
- #3071 Create an interrupt server for every processor in the system
- #3072 Declaration of global functions in driver source files
- #3076 Test suite failures due to floating point usage
- #3077 SPARC: Add lazy floating point context switching
- #3079 Ada tests do not build
- #3080 Infinite loop in SPARC rtems\_invalidate\_multiple\_instruction\_lines()
- #3082 Add 64-bit support for PowerPC
- #3083 parallel make not working
- #3084 Makefile recipe override warning has returned
- #3085 Add hypervisor support for QorIQ BSPs
- #3087 RSB rtems-gdb-7.12-1.cfg MD5 value is ERROR
- #3088 shell test in testsuites/samples/fileio many COMMANDs is lost
- #3089 Inconsistent blocking addressing in RFS
- #3090 Add BSP for i.MX 7
- #3091 Core Dump in powerpc-rtems4.12-ld
- #3096 Shell internal commands should be public.
- #3098 Add new RTEMS repos to github.
- #3099 Add RTEMS FDT wrapper and shell command to libmisc
- #3100 Add Xilinx AXI I2C driver
- #3101 Add I2C Drivers for LM25066A, TMP112, ADS1113 and ADS1115
- #3102 rtems-exeinfo does not decode ARM static constructors.
- #3103 rtems-tools on CentOS 7 Build Failure
- #3109 Add RISC-V support
- #3111 Newlib: Change time\_t and clock\_t integer types to 64-bit
- #3112 POSIX: Make pthread\_mutex\_t self-contained
- #3113 POSIX: Make pthread\_cond\_t self-contained
- #3114 POSIX: Make pthread\_barrier\_t self-contained
- #3115 POSIX: Make pthread\_rwlock\_t self-contained
- #3116 POSIX: Make sem\_t self-contained
- #3117 score: Optimize \_Thread\_queue\_Enqueue() timeout handling
- #3121 clock() implementation in Newlib is broken
- #3122 Simplify and unify BSP\_output\_char
- #3123 GDB 8.0.1 is broken on FreeBSD 11
- #3124 Ignore pshared attribute for POSIX semaphores
- #3125 Accept PTHREAD\_PROCESS\_SHARED for POSIX mutexes
- #3126 Accept PTHREAD\_PROCESS\_SHARED for POSIX barriers
- #3127 MIPS tool build on Darwin (MacOS) fails.
- #3128 RTEMS Tools corvar does not build on Windows.
- #3129 RTEMS Tools covoar build fails on Windows
- #3130 RTEMS Doxygen.in latex output does not build
- #3132 Add reference counting to file descriptors
- #3133 Remove rtems\_libio\_t::driver
- #3134 Remove LIBIO\_FLAGS\_CREATE
- #3135 Devel mailing list doesn't work and Git push impossible due to disk full
- #3136 Use FIFO for file descriptor free list
- #3137 Accept PTHREAD\_PROCESS\_SHARED for POSIX condition variables
- #3139 Remove old ISR parameter from Clock\_driver\_support\_install\_isr() and make it optional
- #3140 CPU Kit broken with --enable-rtems-debug
- #3141 Change the BSP Howto's name to something smaller.
- #3142 POSIX: Reduce size of pthread\_once\_t and make it zero-initialized
- #3148 PSXRDWRV Test failure on Beaglebone Black
- #3152 Beaglebone Black crashes on u-boot master build.
- #3153 Accept PTHREAD\_PROCESS\_SHARED for POSIX rwlocks
- #3157 PowerPC tools don't build on 32-bit hosts
- #3158 Examples v2 does not build
- #3159 Examples v2 trace linker ini files reference non-existing dump-on-error
- #3160 Trace linker score support is broken
- #3163 Add I2C device driver for temperature sensor LM75A
- #3166 New default ticket assignee: NeedsReview
- #3167 Internal status codes must not depend on RTEMS\_POSIX\_API
- #3168 Simplify POSIX\_API\_Control
- #3170 Use BSP\_output\_char via RTEMS printer or simple console driver for test output by default
- #3171 RSB GCC does not build on High Sierra and APFS
- #3172 i386 PC BSP does not reset when bsp\_reset is called.
- #3173 Xilinx AXI I2C driver IP race condition causes clock glitch.
- #3174 Remove rtems\_pthread\_attribute\_compare()
- #3175 Merge FreeBSD timecounter changes from 2015-01-20 to now
- #3176 \_\_getreent in libc.a and generated by confdefs.h
- #3177 Replace/update POSIX Compliance Guide
- #3178 Update sh-rtems4.12 bset to use rtems-default (using old gcc)
- #3179 New warnings from Time Changes
- #3180 ar warning: 'u' modifier ignored since 'D' is the default (see 'U')
- #3181 Various cc1plus warnings for "valid for C/ObjC but not for C++"
- #3182 CLOCK\_REALTIME timeout implementation is not POSIX compliant
- #3185 Change uptime seconds to int32\_t
- #3187 smptests/Makefile.am Issues
- #3188 Add C11 Threading Examples

- #3189 MUTEX\_INITIALIZER missing braces warning
- #3190 RTEMS Tester covoar does not link on MacOS
- #3191 RTEMS Tester covoar dies with no arguments.
- #3198 Add lazy update of line control and baud divisor to NS16550 serial driver
- #3200 m32c tests don't build -- test\_context too large
- #3201 epiphany tools checksum error
- #3202 or1k tools build error
- #3203 Upgrade trac to fix numerous problems.
- #3204 Exception in rtems-test
- #3205 Relative timespec timeouts are subject to integer overflows
- #3207 Supported Architectures Page is out of date
- #3209 RSB should fail on this error
- #3210 Improve the RSB build email message
- #3211 Fix pthread\_create() with user provided stack
- #3212 Qemu Fails to Build, RSB Gives Odd Traceback
- #3213 Move erc32, leon2, leon3, psim and jmr3904 to Tier 2
- #3215 Configuring a System Still Includes Notepads and Has Wrong Heading
- #3216 Replace vprintk() implementation
- #3217 Add RTEMS version, build and tools details to tests
- #3218 Termios canonical mode (ICANON) does not return input line by line
- #3219 Zynq BSP missing linker option --gc-sections
- #3220 Change RTEMS release number scheme from 4.12 to 5
- #3221 RSB wiki page duplicates documentation
- #3224 Upgrade or1k and m32c to Binutils 2.29
- #3225 Upgrade m32c to GDB 8.0.1
- #3226 gdb: pr 16827, fix sim on Mavrck
- #3227 sb-check fails on Msys2 64-bit
- #3228 aarch64 missing from 5/rtems-all build set
- #3229 Add index to all documents.
- #3231 RTEMS Top level README needs updating.
- #3232 Use of `.. include::` in the User Manual should be changed.
- #3234 Quick Start Instructions Inconsistent
- #3235 Fix rtems\_semaphore\_flush() for priority inheritance semaphores
- #3236 Fix thread queue owner priority update in \_Thread\_queue\_Flush\_critical()
- #3237 Fix priority ceiling updates
- #3238 Git push to Trac with more than one commit does not update tickets.
- #3239 Add getentropy() implementation provided by each BSP
- #3240 cpukit/libmisc/stackchk/check.c stack addresses formatted incorrectly.
- #3242 Workarounds for UT699, UT700, and GR712RC errata
- #3243 Simplify global construction
- #3244 Change rtems\_panic() implementation and document this function
- #3245 Replace BSP\_panic() with rtems\_panic()
- #3246 Remove \_BSP\_Fatal\_error()
- #3247 Remove BSP-specific defaults for RTEMS\_BSP\_CLEANUP\_OPTIONS()
- #3248 Add BSP\_VERBOSE\_FATAL\_EXTENSION to RTEMS\_BSP\_CLEANUP\_OPTIONS
- #3249 imx7 does not link getentropy01 test on master
- #3254 Reorganize header files to avoid "make preinstall"
- #3255 Warnings on 64-bit targets
- #3256 Ada run-time needs support for self-contained POSIX synchronization objects
- #3260 libpci depends on BSP-specific header files
- #3261 A couple of documentation typos
- #3264 Add monotonic watchdog based on uptime
- #3265 Use second one based uptime for CLOCK\_MONOTONIC for FreeBSD compatibility
- #3266 cpukit/libpci references BSP headers.
- #3267 rtems/status-checks.h calls printk without including the needed header.
- #3268 PowerPC BSP include naming mess.
- #3270 Remove unused support for MPC505
- #3273 RSB removed used tools configuration files.
- #3277 QorIQ: Add MAC-less DPAA driver to libbsd
- #3278 bsp-builder has incorrect print (%s in output)
- #3281 Add epiphany support to GDB 8.0.0
- #3283 Bad URL in OpenOCD/Xilinx\_Zynq Wiki Page
- #3284 RSB uses hard coded GCC binary paths
- #3285 Reorganize BSP source directory
- #3290 Add device tree support to Altera/Intel Cyclone V BSP
- #3294 gcc version report for released tools is wrong.
- #3298 dlerror non-conformance
- #3305 Add paravirtualization support to ARM
- #3306 Add paravirtualization support to PowerPC
- #3307 PowerPC linkcmds.base missing wildcards on some sections
- #3309 rtems\_task\_create's initial\_mode SMP update
- #3312 RSB macro calls such as define fail on unicode keys.
- #3315 Move expat's home site to github from SF.
- #3318 Improve INTERNAL\_ERROR\_THREAD\_EXITTED to show the id and thread name
- #3320 Add a simple task console driver
- #3323 mhttpd's http etag can result in invalid caching in a browser.
- #3325 Simplify clustered scheduler configuration
- #3327 Eliminate score/cpu/\*/.types.h
- #3328 bootstrap uses non-POSIX compliant echo -e
- #3329 Trac Login Failure (bad password) Causes Internal Error
- #3334 deadlock in \_once()
- #3339 Several PowerPC linker commands do not support constructors/destructors with priority
- #3340 gen83xx warning for macros redefined
- #3341 sparc64: Macro Redefined
- #3342 pthread\_setschedparam() has incorrect prototype
- #3343 pthread\_mutex\_getprioceiling() has incorrect prototype
- #3344 mcf5272/mcf5272.h Timer3 Duplicate Definition
- #3345 mvme3100 spaces needed around quote in macro definitions in bsp.h
- #3346 bf533.h
- #3348 beatnick:spaces needed around quote in macro definitions in bsp.h
- #3349 pc386 edid.h invalid macro names
- #3350 sptimecounter02 warning due to defining \_KERNEL and disabling part of <sys/time.h>
- #3352 Warning in all lpc176x variants
- #3354 PowerPC BSPs duplicate PAGE\_MASK, etc redefinition
- #3358 Deprecate rtems\_disk\_create\_phys(), etc.
- #3374 rtems-test does not honor --mail-from argument
- #3375 Remove command line pre-processor defines
- #3376 Remove cklength program
- #3377 Remove eolstrip program
- #3378 Remove unhex program

- #3379 Remove packhex program
- #3380 Move rtems-bin2c program to rtems-tools
- #3381 rtems-test command line documentation appears to be out of date
- #3382 Testsuite Makefile merge to one per group of tests
- #3383 Require --enable-rtemsbsp with --enable-smp or --enable-multiprocessor
- #3384 Prefer int for int32\_t
- #3385 Generate an error if RTEMS's gcc is not found when the user runs configure
- #3386 Trac's git changeset browsing is suspect.
- #3387 Add subdir-objects to automake flags
- #3388 rtems-tester: possible parsing error for qemuprep-altivec on exclude SMP configuration
- #3389 Warning flags have disappeared with recent autoconf changes
- #3390 NFS: Remove support for cexp
- #3392 infinite loop in RSB's path when a prefix path is not writable
- #3395 rtems-ld does not remove executable when there is an output error
- #3396 rtems-ld does not handle R\_ARM\_V4BX relocation records
- #3397 The register keyword is deprecated in C++11
- #3401 dl06: tms570\* Mixed LSB/MSB Error
- #3402 dl06: mips hurricane Mixed Endian Error
- #3403 RSB RTEMS tool set build is irreproducible
- #3407 Move Gaisler.org and Gaisler.se hosted RSB patches to rtems.org
- #3409 Strip down configure checks to the bare minimum
- #3410 Remove bin2boot program used by i386 BSPs
- #3411 qemuppc does not install linkcmds.base
- #3413 examples-v2 both \_hello and triple\_period fail to build
- #3415 Add examples and tests as components
- #3416 Update Ubuntu RSB Instructions for 17.10
- #3417 Add libdwarf to elftoolchain and provide a C++ wrapper
- #3418 Remove difftest and sorttimes test tools
- #3419 Always build network services (tftps, ftps, ftpd, telnetd, libdebugger)
- #3421 New Trac components for Coverage and Trace
- #3423 examples-v2: m68k/powerpc BSPs undefined reference to \_Thread\_Life\_action\_handler
- #3424 examples-v2: no MIPS BSPs pass configuration step
- #3425 examples-v2: PowerPC fails to build fat\_ramdisk
- #3432 Remove Simple SMP Priority Scheduler
- #3433 Add SMP support for RISC-V
- #3434 Add CONFIGURE\_MINIMUM\_POSIX\_THREAD\_STACK\_SIZE configuration option
- #3435 Add test case for CONFIGURE\_BSP\_PREREQUISITE\_DRIVERS configuration option
- #3436 Remove clock driver Clock\_driver\_support\_shutdown\_hardware() hook
- #3437 Replace use of printf() in free() with a fatal error
- #3443 Remove shgen program
- #3444 Remove nios2gen program
- #3445 Remove multigen script
- #3446 Remove cvsignore-add.sh script
- #3447 Remove rtems-testsuite-autostuff script
- #3451 Remove size\_rtems script
- #3452 Update RISC-V tool chain to support standard 64-bit chips
- #3453 Add RISC-V GDB
- #3454 Tracing Framework Documentation in User Manual
- #3455 Remove install-if-change script
- #3458 rtems-test should not use the env PATH to find covoar
- #3459 Rework initialization and interrupt stack support
- #3460 GDB 8 SIS LEON2 LEON3 Patches
- #3461 Canadian cross compilation of RTEMS tools not supported for x86\_64-w64-mingw32
- #3463 Convert covoar to use DWARF function data
- #3465 Integrate all changes from Linux v3.11 to v4.17 made in the JFFS2 sources
- #3471 Update libfdt as of date 2018-07-09
- #3472 Update of libbsd to a version close to the FreeBSD 12 release
- #3475 Add RTEMS\_PREDICT\_TRUE() and RTEMS\_PREDICT\_FALSE() for static branch prediction hints
- #3478 RISC-V BSP Tester Cleanup Needed
- #3480 CONFIGURE\_MINIMUM\_TASK\_STACK\_SIZE may affect CONFIGURE\_INTERRUPT\_STACK\_SIZE
- #3482 Relax the buffer alignment required by rtems\_partition\_create()
- #3484 RFS: Remove stray call of rtems\_disk\_release() in rtems\_rfs\_buffer\_sync()
- #3486 Use uintptr\_t and size\_t instead of uint32\_t in rtems\_partition\_create()
- #3488 Remove CONFIGURE\_HAS\_OWN\_MOUNT\_TABLE
- #3489 Obsolete CONFIGURE\_HAS\_OWN\_CONFIGURATION\_TABLE
- #3490 Remove CONFIGURE\_HAS\_OWN\_CONFIGURATION\_TABLE
- #3491 Align mprotect() prototype with POSIX
- #3496 Remove superfluous interrupt enable in \_Thread\_Dispatch\_enable()
- #3498 Command and Variable Index is empty
- #3499 The "Index" chapter is empty
- #3500 Change rtems\_waf's RTEMS path check from `bin` to share/rtems<version>
- #3501 MSR\_RI defined multiple places
- #3502 PL111\_LCD\_CONTROL\_LCD\_BPP\_16 Redefined
- #3503 PDF Documentation is missing an index
- #3504 Warning and formatting in bsp/powerpc/mpc55xxevb/dev/dspi.c
- #3505 powerpc/virtex redefined warning
- #3506 waf for building RTEMS applications needs updating
- #3507 Add flexible per-CPU data
- #3508 Add support for thread to processor pinning
- #3510 ATA driver uses deprecated rtems\_blkdev services
- #3511 int/pointer size warnings in powerpc-qoriq\_e6500\_64
- #3512 sb-check: No python command with Python 2 and Python 3 installed
- #3513 Convert tqm8xx console driver to new Termios API
- #3516 sb-set-builder should report disk usage of build
- #3517 RSB Ubuntu Host Requirements Missing Some
- #3518 RSB MacOS Nits
- #3519 RSB does not strictly check args
- #3520 Remove CONFIGURE\_HAS\_OWN\_FILESYSTEM\_TABLE
- #3522 Update mDNSResponder to Apple version v878.30.4
- #3523 Add FEC network interface driver for TQM8XX
- #3525 Add MMC/SDCard support for i.MX 7Dual BSP
- #3526 Convert PTY driver to new Termios API
- #3528 Remove undocumented and untested CONFIGURE\_MAXIMUM\_PTYS
- #3529 Fix issues raised by Coverity Scan for Telnet server
- #3530 Fix issues raised by Coverity Scan for FTP server
- #3531 Add POSIX Attribute Reports for More Than Scheduler (examples-v2)
- #3532 RSB source only download is host specific
- #3533 Add rtems\_task\_exit()
- #3535 Remove stdin, stdout, stderr convenience routines for CEXP
- #3536 Move RTEMS configuration data to a common `config` directory

- #3537 RSB and RTEMS Tools Support for python2 and python3
- #3538 Classic API Barrier Wait Section Title Has Wrong Name
- #3539 Remove CPU\_PROVIDES\_IDLE\_THREAD\_BODY
- #3542 Remove keep\_stdio feature from Telnet service
- #3543 Change Telnet server to allocate most resources during initialization
- #3545 Support O\_DIRECTORY open() flag
- #3546 Support O\_NOFOLLOW open() flag
- #3547 Support O\_CLOEXEC open() flag
- #3549 Obsolete powerpc/virtex BSP
- #3551 Move default configuration to separate library
- #3552 cpu usage error in SMP mode
- #3553 rtems-libbsd Missing waf in Top Directory
- #3554 rtems-libbsd README.waf Needs an Update Sweep
- #3555 IRC bots need to be registered to join #rtems
- #3557 Test ticket
- #3558 Update TracSpamFilter
- #3559 Fix NavAdd plugin.
- #3560 Fix FlexibleAssignTo
- #3561 Migrate to CommitTicketUpdater
- #3562 Use a short paths for the RSB temporary build path on Windows
- #3568 RSB: UnboundLocalError: local variable 'build\_max\_size\_human' referenced before assignment
- #3569 waf version in various rtems-repositories incompatible with python 3.7
- #3576 gdb 8.0.1 sis does not build on Cygwin
- #3577 Avoid CLoog and ISL host dependencies for target GCC
- #3579 testsuite's rtems-test-check.py python version support
- #3583 Add rtems\_malloc() and rtems\_calloc()
- #3585 Deprecate proc\_ptr
- #3587 Deprecate rtems\_context
- #3589 Deprecate rtems\_context\_fp
- #3591 Deprecate region\_information\_block
- #3593 Deprecate rtems\_thread\_cpu\_usage\_t
- #3595 Deprecate rtems\_rate\_monotonic\_period\_time\_t
- #3598 Move internal types of API objects to separate header file
- #3599 Remove m32c architecture port
- #3600 Update or1k tools to use GCC master
- #3602 Update or1k tool chain to use the upstream GCC
- #3603 Remove support for 16-bit object identifiers
- #3604 RTL Unresolved Symbols from common section on i386/pc686 (cloned)
- #3605 RTL Allows Unloading a Module other Modules Depend Upon (cloned)
- #3609 Update Spike Version in RSB (RISC-V simulator)
- #3612 RTL unresolved compaction does not update string indexes after removing a string
- #3620 CommitTicketUpdater does not process commits in order
- #3621 Statically initialize object information structures
- #3622 Remove cache routines working with a processor set
- #3623 rtems-syms invoking m68k-rtemsundefined-gcc
- #3624 MSYS2 builds appear to ignore tcfg file
- #3625 RTL Allows Unloading a Module other Modules Depend Upon (cloned)
- #3626 sigtimedwait() needed when POSIX is disabled
- #3629 Add RSB reporting section to the documentation.
- #3630 Build of rtems-tools fails with i686-w64-mingw32
- #3636 Add rtems\_scheduler\_get\_maximum\_priority()
- #3637 Fix rtems\_task\_restart() argument type
- #3649 Error with IRC announcing in examples-v2 commits.
- #3651 Sphinx 1.8 PDF (latex) on FreeBSD does not build
- #3664 RSB config parsing slow on python3
- #3665 Add low level event recording infrastructure
- #3666 Add support for C++17 std::aligned\_alloc
- #3667 Support data cache disable on ARMv7-AR
- #3669 rtems-docs.git does not build with Sphinx 1.8.2 and 1.8.3
- #3670 examples-v2 uses deprecated or obsolete RTEMS interfaces
- #3671 rtems-test needs a --version option or similar
- #3672 No i386 BSP can link all tests after cache manager changes
- #3673 xilinx\_zynq\_a9\_qemu - fails to link psxconfig01
- #3674 Raspberry Pi Fails to Build
- #3675 RSB: Change default prefix to OS prefix + "rtems" + \$rtems\_version
- #3677 ARM BSP contains ARM code in THUMB only build
- #3678 Add RISC-V BSP with support for the glib
- #3682 Add BSP for Xilinx Zynq UltraScale+ MPSoC platform
- #3683 Git clone via HTTPS does not give much interactive feedback
- #3684 rtems\_print\_buffer is broken
- #3685 Add large memory support to libdl
- #3686 Add library searching and loading to libdl
- #3687 Add architecture section support to libdl and support PowerPC's small data.
- #3688 rtems-docs fails to build with python3
- #3692 libdl does not honour write unlock/lock for sections
- #3693 libdl incorrectly handles MIPS16hi/lo relocs
- #3694 shm\_open has logically unreachable code (Coverity ID: 1399706, 1399714)
- #3699 Wrong system register specified for ARM virtual timer value retrieval
- #3720 mfill shell command uses the wrong arguments for the memset()
- #3724 bsp/lpc24xx: Convert SSP driver to Linux API
- #3725 bsp/lpc24xx: Convert I2C driver to Linux API
- #3728 Set small data section to max size for mvme5500 and motorola\_powerpc BSPs
- #3731 Add rtems\_scheduler\_get\_processor()
- #3732 Add rtems\_scheduler\_get\_processor\_maximum()
- #3733 Add general reg support to libdebugger
- #3734 Add RTEMS\_CONST attribute
- #3735 Remove CONFIGURE\_HAS\_OWN\_MULTIPROCESSING\_TABLE
- #3736 PowerPC Beatnik BSP C++ exceptions broken
- #3741 libdl loading ELF objects from libbsd NFS file system ends in a deadlock
- #3742 T\_config conflicting type qualifiers for 'config'
- #3743 RSB os and arch config logic is broken
- #3746 libdl test dl05.exe failing
- #3747 Address Cortex-M3 Errata 602117
- #3748 libdl uses a linear symbol search on object file symbols
- #3751 No documentation on Region Get Information Directives
- #3753 Rename CONFIGURE\_LIBIO\_MAXIMUM\_FILE\_DESCRIPTOR
- #3754 Users Guide Ubuntu Instructions Have Typo
- #3756 Condition codes in PSR are destroyed by lazy FP context switch
- #3760 BBB MMU update crashes
- #3762 Return the current handler from ARM cp15 set exception call



- #3763 RSB SIS build fails on FreeBSD
- #3768 Add staging support to Makefile.inc
- #3769 RSB BSP Buildsets
- #3770 RSB 3rd party packages failing to build
- #3773 RPi fails to boot
- #3774 RPi2 SMP does not build
- #3775 libdl does not handle ARM mode reloc tramp parsing
- #3776 libdl ARM does not support ARM mode trampolines.
- #3777 libdl object unload debugger delete support is broken
- #3781 RSB crashes in case the host as an unreadable directory in "/"
- #3783 MSYS2 RSB build error
- #3785 Add RISC-V BSP with support for the Freedom E310 Arty A7 FPGA
- #3789 TMS570 applciation build error
- #3792 RSB fails to build on MSYS2
- #3793 trace record tool does not build on Windows
- #3794 Initial POSIX Signals Mask Incorrect
- #3796 docs/develenv directory structure bitrot
- #3797 Add LLVM as a package
- #3798 Add socketmark to libbsd
- #3800 termios - Add Capability to Generate SIGINTR and SIGQUIT
- #3802 RSB Build of Spike Fails on Second Time (bug in upstream spike)
- #3803 RSB ssl context error fetching qemu patches
- #3804 sb-get-sources: Error repo\_mail referenced before assignment
- #3805 libdebugger build error on atsamv
- #3806 Add fatal error for heap errors
- #3808 Fix qemu-couverture-git RSB download file name
- #3809 Fix epiphany-rtems5-gdb-7.8 RSB download file name
- #3810 Use the release details in the release build docs
- #3811 Release source path on ftp.rtems.org is wrong
- #3812 Released RSB has no source set for rtems-tools
- #3813 RSB does not handle --rsb-file in releases
- #3814 Releasing creates 2 copies or the kernel and tools.
- #3815 Improve SMP EDF scheduler configuration
- #3817 RSB fails on FreeBSD 12.0 (32bit and 64bit)
- #3820 Rename psx\_example\_N to something meaningful
- #3821 Port NVMe support from FreeBSD to libbsd
- #3822 Release created VERSION file in rtems-tools-\*.tar.xz is wrong
- #3823 Untar\_ family doesn't handle nested directories
- #3826 top on SMP shows invalid priorities
- #3830 Build problems with user names which contain space characters
- #3831 Duplicate description of Tiers and Rules
- #3833 Simplify RTEMS semaphore configuration
- #3834 Simplify clock driver
- #3835 Support statically allocated threads
- #3836 Specify and test application configuration
- #3837 Rename CONFIGURE\_LIBIO\_MAXIMUM\_FILE\_DESCRIPTOR
- #3838 Rework work area initialization
- #3839 RTEMS revision does not handle `.`
- #3840 Add CONFIGURE\_IMFS\_ENABLE\_MKFIFO
- #3841 Add rtems\_object\_get\_local\_node()
- #3842 RSB RTEMS version message string is fixed to the git hash
- #3843 Add CONFIGURE\_DIRTY\_MEMORY
- #3844 Remove CONFIGURE\_HAS\_OWN\_DEVICE\_DRIVER\_TABLE
- #3845 Remove Ada-specific configuration options
- #3848 Libdebugger test in libbsd should depend on libdebugger.a
- #3849 Fix PSIM memory map
- #3856 posix\_devctl - Add support for SOCKCLOSE
- #3857 Use EAGAIN for POSIX mq wait in ISR error
- #3859 No output from joel scripts in telnet
- #3861 Add CONFIGURE\_VERBOSE\_SYSTEM\_INITIALIZATION
- #3862 Canonicalize CONFIGURE\_ZERO\_WORKSPACE\_AUTOMATICALLY
- #3863 Remove support for the BSP\_ZERO\_WORKSPACE\_AUTOMATICALLY BSP option
- #3864 rtems-tester does not work with gdb simulators
- #3865 Fix linker set item declarations for small data area targets
- #3868 newlib links breaks mingw build
- #3871 Remove rtems\_configuration\_get\_posix\_api\_configuration()
- #3873 Remove CONFIGURE\_HAS\_OWN\_INIT\_TASK\_TABLE
- #3874 Remove CONFIGURE\_POSIX\_HAS\_OWN\_INIT\_THREAD\_TABLE
- #3875 Split up confdefs.h in component based header files
- #3876 Remove CONFIGURE\_DISABLE\_SMP\_CONFIGURATION
- #3881 Add API functions to map a task priority to/from a POSIX thread priority
- #3882 Add POSIX user environment pointer to TCB
- #3885 Context switch extension is broken in SMP configurations
- #3886 Fail an RSB build with --mail option if a repo is not clean
- #3887 Do not report remotes in RSB build log if --mail is used
- #3888 Update rtems\_waf in libbsd
- #3889 Test needed for timer\_create with CLOCK\_MONOTONIC
- #3890 Test needed for clock\_nanosleep with CLOCK\_MONOTONIC
- #3893 RSB staging changes have broken building a 3rd party package
- #3894 Replace the device filesystem with a specialization of the IMFS

## Details

Ticket	Created	Resolution	Component	Reporter	Owner	Modified
#1247	13 years ago	fixed	fs	strauman	Chris Johns	2 years ago
Summary	RTEMS does not implement locks needed by multithreaded newlib					
Description	<p>multi-threaded newlib protects a number of internal data structures (as of newlib-1.15 these comprise:</p> <ul style="list-style-type: none"> <li>• global list of FILE objects</li> <li>• stdio FILE object initializer</li> <li>• individual FILEs [since FILEs with the exception of stdin/stdout/stderr are per-process entities]</li> <li>• global hash table used by telldir/seekdir</li> <li>• individual DIR structures (opendir/readdir)</li> <li>• atexit list</li> <li>• list of environment variables</li> <li>• global timezone variable</li> </ul> <p>) using mutexes. It expects the OS to implement these locks but defaults to not using locking if the OS does not provide an implementation. Currently, RTEMS does *not* provide its own implementation of 'sys/lock.h' and therefore vital data structures in newlib are currently *unprotected* (with the exception of environment variables -- 'envlock.c' had been added to RTEMS a while ago but since then, newlib has introduced more locks and a general OS interface which - once implemented - will obsolete 'envlock.c').</p>					

Note that while semantics of having no protection for individual FILE objects may be tolerable, having no protection for global newlib data structures such as lists of FILES is not acceptable.

I am currently working on an implementation which should be available shortly.

#1394	11 years ago	fixed	tool/newlib	Daniel Hellstrom	Chris Johns	2 years ago
Summary	scandir() fails due to MAXNAMELEN is incorrect					
Description	<p>I have been trying to use scandir() however the newlib one does not work due to MAXNAMLEN and NAMLEN differ. scandir in libcsupport seems to have a fix for this, however my libcsupport_a-scandir.o is empty, I'm guessing because HAVE_SCANDIR is defined.</p> <p>It is used in scandir() (newlib-1.17.0/newlib/lib/posix/scandir.c:117) by the macro DIRSIZ. Where DIRSIZ uses the MAXNAMELEN define which is set incorrectly. It does not match the sizeof(struct dirent) which makes the DIRSIZ return a negative number, then malloc(DIRSIZ(d)) will try to allocate 4GB which fail.</p> <p>My guess is that MAXNAMELEN should be defined in newlib-1.17.0/newlib/lib/sys/rtems/sys/dirent.h or newlib-1.17.0/newlib/lib/sys/rtems/include/limits.h or in a new file.</p> <p>I tried to run the code below on my FAT filesystem, taken directly from the scandir(3) man page.</p> <pre> /* print files in current directory in reverse order */ #include &lt;dirent.h&gt; main(){     struct dirent namelist; int n;     n = scandir(".", &amp;namelist, 0, NULL); if (n &lt; 0)         perror("scandir");     else {         while(n--) {             printf("%s\n", namelist[n]-&gt;d_name); free(namelist[n]);         } free(namelist);     } } </pre>					

#1662	10 years ago	fixed	fs	Bharath Suri	Chris Johns	2 years ago
Summary	termios.c: semaphore not deleted, consequently resulting in failure of rtems_termios_open					
Description	The semaphore osem is still in use in rtems_termios_close while an attempt to delete it is made and hence is not deleted. Consequently, it results in a RTEMS_TOO_MANY on rtems_semaphore_create, which further results in failure of rtems_termios_open.					

#1747	9 years ago	fixed	score	Chris Johns	Sebastian Huber	2 years ago
Summary	Heap extend allows discontinuous memory regions.					
Description	<p>The check in (cpukit/ChangeLog) states:</p> <p>2010-06-07 Sebastian Huber &lt;sebastian.huber@...&gt;</p> <ul style="list-style-type: none"> <li>score/src/heapextend.c: Implemented support for scattered heap areas.</li> </ul> <p>The heap cannot support scattered blocks because the _Heap_Is_block_in_heap assumes the region is continuous between the first and last blocks of the heap. Making the gaps in the regions passed to the heap extend call used is questionable and makes the _Heap_Is_block_in_heap test not really perform the task it's name states. This is an issue because it is this check that determines if a heap free of NULL should proceed. This issue is covered in another PR.</p> <p>I also wonder about a heap free call to an address that maps to one of the "in-use" gap regions. The previous heap code knew if an address was in the heap and therefore it was kind of safe to probe for a valid block. This assumption is now not valid.</p> <p>The former heap extend code:</p> <p><a href="http://www.rtems.org/viewvc/rtems/cpukit/score/src/heapextend.c?revision=1.7&amp;view=markup">http://www.rtems.org/viewvc/rtems/cpukit/score/src/heapextend.c?revision=1.7&amp;view=markup</a></p> <p>clearly states the type of memory that can be added to an existing heap. The current code has no restrictions. The user manual is not great in this area. It would also be useful if comments are added to the heap extend code.</p> <p>The heap extend code is used by the rtems_region_extend call and this call clearly states in the manual that the memory region must be continuous. If this has changed we should discuss the API change and make better note of it. I also suspect the testsuite will need additions to test any API changes.</p>					

#1971	8 years ago	fixed	fs	nopscomn	Chris Johns	2 years ago
Summary	Memory leak in tmpfile()					
Description	<p>Hello,</p> <p>I use tmpfile() in my RTEMS application, and found that it has memory leak. I wrote small test application (see attachment), that output memory usage:</p> <p>Memory usage before: Number of used blocks: 12 Largest used block: 1288 Total bytes used: 3628</p> <p>Memory used after: Number of used blocks: 1013 Largest used block: 1288 Total bytes used: 112064</p> <p>By 1000 iteration, each call tmpfile() cause memory leak about 108 bytes.</p>					

#2132	7 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	<rtems/score/basedefs.h> superfluously includes <limits.h>					
Description	In older RTEMS versions <rtems.h> provided <limits.h> indirectly. The include of <limits.h> was added to not break application source files that relied on this accidentally. We may remove this include in the future.					

#2133	7 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	<rtems/score/basedefs.h> superfluously includes <string.h>					
Description	In older RTEMS versions <rtems.h> provided <string.h> indirectly. The include of <string.h> was added to not break application source files that relied on this accidentally. We may remove this include in the future.					

#2135	7 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	times() and _times() are subject to integer overflows					
Description	The clock_t type is defined as unsigned long for RTEMS in Newlib. With a 1ms clock tick an overflow happens after 7 days on 32-bit long targets.					

#2173	6 years ago	fixed	score	Sebastian Huber	Joel Sherrill	2 years ago
Summary	Potential integer overflow problem in EDF scheduler					

On 2014-03-21 14:46, Gedare Bloom wrote:> On Fri, Mar 21, 2014 at 9:43 AM, Sebastian Huber

<sebastian.huber@...> wrote:

[...]

I have another question regarding the EDF scheduler. Does this work in case \_Watchdog\_Ticks since boot overflows?

No. For this, I think we need to use "deadline folding" which is just modulo arithmetic.

```

void _Scheduler_EDF_Release_job(
    Thread_Control *the_thread, uint32_t deadline
) {

```





To get rid of this bottleneck we should move the watchdog context into the scheduler context to use one watchdog context per scheduler instance. Take care that active watchdogs move in case of a scheduler change of a thread.

#2354	5 years ago	fixed	unspecified	Sebastian Huber		2 years ago
Summary	Replace red-black tree implementation, change API					
Description	<p>The RTEMS red-black tree implementation is not as good as the BSD implementation which performs quite well in a benchmark:</p> <p><a href="https://github.com/sebhub/rb-bench">https://github.com/sebhub/rb-bench</a></p> <p>Proposal:</p> <p><a href="https://github.com/sebhub/rb-bench/blob/master/test-rtree-bsd-for-rtems.c">https://github.com/sebhub/rb-bench/blob/master/test-rtree-bsd-for-rtems.c</a></p> <p>One benefit is that the search/insert is done inline and the red-black tree fixup is done in a general purpose <code>_BSD_RBTtree_Insert_color()</code> function (similar to the Linux red-black tree API).</p> <p>This makes it possible to get rid of the red-black tree implementation used by the JFFS2 support.</p>					
#2355	5 years ago	fixed	arch/sparc	Sebastian Huber	Daniel Hellstrom	2 years ago
Summary	SPARC: Several shared drivers are not SMP ready					
Description	Several drivers in <code>c/src/lib/libbsp/sparc/shared/</code> use <code>interrupt disable/enable</code> for low-level mutual exclusion. This is not enough on SMP configurations.					
#2363	5 years ago	duplicate	arch/sparc	Sebastian Huber		2 years ago
Summary	SPARC: Silent FP context corruption possible					
Description	<p>On uni-processor configurations the post-switch actions (e.g. signal handlers) and context switch extensions may silently corrupt the floating point context. Set test <code>sptest/scontext01</code>.</p> <p>This problem exists for many years and might be working as intended. It is possible to fix this issue using the <code>SPARC_USE_SAFE_FP_SUPPORT</code> option. This is already used for the SMP configurations. The disadvantage is that this disables the deferred floating point support.</p>					
#2366	5 years ago	wontfix	score	Joel Sherrill		2 years ago
Summary	Create a Public API for the Atomic Operations					
Description	<p>Ticket #2364 regarded use of a pthread mutex in three graphics driver as basically an atomic flag to ensure only one <code>open()</code> was active at a time. This created an unnecessary dependency on the POSIX API being enabled. I changed the code to use score Atomic flags.</p> <p>This highlighted the need for a public Atomic API.</p> <p>The existing tests could be converted to the public API, a macro wrapper written for Classic API Atomics, and documentation added. This may be enough to be a small GSOC project.</p>					
#2367	5 years ago	fixed	doc	mw	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	Documentation of User Extensions needs more information					
Description	The documentation for User Extension sets in the C User's Guide could use some clarification. It discusses the multiple sets of extensions, but it is unclear as to whether or not the extensions are added or replaced when <code>rtems_extension_create()</code> is called. There is a section - 22.2.4 (Order of Invocation) that does discuss the operation of the sets, but it only makes sense once the reader understands that the sets are, in fact, additive.					
#2377	5 years ago	wontfix	tool	Sebastian Huber		2 years ago
Summary	rtems_waf: Tools without a version are not supported					
Description	waf configure --prefix=/opt/rtems --rtems=/opt/rtems --rtems-tools=/opt/rtems --rtems-bsps=i386/pc686 Setting top to : /scratch/git-rtems-libbsd Setting out to : /scratch/git-rtems-libbsd/build Could not find any architectures (complete log in /scratch/git-rtems-libbsd-upstream/build/config.log)					
#2385	5 years ago	fixed	arch/arm	Chris Johns	Sebastian Huber	2 years ago
Summary	Warning from commit "bsps/arm: Do not use <code>ARM_ARCH_7A</code> "					
Description	<p>This change <a href="https://git.rtems.org/rtems/commit/?h=4.11&amp;id=d0733bb8">https://git.rtems.org/rtems/commit/?h=4.11&amp;id=d0733bb8</a> generate a warning in user code. The warning is:</p> <pre> .../arm-errata.h:45:1: warning: 'in line' is not at beginning of declaration [-Wold-style-declaration] static bool inline arm_errata_is_applicable_processor_errata_764369(void) ^ </pre>					
#2407	5 years ago	fixed	build	Sebastian Huber	Joel Sherrill	2 years ago
Summary	Enable function and data sections					
Description	<p>In order to reduce the size of executables it is beneficial to put all global functions and data into separate sections. This enables the linker to perform a garbage collection which removes all items not directly referenced. The following steps are necessary:</p> <ol style="list-style-type: none"> <li>1. Modify the build system to use the following compiler and linker flags:  <code>CFLAGS += -function-sections -fdata-sections LDFLAGS += -WI,--gc-sections</code></li> <li>2. Review all linker command files and ensure that linker sets and global constructor sections are not affected by the garbage collection (e.g. use the <code>KEEP()</code> directive of GNU ld).</li> </ol>					
#2408	5 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	4 weeks ago
Summary	Linker set based initialization					
Description	<p>Linker sets are used for example in Linux, FreeBSD (they are used in the RTEMS port of the FreeBSD network stack, e.g. libbsd), eCos and for global C++ constructors. They provide a space efficient and flexible means to initialize modules. A linker set consists of</p> <ul style="list-style-type: none"> <li>• dedicated input sections for the linker (e.g. <code>.ctors</code> and <code>.ctors.*</code> in the case of global constructors),</li> <li>• a begin marker (e.g. provided by <code>__rtbegin.o</code>), and</li> <li>• an end marker (e.g. provided by <code>__ctrend.o</code>).</li> </ul> <p>A module may place a certain data item into the dedicated input section. The linker will collect all such data items in this section and creates a begin and end marker. The initialization code can then use the begin and end markers to find all the collected data items (e.g. function pointers).</p> <p>Lets look how this works using a simple example. For this we need three files <code>myset.h</code>,</p> <pre> #ifndef MYSET_H #define MYSET_H  /* The linker set items */ typedef struct {     void (*func)(void); } item;  /*  * Macro to create a linker set item. The first parameter is  * the designator of the item. It must be unique within the  * module scope. The second parameter is the desired function.  */ #define MYSET_ITEM(i, f) \     __attribute__((used)) \     __attribute__((section(".rtemsroset.myset.content"))) \     static item i = { f }  #endif /* MYSET_H */ </pre>					

module.c

```
#include "myset.h"
#include <stdio.h>

/*
 * Some global function that needs a module specific
 * initialization done by f().
 */
void
g(void)
{
    printf("g()\n");
}

/* The module constructor */
static void
f(void)
{
    printf("f()\n");
}

/*
 * This registers the module constructor f()
 * in the linker set "myset".
 */
MYSET_ITEM(i, &f);
```

Description

and init.c.

```
#include "myset.h"
#include <stddef.h>

/* Should be in a proper header file */
void g(void);

/* Define the start marker */
__attribute__((used))
__attribute__((section(".rtemsroset.myset.begin")))
static volatile const item begin[0];

/* Define the end marker */
__attribute__((used))
__attribute__((section(".rtemsroset.myset.end")))
static volatile const item end[0];

int main(void)
{
    size_t n = &end[0] - &begin[0];
    size_t i;

    /* Call all functions of the linker set */
    for (i = 0; i < n; ++i) {
        (*begin[i].func)();
    }

    /*
     * This will pull in the module.c and register its item in the
     * linker set "myset". So g() can rely on f() being called first.
     */
    g();

    return (0);
}
```

In the linker command file of the GNU linker we need the following statement.

```
.rtemsroset : {
KEEP (*(SORT(.rtemsroset.*)))
```

The `KEEP()` ensures that a garbage collection by the linker will not discard the content of this section. This would be normally the case since the linker set items are not referenced directly. The `SORT()` directive sorts the input sections lexicographically. Please note the lexicographical order of the `.begin`, `.content` and `.end` section name parts in the previous example which ensures that the position of the begin and end markers are right. The interesting part of linker map file of the previous example may look like this.

```
.rtemsroset 0x000000001001990 0x4 load address 0x00000000002268c
*(SORT(.rtemsroset.*))
.rtemsroset.myset.begin
0x000000001001990 0x0 init.o
.rtemsroset.myset.content
0x000000001001990 0x4 module.o
.rtemsroset.myset.end
0x000000001001994 0x0 init.o
```

So what is the benefit of using linker sets to initialize modules? Currently in RTEMS all available managers (semaphore, message queue, barrier, etc.) are initialized since the initialization code doesn't know what is actually used by the application. With the linker set approach we need to initialize only those managers that are used by the application. In case an application uses message queues, then it must call `rtems_message_queue_create()`. In the module implementing this function we can place a linker set item and register the message queue handler constructor. Otherwise, in case the application doesn't use message queues, then there will be no reference to the `rtems_message_queue_create()` function and the constructor is not registered, thus nothing of the message queue handler will be in the final executable.

#2412	5 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Improved priority inheritance implementation					

## Problem

The RTEMS mutexes implement only a very simple approximation of the priority inheritance protocol. The real priority of a thread is only restored once it releases its last mutex. Lets consider this scenario. We have a file system instance protected by one mutex (e.g. JFFS2) and a dynamic memory allocator protected by another mutex. A low priority thread performs writes some log data into a file, thus it acquires the file system instance mutex. The file system allocates dynamic memory. Now a high priority thread interrupts and tries to allocate dynamic memory. The allocator mutex is already owned, so the priority of the low priority thread is raised to the priority of the high priority thread. The memory allocation completes and the allocator mutex is released, since the low priority thread still owns the file system instance mutex it continues to execute with the high priority (the high priority thread is not scheduled). It may now perform complex and long file system operations (e.g. garbage collection, polled flash erase and write functions) with a high priority.

## Functional requirements

- The mutex shall use the priority inheritance protocol to prevent priority inversion. On SMP configurations OMIP shall be used.
- The mutex shall allow vertical nesting (a thread owns multiple mutexes).
- The mutex shall allow horizontal nesting (a thread waits for ownership of a mutex those owner waits for ownership of a mutex, and so on).

- Threads from one scheduler instance shall wait in priority order. The highest priority thread shall be dequeued first.
- The highest priority waiting thread of each scheduler instance shall wait in FIFO order.
- The mutex shall provide an acquire operation with timeout.
- In case a mutex is released, then the previous owner shall no longer use the priorities inherited by this mutex.
- In case a mutex acquire operation timeout occurs, then the current owner of the mutex shall no longer use the priorities inherited by the acquiring thread.
- The order of the mutex release operations may differ from the order of the mutex acquire operations.
- Priority changes not originating due to the priority inheritance protocol shall take place immediately.
- Deadlock shall be detected. In case a deadlock would occur an error status shall be returned or a fatal error shall be generated.
- Deadlocks at application level shall not lead to a deadlock at operating system level.

## Performance requirements

- The mutex acquire operation shall use only object-specific locks in case the mutex is not owned currently.
- The mutex release operation shall use only object-specific locks in case no threads wait for ownership of this mutex.

## Invariants

- A mutex shall be owned by at most one thread.
- A thread shall wait for ownership of at most one mutex.

## Possible implementation

Use a recursive data structure to determine the highest priority available to a thread for each scheduler instance, e.g.

```
typedef struct Thread_Priority_node {
    Priority_Control current_priority;
    Priority_Control real_priority;
    struct Thread_Priority_node *owner;
    RBTREE_Node Node;
    RBTREE_Control Inherited_priorities;
} Thread_Priority_node;

typedef struct {
    ...
    Thread_Priority_node *priority_nodes; /* One per scheduler instances */
    ...
} Thread_Control;
```

Initially a thread has a priority node reflecting its real priority. The Thread\_Priority\_node::owner is NULL. The Thread\_Priority\_node::current\_priority is set to the real priority. The Thread\_Priority\_node::Inherited\_priorities is empty.

In case the thread must wait for ownership of a mutex, then it enqueues its priority node in Thread\_Priority\_node::Inherited\_priorities of the mutex owner.

In case the thread is dequeued from the wait queue of a mutex, then it dequeues its priority node in Thread\_Priority\_node::Inherited\_priorities of the previous mutex owner (ownership transfer) or the current mutex owner (acquire timeout).

In case the minimum of Thread\_Priority\_node::real\_priority and Thread\_Priority\_node::Inherited\_priorities changes, then Thread\_Priority\_node::current\_priority is updated. In case the Thread\_Priority\_node::owner is not NULL, the priority change propagates to the owner, and so on. In case Thread\_Priority\_node::current\_priority changes, the corresponding scheduler is notified.

The biggest issue is the locking on SMP configurations in case of recursive minimum updates.

Somehow we must connect this to the scheduler helping protocol for OMIP. We may have to replace the return value based scheduler operations with a pre-context-switch action. Due to some recent implementation changes the run-time of the \_Thread\_Dispatch() function is no longer average-case performance critical.

<b>#2420</b>	4 years ago	wontfix	tool/rsb	Jakob Viketoft	Chris Johns	3 months ago
Summary	RSB %source file fails					
Description	It seems that the method for accessing an existing file repository both isn't covered much in the "manual", but it also fails to find it. Looking at the python code in download.py, it requires the format <code>file://</code> to identify the local file protocol, but then tries to access the actual file/directory using that the entire url (including <code>file://</code> ).					
	This unfortunately fails and I'm not familiar enough with Python to correct this, although it appears that the <code>file://</code> part should be cut from the URL before calling the "return path.isdir(url)" in the <code>_file_downloader</code> function.					
<b>#2423</b>	4 years ago	fixed	unspecified	Jeffrey Hill		2 years ago
Summary	rtems_iterate_over_all_threads lacks user callback private pointer pass through					
Description	Typically when designing an API that calls a user callback there is a user private "void *" pointer transparently passed through to the user callback so that the user can access his private state inside of his callback without being forced to employ a global variable. A global variable doesn't work very well if there are multiple objects instances created each of them using the same method with <code>rtems_iterate_over_all_threads</code> . This type of "void *" private pointer is of course a standard approach allowing the users callback to behave much the same way as a virtual method in C++, but nevertheless retaining a compatible C based API.					
	An enhanced version of the API might look like this.					
	void rtems_iterate_over_all_threads_xxx( rtems_per_thread_routine routine, void * const pUserPrivatePassThrough );					
	typedef void (*rtems_per_thread_routine_xxx)( Thread_Control *the_thread, void * const pUserPrivatePassThrough );					
	The pUserPrivatePassThrough is not used by the library; it is retained for the duration of the <code>rtems_iterate_over_all_threads_xxx</code> function only so that it can be passed through to the user's callback.					
	thanks for your consideration of this matter					
<b>#2428</b>	4 years ago	fixed	tool/rsb	Joel Sherrill	Chris Johns	2 years ago
Summary	Add 4.12 Tool Target Configurations to RSB					
Description	Even though so far the 4.11 and master tools don't need to be different, 4.12 configurations need to be added. This gives us space to:					
	+ (DONE) remove obsolete targets (avr, h8300, m32r) + (DONE) update versions + complete submission of patches and bump gdb + ...					
<b>#2441</b>	4 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	lpc1768 variants fail to build with error in gpio.c					
Description	arm-lpc1768_mbed_ahb_ram_eth arm-lpc1768_mbed_ahb_ram arm-lpc1768_mbed					
	In file included from <code>../..../rtems/c/src/lib/libbsp/arm/lpc176x/gpio/gpio.c:25:0: ../..../lpc1768_mbed_ahb_ram_eth/lib/include/bsp/gpio.h:28:4: error: #error "BSP_GPIO_PIN_COUNT or BSP_GPIO_PINS_PER_BANK is not defined."</code>					
	<code>#error "BSP_GPIO_PIN_COUNT or BSP_GPIO_PINS_PER_BANK is not defined."</code>					
	<code>../..../lpc1768_mbed_ahb_ram_eth/lib/include/bsp/gpio.h:32:4: error: #error "Invalid BSP_GPIO_PIN_COUNT or BSP_GPIO_PINS_PER_BANK."</code>					
	<code>#error "Invalid BSP_GPIO_PIN_COUNT or BSP_GPIO_PINS_PER_BANK."</code>					
	<code>../..../lpc1768_mbed_ahb_ram_eth/lib/include/bsp/gpio.h:41:5: error: division by zero in #if</code>					
	<code>#if GPIO_LAST_BANK_PINS &gt; 0</code>					
	<code>../..../rtems/c/src/lib/libbsp/arm/lpc176x/gpio/gpio.c:29:8: error: unknown type name 'lpc176x_registered_interrupt_function'</code>					





on						
#2454	4 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	Warning in threadqops.c					
Description	This may apply to the 4.11 branch as well. I am not sure. ../../../../rtems/c/src/././cpukit/score/src/threadqops.c:202:29: warning: passing argument 1 of '_RBTREE_initialize_empty' from incompatible pointer type This happens building many/all BSPs.					
#2455	4 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	Warning in spsimplsched02					
Description	This may apply to the 4.11 branch as well. I am not sure. ../../../../rtems/c/src/././testsuites/sptests/spsimplsched02/init.c:84:5: warning: passing argument 1 of '_Objects_Name_to_id_u32' from incompatible pointer type This happens building many/all BSPs.					
#2457	4 years ago	fixed	arch/powerpc	Joel Sherrill	Aun-Ali Zaidi <admin@...>	2 years ago
Summary	Remove powerpc/ep1a BSP					
Description	Remove the powerpc/ep1a BSP per the instructions at <a href="https://devel.rtems.org/wiki/Developer/Removing_a_BSP">https://devel.rtems.org/wiki/Developer/Removing_a_BSP</a> Rationale: AFAIK this BSP was only used on a program supported by OAR. That program is no longer in active development and is completely frozen. If that situation changes, the BSP can be resurrected. It was introduced 10 years ago and has not has a modification other than general maintenance in the last four years.					
#2458	4 years ago	fixed	arch/powerpc	Joel Sherrill	Ralph Holmes <ralph@...>	2 years ago
Summary	Remove powerpc/score603e BSP					
Description	Remove the powerpc/score603e BSP per the instructions at <a href="https://devel.rtems.org/wiki/Developer/Removing_a_BSP">https://devel.rtems.org/wiki/Developer/Removing_a_BSP</a> Rationale: AFAIK this BSP was only used on a program supported by OAR. That program is no longer in active development and is completely frozen. If that situation changes, the BSP can be resurrected. It was introduced in 1999 and has not has a modification other than general maintenance in the last six years.					
#2459	4 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add rtems_chain_get_first_unprotected() to chain API					
#2464	4 years ago	wontfix	tool	Sebastian Huber		2 years ago
Summary	RSB: Tool patches use the RTEMS version					
Description	In rtems/config/rtems-urls.bset the tool patches are set to an RTEMS version dependent directory. This makes re-use of the general purpose files quite difficult.					
#2468	4 years ago	fixed	arch/i386	Joel Sherrill	Sebastian Huber	2 years ago
Summary	Add Thread Local Storage (TLS) support on x86					
Description	The x86 is one of the architectures which does not support Thread Local Storage. Each architecture requires target architecture specific support to provide this standard language feature. Details on the implementation by the compiler may be found at <a href="http://wiki.osdev.org/Thread_Local_Storage">http://wiki.osdev.org/Thread_Local_Storage</a> . Based on this information, I think a segment register needs to be added to the thread context and some hooks to the TLS implemented. Architecture information on TLS implementation should be added to the CPU Supplement document as this is part of the ABI and context switch. As part of effort, the documentation for the general procedure of adding target specific TLS support should be added to the porting guide or reviewed.					
#2477	4 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	Remove <rtems/debug.h>					
Description	RTEMS has an API for dynamic debug support in <rtems/debug.h>. This feature is sparely used: <pre>cpukit/sapi/src/debug.c: rtems_debug_disable( RTEMS_DEBUG_ALL_MASK ); cpukit/sapi/src/debug.c: void rtems_debug_enable ( cpukit/sapi/src/debug.c: rtems_debug_control to_be_enabled cpukit/sapi/src/debug.c: void rtems_debug_disable ( cpukit/sapi/src/debug.c: rtems_debug_control to_be_disabled cpukit/sapi/src/debug.c: bool rtems_debug_is_enabled( cpukit/sapi/src/debug.c: rtems_debug_control level cpukit/rtems/include/rtems/rtems/regionimpl.h: if ( rtems_debug_is_enabled( RTEMS_DEBUG_REGION ) ) \ cpukit/score/include/rtems/debug.h: typedef uint32_t rtems_debug_control; cpukit/score/include/rtems/debug.h: SCORE_EXTERN rtems_debug_control _Debug_Level; cpukit/score/include/rtems/debug.h: void rtems_debug_enable( cpukit/score/include/rtems/debug.h: rtems_debug_control to_be_enabled cpukit/score/include/rtems/debug.h: void rtems_debug_disable( cpukit/score/include/rtems/debug.h: rtems_debug_control to_be_disabled cpukit/score/include/rtems/debug.h: bool rtems_debug_is_enabled( cpukit/score/include/rtems/debug.h: rtems_debug_control level c/src/lib/libbsp/shared/bootcard.c: * - rtems_debug_enable( RTEMS_DEBUG_ALL_MASK ); c/src/lib/libbsp/shared/bootcard.c: rtems_debug_enable( RTEMS_DEBUG_ALL_MASK ); c/src/lib/libbsp/shared/include/bootcard.h: * - rtems_debug_enable( RTEMS_DEBUG_ALL_MASK ) testsuites/sptests/spregion_err01/init.c: puts( "TA1 - rtems_debug_disable - RTEMS_DEBUG_REGION" ); testsuites/sptests/spregion_err01/init.c: rtems_debug_disable( RTEMS_DEBUG_REGION ); testsuites/sptests/spregion_err01/init.c: puts( "TA1 - rtems_debug_enable - RTEMS_DEBUG_REGION" ); testsuites/sptests/spregion_err01/init.c: rtems_debug_enable( RTEMS_DEBUG_REGION ); testsuites/sptests/sp10/init.c: puts( "Init - rtems_debug_is_enabled - is 0x1 set? No" ); testsuites/sptests/sp10/init.c: is_set = rtems_debug_is_enabled( 0x1 ); testsuites/sptests/sp10/init.c: puts( "Init - rtems_debug_enable - set 0x1" ); testsuites/sptests/sp10/init.c: rtems_debug_enable(0x1); testsuites/sptests/sp10/init.c: puts( "Init - rtems_debug_is_enabled - is 0x1 set? Yes" ); testsuites/sptests/sp10/init.c: is_set = rtems_debug_is_enabled( 0x1 ); testsuites/sptests/sp10/init.c: puts( "Init - rtems_debug_disable - clear 0x1" ); testsuites/sptests/sp10/init.c: rtems_debug_disable(0x1); testsuites/sptests/sp10/init.c: puts( "Init - rtems_debug_is_enabled - is 0x1 set? No" ); testsuites/sptests/sp10/init.c: is_set = rtems_debug_is_enabled( 0x1 );</pre>					
	The only user is the Classic Region and it is only active in case RTEMS_DEBUG is defined. Due to the heap protection support which is also available in case RTEMS_DEBUG is defined, the expensive heap walks are superfluous. We should remove this API entirely to simplify the code base.					
#2487	4 years ago	fixed	tool/website	Joel Sherrill	Chris Johns	2 years ago
Summary	Should <a href="https://devel.rtems.org/wiki/TBR/Delete/SpecBuilder">https://devel.rtems.org/wiki/TBR/Delete/SpecBuilder</a> be Deleted?					
Description	Chris.. you are the only one who knows if this tool is obsolete or not. Please do what you think is right with this page.					
#2488	4 years ago	fixed	unspecified	Joel Sherrill	Ben Gras	2 years ago
Summary	Vagrant Scripts					

Description	Ben.. someone posted on IRC that they used your scripts but the clones point to your personal repos which are out of date I am guessing.					
#2490	4 years ago	wontfix	tool/rsb	Sebastian Huber	Chris Johns	2 years ago
Summary	RSB: Use SHA512 instead of MD5					
Description	Since MD5 is not a secure hash algorithm, we should change all hashes used by the RSB configuration files to use SHA512.					
#2493	4 years ago	fixed	unspecified	Sebastian Huber	Joel Sherrill <joel.sherrill@...>	2 years ago
Summary	Remove notepads					
Description	Notepads were marked as obsolete in <a href="#">#2265</a> . Next step is to remove them. Documentation should mention that notepads are removed and list the alternatives, e.g. POSIX keys or thread local storage.					
#2494	4 years ago	fixed	unspecified	Sebastian Huber		2 years ago
Summary	Remove task variables					
Description	Notepads were marked as obsolete in 4.11. Next step is to remove them. Documentation should mention that notepads are removed and list the alternatives, e.g. POSIX keys or thread local storage.					
#2503	4 years ago	fixed	arch/powerpc	Aun-Ali Zaidi	joel.sherrill@...	2 years ago
Summary	mvme5500 BSP: Exception Handler uses deprecated Notepads.					
Description	The MVME5500 BSP uses Notepads in its exception handler and <a href="#">#2493</a> removes them. This is obviously not portable and requires a rewrite.					
#2509	4 years ago	fixed	tool/website	Santosh Vattam	Joel Sherrill	2 years ago
Summary	Should " <a href="https://devel.rtems.org/wiki/TBR/Delete/BSP_Template">https://devel.rtems.org/wiki/TBR/Delete/BSP_Template</a> " be replaced?					
Description	As part of the GCI Task <a href="https://codein.withgoogle.com/dashboard/task-instances/5106463810781184/?sp-page=1">https://codein.withgoogle.com/dashboard/task-instances/5106463810781184/?sp-page=1</a> , the student has created a new page with a corrected template and placed it under "UserManual?" at: <a href="https://devel.rtems.org/wiki/TBR/UserManual/Submitting_a_BSP/BSP_Template">https://devel.rtems.org/wiki/TBR/UserManual/Submitting_a_BSP/BSP_Template</a> Is it a good idea to replace the older page with the newly created page?					
#2513	4 years ago	fixed	arch/m68k	Joel Sherrill		2 years ago
Summary	Remove m68k/idp BSP					
Description	Remove the m68k/idp BSP per the instructions at <a href="https://devel.rtems.org/wiki/Developer/Removing_a_BSP">https://devel.rtems.org/wiki/Developer/Removing_a_BSP</a>					
#2514	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Make POSIX API mandatory (except signals and the sporadic server)					
Description	The POSIX API is currently a build-time configuration option. In general it is beneficial to avoid build-time configuration options since this reduces the testing scope. Applications not using the POSIX API should observe only a minimal overhead due to this change. This enhancement depends on <a href="#">#2408</a> .					
#2515	4 years ago	fixed	unspecified	Gedare Bloom	Gedare Bloom	2 years ago
Summary	i386 score/libcpu API Layering Violation					
Description	The file libcpu/i386/cpu.h provides functions referenced in rtems/score/i386.h Relatedly, libcpu/i386/cpu.h is the only other consumer than score/cpu.h of the score/interrupts.h. The libcpu/i386/cpu.h should be refactored into rtems/score/i386.h, which could also then subsume rtems/score/interrupts.h.					
#2527	4 years ago	wontfix	tool	Joel Sherrill	Chris Johns	2 years ago
Summary	Move pc386/tools/bin2boot to rtems-tools					
Description	Per discussion with Chris. Begin to eliminate BSP specific tools.					
#2529	4 years ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	2 years ago
Summary	BSP for the Atmel SAM V71/V70/E70/S70 chip platform					
Description	<a href="http://www.atmel.com/products/microcontrollers/arm/sam-v-mcus.aspx">http://www.atmel.com/products/microcontrollers/arm/sam-v-mcus.aspx</a>					
#2536	4 years ago	fixed	tool/rsb	Sebastian Huber	Chris Johns <chrisj@...>	2 years ago
Summary	RSB allows use of insecure hash algorithms like MD5 and SHA1					
Description	Support for these hashes should be removed. Hashes should be mandatory.					
#2537	4 years ago	fixed	unspecified	Joel Sherrill	Joel Sherrill	2 years ago
Summary	Use Newlib exec*() variants and remove RTEMS versions					
Description	In reviewing RTEMS+newlib POSIX conformance, I noticed that our newlib configuration does include the exec*() variants. All of these call _execve() which we already provided. This ticket is just to explain the removal of the RTEMS copies. The functional behavior to the user is still to return ENOSYS.					
#2542	4 years ago	fixed	bsps	Joel Sherrill	joel.sherrill@...	2 years ago
Summary	Review cxx_iostream size change per function-section changes					
Description	It looks like some BSPs with their own linkcmds may have shrunk too much. Norm appears to be 50% while some went to 75-80%. A second look after catching the pattern indicates that the KEEP() section requirements in the linker scripts were not correct and it was missed. Rather than reverting a bunch of patches, this ticket is to review all function-section patches from this one back in time for cxx_iostream shrinking too much. commit <a href="https://github.com/rtems/rtems/commit/6d21c13e5094d490280a941cf0e8333f91f85715">6d21c13e5094d490280a941cf0e8333f91f85715</a> Author: Ralph Holmes <ralph@...> Date: Sat Jan 23 21:15:40 2016 +0000 powerpc/gen5200: Add per-section compilation and linking support. For the brs5l BSP variant:					
#2543	4 years ago	fixed	unspecified	Joel Sherrill	Joel Sherrill	2 years ago
Summary	Obsolete gen68302 BSP					
Description	Delete the gen68302 BSP after 4.11 and before 4.12.					
#2544	4 years ago	duplicate	unspecified	Joel Sherrill	Joel Sherrill	2 years ago
Summary	Osolete m68k/ods68302					
Description	Obsolete and remove the ods68302 BSP before 4.12.					
#2545	4 years ago	fixed	unspecified	Joel Sherrill	Joel Sherrill	2 years ago
Summary	Obsolete mbx8xx BSP					



- Classic partition handler,
- Classic rate-monotonic handler,
- Classic region handler,
- Classic semaphore handler,
- Classic timer handler,
- extension handler,
- IO manager,
- multi-processing management,
- objects management,
- POSIX barrier handler,
- POSIX condition handler,
- POSIX key handler,
- POSIX message queue handler,
- POSIX mutex handler,
- POSIX rwlock handler,
- POSIX semaphore handler,
- POSIX spinlock handler,
- POSIX timer handler,
- signals,
- thread cancellation,
- thread life-cycle changes, and
- thread scheduler changes.

Once this is done, delete `_Thread_Disable_dispatch()` and `_Thread_Enable_dispatch()`. As a side-effect the Giant lock will be removed.

#2556	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary Implement the O(m) Independence-Preserving Protocol (OMIP)

## Background

The O(m) Independence-Preserving Protocol (OMIP) is a generalization of the priority inheritance protocol to clustered scheduling which avoids the non-preemptive sections present with priority boosting. The  $m$  denotes the number of processors in the system. Its implementation requires an extension of the scheduler helping protocol already used for the MrsP semaphores. However, the current implementation of the scheduler helping protocol has two major issues, see Catellani, Sebastiano, Luca Bonato, Sebastian Huber, and Enrico Mezzetti: Challenges in the implementation of MrsP. In Reliable Software Technologies - Ada-Europe 2015, pages 179-195, 2015. Firstly, the run-time of some scheduler operations depend on the size of the resource dependency tree. Secondly, the scheduler operations of threads which don't use shared resources must deal with the scheduler helping protocol in case an owner of a shared resource is somehow involved.

To illustrate the second issue, let us look at the following example. We have a system with eight processors and two L2 caches. We assign processor 0 to a partition P for latency sensitive real-time tasks (e.g. sensor and actuator handling), processors 1, 2 and 3 are assigned to a cluster  $C_A$  and the remaining processors are assigned to a cluster  $C_B$  for soft real-time worker tasks. The worker tasks use a shared resource, e.g. a file system for data storage. Let us suppose a task R of partition P sends a message to the workers. This may make a waiting worker ready, which in turn pre-empts the owner of a shared resource. In this case the scheduler helping protocol takes action and is carried out by the task R. This contradicts the intended isolation of scheduler instances.

The reason for this unfortunate coupling is a design issue of the scheduler helping protocol implementation. Some scheduler operations may return a thread in need of help. For example, if a thread is unblocked which pre-empts an owner of a shared resource, then the pre-empted thread is returned. Once a thread in need of help is returned, the ask for help operation of the scheduler is executed. An alternative to this return value based approach is the introduction of a pre-emption intervention during thread dispatching. Threads taking part in the scheduler helping protocol indicate this with a positive resource count value. In case a thread dispatch occurs and pre-empts an owner of a shared resource, the scheduler ask for help operation is invoked. So, the work is carried out on behalf of the thread which takes part in the scheduler helping protocol.

To overcome the first issue, an improved resource dependency tracking is required. One approach is to use a recursive red-black tree based data structure, see [#2412](#).

## Implementation

There are several steps necessary to implement OMIP.

- Introduce per-scheduler locks.
- Enable context switches with interrupts enabled.
- Add a pre-emption intervention to the thread dispatch.
- Add a table for priority nodes to the thread control block. For each scheduler instance there is one priority node.
- Update the table in case the thread blocks on a resource, a timeout while waiting for a resource occurs, or ownership of a resource is transferred to the thread.
- Use this table in the pre-emption intervention.
- Update the MrsP implementation to the new infrastructure.

Currently, only one scheduler lock for all scheduler instances is used. This simplified the MrsP implementation and due to the presence of a Giant lock, this was not an issue. With the elimination of the Giant lock, however, we need one scheduler lock per scheduler instance to really profit from a decoupled system due to clustered scheduling.

The current implementation of thread dispatching has some implications with respect to the interrupt latency. It is crucial to preserve the system invariant that a thread can execute on at most one processor in the system at a time. This is accomplished with a boolean indicator in the thread context. The processor architecture specific context switch code will mark that a thread context is no longer executing and waits that the heir context stopped execution before it restores the heir context and resumes execution of the heir thread (the boolean indicator is basically a TTAS lock). So, there is one point in time in which a processor is without a thread. This is essential to avoid cyclic dependencies in case multiple threads migrate at once. Otherwise some supervising entity is necessary to prevent deadlocks. Such a global supervisor would lead to scalability problems so this approach is not used. Currently the context switch is performed with interrupts disabled. Thus in case the heir thread is currently executing on another processor, the time of disabled interrupts is prolonged since one processor has to wait for another processor to make progress.

If we add pre-emption intervention to the thread dispatch sequence, then there is an even greater need to avoid this issue with the interrupt latency. Interrupts normally store the context of the interrupted thread on its stack. In case a thread is marked as not executing, we must not use its thread stack to store such an interrupt context. We cannot use the heir stack before it stopped execution on another processor. If we enable interrupts during this transition, then we have to provide an alternative thread independent stack for interrupts in this time frame.

The pre-emption intervention should be added to `_Thread_Do_dispatch()` before the heir is read and perform the following pseudo-code actions.

```
pre_emption_intervention(executing):
if executing.resource_count > 0:
  executing.lock()
if executing.is_ready():
  for scheduler in executing.schedulers:
    scheduler.lock()
if !executing.is_scheduled():
  for scheduler in executing.schedulers:
    scheduler.ask_for_help(executing)
for scheduler in executing.schedulers:
  scheduler.unlock()
else if executing.active_help_level > 0:
  idle.use(executing.scheduler_node)
executing.unlock()
```

Description

The scheduler help operation affects multiple scheduler instances. In terms of locking we have only two options,

- use a global scheduler lock, or
- obtain multiple per-scheduler locks at once.

A global scheduler lock is not an option. To avoid deadlocks obtain the per-scheduler locks in a fixed order. However, in this case the per-scheduler locks will observe different worst-case and average-case acquire times (depending on the order).

Use a recursive data structure to determine the highest priority available to a thread for each scheduler instance, e.g.

```

typedef struct Thread_Priority_node {
    Priority_Control current_priority;
    Priority_Control real_priority;
    struct Thread_Priority_node *owner;
    RBTNode Node;
    RBTNode_Control Inherited_priorities;
} Thread_Priority_node;

typedef struct {
    ...
    Thread_Priority_node *priority_nodes; /* One per scheduler instances */
    ...
} Thread_Control;

```

Initially a thread has a priority node reflecting its real priority. The `Thread_Priority_node::owner` is `NULL`. The `Thread_Priority_node::current_priority` is set to the real priority. The `Thread_Priority_node::Inherited_priorities` is empty.

In case the thread must wait for ownership of a mutex, then it enqueues its priority node in `Thread_Priority_node::Inherited_priorities` of the mutex owner.

In case the thread is dequeued from the wait queue of a mutex, then it dequeues its priority node in `Thread_Priority_node::Inherited_priorities` of the previous mutex owner (ownership transfer) or the current mutex owner (acquire timeout).

In case the minimum of the `Thread_Priority_node::real_priority` and the `Thread_Priority_node::Inherited_priorities` changes, then `Thread_Priority_node::current_priority` is updated. In case the `Thread_Priority_node::owner` its not `NULL`, the priority change propagates to the owner, and so on. In case `Thread_Priority_node::current_priority` changes, the corresponding scheduler is notified.

Use the thread lock to protect the priority nodes.

#2557	4 years ago	fixed	doc	Amar Takhar	Amar Takhar	2 years ago
-------	-------------	-------	-----	-------------	-------------	-------------

Summary: Add word splitting to print output

#2559	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary: Delete the EXTERN pattern

Change the following pattern: some.h:

```

#ifndef SOME_XYZ_EXTERN
#define SOME_XYZ_EXTERN extern
#endif
SOME_XYZ_EXTERN type xyz;

```

some\_xyz.c:

```

#define SOME_XYZ_EXTERN
#include <some.h>

```

Description: into: some.h:

```
extern type xyz;
```

some\_xyz.c:

```

#include <some.h>
type xyz;

```

See discussion:

<https://lists.rtems.org/pipermail/devel/2016-January/013506.html>

Update [Developer/Coding/Conventions](#) accordingly.

#2560	4 years ago	fixed	arch/arm	Sebastian Huber		2 years ago
-------	-------------	-------	----------	-----------------	--	-------------

Summary: smdk2410 is broken due to gp32 removal

Description: The smdk2410 BSPs use files of the removed gp32 BSP.

[\[f2a228b2cb5ce376c56ae8d767084b92f2822af0/rtems\]](https://github.com/rtems/rtems/commit/f2a228b2cb5ce376c56ae8d767084b92f2822af0/rtems)

#2576	4 years ago	fixed	arch/arm	Joel Sherrill	Joel Sherrill <joel@...>	18 months ago
-------	-------------	-------	----------	---------------	--------------------------	---------------

Summary: arm/lpc176x: linker script update (add KEEP() sections)

Description: This BSP's linker script does not include KEEP() directives and thus cannot have per-function and per-data element section support enabled.

The preferred solution is to convert the BSP to use a shared base linker script. The acceptable solution is to add the proper KEEP directives to the existing linker script(s).

Shared linker scripts for the arm, m68k, and sparc have the proper KEEP sections and can serve as examples.

#2606	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary: alarm() uses seconds watchdog and thus is affected by clock changes

Description: alarm() uses `_Watchdog_Insert_seconds()` and thus is affected by clock changes, e.g. via `_TOD_Set()`. This is wrong. The POSIX documentation is not that clear since it talks only about "realtime seconds". However, the FreeBSD implementation uses the uptime. This is also in line with the RTEMS `ualarm()` and `nanosleep()`.

#2608	4 years ago	fixed	posix	Joel Sherrill	Gedare Bloom	2 years ago
-------	-------------	-------	-------	---------------	--------------	-------------

Summary: POSIX Condition Variables Clock Attribute Support

I am beginning to add support for the clock attribute to POSIX condition variables.

[http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread\\_condattr\\_getclock.html](http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_condattr_getclock.html)

Since the clock can't be a CPU time clock, that leaves `CLOCK_MONOTONIC` and `CLOCK_REALTIME`. The thread queue is based on `CLOCK_MONOTONIC` and does not have an option to use `CLOCK_REALTIME`. Threads and timers waiting on `CLOCK_REALTIME` should be impacted by time of day changes.

[https://docs.google.com/document/d/1GsGer0t84p-nUfZFim4Ty0LTDYNhgKBvlwip\\_gLQJTY/edit?usp=sharing](https://docs.google.com/document/d/1GsGer0t84p-nUfZFim4Ty0LTDYNhgKBvlwip_gLQJTY/edit?usp=sharing) is a Google doc with my notes so far in it on POSIX clocks. I will move it to the Wiki as it turns into something more concrete than notes and reflects plans/code.

So the first issue is how best to alter the thread queue to support using either clock source? And what does that do to the current ticks based API since you proposed different time representations for the ticks (relative/monotonic) and seconds (absolute/realtime) structures?

#2617	4 years ago	fixed	score	Joel Sherrill	Sebastian Huber	2 years ago
-------	-------------	-------	-------	---------------	-----------------	-------------

Summary: rtems\_heap\_allocate\_aligned\_with\_boundary() body and prototype inconsistent

The first parameter is `size_t` in the .h and `uintptr_t` in the body. This resulted in a compiler error on the m32c. But it is an inconsistency which should be fixed even if no architecture complained.

The `malloc.h` header file has this:

```
void *rtems_heap_allocate_aligned_with_boundary(
```

Description: `size_t size, uintptr_t alignment, uintptr_t boundary`  
);

malloc\_deferred.c has this:

```
void *rtems_heap_allocate_aligned_with_boundary(
    uintptr_t size, uintptr_t alignment, uintptr_t boundary
)
```

#2624	4 years ago	fixed	tool/newlib	Sebastian Huber	Needs Funding	18 months ago
-------	-------------	-------	-------------	-----------------	---------------	---------------

Summary: Fix the year 2038 problem

RTEMS uses currently a signed 32-bit integer for `time_t` on Newlib. Thus, it is affected by the year 2038 problem. There are only 22 years left and this time span is within the realistic time frame of some RTEMS applications that are developed now.

The `time_t` should be changed to `int64_t` in Newlib. To make sure that all integer operations are carried out properly I suggest to temporarily do this

```
{{#include <sys/_stdint.h>
```

```
typedef struct {
```

```
    int64_t _val;
```

```
} time_t;
```

```
static inline time_t _time_add(time_t a, time_t b) {
```

```
    time_t r = { a._val + b._val }; return r;
```

```
}
```

Description

```
static inline time_t _time_sub(time_t a, time_t b) {
```

```
    time_t r = { a._val - b._val }; return r;
```

```
}
```

```
static inline time_t _time_mul(time_t a, time_t b) {
```

```
    time_t r = { a._val * b._val }; return r;
```

```
}
```

```
static inline time_t _time_div(time_t a, time_t b) {
```

```
    time_t r = { a._val / b._val }; return r;
```

```
} }}}
```

Make sure that RTEMS and Newlib build with this. Add test cases to highlight the `time_t` integer limits.

#2625	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary: Use one lookup tree per-thread for the POSIX keys

Description: Currently a global lookup tree is used for all the POSIX key/value pairs. On SMP configurations this is a bottleneck. Use one lookup tree per thread instead.

#2626	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary: Unify thread cancel/join and delete

Description: The `rtems_task_delete()` is basically a `pthread_cancel()` plus `pthread_join()`. Unify the implementation and introduce a `_Thread_Cancel()` and `_Thread_Join()` to be used by both APIs. Get rid of the Giant lock for thread delete.

#2627	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary: Fix CPU time used for threads on SMP

Description: The CPU time used of a thread is currently maintained per-processor mostly during `_Thread_Dispatch()`. However, on SMP configurations the actual processor of a thread is difficult to figure out since thread dispatching is a highly asynchronous process (e.g. via inter-processor interrupts). Only the intended processor of a thread is known to the scheduler easily. Do the CPU usage accounting during thread heir updates in the context of the scheduler operations. Provide a function to get the CPU usage of a thread using proper locks to get a consistent value.

#2628	4 years ago	wontfix	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	---------	-------	-----------------	-----------------	-------------

Summary: Avoid home-grown condition variable implementation in the Classic Regions

Description: The Classic Region manager enables users to wait until memory is available to satisfy an allocation request. This is done through special purpose code that basically implements a condition variable.

#2631	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary: Use an ISR lock to protect the state of Classic Rate Monotonic objects

Description: The state of Classic Rate Monotonic is currently protected by the Giant lock and ISR disable sections. Use a per-object ISR lock to protect state changes instead.

#2632	4 years ago	fixed	tool/rsb	Joel Sherrill	Chris Johns	2 years ago
-------	-------------	-------	----------	---------------	-------------	-------------

Summary: rtems-tester failure

CentOS 7 on master

```
$ ../rtems-tools/tester/rtems-test --rtems-tools=/home/joel/rtems-4.11-work/tools/4.12 --rtems-bsp=sis find -name "hello.exe" RTEMS Testing - Tester, 4.12 (a5d243d3f8e2)
```

```
Command Line: ../rtems-tools/tester/rtems-test --rtems-tools=/home/joel/rtems-4.11-work/tools/4.12 --rtems-bsp=sis ./sparc-rtems4.12/c/sis/testsuites/samples/hello/hello.exe Python: 2.7.5 (default, Nov 20 2015, 02:00:19) [GCC 4.8.5 20150623 (Red Hat 4.8.5-4)]
```

```
[1/1] p:0 f:0 t:0 i:0 | sparc/sis: hello.exe Traceback (most recent call last):
```

Description: File `"../rtems-tools/tester/rtems-test"`, line 40, in `<module>`

```
    rt.test.run()
```

```
File "/data/home/joel/rtems-4.11-work/rtems-tools/tester/rt/test.py", line 287, in run
```

```
    tst.reraise()
```

```
File "/data/home/joel/rtems-4.11-work/rtems-tools/tester/rt/test.py", line 123, in reraise
```

```
    raise (self.result[0], self.result[1], self.result[2])
```

`TypeError?: init() takes exactly 2 arguments (1 given)`

#2633	4 years ago	fixed	network/legacy	joguinn	Sebastian Huber	2 years ago
-------	-------------	-------	----------------	---------	-----------------	-------------

Summary: waf build failed for rtems-libbsd

The `rtems-libbsd` failed when building with `waf`. Here is the output:

```
[488/845] Compiling freebsd/sys/kern/subr_taskqueue.c In file included from /home/josh/development/rtems/bsps/4.12/i386-rtems4.12/pc386/lib/include/rtems/score/threadimpl.h:36:0,
```

```
from ../freebsd/sys/kern/subr_sleepqueue.c:91:
```

```
/home/josh/development/rtems/bsps/4.12/i386-rtems4.12/pc386/lib/include/rtems/score/watchdogimpl.h: In function 'Watchdog_Per_CPU_insert_relative':
```

/home/josh/development/rtems/bsps/4.12/i386-rtems4.12/pc386/lib/include/rtems/score/watchdogimpl.h:356:18: error: 'struct <anonymous>' has no member named '\_bsd\_ticks'; did you mean 'ticks'?

cpu->Watchdog.ticks + ticks

In file included from ../frebsd/sys/kern/subr\_sleepqueue.c:62:0: ../frebsd/sys/kern/subr\_sleepqueue.c: In function 'sleepq\_set\_timeout':  
../frebsd/sys/kern/subr\_sleepqueue.c:424:29: error: 'Thread\_Timer\_information {aka struct <anonymous>}' has no member named 'state'

Descripti  
on

BSD\_ASSERT(executing->Timer.state == WATCHDOG\_INACTIVE);

../frebsd/sys/kern/subr\_sleepqueue.c:424:2: note: in expansion of macro 'BSD\_ASSERT'

BSD\_ASSERT(executing->Timer.state == WATCHDOG\_INACTIVE); ^

../frebsd/sys/kern/subr\_sleepqueue.c:425:2: error: too many arguments to function '\_Watchdog\_Initialize'

\_Watchdog\_Initialize(&executing->Timer, sleepq\_timeout, ^

In file included from /home/josh/development/rtems/bsps/4.12/i386-rtems4.12/pc386/lib/include/rtems/score/threadimpl.h:36:0,

from ../frebsd/sys/kern/subr\_sleepqueue.c:91:

/home/josh/development/rtems/bsps/4.12/i386-rtems4.12/pc386/lib/include/rtems/score/watchdogimpl.h:178:27: note: declared here

RTEMS\_INLINE\_ROUTINE void \_Watchdog\_Initialize(  
-  
-

Waf: Leaving directory ` /home/josh/development/rtems/rtems-libbsd/build/i386-rtems4.12-pc386' Build failed

#2634	4 years ago	fixed	arch/i386	Joel Sherrill	Pavel Pisa <ppisa@...>	2 years ago
Summary	New warning in pc386 VESA driver					

Pavel.. can you look into this?

Descripti  
on

../frebsd/sys/kern/subr\_sleepqueue.c: In function 'find\_mode\_using\_EDID':

../frebsd/sys/kern/subr\_sleepqueue.c:502:13: warning: dereferencing type-punned pointer will break strict-aliasing rules [-Wstrict-aliasing]

if (\*(uint16\_t\*)&edid.STI[index] == EDID\_STI\_DescriptorUnused) ^

#2638	4 years ago	fixed	unspecified	Joel Sherrill	Joel Sherrill <joel@...>	2 years ago
Summary	pc386: ld -r issue with per function sections					

The pc386 BSP has an issue with "ld -r" when function-sections is enabled which does not seem to occur on any other BSP. The same lines were added to the custom .cfg file as on other BSPs. It is unknown at this point whether this is an x86 specific "ld -r" issue or a pc386 build configuration issue.

Descripti  
on

Per-function-section linking is disabled until this is addressed.

i386-rtems4.12-gcc --pipe -B../frebsd/sys/kern/subr\_sleepqueue.c: In function 'find\_mode\_using\_EDID':  
Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -qnoimplicit -nostdlib -r -Wl,--gc-sections -Wl,-Ttext,0x00100000 -o ne2000\_rel ne2000\_rel-ne2000.o  
/data/home/joel/rtems-4.11-work/tools/4.12/bin/./lib/gcc/i386-rtems4.12/6.0.0/./../i386-rtems4.12/bin/ld: gc-sections requires either an entry or an undefined symbol collect2:  
error: ld returned 1 exit status

#2641	4 years ago	fixed	build	aurelio	Chris Johns	23 months ago
Summary	configure: enable-rtemsbsp doesn't warn if bsp does not exist					

When running configure with an incorrect bsp name the script does not cause an error. You can ever run make without getting any warning message.

The script should check the name of the bsp and continue only if it is a valid bsp. On the other hand if the bsp name given by the user is invalid the script should prompt a message.

#2644	4 years ago	fixed	tool/rsb	Joel Sherrill		2 years ago
Summary	sis does not run on gdb 7.11 but does on gdb 7.9					

I know we reported this on the gdb list but we should have a ticket.

Descripti  
on

Neither gdb nor run works for sis on gdb 4.11. Checked against RTEMS 4.11 tools (gdb 4.9) and it will run sis.

Not sure about other simulators.

#2649	4 years ago	fixed	tool/rsb	Chris Johns	Chris Johns	2 years ago
Summary	RSB remove 4.11, 4.10 and 4.9 from the master branch.					

Having 4.11 on master is confusing users as they build 4.11 tool on master and there may be issues in 4.11 configurations fixed on the 4.11 branch.

Leave 4.9 and 4.10 until they are branched off master. We will make these branches once 4.12 is stable again.

#2663	4 years ago	wontfix	arch/i386	Joel Sherrill	Sebastian Huber	2 years ago
Summary	pc386 BSP has complex dependencies					

In 4.11, the minimum executable did not include open() and close() because the methods rtems\_libio\_post\_driver() and rtems\_libio\_exit() were not included in the executable. On the master, these two methods are showing up in minimum and pulling in these methods.

Descripti  
on

The dependency chain used to be if the console driver was installed, we needed to open and close stdin, stdout, and stderr. Now even without the console configured these are included.

FWIW the minimum size looks pretty good on the master for sis. Fixing this would likely drop it at least another 5%.

#2664	4 years ago	duplicate	score	Joel Sherrill	Sebastian Huber	2 years ago
Summary	spclock_err02					

New test failure on sis but likely all targets.

\* BEGIN OF TEST SPCLOCK\_ERR 2 \* TA1 - rtems\_io\_close - RTEMS\_INVALID\_NUMBER TA1 - rtems\_io\_control - RTEMS\_INVALID\_NUMBER TA1 - rtems\_io\_initialize - RTEMS\_INVALID\_NUMBER TA1 - rtems\_io\_open - RTEMS\_INVALID\_NUMBER TA1 - rtems\_io\_read - RTEMS\_INVALID\_NUMBER TA1 - rtems\_io\_write - RTEMS\_INVALID\_NUMBER TA1 - rtems\_clock\_set - 23:59:59 12/31/2000 - RTEMS\_SUCCESSFUL TA1 - rtems\_clock\_get\_tod - 00:00:00 01/01/2001 - RTEMS\_SUCCESSFUL TA1 - rtems\_clock\_set - 23:59:59 12/31/1999 - RTEMS\_SUCCESSFUL TA1 - rtems\_clock\_get\_tod - 00:00:00 01/01/2000 - RTEMS\_SUCCESSFUL assertion "ticks < 0x400000000" failed: file  
"../cpukit/./././sis/lib/include/rtems/score/watchdogimpl.h", line 316, function: \_Watchdog\_Ticks\_from\_timespec

Breakpoint 1, \_Terminate (the\_source=the\_source@entry=RTEMS\_FATAL\_SOURCE\_ASSERT,

is\_internal=is\_internal@entry=false, the\_error=the\_error@entry=33694096) at ../frebsd/sys/kern/subr\_sleepqueue.c:36

36 { (gdb) bt #0 \_Terminate (the\_source=the\_source@entry=RTEMS\_FATAL\_SOURCE\_ASSERT,

is\_internal=is\_internal@entry=false, the\_error=the\_error@entry=33694096) at ../frebsd/sys/kern/subr\_sleepqueue.c:36

#1 0x0200aed4 in rtems\_fatal (source=source@entry=RTEMS\_FATAL\_SOURCE\_ASSERT,

error=error@entry=33694096) at ../frebsd/sys/kern/subr\_sleepqueue.c:34

#2 0x02004a9c in assert\_func (

file=file@entry=0x201a650 "../cpukit/./././sis/lib/include/rtems/score/watchdogimpl.h", line=line@entry=316, func=func@entry=0x201a6d0 <func\_3277>

"\_Watchdog\_Ticks\_from\_timespec", failedexpr=failedexpr@entry=0x201a638 "ticks < 0x400000000") at ../frebsd/sys/kern/subr\_sleepqueue.c:52

#3 0x0200bbf8 in \_Watchdog\_Ticks\_from\_timespec (ts=0x2022210)

Descripti  
on

at ../cpukit/./././sis/lib/include/rtems/score/watchdogimpl.h:316

#4 \_TOD\_Set\_with\_timestamp (tod\_as\_timestamp=tod\_as\_timestamp@entry=0x2022280)





<b>#2689</b>	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	POSIX key destructors must be called during thread restart					
Description	POSIX key destructors must be called during thread restart. Just like the POSIX cleanup handlers. This ensures that the TLS object destructors are called during thread restart for example. It is important for the global construction, which uses a thread restart to run the Init task in a clean environment.					
<b>#2692</b>	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	User extensions execution order must be clarified					
Description	The implemented and documented execution order of some user extensions disagree. Intended behaviour must be tested. Documentation must be updated accordingly.					
<b>#2693</b>	4 years ago	fixed	doc	Joel Sherrill	Chris Johns	2 years ago
Summary	Update doc to reflect obsoleting rtems_clock_get()					
Description	Ticket to reflect documentation change needed on the master but not on 4.11. When new documentation format is available for master, this needs to be accounted for.					
<b>#2694</b>	4 years ago	worksforme	network/legacy	Joel Sherrill	Sebastian Huber	2 years ago
Summary	linking issue for htonl, etc when using -std=c99					
Description	<p>When -std=c99 is on the compile line, there is a linking error for undefined references to <code>htonl</code>, <code>htons</code>, <code>ntohl</code>, and <code>ntohs</code>. This test case is just for <code>htonl</code> but others should be similar. This likely impacts the 4.11 branch of <code>rtems-libbsd</code> as well but I was testing on master.</p> <p>Test case ===== #include &lt;arpa/inet.h&gt;</p> <pre>int main(     int argc, char argv ) {     uint32_t v = (uint32_t) argc; uint32_t rc = htonl(v); return v; } =====</pre> <p>This script was what I used to find what caused the linking error to go away.</p> <pre>===== RTEMS_MAKEFILE_PATH=/home/joel/rtems-4.11-work/tools/4.12/1386-rtems4.12/pc586/ i386-rtems4.12-gcc -std=c99 \     -B\${RTEMS_MAKEFILE_PATH}/lib -specs bsp_specs -qrtems \ -D_XOPEN_SOURCE=600 -DUSE_SVID main.c -lbsd -lm -lbsd i386-rtems4.12-gcc -std=c99 \     -B\${RTEMS_MAKEFILE_PATH}/lib -specs bsp_specs -qrtems \ -DUSE_SVID main.c -lbsd -lm -lbsd i386-rtems4.12-gcc -std=c99 \     -B\${RTEMS_MAKEFILE_PATH}/lib -specs bsp_specs -qrtems \ main.c -lbsd -lm -lbsd i386-rtems4.12-gcc \     -B\${RTEMS_MAKEFILE_PATH}/lib -specs bsp_specs -qrtems \ main.c -lbsd -lm -lbsd =====</pre>					
<b>#2695</b>	4 years ago	fixed	tool/gcc	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add libatomic for RTEMS					
<b>#2696</b>	4 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Unpredictable errno value returned by <code>sem_wait()</code> in case of semaphore deletion					
Description	<code>_POSIX_Semaphore_Delete()</code> used <code>-1</code> for the thread queue flush status which in turn resulted in an invalid memory access in <code>_POSIX_Semaphore_Translate_core_semaphore_return_code()</code> .					
<b>#2698</b>	4 years ago	fixed	tool/gcc	Sebastian Huber		2 years ago
Summary	GCC 6.1 is broken for microblaze					
Description	<p>The enabled libatomic reveals a bug in the microblaze RTEMS configuration:</p> <pre>configure:3566: checking for C compiler default output file name configure:3588: /scratch/git-rtems-source-builder/rtems/build/microblaze-rtems4.12-gcc-6.0.1-RC-20160415-newlib-6ee81f44e04848901c7b05c968564d34a7ceed06-x86_64-linux-gnu-1/build/.gcc/xgcc -B/scratch/git-rtems-source-builder/rtems/build/microblaze-rtems4.12-gcc-6.0.1-RC-20160415-newlib-6ee81f44e04848901c7b05c968564d34a7ceed06-x86_64-linux-gnu-1/build/.gcc/ -nostdinc -B/scratch/git-rtems-source-builder/rtems/build/microblaze-rtems4.12-gcc-6.0.1-RC-20160415-newlib-6ee81f44e04848901c7b05c968564d34a7ceed06-x86_64-linux-gnu-1/build/microblaze-rtems4.12/newlib/ -isystem /scratch/git-rtems-source-builder/rtems/build/microblaze-rtems4.12-gcc-6.0.1-RC-20160415-newlib-6ee81f44e04848901c7b05c968564d34a7ceed06-x86_64-linux-gnu-1/build/microblaze-rtems4.12/newlib/targ-include -isystem /scratch/git-rtems-source-builder/rtems/build/microblaze-rtems4.12-gcc-6.0.1-RC-20160415-newlib-6ee81f44e04848901c7b05c968564d34a7ceed06-x86_64-linux-gnu-1/build/microblaze-rtems4.12/microblaze-rtems4.12/lib/ -isystem /build/rtems-4.12/microblaze-rtems4.12/include -isystem /build/rtems-4.12/microblaze-rtems4.12/sys-include -g -O2 conftest.c &gt;&amp;5 /build/rtems-4.12/microblaze-rtems4.12/bin/ld: cannot open linker script file xilinx.ld: No such file or directory collect2: error: ld returned 1 exit status</pre> <p>Reason:</p> <pre>gcc/config/microblaze/microblaze.h: %!T*: -dT xilinx.ld%\$)"</pre> <p>This should be somehow fixed in the RTEMS GCC configuration for microblaze.</p>					
<b>#2700</b>	4 years ago	fixed	unspecified	David Biderman	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	<code>cpukit/libfs/src/nfsclient/src/rpcio.c:524:</code> (style) Suspicious condition					
Description	<p><code>cpukit/libfs/src/nfsclient/src/rpcio.c:524:</code> (style) Suspicious condition (assignment + comparison); Clarify expression with parentheses.</p> <p>Source code is</p> <pre>if ( (len = getgroups(NGROUPS, gids) &lt; 0 ) ) { maybe better code if ( (len = getgroups(NGROUPS, gids)) &lt; 0 ) {</pre>					
<b>#2701</b>	4 years ago	fixed	build	printk	Amar Takhar	2 years ago
Summary	Rename asm file with <code>.S</code> (upper case) ext. name					
Description	There are some asm file with <code>.s</code> ext. name, <code>.s</code> and <code>.S</code> is different for gnu as, the pre processed produce <code>.s</code> file from <code>.S</code> . In a word, <code>.S</code> can use <code>#define</code> <code>.s</code> can not. <code>KBuild</code> clean <code>.s</code> files when make clean. I have submit a patch to devel, but blocked. Too big patch.					
<b>#2702</b>	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove descriptor objects for POSIX message queues					
Description	The <code>mq_open()</code> function returns a descriptor to a POSIX message queue object identified by a name. This is similar to <code>sem_open()</code> . In contrast to the POSIX semaphore the POSIX message queues use a separate object for the descriptor. This extra object is superfluous, since the object identifier can be used directly for this purpose, just like for the semaphores.					
<b>#2706</b>	4 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber <sebastian.huber@...>	2 years ago

Summary	Buffer allocation of capture engine is broken on SMP configurations					
Description	The capture engine uses function static variables.					
#2707	4 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	Unsafe use of current processor index in capture engine					
Description	The current processor index is used outside a thread dispatch disabled section.					
#2714	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	A pthread_detach() does not lead to a resource reclamation					
Description	According to POSIX a pthread_detach() should lead to a resource reclamation if the thread is already cancelled.					
#2718	4 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Blocking_CORE_message_queue_Submit() may lead to unpredictable results					
Description	The thread wait return code is not properly initialized before the thread queue enqueue.					
#2722	4 years ago	fixed	tool/newlib	Sebastian Huber	Sebastian Huber	2 years ago
Summary	SEM_VALUE_MAX is unusually small on RTEMS					
Description	RTEMS defines SEM_VALUE_MAX to 32767 in Newlib newlib/libc/sys/rtems/include/limits.h Other systems use INT_MAX or 2147483647.					
#2723	4 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	2 years ago
Summary	CPUINFO command to report per-processor information					
Description	Add a CPUINFO command to report per-processor information, e.g. processor index, online state and scheduler assignment.					
Description	<pre>[/] # cpuinfo ----- PER PROCESSOR INFORMATION ----- INDEX   ONLINE   SCHEDULER ID   SCHEDULER NAME ----- 0   1   0x0f010001   MPS 1   1   0x0f010001   MPS 2   1   0x0f010001   MPS 3   1   0x0f010001   MPS 4   1   0x0f010001   MPS 5   1   0x0f010001   MPS 6   1   0x0f010001   MPS 7   1   0x0f010001   MPS 8   1   0x0f010001   MPS 9   1   0x0f010001   MPS 10   1   0x0f010001   MPS 11   1   0x0f010001   MPS 12   1   0x0f010001   MPS 13   1   0x0f010001   MPS 14   1   0x0f010001   MPS 15   1   0x0f010001   MPS 16   1   0x0f010001   MPS 17   1   0x0f010001   MPS 18   1   0x0f010001   MPS 19   1   0x0f010001   MPS 20   1   0x0f010001   MPS 21   1   0x0f010001   MPS 22   1   0x0f010001   MPS 23   1   0x0f010001   MPS</pre>					
#2725	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Classic binary semaphores without a locking protocol can be released by everyone					
Description	<p>The Classic binary semaphores without a locking protocol can be released by everyone, e.g. in contrast to the POSIX mutexes (all variants) or the Classic binary semaphores with priority inheritance or ceiling, there is no owner check in the release path.</p> <p>This behaviour is a bit unexpected and not documented.</p> <p>The following test case fails in case an owner check is added:</p> <pre>*** BEGIN OF TEST SP 42 *** Exercising blocking discipline w/extract in FIFO order Exercising blocking discipline w/unblock in FIFO order TA00 - unblocked - OK  rtems_semaphore_delete FAILED -- expected (RTEMS_SUCCESSFUL) got (RTEMS_RESOURCE_IN_USE)</pre> <p>This is actually a bug in the test, since an available mutex is released again.</p>					
#2726	4 years ago	fixed	arch/sparc	Sebastian Huber	Daniel Hellstrom	2 years ago
Summary	grascs.c: Questionable use of binary semaphore					
Description	Use a simple binary semaphore or binary semaphore with inherit priority instead.					
Description	<pre>c/src/lib/libbsp/sparc/shared/ascs/grascs.c c/src/lib/libbsp/sparc/shared/ascs/grascs.c /* Create semaphores for blocking ASCS_TC/TM functions */ c/src/lib/libbsp/sparc/shared/ascs/grascs.c if(rtems_semaphore_create(rtems_build_name('A','S','C','0'),1, c/src/lib/libbsp/sparc/shared/ascs/grascs.c (RTEMS_FIFO RTEMS_BINARY_SEMAPHORE) c/src/lib/libbsp/sparc/shared/ascs/grascs.c RTEMS_NO_INHERIT_PRIORITY RTEMS_LOCAL  c/src/lib/libbsp/sparc/shared/ascs/grascs.c RTEMS_NO_PRIORITY_CEILING), 0, c/src/lib/libbsp/sparc/shared/ascs/grascs.c &amp;cfg-&gt;tcsem1) != RTEMS_SUCCESSFUL) { c/src/lib/libbsp/sparc/shared/ascs/grascs.c goto init_error2; c/src/lib/libbsp/sparc/shared/ascs/grascs.c } c/src/lib/libbsp/sparc/shared/ascs/grascs.c if(rtems_semaphore_create(rtems_build_name('A','S','C','2'),0, c/src/lib/libbsp/sparc/shared/ascs/grascs.c (RTEMS_FIFO RTEMS_BINARY_SEMAPHORE) c/src/lib/libbsp/sparc/shared/ascs/grascs.c RTEMS_NO_INHERIT_PRIORITY RTEMS_LOCAL  c/src/lib/libbsp/sparc/shared/ascs/grascs.c RTEMS_NO_PRIORITY_CEILING), 0, c/src/lib/libbsp/sparc/shared/ascs/grascs.c &amp;cfg-&gt;tcsem2) != RTEMS_SUCCESSFUL) {</pre>					

#2727	4 years ago	fixed	fs/fat	Sebastian Huber	Sebastian Huber	2 years ago
Summary	FAT file systems use wrong Semaphore for mutual exclusion					
Description	<pre> cpukit/libfs/src/dosfs/msdos_initsupp.c- cpukit/libfs/src/dosfs/msdos_initsupp.c- sc = rtems_semaphore_create(3, cpukit/libfs/src/dosfs/msdos_initsupp.c- 1, cpukit/libfs/src/dosfs/msdos_initsupp.c- RTEMS_BINARY_SEMAPHORE   RTEMS_FIFO, cpukit/libfs/src/dosfs/msdos_initsupp.c- 0, cpukit/libfs/src/dosfs/msdos_initsupp.c- &amp;fs_info-&gt;vol_sema); cpukit/libfs/src/dosfs/msdos_initsupp.c- </pre>					
	Should use a binary semaphore with inherit priority.					
#2728	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Pipes use wrong semaphore for mutual exclusion					
Description	<pre> cpukit/libfs/src/pipe/ffio.c- sc = rtems_semaphore_create( cpukit/libfs/src/pipe/ffio.c- rtems_build_name('P', 'I', 'P', 'E'), cpukit/libfs/src/pipe/ffio.c- 1, cpukit/libfs/src/pipe/ffio.c- RTEMS_BINARY_SEMAPHORE   RTEMS_INHERIT_PRIORITY   RTEMS_PRIORITY, cpukit/libfs/src/pipe/ffio.c- RTEMS_NO_PRIORITY, cpukit/libfs/src/pipe/ffio.c- &amp;pipe_semaphore cpukit/libfs/src/pipe/ffio.c- ); </pre>					
	Should use a binary semaphore with inherit priority instead.					
#2729	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	TFTP client uses wrong semaphore for mutual exclusion					
Description	<pre> cpukit/libnetworking/lib/tftpDriver.c- rtems_build_name('T', 'F', 'T', 'P'), cpukit/libnetworking/lib/tftpDriver.c- 1, cpukit/libnetworking/lib/tftpDriver.c- RTEMS_FIFO   cpukit/libnetworking/lib/tftpDriver.c- RTEMS_BINARY_SEMAPHORE   cpukit/libnetworking/lib/tftpDriver.c- RTEMS_NO_INHERIT_PRIORITY   cpukit/libnetworking/lib/tftpDriver.c- RTEMS_NO_PRIORITY_CEILING   cpukit/libnetworking/lib/tftpDriver.c- RTEMS_LOCAL, </pre>					
	Should use a binary semaphore with inherit priority.					
#2732	4 years ago	fixed	posix	Gedare Bloom	Gedare Bloom	2 years ago
Summary	Add clock_nanosleep()					
Description	<p>The clock_nanosleep function is provided to enable specifying the clock source (CLOCK_REALTIME or CLOCK_MONOTONIC) and to control whether or not to use an absolute or relative reference point via TIMER_ABSTIME flag.</p> <p>See also: <a href="http://pubs.opengroup.org/onlinepubs/009695399/functions/clock_nanosleep.html">http://pubs.opengroup.org/onlinepubs/009695399/functions/clock_nanosleep.html</a></p>					
#2734	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	pthread_setschedprio() is missing					
Description	<p>See also</p> <p><a href="http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_setschedprio.html">http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_setschedprio.html</a></p> <p>and</p> <p><a href="http://pubs.opengroup.org/onlinepubs/9699919799/functions/V2_chap02.html#tag_15_08_04_01">http://pubs.opengroup.org/onlinepubs/9699919799/functions/V2_chap02.html#tag_15_08_04_01</a></p> <p>In particular the distinction to pthread_setschedparam() (SCHED_FIFO, item 7.).</p> <p>Prototype is defined in Newlib provide &lt;pthread.h&gt;.</p>					
#2735	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	pthread_setschedparam() sets the priority not according to POSIX					
Description	<p>See also</p> <p><a href="http://pubs.opengroup.org/onlinepubs/9699919799/functions/V2_chap02.html#tag_15_08_04_01">http://pubs.opengroup.org/onlinepubs/9699919799/functions/V2_chap02.html#tag_15_08_04_01</a></p> <p>In particular the distinction to pthread_setschedprio() (SCHED_FIFO, item 7.).</p>					
#2736	4 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	pthread_getschedparam() returns wrong priority values					
Description	<p>See also</p> <p><a href="http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_getschedparam.html">http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_getschedparam.html</a></p> <p>"The priority value returned from pthread_getschedparam() shall be the value specified by the most recent pthread_setschedparam(), pthread_setschedprio(), or pthread_create() call affecting the target thread. It shall not reflect any temporary adjustments to its priority as a result of any priority inheritance or ceiling functions."</p>					
#2737	4 years ago	fixed	bsps	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add CLOCK_DRIVER_USE_ONLY_BOOT_PROCESSOR					
Description	Add CLOCK_DRIVER_USE_ONLY_BOOT_PROCESSOR clock driver option. If defined, then do the clock tick processing on the boot processor on behalf of all other processors. Currently, this is intended as a workaround for a Qemu shortcoming on ARM.					
#2740	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Suboptimal type for Timestamp_Control					
Description	<p>Currently we have</p> <pre>typedef struct bintime Timestamp_Control;</pre> <p>this type offers more precision than needed. Maybe use sbintime_t (also known as int64_t) instead to simplify computations.</p>					
#2741	4 years ago	fixed	bsps	Joel Sherrill	Chris Johns	2 years ago
Summary	New warning from printf plugin changes					
Description	<pre> ../../../../../../../../rtems/c/src/lib/libcpu/powerpc/mpc6xx/mmu/pte121.c: In function 'whatPrintf': ../../../../../../../../rtems/c/src/lib/libcpu/powerpc/mpc6xx/mmu/pte121.c:189:46: warning: pointer type mismatch in conditional expression return_Thread_Executing ? (Printf) printf : printk; </pre>					
#2742	4 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	New warning in SHM driver					
Description	<p>Not sure how to fix this one</p> <pre> ../../../../../../../../rtems/c/src/libchip/shmdr/init.c:241:29: warning: assignment from incompatible pointer type [-Wincompatible-pointer-types] </pre>					

on	MPCI_Shm_extensions.fatal = MPC1_Fatal;					
	PowerPC/psim with multiprocessing enabled.					
<b>#2745</b>	4 years ago	fixed	posix	Gedare Bloom	Gedare Bloom	2 years ago
Summary	Use clock from pthread_condattr in pthread_cond_timedwait					
Description	For pthread_cond_timedwait, the condition variable shall have a clock attribute which specifies the clock that shall be used to measure the time specified by the abstime argument. RTEMS currently does not honor the clock attribute.					
	See <a href="http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_cond_timedwait.html">http://pubs.opengroup.org/onlinepubs/9699919799/functions/pthread_cond_timedwait.html</a>					
<b>#2748</b>	4 years ago	fixed	network/legacy	Sebastian Huber	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	Move RTEMS-specific socket wake-up to RTEMS-specific <rtems/rtems_bsdnet.h>					
Description	The <sys/socket.h> contains definitions for the RTEMS-specific socket wake-up support. Move this stuff to <rtems/rtems_bsdnet.h> since this feature is not present in standard network stacks. Portable applications should not use it.					
<b>#2749</b>	4 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 years ago
Summary	rtems_task_set_scheduler() has insufficient parameters					
Description	Task priorities are only valid within a scheduler instance. The rtems_task_set_scheduler() directive moves a task from one scheduler instance to another using the current priority of the thread. However, the current task priority of the source scheduler instance is undefined in the target scheduler instance. Add a third parameter to specify the priority.					
	<pre> /**  * @brief Sets the scheduler instance of a task.  *  * Initially, the scheduler instance of a task is set to the scheduler instance  * of the task that created it. This directive allows to move a task from its  * current scheduler instance to another specified by the scheduler identifier.  *  * @param[in] task_id Identifier of the task. Use @ref RTEMS_SELF to select  * the executing task.  * @param[in] scheduler_id Identifier of the scheduler instance.  * @param[in] priority The task priority with respect to the new scheduler  * instance. The real and initial priority of the task is set to this value.  * The initial priority is used by rtems_task_restart() for example.  *  * @retval RTEMS_SUCCESSFUL Successful operation.  * @retval RTEMS_ILLEGAL_ON_REMOTE_OBJECT Directive is illegal on remote tasks.  * @retval RTEMS_INVALID_ID Invalid task or scheduler identifier.  * @retval RTEMS_INVALID_PRIORITY Invalid priority.  * @retval RTEMS_RESOURCE_IN_USE The task owns resources which deny a scheduler  * change.  *  * @see rtems_scheduler_ident().  */ rtems_status_code rtems_task_set_scheduler(   rtems_id task_id,   rtems_id scheduler_id,   rtems_task_priority priority ); </pre>					
<b>#2750</b>	4 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	Compile Error When Multiprocessing Enabled					
Description	This should impact every BSP with multiprocessing enabled but I saw it on the sparc/leon3 and powerpc/psim					
	<pre> ../../../../psim/lib/include/rtems/score/basedefs.h:229:5: error: static assertion failed: "Message_queue_MP_Packet" _Static_assert(cond, # msg) ../../../../rtems/c/src/../../../../cpukit/rtems/src/msgmp.c:28:1: note: in expansion of macro 'RTEMS_STATIC_ASSERT' RTEMS_STATIC_ASSERT( </pre>					
<b>#2751</b>	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	20 months ago
Summary	Thread dispatch via interrupt is broken at least on ARM and PowerPC					
Description	The ARM and PowerPC interrupt epilogues call _Thread_Dispatch() with interrupts disabled (counter example: SPARC).					
	On SMP configurations, since inter-processor interrupts set the thread dispatch necessary indicator this prevents a thread dispatch notification in post-switch handlers (which all run with interrupts disabled).					
	On all configurations, this is a serious issue for the interrupt latency.					
<b>#2752</b>	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Relax execution environment for thread begin extensions					
Description	Currently, the thread begin extensions are invoked with thread dispatching disabled. There is an explanation for this in the code					
	<pre> /*  * Take care that 'begin' extensions get to complete before  * 'switch' extensions can run. This means must keep dispatch  * disabled until all 'begin' extensions complete.  */ _User_extensions_Thread_begin( executing ); </pre>					
	However, the switch extension is always invoked before the thread begin extension for all threads except the initialization thread. A thread dispatch disabled contexts drastically limits the work which can be carried out in the thread begin extensions. It is for example not possible to call malloc(), create POSIX keys or access C++ thread local storage.					
	The thread begin extension should execute in a normal thread context. Thread begin extensions that are disturbed by a thread dispatch should deal with this locally.					
	With the availability of C++ thread local storage in RTEMS being able to pre-initialize such objects in the thread begin extension would be quite handy.					
<b>#2754</b>	4 years ago	fixed	lib/dl	Patrick Gauvin	Chris Johns	2 years ago
Summary	no .strtab section					
Description	dlopen on the object generated by libfoo.cpp in the attached test case fails and results in the error <code>no .strtab section</code> . readelf shows that the section is present, though:					
	<pre> readelf -S libfoo.o   grep strtab (standard input):97: [92] .shstrtab      STRTAB      00000000 001fb0 00040c 00   0 0 1 (standard input):99: [94] .strtab        STRTAB      00000000 0018b0 00019e 00   0 0 1 </pre>					
	Steps to Reproduce (you may have to edit <code>BSP_DIR</code> in the Makefile):					
	<pre> make clean all qemu-system-arm -m 256M -M xilinx-zynq-a9 -serial null -serial mon:stdio \ -nographic -no-reboot -kernel libdl-strtab-test.exe </pre>					
	Expected Output:					

Description	<p>TEST BEGIN dlopen: no .strtab section assertion "handle != NULL" failed: file "libdl-strtab-test.c", line 46, function: POSIX_Init</p> <p>Development Environment:</p> <ul style="list-style-type: none"> <li><b>RTEMS Version:</b> 4.11 (Branch "4.11", commit <a href="#">3f72dda6ee518d3ea04341ad4df079ecb1895ef7</a>) with the dlerror patches from <a href="#">#2747</a>, and the attached ARM PREL31 support patch (I will be making a separate ticket for this with test code soon).</li> <li><b>System Type:</b> ARM Cortex-A9, xilinx_zynq_a9_qemu BSP</li> <li><b>GCC Version:</b> arm-rtems4.11-gcc (GCC) 4.9.3 20150626 (RTEMS 4.11, RSB 1675a733536d1aec2020011e5e522497a442561a (HEAD, origin/4.11, 4.11), Newlib 2.2.0.20150423)</li> <li><b>RTEMS Configure Options:</b> --target=arm-rtems4.11 --enable-rtemsbsp="xilinx_zynq_a9_qemu xilinx_zynq_zedboard xilinx_zynq_csp_cots xilinx_zynq_csp_hybrid" --enable-tests=samples --enable-posix --prefix=\$HOME/development/rtems/4.11 --disable-networking</li> </ul>					2 years ago	
Summary	<a href="#">#2765</a>	4 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Description	Application level deadlocks may lead to SMP lock level deadlocks						
Description	Due to a missing deadlock detection application level deadlocks may lead to SMP lock level deadlocks.						
Summary	<a href="#">#2768</a>	4 years ago	fixed	unspecified	Chris Johns	Chris Johns	2 years ago
Summary	untar does not keep permissions correctly.						
Description	<p>On disk I have 'x' with:</p> <pre>\$ ls -las x 4 -rwxr-xr-x 1 chris caeng 48 Jul 14 11:46 x</pre> <p>the tar file shows:</p> <pre>\$ tar tvf rootfs.tar -rwxr-xr-x 0 chris caeng 48 Jul 14 11:46 x</pre> <p>and in the IMFS it shows:</p> <pre>[/] # ls -las x 0 -rw-r--r-- 1 root root 48 Jan 1 00:00 x</pre> <p>The makes adding 'joel' scripts difficult.</p>						
Summary	<a href="#">#2769</a>	4 years ago	invalid	unspecified	Chris Johns	Chris Johns	23 months ago
Summary	rtems-syms does not clean up temp files.						
Description	<p>I am seeing temps files such as:</p> <pre>\$ ls -las /tmp/rld-* 0 -rw----- 1 chris wheel 0 Jul 27 18:16 /tmp/rld--04lbaa.rldxx 0 -rw----- 1 chris wheel 0 Jul 27 18:42 /tmp/rld--0niaaa.rldxx 0 -rw----- 1 chris wheel 0 Jul 27 18:39 /tmp/rld--0viaaa.rldxx 0 -rw----- 1 chris wheel 0 Jul 27 18:38 /tmp/rld--1Hhaaa.rldxx 88 -rw----- 1 chris wheel 87426 Jul 27 18:30 /tmp/rld--1libaaa.c 0 -rw----- 1 chris wheel 0 Jul 27 18:24 /tmp/rld--2EZaaa.rldxx 0 -rw----- 1 chris wheel 0 Jul 29 17:11 /tmp/rld--2rwaaa.rldxx 0 -rw----- 1 chris wheel 0 Jul 29 18:14 /tmp/rld--2sBaaa.rldxx 88 -rw----- 1 chris wheel 88148 Jul 29 17:40 /tmp/rld--2umaaa.c 88 -rw----- 1 chris wheel 87426 Jul 27 18:25 /tmp/rld--3baaaa.c 88 -rw----- 1 chris wheel 87426 Jul 27 18:27 /tmp/rld--4Jaaaa.c 0 -rw----- 1 chris wheel 0 Jul 27 18:52 /tmp/rld--4Wiaaa.rldxx 0 -rw----- 1 chris wheel 0 Jul 27 18:38 /tmp/rld--4bfaaa.rldxx</pre> <p>left in /tmp. They look like symbols and so I suspect rtems-syms when building the testsuite with 4.12 (master). This is on FreeBSD.</p>						
Summary	<a href="#">#2770</a>	4 years ago	fixed	doc	Christian Mauderer	Sebastian Huber	2 years ago
Summary	Missing documentation for RTEMS_LINKER_ROSET_CONTENT and RTEMS_LINKER_RWSET_CONTENT						
Description	<p>Currently the two macros RTEMS_LINKER_ROSET_CONTENT RTEMS_LINKER_RWSET_CONTENT are not documented. This should be added as soon as the doc repo is ready for it.</p> <p>The macros have been introduced in this commit: <a href="https://git.rtems.org/rtems/commit/?id=5fe6d07ad5690e3d9c6445ca3a465a700a5a5015">https://git.rtems.org/rtems/commit/?id=5fe6d07ad5690e3d9c6445ca3a465a700a5a5015</a></p>						
Summary	<a href="#">#2771</a>	4 years ago	wontfix	score	Chris Johns		2 years ago
Summary	Empty C++ file with just <rtems.h> does not compile with HEAD.						
Description	<p>I have an application that does not build.</p> <p>The following C++ file:</p> <pre>\$ cat t1.cpp #include &lt;rtems.h&gt;</pre> <p>does not compile with git head <a href="#">5fe6d07ad5690e3d9c6445ca3a465a700a5a5015</a> on Zynq ARM. Build with:</p> <pre>\$ /opt/work/rtems/4.12/bin/arm-rtems4.12-g++ \ -B/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib \ -B/opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib \ -specs bsp_specs -qrtems \ -march=armv7-a -mthumb -mfpu=neon -mfloat-abi=hard -mtune=cortex-a9 \ -g -O2 -DNDEBUG -std=c++11 \ -Werror -Wall -Wextra \ -o t1.o \ -c t1.cpp</pre> <p>Some (too much to post) of the output is:</p>						

Descripti  
on

```
In file included from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/thread.h:36:0,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/heap.h:22,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/types.h:26,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:31,
      from t1.cpp:1:
/opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h: In function 'void _Timestamp_Set(Timestamp_Control*, time_t, long int)':
/opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h:78:33: error: 'timespec2bintime' was not declared in this scope
   timespec2bintime( &_ts, _time );
                        ^
/opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h: In function 'void _Timestamp_Set_to_zero(Timestamp_Control*)':
/opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h:94:8: error: invalid use of incomplete type 'Timestamp_Control {aka struct bintime}'
   _time->sec = 0;
   ^~
In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/time.h:299:0,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h:43,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/thread.h:36,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/heap.h:22,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/types.h:26,
      from /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:31,
      from t1.cpp:1:
/opt/work/rtems/4.12/arm-rtems4.12/include/machine/_time.h:40:15: note: forward declaration of 'Timestamp_Control {aka struct bintime}'
extern struct bintime _Timecounter_Boottimebin;
      ^~~~~~
```

If '-std=c++11' is removed or replaced with '-std=gnu++11' the error becomes:

```
arm-rtems4.12-g++: fatal error: /opt/work/bsps/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/bsp_specs: attempt to rename spec 'endfile' to already defined spec 'old_endfile'
```

#2775	4 years ago	fixed	arch/arm	Chris Johns	Chris Johns <chrisj@...>	2 years ago
Summary	ARM CP15 arm_cp15_set_translation_table_entries fails if TTB in read-only memory					
Descripti on	If the TTB is held in the text section and the section is set to read-only, and cached when booting no section change happen at run time because the table cannot be written too to change. The table cannot be changed unless the MMU is disabled. I suggest the MMU be disabled, the table updated and then the MMU enabled. Note, the issue only shows up on real hardware, qemu does not complain.					
#2776	4 years ago	fixed	score	Alexander Krutwig	Sebastian Huber	2 years ago
Summary	SPI Framework					
Descripti on	Development of a SPI framework which shall be used for further SPI bus and device drivers. The framework shall be developed using the i2c framework as a template. It shall export the Linux Userspace SPI API.					
#2777	4 years ago	fixed	unspecified	Chris Johns	Chris Johns	2 years ago
Summary	Remove librtms++					
Descripti on	This is old and there are better design patterns for threading and C++. We recommend you use the new C++ standards based support.					
#2784	3 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add function to get the current priority of a task by scheduler instance					

Descripti  
on

```
/**
 * @brief Gets the current priority of the specified task with respect to the
 * specified scheduler instance.
 *
 * The current priority reflects temporary priority adjustments due to locking
 * protocols, the rate-monotonic objects on some schedulers and other
 * mechanisms.
 *
 * @param[in] task_id Identifier of the task. Use @ref RTEMS_SELF to select
 * the executing task.
 * @param[in] scheduler_id Identifier of the scheduler instance.
 * @param[out] priority Returns the current priority of the specified task with
 * respect to the specified scheduler instance.
 *
 * @retval RTEMS_SUCCESSFUL Successful operation.
 * @retval RTEMS_ILLEGAL_ON_REMOTE_OBJECT Directive is illegal on remote tasks.
 * @retval RTEMS_INVALID_ADDRESS The priority parameter is @c NULL.
 * @retval RTEMS_INVALID_ID Invalid task or scheduler identifier.
 * @retval RTEMS_NOT_DEFINED The task has no priority within the specified
 * scheduler instance.
 *
 * @see rtems_scheduler_ident().
 */
rtems_status_code rtems_task_get_priority(
  rtems_id task_id,
  rtems_id scheduler_id,
  rtems_task_priority *priority
);
```

#2788	3 years ago	wontfix	score	Chris Johns	Chris Johns	2 years ago
Summary	RTEMS I2C API only defines Standard-mode (Sm) speed as a default.					
Descripti on	The RTEMS I2C API as defined in cpukit/dev/include/dev/i2c/i2c.h only defines the bus speed as Standard-mode (Sm) as defined by the I2C standard. This is set as I2C_BUS_CLOCK_DEFAULT. The default speed is defined by the hardware, ie the devices connected, and not this API. The API should define the speeds as defined in the I2C standard and there should be no default. Drivers like the Cadence driver for the Zynq should be modified to require the bus speed be provided and all future drivers need to provide the speed.					

#2796	3 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Linker sets broken with GCC 7					
See also:	<a href="https://gcc.gnu.org/ml/gcc/2016-09/msg00114.html">https://gcc.gnu.org/ml/gcc/2016-09/msg00114.html</a>					
Description	<p>The</p> <pre>#define MAKEGCCNOTKNOWTHEADDRESS(ptr) asm(":"+r"(ptr))</pre> <p>is probably the best option. It works probably also with link-time optimization.</p>					

#2795	3 years ago	fixed	score	Kuan	Gedare Bloom <gedare@...>	2 years ago
Summary	Overrun Handling for general real-time models					
Description	<p>In the current implementation, if a task period is time out, the next call of <code>rtems_rate_monotonic_period()</code> will only release one following job and manipulate the task period with the calling moment + the next length of period. With the assumption that implicit/constraint deadline and hard real-time model, the above mechanism is okay.</p> <p>However, it may not be applicable for general task models, e.g., soft real-time task, arbitrary deadline, mixed-criticality system [1-4]. It is usually assumed that multiple task jobs of a task are executed in a first-come-first-serve manner. Thus, it is sufficient to release the second task job at the moment the first task job finishes according to a strictly periodic release pattern. The current design in fact shifts the release pattern of periodic/sporadic tasks. Since there maybe more than one postponed jobs due to the preemption, these postponed jobs that should be released are never released to the system.</p> <p>Although there is no standard requirement in reality for deadline misses, with this enhancement, the postponed jobs will be released with the correct number without periodic release shifting. This way of handling is already widely considered in academia from 90s [2] until now [3] or even on multicores as well [4].</p> <p>I refine the following four files and handle this requirement individually. The overhead seems to me negligible. <code>cpukit/rtems/include/rtems/rtems/ratemon.h</code> <code>cpukit/rtems/include/rtems/rtems/ratemonimpl.h</code> <code>cpukit/rtems/src/ratemontimeout.c</code> <code>cpukit/rtems/src/ratemonperiod.c</code> I have tested the enhancement on Qemu and Raspberry Pi Model B+ with corresponding BSPs.</p> <p>I believe this patch as a basis is required for further use for more general real-time task models. This enhancement only affect those timeout cases without changing any behaviour in normal cases. This enhancement is accepted in workshop mixed-criticality (WMC 2016) along with RTSS'16 this year [5].</p> <p>To demonstrate the differences, a heuristic example is prepared in <code>testsuites/sptests/sprmsched01</code> to show the benefit of the enhancement: Given two tasks with implicit deadline that task deadline is equal to its period. Task 1 period is 10000 ticks, whereas task 2 is 2000 ticks. Task 1 has the execution time 6000 ticks, and task 2 has 1000 ticks. Assume Task 1 has a higher priority than task 2. Task 1 only executes 2 times. In the expected result, we can observe that the postponed jobs are continuously released till there is no postponed job left, and the task period will still keep as it is. (Job 3-7 in task 2 are postponed jobs)</p> <p>[1] Buttazzo et al., Soft Real-Time Systems: Predictability vs. Efficiency, Springer 2005, <a href="http://www.springer.com/gp/book/9780387237015">http://www.springer.com/gp/book/9780387237015</a> [2] Lehoczky et al., Fixed priority scheduling of periodic task sets with arbitrary deadlines, RTSS 1990, <a href="http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=128748">http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=128748</a> [3] Georg von der Brüggen et al., Systems with Dynamic Real-Time Guarantees in Uncertain and Faulty Execution Environments, RTSS'16, accepted. [4] Huang et al., Response time bounds for sporadic arbitrary-deadline tasks under global fixed-priority scheduling on multiprocessors, RTNS 2015, <a href="http://dl.acm.org/citation.cfm?doid=2597457.2597459">http://dl.acm.org/citation.cfm?doid=2597457.2597459</a> [5] Chen et al., Overrun Handling for Mixed-Criticality Support in RTEMS, WMC 2016, accepted.</p>					

#2797	3 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add ability to add/remove processors to/from a scheduler instance					
Description	<p>The scheduler configuration is done at link-time. In order to support run-time re-configuration add functions to <code>dd/remove processors to/from a scheduler instance</code>.</p> <pre>/**  * @brief Adds a processor the set of processors owned by the scheduler.  *  * Must be called from task context. This operation obtains and releases the  * objects allocator lock.  *  * @param[in] scheduler_id Identifier of the scheduler.  * @param[in] cpu_index Index of the processor to add.  *  * @retval RTEMS_SUCCESSFUL Successful operation.  * @retval RTEMS_INVALID_ID Invalid scheduler identifier.  * @retval RTEMS_NOT_CONFIGURED The processor is not configured to be used by  * the application.  * @retval RTEMS_INCORRECT_STATE The processor is configured to be used by  * the application, however, it is not available.  */ rtems_status_code rtems_scheduler_add_processor(     rtems_id scheduler_id,     uint32_t cpu_index );  /**  * @brief Removes a processor from set of processors owned by the scheduler.  *  * Must be called from task context. This operation obtains and releases the  * objects allocator lock. Removing a processor from a scheduler is a complex  * operation that involves all tasks in the system.  *  * @param[in] scheduler_id Identifier of the scheduler.  * @param[in] cpu_index Index of the processor to add.  *  * @retval RTEMS_SUCCESSFUL Successful operation.  * @retval RTEMS_INVALID_ID Invalid scheduler identifier.  * @retval RTEMS_INVALID_NUMBER The processor is not owned by the scheduler.  * @retval RTEMS_RESOURCE_IN_USE The set of processors owned by the scheduler  * would be empty after the processor removal and there exists a non-idle  * task that uses this scheduler as its home scheduler.  */ rtems_status_code rtems_scheduler_remove_processor(     rtems_id scheduler_id,     uint32_t cpu_index );</pre>					

#2798	3 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Fix POSIX timer interval					
See also:	<a href="https://lists.rtems.org/pipermail/users/2016-October/030714.html">https://lists.rtems.org/pipermail/users/2016-October/030714.html</a>					
Description						







#2819	3 years ago	fixed	arch/powerpc	Joel Sherrill	Sebastian Huber	2 years ago
-------	-------------	-------	--------------	---------------	-----------------	-------------

Summary: powerpc-ss555 does not compile on master

Recent changes broke this configuration:

```

gmake[6]: Entering directory `./data/home/joel/rtems-4.11-work/rtems-testing/rtems/build-powerpc-ss555-rtems/powerpc-rtems4.12/c/ss555/testsuites/samples/hello' powerpc-rtems4.12-gcc -B../..../ss555/lib/ -specs bsp_specs -drtems -DHAVE_CONFIG_H -I../..../rtems/c/src/././testsuites/samples/hello -I.. -mcpu=505 -Dmpc555 -O2 -g -fno-keep-inline-functions -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT init.o -MD -MP -MF .deps/init.Tpo -c -o init.o ../..../rtems/c/src/././testsuites/samples/hello/init.c In file included from ../..../ss555/lib/include/rtems/score/percpu.h:22:0,
    from ../..../ss555/lib/include/rtems/confdefs.h:32, from ../..../rtems/c/src/././testsuites/samples/hello/init.c:51:
../..../ss555/lib/include/rtems/score/cpuimpl.h:196:3: error: conflicting types for 'CPU_Interrupt_frame'
    } CPU_Interrupt_frame;
    In file included from ../..../ss555/lib/include/bsp/irq.h:28:0,
    from ../..../ss555/lib/include/bsp.h:31, from ../..../rtems/c/src/././testsuites/samples/hello/init.c:17:
../..../ss555/lib/include/libcpu/irq.h:193:3: note: previous declaration of 'CPU_Interrupt_frame' was here
    } CPU_Interrupt_frame;
gmake[6]: * [Init.o] Error 1 gmake[6]: Target `all' not remade because of errors.

```

#2820	3 years ago	fixed	arch/sparc	Joel Sherrill	Sebastian Huber	2 years ago
-------	-------------	-------	------------	---------------	-----------------	-------------

Summary: All SPARC64 BSPs do not Build on master

Recent changes broke all builds:

```

sparc64-rtems4.12-gcc --pipe -DHAVE_CONFIG_H -I../..../cpukit/./././usiii/lib/include -mcpu=ultrasparc3 -DUS3 -DSUN4U -g -O2 -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT libscorecpu_a-sparc64-exception-frame-print.o -MD -MP -MF .deps/libscorecpu_a-sparc64-exception-frame-print.Tpo -c -o libscorecpu_a-sparc64-exception-frame-print.o test -f 'sparc64-exception-frame-print.c' || echo
../..../rtems/c/src/./././cpukit/score/cpu/sparc64/ sparc64-exception-frame-print.c sparc64-rtems4.12-gcc --pipe -DHAVE_CONFIG_H -I../..../
I../..../cpukit/./././usiii/lib/include -mcpu=ultrasparc3 -DUS3 -DSUN4U -g -O2 -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT ..no_cpu/libscorecpu_a-cpucounterread.o -MD -MP -MF ..no_cpu/.deps/libscorecpu_a-cpucounterread.Tpo -c -o ..no_cpu/libscorecpu_a-cpucounterread.o test -f '..no_cpu/cpucounterread.c' || echo
../..../rtems/c/src/./././cpukit/score/cpu/sparc64/..no_cpu/cpucounterread.c:15:0: ../..../cpukit/./././usiii/lib/include/rtems/score/cpu.h: In function '_CPU_ISR_Is_enabled':
../..../cpukit/./././usiii/lib/include/rtems/score/cpu.h:759:12: error: 'psr' undeclared (first use in this function)

    return ( psr & SPARC_PSTATE_IE_MASK ) != 0;
../..../cpukit/./././usiii/lib/include/rtems/score/cpu.h:759:12: note: each undeclared identifier is reported only once for each function it appears in gmake[7]: *
no_cpu/libscorecpu_a-cpucounterread.o Error 1 mv -f .deps/libscorecpu_a-context.Tpo .deps/libscorecpu_a-context.Po In file included from
../..../cpukit/./././usiii/lib/include/rtems/system.h:23:0,

```

#2821	3 years ago	invalid	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
-------	-------------	---------	-------------	---------------	-----------------	-------------

Summary: No BSPs Build on Master

I have the latest tools.

All BSPs appear to fail like this:

```

powerpc-rtems4.11-gcc --pipe -DHAVE_CONFIG_H -I.. -I../cpukit/./././psim/lib/include -meabi -mcpu=603e -msdata=sysv -fno-common -Dppc603e -O2 -g -fno-keep-inline-functions -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT src/libscore_a-smpbarrierwait.o -MD -MP -MF src/.deps/libscore_a-smpbarrierwait.Tpo -c -o src/libscore_a-smpbarrierwait.o test -f 'src/smpbarrierwait.c' || echo
../..../rtems/c/src/./././cpukit/score/ src/smpbarrierwait.c
powerpc-rtems4.11-gcc --pipe -DHAVE_CONFIG_H -I.. -I../cpukit/./././psim/lib/include -meabi -mcpu=603e -msdata=sysv -fno-common -Dppc603e -O2 -g -fno-keep-inline-functions -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT src/libscore_a-kern_tc.o -MD -MP -MF src/.deps/libscore_a-kern_tc.Tpo -c -o src/libscore_a-kern_tc.o test -f 'src/kern_tc.c' || echo
../..../rtems/c/src/./././cpukit/score/ src/kern_tc.c powerpc-rtems4.11-gcc --pipe -DHAVE_CONFIG_H -I.. -I../cpukit/./././psim/lib/include -meabi -mcpu=603e -msdata=sysv -fno-common -Dppc603e -O2 -g -fno-keep-inline-functions -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT src/libscore_a-libatomic.o -MD -MP -MF src/.deps/libscore_a-libatomic.Tpo -c -o src/libscore_a-libatomic.o test -f 'src/libatomic.c' || echo
../..../rtems/c/src/./././cpukit/score/ src/libatomic.c mv -f src/.deps/libscore_a-semaphore.Tpo src/.deps/libscore_a-semaphore.Po mv -f src/.deps/libscore_a-once.Tpo src/.deps/libscore_a-once.Po ../..../rtems/c/src/./././cpukit/score/src/libatomic.c:19:32: fatal error:
machine/_libatomic.h: No such file or directory

#include <machine/_libatomic.h>
compilation terminated. gmake[6]: * [src/libscore_a-libatomic.o] Error 1 In file included from /data/home/joel/rtems-4.11-work/tools/4.11/powerpc-rtems4.11/include/sys/param.h:89:0,
    from ../..../rtems/c/src/./././cpukit/score/src/kern_tc.c:48:
../..../cpukit/./././psim/lib/include/sys/uiio.h:41:9: error: unknown type name 'ssize_t'
    typedef ssize_t ssize_t;
../..../cpukit/./././psim/lib/include/sys/uiio.h:46:9: error: unknown type name 'off_t'
    typedef off_t off_t;
../..../cpukit/./././psim/lib/include/sys/uiio.h:46:17: error: conflicting types for 'off_t'
    typedef off_t off_t;

```

#2822	3 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
-------	-------------	-------	-------------	---------------	-----------------	-------------

Summary: m32csm does not build on master

In file included from ../..../cpukit/./././m32csm/lib/include/rtems/score/types.h:22:0,

```

    from ../..../cpukit/./././m32csm/lib/include/rtems/score/cpu.h:40, from ../..../rtems/c/src/./././cpukit/score/src/percpuasm.c:19:
../..../cpukit/./././m32csm/lib/include/rtems/score/defs.h:244:17: error: size of array 'rtems_static_assert_PER_CPU_OFFSET_EXECUTING' is negative
    typedef int rtems_static_assert_ ## msg [(cond) ? 1 : -1]
../..../rtems/c/src/./././cpukit/score/src/percpuasm.c:98:1: note: in expansion of macro 'RTEMS_STATIC_ASSERT'
    RTEMS_STATIC_ASSERT(
../..../cpukit/./././m32csm/lib/include/rtems/score/defs.h:244:17: error: size of array 'rtems_static_assert_PER_CPU_OFFSET_HEIR' is negative
    typedef int rtems_static_assert_ ## msg [(cond) ? 1 : -1]
../..../rtems/c/src/./././cpukit/score/src/percpuasm.c:103:1: note: in expansion of macro 'RTEMS_STATIC_ASSERT'
    RTEMS_STATIC_ASSERT(

```

#2823	3 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
-------	-------------	-------	-------------	---------------	-----------------	-------------

Summary: Nearly all m68k BSPs do not Build on Master

av5282 is the first

```

In file included from ../..../cpukit/./././av5282/lib/include/rtems/score/types.h:22:0,
    from ../..../cpukit/./././av5282/lib/include/rtems/score/cpu.h:26, from ../..../rtems/c/src/./././cpukit/score/src/percpuasm.c:19:

```



name	ratio	1%	2%	5%	10%	20%	50%	100
CPU_Thread_Idle_body	33.395%	=====						
atsam_spi_setup_transfer	6.061%	=====						
atsam_spi_interrupt	4.690%	=====						
Mutex_recursive_Release	3.011%	=====						
Event_Seize	2.955%	=====						
ARMV7M_NVIC_Interrupt_dispatch	2.885%	=====						
rtems_termios_enqueue_raw_characters	2.771%	=====						
rtems_termios_read_tty	2.722%	=====						
Timecounter_Binuptime	2.653%	=====						
Thread_Do_dispatch	2.240%	=====						
Scheduler_priority_Block	2.112%	=====						
ARMV7M_Interrupt_service_leave	2.100%	=====						
Scheduler_priority_Unblock	1.919%	=====						
Mutex_recursive_Acquire	1.876%	=====						
iproc	1.773%	=====						
CPU_Context_switch								

The change resulted in 10% more total idle time on the system.

#2841	3 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary Add NXP SC16IS752 serial device driver

Description Add Termios device driver for NXP SC16IS752 (RS232/RS485 over SPI or I2C).

#2843	3 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------------	-----------------	-----------------	-------------

Summary Use self-contained objects instead of Classic API for drivers and support libraries

The Classic API has some weaknesses:

- Dynamic memory (the workspace) is used to allocate object pools. This requires a complex configuration with heavy use of the C pre-processor.
- Objects are created via function calls which return an object identifier. The object operations use this identifier and map it internally to an object representation.
- The objects reside in a table, e.g. they are suspect to false sharing of cache lines.
- The object operations use a rich set of options and attributes. For each object operation these parameters must be evaluated and validated at run-time to figure out what to do exactly for this operation.

The overhead for Classic API mutexes used for example in Termios and the SPI framework is significant, see discussion:

<https://lists.rtems.org/pipermail/devel/2016-December/016543.html>

There are some API options available:

- Description
1. Use C11 mutexes and condition variables.
  2. Turn the POSIX synchronization objects into self-contained objects and use them.
  3. Use FreeBSD synchronization objects like **MUTEX(9)** or **CONDVAR(9)**.
  4. Add RTEMS-specific self-contained synchronization objects and use them.

Option 1. and 2. lack support for binary semaphores which are used for task/interrupt synchronization, e.g. Termios.

Option 2. needs run-time evaluation to figure out the actual object variant, e.g. non-recursive, recursive, ceiling, error-checking, robust POSIX mutex.

Option 3. uses hash tables, thus it is not suitable for real-time systems.

Option 1. and 2. lack support for user-defined object names that may help for system diagnostic, tracing and debugging.

Option 4. could be used to avoid all shortcomings of options 1-3. It would be trivial to implement, test and document.

In order to enable user-defined object names one option is to add a const char \*name member to Thread\_queue\_Queue.

#2844	3 years ago	fixed	fs	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	----	-----------------	-----------------	-------------

Summary JFFS2: Add IO controls to get filesystem instance information and force a garbage collection

Description Some applications need to control the garbage collection of the JFFS2 filesystem. For example during bootloader to application transitions with execute in place flashes (XIP).

#2845	3 years ago	fixed	doc	Sebastian Huber		2 years ago
-------	-------------	-------	-----	-----------------	--	-------------

Summary Add I2C framework documentation

Description The new I2C framework lacks documentation.

#2849	3 years ago	fixed	doc	Sebastian Huber		2 years ago
-------	-------------	-------	-----	-----------------	--	-------------

Summary ATA/IDE support in RTEMS is out-dated

Description The ATA/IDE support in RTEMS is out-dated. New platforms should consider to use the SATA support provided by FreeBSD via libbsd. Update the documentation accordingly.

#2850	3 years ago	fixed	doc	Sebastian Huber		2 years ago
-------	-------------	-------	-----	-----------------	--	-------------

Summary Driver manual covers non-existent Analog Driver

Description Remove this chapter from the documentation.

#2851	3 years ago	fixed	doc	Sebastian Huber		2 years ago
-------	-------------	-------	-----	-----------------	--	-------------

Summary Driver manual covers non-existent Discrete Driver

Description Remove this chapter from the documentation.

#2853	3 years ago	fixed	doc	Sebastian Huber		2 years ago
-------	-------------	-------	-----	-----------------	--	-------------

Summary Driver manual covers non-existent Non-Volatile Memory Driver

Description Remove this chapter from the documentation.

#2858	3 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary Add user defined thread names

Description Add user defined thread names to ease debugging, enhance the system diagnostics and improve compatibility to other systems, e.g. Linux and FreeBSD.

Implement pthread\_setname\_np() and pthread\_getname\_np(). Add CONFIGURE\_MAXIMUM\_THREAD\_NAME\_SIZE to the application configuration options. Add a application configuration dependent storage area for thread names to the thread control block.

#2859	3 years ago	fixed	posix	Gedare Bloom	Gedare Bloom	2 years ago
-------	-------------	-------	-------	--------------	--------------	-------------

Summary Implement POSIX Shared Memory Objects

POSIX Shared Memory is a widely used API for inter-process communication. The functions in the API include:

- **shm\_open**
- **ftruncate**

Descripti on	<ul style="list-style-type: none"> <li>• mmap</li> <li>• munmap</li> <li>• shm_unlink</li> <li>• close</li> <li>• fstat</li> <li>• fchown</li> <li>• fchmod</li> </ul>					
<b>#2862</b>	3 years ago	fixed	doc	Chris Johns	Chris Johns	2 years ago
Summar y	docs.rtems.org Add support to ReST format releases.					
Descripti on	Add support to the releases section of the web site to handle ReST packages. The catalogues have a legacy field for texinfo docs. The 4.11.0 and 4.11.1 releases need to have a catalogue added because this did not exist when those releases were created.					
<b>#2863</b>	3 years ago	duplicate	doc	Joel Sherrill	Joel Sherrill	2 years ago
Summar y	Update POSIX 1003.1 Compliance Guide for ReST					
Descripti on	The POSIX 1003.1 Compliance Guide should be auto-generated from a spreadsheet into the ReST format. My vague recollection is that we used shell scripts to do this for texinfo output. I will have to decipher what we used to do and define a new procedure. This impacts 4.11 and newer. One issue is having correct information for what methods are present on a branch. The FACE Conformance Test Suite can be used for ~800 of the methods.					
<b>#2864</b>	3 years ago	fixed	doc	Chris Johns		2 years ago
Summar y	docs.rtems.org Automatic update of branches content when a rtems-doc.git change is made.					
Descripti on	Add support to automatically update the branches when a git commit happens.					
<b>#2865</b>	3 years ago	fixed	doc	Chris Johns	Chris Johns	2 years ago
Summar y	Coverage installed when building the docs repeats catalogue.xml entries					
Descripti on	The catalogue repeats entries.					
<b>#2867</b>	3 years ago	fixed	tool	Stavros Passas	Chris Johns	2 years ago
Summar y	Fix exclude rule in rtems-test-check					
Descripti on	rtems-test-check is responsible of checking the testsuite configuration of a given BSP and adapt it based on a given "command". Currently for the "exclude" command, we never exclude anything, the output of the script is always the whole list of the input tests. This happens because the script always starts with output = \$tests and appends on the list the tests that are not excluded, so the output is always all the tests.					
<b>#2868</b>	3 years ago	fixed	arch/arm	David Binderman	Gedare Bloom <gedare@...>	2 years ago
Summar y	src/c/src/lib/libbsp/arm/smdk2410/smc/smc.c: 3 * pointless local variables ?					
Descripti on	<pre>[src/c/src/lib/libbsp/arm/smdk2410/smc/smc.c:235]: (style) Variable 'cnt1' is modified but its new value is never used. [src/c/src/lib/libbsp/arm/smdk2410/smc/smc.c:243]: (style) Variable 'cnt2' is modified but its new value is never used. [src/c/src/lib/libbsp/arm/smdk2410/smc/smc.c:246]: (style) Variable 'cnt3' is modified but its new value is never used. \$ egrep "cnt1 cnt2 cnt3" src/c/src/lib/libbsp/arm/smdk2410/smc/smc.c uint32_t pblock, i, j, lblock, zone, count, cnt1, cnt2, cnt3; cnt1 = 0; cnt2 = 0; cnt3 = 0; cnt1++; cnt2++; cnt3++; \$ Maybe someone left some debug code in ?</pre>					
<b>#2873</b>	3 years ago	fixed	arch/arm	David Binderman	Gedare Bloom <gedare@...>	2 years ago
Summar y	src/c/src/lib/libbsp/arm/raspberrypi/i2c/i2c.c:320: defective error checking ?					
Descripti on	<pre>src/c/src/lib/libbsp/arm/raspberrypi/i2c/i2c.c:320: (style) Checking if unsigned variable 'rv' is less than zero. Source code is rv = rpi_i2c_setup_transfer(bus); if ( rv &lt; 0 ) { but uint32_t rv = 0; and static int rpi_i2c_setup_transfer(rpi_i2c_bus *bus) Suggest put return value into an int local variable, then sanity check it, then assign it to rv.</pre>					
<b>#2874</b>	3 years ago	fixed	arch/powerpc	David Binderman	Sebastian Huber <sebastian.huber@...>	2 years ago
Summar y	src/c/src/lib/libbsp/powerpc/beatnik/marvell/gt_timer.c: 4 * pointless check ?					
Descripti on	<pre>[src/c/src/lib/libbsp/powerpc/beatnik/marvell/gt_timer.c:102]: (style) Checking if unsigned variable 'timer' is less than zero. [src/c/src/lib/libbsp/powerpc/beatnik/marvell/gt_timer.c:109]: (style) Checking if unsigned variable 'timer' is less than zero. [src/c/src/lib/libbsp/powerpc/beatnik/marvell/gt_timer.c:117]: (style) Checking if unsigned variable 'timer' is less than zero. [src/c/src/lib/libbsp/powerpc/beatnik/marvell/gt_timer.c:128]: (style) Checking if unsigned variable 'timer' is less than zero. Parameter "timer" is only ever type uint32_t, so any check &lt; 0 seem pointless.</pre>					
<b>#2877</b>	3 years ago	fixed	score	Stavros Passas	joel.sherrill@...	2 years ago
Summar y	DHCP client fails on complex networks					
Descripti on	<p>What happens is that on networks with more than one DHCP servers, or on networks that use multiple vlans it can happen that After a DHCP discover our client broadcasts, it receives multiple offers, which is perfectly fine based on the DHCP RFC.</p> <p>However our implementation of a DHCP client, expects a linear execution flow:</p> <ol style="list-style-type: none"> <li>1. Broadcast a DHCP discover;</li> <li>2. Wait for a DHCP offer;</li> <li>3. Transmit a DHCP request;</li> <li>4. Wait for a DHCP ack;</li> </ol> <p>However the network stack is not cleaned between the reception of a DHCP offer and a DHCP ack, so if multiple offers are received, just the first one will be processed during the "Receive DHCP offer" phase, and the next one will be received when we expect a "DHCP ack", which makes our implementation assume the DHCP handshake is invalid and fail. Thus we restart the network and retry the whole process from the beginning which will cause the same issue again.</p> <p>This issue that is present from when I remember in RTEMS, definitely from 4.10 up to now.</p>					
<b>#2878</b>	3 years ago	fixed	arch/sparc	David Binderman	Daniel Hellstrom	2 years ago
Summar y	src/c/src/lib/libbsp/sparc/shared/can/occan.c:1573: broken error checking ?					

src/c/src/lib/libbsp/sparc/shared/can/occan.c:1573]: (style) Checking if unsigned variable 'speed=pelican\_speed\_auto(can)' is less than zero.

Source code is

```
if ( ( speed=pelican_speed_auto(can)) < 0 ){
    /* failed */ return RTEMS_IO_ERROR;
}
```

Description

but

```
unsigned int speed;
```

and

```
static int pelican_speed_auto(occan_priv *priv);
```

I am not sure which C compiler gets using in rtems, but I do know that gcc compiler flag -Wtype-limits will flag this kind of problem.

#2879	3 years ago	fixed	score	David Binderman	Chris Johns	2 years ago
-------	-------------	-------	-------	-----------------	-------------	-------------

Summary src/cpukit/libdebugger/rtems-debugger-server.c: four problems

1.

```
src/cpukit/libdebugger/rtems-debugger-server.c:1306]: (style) Redundant condition: extended. '!extended || (extended && check_pid(pid))' is equivalent to '!extended || check_pid(pid)'
```

Suggest simplify.

2.

```
src/cpukit/libdebugger/rtems-debugger-server.c:1858]: (warning) Possible null pointer dereference: rtems_debugger
```

Source code is

```
if (r < 0) {
    rtems_printf(printer, "error: rtems-db: remote begin: %s: %s\n",
        rtems_debugger->remote->name, strerror(errno));
    free(rtems_debugger);
    rtems_debugger = NULL;
}
/*
 * Reset at the end of the session.
 */
rtems_debugger->flags = 0;
```

Description

Suggest adding `return -1` inside the `if`.

3.

```
src/cpukit/libdebugger/rtems-debugger-server.c:906]: (style) Redundant condition: extended. '!extended || (extended && check_pid(pid))' is equivalent to '!extended || check_pid(pid)'
```

Duplicate.

4.

```
src/cpukit/libdebugger/rtems-debugger-server.c:956]: (warning) Char literal compared with pointer 'p'. Did you intend to dereference it?
```

Source code is

```
while (p != NULL && p != '\0') {
```

Maybe better code

```
while (p != NULL && *p != '\0') {
```

#2880	3 years ago	wontfix	unspecified	David Binderman		2 years ago
-------	-------------	---------	-------------	-----------------	--	-------------

Summary src/cpukit/libfs/src/jffs2/src/readinode.c:189: faulty logic

src/cpukit/libfs/src/jffs2/src/readinode.c:189]: (style) Condition 'tn.fn ofs >= offset' is always true

Source code is

```
if (tn->fn->ofs < offset)
    next = tn->rb.rb_right;
else if (tn->fn->ofs >= offset)
    next = tn->rb.rb_left;
else
    break;
```

Description

Maybe better code

```
if (tn->fn->ofs < offset)
    next = tn->rb.rb_right;
else if (tn->fn->ofs > offset)
    next = tn->rb.rb_left;
else
    break;
```

#2883	3 years ago	fixed	arch/arm	David Binderman	Pavel Pisa	2 years ago
-------	-------------	-------	----------	-----------------	------------	-------------

Summary src/c/src/lib/libbsp/arm/tms570/console/tms570-sci.c:248: strange expression ?

src/c/src/lib/libbsp/arm/tms570/console/tms570-sci.c:248]: (style) Same expression on both sides of '|'

Source code is

```
uint32_t fir_tx_ready = TMS570_SCI_FLR_TX_EMPTY | TMS570_SCI_FLR_TX_EMPTY;
```

Description

#2885	3 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------	-----------------	-----------------	-------------

Summary Fix rtems\_rate\_monotonic\_postponed\_job\_count() prototype

rtems\_rate\_monotonic\_postponed\_job\_count() should return an RTEMS status code. It should be renamed to rtems\_rate\_monotonic\_get\_postponed\_job\_count() or rtems\_rate\_monotonic\_get\_postponed\_jobs() (similar to rtems\_rate\_monotonic\_get\_statistics()).

#2889	3 years ago	fixed	score	Stavros Passas	Stavros Passas <stavros.passas@...>	2 years ago
-------	-------------	-------	-------	----------------	-------------------------------------	-------------









Generating ./src/lib/libbsp/powerpc/virtex4/preinstall.am Generating ./src/lib/libbsp/powerpc/mvme3100/preinstall.am Generating ./src/lib/libbsp/powerpc/beatnik/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/qoriq/preinstall.am Generating ./src/lib/libbsp/powerpc/tqm8xx/preinstall.am Generating ./src/lib/libbsp/powerpc/mvme5500/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/mpc8260ads/preinstall.am Generating ./src/lib/libbsp/powerpc/psim/preinstall.am Generating ./src/lib/libbsp/moxie/moxiesim/preinstall.am  
 Generating ./src/lib/libbsp/sparc/erc32/preinstall.am Generating ./src/lib/libbsp/sparc/leon3/preinstall.am Generating ./src/lib/libbsp/sparc/leon2/preinstall.am Generating  
 ./src/lib/libcpu/arm/preinstall.am Generating ./src/lib/libcpu/lm32/preinstall.am Generating ./src/lib/libcpu/nios2/preinstall.am Generating ./src/lib/libcpu/sparc64/preinstall.am  
 Generating ./src/lib/libcpu/1386/preinstall.am Generating ./src/lib/libcpu/mips/preinstall.am Generating ./src/lib/libcpu/or1k/preinstall.am Generating  
 ./src/lib/libcpu/bfin/preinstall.am Generating ./src/lib/libcpu/sh/preinstall.am Generating ./src/lib/libcpu/m68k/preinstall.am Generating ./src/lib/libcpu/powerpc/preinstall.am  
 Generating ./src/lib/libcpu/sparc/preinstall.am Generating ./src/ada/preinstall.am bash: /home/dhanpal/development/rtems/rsb/source-builder/sb-bootstrap: No such file or directory  
 dhanpal@dhanpal-HP-Pavilion-15-Notebook-PC:~/development/rtems/kernel/rtems\$ sudo -s [sudo] password for dhanpal: root@dhanpal-HP-Pavilion-15-Notebook-  
 PC:~/development/rtems/kernel/rtems# ./bootstrap -c && ./bootstrap -p && \  
 [SHOME/development/rtems/rsb/source-builder/sb-bootstrap

removing automake generated Makefile.in files removing configure files removing alocal.m4 files Generating ./cpukit/libmisc/preinstall.am Generating ./cpukit/preinstall.am  
 Generating ./cpukit/ftpd/preinstall.am Generating ./cpukit/mghttpd/preinstall.am Generating ./cpukit/score/preinstall.am Generating ./cpukit/score/cpu/no\_cpu/preinstall.am Generating  
 ./cpukit/score/cpu/arm/preinstall.am Generating ./cpukit/score/cpu/lm32/preinstall.am Generating ./cpukit/score/cpu/nios2/preinstall.am Generating  
 ./cpukit/score/cpu/epiphany/preinstall.am Generating ./cpukit/score/cpu/sparc64/preinstall.am Generating ./cpukit/score/cpu/m32c/preinstall.am Generating  
 ./cpukit/score/cpu/1386/preinstall.am Generating ./cpukit/score/cpu/mips/preinstall.am Generating ./cpukit/score/cpu/v850/preinstall.am Generating  
 ./cpukit/score/cpu/or1k/preinstall.am Generating ./cpukit/score/cpu/bfin/preinstall.am Generating ./cpukit/score/cpu/sh/preinstall.am Generating ./cpukit/score/cpu/m68k/preinstall.am  
 Generating ./cpukit/score/cpu/powerpc/preinstall.am Generating ./cpukit/score/cpu/moxie/preinstall.am Generating ./cpukit/score/cpu/sparc/preinstall.am Generating  
 ./cpukit/libcrypt/preinstall.am Generating ./cpukit/dev/preinstall.am Generating ./cpukit/libpci/preinstall.am Generating ./cpukit/wrapup/preinstall.am Generating  
 ./cpukit/sapi/preinstall.am Generating ./cpukit/libd/preinstall.am Generating ./cpukit/libcsupport/preinstall.am Generating ./cpukit/ppp/preinstall.am Generating  
 ./cpukit/dtc/libfdt/preinstall.am Generating ./cpukit/libnetworking/preinstall.am Generating ./cpukit/libfs/preinstall.am Generating ./cpukit/libfs/src/nfsclient/preinstall.am Generating  
 ./cpukit/zi/preinstall.am Generating ./cpukit/posix/preinstall.am Generating ./cpukit/librpc/preinstall.am Generating ./cpukit/telnetd/preinstall.am Generating  
 ./cpukit/libdebugger/preinstall.am Generating ./cpukit/rtems/preinstall.am Generating ./cpukit/libmd/preinstall.am Generating ./src/wrapup/preinstall.am Generating  
 ./src/libchip/preinstall.am Generating ./src/lib/libbsp/no\_cpu/no\_bsp/preinstall.am Generating ./src/lib/libbsp/preinstall.am Generating ./src/lib/libbsp/arm/csb336/preinstall.am  
 Generating ./src/lib/libbsp/arm/lpc32xx/preinstall.am Generating ./src/lib/libbsp/arm/realview-pbx-a9/preinstall.am Generating ./src/lib/libbsp/arm/preinstall.am Generating  
 ./src/lib/libbsp/arm/stm32f4/preinstall.am Generating ./src/lib/libbsp/arm/atsam/preinstall.am Generating ./src/lib/libbsp/arm/rtl22xx/preinstall.am Generating  
 ./src/lib/libbsp/arm/atsam320/preinstall.am Generating ./src/lib/libbsp/arm/beagle/preinstall.am Generating ./src/lib/libbsp/arm/edb7312/preinstall.am Generating  
 ./src/lib/libbsp/arm/lm3s69xx/preinstall.am Generating ./src/lib/libbsp/arm/lpc176x/preinstall.am Generating ./src/lib/libbsp/arm/lpc24xx/preinstall.am Generating  
 ./src/lib/libbsp/arm/gumstix/preinstall.am Generating ./src/lib/libbsp/arm/xilinx-zyng/preinstall.am Generating ./src/lib/libbsp/arm/gdbarmsim/preinstall.am Generating  
 ./src/lib/libbsp/arm/lpc32xx/preinstall.am Generating ./src/lib/libbsp/arm/tms570/preinstall.am Generating ./src/lib/libbsp/arm/raspberrypi/preinstall.am Generating  
 ./src/lib/libbsp/arm/altera-cyclone-v/preinstall.am Generating ./src/lib/libbsp/lm32/milkyinst/preinstall.am Generating ./src/lib/libbsp/lm32/lm32\_evr/preinstall.am Generating  
 ./src/lib/libbsp/nios2\_iss/preinstall.am Generating ./src/lib/libbsp/epiphany/preinstall.am Generating ./src/lib/libbsp/epiphany/epiphany\_sim/preinstall.am Generating  
 ./src/lib/libbsp/sparc64/niagara/preinstall.am Generating ./src/lib/libbsp/sparc64/usiii/preinstall.am Generating ./src/lib/libbsp/m32c/m32cbsp/preinstall.am Generating  
 ./src/lib/libbsp/1386/pc386/preinstall.am Generating ./src/lib/libbsp/mips/rbtx4938/preinstall.am Generating ./src/lib/libbsp/mips/rbtx4925/preinstall.am Generating  
 ./src/lib/libbsp/mips/hurricane/preinstall.am Generating ./src/lib/libbsp/mips/jmr3904/preinstall.am Generating ./src/lib/libbsp/mips/malta/preinstall.am Generating  
 ./src/lib/libbsp/mips/psb350/preinstall.am Generating ./src/lib/libbsp/v850/preinstall.am Generating ./src/lib/libbsp/v850/gdbv850sim/preinstall.am Generating  
 ./src/lib/libbsp/or1k/preinstall.am Generating ./src/lib/libbsp/or1k/generic\_or1k/preinstall.am Generating ./src/lib/libbsp/bfin/TL6527M/preinstall.am Generating  
 ./src/lib/libbsp/bfin/bf537Stamp/preinstall.am Generating ./src/lib/libbsp/bfin/eZKit533/preinstall.am Generating ./src/lib/libbsp/sh/genesh2/preinstall.am Generating  
 ./src/lib/libbsp/sh/genesh1/preinstall.am Generating ./src/lib/libbsp/sh/genesh4/preinstall.am Generating ./src/lib/libbsp/sh/shsim/preinstall.am Generating  
 ./src/lib/libbsp/m68k/mcf5235/preinstall.am Generating ./src/lib/libbsp/m68k/genmcf548x/preinstall.am Generating ./src/lib/libbsp/m68k/preinstall.am Generating  
 ./src/lib/libbsp/m68k/mcf5329/preinstall.am Generating ./src/lib/libbsp/m68k/psb360/preinstall.am Generating ./src/lib/libbsp/m68k/av5282/preinstall.am Generating  
 ./src/lib/libbsp/m68k/mcf5225x/preinstall.am Generating ./src/lib/libbsp/m68k/mvme147s/preinstall.am Generating ./src/lib/libbsp/m68k/mvme162/preinstall.am Generating  
 ./src/lib/libbsp/m68k/gen68360/preinstall.am Generating ./src/lib/libbsp/m68k/mmm332/preinstall.am Generating ./src/lib/libbsp/m68k/gen68340/preinstall.am Generating  
 ./src/lib/libbsp/m68k/mcf5235/preinstall.am Generating ./src/lib/libbsp/m68k/mvme167/preinstall.am Generating ./src/lib/libbsp/m68k/uc5282/preinstall.am Generating  
 ./src/lib/libbsp/m68k/mvme147/preinstall.am Generating ./src/lib/libbsp/m68k/mcf5206elite/preinstall.am Generating ./src/lib/libbsp/powerpc/motorola\_powerpc/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/virtex5/preinstall.am Generating ./src/lib/libbsp/powerpc/haleakala/preinstall.am Generating ./src/lib/libbsp/powerpc/ss555/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/qemuppc/preinstall.am Generating ./src/lib/libbsp/powerpc/gen83xx/preinstall.am Generating ./src/lib/libbsp/powerpc/gen5200/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/virtex/preinstall.am Generating ./src/lib/libbsp/powerpc/mpc55xevb/preinstall.am Generating ./src/lib/libbsp/powerpc/t32mppc/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/virtex4/preinstall.am Generating ./src/lib/libbsp/powerpc/mvme3100/preinstall.am Generating ./src/lib/libbsp/powerpc/beatnik/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/qoriq/preinstall.am Generating ./src/lib/libbsp/powerpc/tqm8xx/preinstall.am Generating ./src/lib/libbsp/powerpc/mvme5500/preinstall.am  
 Generating ./src/lib/libbsp/powerpc/mpc8260ads/preinstall.am Generating ./src/lib/libbsp/powerpc/psim/preinstall.am Generating ./src/lib/libbsp/moxie/moxiesim/preinstall.am  
 Generating ./src/lib/libbsp/sparc/erc32/preinstall.am Generating ./src/lib/libbsp/sparc/leon3/preinstall.am Generating ./src/lib/libbsp/sparc/leon2/preinstall.am Generating  
 ./src/lib/libcpu/arm/preinstall.am Generating ./src/lib/libcpu/lm32/preinstall.am Generating ./src/lib/libcpu/nios2/preinstall.am Generating ./src/lib/libcpu/sparc64/preinstall.am  
 Generating ./src/lib/libcpu/1386/preinstall.am Generating ./src/lib/libcpu/mips/preinstall.am Generating ./src/lib/libcpu/or1k/preinstall.am Generating  
 ./src/lib/libcpu/bfin/preinstall.am Generating ./src/lib/libcpu/sh/preinstall.am Generating ./src/lib/libcpu/m68k/preinstall.am Generating ./src/lib/libcpu/powerpc/preinstall.am  
 Generating ./src/lib/libcpu/sparc/preinstall.am Generating ./src/ada/preinstall.am bash: /home/dhanpal/development/rtems/rsb/source-builder/sb-bootstrap: No such file or directory  
 root@dhanpal-HP-Pavilion-15-Notebook-PC:~/development/rtems/kernel/rtems#

#2943	3 years ago	wontfix	unspecified	DHANPAL SINGH		2 years ago
Summary	rtems building error					

Description: i am attaching the screenshot of file system

#2945	3 years ago	worksforme	unspecified	Joel Sherrill	Daniel Hellstrom	2 years ago
Summary	Many failures on LEON3 with SMP disabled					

There are approximately ~100 failures, timeouts, etc on the LEON3 BSP. See this thread for some discussion where Jiri notes it is broken on his checkout from December:

<https://lists.rtems.org/pipermail/devel/2017-March/017277.html>

Passed: 458 Failed: 20 Timeouts: 73 Invalid: 3

Total: 554

Failures:

cdtest.exe spintcritical20.exe dl05.exe spintcritical01.exe spintcritical04.exe spintcritical10.exe spintcritical22.exe sp69.exe spintcritical21.exe sp11.exe  
 spintcritical16.exe spintcritical23.exe psxfile01.exe spintcritical05.exe spintcritical02.exe spintcritical08.exe psxgetrusage01.exe spccucounter01.exe  
 spintcritical03.exe psxtimes01.exe

Description:

Timeouts:

nsecs.exe sptask\_err02.exe sprrivenv01.exe psxkey03.exe psxsignal01.exe psx06.exe psx10.exe sp04.exe mrf5\_fstime.exe ticker.exe psxmgsq03.exe psxkey09.exe  
 psx07.exe sptimerserver01.exe psxusleep.exe psxstack02.exe psxkey07.exe psxkey10.exe stackchk.exe sp01.exe fileio.exe spsimplsched01.exe sp03.exe  
 psxcond01.exe sp65.exe sp62.exe psx11.exe psx12.exe psx02.exe imfs\_fstime.exe psxstack01.exe psxstack01.exe spcbssched01.exe termios.exe mimfs\_fstime.exe  
 psxsignal02.exe psx08.exe top.exe psxrwlock01.exe sp22.exe psxsignal04.exe psxkey04.exe mouse01.exe sp24.exe psx04.exe spdfschd01.exe uid01.exe  
 mdofs\_fstime.exe psx16.exe psxai03.exe sp19.exe psxtime.exe psx09.exe psxkey06.exe psxlock.exe cpause.exe psx05.exe sp66.exe psxsignal03.exe capture.exe  
 sp30.exe psxcleanup.exe psxcancel.exe jffs2\_fstime.exe psxsignal06.exe spstdthreads01.exe psxbarrier01.exe sp31.exe sp73.exe psxalarm.exe spffio03.exe  
 psxtimer01.exe monitor.exe

Invalid:

cxx\_iostream.exe spinternaleror01.exe sptimecounter01.exe

#2946	3 years ago	fixed	unspecified	Chris Johns	joel.sherrill@...	2 years ago
Summary	Add a top level global testsuite configuration file (.tcfg) and a 'user-input' test state.					

Description: Adding a top level testsuite configuration file lets us specify tests that have a common test state across all BSPs.

Adding the test state 'user-input' clearly tags the test as needing user input and test result tools can correctly determine the test result. The current practice of passing a test needing user input is actually hiding the real result of the test.

#2949	3 years ago	wontfix	tool/rsb	Sebastian Huber		2 years ago
Summary	Questionable patch organization in RTEMS tools and RSB					

Patches for RTEMS tools are available via the RTEMS tools repository:

<https://git.rtems.org/rtems-tools/tree/tools>

They are organized using subdirectories.



- source for these methods is merged into newlib
- methods are documented in newlib
- RSB is updated appropriately
- tests are added to RTEMS
- RTEMS POSIX Compliance spreadsheet (<https://goo.gl/AXrnxO>) is updated

#2969	3 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	qoriq BSPs depend on mkimage which is not always available					
Description	The following BSPs do not successfully build on the master because they use UBoot's mkimage which is not part of the standard RTEMS tools. qoriq_core_0 qoriq_core_1 qoriq_p1020rdb					
#2976	3 years ago	fixed	unspecified	Joel Sherrill	Chris Johns	2 years ago
Summary	warnings in rtems-debugger-server.c					
Description	This should be present on any ARM or x86 build. cpukit/libdebugger/rtems-debugger-server.c:393:1: warning: control reaches end of non-void function [-Wreturn-type] cpukit/libdebugger/rtems-debugger-server.c:405:1: warning: control reaches end of non-void function [-Wreturn-type]					
#2977	3 years ago	fixed	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	warnings in Dhrystone Benchmark					
Description	The following warnings show up across the various BSPs for the dhrystone benchmark:  grep "dhrystone.*warning" log/*  log/epiphany-epiphany_sim.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:286:1: warning: control reaches end of non-void function [-Wreturn-type] log/powerpc-haleakala.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:244:3: warning: 'Int_2_Loc' may be used uninitialized in this function [-Wmaybe-uninitialized] log/powerpc-t32mppc.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:244:3: warning: 'Int_2_Loc' may be used uninitialized in this function [-Wmaybe-uninitialized] log/sparc64-niagara.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:220:40: warning: cast from pointer to integer of different size [-Wpointer-to-int-cast] log/sparc64-niagara.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:231:40: warning: cast from pointer to integer of different size [-Wpointer-to-int-cast] log/sparc64-usiii.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:220:40: warning: cast from pointer to integer of different size [-Wpointer-to-int-cast] log/sparc64-usiii.log:../../../../rtems/c/src/../../../../testsuites/benchmarks/dhrystone/dhry_1.c:231:40: warning: cast from pointer to integer of different size [-Wpointer-to-int-cast]					
#2980	3 years ago	workforme	unspecified	Joel Sherrill	Sebastian Huber	2 years ago
Summary	pc586-sse does not compile fsjffs2gc01					
Description	After the tool upgrade, the pc586-sse BSP does not compile the test fsjffs2gc01:  i386-rtems4.12-gcc -B../../../../pc586-sse/lib/ -specs bsp_specs -qrtems -DHAVE_CONFIG_H -I../../../../rtems/c/src/../../../../testsuites/fstests/fsjffs2gc01 -I../../../../rtems/c/src/../../../../testsuites/fstests/support -I../../../../rtems/c/src/../../../../testsuites/fstests/jffs2_support -I../../../../rtems/c/src/../../../../testsuites/fstests/./support/include -I../../../../rtems/c/src/../../../../testsuites/fstests/./psxtests/include -mtune=pentium -march=pentium -msse2 -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT fstest_support.o -MD -MP -MF .deps/fstest_support.Tpo -c -o fstest_support.o test -f'../../../../support/fstest_support.c'    echo '../../../../rtems/c/src/../../../../testsuites/fstests/fsjffs2gc01/./support/fstest_support.c In file included from ../../../../../../rtems/c/src/../../../../testsuites/fstests/fsjffs2gc01/./support/fstest_support.c:30:0: ../../../../../../rtems/c/src/../../../../testsuites/fstests/./psxtests/include/pmacros.h:99:2: error: #error "unsupported size of off_t"  #error "unsupported size of off_t"  gmake[6]: * [fstest_support.o] Error 1 gmake[6]: Leaving directory `./data/home/joel/rtems-work/rtems-testing/rtems/build-i386-pc586-sse-rtems/i386-rtems4.12/c/pc586-sse/testsuites/fstests/fsjffs2gc01`					
#2981	3 years ago	fixed	unspecified	Joel Sherrill	Chris Johns	2 years ago
Summary	testdata excludes on included tcfg files does not work					
Description	It looks like the includes do not always work for .tcfg files. So far these BSPs do not appear to honor the excludes in an included file: log/m32c-m32csim.log log/mips-hurricane.log log/mips-rbtx4925.log log/mips-rbtx4938.log log/moxie-moxiesim.log  mips and moxie are dl tests.					
#2982	3 years ago	invalid	tool/gcc	Chris Johns	Sebastian Huber	2 years ago
Summary	LibBSD broken with GCC+RTEMS changes					
Description	The RTEMS Header test is libbsd is broken. I assume including <rtems.h> and no other is still a requirement. Maybe we need a test for this.  The example code is:  <pre>\$ cat t.c /* /opt/work/rtems/4.12/bin/arm-rtems4.12-gcc -qrtems -B/opt/work/si/rtems/4.12/arm-rtems4.12/lib -B/opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/ --specs bsp_specs -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a9 -ffunction-sections -fdata-sections -DHAVE_RTEMS_SCORE_CPUOPTS_H=1 t.c -c -o t.o */ #include &lt;rtems.h&gt; int main(int argc, char **argv) { (void)argv; (void)argv; return 0; } \$ /opt/work/rtems/4.12/bin/arm-rtems4.12-gcc -qrtems -B/opt/work/si/rtems/4.12/arm-rtems4.12/lib -B/opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/ --specs bsp_specs -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a9 -ffunction-sections -fdata-sections -DHAVE_RTEMS_SCORE_CPUOPTS_H=1 t.c -c -o t.o In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/signal.h:6:0, from /opt/work/rtems/4.12/arm-rtems4.12/include/time.h:178, from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/time.h:268, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h:43, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/thread.h:36, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/heap.h:22, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/types.h:26, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:31, from t.c:7: /opt/work/rtems/4.12/arm-rtems4.12/include/sys/signal.h:53:3: error: unknown type name 'pthread_attr_t' pthread_attr_t *sigev_notify_attributes; /* Notification Attributes */ ^ In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/string.h:10:0, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/defs.h:49, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/types.h:23, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/cpu.h:32, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/system.h:23, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:29, from t.c:7: /opt/work/rtems/4.12/arm-rtems4.12/include/sys/signal.h:202:5: error: unknown type name 'pthread_t' int _EXFUN(pthread_kill, (pthread_t thread, int sig)); ^ In file included from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/config.h:25:0, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/config.h:57, from /opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:33, from t.c:7:</pre>					

Descripti  
on

```

/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/tasks.h:425:3: error: unknown type name 'cpu_set_t'
cpu_set_t
^~~~~~
/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/tasks.h:458:9: error: unknown type name 'cpu_set_t'
const cpu_set_t *cpuset
^~~~~~
/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/tasks.h:581:3: error: unknown type name 'cpu_set_t'
cpu_set_t *cpuset
^~~~~~
$ cat t.cpp
/*
/opt/work/rtems/4.12/bin/arm-rtems4.12-g++ -qrtems -B/opt/work/rtems/4.12/arm-rtems4.12/lib -B/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/ --specs
bsp_specs -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a9 -ffunction-sections -fdata-sections -DHAVE RTEMS_SCORE_CPUOPTS_H=1 t.cpp -c -o
t.o

*/

#include <rtems.h>

int main(int argc, char **argv) {
    (void)argv; (void)argv;
    return 0;
}
$ /opt/work/rtems/4.12/bin/arm-rtems4.12-g++ -qrtems -B/opt/work/rtems/4.12/arm-rtems4.12/lib -B/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/ --specs
bsp_specs -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a9 -ffunction-sections -fdata-sections -DHAVE RTEMS_SCORE_CPUOPTS_H=1 t.cpp -c -o
t.o
In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/signal.h:6:0,
from /opt/work/rtems/4.12/arm-rtems4.12/include/time.h:178,
from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/time.h:268,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/timestamp.h:43,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/thread.h:36,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/heap.h:22,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/types.h:26,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:31,
from t.cpp:7:
/opt/work/rtems/4.12/arm-rtems4.12/include/sys/signal.h:53:3: error: 'pthread_attr_t' does not name a type
pthread_attr_t *sigev_notify_attributes; /* Notification Attributes */
^~~~~~
In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/string.h:10:0,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/defs.h:49,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/types.h:23,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/score/cpu.h:32,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/system.h:23,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:29,
from t.cpp:7:
/opt/work/rtems/4.12/arm-rtems4.12/include/sys/signal.h:202:5: error: 'pthread_t' was not declared in this scope
int _EXFUN(pthread_kill, (pthread_t thread, int sig));
^
/opt/work/rtems/4.12/arm-rtems4.12/include/sys/signal.h:202:5: error: expected primary-expression before 'int'
int _EXFUN(pthread_kill, (pthread_t thread, int sig));
^
/opt/work/rtems/4.12/arm-rtems4.12/include/sys/signal.h:202:5: error: expression list treated as compound expression in initializer [-fpermissive]
int _EXFUN(pthread_kill, (pthread_t thread, int sig));
^
In file included from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/config.h:25:0,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/config.h:57,
from /opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems.h:33,
from t.cpp:7:
/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/tasks.h:425:3: error: 'cpu_set_t' has not been declared
cpu_set_t
^~~~~~
/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/tasks.h:458:9: error: 'cpu_set_t' does not name a type
const cpu_set_t *cpuset
^~~~~~
/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib/include/rtems/rtems/tasks.h:581:3: error: 'cpu_set_t' has not been declared
cpu_set_t *cpuset
^~~~~~

```

Note: The header test in libbsd is currently using C++ and I am not sure why.

#2983	3 years ago	fixed	unspecified	Joel Sherrill	Joel Sherrill <joel@...>	2 years ago
Summary	Create <rtems/inttypes.h> to consolidate extensions to <inttypes.h>					

Per discussion at <https://lists.rtems.org/pipermail/devel/2017-April/017483.html>, create <rtems/inttypes.h> to consolidate extensions to the C99 <inttypes.h> file. A quick search shows that there are the following set of defines which could be consolidated as a starting point. Then these are available to address other printf() format warnings.

```

$ grep -r "#define PRI" . | grep -v PRIORITY | grep -v PRINT ./cpukit/libmisc/shell/main_time.c:#define PRIldtime_t PRId64 ./cpukit/libmisc/shell/main_time.c:#define PRIldtime_t PRId32
./cpukit/libmisc/uuid/gen_uuid.c:#define PRIltime_t PRlu64 ./cpukit/libmisc/uuid/gen_uuid.c:#define PRIltime_t PRlu32 ./cpukit/libmisc/rti-shell.c:#define PRIldoff_t PRld32 ./cpukit/libmisc/rti-
shell.c:#define PRIldoff_t PRld64 ./cpukit/libmisc/src/nfsclient/src/dirutils.c:#define PRIlmode_t PRlo64 ./cpukit/libmisc/src/nfsclient/src/dirutils.c:#define PRIlmode_t PRlo32
./cpukit/libmisc/src/nfsclient/src/dirutils.c:#define PRIldoff_t PRlo64 ./cpukit/libmisc/src/nfsclient/src/dirutils.c:#define PRIldoff_t PRlo32 ./cpukit/libmisc/src/rfs/rtems-rfs-dir.c:#define PRIlooff_t
PRlo64 ./cpukit/libmisc/src/rfs/rtems-rfs-dir.c:#define PRIlooff_t PRlo32 ./cpukit/libmisc/src/rfs/rtems-rfs-file.c:#define PRIldoff_t PRld64 ./cpukit/libmisc/src/rfs/rtems-rfs-rtems-
file.c:#define PRIldoff_t PRld32 ./cpukit/libmisc/src/rfs/rtems-rfs-rtems.c:#define PRIlmode_t PRlo64 ./cpukit/libmisc/src/rfs/rtems-rfs-rtems.c:#define PRIlmode_t PRlo32
./testsuites/psxtests/include/pmacros.h:#define PRIldoff_t PRlo64 ./testsuites/psxtests/include/pmacros.h:#define PRIldoff_t PRlo32 ./testsuites/psxtests/include/pmacros.h:#define
PRIxblksize_t PRlx64 ./testsuites/psxtests/include/pmacros.h:#define PRIxblksize_t PRlx32 ./testsuites/psxtests/include/pmacros.h:#define PRIxblksize_t "lx"
./testsuites/psxtests/include/pmacros.h:#define PRIxblkcnt_t PRlx64 ./testsuites/psxtests/include/pmacros.h:#define PRIxblkcnt_t PRlx32
./testsuites/psxtests/include/pmacros.h:#define PRIxblkcnt_t "lx" ./testsuites/libtests/termios01/init.c:#define PRIldrtems_termios_baud_t PRld32
./testsuites/support/include/pritime.h:#define PRIldtime_t PRld64 ./testsuites/support/include/pritime.h:#define PRIldtime_t PRld32 ./testsuites/support/include/tmacros.h:#define
PRIxrtms_id PRlx16 ./testsuites/support/include/tmacros.h:#define PRIxrtms_id PRlx32 ./testsuites/support/include/tmacros.h:#define PRIldPriority_Control PRlu64
./testsuites/support/include/tmacros.h:#define PRIxPriority_Control PRlx64 ./testsuites/support/include/tmacros.h:#define PRIldrtems_task_priority PRlu32
./testsuites/support/include/tmacros.h:#define PRIxrtms_task_priority PRlx32 ./testsuites/support/include/tmacros.h:#define PRIldWatchdog_Interval PRlu32
./testsuites/psxtests/include/pmacros.h:#define PRIldrtems_interval PRldWatchdog_Interval ./testsuites/support/include/tmacros.h:#define PRIldrtems_entry_numeric_type PRluPTR
./testsuites/support/include/tmacros.h:#define PRIldrtems_task_argument PRldThread_Entry_numeric_type ./testsuites/support/include/tmacros.h:#define PRIxrtms_event_set PRlx32
./testsuites/support/include/tmacros.h:#define PRIxrtms_thread_t PRlx32 ./testsuites/support/include/tmacros.h:#define PRIxrtms_signal_set PRlx32
./testsuites/support/include/tmacros.h:#define PRIxrtms "lx" ./testsuites/support/include/primode.h:#define PRIlmode_t PRlo64 ./testsuites/support/include/primode.h:#define
PRIlmode_t PRlo32 ./testsuites/sptests/sp21/init.c:#define PRIurtems_device_major_number PRlu32 ./testsuites/sptests/sp08/init.c:#define PRIxModes_Control PRlx32
./testsuites/sptests/sp08/init.c:#define PRIxrtms_mode PRlxModes_Control ./testsuites/sptests/sp47/init.c:#define PRIxModes_Control PRlx32 ./testsuites/sptests/sp47/init.c:#define
PRIxrtms_mode PRlxModes_Control

```

#2984	3 years ago	fixed	unspecified	Chris Johns	Amar Takhar	2 years ago
Summary	Changing Trac milestone page fails.					

Changing the default milestone is timing out. It has worked before. The error is:

Gateway Timeout

The gateway did not receive a timely response from the upstream server or application.

#2990	3 years ago	fixed	tool/rsb	Worth Burruss	Chris Johns	17 months ago
-------	-------------	-------	----------	---------------	-------------	---------------



#2993	3 years ago	fixed	score	Chris Johns	joel.sherrill@...	2 years ago
Summary	SMP assert in _Thread_Executing in libdebugger					

The target code in libdebugger has support to recover from exceptions related to invalid memory accesses. GDB may request the server access memory on the target that results in an exception. The exception occurs on the server's remote connection thread and the server needs to recover and return and error to GDB.

Running the debugger01 test with an SMP build of RTEMS and libbsd for `xilinx_zedboard` and issuing `bt` in GDB results in:

```

*** LIBBSD DEBUGGER 1 TEST ***
[144/1950]
shell:cannot set terminal attributes(/dev/console)

RTEMS Shell on /devn/excounss0o:l e<.R TUEsMeS 'Nheexlups' dteov ilcies>t
ccogmemma0n:d s<.C
adence CGEM Gigabit Ethernet Interface> on nexus0
miibus0: <MII bus> on cgem0
[/] # e1000phy0: <Marvell 88E1512 Gigabit PHY> PHY 0 on miibus0
e1000phy0: none, 10baseT, 10baseT-FDX, 100baseTX, 100baseTX-FDX, 1000baseT-FDX, 1000baseT-FDX-master, auto
cgem0: Ethernet address: fa:69:35:9e:04:2f
zy7_sicr0: <Zynq-7000 sicr block> on nexus0
[zone: udpcb] kern.ipc.maxsockets limit reached
notice: cgem0: link state changed to DOWN
add host 10.10.5.1: gateway cgem0
add net default: gateway 10.10.5.1
rtems-db: remote running
rtems-db: tcp remote: listing on port: 1122
notice: cgem0: link state changed to UP

rtems-db: tcp remote: connect host: 10.10.5.2
rtems-db: arm debug: (v3.0) ARMv7 [v7, all CP14 registers] breakpoints:5 watchpoints:3
assertion "cpu_self->thread_dispatch_disable_level != 0 || _ISR_Get_level() != 0" failed: file "../..../cpukit/../../xilinx_zynq_zedboard/lib/include/rtems/score/percpu.h", line 630,
function: _Per_CPU_Get
    
```

If I enable `TARGET_DEBUG` in libdebugger and apply the attached patch I can create the assert with `DIE_ON_ASSERT` set to `1`. The output is:

```

rtems-db: tcp remote: connect host: 10.10.5.2
rtems-db: arm debug: (v3.0) ARMv7 [v7, all CP14 registers] breakpoints:5 watchpoints:3
[] frame = 005664EC sig=1 vector=4 ifsr=00000000 pra=0024173A
[] R0 = 00000158 R1 = 00000004 R2 = 00000001 R3 = 0041AB64
[] R4 = 00000158 R5 = 00000004 R6 = 00000000 R7 = 005606A4
[] R8 = 00000016 R9 = 00000001 R10 = 00000006 R11 = 0041AB64
[] R12 = 00560658 SP = 00566540 LR = 0000FFD PC = 00241736
[] CPSR = 08010173 ----Q--A-FT GE:0 IT:01 M:13 SVC
[] target exception: 0 0 0
assertion "cpu_self->thread_dispatch_disable_level != 0 || _ISR_Get_level() != 0" failed: file "../..../cpukit/../../xilinx_zynq_zedboard/lib/include/rtems/score/percpu.h", line 630,
function: _Per_CPU_Get
    
```

and set to `{{0}}`:

```

rtems-db: tcp remote: connect host: 10.10.5.2
rtems-db: arm debug: (v3.0) ARMv7 [v7, all CP14 registers] breakpoints:5 watchpoints:3
[] frame = 005664EC sig=1 vector=4 ifsr=00000000 pra=0024173A
[] R0 = 00000158 R1 = 00000004 R2 = 00000001 R3 = 0041AB64
[] R4 = 00000158 R5 = 00000004 R6 = 00000000 R7 = 005606A4
[] R8 = 00000016 R9 = 00000001 R10 = 00000006 R11 = 0041AB64
[] R12 = 00560658 SP = 00566540 LR = 0000FFD PC = 00241736
[] CPSR = 08010173 ----Q--A-FT GE:0 IT:01 M:13 SVC
[] target exception: 0 0 0
[] tid:0A01000A: thread:0041F5B0 frame:005664EC
[] server access fault
[] frame = 005664EC sig=1 vector=4 ifsr=00000000 pra=0024173A
[] R0 = 00000158 R1 = 00000004 R2 = 00000001 R3 = 0041AB64
[] R4 = 00000158 R5 = 00000004 R6 = 00000000 R7 = 005606A4
[] R8 = 00000016 R9 = 00000001 R10 = 00000006 R11 = 0041AB64
[] R12 = 00560658 SP = 00566540 LR = 0000FFD PC = 00241736
[] CPSR = 08010173 ----Q--A-FT GE:0 IT:01 M:13 SVC
[] target exception: 0 0 0
[] tid:0A01000A: thread:0041F5B0 frame:005664EC
[] server access fault
    
```

The following lines first two values are `cpu_self->thread_dispatch_disable_level` and `_ISR_Get_level()` which are both `0` so I cannot see a reason the assert is happening:

```

[] target exception: 0 0 0
    
```

#2994	3 years ago	fixed	unspecified	Joel Sherrill	Chris Johns	2 years ago
Summary	tar01 XZ error					

This shows up on erc32 and psim.

```

/dest3/home/test_script: mode: 0755 want: 0755
===== /dest3/symlink ===== (0)This is a test of loading an RTEMS filesystem from an initial tar image.
Untaring chunks from txz - XZ file is corrupt (data) ../..../rtems/c/src/../../testsuites/libtests/tar01/init.c: 272 status == UNTAR_SUCCESSFUL
    
```

#2995	3 years ago	fixed	tool/rsb	Hassan Karim	joel.sherrill@...	2 years ago
Summary	Missing bsets					

When I went to rebuild based on 4.12, I cloned from github. I am no longer getting all of the b-sets that I was expecting. Specifically, 4.12/rtems-sparc

Chris Johns said to submit it as a bug. It must have happened within the last couple of weeks. As my scripts that automated these tasks were working as of around 3/1/2017

```

git clone git://git.rtems.org/rtems-source-builder.git $SETBLDRSCRIPTDIR/sb-set-builder --list-bsets

RTEMS Source Builder - Set Builder, 4.12 (2074bd1168ee) Examining: config Examining: ../rtems/src/rtems-source-builder/source-builder/config Examining: ../rtems/src/rtems-source-builder/bare/config devel/autotools-base.bset devel/autotools-internal.bset devel/autotools.bset devel/dtc.bset devel/libtool.bset devel/libusb.bset devel/or1ksim.bset devel/qemu.bset gnu-tools-4.6.bset gnu-tools-4.8.2.bset lang/gcc491.bset
    
```

#2997	3 years ago	fixed	score	Chris Johns	Chris Johns	2 years ago
Summary	Monitor config command does not handle unlimited objects.					

Running the console's `config` command with unlimited objects gives:

```

[/] # config
INITIAL (startup) Configuration Info
-----
WORKSPACE start: 0x800f0173; size: 0x374c8
TIME usec/tick: 10000; tick/timeslice: 50; tick/sec: 100
MAXIMUMS tasks: -2147483614; timers: -2147483616; sems: -2147483609; que's: -2147483616; ext's: 1
partitions: -2147483616; regions: -2147483616; ports: -2147483616; periods: -2147483616
    
```

<b>#2999</b>	3 years ago	wontfix	tool/rsb	Joel Sherrill	Chris Johns	2 years ago
Summary	sb-check on Cygwin					
Description	<p>It looks like there are two issues in windows.py</p> <ul style="list-style-type: none"> <li>Probes for programs like bison and flex as required.</li> <li>tar - bsdtar must be on mingw. It doesn't appear to exist on cygwin.</li> </ul> <p>I think the fix is pretty simple code-wise but I wanted to get some feedback on why there were a lot more required programs in this file than on other OS.py files.</p>					
<b>#3000</b>	3 years ago	fixed	score	Chris Johns	Joel Sherrill	14 months ago
Summary	Setting interrupt level in the mode arg on SMP returns RTEMS_UNSATISFIED					
Description	<p>If for any reason a user sets the interrupt level in the mode on an SMP build the error <code>RTEMS_UNSATISFIED</code> is returned. The documentation indicates this is a lack of stack and this confusing.</p> <p>The reason this happens is the SMP check for an interrupt level being set is in the score's <code>_Thread_Initialize</code>. I propose that and <code>is_preemptible</code> check be converted to an <code>assert</code> and checks be added to the Classic API to catch these errors and report suitable error codes.</p> <p>There is no meaningful error code available without abusing an existing one so I propose adding <code>RTEMS_INVALID_MODE</code>.</p>					
<b>#3001</b>	3 years ago	fixed	score	Chris Johns	Sebastian Huber	2 years ago
Summary	SMP build of RTEMS Testsuite does not set <code>CONFIGURE_MAXIMUM_PROCESSORS</code>					
Description	<p>The default setting for <code>CONFIGURE_MAXIMUM_PROCESSORS</code> is <code>1</code> and this means <code>rtems_configuration_is_smp_enabled()</code> returns <code>false</code>. Only the <code>smptests</code> set the maximum processor count to <code>CPU_COUNT</code> and therefore run in SMP mode.</p> <p>If SMP is not running in an SMP build when running the tests are the tests really reporting a true indication of the of the system?</p> <p>I would expect we have the API tests, <code>libtests</code> and <code>fstests</code> running with SMP enabled in an SMP build.</p>					
<b>#3003</b>	3 years ago	fixed	fs/fat	munster	Sebastian Huber	2 years ago
Summary	FAT does not support clusters bigger than 32K					
Description	<p>When used with 64KiB clusters, the FAT driver will loop forever in <code>cpukit/libfs/src/dosfs/fat.c</code>, line 580. This happens because <code>struct fat_vol_s</code> declares bytes per cluster variable as <code>uint16_t bpc</code>, whereas it can be as big as 256KiB.</p> <p>Here is a link for Linux FAT driver which doesn't make any assumption about cluster size: <a href="http://lxr.free-electrons.com/source/fs/fat/inode.c?v=2.6.24#L1262">http://lxr.free-electrons.com/source/fs/fat/inode.c?v=2.6.24#L1262</a></p>					
<b>#3006</b>	3 years ago	fixed	arch/sparc	Chris Johns	Daniel Hellstrom	2 years ago
Summary	SPARC LEON3 BSP SMP build is broken.					
Description	<p>The <code>rtems-bsp-builder</code> failure output is:</p> <pre>2 smp-debug sparc/leon3 build: configure: /opt/work/chris/rtems/kernel/rtems.git/configure --target\ =sparc-rtems4.12 --enable-rtemsbsp=leon3 --prefix=/opt/rtems/4.12\ --enable-debug --enable-smp --enable-tests error: c/src/lib/libbsp/sparc/shared/spw/grspw_pkt.c:61:2 error: #error SMP mode not compatible with these interrupt lock primitives</pre> <p>The BSP builder command line is:</p> <pre>RTEMS Tools Project - RTEMS Kernel BSP Builder, 4.12.not_released command: /opt/work/rtems/4.12/bin/rtems-bsp-builder --rtems-\ tools=/build/rtems/tools/4.12\ --rtems=/opt/work/chris/rtems/kernel/rtems.git --build=smp-debug\ --log=x</pre>					
<b>#3007</b>	3 years ago	fixed	arch/arm	munster	joel.sherrill@...	2 years ago
Summary	ARM caching issues					
Description	<p>There are two problems with the caching on ARM:</p> <ul style="list-style-type: none"> <li>In cases where the buffer is not aligned to line boundary at the beginning or the end, the invalidate operation would lose modifications done on the adjacent data. This applies to both L1 and L2 caches.</li> <li>The L2C-310 cache management operations use excessive locking. According to <code>manual</code>, the used operations (Clean Line by PA, Clean and Invalidate Line by PA, Cache Sync) are atomic and do not require locking.</li> </ul> <p>I have attached the proposed patch.</p>					
<b>#3008</b>	3 years ago	fixed	doc	Hassan Karim	chrisj@...	2 years ago
Summary	missing pax causes install failures					
Description	<p>I have tried to install <code>sparc-bsp=erc32</code> on 4 different builds. 3 failed, and 1 flawlessly installed. The others all seem to fail somewhere during make install of test suites. Each reports one missing config problem or another.</p> <p>I believe the problem resulted in a missing package, <code>pax</code> &amp; <code>libbsd-dev</code> on Ubuntu 12.04.5 LTS (GNU/Linux 3.2.0-126-virtual x86_64)</p> <p>I hadn't seen this exact problem because I normally update &amp; upgrade as soon as I get a new image. Pressed for time, I skipped it. So, I am not sure if we need to update the documentation to directly include <code>pax</code>, since it is directly called in <code>configure</code> and breaks if not present.</p> <p><a href="https://docs.rtems.org/rsb/#_host_setups">https://docs.rtems.org/rsb/#_host_setups</a> Under this section, 11.1.5. Ubuntu</p> <p>Add <code>pax</code> to this line <code>\$ sudo apt-get build-dep binutils gcc g++ gdb unzip git python2.7-dev pax</code></p>					
<b>#3009</b>	3 years ago	wontfix	tool/website	Chris Johns	joel.sherrill@...	2 years ago
Summary	Provide invalid link handler for docs.rtems.org so old docs can be removed.					
Description	<p>The docs.rtems.org website has lots of old docs which need to be removed.</p> <p>See <a href="#">#3008</a> for a reference to old documentation.</p>					
<b>#3010</b>	3 years ago	fixed	unspecified	David Binderman	Gedare Bloom <gedare@...>	2 years ago
Summary	<code>src/cpukit/posix/src/mmap.c:189</code> : (style) Suspicious condition					
Description	<p><code>src/cpukit/posix/src/mmap.c:189</code>: (style) Suspicious condition (bitwise operator + comparison); Clarify expression with parentheses.</p> <p>Source code is</p> <pre>    } else if ( ( flags &amp; MAP_PRIVATE != MAP_PRIVATE ) ) {         Maybe better code     } else if ( ( flags &amp; MAP_PRIVATE ) != MAP_PRIVATE ) {</pre>					
<b>#3011</b>	3 years ago	workforme	arch/arm	Arturo Pérez	Gedare Bloom	2 years ago
Summary	Error compiling <code>xilinx_zynq_zedboard</code> .					
Description	<p>I encountered an error compiling the <code>xilinx_zynq_zedboard</code> BSP. I am using a built of the RSB that I compiled in December. With that built of the RSB I could build this BSP several times until I did a git pull of the RTEMS repo two weeks ago. Today I updated my repos of the RTEMS and RSB sources, I rebuilt the RSB and I tried to build again the <code>xilinx_zynq_zedboard</code> BSP, encountering the same error:</p>					



#3012	3 years ago	fixed	tool/newlib	Sebastian Huber	No rule to make target 'posix/include/sys/mman.h', needed by .../cpukit/.../xilinx_zynq_zedboard/lib/include/sys/mman.h'. Stop.	2 years ago
Summary	Global C++ IO streams are broken (cout, cin, cerr)					
Description	<p>The global C++ IO stream objects are initialized here</p> <p><a href="https://gcc.gnu.org/viewcvs/gcc/trunk/libstdc%2B%2B-v3/src/c%2B%2B98/ios_init.cc?view=markup#185">https://gcc.gnu.org/viewcvs/gcc/trunk/libstdc%2B%2B-v3/src/c%2B%2B98/ios_init.cc?view=markup#185</a></p> <p>via a placement new. The "stdout" etc. is thread-local in Newlib</p> <pre data-bbox="191 246 478 280">#define stdout (_REENT-&gt;_stdout)</pre> <p>Using this for a global object like std::cout is quite broken. Which FILE object should be used instead? Potential fix:</p> <pre data-bbox="191 324 813 716">diff --git a/libstdc++-v3/src/c++98/ios_init.cc b/libstdc++-v3/src/c++98/ios_init.cc index c5bcc83..7470c44 100644 --- a/libstdc++-v3/src/c++98/ios_init.cc +++ b/libstdc++-v3/src/c++98/ios_init.cc @@ -33,6 +33,15 @@ @@@ -33,6 +33,15 @@@ #include &lt;ext/stdio_filebuf.h&gt; #include &lt;ext/stdio_sync_filebuf.h&gt;  +#ifdef __rtems_ +#undef stdout +#undef stdin +#undef stderr +#define stdout (_GLOBAL_REENT-&gt;_stdout) +#define stdin (_GLOBAL_REENT-&gt;_stdout) +#define stderr (_GLOBAL_REENT-&gt;_stdout) +#endif + +namespace __gnu_internal_GLIBCXX_VISIBILITY(hidden) +{ +    using namespace __gnu_cxx; }  diff --git a/newlib/libc/stdio/findfp.c b/newlib/libc/stdio/findfp.c index 83d3dc5..7d50951 100644 --- a/newlib/libc/stdio/findfp.c +++ b/newlib/libc/stdio/findfp.c @@@ -259,6 +259,12 @@@ _DEFUN(_sinit, (s),     _sinit_lock_release (); }  +static void __attribute__((__constructor__(0))) +_global_reent_init(void) +{ +    _sinit (_GLOBAL_REENT); +} + +#ifdef _SINGLE_THREAD_ + +_LOCK_INIT_RECURSIVE(static, _sfp_recursive_mutex);</pre>					

#3013	3 years ago	fixed	tool/website	Nikolay Komashinskiy	Amar Takhar	17 months ago
Summary	ProgrammingError?: (1064, "You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'sid='nikolaykomashinskiy' AND authenticated=1 AND name='force_change_passwd at line 1'")					

Hello, during reset password I had an internal error. This card was automatically generated.

**How to Reproduce**

While doing a POST operation on `/reset_password`, Trac issued an internal error.

*(please provide additional details here)*

Request parameters:

```
{u'__FORM_TOKEN': u'56888d70c5e5799302935f97',
u'email': u'nikolay.komashinskiy@yandex.ru',
u'register_phone': u'',
u'rtems_user_phone': u'',
u'username': u'nikolaykomashinskiy'}
```

User agent: Mozilla/5.0 (X11; Linux x86\_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/57.0.2987.98 Safari/537.36

**System Information**

System information not available

**Enabled Plugins**

Plugin information not available

**Interface Customization**

Interface customization information not available

**Python Traceback**

Description

					<pre>Traceback (most recent call last):   File "/data/src/trac/trac/web/main.py", line 620, in _dispatch_request     dispatcher.dispatch(req)   File "/data/src/trac/trac/web/main.py", line 253, in dispatch     resp = chosen_handler.process_request(req)   File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/web_ui.py", line 168, in process_request     self._do_reset_password(req)   File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/web_ui.py", line 256, in _do_reset_password     self._reset_password(req, username, email)   File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/web_ui.py", line 301, in _reset_password     set_user_attribute(self.env, username, 'force_change_passwd', 1)   File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/model.py", line 509, in set_user_attribute     (value, username, attribute))   File "/data/src/trac/trac/db/util.py", line 128, in execute     cursor.execute(query, params if params is not None else [])   File "/data/src/trac/trac/db/util.py", line 72, in execute     return self.cursor.execute(sql_escape_percent(sql), args)   File "/usr/local/lib/python2.7/site-packages/MySQLdb/cursors.py", line 205, in execute     self.errorhandler(self, exc, value)   File "/usr/local/lib/python2.7/site-packages/MySQLdb/connections.py", line 39, in defaulterrorhandler     raise errorclass, errorvalue</pre>	
#3014	3 years ago	fixed	bsps	phongvanpham	joel.sherrill@...	2 years ago
Summary	interrupt vector in the BSP_INTERRUPT_VECTOR_MMIO register is not connected to the BSP_INTERRUPT_VECTOR_MMIO register.					
Description	Some components (like the MySQL server) are not able to connect to the MySQL server for the right reason. See attached Nikolaykomashinskiy' AND authenticated=1 AND name='force_change_passwd' at line 1")					
#3015	3 years ago	fixed	arch/powerpc	phongvanpham	joel.sherrill@...	2 years ago
Summary	Add support for IBM PPC 750 chip					
Description	Currently MPC750 chip is supported. However, PPC750 (from IBM) is very close to MPC750 except minor differences. Enclosed is the delta to support PPC750.					
#3016	3 years ago	fixed	bsps	phongvanpham	joel.sherrill@...	2 years ago
Summary	missing a couple register names + a #ifndef ASM around serial.h inclusion					
Description	In rtems\csrc\libchip\serial\ns16550_p.h, need to add a couple register and #ifndef around serial.h					
#3017	3 years ago	workforme	score	phongvanpham	joel.sherrill@...	2 years ago
Summary	improvement in pci.h					
Description	<p>In pci.h, there are references to BSP_pci_configuration data structure which is in pci.c. However, in this file, there are also references to detect_host_bridge () in detect_raven_bridge.c. For folks that are just interested in pci_read_config_dword() + its brothers, all they need is to include pci.h and content for where BSP_pci_configuration is defined. The rest of the stuff in pci.c should be separate. Or in another word, data structures and #defines involving with BSP_pci_configuration needs to be in separate files rather all stuffed in pci.c</p> <p>I currently do not need this functionality for my BSP (nor do I able to test it), so I cannot modify code and submit. It is best someone who can test the code to make the code change. Or else, just shelf it under the table and/or close this ticket.</p>					
#3018	3 years ago	fixed	tool/rsb	phongvanpham	Chris Johns	2 years ago
Summary	RSB cannot compile tool chain in CentOS 7.					
Description	<p>In CentOS 6.8, everything works fine. But in CentOS 7, it does not. Initial investigation (I did a while back around New Year time) looks like later version of texinfo has an issue with autoconf. Enclosed is the email Chris Johns replied but I didn't follow through since I switched to CentOS 6.8 for my work.</p> <p>"Looks to me like the RSB is trying to download autoconf 2.69-1 and from <a href="https://bugs.debian.org/cgi-bin/bugreport.cgi?bug=711297">https://bugs.debian.org/cgi-bin/bugreport.cgi?bug=711297</a></p> <p>Looks like this autoconf version has a bug. I also noticed my autoconf version is 2.69-11; however, from what I am reading, RSB will download its own version independent of what user has."</p> <p>Chris John replies:</p> <p>"I guess a recent texinfo version has exposed the issue. I suggest you get the patch from the link in the bug report, create a patch for rtems-tools.git to add the autoconf patch, then create a patch to the RSB adding the patch to the autoconf build, finally 'git send-email' the patches to devel@... for review."</p>					
#3023	3 years ago	fixed	tool/newlib	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Parameter of CPU_COPY() are in wrong order					
Description	<p>According to the FreeBSD man page we have:</p> <p><a href="https://www.freebsd.org/cgi/man.cgi?query=cpuset&amp;sektion=9&amp;apropos=0&amp;manpath=FreeBSD+11.0-RELEASE+and+Ports">https://www.freebsd.org/cgi/man.cgi?query=cpuset&amp;sektion=9&amp;apropos=0&amp;manpath=FreeBSD+11.0-RELEASE+and+Ports</a></p> <pre>CPU_COPY(cpuset_t *from, cpuset_t *to);</pre> <p>However, in Newlib we have:</p> <pre>static __inline void CPU_COPY( cpu_set_t *dest, const cpu_set_t *src ) {     *dest = *src; }</pre>					
#3025	3 years ago	fixed	unspecified	Chris Johns	joel.sherrill@...	2 years ago
Summary	m32c/m32csm does not build linpack-pc.c					
Description	<p>1 tests m32c/m32csm build:</p> <pre>configure: /opt/work/chris/rtems/kernel/rtems.git/configure --target\ =m32c-rtems4.12 --enable-rtemsbps=m32csm --prefix=/opt/rtems/4.12 --enable-tests</pre> <p>error: testsuites/benchmarks/linpack/linpack-pc.c:253:33: error: storage size of 'a' isn't constant</p> <pre>error: testsuites/benchmarks/linpack/linpack-pc.c:253:21: error: storage size of 'aa' isn't constant</pre>					
#3027	3 years ago	fixed	tool/rsb	Worth Burruss	Chris Johns	2 years ago
Summary	RTEMS source builder fails when building gcc documentation with newer versions of gcc					
Description	Originally discovered with MSYS2 on windows. Building the gcc compiler fails for older versions of gcc (ie 4.8.3) when building bfin and m32c architectures. The gcc maintainers recommend the use of MISSING=teinfo switch during configuration. A possible solution is attached.					
#3032	3 years ago	fixed	tool/newlib	Sebastian Huber	Sebastian Huber	2 years ago
Summary	CPU_NAND_S() implementation is not in line with FreeBSD					
Description	<p>According to the FreeBSD man page we have:</p> <p><a href="https://www.freebsd.org/cgi/man.cgi?query=cpuset&amp;sektion=9&amp;apropos=0&amp;manpath=FreeBSD+11.0-RELEASE+and+Ports">https://www.freebsd.org/cgi/man.cgi?query=cpuset&amp;sektion=9&amp;apropos=0&amp;manpath=FreeBSD+11.0-RELEASE+and+Ports</a></p> <p>The CPU_NAND() macro removes CPUs in src from dst. (It is the cpuset(9) equivalent of the scalar: dst &amp;= ~ src.)</p> <p>However, in Newlib we had:</p>					



```

../gdb-7.12/gdb/common/vec.h:711:18: note: expanded from macro '\
DEF_VEC_FUNC_P'
static inline T *VEC_OP (T,address)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:151:1: note: expanded from here
VEC_tp_t_address
^
../gdb-7.12/gdb/record-btrace.c:2445:1: warning: unused function 'VEC_tp_t_lower_bound' [-Wunused-function]
../gdb-7.12/gdb/common/vec.h:428:20: note: expanded from macro 'DEF_VEC_P'
VEC_T(T);
^
../gdb-7.12/gdb/common/vec.h:717:24: note: expanded from macro '\
DEF_VEC_FUNC_P'
static inline unsigned VEC_OP (T,lower_bound)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:155:1: note: expanded from here
VEC_tp_t_lower_bound
^
../gdb-7.12/gdb/record-btrace.c:2445:1: warning: unused function 'VEC_tp_t_alloc' [-Wunused-function]
../gdb-7.12/gdb/common/vec.h:429:27: note: expanded from macro 'DEF_VEC_P'
DEF_VEC_FUNC_P(T)
^
../gdb-7.12/gdb/common/vec.h:744:23: note: expanded from macro '\
DEF_VEC_ALLOC_FUNC_P'
static inline VEC(T) *VEC_OP (T,alloc)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:166:1: note: expanded from here
VEC_tp_t_alloc
^
../gdb-7.12/gdb/record-btrace.c:2445:1: warning: unused function 'VEC_tp_t_free' [-Wunused-function]
../gdb-7.12/gdb/common/vec.h:429:27: note: expanded from macro 'DEF_VEC_P'
DEF_VEC_FUNC_P(T)
^
../gdb-7.12/gdb/common/vec.h:751:20: note: expanded from macro '\
DEF_VEC_ALLOC_FUNC_P'
static inline void VEC_OP (T,free)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:170:1: note: expanded from here
VEC_tp_t_free
^
../gdb-7.12/gdb/record-btrace.c:2445:1: warning: unused function 'VEC_tp_t_merge' [-Wunused-function]
../gdb-7.12/gdb/common/vec.h:429:27: note: expanded from macro 'DEF_VEC_P'
DEF_VEC_FUNC_P(T)
^
../gdb-7.12/gdb/common/vec.h:784:23: note: expanded from macro '\
DEF_VEC_ALLOC_FUNC_P'
static inline VEC(T) *VEC_OP (T,merge) (VEC(T) *vec1, VEC(T) *vec2)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:187:1: note: expanded from here
VEC_tp_t_merge
^
../gdb-7.12/gdb/record-btrace.c:2445:1: warning: unused function 'VEC_tp_t_safe_grow' [-Wunused-function]
../gdb-7.12/gdb/common/vec.h:429:27: note: expanded from macro 'DEF_VEC_P'
DEF_VEC_FUNC_P(T)
^
../gdb-7.12/gdb/common/vec.h:817:20: note: expanded from macro '\
DEF_VEC_ALLOC_FUNC_P'
static inline void VEC_OP (T,safe_grow)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:205:1: note: expanded from here
VEC_tp_t_safe_grow
^
../gdb-7.12/gdb/record-btrace.c:2445:1: warning: unused function 'VEC_tp_t_safe_insert' [-Wunused-function]
../gdb-7.12/gdb/common/vec.h:429:27: note: expanded from macro 'DEF_VEC_P'
DEF_VEC_FUNC_P(T)
^
../gdb-7.12/gdb/common/vec.h:835:18: note: expanded from macro '\
DEF_VEC_ALLOC_FUNC_P'
static inline T *VEC_OP (T,safe_insert)
^
../gdb-7.12/gdb/common/vec.h:399:22: note: expanded from macro 'VEC_OP'
#define VEC_OP(T,OP) VEC_##T##_##OP
^
<scratch space>:225:1: note: expanded from here
VEC_tp_t_safe_insert
^
2 warnings generated.
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -I/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -l-
-l../gdb-7.12/gdb -l../gdb-7.12/gdb/common -l../gdb-7.12/gdb/config -DLOCALEDIR=""/rtems-source-builder/rtems~/rtems/4.12/share/locale/"" -DHAVE_CONFIG_H -
-l../gdb-7.12/gdb/./include/opcode -l../gdb-7.12/gdb/./opcodes/.. -l../gdb-7.12/gdb/./readline/.. -l../gdb-7.12/gdb/./zlib -l../gdb-7.12/gdb/./bfd -l../gdb-7.12/gdb/./bfd -l../gdb-7.12/gdb/./include -l../libdecnumber -l../gdb-7.12/gdb/./libdecnumber -l../gdb-7.12/gdb/gnuilib/import -lbuild-gnuilib/import -DTUI=1 -I/rtems-source-
builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -
I/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -I/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -Wall -
Wpointer-arith -Wno-unused -Wunused-value -Wunused-function -Wno-switch -Wno-char-subscripts -Wempty-body -Wunused-but-set-parameter -Wunused-but-set-variable -
Wno-sign-compare -Wno-write-strings -Wno-narrowing -Wformat-nonliteral -c -o debug.o -MT debug.o -MMD -MP -MF .deps/debug.Tpo ../gdb-7.12/gdb/debug.c
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -I/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -l-
-l../gdb-7.12/gdb -l../gdb-7.12/gdb/common -l../gdb-7.12/gdb/config -DLOCALEDIR=""/rtems-source-builder/rtems~/rtems/4.12/share/locale/"" -DHAVE_CONFIG_H -
-l../gdb-7.12/gdb/./include/opcode -l../gdb-7.12/gdb/./opcodes/.. -l../gdb-7.12/gdb/./readline/.. -l../gdb-7.12/gdb/./zlib -l../gdb-7.12/gdb/./bfd -l../gdb-7.12/gdb/./bfd -l../gdb-7.12/gdb/./include -l../libdecnumber -l../gdb-7.12/gdb/./libdecnumber -l../gdb-7.12/gdb/gnuilib/import -lbuild-gnuilib/import -DTUI=1 -I/rtems-source-
builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -
I/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -I/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -Wall -

```



```

2 warnings generated.
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -l/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -l-
-././gdb-7.12/gdb -././gdb-7.12/gdb/common -././gdb-7.12/gdb/config -DLOCALEDIR=""/rtems-source-builder/rtems~/rtems/4.12/share/locale"" -DHAVE_CONFIG_H -
-././gdb-7.12/gdb/.include/opcodes -././gdb-7.12/gdb/.opcodes/. -././gdb-7.12/gdb/.readline/. -././gdb-7.12/gdb/.zlib -./bfd -././gdb-7.12/gdb/.bfd -././gdb-
7.12/gdb/.include -./libdecnumber -././gdb-7.12/gdb/.libdecnumber -././gdb-7.12/gdb/gnulib/import -lbuild-gnulib/import -DTUI=1 -l/rtems-source-
builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -
l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -Wall -
Wpointer-arith -Wno-unused -Wunused-value -Wunused-function -Wno-switch -Wno-char-subscripts -Wempty-body -Wunused-but-set-parameter -Wunused-but-set-variable -
Wno-sign-compare -Wno-write-strings -Wno-narrowing -Wformat-nonliteral -c -o compile-loc2c.o -MT compile-loc2c.o -MMD -MP -MF .deps/compile-loc2c.Tpo -././gdb-
7.12/gdb/compile/compile-loc2c.c
clang: warning: treating 'c' input as 'c++' when in C++ mode, this behavior is deprecated
warning: unknown warning option '-Wunused-but-set-parameter'; did you mean '-Wunused-parameter'? [-Wunknown-warning-option]
warning: unknown warning option '-Wunused-but-set-variable'; did you mean '-Wunused-const-variable'? [-Wunknown-warning-option]
2 warnings generated.
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -l/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -l-
-././gdb-7.12/gdb -././gdb-7.12/gdb/common -././gdb-7.12/gdb/config -DLOCALEDIR=""/rtems-source-builder/rtems~/rtems/4.12/share/locale"" -DHAVE_CONFIG_H -
-././gdb-7.12/gdb/.include/opcodes -././gdb-7.12/gdb/.opcodes/. -././gdb-7.12/gdb/.readline/. -././gdb-7.12/gdb/.zlib -./bfd -././gdb-7.12/gdb/.bfd -././gdb-
7.12/gdb/.include -./libdecnumber -././gdb-7.12/gdb/.libdecnumber -././gdb-7.12/gdb/gnulib/import -lbuild-gnulib/import -DTUI=1 -l/rtems-source-
builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -
l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -Wall -
Wpointer-arith -Wno-unused -Wunused-value -Wunused-function -Wno-switch -Wno-char-subscripts -Wempty-body -Wunused-but-set-parameter -Wunused-but-set-variable -
Wno-sign-compare -Wno-write-strings -Wno-narrowing -Wformat-nonliteral -c -o compile-c-support.o -MT compile-c-support.o -MMD -MP -MF .deps/compile-c-support.Tpo
-././gdb-7.12/gdb/compile/compile-c-support.c
clang: warning: treating 'c' input as 'c++' when in C++ mode, this behavior is deprecated
2 warnings generated.
warning: unknown warning option '-Wunused-but-set-parameter'; did you mean '-Wunused-parameter'? [-Wunknown-warning-option]
warning: unknown warning option '-Wunused-but-set-variable'; did you mean '-Wunused-const-variable'? [-Wunknown-warning-option]
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -l/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -l-
-././gdb-7.12/gdb -././gdb-7.12/gdb/common -././gdb-7.12/gdb/config -DLOCALEDIR=""/rtems-source-builder/rtems~/rtems/4.12/share/locale"" -DHAVE_CONFIG_H -
-././gdb-7.12/gdb/.include/opcodes -././gdb-7.12/gdb/.opcodes/. -././gdb-7.12/gdb/.readline/. -././gdb-7.12/gdb/.zlib -./bfd -././gdb-7.12/gdb/.bfd -././gdb-
7.12/gdb/.include -./libdecnumber -././gdb-7.12/gdb/.libdecnumber -././gdb-7.12/gdb/gnulib/import -lbuild-gnulib/import -DTUI=1 -l/rtems-source-
builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -
l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -Wall -
Wpointer-arith -Wno-unused -Wunused-value -Wunused-function -Wno-switch -Wno-char-subscripts -Wempty-body -Wunused-but-set-parameter -Wunused-but-set-variable -
Wno-sign-compare -Wno-write-strings -Wno-narrowing -Wformat-nonliteral -c -o inflow.o -MT inflow.o -MMD -MP -MF .deps/inflow.Tpo -././gdb-7.12/gdb/inflow.c
clang: warning: treating 'c' input as 'c++' when in C++ mode, this behavior is deprecated
2 warnings generated.
././gdb-7.12/gdb/compile/compile-loc2c.c:733:6: warning: variable 'uoffset' is uninitialized when used here [-Wuninitialized]
    uoffset += dwarf2_per_cu_text_offset (per_cu);
    ^~~~~~
././gdb-7.12/gdb/compile/compile-loc2c.c:671:23: note: initialize the variable 'uoffset' to silence this warning
    uint64_t uoffset; reg;
    ^
    = 0
warning: unknown warning option '-Wunused-but-set-parameter'; did you mean '-Wunused-parameter'? [-Wunknown-warning-option]
warning: unknown warning option '-Wunused-but-set-variable'; did you mean '-Wunused-const-variable'? [-Wunknown-warning-option]
2 warnings generated.
2 warnings generated.
17 warnings generated.
2 warnings generated.
3 warnings generated.
2 warnings generated.
99 warnings generated.
Making init.c
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -l/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -l-
-././gdb-7.12/gdb -././gdb-7.12/gdb/common -././gdb-7.12/gdb/config -DLOCALEDIR=""/rtems-source-builder/rtems~/rtems/4.12/share/locale"" -DHAVE_CONFIG_H -
-././gdb-7.12/gdb/.include/opcodes -././gdb-7.12/gdb/.opcodes/. -././gdb-7.12/gdb/.readline/. -././gdb-7.12/gdb/.zlib -./bfd -././gdb-7.12/gdb/.bfd -././gdb-
7.12/gdb/.include -./libdecnumber -././gdb-7.12/gdb/.libdecnumber -././gdb-7.12/gdb/gnulib/import -lbuild-gnulib/import -DTUI=1 -l/rtems-source-
builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -
l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -l/System/Library/Frameworks/Python.framework/Versions/2.7/include/python2.7 -Wall -
Wpointer-arith -Wno-unused -Wunused-value -Wunused-function -Wno-switch -Wno-char-subscripts -Wempty-body -Wunused-but-set-parameter -Wunused-but-set-variable -
Wno-sign-compare -Wno-write-strings -Wno-narrowing -Wformat-nonliteral -c -o init.o -MT init.o -MMD -MP -MF .deps/init.Tpo init.c
clang: warning: treating 'c' input as 'c++' when in C++ mode, this behavior is deprecated
warning: unknown warning option '-Wunused-but-set-parameter'; did you mean '-Wunused-parameter'? [-Wunknown-warning-option]
warning: unknown warning option '-Wunused-but-set-variable'; did you mean '-Wunused-const-variable'? [-Wunknown-warning-option]
2 warnings generated.
rm -f gdb
/usr/bin/c++ -O2 -pipe -fbracket-depth=1024 -l/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/include -g -O2 -
Wi_no_pie -l/rtems-source-builder/rtems/build/tmp/sb-peer/4.12/rtems-powerpc/rtems-source-builder/rtems~/rtems/4.12/lib \
-o gdb gdb.o rs6000-tdep.o ppc-sysv-tdep.o solib-svr4.o ravenscar-thread.o ppc-ravenscar-thread.o ser-base.o ser-unix.o ser-pipe.o ser-tcp.o remote.o dcache.o
tracepoint.o ax-general.o ax-gdb.o remote-fileio.o remote-notif.o ctf.o tracefile.o tracefile-tfile.o remote-sim.o cli-dump.o cli-decode.o cli-script.o cli-cmds.o cli-setshow.o cli-
logging.o cli-interp.o cli-utils.o mi-out.o mi-console.o mi-cmds.o mi-cmd-catch.o mi-cmd-env.o mi-cmd-var.o mi-cmd-break.o mi-cmd-stack.o mi-cmd-file.o mi-cmd-disas.o mi-
symbol-cmds.o mi-cmd-target.o mi-cmd-info.o mi-cmd-interp.o mi-main.o mi-parse.o mi-geotop.o tui-command.o tui-data.o tui-disasm.o tui-file.o tui-hooks.o tui-interp.o tui-io.o tui-
layout.o tui-out.o tui-regs.o tui-source.o tui-stack.o tui-win.o tui-windata.o tui-wingeneral.o tui-winsource.o tui.o python.o py-arch.o py-auto-load.o py-block.o py-bpevent.o py-
breakpoint.o py-cmd.o py-cmd.o py-continueevent.o py-xmethods.o py-event.o py-evtregistry.o py-evt.o py-exitedevent.o py-finishbreakpoint.o py-frame.o py-filter.o py-
function.o py-gdb-readline.o py-inferior.o py-infevents.o py-inftread.o py-lazy-string.o py-linetable.o py-newobjfileevent.o py-objfile.o py-param.o py-prettyprint.o py-
progspace.o py-signalevent.o py-stopevent.o py-symbol.o py-symbtab.o py-threadevent.o py-type.o py-unwind.o py-utils.o py-value.o py-varobj.o guile.o elfread.o stap-probe.o
dtrace-probe.o posix-hdep.o posix-parser.o c-exp.o cp-name-parser.o ada-exp.o jv-exp.o f-exp.o m2-exp.o f-exp.o rust-exp.o version.o annotate.o
addrmap.o auto-load.o auxv.o agent.o bfd-target.o blockframe.o breakpoint.o break-catch-sig.o break-catch-throw.o break-catch-syscall.o findvar.o regcache.o cleanups.o
charset.o continuations.o corelow.o disasm.o dummy-frame.o dfp.o source.o value.o eval.o valops.o valarith.o valprint.o printcmd.o block.o symbtab.o psymtab.o symfile.o
symfile-debug.o symmisc.o linespec.o dictionary.o namespace.o location.o incall.o infcmd.o infrun.o exprrt.o environ.o stack.o tid-parse.o thread.o thread-fsm.o
exceptions.o extension.o filesystem.o filestuff.o inf-child.o inters.o minidebug.o main.o macrotab.o macrocmd.o macroexp.o macroscope.o mi-common.o event-loop.o event-
top.o inf-loop.o completer.o gdbarch.o arch-utils.o gdbtypes.o gdb_bfd.o gdb_obstack.o osabi.o copying.o memcmd.o mem-break.o target.o target-dcache.o parse.o
language.o build-id.o buildsym.o findcmd.o std-regs.o signals-state-save-restore.o signals.o exec.o reverse.o bcache.o objfiles.o observer.o minsyms.o maint.o demangle.o
dbrread.o coffread.o coff-pe-read.o dwarf2read.o mipsread.o corefile.o dwarf2exp.o dwarf2loc.o dwarf2-frame.o dwarf2-frame-tailcall.o ada-lang.o c-lang.o d-
lang.o f-lang.o objc-lang.o ada-tasks.o ada-varobj.o c-varobj.o ui-out.o cli-out.o varobj.o vec.o go-lang.o go-valprint.o go-typeprint.o jv-lang.o jv-valprint.o jv-typeprint.o jv-
varobj.o m2-lang.o opencl-lang.o p-lang.o p-typeprint.o p-valprint.o selftest.o sentinel-frame.o complaints.o typeprint.o ada-typeprint.o c-typeprint.o f-typeprint.o m2-
typeprint.o ada-valprint.o c-valprint.o cp-valprint.o d-valprint.o f-valprint.o m2-valprint.o ser-event.o serial.o mdebugread.o top.o utils.o ui-file.o user-regs.o frame.o frame-
unwind.o doublest.o frame-base.o inline-frame.o gnu-v2-abi.o gnu-v3-abi.o cp-abi.o cp-support.o cp-namespaces.o d-namespaces.o reggroups.o rust-lang.o trad-frame.o tramp-
frame.o solib.o solib-target.o prologue-value.o memory-map.o memrange.o xml-support.o xml-syscall.o xml-utils.o target-descriptions.o target-memory.o xml-tdecs.o xml-
builtin.o inferior.o osdata.o gdb_usleep.o record.o record-full.o gcore.o gdb_vecs.o jit.o progspace.o skip.o probe.o common-utils.o buffer.o ptid.o gdb-dlfcn.o common-agent.o
format.o registry.o btrace.o record-btrace.o waitstatus.o print-utils.o rsp-low.o errors.o common-debug.o debug.o common-exceptions.o btrace-common.o fileio.o common-
regcache.o compile.o compile-c-symbols.o compile-c-types.o compile-object-load.o compile-object-run.o compile-loc2c.o compile-c-support.o inflow.o init.o \
./sim/ppc/libsim.a ./readline/libreadline.a ./opcodes/libopcodes.a ./bfd/libbfd.a -L./zlib -lz ./libiberty/libiberty.a ./libdecnumber/libdecnumber.a -lncurses -lm -
l/System/Library/Frameworks/Python.framework/Versions/2.7/lib/python2.7/config -ldl -framework CoreFoundation -pythont2.7 -u _PyMac_Error
/System/Library/Frameworks/Python.framework/Versions/2.7/Python -lexpat ./libiberty/libiberty.a build-gnulib/import/libgnu.a -liconv
Undefined symbols for architecture x86_64:
" _error", referenced from:
    _sim_io_print filtered in libsim.a(sim_calls.o)
    _sim_load in libsim.a(sim_calls.o)
    _sim_create_inferior in libsim.a(sim_calls.o)
    _sim_io_read_stdin in libsim.a(sim_calls.o)
    _sim_io_write_stdout in libsim.a(sim_calls.o)
    _sim_io_write_stderr in libsim.a(sim_calls.o)
    _sim_io_flush_stdoutoutput in libsim.a(sim_calls.o)
...
(maybe you meant: _device_error, __Z20host_to_fileio_errori, _bfd_get_error_handler, _bfd_default_error_handler, _bfd_set_error_handler,
_bfd_set_error_program_name, __Z28dwarf_reg_to_regnum_or_errorP7gdbarchm, __Z29observer_detach_command_errorP8observer, _sim_io_error,
_deprecated_error_begin_hook, __Z35throw_max_completions_reached_error, __Z25type_name_no_tag_or_errorP4type, __Z12memory_error18target_xfer_status,

```

```

_bfd_error_handler, __Z20annotate_error_beginv, __Z19compile_rx_or_errorP17re_pattern_bufferPKcS2, __Z12catch_errorsPFiPvES_Pc11return_mask,
__Z20memory_error_message18target_xfer_statusP7gdbarchm, __Z11range_errorPKcz, __Z13gdb_xml_errorP14gdb_xml_parserPKcz,
__Z29observer_notify_command_error, __Z14gdb_bfd_errmsg9bfd_errorPpc, __Z29observer_attach_command_errorPFvvE, __Z27gdbpy_print_python_errors_pv, __Z14internal_errorPKcIS0_z,
__Z17get_regcomp_erroriP17re_pattern_buffer, __Z14annotate_errory)
ld: symbol(s) not found for architecture x86_64
clang: error: linker command failed with exit code 1 (use -v to see invocation)
make[2]: *** [gdb] Error 1
make[1]: *** [all-gdb] Error 2
make: *** [all] Error 2
shell cmd failed: /bin/sh -ex /rtems-source-builder/rtems/build/powerpc-rtems4.12-gdb-7.12-x86_64-apple-darwin14.5.0-1/doi
error: building powerpc-rtems4.12-gdb-7.12-x86_64-apple-darwin14.5.0-1

```

#3054	3 years ago	fixed	unspecified	AndiK	Andreas Kölbl <andreas.koelbl@...>	2 years ago
Summary	gdb 7.12.1 on RSB 4.12 branch fail to build on Archlinux					
Description	7.12.1 does not compile with latest guile As already stated here: <a href="https://sourceware.org/bugzilla/show_bug.cgi?id=21104">https://sourceware.org/bugzilla/show_bug.cgi?id=21104</a> GDB in version 7.12.1 fails when trying to compile on Archlinux. GDB uses deprecated functions of libguile which were gone in version 2.2 of libguile. As GDB states in its configure script to support version 2.2 of libguile it fails compiling. Tested with the latest rtems source builder on master.					
#3056	3 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add EDF SMP scheduler					
Description	The current SMP schedulers are all fixed-priority schedulers. Add a job-level fixed priority scheduler (EDF).					
#3057	3 years ago	fixed	tool/gcc	Sebastian Huber	Daniel Hellstrom	2 years ago
Summary	Add a workaround for the LEON3FT store-store errata					
Description	GCC needs support to provide a workaround for the LEON3FT store-store errata, e.g. <a href="https://gcc.gnu.org/ml/gcc-patches/2017-06/msg01577.html">https://gcc.gnu.org/ml/gcc-patches/2017-06/msg01577.html</a> and follow up versions.					
#3059	3 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add a simple processor affinity support to the EDF SMP scheduler					
Description	Add support to the EDF SMP scheduler to honour one-to-one and one-to-all thread processor affinities. Use one ready queue for threads with a one-to-all affinity. Use one ready queue for each of the one-to-one threads for each processor. Since a red-black tree is used for the ready queues, the space overhead of one pointer per ready queue is small.					
#3061	3 years ago	invalid	tool	Chris Johns	chrisj@...	2 years ago
Summary	including 'unistd.h' in C++ does not build.					
Description	<p>Including <a href="#">unistd.h</a> in a C++ program does not compile with the RSB for today:</p> <pre> \$ /opt/work/rtems/4.12/bin/arm-rtems4.12-g++ -B/opt/work/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib -B/opt/work/si/rtems/4.12/arm-rtems4.12/xilinx_zynq_zc706/lib -specs bsp_specs-qrtems -march=armv7-a -mthumb -mfpu=neon -mfloat-abi=hard -mtune=cortex-a9 -g -O2 u.cpp In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/_pthreadtypes.h:24:0,       from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/types.h:239,       from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/unistd.h:12,       from /opt/work/rtems/4.12/arm-rtems4.12/include/unistd.h:4,       from u.cpp:6: /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h: In function 'void CPU_AND_S(size_t, cpu_set_t*, const cpu_set_t*, const cpu_set_t*)': /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:147:3: error: 'BIT_AND2' was not declared in this scope   BIT_AND2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~ /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:147:3: note: suggested alternative: 'BIT_AND'   BIT_AND2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~   BIT_AND /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h: In function 'void CPU_OR_S(size_t, cpu_set_t*, const cpu_set_t*, const cpu_set_t*)': /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:159:3: error: 'BIT_OR2' was not declared in this scope   BIT_OR2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~ /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:159:3: note: suggested alternative: 'BIT_OR'   BIT_OR2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~   BIT_OR /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h: In function 'void CPU_XOR_S(size_t, cpu_set_t*, const cpu_set_t*, const cpu_set_t*)': /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:171:3: error: 'BIT_XOR2' was not declared in this scope   BIT_XOR2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~ /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:171:3: note: suggested alternative: 'BIT_OR'   BIT_XOR2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~   BIT_OR /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h: In function 'void CPU_NAND_S(size_t, cpu_set_t*, const cpu_set_t*, const cpu_set_t*)': /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:183:3: error: 'BIT_NAND2' was not declared in this scope   BIT_NAND2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~ /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:183:3: note: suggested alternative: 'BIT_NAND'   BIT_NAND2(_cpu_set_bits(setsize), destset, srcset1, srcset2);   ^~~~~~   BIT_NAND In file included from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:46:0,       from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/_pthreadtypes.h:24,       from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/types.h:239,       from /opt/work/rtems/4.12/arm-rtems4.12/include/sys/unistd.h:12,       from /opt/work/rtems/4.12/arm-rtems4.12/include/unistd.h:4,       from u.cpp:6: /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h: In function 'int CPU_COUNT_S(size_t, const cpu_set_t*)': /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:194:10: error: '___bitcount' was not declared in this scope   return BIT_COUNT(_cpu_set_bits(setsize), set);          ^ /opt/work/rtems/4.12/arm-rtems4.12/include/sys/cpuset.h:194:10: note: suggested alternative: '___count' </pre>					
#3063	3 years ago	fixed	config	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Make the EDF scheduler the default SMP scheduler					
Description	The EDF SMP scheduler supports simple thread processor affinities (see <a href="#">#3059</a> ) with a small run-time overhead. The current default SMP scheduler lacks support for thread processor affinities at all. The EDF SMP scheduler offers a good feature set for most applications. So, use it by default. Run-time libraries like libgomp, MTAPI, work stealing schedulers, language interpreters (e.g. Erlang virtual machine), etc. use a one-to-one thread processor affinity for example.					
#3069	3 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add rtems_scheduler_ident_by_processor()					

<p>Descripti on</p>	<pre>/**  * @brief Identifies a scheduler by a processor index.  *  * @param[in] cpu_index The processor index.  * @param[out] id The scheduler identifier associated with the processor index.  *  * @retval RTEMS_SUCCESSFUL Successful operation.  * @retval RTEMS_INVALID_ADDRESS The @a id parameter is @c NULL.  * @retval RTEMS_INVALID_NAME Invalid processor index.  * @retval RTEMS_INCORRECT_STATE The processor index is valid, however, this  * processor is not owned by a scheduler.  */</pre>
<p>Summar y</p>	<p><b>#3070</b> 3 years ago fixed rtems Sebastian Huber Sebastian Huber 2 years ago</p> <p>Add rtems_scheduler_ident_by_processor_set()</p>
<p>Descripti on</p>	<pre>/**  * @brief Identifies a scheduler by a processor set.  *  * The scheduler is selected according to the highest numbered online processor  * in the specified processor set.  *  * @param[in] cpuset_size Size of the specified processor set buffer in  * bytes. This value must be positive.  * @param[out] cpuset The processor set to identify the scheduler.  * @param[out] id The scheduler identifier associated with the processor set.  *  * @retval RTEMS_SUCCESSFUL Successful operation.  * @retval RTEMS_INVALID_ADDRESS The @a id parameter is @c NULL.  * @retval RTEMS_INVALID_SIZE Invalid processor set size.  * @retval RTEMS_INVALID_NAME The processor set contains no online processor.  * @retval RTEMS_INCORRECT_STATE The processor set is valid, however, the  * highest numbered online processor in the specified processor set is not  * owned by a scheduler.  */ rtems_status_code rtems_scheduler_ident_by_processor_set(     size_t cpuset_size,     cpu_set_t *cpuset,     rtems_id *id );</pre>
<p>Summar y</p>	<p><b>#3071</b> 3 years ago fixed bsp Sebastian Huber Sebastian Huber 2 years ago</p> <p>Create an interrupt server for every processor in the system</p>
<p>Descripti on</p>	<p>Create an interrupt server for every processor in the system with a one-to-one thread processor affinity. This allows load balancing for interrupt processing. Add support routines to customize the setup after initialization.</p>
<p>Summar y</p>	<p><b>#3072</b> 3 years ago fixed arch/sparc Sebastian Huber Daniel Hellstrom 2 years ago</p> <p>Declaration of global functions in driver source files</p>
<p>Descripti on</p>	<p>There are declarations of global functions in various driver source files, e.g.</p> <p>c/src/lib/libbsp/sparc/shared/drvmgr/ambapp_bus_glib.c c/src/lib/libbsp/sparc/shared/drvmgr/ambapp_bus.c</p> <p>The declaration should move to a header file or a static function should be used.</p>
<p>Summar y</p>	<p><b>#3076</b> 3 years ago fixed unspecified Sebastian Huber Sebastian Huber 2 years ago</p> <p>Test suite failures due to floating point usage</p>
<p>Descripti on</p>	<p>Several tests fail due to an unaccounted use of the floating point unit:</p> <p>BLOCK 6 BLOCK 14 CONSTRUCTOR/DESTRUCTOR CRYPT 1 DUMPBUF 1 FLASHDISK 1 FSBDBPART 1 FSDOSFSFORMAT 1 FSDOSFSNAME 1 FSERROR DOSFS FSERROR JFFS2 FSERROR MOUNTED IMFS FSERROR RFS FSERROR ROOT IMFS FSPERMISSION JFFS2 FSPERMISSION MOUNTED IMFS FSPERMISSION RFS FSPERMISSION ROOT IMFS FSRENAME MOUNTED IMFS FTP 1 libdl (RTL) 1 libdl (RTL) 4 libdl (RTL) 5 MGHSTPD 1 MONITOR 2 MOUSE 1 NETWORKING 1 PSXFILE 1 PSXIMFS 1 PSXIMFS 2 PSXPASSWD 2 PSXPIPE 1 PSXSTAT SMP 1 SMP 3 SMP 8 SMP 9 SMPAFFINITY 1 SMPSCHEMULER 1 SPERROR 1 SPERROR 2 SPERROR 3 SYSCALL 1 TAR 1 TERMIO 3 TERMIO 4 TERMIO 5 TERMIO 6 TERMIO 7</p>
<p>Summar y</p>	<p><b>#3077</b> 3 years ago fixed arch/sparc Sebastian Huber Sebastian Huber 2 years ago</p> <p>SPARC: Add lazy floating point context switching</p>
<p>Descripti on</p>	<p>The uniprocessor floating point context switching is unsafe, e.g. it is possible to silently corrupt the floating point context. The SMP floating point switching is safe, however, it doesn't use a deferred switch. Implement lazy floating point switching in uniprocessor configurations. This fixes test case spcontext01.</p>
<p>Summar y</p>	<p><b>#3079</b> 3 years ago fixed build Sebastian Huber Sebastian Huber &lt;sebastian.huber@...&gt; 2 years ago</p> <p>Ada tests do not build</p>
<p>Descripti on</p>	<p>A "make" in the top level build directory does not build the Ada tests (used to work some weeks ago). A "make" in ./sparc-rtems4.12/c/erc32/ada-tests for example works.</p> <p>The configuration step seems to work:</p> <pre>configure: configuring in ada-tests configure: running /bin/sh '././././././rtems/c/src/ada-tests/configure' '--prefix=/home/joel/rtems-4.11-work/bsp-install' '--host=sparc-rtems4.12' '--build=x86_64-pc-linux-gnu' '--target=sparc-rtems4.12' '--enable-smp' '--disable-profiling' '--disable-multiprocessing' '--enable-rtems-debug' '--enable-cxx' '--disable-rdbg' '--enable-maintainer-mode' '--enable-tests' '--enable-networking' '--enable-posix' '--disable-iron' '--disable-deprecated' '--enable-ada' '--enable-expada' 'SIMSPARC_FAST_IDLE=1' '--with-target-subdir=sparc-rtems4.12' '--exec-prefix=/home/joel/rtems-4.11-work/bsp-install/sparc-rtems4.12' '--includedir=/home/joel/rtems-4.11-work/bsp-install/sparc-rtems4.12/include' 'build_alias=x86_64-pc-linux-gnu' 'host_alias=sparc-rtems4.12' 'target_alias=sparc-rtems4.12' '--with-project-root=../..' '--with-project-top=../..' 'RTEMS_BSP=erc32' 'RTEMS_CPU_MODEL=erc32' 'RTEMS_BSP_FAMILY=erc32' 'CFLAGS=-mcpu=cypress -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs' '--enable-rtems-root=..' '--enable-project-root=../././erc32' '--with-project-top=../././' '--enable-rtemsbsp=erc32' --cache-file=/dev/null --srcdir=.././././rtems/c/src/ada-tests configure: loading site script /usr/share/site/x86_64-unknown-linux-gnu checking for gmake... gmake</pre> <p>However:</p> <pre>gmake[4]: Entering directory '/scratch/git-rtems-testing/rtems/build-sparc-erc32-rtems/sparc-rtems4.12/c/erc32/ada-tests' gmake[4]: Nothing to be done for 'all-am'.</pre>
<p>Summar y</p>	<p><b>#3080</b> 3 years ago fixed arch/sparc Sebastian Huber Sebastian Huber 2 years ago</p> <p>Infinite loop in SPARC rtems_invalidate_multiple_instruction_lines()</p>
<p>Descripti on</p>	<p>A</p> <pre>#define CPU_INSTRUCTION_CACHE_ALIGNMENT 0</pre> <p>is not a good idea in case the default range functions are used.</p>
<p>Summar y</p>	<p><b>#3082</b> 3 years ago fixed arch/powerpc Sebastian Huber Sebastian Huber 13 months ago</p> <p>Add 64-bit support for PowerPC</p>





#3091	3 years ago	fixed	tool	Joel Sherrill	Sebastian Huber	2 years ago
Summary	Core Dump in powerpc-rtems4.12-ld					
Description	This appears to have been introduced by the new binutils. Impacts qemu prep and qemu prep-altivec BSPs. gmake[8]: Entering directory `~/data/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemu prep-rtems/powerpc-rtems4.12/c/qemu prep/lib/libbsp/powerpc/motorola_powerpc/qemu_fakerom' powerpc-rtems4.12-ld -o qemu_fakerom.bin qemu_fakerom.o qemu_fakeres.o --format binary -nostdlib -Ttext 0xffff0000 --section-start=.romentry=0xffffffc gmake[8]: * [qemu_fakerom.bin] Segmentation fault					
#3096	3 years ago	fixed	shell	Chris Johns	Chris Johns	2 years ago
Summary	Shell internal commands should be public.					
Description	A few of the functions held in <code>cpukit/libmisc/shell/internal.h</code> are useful in building system. For example <code>rtems_shell_register_monitor_commands()</code> and <code>rtems_shell_execute_cmd()</code> . The shell commands are important and systems may provide other scripting mechanisms, for example sequences in YAML files. Providing public access lets users know the functions are supported.					
#3098	3 years ago	fixed	admin	Chris Johns	Amar Takhar	17 months ago
Summary	Add new RTEMS repos to github.					
Description	Please add: 1. rtems-docs.git 2. rtems-release.git to our github repos.					
#3099	3 years ago	fixed	unspecified	Chris Johns	Chris Johns	2 years ago
Summary	Add RTEMS FDT wrapper and shell command to libmisc					
Description	Provide a wrapper to the FDT library for use on RTEMS. The wrapper provides a simplified interface suitable for applications. The shell command provides access to registered FDT blobs so a user can search the tree like a file system and optionally read and write from device addresses.					
#3100	3 years ago	fixed	arch/arm	Chris Johns	Chris Johns	2 years ago
Summary	Add Xilinx AXI I2C driver					
Description	Add a Xilinx AXI I2C driver.					
#3101	3 years ago	fixed	score	Chris Johns	Chris Johns	2 years ago
Summary	Add I2C Drivers for LM25066A, TMP112, ADS1113 and ADS1115					
Description	Add drivers for: 1. LM25066A 2. TMP112 3. ADS1113 4. ADS1115					
#3102	3 years ago	fixed	tool	Chris Johns	Chris Johns	2 years ago
Summary	rtems-exeinfo does not decode ARM static constructors.					
Description	The sections for ARM are not the same as other architectures.					
#3103	3 years ago	fixed	tool	Joel Sherrill	chrisj@...	2 years ago
Summary	rtems-tools on CentOS 7 Build Failure					
Description	<p>A build failure for rtems-tools on the master has been reported on CentOS 7. This is my notes as I try to reproduce it.</p> <pre>[joel@localhost rtems-tools]\$ ./waf configure Setting top to : /home/joel/rtems-work/rtems-tools Setting out to : /home/joel/rtems-work/rtems-tools/build Version : 4.12.78bbe4c1a31d (4.12) Checking for program 'python' : /usr/bin/python Checking for python version &gt;= 2.6.6 : 2.7.5 Checking for 'gcc' (C compiler) : /usr/bin/gcc Checking for 'g++' (C++ compiler) : /usr/bin/g++ Checking for header alloca.h : yes Checking for header fcntl.h : yes Checking for header process.h : not found Checking for header stdlib.h : yes Checking for header string.h : yes Checking for header strings.h : yes Checking for header sys/file.h : yes Checking for header sys/stat.h : yes Checking for header sys/time.h : yes Checking for header sys/types.h : yes Checking for header sys/wait.h : yes Checking for headerunistd.h : yes Checking for header vfork.h : not found Checking for function getrusage : yes Checking for program 'm4' : /usr/bin/m4 Checking for header sys/wait.h : yes Checking for function kill : yes Checking for 'gcc' (C compiler) : /usr/bin/gcc Checking for 'g++' (C++ compiler) : /usr/bin/g++ Checking for 'g++' (C++ compiler) : /usr/bin/g++ Checking for function open64 : not found Checking for function stat64 : not found 'configure' finished successfully (0.786s) ===== [joel@localhost rtems-tools]\$ ./waf -j 1 --verbose Waf: Entering directory `~/home/joel/rtems-work/rtems-tools/build' [ 88/151] Compiling rtemstoolkit/rld-process.cpp 11:58:16 runner [/usr/bin/g++, '-pipe', '-g', '-O2', '-Wall', '-Wextra', '-pedantic', '-I./rtemstoolkit', '-I../rtemstoolkit', '-I./rtemstoolkit/elftoolchain/libelf', '-I../rtemstoolkit/elftoolchain/libelf', '-I./rtemstoolkit/elftoolchain/common', '-I./rtemstoolkit/elftoolchain/common', '-I./rtemstoolkit/libiberty', '-I../rtemstoolkit/libiberty', '-DHAVE_CONFIG_H=1', '-DRTEMS_VERSION="4.12"', '-DRTEMS_RELEASE="4.12.78bbe4c1a31d"', '-DFASTLZ_LEVEL=1', '-I./rtemstoolkit/rld-process.cpp', '-c', '-o/home/joel/rtems-work/rtems-tools/build/rtemstoolkit/rld-process.cpp.7.o'] In file included from ../rtemstoolkit/libiberty/libiberty.h:42:0, from ../rtemstoolkit/rld-process.cpp:64: ../rtemstoolkit/libiberty/ansidecl.h:169:64: error: new declaration 'char* basename(const char*)' # define ATTRIBUTE_NONNULL(m) attribute ((nonnull (m))) ../rtemstoolkit/libiberty/libiberty.h:112:64: note: in expansion of macro 'ATTRIBUTE_NONNULL' extern char *basename (const char *) ATTRIBUTE_RETURNS_NONNULL ATTRIBUTE_NONNULL(1); In file included from ../rtemstoolkit/rld-process.cpp:24:0: /usr/include/string.h:599:26: error: ambiguates old declaration 'const char* basename(const char*)' extern "C++" const char *basename (const char *filename); In file included from ../rtemstoolkit/libiberty/libiberty.h:42:0, from ../rtemstoolkit/rld-process.cpp:64: ../rtemstoolkit/libiberty/ansidecl.h:169:64: error: declaration of 'int vasprintf(char, const char*, va_list tag*)' has a different exception specifier # define ATTRIBUTE_NONNULL(m) attribute ((nonnull (m))) ../rtemstoolkit/libiberty/ansidecl.h:198:80: note: in expansion of macro 'ATTRIBUTE_NONNULL' # define ATTRIBUTE_PRINTF(m, n) attribute ((format (printf, m, n))) ATTRIBUTE_NONNULL(m) ../rtemstoolkit/libiberty/libiberty.h:651:55: note: in expansion of macro 'ATTRIBUTE_PRINTF' extern int vasprintf (char , const char *, va_list) ATTRIBUTE_PRINTF(2,0); In file included from ../rtemstoolkit/rld-process.cpp:23:0: /usr/include/stdio.h:399:12: error: from previous declaration 'int vasprintf(char, const char*, va_list tag*) throw ()' extern int vasprintf (char restrict ptr, const char *restrict f, Waf: Leaving directory `~/home/joel/rtems-work/rtems-tools/build' Build failed -&gt; task in 'rld' failed with exit status 1: {task 23048432: cxx rld-process.cpp -&gt; rld-process.cpp.7.o} [/usr/bin/g++, '-pipe', '-g', '-O2', '-Wall', '-Wextra', '-pedantic', '-I./rtemstoolkit', '-I../rtemstoolkit', '-I./rtemstoolkit/elftoolchain/libelf', '-I../rtemstoolkit/elftoolchain/libelf', '-I./rtemstoolkit/elftoolchain/common', '-I../rtemstoolkit/elftoolchain/common', '-I./rtemstoolkit/libiberty', '-I..</pre>					

```
l./rtemstoolkit/libiberty', '-DHAVE_CONFIG_H=1', '-DRTEMS_VERSION="4.12"', '-DRTEMS_RELEASE="4.12.78bbe4c1a31d"', '-DFASTLZ_LEVEL=1',
'./rtemstoolkit/rld-process.cpp', '-c', '-o/home/joel/rtems-work/rtems-tools/build/rtemstoolkit/rld-process.cpp.7.o']
===== Looking down into libiberty.h, I picked on basename()
```

**/\* HAVE\_DECL\_\* is a three-state macro: undefined, 0 or 1. If it is undefined, we haven't run the autoconf check so provide the declaration without arguments. If it is 0, we checked and failed to find the declaration so provide a fully prototyped one. If it is 1, we found it so don't provide any declaration at all. \*/**

**#if !HAVE\_DECL\_BASENAME**

**#if defined (GNU LIBRARY )**

defined (linux) \

defined (FreeBSD)	defined (OpenBSD)	defined (NetBSD) \
defined (CYGWIN)	defined (CYGWIN32)	defined (MINGW32) \
defined (DragonFly)	defined (HAVE_DECL_BASENAME)	

**extern char \*basename (const char \*) ATTRIBUTE\_RETURNS\_NONNULL ATTRIBUTE\_NONNULL(1); #else /\* Do not allow basename to be used if there is no prototype seen. We**

**either need to use the above prototype or have one from autoconf which would result in HAVE\_DECL\_BASENAME being set. \*/**

**#define basename basename\_cannot\_be\_used\_without\_a\_prototype #endif #endif ===== The native CentOS 7 has this definition of basename:**

**# ifndef basename /\* Return the file name within directory of FILENAME. We don't**

**declare the function if the 'basename' macro is available (defined in <libgen.h>) which makes the XPG version of this function available. \*/**

**# ifdef CORRECT\_ISO\_CPP\_STRING\_H\_PROTO extern "C++" char \*basename (char \*filename)**

**THROW asm ("basename") nonnull ((1));**

**extern "C++" const char \*basename (const char \*filename)**

**THROW asm ("basename") nonnull ((1));**

**# else extern char \*basename (const char \*filename) THROW nonnull ((1)); # endif # endif #endif**

**#3109** 3 years ago fixed arch/riscv Sebastian Huber Hesham Almatary 19 months ago

Summary Add RISC-V support

Description Add RISC-V 32-bit tool chain to RSB consisting of Binutils, GCC, Newlib and GDB. Add CPU port and a basic simulator BSP.

**#3111** 3 years ago fixed tool/newlib Sebastian Huber Sebastian Huber 2 years ago

Summary Newlib: Change time\_t and clock\_t integer types to 64-bit

**#3112** 3 years ago fixed posix Sebastian Huber Sebastian Huber 2 years ago

Summary POSIX: Make pthread\_mutex\_t self-contained

Change the POSIX mutex into a self-contained object using <sys/lock.h>, e.g.

```
typedef struct {
    struct _Mutex_recursive_Control _mutex;
    unsigned int _flags;
    struct _Scheduler_Control *_scheduler;
    _uint64_t _priority_ceiling;
} pthread_mutex_t;
```

**#3113** 3 years ago fixed posix Sebastian Huber Sebastian Huber 2 years ago

Summary POSIX: Make pthread\_cond\_t self-contained

Change the POSIX condition variable into a self-contained object using <sys/lock.h>, e.g.

```
typedef struct {
    struct _Condition_Control _condition;
    pthread_mutex_t *_mutex;
    clockid_t _clock;
} pthread_cond_t;
```

**#3114** 3 years ago fixed posix Sebastian Huber Sebastian Huber 2 years ago

Summary POSIX: Make pthread\_barrier\_t self-contained

Change the POSIX barrier into a self-contained object using <sys/lock.h>, e.g.

```
typedef struct {
    struct _Thread_queue_Queue _queue;
    unsigned int _flags;
    unsigned int _count;
} pthread_barrier_t;
```

**#3115** 3 years ago fixed posix Sebastian Huber Sebastian Huber 2 years ago

Summary POSIX: Make pthread\_rwlock\_t self-contained

Change the POSIX read-write lock into a self-contained object using <sys/lock.h>, e.g.

```
typedef struct {
    struct _Thread_queue_Queue _queue;
    unsigned int _flags;
    unsigned int _readers;
} pthread_rwlock_t;
```

**#3116** 3 years ago fixed posix Sebastian Huber Sebastian Huber 2 years ago

Summary POSIX: Make sem\_t self-contained

Change the POSIX semaphore into a self-contained object using <sys/lock.h>, e.g.

```
typedef struct {
    struct _Semaphore_Control _sem;
} sem_t;
```

**#3117** 3 years ago fixed score Sebastian Huber Sebastian Huber 2 years ago

Summary score: Optimize \_Thread\_queue\_Enqueue() timeout handling

Description Use the Thread\_queue\_Context::enqueue\_callout to do the timeout handling. This avoids the switch statement in \_Thread\_queue\_Timeout(). It removes the thread queue dependency to \_Thread\_Timeout().

<b>#3121</b>	2 years ago	fixed	tool/newlib	Sebastian Huber	Sebastian Huber	2 years ago
Summary	clock() implementation in Newlib is broken					
Description	Newlib uses <code>_times_r()</code> in <code>clock()</code> . The problem is that the <code>_times_r()</code> clock frequency is defined by <code>sysconf(_SC_CLK_TCK)</code> . The clock frequency of <code>clock()</code> is the constant <code>CLOCKS_PER_SEC</code> . FreeBSD uses <code>getusage()</code> for <code>clock()</code> .					
<b>#3122</b>	2 years ago	fixed	bsps	Sebastian Huber	Sebastian Huber	11 months ago
Summary	Simplify and unify <code>BSP_output_char</code>					
Description	The <code>BSP_output_char</code> should output a char and not mingle with high level processing, e.g. '\n' to '\r\n' translation. Move this translation to <code>rtems_putc()</code> . Remove it from all the <code>BSP_output_char</code> implementations.					
<b>#3123</b>	2 years ago	wontfix	tool/gdb	Sebastian Huber	Sebastian Huber	2 years ago
Summary	GDB 8.0.1 is broken on FreeBSD 11					
Description	<p>I tried to add the patches for 7.11, but this results in:</p> <pre> -----  --- gdb/gnulib/import/stddef.in.h.orig 2016-10-07 23:33:10.529558000 -0700  +++ gdb/gnulib/import/stddef.in.h      2016-10-07 23:33:23.824676000 -0700 ----- Patching file gdb/gnulib/import/stddef.in.h using Plan A... Hunk #1 failed at 82. 1 out of 1 hunks failed--saving rejects to gdb/gnulib/import/stddef.in.h.rej                     </pre>					
<b>#3124</b>	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Ignore <code>pshared</code> attribute for POSIX semaphores					
Description	Since we have only one process, sharing between processes is trivial.					
<b>#3125</b>	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Accept <code>PTHREAD_PROCESS_SHARED</code> for POSIX mutexes					
Description	Since we have only one process, sharing between processes is trivial.					
<b>#3126</b>	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Accept <code>PTHREAD_PROCESS_SHARED</code> for POSIX barriers					
Description	Since we have only one process, sharing between processes is trivial.					
<b>#3127</b>	2 years ago	fixed	tool/gcc	Chris Johns	Chris Johns	17 months ago
Summary	MIPS tool build on Darwin (MacOS) fails.					
Description	<p>This is the same bug that effects FreeBSD. For details see:  <a href="https://gcc.gnu.org/bugzilla/show_bug.cgi?id=66032">https://gcc.gnu.org/bugzilla/show_bug.cgi?id=66032</a> <a href="https://gcc.gnu.org/bugzilla/show_bug.cgi?id=62097">https://gcc.gnu.org/bugzilla/show_bug.cgi?id=62097</a></p>					
<b>#3128</b>	2 years ago	fixed	tool	Chris Johns	chrisj@...	2 years ago
Summary	RTEMS Tools <code>covar</code> does not build on Windows.					
Description	<p>The following error has appeared on Windows:</p> <pre> In file included from ../rtemstoolkit/elftoolchain/libelf/gelf.h:34:0,                  from ../rtemstoolkit/rld-elf-types.h:29,                  from ../rtemstoolkit/rld.h:72,                  from ../rtemstoolkit/rld-process.h:31,                  from ../tester/covoar/ObjdumpProcessor.h:16,                  from ../tester/covoar/DesiredSymbols.h:18,                  from ../tester/covoar/app_common.h:6,                  from ../tester/covoar/app_common.cc:40: ../rtemstoolkit/elftoolchain/libelf/libelf.h:33:23: fatal error: sys/queue.h: No such file or directory #include &lt;sys/queue.h&gt;                  ^ compilation terminated.  Waf: Leaving directory `D:/opt/rtems/rsb.git/rtems/build/rth/rtems-tools.git/build'                     </pre>					
<b>#3129</b>	2 years ago	fixed	tool	Chris Johns	joel	2 years ago
Summary	RTEMS Tools <code>covoar</code> build fails on Windows					
Description	<p>The following warnings and errors are present so the RSB tools do not finish and install:</p>					

```
[ 97/150] Compiling linkers/rtems-syms.cpp
[ 98/150] Compiling linkers/rtems-rapper.cpp
[ 99/150] Compiling linkers/rtems-exeinfo.cpp
In file included from ../rtemstoolkit/rld-files.cpp:30:0:
../rtemstoolkit/rld-files.cpp: In destructor 'virtual rld::files::image::~image()':
../rtemstoolkit/rld.h:111:75: warning: throw will always call terminate() [-Wterminate]
  rld::error ( _what, std::string ( _FILE_ ) + ":" + to_string ( _LINE_ ) )
  ^
^
^
../rtemstoolkit/rld-files.cpp:256:15: note: in expansion of macro 'rld_error_at'
  throw rld_error_at ("references when destructing image");
  ^
^
^
../rtemstoolkit/rld.h:111:75: note: in C++11 destructors default to noexcept
  rld::error ( _what, std::string ( _FILE_ ) + ":" + to_string ( _LINE_ ) )
  ^
^
^
../rtemstoolkit/rld-files.cpp:256:15: note: in expansion of macro 'rld_error_at'
  throw rld_error_at ("references when destructing image");
  ^
^
^
```

#3130	2 years ago	fixed	doc	Chris Johns	chrisj@...	2 years ago
Summary	RTEMS 5.1: Fixing linker warnings in CoverageFactory.cc					

Description: [100/150] Compiling tester/covovar/app\_common.cc  
 [101/150] Compiling tester/covovar/CoverageFactory.cc  
 [102/150] Compiling tester/covovar/CoverageMap.cc  
 [103/150] Compiling tester/covovar/CoverageMapBase.cc  
 [104/150] Compiling tester/covovar/CoverageRanges.cc  
 [105/150] Compiling tester/covovar/CoverageReaderBase.cc  
 [106/150] Compiling tester/covovar/CoverageReaderOEMU.cc  
 [107/150] Compiling tester/covovar/CoverageReaderRTEMS.cc  
 [108/150] Compiling tester/covovar/CoverageReaderSkyeye.cc  
 [109/150] Compiling tester/covovar/CoverageReaderTSIM.cc  
 [110/150] Compiling tester/covovar/CoverageWriterBase.cc  
 [111/150] Compiling tester/covovar/CoverageWriterRTEMS.cc  
 [112/150] Compiling tester/covovar/CoverageWriterSkyeye.cc  
 [113/150] Compiling tester/covovar/CoverageWriterTSIM.cc  
 [114/150] Compiling tester/covovar/Executables.cc  
 [115/150] Compiling tester/covovar/ExecutablesBase.cc  
 [116/150] Compiling tester/covovar/ExecutablesInfo.cc  
 [117/150] Compiling tester/covovar/ExecutablesInfoBase.cc  
 [118/150] Compiling tester/covovar/ExecutablesInfoOEMU.cc  
 [119/150] Compiling tester/covovar/ExecutablesInfoRTEMS.cc  
 [120/150] Compiling tester/covovar/ExecutablesInfoSkyeye.cc  
 [121/150] Compiling tester/covovar/ExecutablesInfoTSIM.cc  
 [122/150] Compiling tester/covovar/ExecutablesInfoBaseOEMU.cc  
 [123/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMS.cc  
 [124/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeye.cc  
 [125/150] Compiling tester/covovar/ExecutablesInfoBaseTSIM.cc  
 [126/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBase.cc  
 [127/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMSBase.cc  
 [128/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeyeBase.cc  
 [129/150] Compiling tester/covovar/ExecutablesInfoBaseTSIMBase.cc  
 [130/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBaseOEMU.cc  
 [131/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMSBaseRTEMS.cc  
 [132/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeyeBaseSkyeye.cc  
 [133/150] Compiling tester/covovar/ExecutablesInfoBaseTSIMBaseTSIM.cc  
 [134/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBaseOEMUBase.cc  
 [135/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMSBaseRTEMSBase.cc  
 [136/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeyeBaseSkyeyeBase.cc  
 [137/150] Compiling tester/covovar/ExecutablesInfoBaseTSIMBaseTSIMBase.cc  
 [138/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBaseOEMUBaseOEMU.cc  
 [139/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMSBaseRTEMSBaseRTEMS.cc  
 [140/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeyeBaseSkyeyeBaseSkyeye.cc  
 [141/150] Compiling tester/covovar/ExecutablesInfoBaseTSIMBaseTSIMBaseTSIM.cc  
 [142/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBaseOEMUBaseOEMUBaseOEMU.cc  
 [143/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMSBaseRTEMSBaseRTEMSBaseRTEMS.cc  
 [144/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeyeBaseSkyeyeBaseSkyeyeBaseSkyeye.cc  
 [145/150] Compiling tester/covovar/ExecutablesInfoBaseTSIMBaseTSIMBaseTSIMBaseTSIM.cc  
 [146/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBaseOEMUBaseOEMUBaseOEMUBaseOEMU.cc  
 [147/150] Compiling tester/covovar/ExecutablesInfoBaseRTEMSBaseRTEMSBaseRTEMSBaseRTEMSBaseRTEMS.cc  
 [148/150] Compiling tester/covovar/ExecutablesInfoBaseSkyeyeBaseSkyeyeBaseSkyeyeBaseSkyeyeBaseSkyeye.cc  
 [149/150] Compiling tester/covovar/ExecutablesInfoBaseTSIMBaseTSIMBaseTSIMBaseTSIMBaseTSIM.cc  
 [150/150] Compiling tester/covovar/ExecutablesInfoBaseOEMUBaseOEMUBaseOEMUBaseOEMUBaseOEMUBaseOEMU.cc

#3132	2 years ago	fixed	fs	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add rtems_libio_t::flags to CoverageReaderTSIM.cc					

Description: The file descriptor used to read the file during a close() operation may result in a use after free. Finding such errors in applications is difficult. Especially in SMP systems using the highly dynamic libsd task.

The file descriptor used to read the file during a close() operation may result in a use after free. Finding such errors in applications is difficult. Especially in SMP systems using the highly dynamic libsd task.

To improve performance, the file descriptors add a bit field for the reference count to the rtems\_libio\_t::flags and use atomic operations to maintain the flags.

Each operation using a file descriptor should perform a sequence like this:

```
int rtems_libio_t::read( rtems_libio_t::DesiredSymbols.cc:517:36: error: 'realpath' was not declared in this scope
  realpath( inputBuffer, rpath );
  ^
unsigned int flags;
}

Waf: Leaving directory 'D:/opt/rtems/bsp02/git/build'
Build failed.
Set errno and return_minus_one( EBADF );
-> task in 'covovar' failed with exit status 1 (run with -v to display more information)

iop = rtems_libio_iop( fd );
flags = rtems_libio_iop_hold( iop );

if ( ( flags & LIBIO_FLAGS_OPEN ) == 0 ) {
  rtems_libio_iop_drop( _iop );
  rtems_set_errno_and_return_minus_one( EBADF );
}

do_op( iop, ... );
rtems_libio_iop_drop( iop );
return 0;
}
```

A close() should return -1 with EBUSY in case the file descriptor is referenced. In this case, no close operation will be performed.

#3133	2 years ago	fixed	fs	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove rtems_libio_t::driver					

Description: Remove unused rtems\_libio\_t::driver member.

#3134	2 years ago	fixed	fs	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove LIBIO_FLAGS_CREATE					

Description: Remove unused LIBIO\_FLAGS\_CREATE flag.

#3135	2 years ago	fixed	admin	Sebastian Huber	amar@...	2 years ago
Summary	Devel mailing list doesn't work and Git push impossible due to disk full					

I got this:

```
git push
Counting objects: 18, done.
Delta compression using up to 12 threads.
Compressing objects: 100% (17/17), done.
Writing objects: 100% (18/18), 1.68 KiB | 0 bytes/s, done.
Total 18 (delta 16), reused 0 (delta 0)
remote: error: file write error (No space left on device)
remote: fatal: unable to write sha1 file
error: remote unpack failed: unpack-objects abnormal exit
To ssh://dispatch.rtems.org/data/git/rtems.git
! [remote rejected] upstream -> master (unpacker error)
error: failed to push some refs to 'ssh://sebh@dispatch.rtems.org/data/git/rtems.git'
```

We have on dispatch.rtems.org:

```
Filesystem      Size  Used Avail Capacity Mounted on
/dev/gpt/root0  88G   82G  -600M  101% /
```

#3136	2 years ago	fixed	fs	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Use FIFO for file descriptor free list					

Description: Currently, the free list of file descriptors is organized as a LIFO. In erroneous systems which use a file descriptor after a call to close(), this increases the likelihood that this error is undetected due to the prompt re-use of the file descriptor. The use of a FIFO has the benefit that free file descriptors remain on the free list as long as possible. This increases the time frame in which an invalid use of a closed file descriptor returns an error status.

#3137	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Accept PTHREAD_PROCESS_SHARED for POSIX condition variables					

Since we have only one process, sharing between processes is trivial.

Descripti	#3139	2 years ago	fixed	bsps	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove old ISR parameter from Clock_driver_support_install_isr() and make it optional						
Descripti	The old ISR is not used by the clock driver shell.						
on	#3140	2 years ago	fixed	score	Chris Johns	joel.sherrill@...	2 years ago
Summary	CPU Kit broken with --enable-rtems-debug						
Descripti	Building with:						
on	<pre>.../rtems.git/configure --target=arm-rtems4.12 --prefix=/opt/work/chris/rtems/kernel/4.12 --disable-networking --enable-rtemsbsp=beagleboneblack --enable-maintainer-mode --enable-rtems-debug</pre>						
Summary	results in an error:						
Descripti	<pre>gmake[5]: Entering directory '/opt/work/chris/rtems/kernel/bsps/beagleboneblack/arm-rtems4.12/c/beagleboneblack/cpukit/score' arm-rtems4.12-gcc --pipe -DHAVE_CONFIG_H -I. -I../cpukit/./././beagleboneblack/lib/include -mcpu=cortex-a8 -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT src/libscore_a-semaphore.o -MD -MP -MF src/deps/libscore_a-semaphore.Tpo -c -o src/libscore_a-semaphore.o `test -f 'src/semaphore.c'    echo '/opt/work/chris/rtems/kernel/rtems.git/c/src/./././cpukit/score/'` src/semaphore.c In file included from /opt/work/chris/rtems/kernel/rtems.git/c/src/./././cpukit/score/src/semaphore.c:21:0: /opt/work/chris/rtems/kernel/rtems.git/c/src/./././cpukit/score/src/semaphore.c: In function '_Semaphore_Post': /opt/work/chris/rtems/kernel/rtems.git/c/src/./././cpukit/score/src/semaphore.c:134:27: error: 'UINT_MAX' undeclared (first use in this function); did you mean 'UINT8_MAX'?   _Assert( sem-&gt;count &lt; UINT_MAX );       ^ ././cpukit/./././beagleboneblack/lib/include/rtems/score/assert.h:67:12: note: in definition of macro '_Assert'   (( _e ) ? \    ^ /opt/work/chris/rtems/kernel/rtems.git/c/src/./././cpukit/score/src/semaphore.c:134:27: note: each undeclared identifier is reported only once for each function it appears in   _Assert( sem-&gt;count &lt; UINT_MAX );       ^ ././cpukit/./././beagleboneblack/lib/include/rtems/score/assert.h:67:12: note: in definition of macro '_Assert'   (( _e ) ? \    ^ gmake[5]: *** [Makefile:4571: src/libscore_a-semaphore.o] Error 1</pre>						
Summary	We need the <code>rtems-bsp-builder</code> to be run on a regular basis to catch these errors.						
Descripti	Tools are:						
on	<pre>\$ /opt/work/rtems/4.12/bin/arm-rtems4.12-gcc --version arm-rtems4.12-gcc (GCC) 7.2.0 20170814 (RTEMS 4.12, RSB e6d0a8bae6d16eba605370ca11a5928b797820bb-modified, Newlib 2.5.0.20170818)</pre>						
Summary	#3141	2 years ago	fixed	doc	Chris Johns	Chris Johns	2 years ago
Summary	Change the BSP Howto's name to something smaller.						
Descripti	The BSP Howto's current name is:						
on	<p><b>RTEMS BSP and Device Driver Development Guide</b></p> <p>This is long and causes problems in the PDF output. Change the name to:</p> <p><b>RTEMS BSP and Driver Guide</b></p>						
Summary	#3142	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	POSIX: Reduce size of pthread_once_t and make it zero-initialized						
Descripti	A zero-initialized pthread_once_t reduces the ROM usage of RTEMS applications, since the global pthread_once_t objects may reside in the BSS section.						
on	#3148	2 years ago	fixed	posix	Chris Johns	joel.sherrill@...	2 years ago
Summary	PSXRDWRV Test failure on Beaglebone Black						
Descripti	Running <code>rtems-test</code> with a recent u-boot and a current master this failure is reported:						
on	<pre>] RTEMS Beagleboard: am335x-based ] ] ] *** BEGIN OF TEST PSXRDWRV *** ] writev bad file descriptor -- EBADF ] writev error 1: 22=Invalid argument ] Error during error test!!!!</pre>						
Summary	#3152	2 years ago	wontfix	arch/arm	Chris Johns	Chris Johns	17 months ago
Summary	Beaglebone Black crashes on u-boot master build.						
Descripti	The crash with a Linux type image and no FDT is:						
on	<pre>] ## Booting kernel from Legacy Image at 82000000 ... ] Image Name: RTEMS ] Image Type: ARM Linux Kernel Image (gzip compressed) ] Data Size: 60886 Bytes = 59.5 KiB ] Load Address: 80000000 ] Entry Point: 80000000 ] Verifying Checksum ... OK ] Uncompressing Kernel Image ... OK ] ] Starting kernel ... ] ] data abort ] ] MAYBE you should read doc/README.arm-unaligned-accesses ] ] pc : [&lt;8000010c&gt;] lr : [&lt;800000ac&gt;] ] sp : 80101000 ip : 0000000c fp : 9f35ac28 ] r10: 9f3ad0f4 r9 : 00000000 r8 : 9f238f40 ] r7 : 00000000 r6 : 80000100 r5 : 00000e05 r4 : 60000193 ] r3 : 9f238fe0 r2 : 80000100 r1 : 00000e05 r0 : 60000193 ] Flags: nzcw IRQs off FIQs on Mode SVC_32 ] Resetting CPU ...</pre>						
Summary	and the code is:						

```
BSP_START_TEXT_SECTION void bsp_start_hook_0(void)
{
}
80000104: e12fff1e bx lr

80000108 <bsp_start_hook_1>:
BSP_START_TEXT_SECTION static inline arm_a8core_start_set_vector_base(void)
{
/*
 * Do not use bsp_vector_table_begin == 0, since this will get optimized away.
 */
if (bsp_vector_table_end != bsp_vector_table_size) {
80000108: e3002040 movw r2, #64 ; 0x40
8000010c: e3003040 movw r3, #64 ; 0x40
80000110: e3482000 movt r2, #32768 ; 0x8000
80000114: e3403000 movt r3, #0
80000118: e1520000 cmp r2, r3
8000011c: e1520000 cmp r2, r3
}
}
```

#3153	2 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	-------------	-----------------	-----------------	-------------

Summary: Accept PTHREAD\_PROCESS\_SHARED for POSIX rwlocks

Description: Since we have only one process, sharing between processes is trivial.

#3157	2 years ago	fixed	unspecified	Jeff Mayes	Joel Sherrill	2 years ago
-------	-------------	-------	-------------	------------	---------------	-------------

Summary: PowerPC tools don't build on 32-bit hosts

Description: Using RSB and trying to build PowerPC. Updated RSB just a few days ago. i386 and arm build successfully, but PowerPC fails.  
 configure:3662: checking for suffix of object files configure:3684: /opt/rtems-tools/rsb/rtems/build/powerpc-rtems4.12-gcc-7.2.0-newlib-2.5.0.20170818-i686-pc-cygwin-1/build/.gcc/xgcc -B/opt/rtems-tools/rsb/rtems/build/powerpc-rtems4.12-gcc-7.2.0-newlib-2.5.0.20170818-i686-pc-cygwin-1/build/.gcc/ -nostdinc -B/opt/rtems-tools/rsb/rtems/build/powerpc-rtems4.12-gcc-7.2.0-newlib-2.5.0.20170818-i686-pc-cygwin-1/build/powerpc-rtems4.12/me6500/m64/newlib/ -isystem /opt/rtems-tools/rsb/rtems/build/powerpc-rtems4.12-gcc-7.2.0-newlib-2.5.0.20170818-i686-pc-cygwin-1/build/powerpc-rtems4.12/me6500/m64/newlib/targ-include -isystem /opt/rtems-tools/rsb/rtems/build/powerpc-rtems4.12-gcc-7.2.0-newlib-2.5.0.20170818-i686-pc-cygwin-1/gcc-7.2.0/newlib/libc/include -B/desk/rtems/powerpc-rtems4.12/bin/ -B/desk/rtems/powerpc-rtems4.12/lib/ -isystem /desk/rtems/powerpc-rtems4.12/include -isystem /desk/rtems/powerpc-rtems4.12/sys-include -mcpu=e6500 -m64 -c -g -O2 conftest.c >&S Assembler messages: Fatal error: -a64 unsupported configure:3688: \$? = 1 configure: failed program was: | /\* confdefs.h \*/ | #define PACKAGE\_NAME "GNU C Runtime Library" | #define PACKAGE\_TARNAME "libgcc" | #define PACKAGE\_VERSION "1.0" | #define PACKAGE\_STRING "GNU C Runtime Library 1.0" | #define PACKAGE\_BUGREPORT "" | #define PACKAGE\_URL "http://www.gnu.org/software/libgcc/" | /\* end confdefs.h. \*/ | int | main () { | ; | return 0; | } configure:3702: error: in `opt/rtems-tools/rsb/rtems/build/powerpc-rtems4.12-gcc-7.2.0-newlib-2.5.0.20170818-i686-pc-cygwin-1/build/powerpc-rtems4.12/me6500/m64/libgcc': configure:3705: error: cannot compute suffix of object files: cannot compile

#3158	2 years ago	fixed	unspecified	Chris Johns	Chris Johns	2 years ago
-------	-------------	-------	-------------	-------------	-------------	-------------

Summary: Examples v2 does not build

Description: Updating waf breaks the rootfs. Add rootfs support to [rtems-waf.git](https://github.com/rtems/rtems-waf).

#3159	2 years ago	fixed	unspecified	Chris Johns	Chris Johns	2 years ago
-------	-------------	-------	-------------	-------------	-------------	-------------

Summary: Examples v2 trace linker ini files reference non-existing dump-on-error

Description: Remove the dump-on-error option.

#3160	2 years ago	fixed	unspecified	Chris Johns	Chris Johns	2 years ago
-------	-------------	-------	-------------	-------------	-------------	-------------

Summary: Trace linker score support is broken

Description: The trace linker needs to be updated to build. I am not sure which bit is broken. Building the tools gives:

Description

				[ 7/15] Compiling build/arm-rtems4.12-beagleboneblack/hello/both_hello/test.c.2.0 /Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:134:13: error: 'Thread_queue_Flush_callout' undeclared here (not in a function); did you mean 'Thread_queue_Flush_filter'?			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: { sizeof (Thread_queue_Flush_callout), "Thread_queue_Flush_callout" }, ^~~~~~ Thread_queue_Flush_filter			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:140:13: error: 'CORE_mutex_Status' undeclared here (not in a function); did you mean 'CORE_mutex_Control'?			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: { sizeof (CORE_mutex_Status), "CORE_mutex_Status" }, ^~~~~~ CORE_mutex_Control			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:143:19: error: unknown type name 'CORE_mutex_Attributes'			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: { sizeof (const CORE_mutex_Attributes*), "const CORE_mutex_Attributes*" }, ^~~~~~			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:160:13: error: 'CORE_mutex_API_mp_support_callout' undeclared here (not in a function)			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: { sizeof (CORE_mutex_API_mp_support_callout), "CORE_mutex_API_mp_support_callout" }, ^~~~~~			
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:321:13: error: 'Objects_Locations' undeclared here (not in a function); did you mean 'Objects_Information'?			
#3163	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber		2 years ago
Summary	Add Objects_Information to the rtems4.12 POSIX API headers.						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:321:31: error: expected expression before ')' token			
#3166	2 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber		2 years ago
Summary	New POSIX API function: rtems4.12 posix thread attributes.						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:342:31: error: expected expression before ')' token			
Description	We have a hard time with rtems4.12 POSIX API working on them. One problem is that the tickets are assigned to a real person by default. Assign the tickets to a virtual person.						
#3167	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber		2 years ago
Summary	Internal POSIX API changes to support C11/C++11 APIs.						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:368:31: error: expected expression before ')' token			
Description	The internal POSIX API changes to support C11/C++11 APIs and error codes used by the POSIX and C11/C++11 APIs. In case the POSIX API is disabled, the C11/C++11 support must be used.						
#3168	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber		2 years ago
Summary	Simple POSIX API changes to support C11/C++11 APIs.						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:548:13: error: 'Thread_Start_types' undeclared here (not in a function); did you mean '_Thread_Start'?			
Description	The Thread_Start_types is a POSIX API header. This is at least in line with Linux.						
#3170	2 years ago	fixed	unspecified	Chris Johns	Chris Johns		2 years ago
Summary	Use rtems4.12 posix thread attributes for test output by default.						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: { sizeof (Thread_blocking_operation_States), "Thread_blocking_operation_States" }, ^~~~~~			
Description	Test runs with a driver for driven console driver result in untable test outcomes.						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:678:3: warning: implicit declaration of function 'printk'; did you mean 'printf'? [-Wimplicit-function-declaration]			
Description	The printk() function is not declared in the test code.						
#3171	2 years ago	fixed	tool/gcc	Chris Johns	Chris Johns		17 months ago
Summary	RSB Doc sites development/rtems/4.12/bin/arm-rtems4.12-gcc: void CORE_mutex_Flush(CORE_mutex_Control* a1, Thread_queue_Flush_callout a2, uint32_t a3);						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:743:55: error: expected declaration specifiers or '...' before 'Thread_queue_Flush_callout'			
Description	The issue has been reported upstream as <a href="https://gcc.gnu.org/bugzilla/show_bug.cgi?id=81797">https://gcc.gnu.org/bugzilla/show_bug.cgi?id=81797</a> .						
#3172	2 years ago	fixed	arch/386	Chris Johns	Chris Johns		2 years ago
Summary	i386 FreeBSD compatibility changes for rtems4.12 bin/arm-rtems4.12-gcc: void _wrap_CORE_mutex_Flush(CORE_mutex_Control* a1, Thread_queue_Flush_callout a2, uint32_t a3)						
				/Users/chris/development/rtems/4.12/bin/arm-rtems4.12-gcc: hello-deep.c:757:1: error: unknown type name 'CORE_mutex_Status'; did you mean 'CORE_mutex_Control'?			
Description	Remove the CORE_mutex_Status from the rtems4.12 POSIX API headers. It is not a standard POSIX API function.						
#3173	2 years ago	fixed	arch/arm	Chris Johns	Chris Johns		2 years ago
Summary	Xilinx AXI I2C driver race condition causes clock glitch.						
Description	The Xilinx AXI I2C IP has a race condition when the PIRQ read FIFO level is reached and the clock is throttling. This is a snip of the errors.						
#3174	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber		2 years ago
Summary	Remove rtems_thread_attribute_compare()						
Description	The rtems_thread_attribute_compare() function is undocumented and used only in one test. Move it to the test.						
#3175	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber		17 months ago
Summary	Merge FreeBSD timecounter changes from 2015-01-20 to now						
#3176	2 years ago	fixed	tool/newlib	Joel Sherrill	Joel Sherrill		18 months ago
Summary	getreent in libc.a and generated by confdefs.h						
Description	Some applications are getting duplicate symbol definitions for getreent(). One of the examples-v2 programs is doing this. It is because there are two bodies for this method -- one from confdefs.h and another from newlib. <a href="https://sourceware.org/ml/newlib/2017/msg01020.html">https://sourceware.org/ml/newlib/2017/msg01020.html</a> addresses the issues and needs to be incorporated by the RSB. <a href="https://sourceware.org/ml/newlib/2017/msg01019.html">https://sourceware.org/ml/newlib/2017/msg01019.html</a> is a cleanup that was spotted at the same time. It can be picked up by a newlib snapshot.						
#3177	2 years ago	fixed	doc	Joel Sherrill	Chris Johns		2 years ago
Summary	Replace/update POSIX Compliance Guide						
Description	The POSIX Compliance Guide was never converted from texinfo. Beyond that, it is out of date and follows the outline of the printed version of the POSIX standard which no one sees anymore. This ticket proposes: 1. new Sphinx document 2. contents generated from POSIX API tracking spreadsheet (CSV) 3. outline per .h file, not functional area 4. use bullets, not tables so easier to format						
#3178	2 years ago	fixed	tool/gcc	Joel Sherrill	Joel Sherrill <jjoel@...>		2 years ago
Summary	Update sh-rtems4.12 bset to use rtems-default (using old gcc)						
Description	I built a toolset and all BSPs on Centos 7 after switching this to rtems-default.bset again. There was no comment indicating why it was using an older gcc so I assume something has been fixed.						







- This one is not a huge deal since it's just that request process users won't even notice when this happens.

Upgrading trac is a weeklong project usually I will start preparing for it and update here.

#3204	2 years ago	worksforme	tool	Joel Sherrill	Chris Johns	3 months ago
Summary	Exception in rtems-test					
Description	<p>Note: No category for rtems-tools.</p> <p>My first attempt to send run logs didn't go so well. This was a weird failure mode. It didn't exit but had to be killed by hand. I dropped off the options related to mailing the log and it still failed. This is on an up to date CentOS 7 (rtbf64c 7.4) as well as my 7.3 VM.</p> <pre>+ /home/joel/rtems-work/rtems-tools/tester/rtems-test --rtems-tools=/home/joel/rtems-work/tools/4.12 --rtems-bsp=erc32 --log=run.log --mail --mail-from=joel@rtems.org --mail-to=build@lists.rtems.org ./sparc-rtems4.12/c/erc32/testsuites/samples/ticker/ticker.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/minimum/minimum.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/iostream/cxx_ostream.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/fileio/fileio.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/capture/capture.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/nsecs/nsecs.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/paranoia/paranoia.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/cdtest/cdtest.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/base_sp/base_sp.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/unlimited/unlimited.exe ./sparc-rtems4.12/c/erc32/testsuites/samples/hello/hello.exe RTEMS Testing - Tester, 4.12 (52513610668b) [ 5/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: hello.exe [ 6/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: cxx_ostream.exe [ 3/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: cdtest.exe [ 9/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: paranoia.exe [ 7/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: minimum.exe [ 1/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: base_sp.exe [11/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: unlimited.exe [ 4/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: fileio.exe [10/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: ticker.exe [ 2/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: capture.exe [ 8/11] p:0 f:0 u:0 e:0 l:0 B:0 t:0 i:0   sparc/erc32: nsecs.exe Traceback (most recent call last):   File "/home/joel/rtems-work/rtems-tools/tester/rtems-test", line 40, in &lt;module&gt;     rt.test.run()   File "/data/home/joel/rtems-work/rtems-tools/tester/rt/test.py", line 336, in run     job_trace)   File "/data/home/joel/rtems-work/rtems-tools/tester/rt/test.py", line 189, in report_finished     reports.log(tst.executable, report_mode)   File "/data/home/joel/rtems-work/rtems-tools/tester/rt/report.py", line 193, in log     exe = path.basename(self.results[name]['exe'])   File "/home/joel/rtems-work/rtems-tools/rtemstoolkit/path.py", line 77, in basename     return shell(os.path.basename(path))   File "/usr/lib64/python2.7/posixpath.py", line 121, in basename     i = p.rfind('/') + 1 AttributeError: 'NoneType' object has no attribute 'rfind'</pre>					

#3205	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Relative timespec timeouts are subject to integer overflows					
Description	As a best-effort approach, a very large relative timeout should result in the maximum monotonic watchdog value and not in an undefined integer overflow.					
#3207	2 years ago	fixed	doc	Joel Sherrill		2 years ago
Summary	Supported Architectures Page is out of date					
Description	<p><a href="https://devel.rtems.org/wiki/TBR/UserManual/SupportedCPU">https://devel.rtems.org/wiki/TBR/UserManual/SupportedCPU</a> is out of date. I have the information to update it if that's what we want to do.</p> <p>I don't know the best way to provide this broad view from 4.6 up on what architectures are supported. The wiki seems OK.</p>					

#3209	2 years ago	fixed	tool/rsb	Joel Sherrill	Chris Johns	23 months ago
Summary	RSB should fail on this error					
Description	<p>I was updating the md5's to sha512's on qemu and made a typo which resulted in this message:</p> <pre>reporting: devel/qemu-git-1.cfg -&gt; qemu-42d58e7c6760cb9c55627c28ae538e27dcf2f144-x86_64-linux-gnu-1.xml error: qemu-git-1.cfg:57: invalid number of hash args loading: vdeplug get: requires ()</pre> <p>The error message did not result in the build aborting. Perhaps this should be a fatal error.</p> <p>The broken RSB fragment was in qemu-git-1.cfg:</p> <pre>%patch add qemu % {rtems_http_git}/rtems-tools/plain/tools/qemu/0001-openrisc-terminate-qemu-process-upon-receiving-a-hal.patch -%hash md5 0001-openrisc-terminate-qemu-process-upon-receiving-a-hal.patch 6aa9dfc4522466ab4a463129b3b9cb1d +%hash md5 376ea9e07c4c8077b345af02856549843dff2ad73b5da5886c71e859c4a0849522c59dcd05724270756763438aecdb70211ea2ae8cac28056cb17da53c3981e1</pre>					

#3210	2 years ago	fixed	tool/rsb	Chris Johns	Chris Johns	2 years ago
Summary	Improve the RSB build email message					
Description	The message needs more detail to provide a suitable archive.					
#3211	2 years ago	fixed	posix	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Fix pthread_create() with user provided stack					
Description	In case the user provides a stack with address and size, then do not alter the stack size.					

#3212	2 years ago	worksforme	tool/rsb	Joel Sherrill	Chris Johns	3 months ago
Summary	Qemu Fails to Build, RSB Gives Odd Traceback					
Description	<p>After applying the attached patch to update the md5's to sha512's, something goes wrong in the RSB build of Qemu. There is nothing obvious from the qemu build directory. But it appears that the cd into the qemu git directory didn't work and it is acting on my RSB git clone. The RSB trace is:</p>					

Description	<pre> script: 78: cd "/data/home/joel/rtems-work/rtems-source-builder/bare/build/qemu-42d58e7c6760cb9c55627c28ae538e27dcf2f144-x86_64-linux-gnu-1" script: 79: echo "=&gt; qemu-42d58e7c6760cb9c55627c28ae538e27dcf2f144-x86_64-linux-gnu-1:" script: 80: echo "=&gt; %prep:" script: 81: build_top=\$(pwd) script: 82: source_dir_qemu="qemu-42d58e7c6760cb9c55627c28ae538e27dcf2f144" source setup: qemu-42d58e7c6760cb9c55627c28ae538e27dcf2f144-x86_64-linux-gnu-1: source=qemu -q -n qemu-42d58e7c6760cb9c55627c28ae538e27dcf2f144 making dir: /data/home/joel/rtems-work/rtems-source-builder/bare/sources/git _url: git://git.qemu-project.org/qemu.git?pull?checkout=42d58e7c6760cb9c55627c28ae538e27dcf2f144?submodule=dtc -&gt; /data/home/joel/rtems-work/rtems-source-builder/bare/sources/git/qemu.git cmd: (/data/home/joel/rtems-work/rtems-source-builder/bare/sources/git/qemu.git) /usr/bin/git status exe: [/usr/bin/git, 'status'] # On branch am # Untracked files: # (use "git add &lt;file&gt;..." to include in what will be committed) # # .././././am/ # ../././qemu # ../././nohup.out # ../././gcc7/ # ../././rtems/4.10-targets # ../././rtems/all # ../././rtems/chris # ../././rtems/do_a # ../././rtems/do_all # ../././rtems/nohup.out # ../././rtems/p_rm # ../././rtems/sh-gdb.diff nothing added to commit but untracked files present (use "git add" to track) cmd: (/data/home/joel/rtems-work/rtems-source-builder/bare/sources/git/qemu.git) /usr/bin/git clean -f -d exe: [/usr/bin/git, '-f', '-d'] </pre>					
#3213	2 years ago	fixed	tool	Joel Sherrill	Chris Johns	3 months ago
Summary	<p>Move erc27 from (on3, tsim and m32c) to Tier 2          HEAD is now at 96485e3 Add SHA512 checksums for qemu sources          Based on these notes on github, please commit the bare sources (/data/home/joel/rtems-work/rtems-source-builder/bare/sources/git/qemu.git) /usr/bin/git checkout master          exe: [/usr/bin/git, 'checkout', 'master']          Switched to branch master          git: pull https://lists.rtems.org/pipermail/build/2017-October/000018.html          git: pull https://lists.rtems.org/pipermail/build/2017-October/000021.html          cmd: (/data/home/joel/rtems-work/rtems-source-builder/bare/sources/git/qemu.git) /usr/bin/git pull          exe: [/usr/bin/git, 'pull']          Build Set: Time 0:05:24.810871          about user terminated</p>					
#3215	2 years ago	fixed	doc	Joel Sherrill	Joel Sherrill	2 years ago
Summary	<p>Configuring a System Still Includes Notepads and Has Wrong Heading</p> <p>This section has the wrong heading and needs to be deleted anyway.</p>					
Description	<p>24.8.2. Specify Maximum Classic API Timers          CONSTANT:          CONFIGURE_ENABLE_CLASSIC_API_NOTEPADS</p>					
#3216	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	<p>Replace vprintf() implementation</p>					
Description	<p>The current vprintf() implementation has a questionable licence header, lacks support for the 'z' and 'j' format specifiers, is not robust against invalid format specifiers, uses a global variable for output. Replace it with a stripped down version of the FreeBSD kernel kvprintf() function.</p>					
#3217	2 years ago	fixed	lib	Chris Johns	Chris Johns	2 years ago
Summary	<p>Add RTEMS version, build and tools details to tests</p>					
Description	<p>Published test results need the RTEMS version, how it is built and the tools used to build the kernel and tests.</p>					
#3218	2 years ago	fixed	dev/serial	Sebastian Huber	Sebastian Huber	2 years ago
Summary	<p>Termios canonical mode (ICANON) does not return input line by line</p>					
Description	<p>In canonical mode, input is made available line by line. We must stop the canonical buffer filling upon reception of an end-of-line character.</p>					
#3219	2 years ago	fixed	bsps	Chris Johns	Chris Johns	18 months ago
Summary	<p>Zynq BSP missing linker option --gc-sections</p>					
Description	<p>This Zynq BSP is missing this option.</p>					
#3220	2 years ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	2 years ago
Summary	<p>Change RTEMS release number scheme from 4.12 to 5</p> <p>As discussed here  <a href="https://lists.rtems.org/pipermail/devel/2017-October/019169.html">https://lists.rtems.org/pipermail/devel/2017-October/019169.html</a>          it was agreed to use version 5.1 with the new number scheme for the next RTEMS release.</p> <p>Most important items of this release:</p> <ul style="list-style-type: none"> <li>• SMP support</li> <li>• 64-bit time_t (year 2038 problem)</li> <li>• the network stack header consolidation and the move to Newlib</li> <li>• self-contained POSIX synchronization objects (impacting the configuration)</li> <li>• improved Ada support (however, not all Ada tests pass currently)</li> </ul> <p>The following steps are necessary to carry out the number change:</p> <ol style="list-style-type: none"> <li>1. <del>Change version of RTEMS tools</del></li> <li>2. <del>Change version of RSB</del></li> <li>3. <del>Change version of RTEMS</del></li> <li>4. <del>Documentation repo - Easy</del></li> <li>5. <del>Documentation website repo - Easy</del></li> <li>6. Release procedure repo. Easy.</li> <li>7. <del>Trac tickets - Not sure</del></li> <li>8. <del>Trac wiki - Medium(?) - A wiki search of 4.12 gives 21 hits</del></li> <li>9. rtems.org website. That needs Joel.</li> <li>10. Make announcement on the devel and user mailing list</li> </ol>					
#3224	2 years ago	fixed	tool/binutils	Sebastian Huber	Sebastian Huber	2 years ago
Summary	<p>Upgrade or1k and m32c to Binutils 2.29</p>					

#3225	2 years ago	fixed	tool/gdb	Sebastian Huber	Sebastian Huber	2 years ago	
Summary	Upgrade m32c to GDB 8.0.1						
#3226	2 years ago	fixed	tool/gdb	Sebastian Huber	Sebastian Huber	2 years ago	
Summary	gdb: pr 16827, fix sim on Mavrck						
#3227	2 years ago	workforme	admin	Joel Sherrill	Chris Johns	2 years ago	
Summary	sb-check fails on Msys2 64-bit						
Description	<p>There must be a recent change to msys2 which is breaking things. I installed the 64-bit version from <a href="https://msys2.github.io/">https://msys2.github.io/</a> per the instructions at <a href="https://docs.rtems.org/branches/master/user/hosts/index.html#microsoft-windows">https://docs.rtems.org/branches/master/user/hosts/index.html#microsoft-windows</a></p> <pre>\$ ./source-builder/sb-check error: no hosts defaults found; please add</pre> <p>After adding some prints, I learned this:</p> <pre>\$ ./source-builder/sb-check posix made it MSYS_NT-10.0 error: no hosts defaults found; please add</pre> <p>I filled in options.py and windows.py to recognize this as MSYS2. I was then able to run sb-check. But it wasn't happy. Apparently the pacman command in the User's Guide is missing some packages based on newer versions:</p> <pre>\$ ./source-builder/sb-check posix MSYS_NT-10.0 RTEMS Source Builder - Check, 5 (8b30eb3f440a modified) error: exe: not found: (_ar) ar error: exe: not found: (_as) as error: exe: not found: (_cc) x86_64-w64-mingw32-gcc error: exe: not found: (_cxx) x86_64-w64-mingw32-g++ error: exe: not found: (_ld) ld error: exe: not found: (_nm) nm error: exe: not found: (_objcopy) objcopy error: exe: not found: (_objdump) objdump error: exe: not found: (_ranlib) ranlib Environment is not correctly set up</pre> <p>I installed binutils explicitly with pacman and then sb-check is complaining about gcc. I did a find to locate the gcc's installed:</p> <pre>\$ find / -name "*gcc.*" /home/jrs007/.ssh/id_rsa_gcc.pub /mingw64/bin/gcc.exe /mingw64/bin/x86_64-w64-mingw32-gcc.exe /mingw64/lib/gcc/x86_64-w64-mingw32/6.2.0/include/stdint-gcc.h /mingw64/lib/gcc/x86_64-w64-mingw32/6.2.0/libgcc.a /mingw64/share/info/gcc.info.gz /mingw64/share/man/man1/gcc.1.gz /usr/share/vim/vim80/compiler/gcc.vim find: failed to read file names from file system at or below '/': No such file or directory  jrs007@JRS-OAR-Laptop MINGW64 /c/opt/rtems/rsb/source-builder \$ ./mingw64/bin/x86_64-w64-mingw32-gcc.exe --version x86_64-w64-mingw32-gcc.exe (Rev2, Built by MSYS2 project) 6.2.0 Copyright (C) 2016 Free Software Foundation, Inc. This is free software; see the source for copying conditions. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.</pre>						
	#3228	2 years ago	fixed	tool/rsb	Chris Johns		2 years ago
	Summary	aarch64 missing from 5/rtems-all build set					
	Description	This arch needs to be added to the all build set.					
#3229	2 years ago	fixed	doc	Chris Johns	Chris Johns	17 months ago	
Summary	Add index to all documents.						
Description	Indexes currently do not work. Fix this adding them to all documents. Add index entries where possible.						
#3232	2 years ago	fixed	doc	Chris Johns	Chris Johns	2 years ago	
Summary	Use of <code>.. include::</code> in the User Manual should be changed.						
Description	This trick for Sphinx highlights an issue when using <code>.. include::</code> , we should be using <code>.. toctree::</code> : <a href="https://github.com/sphinx-doc/sphinx/issues/3432">https://github.com/sphinx-doc/sphinx/issues/3432</a>						
#3234	2 years ago	invalid	doc	Joel Sherrill	Joel Sherrill	2 years ago	
Summary	Quick Start Instructions Inconsistent						
Description	In section 5 of the User's Manual, the clone of rtems-source-builder has you clone it into rsb but the sb-bootstrap command is based on cloning it into the rsb subdirectory.						
#3235	2 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 years ago	
Summary	Fix rtems_semaphore_flush() for priority inheritance semaphores						
Description	The _Semaphore_Get_operations() must return the proper operations for priority inheritance semaphores. Add a test case for rtems_semaphore_flush() with priority inheritance.						
#3236	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago	
Summary	Fix thread queue owner priority update in _Thread_queue_Flush_critical()						
Description	The thread queue extract operations performed by the _Thread_queue_Flush_critical() may result in a priority change of the thread queue owner. Carry out the scheduler priority						

<b>#3237</b>	update operation. This is especially important in SMP configurations. 2 years ago	fixed	score	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Fix priority ceiling updates					
Description	We must not clear the priority updates in <code>_Thread_queue_Extract_locked()</code> since this function is used by the priority ceiling surrender operations after the ceiling priority handover from the previous owner to the new owner. This is especially important in SMP configurations. Move the <code>_Thread_queue_Context_clear_priority_updates()</code> invocation to the callers.					
<b>#3238</b>	2 years ago	fixed	admin	Chris Johns	Amar Takhar	17 months ago
Summary	Git push to Trac with more than one commit does not update tickets.					
Description	The git push to trac hook does not queue or handle a number of commits in a push. As a result updates to tickets can be missed.					
<b>#3239</b>	2 years ago	fixed	dev	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add <code>getentropy()</code> implementation provided by each BSP					
Description	The <code>getentropy()</code> system call was introduced by OpenBSD and is now also available on glibc 2.25 and later. It is used for example by <code>arc4random_buf()</code> . Which in turn is used by various cryptographic functions.					
<b>#3240</b>	2 years ago	fixed	lib	Andrei Chichak	Chris Johns	2 years ago
Summary	cpukit/libmisc/stackchk/check.c stack addresses formatted incorrectly.					
Description	The function <code>Stack_check_Dump_threads_usage</code> displays the stack high, low, and current pointers incorrectly. Instead of displaying these pointers in conventional hex format, the values have a proper prefix of 0x, but the pointer value is displayed in decimal. The incorrect <code>inttypes.h</code> formatting define was used.					
<b>#3242</b>	2 years ago	fixed	tool/gcc	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Workarounds for UT699, UT700, and GR712RC errata					
Description	<p><a href="https://gcc.gnu.org/ml/gcc-patches/2017-11/msg01751.html">https://gcc.gnu.org/ml/gcc-patches/2017-11/msg01751.html</a></p> <p>This patch series adds workarounds for the newly discovered errata for UT699, UT700, and GR712RC. The errata and possible workarounds are described in the following documents available at <a href="http://www.gaisler.com/index.php/information/app-tech-notes">http://www.gaisler.com/index.php/information/app-tech-notes</a>:</p> <p>GRLIB-TN-0010 - LEON3/FT AHB Deadlock After Sequence of Load and Atomic Instructions GRLIB-TN-0011 - LEON3/FT AHB Lock Release during Atomic Operation GRLIB-TN-0012 - GR712RC Incorrect Annulation of Floating-point Operation on Instruction Cache Parity Error GRLIB-TN-0013 - GRFP Floating-point controller: Missing FDIV/FSQRT Result</p> <p>Daniel Cederman (4):</p> <p>[SPARC] Errata workaround for GRLIB-TN-0012 [SPARC] Errata workaround for GRLIB-TN-0011 [SPARC] Errata workaround for GRLIB-TN-0010 [SPARC] Errata workaround for GRLIB-TN-0013</p>					
<b>#3243</b>	2 years ago	fixed	score	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Simplify global construction					
Description	For the SMP support the global construction was changed to use an approach with a thread restart after global construction. With this implementation thread-local objects and POSIX keys initialized during global construction are not present in the initialization thread (main thread). This is not in line with what users familiar with GNU/Linux or FreeBSD would expect. See for example: <a href="https://lists.rtems.org/pipermail/users/2017-July/031525.html">https://lists.rtems.org/pipermail/users/2017-July/031525.html</a>					
<b>#3244</b>	2 years ago	fixed	rtems	Sebastian Huber	Sebastian Huber	21 months ago
Summary	Change <code>rtems_panic()</code> implementation and document this function					
Description	The current <code>rtems_panic()</code> implementation is quite heavy weight. It depends on <code>_exit()</code> which calls the global destructors. It uses <code>fprintf(stderr, ...)</code> for output which depends on an initialized console device and the complex <code>printf()</code> . Introduce a new fatal source <code>RTEMS_FATAL_SOURCE_PANIC</code> for <code>rtems_panic()</code> and output via <code>printk()</code> . Document this function in Fatal Manager chapter. Replace all <code>BSP_panic()</code> with <code>rtems_panic()</code> .					
<b>#3245</b>	2 years ago	fixed	arch/powerpc	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Replace <code>BSP_panic()</code> with <code>rtems_panic()</code>					
Description	Due to a new <code>rtems_panic()</code> implementation, it is possible to replace the PowerPC-specific <code>BSP_panic()</code> with <code>rtems_panic()</code> . Remove <code>BSP_panic()</code> implementations.					
<b>#3246</b>	2 years ago	fixed	arch/powerpc	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove <code>_BSP_fatal_error()</code>					
Description	BSPs can use the <code>bsp_fatal_extension()</code> to provide BSP-specific fatal error handling. There is no need for a <code>_BSP_fatal_error()</code> .					
<b>#3247</b>	2 years ago	fixed	build	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove BSP-specific defaults for <code>RTEMS_BSP_CLEANUP_OPTIONS()</code>					
Description	Remove BSP-specific defaults for <code>RTEMS_BSP_CLEANUP_OPTIONS()</code> to simplify the BSP configuration and documentation. Change default to: <code>BSP_PRESS_KEY_FOR_RESET=0 BSP_RESET_BOARD_AT_EXIT=1 BSP_PRINT_EXCEPTION_CONTEXT=1</code>					
<b>#3248</b>	2 years ago	fixed	build	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add <code>BSP_VERBOSE_FATAL_EXTENSION</code> to <code>RTEMS_BSP_CLEANUP_OPTIONS</code>					
Description	Add <code>BSP_VERBOSE_FATAL_EXTENSION</code> to <code>RTEMS_BSP_CLEANUP_OPTIONS</code> to optionally print the RTEMS version, the fatal source and the fatal code in the shared <code>bsp_fatal_extension()</code> .					
<b>#3249</b>	2 years ago	fixed	arch/arm	Joel Sherrill	Sebastian Huber	2 years ago
Summary	imx7 does not link <code>getentropy01</code> test on master					
Description	<pre>arm-rtems5-gcc -B./..../imx7/lib/ -specs bsp_specs -qrtems -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a7 -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -Wl,-gc-sections -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a7 -Wl,-wrap=printf -Wl,-wrap=puts -Wl,-wrap=putchar -o getentropy01.exe init.o init.o: In function `test_getentropy': /home/joel/rtems-work/rtems-testing/rtems/build-arm-imx7-rtems/arm-rtems5/c/imx7/testsuites/libtests/getentropy01/./..../rtems/c/src/./..../testsuites/libtests/getentropy01/init.c:57: undefined reference to `getentropy' /home/joel/rtems-work/rtems-testing/rtems/build-arm-imx7-rtems/arm-rtems5/c/imx7/testsuites/libtests/getentropy01/./..../rtems/c/src/./..../testsuites/libtests/getentropy01/init.c:59: undefined reference to `getentropy'</pre>					
<b>#3254</b>	2 years ago	fixed	build	Sebastian Huber		15 months ago
Summary	Reorganize header files to avoid "make preinstall"					
<b>#3255</b>	2 years ago	duplicate	arch/powerpc	Joel Sherrill	Sebastian Huber	2 years ago
Summary	Warnings on 64-bit targets					
Description	This occurred on the 64 bit PowerPC and SPARC64 targets. <code>log/powerpc-qoriq_e6500_64.log:./..../rtems/c/src/./..../cpukit/libmisc/rtems-fdt/rtems-fdt-shell.c:57:27: warning: cast to pointer from integer of different size [-Wint-to-pointer-</code>					



Description	removing <code>preinstall</code> exposes this. The specific issue appears with <code>irq.h</code> when building the <code>no-preinstall</code> branch. There is a PowerPC BSP family header and a number of BSPs also have an <code>irq.h</code> which overrides families header. The code has <code>#include &lt;bsp/irq.h&gt;</code> and the header used depends on the include order on the GCC command line. This is fragile for any user. These headers needs to be moved to BSP specific paths, for example <code>#include &lt;mvm3100/irq.h&gt;</code>					
#3270	2 years ago	fixed	arch/powerpc	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Remove unused support for MPC505					
Description	There is some support for MPC505 in libcpu, however, I cannot find a BSP for this code. Remove this apparently dead code.					
#3277	2 years ago	fixed	network/libbsd	Sebastian Huber	Sebastian Huber	2 years ago
Summary	QoriQ: Add MAC-less DPAA driver to libbsd					
Description	The SDK Linux DPAA driver supports a so called MAC-less interface driver. This driver allows Ethernet communication between guest systems of a hypervisor.					
#3278	2 years ago	fixed	tool	Joel Sherrill	Chris Johns	2 years ago
Summary	bsp-builder has incorrect print (%s in output)					
Description	I don't think the tools have branches so only impacts master. Notice the "run: %s:" [1114/1565] powerpc/mpc5674fevb (profiling) Configuring run: %s: powerpc/mpc5674fevb.profiling\ /home/joel/rtems-work/rtems/configure --target=powerpc-rtems5\ --enable-rtemsbsp=mpc5674fevb --prefix=/home/joel/rtems-work/bsps\ --enable-profiling					
#3281	2 years ago	wontfix	tool/gdb	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add epiphany support to GDB 8.0.0					
#3283	2 years ago	fixed	doc	Joel Sherrill	Chris Johns	2 years ago
Summary	Bad URL in OpenOCD/Xilinx_Zynq Wiki Page					
Description	<a href="https://devel.rtems.org/wiki/Debugging/OpenOCD/Xilinx_Zynq">https://devel.rtems.org/wiki/Debugging/OpenOCD/Xilinx_Zynq</a> has a link to the Zedboard Processor Debug Adapter. I think the URL has changed to this but would like someone more knowledgeable to confirm that before it is changed. <a href="http://zedboard.org/accessories/zedboard-processor-debug-adapter">http://zedboard.org/accessories/zedboard-processor-debug-adapter</a>					
#3284	2 years ago	fixed	tool/rsb	Sebastian Huber	Sebastian Huber <sebastian.huber@...>	2 years ago
Summary	RSB uses hard coded GCC binary paths					
Description	In order to build a tool chain with Ada support you need a native GCC with Ada support of the same version as the cross compiler. The RSB uses hard coded paths for the gcc and g++ programs: <pre>source-builder/defaults.mc: __cc:      exe,   required, '/usr/bin/gcc' source-builder/defaults.mc: __cxx:    exe,   required, '/usr/bin/g++'</pre> So, the RSB user must change the main GCC installation of the machine to build a particular RTEMS tool chain. This is undesired/infeasible in most situations.					
#3285	2 years ago	fixed	build	Sebastian Huber	Sebastian Huber	19 months ago
Summary	Reorganize BSP source directory					
Description	Now, that all BSP header files are in <ul style="list-style-type: none"> <li>bsps/include</li> <li>bsps/@RTEMS_CPU@/include</li> <li>bsps/@RTEMS_CPU@/@RTEMS_BSP_FAMILY@/include</li> </ul> we should also move the BSP sources to this new directory tree. How do we want to organize the BSP sources in bsp/@RTEMS_CPU@/@RTEMS_BSP_FAMILY@? <ul style="list-style-type: none"> <li>include (this is already there, see <a href="#">#3254</a>)</li> <li>config <ul style="list-style-type: none"> <li>somebsp.cfg</li> </ul> </li> <li>start (everything required to run a minimal application without devices) <ul style="list-style-type: none"> <li>start.S</li> <li>bspstart.c</li> <li>bspmp.c</li> <li>linkcmds</li> </ul> </li> <li>cache (everything for the cache controller support)</li> <li>irq (everything for the interrupt controller support)</li> <li>console (everything for the console driver)</li> <li>clock (everything for the clock driver)</li> <li>i2c (everything for the I2C driver)</li> <li>spi (everything for the SPI driver)</li> <li>net (legacy network stack drivers)</li> <li>mpci (RTEMS_MULTIPROCESSING support)</li> <li>rtc (everything for the RTC driver)</li> <li>ata (everything for the ATA driver)</li> <li>contrib (import of external sources) <ul style="list-style-type: none"> <li>The layout of external sources should be used as is if possible.</li> </ul> </li> </ul>					
#3290	2 years ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	2 years ago
Summary	Add device tree support to Altera/Intel? Cyclone V BSP					
#3294	2 years ago	fixed	tool/rsb	Chris Johns	Chris Johns	2 years ago
Summary	gcc version report for released tools is wrong.					
Description	The release gcc version string has the RTEMS release and not the actual release.					
#3298	2 years ago	fixed	lib/dl	Chris Johns	Chris Johns	13 months ago
Summary	dlerror non-conformance					
Description	This is a port of the 4.11 patches from <a href="#">#2747</a> to <code>master</code> . Please refer to that ticket for details.					
#3305	2 years ago	fixed	arch/arm	Joel Sherrill	Joel Sherrill	2 years ago
Summary	Add paravirtualization support to ARM					
Description	The Arm port does not currently have paravirtualization support.					
#3306	2 years ago	fixed	arch/powerpc	Joel Sherrill	Joel Sherrill <joel@...>	2 years ago
Summary	Add paravirtualization support to PowerPC					
Description	The PowerPC port does not currently have paravirtualization support.					
#3307	2 years ago	fixed	arch/powerpc	Joel Sherrill	Joel Sherrill	18 months ago



Summary	PowerPC linkcmds.base missing wildcards on some sections				
Description	Some sections were missing sections. Wildcards needed to be added.				
#3309	2 years ago	fixed	doc	Chris Johns	17 months ago
Summary	rtems_task_create's initial_mode SMP update				
Description	The <code>initial_mode</code> cannot have the non-preempt flag or an interrupt level set or an RTEMS_UNSATISFIED error is returned. This is not documented in the directive.				
#3312	2 years ago	fixed	tool/rsb	Chris Johns	Chris Johns
Summary	RSB macro calls such as define fail on unicode keys.				
Description	<p>The <code>define</code> call in <code>macros.py</code> checks for a <code>str</code> while the <code>_setitem</code> call can convert a <code>unicode</code> string to <code>str</code>. Remove the check.</p> <p>Remove the other places in <code>macros.py</code> a <code>key</code> <code>str</code> check is made and see if they can be improved.</p> <p>The following has been reported to me:</p> <pre> cd rtems-source-builder-4.11.3/rtems ./source-builder/sb-set-builder --prefix=/home/user/rtems/4.11 --log=arm.txt --without-rtems 4.11/rtems-arm Traceback (most recent call last):   File "./source-builder/sb-set-builder", line 29, in &lt;module&gt;     setbuilder.run()   File "./source-builder/sb/setbuilder.py", line 526, in run     opts = options.load(sys.argv, optargs)   File "./source-builder/sb/options.py", line 668, in load     version.load_release_settings(o.defaults)   File "./source-builder/sb/version.py", line 123, in load_release_settings     sources.hash((hs[0], hash[0], hs[1]), macros, setting_error)   File "./source-builder/sb/sources.py", line 105, in hash     macros.define_file, '%s %s' % (args[0], args[2]))   File "./source-builder/sb/macros.py", line 439, in define     raise TypeError('bad key type: %s' % (type(key))) TypeError: bad key type: &lt;type 'unicode'&gt; </pre>				
#3315	2 years ago	fixed	tool/rsb	Chris Johns	Chris Johns
Summary	Move expat's home site to github from SF.				
Description	Move expat's home site from SF to github: <a href="https://libexpat.github.io/">https://libexpat.github.io/</a>				
#3318	2 years ago	fixed	bsps	mletcher	Sebastian Huber
Summary	Improve INTERNAL_ERROR_THREAD_EXITTED to show the id and thread name				
Description	<p>It might be more helpful in the case of a thread exit to output some information about that thread to make tracking it down simpler.</p> <p>This example works ok.</p> <pre> static void thread_exitted_print_info(rtems_tcb *tcb) {     printf("Thread exited: %s (id %d)\n", tcb-&gt;Object.name, tcb-&gt;Object.id) } </pre> <p>/* In your configuration: */ #define CONFIGURE_INITIAL_EXTENSIONS \ { .thread_exitted = thread_exitted_print_info }</p>				
#3320	2 years ago	fixed	dev/serial	Sebastian Huber	Sebastian Huber <sebastian.huber@...>
Summary	Add a simple task console driver				
Description	The default console driver for tests is the simple console driver. It uses a polled output via <code>rtems_putc()</code> done directly in the context of the executing thread. This is a problem for timing sensitive tests. Add a simple task console driver.				

```

.. index:: CONFIGURE_APPLICATION_NEEDS_SIMPLE_TASK_CONSOLE_DRIVER

.. _CONFIGURE_APPLICATION_NEEDS_SIMPLE_TASK_CONSOLE_DRIVER:

CONFIGURE_APPLICATION_NEEDS_SIMPLE_TASK_CONSOLE_DRIVER
-----

CONSTANT:
  ``CONFIGURE_APPLICATION_NEEDS_SIMPLE_TASK_CONSOLE_DRIVER``

DATA TYPE:
  Boolean feature macro.

```

#3323	2 years ago	fixed	lib	Chris Johns	Chris Johns	23 months ago
-------	-------------	-------	-----	-------------	-------------	---------------

Summary: <https://devel.rtems.org/issue/show/3323>  
 Description: The DEFAULT\_VALUES uses the mtime and file length and this can cause subtle issues if a target has no RTC or it is incorrect and files are being copied without preserving the mtime or changes have been made to the file. This has been fixed to use the length. The cp and untar code do not update a file's time. Add support for an etag callback so a user can manage the tag, ie MD5 or something similar. the application wishes to include the Simple Task Console Device Driver.

#3325	2 years ago	fixed	config	Sebastian Huber	Sebastian Huber	2 years ago
-------	-------------	-------	--------	-----------------	-----------------	-------------

Summary: <https://devel.rtems.org/issue/show/3325>  
 Description: Improve the scheduler configuration documentation according to user review. Do not use names derived from scheduler implementation details. Instead use names derived from the scheduler configuration or documentation. Provide defines for backward compatibility. The device driver reads via ``getchar()``.

#3327	2 years ago	fixed	score	Joel Sherrill		2 years ago
-------	-------------	-------	-------	---------------	--	-------------

Summary: <https://devel.rtems.org/issue/show/3327>  
 Description: This device driver writes into a write buffer. The count of characters written into the write buffer is returned. It might be less than the requested count, in case the write buffer is full. The write is non-blocking and may be called from an interrupt. A GPU (iint32ptr) that is required. Some of the types.h files define a CPU specific simple vectored ISR handler reads from the write buffer and outputs the characters via ``rtems\_putc()``. This task runs with the least important priority. The write buffer size is 2047 characters and it is not configurable. If unused, delete the ISR handler prototype. If used, move to cpu.h Use ``fsync(STDOUT\_FILENO)`` or ``fdatasync(STDOUT\_FILENO)`` to drain the write buffer.

#3328	2 years ago	fixed	build	Amaan Cheval		2 years ago
-------	-------------	-------	-------	--------------	--	-------------

Summary: <https://devel.rtems.org/issue/show/3328>  
 Description: bootstrap uses non-POSIX compliant echo -e. The Termios framework is not used. There is no support to change device settings, e.g. baud, stop bits, parity, etc. On certain shells, the "-e" option is not supported, and causes echo to output the flag along with the quoted text.

```

The
-> % sh
$ echo -e "foo bar"
-e foo bar
$ * ``CONFIGURE_APPLICATION_NEEDS_SIMPLE_CONSOLE_DRIVER``, and
  ``CONFIGURE_APPLICATION_NEEDS_SIMPLE_TASK_CONSOLE_DRIVER``

```

This varies by shell, and is not even consistent between sh or bash. It was introduced while removing the make preinstall stage here, and may still work on most shells, though it didn't for me on sh on Ubuntu 16.04 LTS (4.4.0-78-generic x86\_64 GNU/Linux). Configuration options are virtually resolved. A patch is attached. Reference to the POSIX standard which confirms that -n is the only argument supported. <http://pubs.opengroup.org/onlinepubs/9699919799/utilities/echo.html> Link to POSIX for printf(1): <http://pubs.opengroup.org/onlinepubs/9699919799/utilities/printf.html>

#3329	2 years ago	fixed	tool/website	Joel Sherrill	Amar Takhar	17 months ago
-------	-------------	-------	--------------	---------------	-------------	---------------

Summary: <https://devel.rtems.org/issue/show/3329>  
 Description: Trac Login Failure (bad password) Causes Internal Error  
 Behavior is as expected with a bad user name.  
 Try to login to Trac with a bad password:  
 Oops... Trac detected an internal error: ProgrammingError?: (1064, "You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'sid='joel.sherrill' AND authenticated=1 AND name='failed\_logins\_count at line 1') There was an internal error in Trac. It is recommended that you notify your local Trac administrator with the information needed to reproduce the issue. To that end, you could anonymous ProgrammingError?: (1064, "You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'sid='joel.sherrill' AND authenticated=1 AND name='failed\_logins\_count at line 1')  
 ==== How to Reproduce ====  
 While doing a POST operation on [/login](#), Trac issued an internal error.  
 (please provide additional details here)  
 Request parameters:  

```
{u'_FORM_TOKEN': u'0dc25ae350c181046ceae015',
 u'password': u'XXX',
 u'referer': u'https://devel.rtems.org/ticket/3328',
 'user_locked': False,
 'username': u'joel.sherrill'}
```

 User agent: [Mozilla/5.0 \(X11; Linux x86\\_64\) KHTML/4.14.8 \(like Gecko\) Konqueror/4.14 Fedora/4.14.8-6.el7\\_3](#)  
**System Information**  
 System information not available  
**Enabled Plugins**  
 Plugin information not available  
**Interface Customization**  
 Interface customization information not available  
**Python Traceback**

Description

```

Traceback (most recent call last):
  File "/data/src/trac/trac/web/main.py", line 620, in _dispatch_request
    dispatcher.dispatch(req)
  File "/data/src/trac/trac/web/main.py", line 220, in dispatch
    chosen_handler = self._pre_process_request(req, chosen_handler)
  File "/data/src/trac/trac/web/main.py", line 429, in _pre_process_request
    chosen_handler = filter_pre_process_request(req, chosen_handler)
  File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/api.py", line 478, in pre_process_request
    if not req.session.authenticated or \
  File "/data/src/trac/trac/web/api.py", line 491, in _getattr__
    value = self.callbacks[name](self)
  File "/data/src/trac/trac/web/main.py", line 354, in _get_session
    return Session(self.env, req)
  File "/data/src/trac/trac/web/session.py", line 243, in __init__
    if req.authname == 'anonymous':
  File "/data/src/trac/trac/web/api.py", line 491, in _getattr__
    value = self.callbacks[name](self)
  File "/data/src/trac/trac/web/main.py", line 172, in authenticate
    authname = authenticator.authenticate(req)
  File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/util.py", line 81, in wrap
    return func(self, *args, **kwds)
  File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/web_ui.py", line 395, in authenticate
    guard.failed_count(f_user, req.remote_addr)
  File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/guard.py", line 107, in failed_count
    set_user_attribute(self.env, user, key, count)
  File "/data/trac/plugins/TracAccountManager-0.5.dev0-py2.7.egg/acct_mgr/model.py", line 509, in set_user_attribute
    (value, username, attribute))
  File "/data/src/trac/trac/db/util.py", line 128, in execute
    cursor.execute(query, params if params is not None else [])
  File "/data/src/trac/trac/db/util.py", line 72, in execute
    return self.cursor.execute(sql_escape_percent(sql), args)
  File "/usr/local/lib/python2.7/site-packages/MySQLdb/cursors.py", line 205, in execute
    self.errorhandler(self, exc, value)
  File "/usr/local/lib/python2.7/site-packages/MySQLdb/connections.py", line 36, in defaulterrorhandler
    raise errorclass, errorvalue
    
```

#3334	2 years ago	fixed	posix	Joel Sherrill	Stavros Paspas	Sebastian Huber	13 months ago
Summary	ProgrammingError: 11054. "You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'deadlock in once()' at line 1") Create a ticket.						

RTEMS is not getting locked up when using certain c++ functionality. Issue happens for example when std::future is combined with std::async. Inverting the order seems like this happens if std::async executes before std::future gets scheduled to run. Both of these create a pthread\_once instance. \_once() uses a common semaphore for all calls, thus the first function (async.get usually) gets the lock, calls its "init" function (which blocks until the second function has completed. After this, std::future also uses pthread\_once to execute, but because the lock is already taken, it also blocks, causing a deadlock.

Attached you can find a test application that reproduces the deadlock.

#3339	2 years ago	fixed	arch/powerpc	Joel Sherrill		Sebastian Huber <sebastian.huber@...>	2 months ago
Summary	Several PowerPC linker commands do not support constructors/destructors with priority						

This BSP shouldn't have trouble linking any of the tests so I was surprised at this failure.

```

gmake[6]: Entering directory `/data/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemuppc-rtems/powerpc-rtems5/c/qemuppc/testsuites/sptests/spgglobalcon02' powerpc-rtems5-gcc -mcpu=603e -Dppc603e -O2 -g -fno-keep-inline-functions -mcpu=603e -Dppc603e -B/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemuppc-rtems/powerpc-rtems5/c/qemuppc/lib/libbsp/powerpc/qemuppc -B/home/joel/rtems-work/rtems-testing/rtems/rtems/c/src/lib/libbsp/powerpc/qemuppc/startup/ -specs bsp_specs -qrtems -L./.././../qemuppc/lib -L/home/joel/rtems-work/rtems-testing/rtems/rtems/c/src/lib/libbsp/powerpc/shared/startup -Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -o spgglobalcon02.exe init. /data/home/joel/rtems-work/tools/5/bin/./lib/gcc/powerpc-rtems5/7.3.0/./.././../powerpc-rtems5/bin/ld: section .ctors.64535 LMA [00000000ffc19780,00000000ffc19783] overlaps section .sdata LMA [00000000ffc19780,00000000ffc19807] collect2: error: ld returned 1 exit status gmake[6]: * [spgglobalcon02.exe] Error 1 gmake[6]: Leaving directory `/data/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemuppc-rtems/powerpc-rtems5/c/qemuppc/testsuites/sptests/spgglobalcon02' gmake[5]: * [spgglobalcon02] Error 2
    
```

#3340	2 years ago	fixed	arch/powerpc	Joel Sherrill		Sebastian Huber	2 years ago
Summary	gen83xx warning for macros redefined						

```

log/powerpc-hsc_cm01.log:/home/joel/rtems-work/rtems-testing/rtems/rtems/bsps/powerpc/gen83xx/include/bsp/hwreg_vals.h:244:0: warning: "FPGA_START" redefined log/powerpc-hsc_cm01.log:/home/joel/rtems-work/rtems-testing/rtems/rtems/bsps/powerpc/gen83xx/include/bsp/hwreg_vals.h:246:0: warning: "FPGA_SIZE" redefined

Looking at the code, it is pretty clear that the macros are redefined. Unfortunately one of the three has a different value the second time:

=====
/* fpga BCSR register */ #define FPGA_START 0xF8000000 #define FPGA_SIZE 0x8000 #define FPGA_END (FPGA_START+FPGA_SIZE-1)

/*
 * working values for various registers, used in start/start.S */

/* fpga config 16 MB size */ #define FPGA_CONFIG_START 0xF8000000 #define FPGA_CONFIG_SIZE 0x01000000 /* fpga register 8 MB size */ #define FPGA_REGISTER_START 0xF9000000 #define FPGA_REGISTER_SIZE 0x00800000 /* fpga fifo 8 MB size */ #define FPGA_FIFO_START 0xF9800000 #define FPGA_FIFO_SIZE 0x00800000

#define FPGA_START (FPGA_CONFIG_START) fpga window size 32 MByte #define FPGA_SIZE (0x02000000) #define FPGA_END (FPGA_START+FPGA_SIZE-1)
=====
    
```

#3341	2 years ago	fixed	arch/sparc64	Joel Sherrill		Gedare Bloom	2 years ago
Summary	sparc64: Macro Redefined						

log/sparc64-usiii.log:/home/joel/rtems-work/rtems-testing/rtems/rtems/bsps/sparc64/include/arch/stack.h:56:0: warning: "STACK\_BIAS" redefined

This is defined in two header files with the same value. Not sure what the proper fix is.

#3342	2 years ago	fixed	posix	Joel Sherrill		Joel Sherrill	20 months ago
Summary	pthread_setschedparam() has incorrect prototype						

We are missing the const on the third parameter. This requires a change to newlib and RTEMS. The correct prototype is:

```

int pthread_setschedparam(
    pthread_t thread, int policy, const struct sched_param *param
)
    
```

#3343	2 years ago	fixed	posix	Joel Sherrill		Joel Sherrill	20 months ago
Summary	pthread_mutex_getprioceiling() has incorrect prototype						

We are missing the const and restrict on the first parameter. This requires a change to newlib and RTEMS. The correct prototype is:

```

int pthread_mutex_getprioceiling(
    const pthread_mutex_t *restrict mutex, int *prioceiling
)
    
```

#3344	2 years ago	fixed	arch/m68k	Joel Sherrill		Joel Sherrill	2 years ago
Summary	mcf5272/mcf5272.h Timer3 Duplicate Definition						

y Descripti on	This .h file uses the same macro names for two blocks of INT macros. My assumption given that the second looks to be a different INT, is that it should not be INT3 again but INT3. --- a/bbps/m68k/include/mcf5272/mcf5272.h +++ b/bbps/m68k/include/mcf5272/mcf5272.h @@ -88,9 +88,9 @@ #define MCF5272_ICR1_INT3_PI (bit(23)) #define MCF5272_ICR1_INT3_IPL(x) ((x) << 20) #define MCF5272_ICR1_INT3_MASK ((7) << 20) -#define MCF5272_ICR1_INT3_PI (bit(19)) -#define MCF5272_ICR1_INT3_IPL(x) ((x) << 16) -#define MCF5272_ICR1_INT3_MASK ((7) << 16) +#define MCF5272_ICR1_INT4_PI (bit(19)) +#define MCF5272_ICR1_INT4_IPL(x) ((x) << 16) +#define MCF5272_ICR1_INT4_MASK ((7) << 16)	#3345	2 years ago	fixed	arch/powerpc	Joel Sherrill	Joel Sherrill	2 years ago	
Summar y	mvme3100 spaces needed around quote in macro definitions in bsp.h								
Descripti on	Various BSP_I2c_XXX_DEV_NAME macros have a stray " at the end of the first parameter.								
#3346	2 years ago	fixed	arch/bfin	Joel Sherrill	Joel Sherrill			2 years ago	
Summar y	bf533.h								
Descripti on	TIMER_STATUS, TIMER< DISABLE, and TIMER_ENABLE are defined in bf52x.h and in bf533.h. Disable second definition in full bf533 register set list and add a sanity check to ensure it stays the same. In file included from /home/joel/rtems-work/rtems-testing/rtems/rtems/bbps/bfin/TLL6527M/include/bsp.h:28:0, from .././.././../rtems/c/src/libchip/display/disp_hcms29xx.c:26: /home/joel/rtems-work/rtems-testing/rtems/rtems/bbps/bfin/include/bf52x.h:43:0: warning: "TIMER_STATUS" redefined #define TIMER_STATUS 0xffc00648								
#3348	2 years ago	fixed	arch/powerpc	Joel Sherrill	Joel Sherrill			2 years ago	
Summar y	beatnick:spaces needed around quote in macro definitions in bsp.h								
Descripti on	Macros need spaces around ", "								
#3349	2 years ago	fixed	arch/i386	Joel Sherrill	Joel Sherrill			2 years ago	
Summar y	pc386 edid.h invalid macro names								
Descripti on	Minus sign not underbar in macro name. -#define DVS_HDMI-a 0x2 -#define DVS_HDMI-b 0x3 +#define DVS_HDMI_a 0x2 +#define DVS_HDMI_b 0x3								
#3350	2 years ago	fixed	rtems	Joel Sherrill	Sebastian Huber			2 years ago	
Summar y	sptimecounter02 warning due to defining _KERNEL and disabling part of <sys/time.h>								
Descripti on	The bottom of <sys/time.h> is protected by ifndef _KERNEL where gettimeofday() is prototyped. sptimecounter02 is the only test which trips this. In file included from /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/confdefs.h:323:0, from .././.././../rtems/c/src/./../testsuites/sptests/sptimecounter02/init.c:268: /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/imfs.h: In function 'IMFS_update_atime': /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/imfs.h:345:3: warning: implicit declaration of function 'gettimeofday' [-Wimplicit-function-declaration] gettimeofday( &now, 0 );								
#3352	2 years ago	fixed	arch/arm	Joel Sherrill	Sebastian Huber			2 years ago	
Summar y	Warning in all lpc176x variants								
Descripti on	bbps/arm/lpc176x/include/bsp.h defines OPERATION_COUNT in an attempt to override the autoconf generated constant. This conflicts and results in this warning: /home/joel/rtems-work/rtems-testing/rtems/rtems/bbps/arm/lpc176x/include/bsp.h:42:0: warning: "OPERATION_COUNT" redefined I understand why this is lowered by the BSP but the mechanism used is not good. And if the include file order is different between tests, you could get the BSP value or the autoconf generated value based on the order. This warning needs to be fixed and a safer mechanism for a BSP to override OPERATION_COUNT defined. My first suggestion is to use BSP_OPERATION_COUNT and add logic to one of the common test .h files to undef OPERATION_COUNT and redefine it to BSP_OPERATION_COUNT if it is defined. A safer option might be to change the name of the autoconf generated variable to OPERATION_COUNT_DEFAULT and rely on logic in a common test support .h to define OPERATION_COUNT to OPERATION_COUNT_DEFAULT or BSP_OPERATION_DEFAULT.								
#3354	2 years ago	fixed	arch/powerpc	Joel Sherrill	Joel Sherrill			2 years ago	
Summar y	PowerPC BSPs duplicate PAGE_MASK, etc redefinition								
Descripti on	The following BSPs: powerpc-beatnik powerpc-mcp750 powerpc-mtx603e powerpc-mvme2100 powerpc-mvme2307 powerpc-mvme5500 powerpc-qemuprep-altivec powerpc-qemuprep use bbps/powerpc/include/libcpu/page.h which defines _ALIGN, PAGE_MASK, and PAGE_SIZE. These are defined by <machine/param.h>. I think the solution is to delete the versions in libcpu/page.h. Comments appreciated. ===== In file included from .././.././../rtems/c/src/lib/libbsp/powerpc/mvme5500/./../powerpc/shared/startup/pgtbl_setup.c:3:0: /home/joel/rtems-work/rtems-testing/rtems/rtems/bbps/powerpc/include/libcpu/page.h:22:0: warning: "PAGE_MASK" redefined #define PAGE_MASK ~(PAGE_SIZE-1) In file included from /data/home/joel/rtems-work/tools/5/powerpc-rtems5/include/sys/_cpuset.h:36:0, from /data/home/joel/rtems-work/tools/5/powerpc-rtems5/include/sys/cpuset.h:45, from /data/home/joel/rtems-work/tools/5/powerpc-rtems5/include/sys/_pthreadtypes.h:24, from /data/home/joel/rtems-work/tools/5/powerpc-rtems5/include/sys/types.h:239, from /data/home/joel/rtems-work/tools/5/powerpc-rtems5/include/sys/time.h:43, from /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/score/timestamp.h:43, from /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/score/thread.h:36, from /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/score/heap.h:22, from /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems/rtems/types.h:26, from /home/joel/rtems-work/rtems-testing/rtems/rtems/cpukit/include/rtems.h:31, from .././.././../rtems/c/src/lib/libbsp/powerpc/mvme5500/./../powerpc/shared/startup/pgtbl_setup.c:1: /data/home/joel/rtems-work/tools/5/powerpc-rtems5/include/machine/param.h:70:0: note: this is the location of the previous definition #define PAGE_MASK (PAGE_SIZE - 1)								
#3358	2 years ago	fixed	lib/block	Sebastian Huber	Sebastian Huber			15 months ago	
Summar y	Deprecate rtems_disk_create_phys(), etc.								
Descripti on	There are currently two implementations of a block device (disk). Deprecate the legacy rtems_disk_create_phys(), etc. implementation. Remove all RTEMS internal uses except in the block01 test. Add RTEMS_DEPRECATED attribute to API.								
#3374	2 years ago	fixed	tool	Joel Sherrill	Chris Johns			17 months ago	
Summar y	rtems-test does not honor --mail-from argument								
	This is on the master but may apply to other branches.								

Descripti on \$ /home/joel/rtems-work/rtems-tooltester/rtems-test --rtems-tools=/home/joel/rtems-work/tools/5 --rtems-bsp=erc32 --log=run.log --mail --mail-from=joel@... --mail-to=build@...  
 .sparc-rtems5/c/erc32/testsuites/samples/base\_sp/base\_sp.exe error: no valid from address for mail

The rtems-test command will work if you have a ~/.mailrc with something like this:

#3375	2 years ago	fixed	tool	Sebastian Huber	Sebastian Huber	17 months ago
-------	-------------	-------	------	-----------------	-----------------	---------------

Summary Remove command line pre-processor defines

Command line defines defined by the build system make it difficult get a consistent view of the sources from other entities, e.g. static code analysis, code editors and reviews.

Command line defines are currently used here:

```
c/src/lib/libbsp/mips/hurricane/Makefile.am:libbsp_a_CPPFLAGS = $(AM_CPPFLAGS) -DRM52XX
c/src/lib/libbsp/mips/rbt4938/Makefile.am:libbsp_a_CPPFLAGS = $(AM_CPPFLAGS) -DTX49
c/src/lib/libbsp/mips/jmr3904/Makefile.am:libbsp_a_CPPFLAGS = $(AM_CPPFLAGS) -DTX39
cpukit/pppd/Makefile.am:libpppd_a_CPPFLAGS = $(AM_CPPFLAGS) -D_BSD_VISIBLE -I$(srcdir)/../libmd
cpukit/libfs/Makefile.am:libjffs2_a_CPPFLAGS += -D_ECOS
cpukit/libfs/Makefile.am:libjffs2_a_CPPFLAGS += '-DKBUILD_MODNAME="JFFS2"'
cpukit/mghttpd/Makefile.am:# libmghttpd_a_CPPFLAGS += -DHAVE_MD5
cpukit/mghttpd/Makefile.am:libmghttpd_a_CPPFLAGS += -DNO_SSL -DNO_POPEN -DNO CGI -DUSE_WEBSOCKET
cpukit/librpc/Makefile.am:librpc_CPPFLAGS = -D_RPC_read=read -D_RPC_write=write -D_RPC_close=close \
cpukit/libnetworking/Makefile.am:libnetworking_CPPFLAGS = -DINET -DNFS \
cpukit/libnetworking/Makefile.am:libnetworking_CPPFLAGS = -DNO_POLL -DNO_SELECT -D_BSD_VISIBLE -D_THREAD_SAFE
cpukit/libnetworking/Makefile.am:libnetworking_CPPFLAGS = -DNO_POLL -DNO_SELECT
cpukit/libnetworking/Makefile.am:libnetworking_CPPFLAGS = $(AM_CPPFLAGS) $(libnetworking_CPPFLAGS) -D_BSD_VISIBLE
cpukit/libidl/Makefile.am:libidl_a_CPPFLAGS = $(AM_CPPFLAGS) -DRTEMS_RTL_RAP_LOADER=1 -DRTEMS_RTL_ELF_LOADER=1
```

#3376	2 years ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
-------	-------------	-------	------	-----------------	-----------------	---------------

Summary Remove cklength program

The cklength program (tools/build/cklength.c) has no license information and is unused in the RTEMS build. General usability is questionable, for example a

```
awk 'length($0) > 80' < file
```

performs a similar task. Remove it.

#3377	2 years ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
-------	-------------	-------	------	-----------------	-----------------	---------------

Summary Remove eolstrip program

The eolstrip program (tools/build/eolstrip.c) has no license information and is unused in the RTEMS build. General usability is questionable, for example a

```
sed -i 's/[[:space:]]*$/' file
```

performs a similar task. Remove it.

#3378	2 years ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
-------	-------------	-------	------	-----------------	-----------------	---------------

Summary Remove unhex program

The unhex program (tools/build/unhex.c) has no license information and is unused in the RTEMS build. Users of HEX files should consider to use ELF instead. Remove it.

#3379	2 years ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
-------	-------------	-------	------	-----------------	-----------------	---------------

Summary Remove packhex program

The packhex program ( tools/build/packhex.c) is exported to the standard RTEMS build infrastructure via the PACKHEX variable. It is used by some legacy BSPs. It as unclear license information:

```
***** P A C K H E X . C *****
*
* Packhex is a hex-file compaction utility. It attempts to concatenate
* hex records to produce more size-efficient packaging.
*
* Limitations: Input files must be correctly formatted. This utility
* is not robust enough to detect hex-record formatting
* errors.
*
* Published: May 1993 Embedded Systems Programming magazine
* "Creating Faster Hex Files"
*
* URL: ESP magazine: http://www.embedded.com
* Source Code: ftp://ftp.mfi.com/pub/espmag/1993/pakhex.zip
*
* Author: Mark Gringrich
*
* Compiler: Microsoft C 6.0
* cl /F 1000 packhex.c
*
*****
```

Move it to rtems-tools.

#3380	2 years ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
-------	-------------	-------	------	-----------------	-----------------	---------------

Summary Move rtems-bin2c program to rtems-tools

The rtems-bin2c program (tools/build/rtems-bin2c.c) is exported to the standard RTEMS build infrastructure via the BIN2C variable. Move it to rtems-tools.

#3382	2 years ago	fixed	build	Chris Johns	Chris Johns	17 months ago
-------	-------------	-------	-------	-------------	-------------	---------------

Summary Testsuite Makefile merge to one per group of tests

Merge the nested Makefile.am files into a single file per group of tests.

A single Makefile.am for all tests is not practical at this point in time because a test is an estimated 7 lines and with over 750 tests this means the file would be too big and a conflict hot spot.

#3383	2 years ago	fixed	build	Chris Johns	Chris Johns	2 years ago
-------	-------------	-------	-------	-------------	-------------	-------------

Summary Require --enable-rtemsbsp with --enable-smp or --enable-multiprocessor

Summary	There is a limited number of BSPs that support SMP or MP so using the BSP wildcard will result in a failed build. Require the user provide a BSP.					
#3384	2 years ago	fixed	tool/gcc	Sebastian Huber	Sebastian Huber	3 months ago
Summary	Prefer int for int32_t					
Description	<p>Common systems like Linux and FreeBSD define int32_t to int. This means a lot of third party code works well in these cases:</p> <pre>#include &lt;stdint.h&gt;  void f(int32_t);  void f(int);  void g(int32_t *);  void h(void) {     int i;     g(&amp;i); }</pre> <p>On RTEMS you get however in C</p> <pre>test.c:5:6: error: conflicting types for 'f' void f(int); ^ test.c:3:6: note: previous declaration of 'f' was here void f(int32_t); ^ test.c: In function 'h': test.c:12:4: warning: passing argument 1 of 'g' from incompatible pointer type [-Wincompatible-pointer-types]     g(&amp;i);     ^ test.c:7:6: note: expected 'int32_t * {aka long int *}' but argument is of type 'int *' void g(int32_t *); ^</pre> <p>and C++</p> <pre>test.c: In function 'void h()': test.c:12:4: error: invalid conversion from 'int*' to 'int32_t* {aka long int*}' [-fpermissive]     g(&amp;i);     ^~ test.c:7:6: note: initializing argument 1 of 'void g(int32_t*)' void g(int32_t *); ^</pre> <p>This is due to a Newlib speciality which uses long for int32_t if long is a 32-bit type. To ease the use of third party software in RTEMS we should override this option and use int for int32_t just like the standard host operating systems (e.g. Linux and FreeBSD). Only a small GCC patch is required to do this:</p> <pre>diff --git a/gcc/config/rtems.h b/gcc/config/rtems.h index 439199d4cbb..9b1408efe6f 100644 --- a/gcc/config/rtems.h +++ b/gcc/config/rtems.h @@ -48,3 +48,7 @@  -latomic -lc -lgcc --end-group %!{!qno!linkcmds: -T linkcmds%s}}}"  #define TARGET_POSIX_IO + +/* Use int for int32_t (see stdint-newlib.h). */ +#undef STDINT_LONG32 +#define STDINT_LONG32 0</pre>					
#3385	2 years ago	fixed	build	Chris Johns	Chris Johns	2 years ago
Summary	Generate an error if RTEMS's gcc is not found when the user runs configure					
Description	Generate an error when the user runs configure if one cannot be found in the path.					
#3386	2 years ago	invalid	admin	Chris Johns	Amar Takhar	17 months ago
Summary	Trac's git changeset browsing is suspect.					
Description	<p>It is critical this interface works because we have moved to Trac for release notes and the release notes contain links to the <a href="#">changesets</a> because we reference the tickets in the commits.</p> <p>Some requests work:</p> <ol style="list-style-type: none"> <li>900c40730dbec34cd7a6f1c03c80896951bf1b9c/rtems</li> <li>d8de6b9dbe4ab1ef375ecce55e8bfb1028c5dd13/rtems</li> <li>9704efb4ec088a472842cbc9bc46392685ebc806/rtems</li> </ol> <p>and others do not:</p> <ol style="list-style-type: none"> <li>2afb22b7e1ebcbe40373ff7e0efae7d207c655a9/rtems</li> </ol> <p>Notes:</p> <ul style="list-style-type: none"> <li>items 2. and 3. are either side of the changeset a. in the commit history of RTEMS.</li> <li>Clicking on 3. and then the <a href="#">Next Changeset</a> link also fails.</li> </ul>					
#3387	2 years ago	wontfix	build	Chris Johns	Sebastian Huber	3 months ago
Summary	Add subdir-objects to automake flags					
Description	This will be fixed by the new build system, see <a href="#">#3818</a> .					
#3389	23 months ago	fixed	config	Joel Sherrill		17 months ago
Summary	Warning flags have disappeared with recent autoconf changes					
Description	As of March 30, the compiler invocations had warnings flags. As of today (4/11), there are no warnings flag on most of the compiler invocations. Something has been lost in the updates.					
#3390	23 months ago	fixed	network/legacy	Sebastian Huber	Sebastian Huber	23 months ago
Summary	NFS: Remove support for cexp					
Description	<p>There is some support for cexp and tests in the NFS client directory:</p> <pre>cpukit/libfs/src/nfsclient/src/cexp.c cpukit/libfs/src/nfsclient/src/dirutils.c cpukit/libfs/src/nfsclient/src/nfs.modini.c cpukit/libfs/src/nfsclient/src/nfsTest.c</pre>					

cpuikit/libfs/src/nfsclient/src/rpcio.modini.c						
Description	There are also some *.rel files installed. This stuff is probably unused. If it is still in use it should move elsewhere, e.g. some general cexp support outside of the main RTEMS sources. Dead/untested code should not be present in the RTEMS code base.					
	See also:					
	<a href="https://lists.rtems.org/pipermail/users/2018-April/032182.html">https://lists.rtems.org/pipermail/users/2018-April/032182.html</a>					
#3392	23 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	23 months ago
Summary	infinite loop in RSB's path when a prefix path is not writable					
Description	The code gets the <code>dirname()</code> of the path stepping up until there is no path however <code>dirname('/')</code> is <code>/</code> so the path never has a length of <code>0</code> .					
#3395	23 months ago	fixed	tool	Chris Johns	Chris Johns	23 months ago
Summary	rtems-ld does not remove executable when there is an output error					
Description	An error when outputting an executable does not clean up the file and leaves an incorrect format file. This is happening with the beagle bone black BSP and test dl06.					
#3396	23 months ago	fixed	tool	Chris Johns	Chris Johns	23 months ago
Summary	rtems-ld does not handle R_ARM_V4BX relocation records					
Description	The R_ARM_V4BX does not have a symbol and this raised an error with dl06 with a ARMv7 instruction set when merging sections when creating a RAP image. Ignore this relocation record.					
#3397	23 months ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	23 months ago
Summary	The register keyword is deprecated in C++11					
Description	The following code gives a warning with GCC and <code>-std=c++17</code> :					
	<pre>void f(void) {     register int i; }</pre>					
	<pre>test.cc: In function 'void f()': test.cc:3:15: warning: ISO C++1z does not allow 'register' storage class specifier [-Wregister]     register int i;     ^</pre>					
	Remove the use of the register keyword at least in the public header files for C++ compatibility.					
#3401	23 months ago	fixed	tool	Joel Sherrill	chrisj@...	17 months ago
Summary	dl06: tms570* Mixed LSB/MSB Error					
Description	<pre>ld-arm-tms570ls3137_hdk-rtems/arm-rtems5/c/tms570ls3137_hdk/testsuites/libtests/ rtems-ld -r /home/joel/rtems-work/rtems-testing/rtems/build-arm-tms570ls3137_hdk-rtems/arm-rtems5/c/tms570ls3137_hdk -O rap -b dl06.pre -e rtems_main -s \ -o dl06.rap dl06-o1.o dl06-o2.o -lm error: elf.check_file: /data/home/joel/rtems-work/tools/5/bin/./lib/gcc/arm-rtems5/7.3.0/././././arm-rtems5/lib/libc.a:lib_a_Exit.o@23760: Mixed data types not allowed (LSB/MSB).</pre>					
#3402	23 months ago	fixed	tool	Joel Sherrill	chrisj@...	17 months ago
Summary	dl06: mips hurricane Mixed Endian Error					
Description	<pre>Also occurs on rbt4925 and rbt4938 rtems-ld -r /home/joel/rtems-work/rtems-testing/rtems/build-mips-hurricane-rtems/mips-rtems5/c/hurricane -O rap -b dl06.pre -e rtems_main -s \ -o dl06.rap dl06-o1.o dl06-o2.o -lm error: elf.check_file: /data/home/joel/rtems-work/tools/5/bin/./lib/gcc/mips-rtems5/7.3.0/././././mips-rtems5/lib/libc.a:lib_a_Exit.o@23298: Mixed data types not allowed (LSB/MSB).</pre>					
#3403	23 months ago	fixed	tool/rsb	Sebastian Huber	Sebastian Huber	23 months ago
Summary	RSB RTEMS tool set build is irreproducible					
Description	The RTEMS 5 tool set contains the RTEMS tools (rtems-tools). The version of the RTEMS tools is determined by the tool set build time since the current Git master branch is fetched. Instead use an explicit RTEMS tools version (similar to all other tools, e.g. Binutils, Newlib, GCC, GDB) to make the RTEMS tool set independent of the arbitrary build time.					
#3407	23 months ago	fixed	tool	Joel Sherrill		17 months ago
Summary	Move Gaisler.org and Gaisler.se hosted RSB patches to rtems.org					
Description	Jiri has suggested that the patches used in the RSB that are hosted by him be moved to rtems.org and the RSB patches link be changed. This impacts at least qemu.					
#3409	23 months ago	wontfix	build	Sebastian Huber	Sebastian Huber	3 months ago
Summary	Strip down configure checks to the bare minimum					
Description	There are a lot of configure checks which produce <code>HAVE_*</code> defines which are no longer used or superfluous since we demand a recent Newlib version anyway.					
#3410	23 months ago	fixed	arch/i386	Sebastian Huber	Sebastian Huber	23 months ago
Summary	Remove bin2boot program used by i386 BSPs					
Description	For which boot loader is this? Can it be removed? The sources have no copyright information.					
#3411	23 months ago	fixed	arch/powerpc	Joel Sherrill	Sebastian Huber	23 months ago
Summary	qemuppc does not install linkcmds.base					
Description	examples-v2 fail to compile qemuppc because linkcmds.base is not installed. They build OK for sparc/erc32. This must be a minor glitch from the build system changes.					
#3413	23 months ago	fixed	arch/powerpc	Joel Sherrill	Sebastian Huber	3 months ago
Summary	examples-v2 both_hello and triple_period fail to build					
Description	examples-v2 doesn't build for qemuppc. both_hello fails because of something going on with rtems-ld. Taking that out of the wscript results in getting further but fails with an undefined error for the same symbol.					
Description	<pre>/home/joel/rtems-work/tools/5/bin/powerpc-rtems5-gcc: hello-deep.o: In function `wrapThread_Life_action_handler': /home/joel/rtems-work/tools/5/bin/powerpc-rtems5-gcc: /home/joel/rtems-work/examples-v2/build/powerpc-rtems5-qemuppc/ hello-deep.c:1304: undefined reference to `Thread_Life_action_handler' /home/joel/rtems-work/tools/5/bin/powerpc-rtems5-gcc: collect2: error: ld returned 1 exit status error: linking: Linker error</pre>					
#3415	23 months ago	fixed	admin	Joel Sherrill	Chris Johns	17 months ago
Summary	Add examples and tests as components					

Descripti on	It seems as if we should have tests and examples as components.					
<b>#3416</b>	23 months ago	fixed	tool	Joel Sherrill	Joel Sherrill <joel@...>	3 months ago
Summar y	Update Ubuntu RSB Instructions for 17.10					
Descripti on	The command in 3.1.5 of the RSB guide for Ubuntu seems to work for 17.10 but on at least one system gives the error: Error :: You must put some 'source' URIs in your sources.list A description of how to address this is at: <a href="https://askubuntu.com/questions/496549/error-you-must-put-some-source-uris-in-your-sources-list">https://askubuntu.com/questions/496549/error-you-must-put-some-source-uris-in-your-sources-list</a> Perhaps this would be useful info to update the RSB guide with (updated Ubuntu works + hint)					
<b>#3417</b>	22 months ago	fixed	tool	Chris Johns	Chris Johns	17 months ago
Summar y	Add libdwf to elftoolchain and provide a C++ wrapper					
Descripti on	Update the elftoolchain and add libdwf. Provide a C++ framework to create reusable access to libdwf.					
<b>#3418</b>	22 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	22 months ago
Summar y	Remove difftest and sorttimes test tools					
Descripti on	Evaluation of test results and report generation should move to somewhere else, e.g. the RTEMS tester.					
<b>#3419</b>	22 months ago	fixed	network/legacy	Sebastian Huber	Sebastian Huber	22 months ago
Summar y	Always build network services (tftps, ftpfs, ftpd, telnetd, libdebugger)					
Descripti on	Always build network services (tftps, ftpfs, ftpd, telnetd, libdebugger) which only depend on the POSIX socket API (provided by Newlib header files) as support libraries. Remove them from libbsd. The network services must reside in dedicated libraries to avoid a cyclic dependency between libbsd.a and librtemscpu.a.					
<b>#3421</b>	22 months ago	wontfix	admin	Joel Sherrill	chrisj@...	17 months ago
Summar y	New Trac components for Coverage and Trace					
Descripti on	Both coverage and tracing are large enough areas that lumping them into tools or other random categories makes work on them harder to trac. Please add coverage and tracing. Coverage could be a subcategory of tools.T Tracing could be a standalone component. It has target and tool components.					
<b>#3423</b>	22 months ago	duplicate	admin	Joel Sherrill		22 months ago
Summar y	examples-v2: m68k/powerpc BSPs undefined reference to _Thread_Life_action_handler					
Descripti on	fat_ramdisk is failing to link on multiple m68k and powerpc BSPs. Errors below the list of BSPs m68k-av5282 m68k-gen68340 m68k-gen68360 m68k-gen68360_040 m68k-mcf5206elite m68k-mcf52235 m68k-mcf5225x m68k-mcf5235 m68k-mcf5329 m68k-mrm332 m68k-pgh360 m68k-uC5282 powerpc-mpc8260ads powerpc-qemuppc powerpc-qoriq_e6500_64 powerpc-ss555 [20/20] Processing rtrace: build/m68k-rtems5-av5282/filesystem/fat_ramdisk/init.c.4.o build/m68k-rtems5-av5282/filesystem/fat_ramdisk/fs-root.tar.c.4.o -> build/m68k-rtems5-av5282/filesystem/fat_ramdisk/fat_ramdisk.texe /home/joel/rtems-work/tools/5/bin/m68k-rtems5-gcc: /tmp/cclRjaaa.o: In function `__wrap__Thread_Life_action_handler': /home/joel/rtems-work/tools/5/bin/m68k-rtems5-gcc: /tmp/cckrhaaa.c:1248: undefined reference to `__Thread_Life_action_handler' /home/joel/rtems-work/tools/5/bin/m68k-rtems5-gcc: collect2: error: ld returned 1 exit status error: linking: Linker error					
<b>#3424</b>	22 months ago	fixed	examples	Joel Sherrill	Joel Sherrill	17 months ago
Summar y	examples-v2: no MIPS BSPs pass configuration step					
Descripti on	Checking for program 'ar' : /home/joel/rtems-work/tools/5/bin/mips-rtems5-ar Checking for program 'g++, c++' : /home/joel/rtems-work/tools/5/bin/mips-rtems5-g++ Checking for program 'ar' : /home/joel/rtems-work/tools/5/bin/mips-rtems5-ar Checking for program 'gas, gcc' : /home/joel/rtems-work/tools/5/bin/mips-rtems5-gcc Checking for program 'ar' : /home/joel/rtems-work/tools/5/bin/mips-rtems5-ar Compiler version (mips-rtems5-gcc) : 7.3.0 20180125 (RTEMS 5, RSB 6d9c77c77d271d1fc2dfe8493d6713930b52a6dd, Newlib 3.0.0) Checking for RTEMS CPU options header : started -> processing test results : 1 test failed One of the tests has failed, read config.log for more information (complete log in /data/home/joel/rtems-work/examples-v2/build/config.log) + check_fatal 1 'failed waf configure - examples-v2 on rbtx4925'					
<b>#3425</b>	22 months ago	fixed	unspecified	Joel Sherrill		21 months ago
Summar y	examples-v2: PowerPC fails to build fat_ramdisk					
Descripti on	beatnik, gwlcfm, haleakala, mpc5566evb, mpc5566evb_spe, mpc5566evb_spe, mpc5643l_evb, mpc5668g, mpc5674f_ecu508_app, mpc5674f_ecu508_boot, mpc5674fevb, mpc5674fevb_spe, mpc5674f_rsm6, mvme3100, mvme3100, phycore_mpc5554, qemu prep-alivec, qemu prep [5/7] Compiling build/powerpc-rtems5-beatnik/filesystem/fat_ramdisk/fs-root.tar In file included from /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/libcpu/powerpc-utility.h:40:0, from /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/bsp/vectors.h:40, from /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/bsp.h:27, from ../gdb/overwrite/rtems_init.c:7: /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/rtems/powerpc/powerpc.h:283:2: error: #error "Unsupported CPU Model" #error "Unsupported CPU Model" ^~~~~~ In file included from /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/libcpu/powerpc-utility.h:40:0, from /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/bsp/vectors.h:40, from /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/bsp.h:27, from ../hello/hello_world_c/test.c:21: /home/joel/rtems-work/bsp-install/powerpc-rtems5/beatnik/lib/include/rtems/powerpc/powerpc.h:283:2: error: #error "Unsupported CPU Model" #error "Unsupported CPU Model" ^~~~~~ Waf: Leaving directory `data/home/joel/rtems-work/examples-v2/build/powerpc-rtems5-beatnik' Build failed					
<b>#3432</b>	22 months ago	wontfix	score	Joel Sherrill		18 months ago
Summar y	Remove Simple SMP Priority Scheduler					
Descripti on	This scheduler was the first SMP scheduler added. It was created to have an easy SMP scheduler to debug. This was especially important when all of the SMP modifications and support were new. A Simple Scheduler has a use case as a low resource alternative for small uniprocessor systems. But the SMP variant just doesn't seem to have a good use case. If					



Descri tion	you have an SMP system, the application is almost certain to have enough resources where the more complicated data structures used by the other schedulers wouldn't be a burden. The Deterministic Priority Scheduler uses ~3K for FIFO with 256 priorities. This should not be an issue for an SMP system.					
	This ticket is a proposal to remove this as no longer having a use case.					
#3433	22 months ago	fixed	arch/riscv	Sebastian Huber	Sebastian Huber	14 months ago
Summar y	Add SMP support for RISC-V					
Descri tion	The project includes the following tasks: <ul style="list-style-type: none"> <li>• add CPU counter support</li> <li>• add context validation code</li> <li>• add BSP support for Qemu</li> <li>• add support for device tree provided by Qemu</li> <li>• fix all unexpected test suite failures running on Qemu</li> <li>• add build system support to enable an SMP build</li> <li>• add SMP implementation</li> </ul>					
#3434	22 months ago	fixed	config	Sebastian Huber	Sebastian Huber	19 months ago
Summar y	Add CONFIGURE_MINIMUM_POSIX_THREAD_STACK_SIZE configuration option					
#3435	22 months ago	fixed	config	Sebastian Huber	Sebastian Huber	18 months ago
Summar y	Add test case for CONFIGURE_BSP_PREREQUISITE_DRIVERS configuration option					
Descri tion	This configuration option is untested					
#3436	22 months ago	fixed	dev	Sebastian Huber	Sebastian Huber	3 months ago
Summar y	Remove clock driver Clock_driver_support_shutdown_hardware() hook					
Descri tion	Most applications use a clock driver and most BSPs use the clock driver framework provided by clockimpl.h. This framework offers a Clock_driver_support_shutdown_hardware() hook which is used like this. <pre> #ifdef Clock_driver_support_shutdown_hardware /**  * @brief Clock_exit  *  * This routine allows the clock driver to exit by masking the interrupt and  * disabling the clock's counter.  */ void Clock_exit( void ) {     Clock_driver_support_shutdown_hardware();      /* do not restore old vector */ } #endif ... #ifdef Clock_driver_support_shutdown_hardware atexit( Clock_exit ); #endif </pre> <p>The aim is to stop clock tick interrupts at some late point in the exit() procedure.</p> <p>The use of atexit() pulls in malloc() which pulls in errno. It is incompatible with the intention of the CONFIGURE_DISABLE_NEWLIB_REENTRANCY configuration option.</p> <p>The exit() function must be called from thread context, so accompanied clock tick interrupts should cause no harm. On the contrary, someone may assume a normal operating system operation, e.g. working timeouts.</p> <p>Remove the superfluous Clock_driver_support_shutdown_hardware() hook.</p>					
#3437	22 months ago	fixed	unspecified	Sebastian Huber	Sebastian Huber	21 months ago
Summar y	Replace use of printk() in free() with a fatal error					
Descri tion	An invalid heap usage such as a double free is usually a fatal error. Replace the use of printk() in free() with a fatal error. Introduce a new fatal error source for heap errors.					
#3443	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
Summar y	Remove shgen program					
Descri tion	Rename it to rtems-shgen.					
#3444	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	20 months ago
Summar y	Remove nios2gen program					
Descri tion	Rename it to rtems-nios2gen					
#3445	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
Summar y	Remove multigen script					
Descri tion	This script is unused and out dated.					
#3446	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
Summar y	Remove cvsignore-add.sh script					
Descri tion	This script is obsolete since moving to Git.					
#3447	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
Summar y	Remove rtems-testsuite-autostuff script					
Descri tion	It is not used.					
#3451	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
Summar y	Remove size_rtems script					
Descri tion	This script is horribly out of date. A new version could be placed in RTEMS tools if necessary.					
#3452	21 months ago	fixed	arch/riscv	Sebastian Huber	Sebastian Huber	19 months ago
Summar y	Update RISC-V tool chain to support standard 64-bit chips					
Descri tion	First step is to include this bug fix in Binutils:					

on	<a href="https://sourceware.org/bugzilla/show_bug.cgi?id=23244">https://sourceware.org/bugzilla/show_bug.cgi?id=23244</a>					
<b>#3453</b>	21 months ago	fixed	arch/riscv	Sebastian Huber	Sebastian Huber	21 months ago
Summary	Add RISC-V GDB					
<b>#3454</b>	21 months ago	fixed	doc	Vidushi Vashishth	Vidushi Vashishth	13 months ago
Summary	Tracing Framework Documentation in User Manual					
Description	<p>1) Write up a new chapter in the user manual regarding the existing tracing framework in RTEMS. Include a description of the components of the tracing framework and the various techniques used to generate traces currently. Add explanatory demonstrations and samples.</p> <p>2) Expand the chapter to include CTF generation (currently under development) as it evolves.</p>					
<b>#3455</b>	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
Summary	Remove install-if-change script					
Description	<p>The last installed tool in RTEMS repository is the install-if-change script. This script does the same as the standard "install" program with an additional feature to install variants via the -V command line option.</p> <p>This script is used by the standard Makefile support:</p> <pre>c/src/make/host.cfg.in:INSTALL_CHANGE=\$(PROJECT_BIN)/install-if-change</pre> <p>The INSTALL_CHANGE is used by:</p> <pre>c/src/make/host.cfg.in:ifndef INSTALL_CHANGE c/src/make/host.cfg.in:INSTALL_CHANGE=\$(PROJECT_BIN)/install-if-change c/src/make/host.cfg.in:INSTALL_VARIANT=\$(INSTALL_CHANGE) -V "\$\$(LIB_VARIANT)"</pre> <p>Is the variant stuff still supported?</p> <p>I would remove the support for it and replace the "install-if-change" script with the standard "install" program.</p>					
<b>#3458</b>	21 months ago	fixed	tool	Chris Johns	Chris Johns <chrisj@...>	21 months ago
Summary	rtems-test should not use the env PATH to find covoar					
Description	<p>The <code>rtems-test</code> command should know where <code>covoar</code> is when invoking it. It cannot use the environment's path. The path can contain invalid or outdated versions with subtle issues that could be hard to find.</p> <p>There should be no need to run install to use and test <code>rtems-test</code> with coverage.</p> <p>The <code>rtems-test</code> python code for running the tests knows where it is and adjusts. For example using an absolute path to <code>rtems-tests</code> in a build directly results in it being able to find the development tree <code>rtemstoolkit</code> and configuration data. The command needs to be taught to find the development version of <code>covoar</code>.</p> <p>Note, currently <code>covoar</code> needs external tools and this is currently using the environment's path however there is work underway to remove this dependence so there case does not need to be handled.</p>					
<b>#3459</b>	21 months ago	fixed	score	Sebastian Huber	Sebastian Huber	12 months ago
Summary	Rework initialization and interrupt stack support					
Description	<p>We need an initialization stack to run the sequential system initialization before multitasking is enabled. The system initialization is done with interrupts disabled.</p> <p>We need an interrupt stack for interrupt processing. This helps to avoid a per thread stack overhead for interrupt processing. The size for interrupt stack is application dependent, e.g. maximum interrupt nest level, stack demands of interrupt handlers.</p> <p>The initialization and interrupt stacks are needed for each processor in the system.</p> <p>Since interrupts are disabled during the sequential system initialization we can re-use the interrupt stack for the initialization stack. This is important for low end targets, with very limited RAM sizes. We need the initialization stack before a proper C run-time environment is set up e.g. we cannot assume that the access to global data is available. The stack memory area begin and size should be available via global symbols (named addresses). On some BSPs, e.g. ARM, this is done via the linker command file.</p> <p>It should be possible to set the stack size via the <code>CONFIGURE_INTERRUPT_STACK_SIZE</code> configuration option and not via some magic stuff in linker command files.</p> <p>Many BSPs set the BSS area to zero during system initialization. Thus, the initialization stack must not be contained in the BSS area.</p> <p>The interrupt stack implementation is currently controlled by the following CPU port defines:</p>					

```

/**
 * Does RTEMS manage a dedicated interrupt stack in software?
 *
 * If TRUE, then a stack is allocated in @ref _ISR_Handler_initialization.
 * If FALSE, nothing is done.
 *
 * If the CPU supports a dedicated interrupt stack in hardware,
 * then it is generally the responsibility of the BSP to allocate it
 * and set it up.
 *
 * If the CPU does not support a dedicated interrupt stack, then
 * the porter has two options: (1) execute interrupts on the
 * stack of the interrupted task, and (2) have RTEMS manage a dedicated
 * interrupt stack.
 *
 * If this is TRUE, @ref CPU_ALLOCATE_INTERRUPT_STACK should also be TRUE.
 *
 * Only one of @ref CPU_HAS_SOFTWARE_INTERRUPT_STACK and
 * @ref CPU_HAS_HARDWARE_INTERRUPT_STACK should be set to TRUE. It is
 * possible that both are FALSE for a particular CPU. Although it
 * is unclear what that would imply about the interrupt processing
 * procedure on that CPU.
 *
 * Port Specific Information:
 *
 * XXX document implementation including references if appropriate
 */
#define CPU_HAS_SOFTWARE_INTERRUPT_STACK FALSE

/**
 * Does this CPU have hardware support for a dedicated interrupt stack?
 *
 * If TRUE, then it must be installed during initialization.
 * If FALSE, then no installation is performed.
 *
 * If this is TRUE, @ref CPU_ALLOCATE_INTERRUPT_STACK should also be TRUE.
 *
 * Only one of @ref CPU_HAS_SOFTWARE_INTERRUPT_STACK and
 * @ref CPU_HAS_HARDWARE_INTERRUPT_STACK should be set to TRUE. It is
 * possible that both are FALSE for a particular CPU. Although it
 * is unclear what that would imply about the interrupt processing
 * procedure on that CPU.
 *
 * Port Specific Information:
 *
 * XXX document implementation including references if appropriate
 */
#define CPU_HAS_HARDWARE_INTERRUPT_STACK TRUE

/**
 * Does RTEMS allocate a dedicated interrupt stack in the Interrupt Manager?
 *
 * If TRUE, then the memory is allocated during initialization.
 * If FALSE, then the memory is allocated during initialization.

```

#3460	21 months ago	fixed	tool/gdb	Chris Johns	Chris Johns	13 months ago
-------	---------------	-------	----------	-------------	-------------	---------------

Summary: This should be TRUE if CPU\_HAS\_SOFTWARE\_INTERRUPT\_STACK is TRUE.  
 Description: Jiri patch for gdb-8.0.1.  
 XXX document implementation including references if appropriate

#3461	21 months ago	fixed	tool	Sebastian Huber	Sebastian Huber	21 months ago
-------	---------------	-------	------	-----------------	-----------------	---------------

Summary: Define CPU\_ALLOCATE\_INTERRUPT\_STACK TRUE  
 Canadian cross compilation of RTEMS tools not supported for x86\_64-w64-mingw32  
 Do the following steps to unify and simplify the initialization and interrupt stack support.

#3463	21 months ago	fixed	tool	Chris Johns	Chris Johns	17 months ago
-------	---------------	-------	------	-------------	-------------	---------------

Summary: Convert RTEMS\_DECLARE\_GLOBAL\_SYMBOL() and RTEMS\_DEFINE\_GLOBAL\_SYMBOL() macros to basedefs.h, to allow a global symbol definition via C code, e.g. in confdefs.h to  
 Convert RTEMS\_DECLARE\_GLOBAL\_SYMBOL() and RTEMS\_DEFINE\_GLOBAL\_SYMBOL() macros to basedefs.h, to allow a global symbol definition via C code, e.g. in confdefs.h to  
 2. Add a special input section ".rtemsstack" to the linker command files to allow a placement of the interrupt stacks. The BSPs can provide the optimal memory location for this section, e.g. on-chip RAM, tightly-coupled memory.

#3465	20 months ago	fixed	fs/jffs2	Sebastian Huber	Sebastian Huber	17 months ago
-------	---------------	-------	----------	-----------------	-----------------	---------------

Summary: This makes the CPU\_HAS\_SOFTWARE\_INTERRUPT\_STACK and CPU\_HAS\_HARDWARE\_INTERRUPT\_STACK CPU port defines superfluous, since the low level initialization code has all information available via global symbols.  
 Integrate all changes from Linux v3.11 to v4.17 made in the JFFS2 sources  
 This makes the CPU\_ALLOCATE\_INTERRUPT\_STACK CPU port define superfluous, since the interrupt stacks are allocated by confdefs.h for all architectures. There is no need for BSP-specific linker command file magic.  
 The original import version of the JFFS2 sources was Linux v3.11 (September 2013). Update the JFFS2 sources to Linux v4.17.  
 The optional CPU interrupt stack setup() is still useful to customize the registration of the interrupt stack area in the per-CPU information.  
 The git command to generate the patches is:

```

git format-patch v3.11..v4.17 -- include/uapi/linux/jffs2.h fs/jffs2/LICENCE fs/jffs2/acl.h fs/jffs2/build.c fs/jffs2/compr.c fs/jffs2/compr.h fs/jffs2/compr_rtime.c fs/jffs2/compr_rubin.c fs/jffs2/compr_zlib.c fs/jffs2/debug.c fs/jffs2/erase.c fs/jffs2/gc.c fs/jffs2/jffs2_fs_i.h fs/jffs2/jffs2_fs_sb.h fs/jffs2/nodelist.c fs/jffs2/nodelist.h fs/jffs2/nodemgmt.c fs/jffs2/read.c fs/jffs2/readinode.c fs/jffs2/scan.c fs/jffs2/summary.h fs/jffs2/write.c fs/jffs2/xattr.h

```

We need a source file transformation in the patches:

```

sed -i 's%/fs/jffs2%/cpukit/libfs/src/jffs2/src%g' 00*

```

To support the first commit:

```

From e8bbeeb755a077cfc0f814b07739f9225642d65c Mon Sep 17 00:00:00 2001
From: Cody P Schafer <cody@linux.vnet.ibm.com>
Date: Thu, 23 Jan 2014 15:56:11 -0800
Subject: [PATCH 01/24] fs/jffs2: use rbtree postorder iteration helper instead of opencoding

Use rbtree_postorder_for_each_entry_safe() to destroy the rbtree instead of opencoding an alternate postorder iteration that modifies the tree

Signed-off-by: Cody P Schafer <cody@linux.vnet.ibm.com>
Cc: Michel Lespinasse <walken@google.com>
Cc: Jan Kara <jack@suse.cz>
Cc: David Woodhouse <dwmw2@infradead.org>
Signed-off-by: Andrew Morton <akpm@linux-foundation.org>
Signed-off-by: Linus Torvalds <torvalds@linux-foundation.org>

```

we have to a postorder iterator to the red-black tree support code.

The remaining 23 patches are easy to apply.

#3471	20 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	20 months ago
-------	---------------	-------	-----	-----------------	-----------------	---------------

Summary: Update libfdt as of date 2018-07-09

Descri ption	The initial import of libfdt was in 2015. Update it to the version as of date 2018-07-09.						
Summar y	#3472	20 months ago	fixed	network/libbsd	Sebastian Huber	Sebastian Huber	13 months ago
Descri ption	Update of libbsd to a version close to the FreeBSD 12 release						
Descri ption	The FreeBSD project is about to prepare the FreeBSD 12 release soon: <a href="https://www.freebsd.org/releases/12.0R/schedule.html">https://www.freebsd.org/releases/12.0R/schedule.html</a>						
Descri ption	Use this time frame to update the libbsd stepwise to a FreeBSD trunk version close to the FreeBSD 12 release.						
Summar y	#3475	20 months ago	fixed	score	Sebastian Huber	Sebastian Huber	20 months ago
Summar y	Add RTEMS_PREDICT_TRUE() and RTEMS_PREDICT_FALSE() for static branch prediction hints						
Descri ption	Add macros to <rtems/score/basedefs.h> for the GNU extension builtin_expect(). Use RTEMS_PREDICT_TRUE() and RTEMS_PREDICT_FALSE() similar to the FreeBSD predict_true() and predict_false(). Alternatives are the Linux likely() and unlikely() or directly the GCC builtin_expect(), however, the FreeBSD names seem to be the most easy to understand.						
Summar y	#3478	20 months ago	fixed	arch/riscv	Joel Sherrill	Sebastian Huber	19 months ago
Summar y	RISCV BSP Tester Cleanup Needed						
Descri ption	rtems-tools currently has the following bsp testing configurations:						
Descri ption	<pre>\$ find . -name "**riscv*.ini" ./tester/rtems/rtems-bsps-riscv64.ini ./tester/rtems/testing/bsps/riscv64_generic.ini ./tester/rtems/testing/bsps/riscv_generic.ini ./tester/rtems/rtems-bsps-riscv32.ini</pre>						
Descri ption	rtems-bsps.ini does not include the riscv.						
Descri ption	tester/rtems/rtems-bsps-tiers.ini does not list the riscv						
Summar y	#3480	19 months ago	fixed	config	Sebastian Huber	Sebastian Huber	17 months ago
Summar y	CONFIGURE_MINIMUM_TASK_STACK_SIZE may affect CONFIGURE_INTERRUPT_STACK_SIZE						
Descri ption	In case an application defines CONFIGURE_MINIMUM_TASK_STACK_SIZE, then this may change the CONFIGURE_INTERRUPT_STACK_SIZE as well:						
Descri ption	<pre>#ifndef CONFIGURE_INTERRUPT_STACK_SIZE #define BSP_INTERRUPT_STACK_SIZE #define CONFIGURE_INTERRUPT_STACK_SIZE BSP_INTERRUPT_STACK_SIZE #else #define CONFIGURE_INTERRUPT_STACK_SIZE CONFIGURE_MINIMUM_TASK_STACK_SIZE #endif #endif</pre>						
Descri ption	I think this is not what a user expects.						
Summar y	#3482	19 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	19 months ago
Summar y	Relax the buffer alignment required by rtems_partition_create()						
Descri ption	Buffer alignment required by rtems_partition_create() is too strict since it is checked via _Addresses_Is_aligned() which is						
Descri ption	<pre>RTEMS_INLINE_ROUTINE bool _Addresses_Is_aligned ( const void *address ) { #if (CPU_ALIGNMENT == 0) return true; #else return (((uintptr_t)address % CPU_ALIGNMENT) == 0); #endif }</pre>						
Descri ption	The CPU_ALIGNMENT must take long double and vector data type alignment requirements into account. For the partition maintenance only pointer alignment is required. The user should ensure that its buffer is suitable for the items it wants to manage. The user should not be burdened to provide buffers with the maximum architecture alignment, e.g. why need a 16 byte aligned buffer if you want to manage items with 4 byte integers only?						
Summar y	#3484	19 months ago	fixed	fs/rfs	Sebastian Huber	Sebastian Huber	19 months ago
Summar y	RFS: Remove stray call of rtems_disk_release() in rtems_rfs_buffer_sync()						
Descri ption	The function rtems_rfs_buffer_sync() erroneously calls rtems_disk_release(). This screws up the reference counting of the disk.						
Summar y	#3486	19 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	19 months ago
Summar y	Use uintptr_t and size_t instead of uint32_t in rtems_partition_create()						
Descri ption	Use uintptr_t to specify the length of the partition buffer area instead of uint32_t. This is in line with rtems_region_create(). On 64-bit targets, the length may exceed 4GiB. Use size_t for the buffer size, since on some targets the single object size is less than the overall address range, e.g. m32c sizeof(uintptr_t) > sizeof(size_t).						
Summar y	#3488	19 months ago	fixed	config	Sebastian Huber	Sebastian Huber	18 months ago
Summar y	Remove CONFIGURE_HAS_OWN_MOUNT_TABLE						
Descri ption	RTEMS has the configuration option CONFIGURE_HAS_OWN_MOUNT_TABLE since 1999. This configuration option is broken since RTEMS 4.11. Remove this broken configuration option.						
Summar y	#3489	19 months ago	fixed	config	Sebastian Huber	Sebastian Huber	18 months ago
Summar y	Obsolete CONFIGURE_HAS_OWN_CONFIGURATION_TABLE						
Descri ption	Obsolete the CONFIGURE_HAS_OWN_CONFIGURATION_TABLE configuration option. The RTEMS configuration should be done via explicit configuration options to allow more freedom for implementation changes.						
Summar y	#3490	19 months ago	fixed	config	Sebastian Huber	Sebastian Huber	11 months ago
Summar y	Remove CONFIGURE_HAS_OWN_CONFIGURATION_TABLE						
Descri ption	This configuration option was obsoleted in RTEMS 5.1.						
Summar y	#3491	19 months ago	fixed	posix	Sebastian Huber	Sebastian Huber	18 months ago
Summar y	Align mprotect() prototype with POSIX						
Descri ption	The correct prototype is:						
Descri ption	<pre>int mprotect(void *, size_t, int);</pre>						
Summar y	#3496	19 months ago	fixed	score	Sebastian Huber	Sebastian Huber	19 months ago
Summar y	Remove superfluous interrupt enable in _Thread_Dispatch_enable()						





Summary	The RSB loose argument parsing in the RSB needs to change. The RSB needs to strictly check arguments to avoid simple user errors.					
#3520	18 months ago	fixed	config	Sebastian Huber	Sebastian Huber	18 months ago
Summary	Remove CONFIGURE_HAS_OWN_FILESYSTEM_TABLE					
Description	This configuration is untested and undocumented. Remove it to avoid a potential exposure of internal data structures to the application domain.					
#3522	18 months ago	fixed	network/libbsd	Sebastian Huber	Sebastian Huber	18 months ago
Summary	Update mDNSResponder to Apple version v878.30.4					
Description	<p>Download</p> <p>mDNSResponder-561.1.1.tar.gz mDNSResponder-567.tar.gz mDNSResponder-576.30.4.tar.gz mDNSResponder-625.41.2.tar.gz mDNSResponder-765.1.2.tar.gz mDNSResponder-765.20.4.tar.gz mDNSResponder-765.30.11.tar.gz mDNSResponder-765.50.9.tar.gz mDNSResponder-878.1.1.tar.gz mDNSResponder-878.20.3.tar.gz mDNSResponder-878.30.4.tar.gz</p> <p>from</p> <p><a href="https://opensource.apple.com/tarballs/mDNSResponder/">https://opensource.apple.com/tarballs/mDNSResponder/</a></p> <p>Merge each update into libbsd/mDNSResponder.</p>					
#3523	18 months ago	fixed	network/libbsd	Sebastian Huber	Sebastian Huber	18 months ago
Summary	Add FEC network interface driver for TQM8XX					
Description	Import legacy network driver and port it to libbsd.					
#3525	18 months ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Add MMC/SDCard support for i.MX 7Dual BSP					
Description	Port device drivers from FreeBSD for i.MX 7Dual uSDHC module.					
#3526	18 months ago	fixed	dev/serial	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Convert PTY driver to new Termios API					
Description						
#3528	17 months ago	fixed	config	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Remove undocumented and untested CONFIGURE_MAXIMUM_PTYS					
Description	Remove the undocumented and untested CONFIGURE_MAXIMUM_PTYS configuration option. Add a rtems_telnetd_config_table::client_maximum member to the Telnet configuration.					
#3529	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Fix issues raised by Coverity Scan for Telnet server					
#3531	17 months ago	fixed	unspecified	Joel Sherrill	Joel Sherrill	17 months ago
Summary	Add POSIX Attribute Reports for More Than Scheduler (examples-v2)					
Description	<p>Add programs to report default attributes for various POSIX objects including barriers, condition variables, message queues, mutexes, pthreads, and rwlocks. The programs should be able to run on any POSIX host and report what it uses for object attribute defaults.</p> <p>Object attribute defaults are unspecified by POSIX. The portable practice is to explicitly set every attribute. These programs allow one to probe and compare various operating system implementations.</p>					
#3532	17 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	10 months ago
Summary	RSB source only download is host specific					
Description	<p>The RSB source only download is host specific. Configurations for builds can restrict sources or patches by host to work around specific host issues. Currently a source only download is host specific because the host check is based on the host the RSB is being run on.</p> <p>The release process uses source only downloading to create the complete set of sources in a release. This issue means some host specific source may not be captured.</p> <p>I am yet to figure how to resolve this issue because the download logic is driven by the configuration scripts and this type of logic exists in configuration files such as <a href="#">rtems-gcc-7.3.0-newlib-d13c84eb07e35984bf7a974cd786a6cdac29e6b9.cfg</a> :</p> <pre>%if %{_build_os} == freebsd    %{_build_os} == darwin %patch add gcc--rsb-file=freebsd-libgcc-sed-fix.patch -p0 https://gcc.gnu.org/bugzilla/attachment.cgi?id=41380 %hash sha256 freebsd-libgcc-sed-fix.patch 8a11bd619c2e55466688e328da00b387d02395c1e8ff4a99225152387a1e60a4 %endif</pre> <p>The simpler construct in <a href="#">rtems-tools-common-1.cfg</a> of:</p> <pre>%ifos win32 mingw ming32 SB_BUILD_ROOT_WAF=\$SB_BUILD_ROOT\$(echo %{_prefix}   cut -c 1-2) %else SB_BUILD_ROOT_WAF=\$SB_BUILD_ROOT %endif</pre> <p>is easier to manage as the <code>%ifos</code> logic can always return <code>True</code> however the <code>%else</code> path also need to be followed and this could break the logic in a configuration file. Yes, the example is not about sources or patches however it shows what could be used. I do not think creating a new variable such as <code>%{download_only}</code> and adding logic to the configuration file will help, for example:</p> <pre>%if %{download_only}    %{_build_os} == freebsd    %{_build_os} == darwin %patch add gcc-foobar-bsd.patch %else %patch add gcc-foobar-gnu.patch %endif</pre> <p>We require the logic to follow the <code>%if True</code> path <b>and</b> the <code>%else</code> path.</p>					
#3533	17 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Add rtems_task_exit()					
Description	<p>The rtems_task_delete(RTEMS_SELF) function does not return. In order to aid compilers and static analysis tools provide an rtems_task_exit() function which can be specified as a no return function.</p> <pre>void rtems_task_exit(void) RTEMS_NO_RETURN;</pre> <p>This is similar to the POSIX equivalent.</p> <pre>void pthread_exit (void * __value_ptr) __dead2;</pre>					
#3535	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago

Summary	Remove stdin, stdout, stderr convenience routines for CEXP					
Description	These functions should be moved to a general CEXP support.					
#3536	17 months ago	fixed	tool	Chris Johns	Chris Johns	17 months ago
Summary	Move RTEMS configuration data to a common <code>config</code> directory					
Description	Move the <code>rtems-bsp-builder</code> configuration files to a common area in the RTEMS Tools project and create an <code>rtems.py</code> module to handle the configuration. This allows a number of tools access to the <code>arch/bsp</code> data. In time this directory of data can move into the <code>rtems.git</code> repo.					
#3537	17 months ago	fixed	tool	Chris Johns	Chris Johns	15 months ago
Summary	RSB and RTEMS Tools Support for python2 and python3					
Description	Upstream python does not create a <code>python</code> command any more and creates <code>python2</code> and <code>python3</code> . Distributions and operating systems are starting to ship without the <code>python</code> command. The RSB and RTEMS Tools python commands need to be updated and tested so they run on Python2 and Python3 and support added to use the available commands.					
#3538	17 months ago	fixed	doc	Joel Sherrill	Joel Sherrill	17 months ago
Summary	Classic API Barrier Wait Section Title Has Wrong Name					
Description	The section title says obtain not wait. Likely also applies to 4.11.					
#3539	17 months ago	fixed	score	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Remove CPU_PROVIDES_IDLE_THREAD_BODY					
Description	Remove the CPU_PROVIDES_IDLE_THREAD_BODY option to avoid unnecessary conditional compilation.					
#3542	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Remove keep_stdio feature from Telnet service					
Description	The Telnet service started via <code>rtems_telnetd_start()</code> has a <code>keep_stdio</code> feature. This just a task and executes the command function in a loop. For this kind of service we do not library support. This can be done by an application task on its own. Remove this functionality and provide only the real Telnet services.					
#3543	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Change Telnet server to allocate most resources during initialization					
Description	The Telnet server currently creates the resources needed for a client connection on demand. Allocate most resources during initialization to avoid sporadic resource shortage issues.					
#3545	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Support O_DIRECTORY open() flag					
Description	Use this flag in <code>opendir()</code> .					
#3546	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Support O_NOFOLLOW open() flag					
Description						
#3547	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Support O_CLOEXEC open() flag					
Description	This is a POSIX flag. Make sure its use causes no open failure.					
#3549	17 months ago	fixed	arch/powerpc	Sebastian Huber	Sebastian Huber	17 months ago
Summary	Obsolete powerpc/virtex BSP					
Description	This BSP is quite old (was added 1995), unmaintained and likely without users: <a href="https://lists.rtems.org/pipermail/users/2018-September/032557.html">https://lists.rtems.org/pipermail/users/2018-September/032557.html</a>					
#3551	17 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Move default configuration to separate library					
Description	An RTEMS application default configuration is contained in <code>cpukit/libmisc/dummy/default-configuration.c</code> . This default configuration is contained in <code>librtemscpu.a</code> . This has at least two problems: <ol style="list-style-type: none"> <li>1. Application configuration errors may pull in the default configuration which in turn leads to multiply define symbols error. This is quite confusing. You have to consult the linker map file to figure out what cased the pull in of the default configurations. You need to know what a linker map file is and how you generate it with your build system. This is not very user friendly.</li> <li>2. It prevents the use of default configuration items for each subsystem in <code>librtemscpu.a</code>. This can be used to reduce the size of the configuration itself.</li> </ol> Proposed change: Move the default configuration to a separate library, e.g. <code>librtemsdefaultconfig.a</code> .					
#3552	17 months ago	fixed	shell	jameszj	Chris Johns	3 months ago
Summary	cpu usage error in SMP mode					
Description	<ul style="list-style-type: none"> <li>• CPU load display error in SMP mode Load Average: 100.510% Load: 100.966% Idle: 99.033% In fact,CPU is doing nothing.</li> <li>• priority display unreadable in SMP mode in different Schedulers priority is map to a core priority, I think unmap maybe reasonable when display the information</li> </ul> I create a patch about this,see the attachment.					
#3553	17 months ago	fixed	build	Joel Sherrill		16 months ago
Summary	rtems-libbsd Missing waf in Top Directory					
Description	At least examples-v2 and rtems-libbsd use waf to build. examples-v2 has a copy of waf known to work for the users' convenience. rtems-libbsd is missing one. Add one to rtems-libbsd. Also (if there are other repos using waf), make sure they have a copy of waf also.					
#3554	17 months ago	fixed	network/libbsd	Joel Sherrill	Sebastian Huber	14 months ago
Summary	rtems-libbsd README.waf Needs an Update Sweep					
Description	It is out of date at least by mentioning 4.12 instead of 5. If there are other nits or issues, they need to be addressed while updating the release info.					



#3555	17 months ago	fixed	admin	Amar Takhar	Amar Takhar	17 months ago
Summary	IRC bots need to be registered to join #rtems					
Description	Due to the spam on Freenode only registered users can join #rtems. The bots both need accounts now.					
#3557	17 months ago	fixed	admin	Amar Takhar	Amar Takhar	17 months ago
Summary	Test ticket					
Description	Using this as a test ticket to test out my fix.					
#3558	17 months ago	fixed	admin	Amar Takhar	Amar Takhar	17 months ago
Summary	Update TracSpamFilter?					
Description	Updated to the latest Trac Spam Filter and upgraded captcha to v2 to avoid any errors. This was reported a while back and should fix any issues.					
#3559	17 months ago	fixed	admin	Amar Takhar	Amar Takhar	17 months ago
Summary	Fix NavAdd? plugin.					
Description	<p>I had no idea but this had gotten removed in the last upgrade I've re-added it.</p> <p>This makes a few changes to the navigation:</p> <ul style="list-style-type: none"> <li>"New Ticket" now goes to /wiki/NewTicket</li> <li>There is a new button "New Ticket (direct)" in the upper right for those who want to directly go to creating a ticket.</li> <li>"My Tickets" used to go to a query but now goes to the new <a href="#">wiki:MyTickets</a> page.</li> </ul> <p>These changes existed years ago when NavAdd? was working I opened this ticket in case anyone has complaints about it coming back if not I will close it in a few days.</p>					
#3560	17 months ago	fixed	admin	Amar Takhar	Amar Takhar	17 months ago
Summary	Fix FlexibleAssignTo?					
Description	<p>When we first went to trac we had restrictions on the 'owner' to developers only. When track was upgraded this broke completely but all the code to handle this was already in place.</p> <p>I took the time to fix it today so we have dropdowns again.</p> <p>I've created this ticket to see if anyone has an issue with this should we keep it? Drop it? I know it's been years but it was our original choice.</p> <p>See any ticket the 'reassign to' and on a new ticket the 'assign to' is now a dropdown. These are based on trac permissions so we can always add more if we need it but it really should be restricted to having a project member be the owner so we can ensure tickets are closed and sorted properly.</p>					
#3561	17 months ago	fixed	admin	Amar Takhar	Amar Takhar	16 months ago
Summary	Migrate to CommitTicketUpdater?					
Description	<p>The old script was ancient and outdated. I've now killed it off and moved to the internal system described here:</p> <p><a href="https://trac.edgewall.org/wiki/CommitTicketUpdater">https://trac.edgewall.org/wiki/CommitTicketUpdater</a></p> <p>This should handle all scenarios if it does not please let me know. I will leave this ticket open for a week or so.</p>					
#3562	17 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	16 months ago
Summary	Use a short paths for the RSB temporary build path on Windows					
Description	<p>The <code>#{tmproot}</code> path is currently based on a <code>BuildRoot</code> setting in the build configuration files. The line is:</p> <pre>BuildRoot: %#{tmppath}/%{name}-root-%#{_id_u}-n)</pre> <p>This is for a shared <code>\$STEMP</code> path plus the name is not shortened so on Windows these paths become long. Remove the <code>BuildRoot</code> from all configuration files and add support for a shortened temporary path. Windows needs short paths due to the 256 max. path length issue.</p>					
#3568	17 months ago	fixed	tool/rsb	Sebastian Huber	Chris Johns	14 months ago
Summary	RSB: UnboundLocalError?: local variable 'build_max_size_human' referenced before assignment					
Description	<pre>../source-builder/sb-set-builder --prefix=/build/rtems/5.5/rtems-or1k</pre> <pre>... config: tools/rtems-gcc-4.9.3-newlib-08eab6396f678cf5e5968acaed0bae9fd129983b.cfg package: or1k-rtems5-gcc-4.9.3-newlib-08eab6396f678cf5e5968acaed0bae9fd129983b-x86_64-linux-gnu-1 warning: gcc-4.9.3-or1k.patch: no hash found building: or1k-rtems5-gcc-4.9.3-newlib-08eab6396f678cf5e5968acaed0bae9fd129983b-x86_64-linux-gnu-1 error: building or1k-rtems5-gcc-4.9.3-newlib-08eab6396f678cf5e5968acaed0bae9fd129983b-x86_64-linux-gnu-1 Build FAILED See error report: rsb-report-or1k-rtems5-gcc-4.9.3-newlib-08eab6396f678cf5e5968acaed0bae9fd129983b-x86_64-linux-gnu-1.txt error: building or1k-rtems5-gcc-4.9.3-newlib-08eab6396f678cf5e5968acaed0bae9fd129983b-x86_64-linux-gnu-1 Mailing report: build@rtems.org Traceback (most recent call last):   File "../source-builder/sb/cmd-set-builder.py", line 26, in &lt;module&gt;     setbuilder.run()   File "/scratch/git-rtems-source-builder/source-builder/sb/setbuilder.py", line 619, in run     b.build(deps, mail = mail)   File "/scratch/git-rtems-source-builder/source-builder/sb/setbuilder.py", line 530, in build     body += 'Maximum build usage: ' + build_max_size_human + os.linesep UnboundLocalError: local variable 'build_max_size_human' referenced before assignment</pre>					
#3569	17 months ago	fixed	build	Malte Münch	Chris Johns	6 days ago
Summary	waf version in various rtems-repositories incompatible with python 3.7					
Description	<p>The current waf version included in rtems-tools is waf 1.9.9 (389f3f3b289f6b835a21ad4e128076cdb463d34d) it crashes when executed with python3. The current version of waf is 2.0.12 and resolves this issue.</p>					
#3576	16 months ago	fixed	tool/gdb	Joel Sherrill	Joel Sherrill	16 months ago
Summary	gdb 8.0.1 sis does not build on Cygwin					
Description	<p>Cygwin no longer has libtermcap. gdb/sim/erc32 needs a patch to find libncurses. Upstream gdb patch already merged.</p> <p><a href="https://sourceware.org/git/gitweb.cgi?p=binutils-gdb.git;a=commitdiff;h=c1230d1bab8e36e1aa40f3bbadcef9b5d9ddc041">https://sourceware.org/git/gitweb.cgi?p=binutils-gdb.git;a=commitdiff;h=c1230d1bab8e36e1aa40f3bbadcef9b5d9ddc041</a></p> <p>This ticket is just to contain a patch that applies cleanly to gdb 8.0.1 and to track adding that patch to the RSB.</p>					
#3577	16 months ago	fixed	tool/gcc	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Avoid CLoog and ISL host dependencies for target GCC					
Description	<p>We already use GCC in-tree libraries for MPFR, MPC, GMP and zlib. Use them also for CLoog and ISL. This helps to ensure that the same target code is generated across host systems. It also helps to avoid GCC build issues in case future versions of ISL and CLoog available on the host system are incompatible to the GCC version picked up by the RSB for RTEMS.</p>					
#3579	16 months ago	fixed	admin	Chris Johns	Chris Johns <chrisj@...>	16 months ago

Summary	testsuite's rtems-test-check.py python version support					
Description	This command used in the testsuite needs to find a suitable python or the build system needs to find it and invoke it with that python.					
#3583	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Add rtems_malloc() and rtems_calloc()					
Description	The standard C/POSIX functions malloc() and calloc() set errno in case of an error. A dependency to errno pulls in getreent() which pulls in a lot of data structures and functions. This is an issue in low level code especially in the area of a basic board support package initialization and device drivers. Provide rtems_malloc() and rtems_calloc() functions declared in <rtems/malloc.h> which do the same as the corresponding C/POSIX functions except setting errno. The posix_memalign() and aligned_alloc() functions do not have this issue with the errno.					
#3585	16 months ago	fixed	score	Sebastian Huber	Sebastian Huber	3 months ago
Summary	Deprecate proc_ptr					
Description	See comment in basedefs.h					
Description	<pre>/**  * XXX: Eventually proc_ptr needs to disappear!!!  */ typedef void * proc_ptr;</pre>					
#3587	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Deprecate rtems_context					
Description	The rtems_context typedef as no corresponding API. A user can do nothing with it. It is only used in cpukit/libmisc/monitor/mon-monitor.c and cpukit/libmisc/monitor/mon-editor.c in RTEMS. Deprecate it in this release.					
#3589	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Deprecate rtems_context_fp					
Description	The rtems_context_fp typedef as no corresponding API. A user can do nothing with it. It is only used in cpukit/libmisc/monitor/mon-editor.c in RTEMS. Deprecate it in this release.					
#3591	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Deprecate region_information_block					
Description	The region_information_block typedef as no corresponding API. It has no proper namespace prefix. A user can do nothing with it. It is only used in cpukit/libmisc/cpuse/cpusagetop.c and cpukit/libmisc/shell/main_mallocinfo.c in RTEMS. Deprecate it in this release.					
#3593	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Deprecate rtems_thread_cpu_usage_t					
Description	The rtems_thread_cpu_usage_t typedef as no corresponding API. It violates the POSIX namespace. A user can do nothing with it. It is only used in cpukit/include/rtems/rtems/ratemon.h in RTEMS. Deprecate it in this release.					
#3595	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Deprecate rtems_rate_monotonic_period_time_t					
Description	The rtems_rate_monotonic_period_time_t typedef as no corresponding API. It violates the POSIX namespace. A user can do nothing with it. It is only used in cpukit/include/rtems/rtems/ratemon.h in RTEMS. Deprecate it in this release.					
#3598	16 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	15 months ago
Summary	Move internal types of API objects to separate header file					
Description	<p>The &lt;rtems.h&gt; header file still exposes a lot of implementation details via the definition of internal data structures, e.g. the *_Control structures of the API objects. They are only necessary for the application configuration. Move them to separate header files. Currently we have:</p> <ul style="list-style-type: none"> <li>• &lt;rtems/rtems/XYZ.h&gt;</li> <li>• &lt;rtems/rtems/XYZimpl.h&gt;</li> </ul> <p>Use</p> <ul style="list-style-type: none"> <li>• &lt;rtems/rtems/XYZdata.h&gt;</li> </ul> <p>for this new header file.</p> <p>Potential new header files are:</p> <ul style="list-style-type: none"> <li>• rtems/extensiondata.h</li> <li>• rtems/rtems/asrdata.h</li> <li>• rtems/rtems/barrierdata.h</li> <li>• rtems/rtems/dpmemdata.h</li> <li>• rtems/rtems/eventdata.h</li> <li>• rtems/rtems/messagedata.h</li> <li>• rtems/rtems/partdata.h</li> <li>• rtems/rtems/ratemondata.h</li> <li>• rtems/rtems/regiondata.h</li> <li>• rtems/rtems/semdata.h</li> <li>• rtems/rtems/tasksdata.h</li> <li>• rtems/rtems/timerdata.h</li> </ul>					
#3599	16 months ago	fixed	arch/m32c	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Remove m32c architecture port					
Description	The m32c architecture port is incomplete, e.g. important features such as interrupt support are missing. It never run on real hardware. The tools are out dated and unmaintained. There are no known users: <a href="https://lists.rtems.org/pipermail/users/2018-January/031991.html">https://lists.rtems.org/pipermail/users/2018-January/031991.html</a>					
#3600	16 months ago	fixed	arch/or1k	Joel Sherrill	Joel Sherrill	3 months ago
Summary	Update or1k tools to use GCC master					
Description	Stafford Horne emailed me to say that he just pushed the or1k gcc to the FSF repository. We can now switch from gcc 4.9.3 to a hash from the gcc master. I was testing periodically from his repository before the merge so it should be working. I am marking this as a blocker but expect it to be easy and quick to resolve. We don't want to release using gcc 4.9.3 for any target.					
#3602	16 months ago	fixed	arch/or1k	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Update or1k tool chain to use the upstream GCC					
#3603	16 months ago	fixed	score	Sebastian Huber	Sebastian Huber	16 months ago
Summary	Remove support for 16-bit object identifiers					
Description	The RTEMS_USE_16_BIT_OBJECT define is not set by an RTEMS port. Remove support for 16-bit object identifiers. If someone really wants to use RTEMS on a 16-bit target, then it is better to use self-contained objects instead of playing around with object identifier optimizations.					



Descripti  
on

```

/**
 * @brief Flushes multiple data cache lines for a set of processors
 *
 * Dirty cache lines covering the area are transferred to memory.
 * Depending on the cache implementation this may mark the lines as invalid.
 *
 * This operation should not be called from interrupt context.
 *
 * @param[in] addr The start address of the area to flush.
 * @param[in] size The size in bytes of the area to flush.
 * @param[in] setsize The size of the processor set.
 * @param[in] set The target processor set.
 */
void rtems_cache_flush_multiple_data_lines_processor_set(
  const void *addr,
  size_t size,
  const size_t setsize,
  const cpu_set_t *set
);

/**
 * @brief Invalidates multiple data cache lines for a set of processors
 *
 * The cache lines covering the area are marked as invalid. A later read
 * access in the area will load the data from memory.
 *
 * In case the area is not aligned on cache line boundaries, then this
 * operation may destroy unrelated data.
 *
 * This operation should not be called from interrupt context.
 *
 * @param[in] addr The start address of the area to invalidate.
 * @param[in] size The size in bytes of the area to invalidate.
 * @param[in] setsize The size of the processor set.
 * @param[in] set The target processor set.
 */
void rtems_cache_invalidate_multiple_data_lines_processor_set(
  const void *addr,
  size_t size,
  const size_t setsize,
  const cpu_set_t *set
);

/**
 * @brief Flushes the entire data cache for a set of processors
 *
 * This operation should not be called from interrupt context.
 *
 * @see rtems_cache_flush_multiple_data_lines().
 *
 * @param[in] setsize The size of the processor set.
 * @param[in] set The target processor set.
 */
void rtems_cache_flush_entire_data_processor_set(
  const size_t setsize,
  const cpu_set_t *set
);

/**
 * @brief Invalidates the entire cache for a set of processors
 *
 * This function is responsible for performing a data cache
 * invalidate. It invalidates the entire cache for a set of
 * processors.
 *
 * This operation should not be called from interrupt context.
 *
 * @param[in] setsize The size of the processor set.
 * @param[in] set The target processor set.
 */
void rtems_cache_invalidate_entire_data_processor_set(
  const size_t setsize,
  const cpu_set_t *set
);

```

#3624	15 months ago	wontfix	build	Joel Sherrill	4 months ago
-------	---------------	---------	-------	---------------	--------------

Summary MSYS2 builds appear to ignore tcfg file

Descripti  
on

Building m68k/mrm332 on Linux and MSYS2 to compare results. Builds with all tests on Linux. Multiple build failures on MSYS2. Some appear to be because on MSYS2, tests are being build which are marked as exclude in the .tcfg file. For example, <https://git.rtems.org/rtems/tree/bsps/m68k/mrm332/config/mrm332-testsuite.tcfg#n11> says that fsdosfsname01 should be excluded but it is being built as shown below:

```

m68k-rtems5-gcc -mcpu=cpu32 -Os -g -fomit-frame-pointer -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -
B./../lib/libbsp/m68k/mrm332 -B/home/jrs007/rtems-work/rtems/bsps/m68k/mrm332/start -specs bsp_specs -qrtems -L./../cpukit -L/home/jrs007/rtems-
work/rtems/bsps/m68k/shared/start -Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -o fsdosfsname01.exe fsdosfsname01/fsdosfsname01-init.o
support/fsdosfsname01-ramdisk_support.o ./../lib/libbsp/m68k/mrm332/librtemsbsp.a ./../cpukit/librtemscpu.a
c:/msys64/home/jrs007/rtems-work/tools/5/bin/./lib/gcc/m68k-rtems5/7.3.0/./../m68k-rtems5/bin/ld.exe: fsdosfsname01.exe section ` .text' will not fit in region `rom'

c:/msys64/home/jrs007/rtems-work/tools/5/bin/./lib/gcc/m68k-rtems5/7.3.0/./../m68k-rtems5/bin/ld.exe: region `rom' overflowed by 874128 bytes

collect2.exe: error: ld returned 1 exit status

make[5]: *** [Makefile:1910: fsdosfsname01.exe] Error 1

```

#3625	15 months ago	fixed	lib/dl	Kevin Gordon	Chris Johns	15 months ago
-------	---------------	-------	--------	--------------	-------------	---------------

Summary RTL Allows Unloading a Module other Modules Depend Upon (cloned)

Cloned from #3195:  
Consider the following example using ELF .o files from compiled source files module-0.c and module-1.c from ticket #3194:

Description	<p>module-0.o is loaded using dlopen() with no code or data dependencies. module-1.o is loaded using dlopen() with both code and data dependencies on module-0 which are resolved by RTL.</p> <p>The RTL function dlclose() returns no error when module-0 is unloaded, when it should return an error and not unload module-0. This becomes quite dangerous because a subsequent call to module1Function1() in the currently-loaded module-1.o, which accesses shared_resource_0[ ] and calls module0Function0(), will result in an unexpected trap on qemu or the call succeeding with the correct return value on hardware when it should not.</p> <p>The erroneous successful unload() of module-0 aside, it appears as though the resources are not actually deleted and I believe this ticket is related to tickets #3192 and #3194.</p> <p>Architecture is sparc-leon3 using both the RTEMS 4.11.1 public release and rtems master @f043b9bd3bf25626fb1a311dd7fa041eacc68adc with rtems-source-builder @55f2d69e9b67cde23d61375fa34ef5b0f04a985d.</p> <p>Execution environments are qemu-system-sparc and LEON3 UT700 hardware.</p>					
Summary	#3626	15 months ago	fixed	posix	Joel Sherrill	Sebastian Huber 15 months ago
	sigtimedwait() needed when POSIX is disabled					
	When POSIX is disabled, psxmsgq01 does not link. Should we enable sigtimedwait() when POSIX is disabled or disable this test?					
Description	<pre data-bbox="191 436 1484 492">/data/home/joel/rtems-work/tools/5/bin/./lib/gcc/powerpc-rtems5/7.3.0/././././powerpc-rtems5/bin/ld: psxmsgq01/psxmsgq01-init.o: in function `wait_for_signal': /home/joel/rtems-work/rtems-testing/rtems/build-powerpc-ss555-rtems/powerpc-rtems5/c/ss555/testsuites/psxtests/./././././rtems/c/src/././testsuites/psxtests/psxmsgq01/init.c:932: undefined reference to `sigtimedwait'</pre>					
Summary	#3636	15 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber 15 months ago
	Add rtems_scheduler_get_maximum_priority()					
	The maximum task priority depends on the scheduler instance. It is a configuration parameter. Add a function to get it at runtime.					
Description	<pre data-bbox="191 627 1484 873">/**  * @brief Gets the maximum task priority of the specified scheduler instance.  *  * @param[in] scheduler_id Identifier of the scheduler instance.  * @param[out] priority Pointer to a task priority value.  *  * @retval RTEMS_SUCCESSFUL Successful operation.  * @retval RTEMS_INVALID_ADDRESS The @a priority parameter is @c NULL.  * @retval RTEMS_INVALID_ID Invalid scheduler instance identifier.  */ rtems_status_code rtems_scheduler_get_maximum_priority(     rtems_id scheduler_id,     rtems_task_priority *priority );</pre>					
Summary	#3637	15 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber 15 months ago
	Fix rtems_task_restart() argument type					
Description	The argument type must be rtems_task_argument in rtems_task_restart() similar to rtems_task_start(). This is a severe issue on 64-bit targets since it prevents to pass pointer values to the task.					
Summary	#3649	15 months ago	fixed	admin	Joel Sherrill	Amar Takhar 13 months ago
	Error with IRC announcing in examples-v2 commits.					
Description	<pre data-bbox="191 1108 1484 1411">remote: 1: mail vc@rtems.org remote: 2: update github remote: 4: IRC remote: usage: &lt;file with rev-list&gt; &lt;repo name without .git&gt; remote: 5: Buildbot To ssh://joel@dispatch.rtems.org/data/git/examples-v2.git ced6542..276a025A am -&gt; master</pre>					
Summary	#3651	15 months ago	fixed	doc	Chris Johns	3 months ago
	Sphinx 1.8 PDF (latex) on FreeBSD does not build					
	The build fails with <code>pdfindex</code> complaining on an <i>Undefined Control Sequence</i> :					
Description	<pre data-bbox="191 1545 1484 1612">! Undefined control sequence. &lt;argument&gt; \spxpagem  l.88 ...ecture}, \hyperindexformat{\spxpagem}{183}</pre>					
	The Tex is:					
	<pre data-bbox="191 1646 1484 1680">\item[ {Architecture}\index {Architecture@\spxentry {Architecture} spxpagem}\phantomsection\label{\detokenize{glossary/index:term-architecture}}}] \leavevmode</pre>					
	And the IDX entry from <code>makeindex</code> is:					
	<pre data-bbox="191 1713 1484 1747">\item \spxentry {Architecture}, \hyperindexformat{\spxpagem}{183}</pre>					
Summary	#3664	15 months ago	fixed	tool/rsb	Chris Johns	Chris Johns 15 months ago
	RSB config parsing slow on python3					
Description	The execute support on python3 is slow and this slows the config file parsing.					
Summary	#3665	15 months ago	fixed	lib	Sebastian Huber	Sebastian Huber 3 months ago
	Add low level event recording infrastructure					
	Add low level event recording infrastructure for system and user defined events. The infrastructure should be able to record high frequency events such as					
	<ul data-bbox="191 2016 478 2094" style="list-style-type: none"> <li>• SMP lock acquire/release,</li> <li>• interrupt entry/exit,</li> <li>• thread switches,</li> <li>• UMA zone allocate/free,</li> <li>• Ethernet packet input/output, etc.</li> </ul>					
	It should allow post-mortem analysis in fatal error handlers, e.g. the last events should be in the record buffer, the newest event overwrites the oldest event. It should be possible to detect record buffer overflows for consumers that expect a continuous stream of events, e.g. to display the system state in real-time.					

The framework should support high-end SMP machines (more than 1GHz processor frequency, more than four processors).

The existing capture engine tries to solve this problem, but its performance is not good enough for high-end production systems. The main issues are the variable-size buffers and the use of SMP locks for synchronization. To fix this, the API would change significantly.

Add a new API instead. The implementation should use per-processor data structures and no atomic read-modify-write operations. It is pretty much a per-processor ring buffer for record events.

Use the CPU counter to get the time of events. Combine it with periodic uptime events to synchronize it with CLOCK\_REALTIME.

Here is an example of the

```
/**
 * @brief Produces a record item.
 *
 * @param event The record event without a time stamp for the item.
 * @param data The record data for the item.
 */
void rtems_record_produce( rtems_record_event event, rtems_record_data data );
```

Descripti  
on

function PowerPC machine code generated by GCC:

```
00000000 <rtems_record_produce>:
0: 7d 00 00 a6 mfmshr r8
4: 7c 00 01 46 wrteei 0
8: 7d 2e 82 a6 mfspr r9,526
c: 7d 50 42 a6 mfsprg r10,0
10: 81 4a 02 b4 lwz r10,692(r10)
14: 55 29 50 2a rlwinm r9,r9,10,0,21
18: 7d 23 1b 78 or r3,r9,r3
1c: 81 2a 00 00 lwz r9,0(r10)
20: 80 ca 00 08 lwz r6,8(r10)
24: 38 e9 00 01 addi r7,r9,1
28: 7d 29 30 38 and r9,r9,r6
2c: 55 29 18 38 rlwinm r9,r9,3,0,28
30: 7d 2a 4a 14 add r9,r10,r9
34: 90 69 00 48 stw r3,72(r9)
38: 90 89 00 4c stw r4,76(r9)
3c: 7c 20 04 ac lwsync
40: 90 ea 00 00 stw r7,0(r10)
44: 7d 00 01 06 wrtee r8
48: 4e 80 00 20 blr
```

#3666	15 months ago	fixed	lib	Sebastian Huber	Sebastian Huber	14 months ago
-------	---------------	-------	-----	-----------------	-----------------	---------------

Summary  
Add support for C++17 std::aligned\_alloc

In C++17 there is a std::aligned\_alloc():

[https://en.cppreference.com/w/cpp/memory/c/aligned\\_alloc](https://en.cppreference.com/w/cpp/memory/c/aligned_alloc)

Descripti  
on

Unfortunately, it doesn't work with RTEMS currently:

[https://gcc.gnu.org/bugzilla/show\\_bug.cgi?id=85904](https://gcc.gnu.org/bugzilla/show_bug.cgi?id=85904)

Provide aligned\_alloc() and memalign() (as a strong alias to aligned\_alloo()) by RTEMS.

#3667	15 months ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	14 months ago
-------	---------------	-------	----------	-----------------	-----------------	---------------

Summary  
Support data cache disable on ARMv7-AR

#3669	15 months ago	fixed	doc	Chris Johns	Amar Takhar	13 months ago
-------	---------------	-------	-----	-------------	-------------	---------------

Summary  
rtems-docs.git does not build with Sphinx 1.8.2 and 1.8.3

The docs do not build with Sphinx 1.8. Recent posts indicate some changes to support unicode indexes via [xindy](#) have caused this and the solution being discussed is to use the generate [Makefile](#) ...

<https://github.com/rtd/readthedocs.org/issues/4454>

The need to use the [Makefile](#) is debatable however what it contains is important as it defines what needs to happen.

This recent issue can be seen in the Tex generated file for the User Manual ([user.tex](#)). It contains:

```
\item[ {Waf\index{Waf@\spxentry{Waf}\spxpagem}}\phantomsection\label{\detokenize{glossary\index:term-waf}}}\leavevmode
Waf build system. For more information see \sphinxurl{http://www.waf.io}
```

Descripti  
on

Our current build uses [pdflatex](#) directly and there is an error as [spxpagem](#) is not defined.

If you inspect a version 1.8 generated Makefile the command [latexmk](#) is used. This wraps the PDF generation so the correct number of passes are performed. Using this tool should be considered.

The [Makefile](#) contains:

```
export XINDYOPTS = -L english -C utf8 -M sphinx.xdy
```

The [sphinx.xdy](#) contains the needed [spxpagem](#). I can only conclude sphinx needs to be built with [xindy](#) because the reference is always generated.

The problem for building FreeBSD is [xindy](#) is not an available command.

#3670	14 months ago	fixed	examples	Chris Johns	joel@...	14 months ago
-------	---------------	-------	----------	-------------	----------	---------------

Summary  
examples-v2 uses deprecated or obsolete RTEMS interfaces

The examples need to be change to use what ever is the newer method of doing something.

```
../filesystem/fat_ramdisk/init.c:46:3: warning: 'rtems_blkdev_generic_open' is deprecated [-Wdeprecated-declarations]
open_entry:      rtems_blkdev_generic_open,
^~~~~~
```

Descripti  
on

```
In file included from /opt/work/chris/rtems/kernel/5/arm-rtems5/xilinx_zynq_zedboard/lib/include/rtems/ramdisk.h:17:0:
from ../filesystem/fat_ramdisk/init.c:16:
/opt/work/chris/rtems/kernel/5/arm-rtems5/xilinx_zynq_zedboard/lib/include/rtems/blkdev.h:408:1: note: declared here
rtems_blkdev_generic_open(
^~~~~~
```

```
../filesystem/fat_ramdisk/init.c:47:3: warning: 'rtems_blkdev_generic_close' is deprecated [-Wdeprecated-declarations]
close_entry:     rtems_blkdev_generic_close,
^~~~~~
```

```
In file included from ../ticker/low_ticker/init.c:88:0:
/opt/work/chris/rtems/kernel/5/arm-rtems5/xilinx_zynq_zedboard/lib/include/rtems/confdefs.h:3276:4: warning: #warning "The CONFIGURE_TERMIOS_DISABLED configuration option is obsolete since RTEMS 5.1" [-Wcpp]
#warning "The CONFIGURE_TERMIOS_DISABLED configuration option is obsolete since RTEMS 5.1"
^~~~~~
```

#3672	14 months ago	fixed	arch/i386	Joel Sherrill		13 months ago
-------	---------------	-------	-----------	---------------	--	---------------



<p> <pre> git clone git://git.rtems.org/rtems-libbsd.git Cloning into 'rtems-libbsd'... remote: Counting objects: 34566, done. remote: Compressing objects: 100% (8700/8700), done. remote: Total 34566 (delta 24457), reused 34566 (delta 24457) Receiving objects: 100% (34566/34566), 30.33 MiB   1.34 MiB/s, done. Resolving deltas: 100% (24457/24457), done. Checking out files: 100% (5159/5159), done.                     </pre> </p>	#3684	13 months ago	fixed	lib	Chris Johns	Chris Johns	13 months ago
<p>Summary</p> <p>rtems_print_buffer is broken</p> <p>Consider this call:</p> <pre>#include &lt;rtems/dumpbuf.h&gt; rtems_print_buffer ((const unsigned char *) "\x12\x23\x56\x78", 4);</pre> <p>On <code>psim</code> you get:</p> <pre>1f 2f 5f 7f           .#Vx           </pre>	#3685	13 months ago	fixed	lib/dl	Chris Johns	Chris Johns	2 months ago
<p>Summary</p> <p>Add large memory support to libdl</p> <p>Add large memory support to libdl. Some architectures use small relative offsets with smaller instructions for performance reasons. Object files loaded at addresses that are outside the relative range require trampoline calls that bridge the instruction in the object to the target symbol. The mechanism used depends on the archives. Libdl requires generic support to parse the relocation record before the object file allocation to provide the memory to hold the trampoline calls. The ARM and PowerPC architectures require trampolines. This is called veneers on ARM.</p>	#3686	13 months ago	fixed	lib/dl	Chris Johns	Chris Johns	7 days ago
<p>Summary</p> <p>Add library searching and loading to libdl</p> <p>Provide support to search library files (archives) for symbols loading the object file that contains the symbol. The support shall:</p> <ol style="list-style-type: none"> <li>1. Parse a configuration file called <code>/etc/libdl.conf</code> for the list of archive symbols to load. Support <code>fnmatch()</code> wildcard parsing. Allow runtime updates reloading if there is a change.</li> <li>2. Maintain archive symbol tables in memory to improve symbol search performance. Archives must have a <code>ranlib</code> generated symbol table. Reload an archive if it has changed.</li> <li>3. Make sure separate text and data built object files is supported. Assume a duplicate symbol means that section and symbol has already been loaded. Load all sections not loaded. There is no need to be efficient at this point in time.</li> <li>4. Add support to check if there are any system wide unresolved symbols.</li> <li>5. Automatically unloaded archive object files that are not referenced.</li> <li>6. Duplicate symbols in archives is not an error. The first archive that has the symbol in an object file is loaded.</li> </ol> <p>The feature adds <b>symbol based demand loading</b> of object files to <code>libdl</code>. A user loads an object file using the <code>dlopen</code> function and unresolved symbols are loaded from the libraries hosted on the target.</p>	#3687	13 months ago	fixed	lib/dl	Chris Johns	Chris Johns	7 days ago
<p>Summary</p> <p>Add architecture section support to libdl and support PowerPC's small data.</p> <p>Add support for architecture specific sections. Allow architecture back end support to handle sections that are specific to an architecture. Add PowerPC <code>.sdata</code> and <code>.sbss</code> support. The PowerPC can support a <b>small data</b> 64K continuous system wide region of memory. Small data accesses are faster as the instruction is smaller however the variable is referenced as a signed 16bit offset from the register <code>r13</code>. This register is offset from the region's base address by 32K. The linker creates the <code>.sdata</code> and <code>.sbss</code> regions and sets the <code>_SDA_BASE_</code> symbol which is loaded into <code>r13</code>. Any run-time loaded code with small data support needs space in the small data region therefore a BSP needs a way to define the space and the linker needs to allocate it. Provide a way for PowerPC BSPs to add extra memory to the small data region. RTEMS supports the PowerPC EABI and uses <code>sysv</code> small data allocations. RTEMS uses the default variable size of <code>8</code> as the selector for a variable to be allocated in the small data region. The GCC user manual recommends all code is built with the same settings. Dynamically loaded code could be built with small data disabled and if enabled the default size is recommended. Note, small data is system wide which means a default size of <code>8</code> allows only 8192 8 byte variables. Provide an allocator to manage the available small data memory.</p>	#3688	13 months ago	fixed	doc	Chris Johns		3 months ago
<p>Summary</p> <p>rtems-docs fails to build with python3</p> <p>Generating <code>generated-posix-compliance.rst</code> fails with Python3 as reported in <a href="https://github.com/sphinx-doc/sphinx/issues/6021#issuecomment-460701861">https://github.com/sphinx-doc/sphinx/issues/6021#issuecomment-460701861</a></p>	#3692	13 months ago	fixed	lib/dl	Chris Johns	Chris Johns	13 months ago
<p>Summary</p> <p>libdl does not honour write unlock/lock for sections</p> <p>The allocator does no honour write unlock and lock for read-only sections as it should. This can used to write protect executable memory.</p>	#3694	13 months ago	fixed	fs	Joel Sherrill	Gedare Bloom	12 months ago
<p>Summary</p> <p>shm_open has logically unreachable code (Coverity ID: 1399706, 1399714)</p> <p>Coverity ID: 1399706 and 1399714 File: shmopen.c Method: shm_open for first</p> <pre> dead_error_condition: The condition oflag &amp; 0 cannot be true. 289 if ( oflag &amp; O_RDONLY ) {  CID 1399706 (#1 of 1): Logically dead code (DEADCODE) dead_error_line: Execution cannot reach this statement: flags  = 2U;. 290 flags  = LIBIO_FLAGS_READ; 291 } else {                     </pre> <p>URL: <a href="https://scan5.coverity.com/reports.htm#v29811/p10069/fileInstanceId=153084281&amp;defectInstanceId=42558012&amp;mergedDefectId=1399706&amp;fileStart=1&amp;fileEnd=250">https://scan5.coverity.com/reports.htm#v29811/p10069/fileInstanceId=153084281&amp;defectInstanceId=42558012&amp;mergedDefectId=1399706&amp;fileStart=1&amp;fileEnd=250</a></p> <p>Same issue at other place in same file:</p> <pre> 197 int flags; dead_error_condition: The condition oflag &amp; 0 cannot be true. 198 if ( oflag &amp; O_RDONLY ) {  CID 1399714 (#1 of 1): Logically dead code (DEADCODE) dead_error_line: Execution cannot reach this statement: flags = 4;. 199 flags = RTEMS_FS_PERMS_READ; 200 } else {                     </pre>	#3699	13 months ago	fixed	arch/arm	Kinsey Moore	Sebastian Huber	13 months ago



Summary	Wrong system register specified for ARM virtual timer value retrieval					
Description	In arm_cp15_get_counter_pl1_virtual_timer_value() in cpukit/score/cpu/arm/include/libcpu/arm-cp15.h, the system register specified by "p15, 0, %[val], c14, c2, 0" is actually the system register for the physical timer value. This should be "p15, 0, %[val], c14, c3, 0" for the virtual timer value as used in the setter.					
#3720	12 months ago	fixed	shell	Sebastian Huber	Sebastian Huber	12 months ago
Summary	mfill shell command uses the wrong arguments for the memset()					
#3724	12 months ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	12 months ago
Summary	bsp/lpc24xx: Convert SSP driver to Linux API					
#3725	12 months ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	10 months ago
Summary	bsp/lpc24xx: Convert I2C driver to Linux API					
Description						
#3728	11 months ago	fixed	bsps	Chris Johns	Chris Johns	11 months ago
Summary	Set small data section to max size for mvme5500 and motorola_powerpc BSPs					
Description	These are large memory targets that can support libdl. Make the small data memory the maximum size.					
#3731	11 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	11 months ago
Summary	Add rtems_scheduler_get_processor()					
Description	Add rtems_scheduler_get_processor() as a replacement for rtems_get_current_processor(). The rtems_get_current_processor() is a bit orphaned. Adopt it by the Scheduler Manager. This is in line with the glibc sched_getcpu() function.					
#3732	11 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	11 months ago
Summary	Add rtems_scheduler_get_processor_maximum()					
Description	Add rtems_scheduler_get_processor_maximum() as a replacement for rtems_get_processor_count(). The rtems_get_processor_count() is a bit orphaned. Adopt it by the Scheduler Manager. The count is also misleading, since the processor set may have gaps and the actual count of online processors may be less than the value returned by rtems_get_processor_count().					
#3733	11 months ago	fixed	lib/debugger	Chris Johns	Chris Johns	11 months ago
Summary	Add general reg support to libdebugger					
Testing master on a Zynq reports:						
<pre>(gdb) target remote 10.10.5.45:1122 Remote debugging using 10.10.5.45:1122 Truncated register 19 in remote 'g' packet</pre>						
It looks to me like gdb is now smart enough to know this ARM arch has a NEON and floating point registers:						
<pre>(gdb) maint print registers Name      Nr Rel Offset  Size Type r0         0  0   0         4 uint32_t r1         1  1   4         4 uint32_t r2         2  2   8         4 uint32_t r3         3  3  12         4 uint32_t r4         4  4  16         4 uint32_t r5         5  5  20         4 uint32_t r6         6  6  24         4 uint32_t r7         7  7  28         4 uint32_t r8         8  8  32         4 uint32_t r9         9  9  36         4 uint32_t r10        10 10  40         4 uint32_t r11        11 11  44         4 uint32_t r12        12 12  48         4 uint32_t sp         13 13  52          4 *1 lr         14 14  56         4 uint32_t pc         15 15  60          4 *1 f0         16 16  64        12 _arm_ext f1         17 17  76        12 _arm_ext f2         18 18  88        12 _arm_ext f3         19 19 100        12 _arm_ext f4         20 20 112        12 _arm_ext f5         21 21 124        12 _arm_ext f6         22 22 136        12 _arm_ext f7         23 23 148        12 _arm_ext fps        24 24 160         4 uint32_t cpsr       25 25 164         4 uint32_t</pre>						
The target support in libdebugger is a simple array of 32bit ints. This needs to change to handle registers at various offsets. The lack of fp regs was a simplification at the time I first implement this server. Looks like I need to sort this out.						
#3734	11 months ago	fixed	score	Sebastian Huber	Sebastian Huber	11 months ago
Summary	Add RTEMS_CONST attribute					
Description	Add RTEMS_CONST attribute to make the compiler specific <code>attribute((const))</code> available.					
#3735	11 months ago	fixed	config	Sebastian Huber	Sebastian Huber	3 months ago
Summary	Remove CONFIGURE_HAS_OWN_MULTIPROCESSING_TABLE					
Description	Remove the CONFIGURE_HAS_OWN_MULTIPROCESSING_TABLE configuration option. The RTEMS configuration should be done via explicit configuration options to allow more freedom for implementation changes. The use of this configuration option had a note in the documentation: "This is a configuration parameter which is very unlikely to be used by an application. If you find yourself wanting to use it in an application, please reconsider and discuss this on the RTEMS Users mailing list." No discussion took place in a couple of years about this topic.					
#3736	11 months ago	fixed	arch/powerpc	Chris Johns	Sebastian Huber <sebastian.huber@...>	4 months ago
Summary	PowerPC Beatnik BSP C++ exceptions broken					
Running <code>cdtest.exe</code> fails. I am wondering if there is an issue in the <code>linkcmd</code> scripts this BSP uses. The psim works.						
The trace is:						

```

config addr is 0xf1000cf8
config data is 0xf1000cfc
Welcome to RTEMS rtems-5.0.0 (PowerPC/Generic (classic FPU)/beatnik)
CPU: MPC7457
Board Type: MVME5500-0161 (S/N E1712C9)
Bus Clock Freq: 133333333 Hz
CPU Clock Freq: 1000000000 Hz
Memory: 536870912 bytes
-----
Now BSP_mem_size = 0x1fe00000
Configuration.work_space_size = a170
Page table setup finished; will activate it NOW....
Going to start PCI buses scanning and initialization
Number of PCI buses found is : 3
MSR 0x2003032
Exit from bspstart
Universe II PCI-VME bridge detected at 0x82000000, IRQ 76
Universe Master Ports:
Port VME-Addr Size PCI-Adrs Mode:
0: 0x20000000 0x0e000000 0x90000000 A32, D64 [MBLT], Dat, Sup
1: 0x00000000 0x00ff0000 0x9f000000 A24, D64 [MBLT], Dat, Sup
2: 0x00000000 0x00010000 0x9fff0000 A16, D64, Dat, Sup
7: 0x00000000 0x01000000 0x9e000000 CSR, D64, Dat, Sup
Universe Slave Ports:
Port VME-Addr Size PCI-Adrs Mode:
0: 0x90000000 0x1fe00000 0x00000000 A32, Pgm, Dat, Sup, Usr, PWEN, PRE
N
vmeUniverse IRQ manager: looking for registers on VME...
Trying to find CRG on VME...
vmeUniverse IRQ manager - registers not found on VME; falling back to PCI

*** BEGIN OF TEST CONSTRUCTOR/DESTRUCTOR ***
*** TEST VERSION: 5.0.0.8a8b95aa1d6932ba9d2acd7a785100f7d0919205-modified
*** TEST STATE: EXPECTED-PASS
*** TEST BUILD: RTEMS_NETWORKING RTEMS_POSIX_API
*** TEST TOOLS: 7.4.0 20181206 (RTEMS 5, RSB 9a3e12e5820918057633798c3fe2
a1f952fb4e56, Newlib 1d35a003f)
GLOBAL: Hey I'm in base class constructor number 1 for 0x5c404.
GLOBAL: Hey I'm in base class constructor number 2 for 0x5c410.
GLOBAL: Hey I'm in derived class constructor number 3 for 0x5c410.
LOCAL: Hey I'm in base class constructor number 4 for 0x6cbdc.
LOCAL: Hey I'm in base class constructor number 5 for 0x6cbd0.
LOCAL: Hey I'm in base class constructor number 6 for 0x6cbc4.
LOCAL: Hey I'm in base class constructor number 7 for 0x6cbb8.
LOCAL: Hey I'm in derived class constructor number 8 for 0x6cbb8.
IO Stream not tested
LOCAL: Hey I'm in derived class destructor number 8 for 0x6cbb8.
Derived class - Instantiation order 8
LOCAL: Hey I'm in base class destructor number 7 for 0x6cbb8.
Derived class - Instantiation order 8
LOCAL: Hey I'm in base class destructor number 6 for 0x6cbc4.
Derived class - Instantiation order 6
LOCAL: Hey I'm in base class destructor number 5 for 0x6cbd0.
Derived class - Instantiation order 5
LOCAL: Hey I'm in base class destructor number 4 for 0x6cbdc.
Derived class - Instantiation order 5
*** TESTING C++ EXCEPTIONS ***

fatal source: RTEMS_FATAL_SOURCE_EXIT
bsp_fatal_extension(): RTEMS terminated

```

Descripti  
on

#3741	10 months ago	fixed	lib/dl	dufault	Chris Johns	10 months ago
Summary	libdl loading ELF objects from libbsd NFS file system ends in a deadlock					
Description	<p>For ELF files the run-time loader calls this chain:</p> <ul style="list-style-type: none"> <li>• <code>rtems_rtl_elf_file_load()</code></li> <li>• <code>rtems_rtl_alloc_lock()</code></li> <li>• <code>rtems_rtl_alloc_heap()</code></li> <li>• <code>_RTEMS_Lock_allocator()</code></li> </ul> <p><code>_RTEMS_Lock_allocator()</code> locks all heap operations. RTL then calls <code>read()</code> and for NFS file systems the NFS threads try to use the heap, locking up the system.</p>					
#3742	10 months ago	fixed	test	Chris Johns	joel@...	10 months ago
Summary	T_config conflicting type qualifiers for 'config'					
Description	<p>Running the <code>rtems-bsp-builder</code> on FreeBSD is give an error in <code>ttest01</code> for bsps:</p> <ul style="list-style-type: none"> <li>• <code>arm/csb336</code></li> <li>• <code>arm/csb337</code></li> <li>• <code>arm/csb637</code></li> <li>• <code>arm/kit637_v6</code></li> <li>• <code>mips/csb350</code></li> </ul> <p>The error being reported is:</p> <pre>error: testsuites/libtests/ttest01/init.c:146:23: error: conflicting type qualifiers for 'config'</pre> <p>The builder command line is:</p> <pre>/opt/work/chris/rtems/rt/rtems-tools.git/tester/rtems-bsp-builder \ --rtems-tools=/opt/work/rtems/5 \ --rtems=/opt/work/chris/rtems/kernel/rtems.git \ --log=everything-tests \ --profile=everything \ --build=tests \ --jobs=7/6</pre> <p>A BSP configure command line is:</p> <pre>/opt/work/chris/rtems/kernel/rtems.git/configure \ --target=mips-rtems5 --enable-rtemsbsp=csb350 --prefix=/opt/rtems/5 \ --enable-tests --disable-smp</pre>					
#3743	10 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	10 months ago
Summary	RSB os and arch config logic is broken					
Description	<p>The config file processing of conditionals:</p> <ul style="list-style-type: none"> <li>• <code>%ifos</code></li> <li>• <code>%ifnos</code></li> <li>• <code>%ifarch</code></li> </ul> <p>do not correctly process lists of arguments. The argument list is split in 2 with the first element correct handled and the remaining treated as a lump. The argument list needs to be split evenly.</p>					
#3746	10 months ago	fixed	lib/dl	Chris Johns	Chris Johns <chrisj@...>	10 months ago
Summary	libdl test dl05.exe failing					
Description	<p>This test is failing because the second stage of the symbol loading does not check if a section referenced by a symbol has been loaded. It is not clear yet if the lack of support in <code>libdl</code> for <code>group</code> sections is a factor.</p>					
#3747	10 months ago	fixed	arch/arm	Sebastian Huber	Sebastian Huber	10 months ago
Summary	Address Cortex-M3 Errata 602117					
Description	<p>While testing on a NXP LPC1788 it found that this chip is affected by the Cortex-M3 Errata 602117. NXP didn't bother to document this in their errata sheet for the chip:</p> <p><a href="https://www.nxp.com/docs/en/errata/ES_LPC177X_8X.pdf">https://www.nxp.com/docs/en/errata/ES_LPC177X_8X.pdf</a></p> <p>To avoid the issues, you have to compile everything with <code>-mfix-cortex-m3-ldrd</code>. This option is enabled by default, if you use <code>-mcpu=cortex-m3</code>.</p> <p>I think we have to change our GCC multilibs to account for this errata. For example:</p> <pre>diff --git a/gcc/config/arm/t-rtems b/gcc/config/arm/t-rtems index 026a5895662..e276b4f3e57 100644 --- a/gcc/config/arm/t-rtems +++ b/gcc/config/arm/t-rtems @@ -1,7 +1,7 @@  # Custom RTEMS multilibs for ARM  -MULTILIB_OPTIONS = mbig-endian mthumb march=armv6-m/march=armv7-a/march=armv7-r/march=armv7-m/mcpu=cortex-m7 mfpu=neon/mfpu=vfp/mfpu=vfpv3-d16/mfpu=fpv4-sp-d16/mfpu=fpv5-d16 mfloat-abi=hard +MULTILIB_OPTIONS = eb thumb armv6-m armv7-a armv7-r armv7-m cortex-m7 neon vfp vfpv3-d16 fpv4-sp-d16 fpv5-d16 hard +MULTILIB_OPTIONS = mbig-endian mthumb march=armv6-m/march=armv7-a/march=armv7-r/mcpu=cortex-m3/mcpu=cortex-m4/mcpu=cortex-m7 mfpu=neon/mfpu=vfp/mfpu=vfpv3-d16/mfpu=fpv4-sp-d16/mfpu=fpv5-d16 mfloat-abi=hard +MULTILIB_DIRS = eb thumb armv6-m armv7-a armv7-r cortex-m3 cortex-m4 cortex-m7 neon vfp vfpv3-d16 fpv4-sp-d16 fpv5-d16 hard   # Enumeration of multilibs  @@ -16,7 +16,8 @@ MULTILIB_REQUIRED += mthumb/march=armv7-a/mfpu=neon/mfloat-abi=hard MULTILIB_REQUIRED += mthumb/march=armv7-a MULTILIB_REQUIRED += mthumb/march=armv7-r/mfpu=vfpv3-d16/mfloat-abi=hard MULTILIB_REQUIRED += mthumb/march=armv7-r -MULTILIB_REQUIRED += mthumb/march=armv7-m/mfpu=fpv4-sp-d16/mfloat-abi=hard +MULTILIB_REQUIRED += mthumb/mcpu=cortex-m3 +MULTILIB_REQUIRED += mthumb/mcpu=cortex-m4 +MULTILIB_REQUIRED += mthumb/mcpu=cortex-m4/mfpu=fpv4-sp-d16/mfloat-abi=hard MULTILIB_REQUIRED += mthumb/mcpu=cortex-m7/mfpu=fpv5-d16/mfloat-abi=hard -MULTILIB_REQUIRED += mthumb/march=armv7-m MULTILIB_REQUIRED += mthumb</pre>					
#3748	10 months ago	fixed	lib/dl	Chris Johns	Chris Johns <chrisj@...>	10 months ago
Summary	libdl uses a linear symbol search on object file symbols					
Description	<p>Symbol searching has two parts, searching the object file and searching the global symbol table. Currently the object file search is linear and the global table search uses a hash table.</p> <p>A large incrementally linked object file can have a large local and global set of symbols and this can slow the loading process. This issue does not show up for small object files with a few symbols which is typically how our libraries are made.</p> <p>Change the object file symbol search to a binary search (<code>bsearch</code>). A hash table for each object file would increase the in memory object file footprint by a significant amount and would harm the small object file use case that only have a few symbols. A binary search is a suitable compromise.</p>					

#3751	10 months ago	fixed	doc	Joel Sherrill	Joel Sherrill <joel@...>	3 months ago
Summary	No documentation on Region Get Information Directives					
Description	rtems_region_get_information and rtems_region_get_free_information are not documented in the Classic API Users Guide. They have been present since at least 4.6 and should be documented.					
#3753	10 months ago	fixed	config	Joel Sherrill	Sebastian Huber <sebastian.huber@...>	3 months ago
Summary	Rename CONFIGURE_LIBIO_MAXIMUM_FILE_DESCRIPTOR					
Description	CONFIGURE_LIBIO_MAXIMUM_FILE_DESCRIPTOR probably should not mention LIBIO as that is an internal component/organization aid which should not be visible to the user. This ticket is to discuss renaming CONFIGURE_LIBIO_MAXIMUM_FILE_DESCRIPTOR to just CONFIGURE_MAXIMUM_FILE_DESCRIPTOR. Perhaps deprecate now and obsolete in next major version. Include code to warn and map old name to new. Thoughts?					
#3754	9 months ago	fixed	doc	Joel Sherrill	Joel Sherrill	7 months ago
Summary	Users Guide Ubuntu Instructions Have Typo					
Description	sudo should be sudo					
#3756	9 months ago	fixed	arch/sparc	Sebastian Huber	Sebastian Huber	9 months ago
Summary	Condition codes in PSR are destroyed by lazy FP context switch					
Description	<a href="https://lists.rtems.org/pipermail/devel/2019-June/026014.html">https://lists.rtems.org/pipermail/devel/2019-June/026014.html</a>					
#3760	9 months ago	fixed	arch/arm	Chris Johns	Chris Johns <chrisj@...>	7 months ago
Summary	BBB MMU update crashes					
Description	Calling <code>arm_cp15_set_translation_table_entries()</code> on a BBB (Cortex-A8) crashes in the call to <code>arm_cp15_tlb_invalidate_entry_all_asids()</code> . There is no HYP support in the BBB's A8. The <code>cp15</code> register is documented in the A8 manual but the BBB device from TI does not have the support built in. A check of the A8 doco from ARM says this is for use in HYP mode so should we be using without checking if HYP is supported and if it is active? I am also wondering if we use should be using it on the Zynq. I have no idea why the Zync (A9) does not complain, it may be ignoring the invalidate request. While looking at this code I was wondering why we do not follow ARM's recommendation of 'break-make' updates of the TLB? I do not know we could support such a process because we may be asked to invalidate the entry for the text section we are running in to update it. Note, following the other path in the call works on a BBB.					
#3762	8 months ago	fixed	arch/arm	Chris Johns	Chris Johns	8 months ago
Summary	Return the current handler from ARM cp15 set exception call					
Description	Update the cp15 call <code>arm_cp15_set_exception_handler()</code> to return the current handler. This lets code catch and return an exception handler, for example code to probe suspect hardware. This is need to probe the memory map debug registers for debug v7 implementations.					
#3763	8 months ago	fixed	tool/rsb	Chris Johns	Chris Johns <chrisj@...>	7 months ago
Summary	RSB SIS build fails on FreeBSD					
Description	The RSB SIS build for RISCv fails on FreeBSD with:					

```
+ FLAGS='-O2 -pipe -fbracket-depth=1024 -l/opt/work/chris/rtems/rsb/rtems-source-builder.git/rtems/build/tmp/sb-chris/5/rtems-sis/opt/work/rtems/5/include ' ./.configure '--
build=x86_64-freebsd12.0' '--host=x86_64-freebsd12.0' '--program-prefix=sis-rtems5-' '--prefix='
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a thread-safe mkdir -p... build-aux/install-sh -c -d
checking for gawk... no
checking for mawk... no
checking for nawk... nawk
checking whether make sets $(MAKE)... yes
checking for x86_64-freebsd12.0-gcc... /usr/bin/cc -O2 -pipe -fbracket-depth=1024 -l/opt/work/chris/rtems/rsb/rtems-source-builder.git/rtems/build/tmp/sb-chris/5/rtems-
sis/opt/work/rtems/5/include accepts -g... yes
checking whether the C compiler works... yes
checking for C compiler default output file name... a.out
checking for suffix of executables...
checking whether we are cross compiling... no
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether /usr/bin/cc -O2 -pipe -fbracket-depth=1024 -l/opt/work/chris/rtems/rsb/rtems-source-builder.git/rtems/build/tmp/sb-chris/5/rtems-
sis/opt/work/rtems/5/include accepts -g... yes
checking for /usr/bin/cc -O2 -pipe -fbracket-depth=1024 -l/opt/work/chris/rtems/rsb/rtems-source-builder.git/rtems/build/tmp/sb-chris/5/rtems-sis/opt/work/rtems/5/include
option to accept ISO C89... none needed
checking for style of include used by make... GNU
checking dependency style of /usr/bin/cc -O2 -pipe -fbracket-depth=1024 -l/opt/work/chris/rtems/rsb/rtems-source-builder.git/rtems/build/tmp/sb-chris/5/rtems-
sis/opt/work/rtems/5/include... gcc3
checking how to run the C preprocessor... /usr/bin/cc -O2 -pipe -fbracket-depth=1024 -l/opt/work/chris/rtems/rsb/rtems-source-builder.git/rtems/build/tmp/sb-chris/5/rtems-
sis/opt/work/rtems/5/include -E
checking for grep that handles long lines and -e... /usr/bin/grep
checking for egrep... /usr/bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking fcntl.h usability... yes
checking fcntl.h presence... yes
checking for fcntl.h... yes
checking stddef.h usability... yes
checking stddef.h presence... yes
checking for stddef.h... yes
checking for stdlib.h... (cached) yes
checking for string.h... (cached) yes
checking sys/time.h usability... yes
checking sys/time.h presence... yes
checking for sys/time.h... yes
checking for unistd.h... (cached) yes
checking termios.h usability... yes
checking termios.h presence... yes
checking for termios.h... yes
checking for reading in 'readline... no
configure: error: the required "readline" library is missing
```

#3768	8 months ago	fixed	build	Chris Johns	Chris Johns	8 months ago
-------	--------------	-------	-------	-------------	-------------	--------------

Summary: Add support to the RSB for BSP build sets. The support includes building 3rd party packages for a BSP.

Description: Add support to the RSB for BSP build sets. The support includes building 3rd party packages for a BSP. The support includes building 3rd party packages for a BSP.

#3769	8 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	8 months ago
-------	--------------	-------	----------	-------------	-------------	--------------

Summary: RSB BSP buildsets

Description: Add support to the RSB for BSP build sets. The support includes building 3rd party packages for a BSP.

1. Add BSP buildset support
2. Build packages for a BSP
3. Stage buildset builds if not the outer build so dependent packages and be built before a package and used
4. Fix packages to support staged builds

#3770	8 months ago	wontfix	tool/rsb	Chris Johns		3 months ago
-------	--------------	---------	----------	-------------	--	--------------

Summary: RSB 3rd party packages failing to build

Description: The following packages do not build or have issues and will be removed if they are not updated:

1. ntp
2. microwindows
3. nxlib
4. lwip

The lwip patch used by this package needs to be updated. The `install` target for the `Makefile` does not support `DESTDIR` and cannot be staged. It is being built however a lack of `DESTDIR` is not compatible with the requirements of the RSB for staged builds. The package installs directly to the `prefix` which is not suppose to happen.

The packages will need to be fixed or removed before 5.1. There is no point releasing the RSB with packages that are broken.

#3773	7 months ago	fixed	arch/arm	Chris Johns	Chris Johns	7 months ago
-------	--------------	-------	----------	-------------	-------------	--------------

Summary: RPi fails to boot

Description: The RPi BSP fails to boot with the current master. A bsect of the repo shows the failure appears after this change [\[bdec62c4/rtems\]](#).

#3774	7 months ago	fixed	arch/arm	Chris Johns	Sebastian Huber <sebastian.huber@...>	7 months ago
-------	--------------	-------	----------	-------------	---------------------------------------	--------------

Summary: RPi2 SMP does not build

Description: 

```
arm-rtems5-gcc -march=armv7-a -mthumb -mcpu=neon -mfloat-abi=hard -mtune=cortex-a7 -O1 -g -ffunction-sections -fdata-sections -ffunction-sections -fdata-sections -Wall
-Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -B./../lib/libbsp/arm/raspberrypi -
B/opt/work/chris/rtems/kernel/rtems.git/bsps/arm/raspberrypi/start -specs bsp_specs -qrtems -L./../cpukit -L/opt/work/chris/rtems/kernel/rtems.git/bsps/arm/shared/start -WI,-
-wraps=printf -WI,-wraps=puts -WI,-wraps=putchar -WI,-gc-sections -o alloc.norun.exe POSIX/calloc.o ./../cpukit/librtemsdefaultconfig.a
./../lib/libbsp/arm/raspberrypi/librtemsbsp.a ./../cpukit/librtemscpu.a ./../cpukit/librtemstest.a
/opt/work/rtems/5/lib/gcc/arm-rtems5/7.4.0/./../arm-rtems5/bin/ld: alloc.norun.exe section `rtemsstack' will not fit in region `VECTOR_RAM'
/opt/work/rtems/5/lib/gcc/arm-rtems5/7.4.0/./../arm-rtems5/bin/ld: section `start VMA [0000000000008000,00000000000085ff] overlaps section `rtemsstack VMA
[000000000000040,000000000000203f]
/opt/work/rtems/5/lib/gcc/arm-rtems5/7.4.0/./../arm-rtems5/bin/ld: region `VECTOR_RAM' overflowed by 114752 bytes
```

Configured with ...

```
/opt/work/chris/rtems/kernel/rtems.git/configure --target=arm-rtems5 --prefix=/opt/work/chris/rtems/kernel/5 --disable-networking --enable-maintainer-mode --enable-rtems-
debug --enable-tests --enable-rtemsbsp=raspberrypi2 --enable-smp
```

#3775	7 months ago	fixed	lib/dl	Chris Johns	Chris Johns	7 months ago
-------	--------------	-------	--------	-------------	-------------	--------------

Summary: libdl does not handle ARM mode reloc tramp parsing

<p> <a href="#">#3776</a> 7 months ago fixed lib/dl Chris Johns Chris Johns 7 months ago                 </p> <p>                     Summary: libld ARM does not support ARM mode trampolines.                 </p> <p>                     Description: The BBB fails on libld tests because the trampoline parsing of reloc records does not handle the ABS type relocs when the code is built in ARM mode.                 </p>
<p> <a href="#">#3777</a> 7 months ago fixed lib/dl Chris Johns Chris Johns 7 months ago                 </p> <p>                     Summary: libld object unload debugger delete support is broken                 </p> <p>                     Description: The BBB is ARM mode and crashes <code>dl09.exe</code>. This is due to only Thumb mode trampoline support.                 </p>
<p> <a href="#">#3781</a> 7 months ago fixed tool/rsb Sebastian Huber Sebastian Huber 3 months ago                 </p> <p>                     Summary: RSB crashes in case the host as an unreadable directory in "/"                 </p> <p>                     Description: The test <code>dl09.exe</code> crashes on BBB, Zedboard, and RPi2 but runs on arm qemu and psim. The issue is uncovered by the heap protection support in <code>free()</code> where the free block has been touched. It turns out <code>_rtdl_linkmap_delete()</code> list code is broken. The object module's block should not be walked to the end.                 </p>

```

butrfeld@elektra:~/rtemsSMP/src/rsb/rtems$ ./source-builder/sb-set-builder --source-only-download 5/rtems-sparc
RTEMS Source Builder - Set Builder, 5 (29fab0500e22)
Traceback (most recent call last):
  File "../source-builder/sb/cmd-set-builder.py", line 26, in <module>
    setbuilder.run()
  File "/users/staff/butrfeld/rtemsSMP/src/rsb/source-builder/sb/setbuilder.py", line 674, in run
    if not check.host_setup(opts):
  File "/users/staff/butrfeld/rtemsSMP/src/rsb/source-builder/sb/check.py", line 127, in host_setup
    if not path_check(opts):
  File "/users/staff/butrfeld/rtemsSMP/src/rsb/source-builder/sb/check.py", line 115, in path_check
    elif not path.exists(p):
  File "/users/staff/butrfeld/rtemsSMP/src/rsb/source-builder/sb/path.py", line 131, in exists
    return _exists(shell(paths))
  File "/users/staff/butrfeld/rtemsSMP/src/rsb/source-builder/sb/path.py", line 124, in _exists
    return basename(p) in ['.'] + listdir(dirname(p))
  File "/users/staff/butrfeld/rtemsSMP/src/rsb/source-builder/sb/path.py", line 118, in listdir
    return os.listdir(hp)
OSError: [Errno 13] Permission denied: '/adm'
    
```

<p>                     Description: The root directory "/" looks like this:                 </p> <pre> butrfeld@elektra:/\$ ls -ls total 89 4 drwxr-x---+ 6 root root 4096 Nov 5 2018 adm 4 drwxr-xr-x 2 root root 4096 Apr 10 06:17 bin                 </pre>
--

<p> <a href="#">#3783</a> 7 months ago fixed tool/rsb jameszsj 6 months ago                 </p> <p>                     Summary: MSYS2 RSB build error                 </p> <p>                     Description: I tried to update the compiler to RSB master, and encountered an error. command line:                       <code>../source-builder/sb-set-builder --dry-run --with-download 5/rtems-arm</code>                       error message:                       <code>config: tools/rtems-gdb-8.2.1-1.cfg error: shell macro failed: sh -c "/mingw64/bin/python2-config --ldflags   awk 'BEGIN{FS=" "}python/{for(i=1;i&lt;NF;++i)if(match(\$i,".*python.*")) print "lib"substr(\$i,3)*";}"; 1: }python/{for(i=1;i&lt;NF;++i)if(match(\$i,".*python.*")) print libsubstr(\$i,3)*";}": -c: line 0: unexpected EOF while looking for matching `                     }python/{for(i=1;i&lt;NF;++i)if(match(\$i,".*python.*")) print libsubstr(\$i,3)*";}": -c: line 1: syntax error: unexpected end of file Build FAILED Build Set: Time 0:00:47.324763 Build FAILED</code> </p>
<p> <a href="#">#3785</a> 7 months ago fixed arch/riscv pragnesh 3 months ago                 </p> <p>                     Summary: Add RISC-V BSP with support for the Freedom E310 Arty A7 FPGA                 </p>
<p> <a href="#">#3789</a> 6 months ago fixed arch/arm Andreas Werner Sebastian Huber 3 months ago                 </p> <p>                     Summary: TMS570 application build error                 </p>

**expected behaviour**

Build without errors and without runtime errors

**undesired behaviour**

bsp\_start\_hook\_0\_done is undefined CPACR Register is not setup

**target hardware**

Hercules Safety MCU development Kit TMS570 MCU

**toolchain version**

Modified GCC, binutils and gdb build script to build armeb compiler build with RTEMS Source Builder master(see patches for RTEMS Soucre Builder) I need a ARM Compiler with Big Endian Support as default for TMS570.

**configuration options for bsp**

`../rtems/configure --prefix=[bsp path]/bsp/armeb-rtems5' '--host=arm-rtems5' '--target=arm-rtems5' '--enable-posix' '--enable-rtems-debug' '--disable-tests' '--disable-networking' '--enable-rtemsbsp=tms570ls3137_hdk' 'CC_FOR_TARGET=armeb-rtems5-gcc' 'CXX_FOR_TARGET=armeb-rtems5-gcc' 'AR=armeb-rtems5-ar' 'TMS570_USE_HWINIT_STARTUP=1'`

Test on master commit RTEMS (4a9a58ea8ad75248af5876c01ef654f9bc59c312)

**Bug Fix**

define symbol bsp\_start\_hook\_0\_done in start.S add if defined(ARM\_ARCH\_7R) see patches

#3792	6 months ago	fixed	admin	Jeff Mayes	Chris Johns	6 months ago
-------	--------------	-------	-------	------------	-------------	--------------

**Summary**  
RSB fails to build on MSYS2

**Description**  
Fresh install of Windows 10, with updates. Then installed MSYS2 as instructed here: <https://docs.rtems.org/branches/master/user/hosts/windows.html#msys2>

Fetches the RSB, and then tried to build rtems-sparc tools, like this...

```
$ ../source-builder/sb-set-builder --prefix=/home/mayes/dev/rtems/5 5/rtems-sparc RTEMS Source Builder - Set Builder, 5 (b45df48a51bc) Build Set: 5/rtems-sparc Build Set: 5/rtems-autotools.bset Build Set: 5/rtems-autotools-internal.bset config: tools/rtems-autoconf-2.69-1.cfg ... .. config: devel/expat-2.1.0-1.cfg package: expat-2.1.0-x86_64-w64-mingw32-1 building: expat-2.1.0-x86_64-w64-mingw32-1 sizes: expat-2.1.0-x86_64-w64-mingw32-1: 9.229MB (installed: 2.037MB) cleaning: expat-2.1.0-x86_64-w64-mingw32-1 reporting: devel/expat-2.1.0-1.cfg -> expat-2.1.0-x86_64-w64-mingw32-1.txt reporting: devel/expat-2.1.0-1.cfg -> expat-2.1.0-x86_64-w64-mingw32-1.xml Config: tools/rtems-gdb-8.3-1.cfg error: shell macro failed: sh -c "mingw64/bin/python2-config --ldflags | awk 'BEGIN{FS=" "}/python/{for(i=1;i<NF;+ +)if(match($i,"*python.*")) print "lib"substr($i,3)*";"}'": 1: }/python/{for(i=1;i<NF;+ +)if(match($i,"*python.*")) print libsubstr($i,3)*";"}: -c: line 0: unexpected EOF while looking for matching ` }/python/{for(i=1;i<NF;+ +)if(match($i,"*python.*")) print libsubstr($i,3)*";"}: -c: line 1: syntax error: unexpected end of file Build FAILED Build Set: Time 0:07:19.564000 Build FAILED
```

This happens when using Python3 and also when using Python2.

#3793	6 months ago	fixed	tool	Chris Johns		3 months ago
-------	--------------	-------	------	-------------	--	--------------

**Summary**  
trace record tool does not build on Windows

**Description**  
The error is:

```
../trace/record/record-main-ltng.c:32:10: fatal error: sys/queue.h: No such file or directory
#include <sys/queue.h>
```

This is with the version the RSB is using

#3794	6 months ago	fixed	posix	Joel Sherrill	Joel Sherrill	5 months ago
-------	--------------	-------	-------	---------------	---------------	--------------

**Summary**  
Initial POSIX Signals Mask Incorrect

RTEMS initial signal mask for the "process" does not match the behavior of Linux, FreeBSD, and Cygwin.

There are some subtle rules which need to be followed for the value of the created thread's signal mask. Because signals are part of C99 and enhanced by POSIX, both Classic API tasks and POSIX threads have to have them enabled.

1. Internal system threads should have no signals enabled. They have no business executing user signal handlers -- especially IDLE.
2. The initial signal mask for other threads needs to follow the implication of a pure C99 environment which only has the methods raise() and signal(). This implies that all signals are unmasked until the thread explicitly uses a POSIX methods to block some. This applies to both Classic tasks and POSIX threads created as initialization tasks/threads (e.g. before the system is up).
3. After the initial threads are created, the signal mask should be inherited from the creator. This can be done based on system state.

RTEMS behavior was incorrect by blocking all signals initially and for Classic API tasks.

**Notes:**

- The default signal mask does not matter for any application that does not use POSIX signals.
- It is assumed that Classic API tasks should provide a compliant C run-time environment. Hence the default signal mask state matters.

**Description**  
Impact on Applications and Tests ===== In general, an application should always explicitly block or unmask any signals that it intends to process. If there is concern about which thread may process it, then it should be blocked in all threads that are not intended to process it. The following code can be used to block all signals. This method can be used in the initialization task/thread to mimic historical behavior:

```
static void block_all_signals(void)
{
    int         sc;
    sigset_t    mask;

    sc = sigfillset( &mask );
    // check sc == 0

    sc = pthread_sigmask( SIG_BLOCK, &mask, NULL );
    // check sc == 0
}
```

#3796	6 months ago	fixed	doc	Gedare Bloom	Joel Sherrill <joel@...>	3 months ago
-------	--------------	-------	-----	--------------	--------------------------	--------------

**Summary**  
docs/develenv directory structure bitrot

**Description**  
The directory structure described in the Development Environment Guide is outdated and does not reflect changes made in relocating BSPs to the bsp/ directory and refactoring the include paths.

#3797	6 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	3 months ago
-------	--------------	-------	----------	-------------	-------------	--------------

**Summary**  
Add LLVM as a package

**Description**  
Add [5/rtems-llvm](#) to build LLVM for supported hosts. This can be used to help resolve the dependency the recent trace changes have created by using LLVM symbol/dwarf support.

#3798	5 months ago	fixed	network/libbsd	Joel Sherrill	Sebastian Huber	3 months ago
-------	--------------	-------	----------------	---------------	-----------------	--------------

**Summary**  
Add socketmark to libbsd

**Description**  
Now that pselect() is in libbsd, socketmark() is the only method called out by any of the four POSIX profiles in the FACE Technical Standard (<http://opengroup.org/face>) which is not provided by rtems-libbsd.

#3802	5 months ago	fixed	tool/rsb	Joel Sherrill	Hesham Almatary	3 months ago
-------	--------------	-------	----------	---------------	-----------------	--------------

**Summary**  
RSB Build of Spike Fails on Second Time (bug in upstream spike)

**Description**  
See <https://github.com/riscv/riscv-isa-sim/issues/348>

When this is fixed in the upstream, bump the hash in the RSB. Until then, use the attached patch.

#3805	4 months ago	invalid	lib/debugger	Joel Sherrill	Chris Johns	4 months ago
-------	--------------	---------	--------------	---------------	-------------	--------------

**Summary**  
libdebugger build error on atsamv

This was caught in a build sweep using rtems-bsp-builder.

**Description**  
Configure command:

```
/home/joel/rtems-cron-5/rtems/configure --target=arm-rtems5 --enable-rtemsbsp=atsamv --prefix=/home/joel/rtems-cron-5/tools/5/bsps --enable-rtems-debug --disable-smp
```

Compiler output:

```

arm-rtems5-gcc --pipe -DHAVE_CONFIG_H -I. -I/home/joel/rtems-cron-5/b-atsam/arm-rtems5/c/atsamv/include -I/home/joel/rtems-cron-5/rtems/cpukit/include -
I/home/joel/rtems-cron-5/rtems/cpukit/score/cpu/arm/include -I/home/joel/rtems-cron-5/rtems/cpukit/libnetworking -mthumb -mcpu=cortex-m7 -mfpv5-d16 -mfloat-
abi=hard -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT libdebugger/rtems-
debugger-arm.o -MD -MP -MF $depbase.Tpo -c -o libdebugger/rtems-debugger-arm.o /home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c &&
mv -f $depbase.Tpo $depbase.Po
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c: In function 'arm_debug_mmap_enable':
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:826:12: warning: unused variable 'abort_handler' [-Wunused-variable]
void* abort_handler;
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c: In function 'arm_debug_unlock_abort':
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1593:53: error: 'arm_switch_reg' undeclared (first use in this function)
#define EXCEPTION_ENTRY_EXC() (void) arm_switch_reg
    ^
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1609:3: note: in expansion of macro 'EXCEPTION_ENTRY_EXC'
EXCEPTION_ENTRY_EXC();
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1593:53: note: each undeclared identifier is reported only once for each function it appears
in
#define EXCEPTION_ENTRY_EXC() (void) arm_switch_reg
    ^
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1609:3: note: in expansion of macro 'EXCEPTION_ENTRY_EXC'
EXCEPTION_ENTRY_EXC();
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1607:24: warning: variable 'frame' set but not used [-Wunused-but-set-variable]
CPU_Exception_frame* frame;
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c: In function 'target_exception_undefined_instruction':
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1593:53: error: 'arm_switch_reg' undeclared (first use in this function)
#define EXCEPTION_ENTRY_EXC() (void) arm_switch_reg
    ^
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1619:3: note: in expansion of macro 'EXCEPTION_ENTRY_EXC'
EXCEPTION_ENTRY_EXC();
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c: In function 'target_exception_supervisor_call':
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1593:53: error: 'arm_switch_reg' undeclared (first use in this function)
#define EXCEPTION_ENTRY_EXC() (void) arm_switch_reg
    ^
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1642:3: note: in expansion of macro 'EXCEPTION_ENTRY_EXC'
EXCEPTION_ENTRY_EXC();
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c: In function 'target_exception_prefetch_abort':
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1593:53: error: 'arm_switch_reg' undeclared (first use in this function)
#define EXCEPTION_ENTRY_EXC() (void) arm_switch_reg
    ^
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1659:3: note: in expansion of macro 'EXCEPTION_ENTRY_EXC'
EXCEPTION_ENTRY_EXC();
    ^~~~~~
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c: In function 'target_exception_data_abort':
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1593:53: error: 'arm_switch_reg' undeclared (first use in this function)
#define EXCEPTION_ENTRY_EXC() (void) arm_switch_reg
    ^
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1676:3: note: in expansion of macro 'EXCEPTION_ENTRY_EXC'
EXCEPTION_ENTRY_EXC();
    ^~~~~~
At top level:
/home/joel/rtems-cron-5/rtems/c/src/././cpukit/libdebugger/rtems-debugger-arm.c:1605:1: warning: 'arm_debug_unlock_abort' defined but not used [-Wunused-function]
arm_debug_unlock_abort(void)

```

Descripti  
on



#3806	4 months ago	fixed	score	Sebastian Huber	Sebastian Huber	4 months ago
Summary	Add fatal error for heap errors					
Description	<p>Currently, the following fatal error is generate in case of heap errors:</p> <pre>static void _Heap_Protection_block_error_default(     Heap_Control *heap,     Heap_Block *block ) {     /* FIXME */     _Terminate( INTERNAL_ERROR_CORE, 0xdeadbeef ); }</pre> <p>Replace this with a dedicated fatal error source and a context structure (similar to assert()).</p>					
#3808	4 months ago	fixed	tool/rsb	Chris Johns	Joel Sherrill	3 months ago
Summary	Fix qemu-couverture-git RSB download file name					
Description	<p>The file name for qemu-couverture-git is a git hash. This results in a file in a release source directory that has no meaning ...</p> <p><a href="https://ftp.rtems.org/pub/rtems/releases/5/5.0.0/5.0.0-m1911/sources/">https://ftp.rtems.org/pub/rtems/releases/5/5.0.0/5.0.0-m1911/sources/</a></p> <p>The release build output shows the issue ...</p> <pre>package: qemu-e9299f7591c8ecf3389922f4e7672b6bc5deae71-x86_64-pc-solaris2-1 download: https://github.com/AdaCore/qemu/archive/e9299f7591c8ecf3389922f4e7672b6bc5deae71.tar.gz -&gt; sources/e9299f7591c8ecf3389922f4e7672b6bc5deae71.tar.gz redirect: https://codelead.github.com/AdaCore/qemu/tar.gz/e9299f7591c8ecf3389922f4e7672b6bc5deae71 downloading: sources/e9299f7591c8ecf3389922f4e7672b6bc5deae71.tar.gz - 0.0 bytes</pre>					
#3809	4 months ago	fixed	tool/rsb	Chris Johns	Joel Sherrill <joel@...>	3 months ago
Summary	Fix epiphany-rtems5-gdb-7.8 RSB download file name					
Description	<p>The file name for epiphany-rtems5-gdb-7.8 is a git hash. This results in a file in a release source directory that has no meaning ...</p> <p><a href="https://ftp.rtems.org/pub/rtems/releases/5/5.0.0/5.0.0-m1911/sources/">https://ftp.rtems.org/pub/rtems/releases/5/5.0.0/5.0.0-m1911/sources/</a></p> <p>The release build output shows the issue ...</p> <pre>download: https://github.com/adapteva/epiphany-binutils-gdb/archive/f05996c7c42e6b2781946acbab153a481ce3fd0b.zip sources/f05996c7c42e6b2781946acbab153a481ce3fd0b.zip redirect: https://codelead.github.com/adapteva/epiphany-binutils-gdb/zip/f05996c7c42e6b2781946ac...&lt;see log&gt; downloading: sources/f05996c7c42e6b2781946acbab153a481ce3fd0b.zip - 0.0 bytes</pre>					
#3811	4 months ago	fixed	admin	Chris Johns	Chris Johns <chrisj@...>	4 months ago
Summary	Release source path on ftp.rtems.org is wrong					
Description	The released source directory in the release snapshot is wrong. The RSB is fetching .. <a href="https://ftp.rtems.org/pub/rtems/releases/5/5.0.0-m1911/sources/">https://ftp.rtems.org/pub/rtems/releases/5/5.0.0-m1911/sources/</a>					
#3812	4 months ago	fixed	admin	Chris Johns	Chris Johns	5 days ago
Summary	Released RSB has no source set for rtems-tools					
Description	<p>Building a release RSB fails in the rtems-tools build with:</p> <pre>script: 85: rtems_tools_source="rtems-tools-5.0.0-m1911" script: 86: source_dir_rtems_tools=\${rtems_tools_source} source setup: rtems-tools-5.0.0-m1911-1: source rtems-tools -q -n \${rtems_tools_source} error: no source set: rtems-tools (source-rtems-tools)</pre>					
#3814	4 months ago	fixed	admin	Chris Johns	Chris Johns	4 months ago
Summary	Releasing creates 2 copies of the kernel and tools.					
Description	<p>The release snapshot <a href="#">m1911</a> as found here:</p> <p><a href="https://ftp.rtems.org/pub/rtems/releases/5/5.0.0/5.0.0-m1911/">https://ftp.rtems.org/pub/rtems/releases/5/5.0.0/5.0.0-m1911/</a></p> <p>has a kernel ( <a href="#">rtems-5.0.0-m1911.tar.xz</a> ) in the top directory and another copy in the <a href="#">sources</a> directory.</p> <p>The top level copy is the head of the branch, in this case <a href="#">master</a> while I suspect the copy in the <a href="#">sources</a> directory is created by the RSB when collecting the source.</p> <p>Which is correct for a release? I am not sure, the tagged version in the RSB or the release packaged version?</p> <p>I tend to think the release packaged version is used and the RSB collected versions should not be collected. They are only useful when working from git.</p>					
#3815	4 months ago	fixed	score	Sebastian Huber	Sebastian Huber	2 months ago
Summary	Improve SMP EDF scheduler configuration					
Description	It is currently quite easy to misconfigure the SMP EDF scheduler so that not enough memory is reserved for the scheduler data structures. The only feedback to the user from these configuration errors is a memory corruption. Improve the configuration means or at least issue a fatal error.					
#3821	4 months ago	fixed	network/libbsd	Sebastian Huber	Sebastian Huber	3 months ago
Summary	Port NVMe support from FreeBSD to libbsd					
#3823	3 months ago	fixed	rtems	Jonathan Brandmeyer	Sebastian Huber <sebastian.huber@...>	3 months ago
Summary	Untar_family doesn't handle nested directories					
Description	<p>At least, not in some circumstances.</p> <p>For example, foo/bar.txt untar's just fine, but foo/bar/baz.txt does not. If sub-directory foo/ exists first, then foo/bar/baz.txt does unpack correctly.</p> <p>We only use the Untar_*( ) family during our initial programming workflow, so hacking around this problem wasn't too laborious for us.</p>					
#3826	3 months ago	duplicate	shell	Chris Johns		3 months ago
Summary	top on SMP shows invalid priorities					
Description	<p>Running <a href="#">top</a> on a Zynq <a href="#">zc706</a> gives ...</p> <pre>ID   NAME   RPRI   CPRI   TIME   TOTAL   CURRENT -----+-----+-----+-----+-----+-----+----- 0x0a010008   IRQS       4611686018427388000   4611686018427388000   2.437559   0.000   0.022</pre> <p>The code in question is ... <a href="https://git.rtems.org/rtems/tree/cpukit/libmisc/cpuuse/cpuusagetop.c#n447">https://git.rtems.org/rtems/tree/cpukit/libmisc/cpuuse/cpuusagetop.c#n447</a></p> <p>What is best API to show a priority that makes this code robust?</p>					
#3830	3 months ago	fixed	tool/rsb	Sebastian Huber	Sebastian Huber	3 months ago
Summary	Build problems with user names which contain space characters					

Descripti on	The RSB uses the user name as path components. This does not work well if the user name contains space characters. Use the user ID number instead.					
#3831	3 months ago	fixed	doc	Joel Sherrill	Chris Johns	3 months ago
Summar y	Duplicate description of Tiers and Rules					
Descripti on	I think <a href="https://docs.rtems.org/branches/master/user/hardware/tiers.html">https://docs.rtems.org/branches/master/user/hardware/tiers.html</a> is intended to be the real site of this information. However, <a href="https://devel.rtems.org/wiki/Developer/Architectures">https://devel.rtems.org/wiki/Developer/Architectures</a> also describes the tiers rules with slightly different language. I think the Wiki page can be reviewed and removed. But any references and sub-pages should be dealt with at the same time. <a href="https://devel.rtems.org/search?q=Developer%2FArchitectures&amp;noquickjump=1&amp;wiki=on">https://devel.rtems.org/search?q=Developer%2FArchitectures&amp;noquickjump=1&amp;wiki=on</a> shows two sub-pages to deal with: <ul style="list-style-type: none"> <li><a href="https://devel.rtems.org/wiki/Developer/Architectures/ARM">https://devel.rtems.org/wiki/Developer/Architectures/ARM</a> which is one sentence and can be removed.</li> <li><a href="https://devel.rtems.org/wiki/Developer/Architectures/ARM/ARM-EABI">https://devel.rtems.org/wiki/Developer/Architectures/ARM/ARM-EABI</a> which probably should move to the Users Manual.</li> </ul> This would eliminate a few pages and a point of duplication for a very important concept to the RTEMS Project.					
#3833	3 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	3 months ago
Summar y	Simplify RTEMS semaphore configuration					
Descripti on	In SMP configurations, the maximum count of MrsP semaphores must be configured via CONFIGURE_MAXIMUM_MRSP_SEMAPHORES. The MrsP semaphore implementation predates the addition of self-contained synchronization objects. At this time, the potential memory reduction was justified considering the more complex configuration and additional use of the workspace. With the availability of self-contained synchronization options, e.g. POSIX mutexes, this is no longer justified. Memory constrained applications should use the self-contained synchronization objects. Remove the CONFIGURE_MAXIMUM_MRSP_SEMAPHORES configuration option. This has only an impact on applications which use SMP and a large number of scheduler instances.					
#3834	3 months ago	fixed	dev	Sebastian Huber	Sebastian Huber	2 months ago
Summar y	Simplify clock driver					
Descripti on	Use a system initialization handler to initialize the clock driver instead of using a legacy IO driver. This makes the system initialization more modular and removes a bit of overhead introduced by the legacy IO driver dependency.					
#3837	3 months ago	duplicate	config	Sebastian Huber	Sebastian Huber	3 months ago
Summar y	Rename CONFIGURE_LIBIO_MAXIMUM_FILE_DESCRIPTOR					
Descripti on	Rename CONFIGURE_LIBIO_MAXIMUM_FILE_DESCRIPTOR in CONFIGURE_MAXIMUM_FILE_DESCRIPTOR. Issue a C preprocessor warning if CONFIGURE_LIBIO_MAXIMUM_FILE_DESCRIPTOR is used and map it to CONFIGURE_MAXIMUM_FILE_DESCRIPTOR.					
#3839	3 months ago	fixed	build	Chris Johns	Chris Johns	3 months ago
Summar y	RTEMS revision does not handle <code>-</code>					
Descripti on	RTEMS configure logic that takes a version number and splits it into major, minor and revision values. The current release snapshots have a version number of <code>5.0.0-m1912</code> and this is not correct parsed.					
#3840	3 months ago	fixed	config	Sebastian Huber	Sebastian Huber	3 months ago
Summar y	Add CONFIGURE_IMFS_ENABLE_MKFIFO					
Descripti on	Obsolete undocumented configuration options CONFIGURE_MAXIMUM_FIFOS and CONFIGURE_MAXIMUM_PIPES. Replace them with a new option: CONFIGURE_IMFS_ENABLE_MKFIFO.					
#3841	3 months ago	fixed	rtems	Sebastian Huber	Sebastian Huber	2 months ago
Summar y	Add <code>rtems_object_get_local_node()</code>					
Descripti on	Add <pre>/**  * @brief Get the local MPC1 node number.  *  * @return The local MPC1 node number.  */ uint16_t rtems_object_get_local_node( void );</pre> to avoid the direct use of internal data structures.					
#3842	3 months ago	fixed	tool/rsb	Chris Johns	Chris Johns	3 months ago
Summar y	RSB RTEMS version message string is fixed to the git hash					
Descripti on	The version embedded in the RTEMS version message is currently the git hash. This breaks in a release where the version is reported as <code>no-repo</code> . The RTEMS version message is embedded in the gcc version string.					
#3843	3 months ago	fixed	config	Sebastian Huber	Sebastian Huber	3 weeks ago
Summar y	Add CONFIGURE_DIRTY_MEMORY					
Descripti on	Change the BSP_DIRTY_MEMORY BSP option (build-time configuration) into a CONFIGURE_DIRTY_MEMORY application configuration option (link-time configuration).					
#3844	3 months ago	fixed	config	Sebastian Huber	Sebastian Huber	3 months ago
Summar y	Remove CONFIGURE_HAS_OWN_DEVICE_DRIVER_TABLE					
Descripti on	Remove the CONFIGURE_HAS_OWN_DEVICE_DRIVER_TABLE configuration option. The RTEMS configuration should be done via explicit configuration options to allow more freedom for implementation changes. The CONFIGURE_HAS_OWN_DEVICE_DRIVER_TABLE configuration option had no test case. There was an attempt to get user feedback about this option: <a href="https://lists.rtems.org/pipermail/users/2019-April/033131.html">https://lists.rtems.org/pipermail/users/2019-April/033131.html</a>					
#3845	3 months ago	fixed	config	Sebastian Huber	Sebastian Huber	3 months ago
Summar y	Remove Ada-specific configuration options					
Descripti on	We have currently three Ada related configuration options: <ul style="list-style-type: none"> <li>CONFIGURE_GNAT_RTEMS</li> <li>CONFIGURE_MAXIMUM_ADA_TASKS</li> <li>CONFIGURE_MAXIMUM_FAKE_ADA_TASKS</li> </ul> The CONFIGURE_MAXIMUM_FAKE_ADA_TASKS option has no effect. The CONFIGURE_GNAT_RTEMS is mandatory to use the CONFIGURE_MAXIMUM_ADA_TASKS option. So, if you just use <pre>#define CONFIGURE_MAXIMUM_ADA_TASKS 123</pre> then you get a re-definition warning and hopefully pay attention to it. This is not very user friendly from point of view. The CONFIGURE_MAXIMUM_ADA_TASKS just adds the configured count to CONFIGURE_MAXIMUM_POSIX_THREADS. The original purpose of these was to: CONFIGURE_GNAT_RTEMS - add in resources required by Ada run-time independent of the number of Ada tasks (e.g. POSIX threads) CONFIGURE_MAXIMUM_ADA_TASKS - add in POSIX threads, condition variable, and mutex required for each Ada task CONFIGURE_MAXIMUM_FAKE_ADA_TASKS - add in condition variables and mutex required by Ada run-time for a task/thread created outside the Ada run-time which invokes Ada code and is thus a user of the run-time. Given that you can turn on unlimited threads now and condition variables and mutexes are static, I don't think they have a need any longer. Plus it sounds like they bit rotted. If we					

needed them still, they would have to be fixed.

We still need documentation that Ada tasks are POSIX threads and must be accounted for in configuring the system. So when moving documentation around, please make that point clear in the CONFIGURE\_MAXIMUM\_POSIX\_THREADS description.

See also:

<https://lists.rtems.org/pipermail/devel/2019-December/056523.html>

#3856	7 weeks ago	fixed	posix	Joel Sherrill	Joel Sherrill	7 weeks ago
Summary	posix_devctl - Add support for SOCKCLOSE					
Description	The FACE Technical Standard, Edition 3.0 and later require the definition of the subcommand SOCKCLOSE in <devctl.h>. Reference: <a href="https://www.opengroup.org/face">https://www.opengroup.org/face</a> The SOCKCLOSE constant has previously been added to <devctl.h> in newlib.					
#3857	6 weeks ago	fixed	posix	Joel Sherrill	Joel Sherrill	4 weeks ago
Summary	Use EAGAIN for POSIX mq wait in ISR error					
Description	POSIX message queues which are about to block in an ISR currently return ENOMEM. This is a status not listed by POSIX. The better status is EAGAIN per <a href="https://pubs.opengroup.org/onlinepubs/9699919799/functions/mq_receive.html">https://pubs.opengroup.org/onlinepubs/9699919799/functions/mq_receive.html</a> .					
#3861	4 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	4 weeks ago
Summary	Add CONFIGURE_VERBOSE_SYSTEM_INITIALIZATION					
Description	Add a configuration option to print some information during system initialization.					
#3862	4 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	4 weeks ago
Summary	Canonicalize CONFIGURE_ZERO_WORKSPACE_AUTOMATICALLY					
Description	The CONFIGURE_ZERO_WORKSPACE_AUTOMATICALLY configuration option is documented to be a boolean feature macro (is defined or undefined). However, in confdefs.h it uses the values TRUE and FALSE. It is the only configuration option implemented like this. Change it to use defined/undefined instead like the other options. This affects existing application configurations which use: <pre>#define CONFIGURE_ZERO_WORKSPACE_AUTOMATICALLY FALSE</pre> An unintentional zero of the workspace has an effect on the system boot time. This is an acceptable trade-off for the more canonical configuration.					
#3863	4 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	4 weeks ago
Summary	Remove support for the BSP_ZERO_WORKSPACE_AUTOMATICALLY BSP option					
Description	BSPs had the option to enable the CONFIGURE_ZERO_WORKSPACE_AUTOMATICALLY via the BSP_ZERO_WORKSPACE_AUTOMATICALLY BSP option. There is no BSP which defines this option. In addition, it makes no sense that a BSP can influence this high level system configuration.					
#3865	4 weeks ago	fixed	score	Sebastian Huber	Sebastian Huber	4 weeks ago
Summary	Fix linker set item declarations for small data area targets					
Description	Some targets (e.g. 32-bit PowerPC) have a small-data area. Linker set items are not in the small data area. We have to tell this the compiler, otherwise linker error may occur due to a mismatch of relocations. There are two options to do this. <ol style="list-style-type: none"><li>1. We can declare items as an array of unspecified size and define items as an array with one element. The problem with this is that it breaks existing code, e.g. an item initializer would have to change.</li><li>2. We add the section to the declaration. The problem is that in this case we need a dedicated declaration macro for the ordered items.</li></ol> Since item declarations are rarely used, we select option 2.					
#3868	3 weeks ago	fixed	tool/rsb	Chris Johns	Chris Johns <chrisj@...>	3 weeks ago
Summary	newlib links breaks mingw build					
Description	The following patch in newlib adds links and Windows does not have symlinks and it is emulated as copy. This complicates a bsdtar extraction of source ... <a href="https://github.com/RTEMS/sourceware-mirror-newlib-cygwin/commit/cfc4955234828881145a20987c8a0a3cd373585c">https://github.com/RTEMS/sourceware-mirror-newlib-cygwin/commit/cfc4955234828881145a20987c8a0a3cd373585c</a> I tried the <code>-E</code> option that was added to the RSB to extract the tar file a second time, this has worked with other tar files with symlinks however it does not work. I have no investigated why. We need Windows building to make a release. <b>Note, this is in the <code>tools/rsb</code> component however is not an RSB bug. I need input on what the RSB needs to do to fix this issue if that is the path we take.</b>					
#3871	3 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	2 weeks ago
Summary	Remove rtems_configuration_get_posix_api_configuration()					
Description	The corresponding data structure not longer exists. This function was not tested.					
#3873	3 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	8 days ago
Summary	Remove CONFIGURE_HAS_OWN_INIT_TASK_TABLE					
Description	The CONFIGURE_HAS_OWN_INIT_TASK_TABLE and CONFIGURE_POSIX_HAS_OWN_INIT_THREAD_TABLE are the last <code>*_HAS_OWN_*</code> configuration options. These two options are probably unused, see also: <a href="https://lists.rtems.org/pipermail/users/2019-April/033129.html">https://lists.rtems.org/pipermail/users/2019-April/033129.html</a> <a href="https://lists.rtems.org/pipermail/users/2019-April/033130.html">https://lists.rtems.org/pipermail/users/2019-April/033130.html</a> Removing them simplifies the configuration. If there is a real user need which shows up after the removal, we can resurrect them on demand. Using CONFIGURE_HAS_OWN_INIT_TASK_TABLE would have required the use of the undocumented CONFIGURE_INIT_TASK_TABLE and CONFIGURE_INIT_TASK_TABLE_SIZE configuration options.					
#3874	3 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	8 days ago
Summary	Remove CONFIGURE_POSIX_HAS_OWN_INIT_THREAD_TABLE					
Description	The CONFIGURE_HAS_OWN_INIT_TASK_TABLE and CONFIGURE_POSIX_HAS_OWN_INIT_THREAD_TABLE are the last <code>*_HAS_OWN_*</code> configuration options. These two options are probably unused, see also: <a href="https://lists.rtems.org/pipermail/users/2019-April/033129.html">https://lists.rtems.org/pipermail/users/2019-April/033129.html</a> <a href="https://lists.rtems.org/pipermail/users/2019-April/033130.html">https://lists.rtems.org/pipermail/users/2019-April/033130.html</a> Removing them simplifies the configuration. If there is a real user need which shows up after the removal, we can resurrect them on demand. Using CONFIGURE_POSIX_HAS_OWN_INIT_THREAD_TABLE would have required the use of the undocumented CONFIGURE_POSIX_INIT_THREAD_TABLE_NAME and CONFIGURE_POSIX_INIT_THREAD_TABLE_SIZE configuration options.					
#3875	3 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	8 days ago
Summary	Split up confdefs.h in component based header files					
Description	The confdefs.h header file is large, complex, and hard to review. Split it up into component header files to make it easier to maintain and review. The general approach is to place the default configuration of things in librtmscpu.a. The benefit is that the application configuration object file will only include data structures which have a user-defined value. The component based header files include their dependencies explicitly. It should be possible to include component based header files separately to ease testing. For example we could use this template:					

```
#ifndef RTEMS_CONFDEFS_FOOBAR_H
#define RTEMS_CONFDEFS_FOOBAR_H

#ifdef CONFIGURATION_TEMPLATE_h
#error "Do not include this file directly, use <rtems/confdefs.h> instead"
#endif

#ifdef CONFIGURE_INIT && \
    defined(CONFIGURE_FOOBAR_STUFF) && \
    defined(CONFIGURE_MORE_FOOBAR_STUFF)

/* Foobar includes */

#ifdef __cplusplus
extern "C" {
#endif /* __cplusplus */

/* Configure foobar. */

#ifdef __cplusplus
}
#endif /* __cplusplus */

#endif /* CONFIGURE_INIT */

#endif /* RTEMS_CONFDEFS_FOOBAR_H */
```

In case CONFIGURE\_INIT is not defined, then including <rtems/confdefs.h> should expose nothing to the C compiler.

Here is a first proposal to group the configuration in components:

Descripti  
on

```
rtems/
confdefs.h
This file just includes the component based header files listed below.
confdefs/
bdbuf.h
classicobj.h
Classic API objects
classictaskinit.h
Classic initialization task
driverclock.h
Clock driver and related configuration, e.g. CONFIGURE_MICROSECONDS_PER_TICK
driverconsolesimple.h
Simple console driver configuration
driverlegacy.h
Legacy IO driver configuration table
extensions.h
User extensions, internal extensions
filesystem.h
Filesystem configuration
general.h
Basic stuff which is mandatory to configure, e.g. ISR stacks, per-CPU information
libpci.h
PCI library configuration
malloc.h
Malloc configuration
mpci.h
MPCI specific configuration options
msgq.h
General message queue configuration
obsolete.h
Warning about the use of obsolete configure options
posixkeys.h
POSIX keys
posixobj.h
POSIX objects
posixthreadsinit.h
POSIX initialization threads
scheduler.h
Scheduler configuration
support.h
Support macros for confdefs header files
threads.h
General thread configuration (e.g. thread control block)
unlimited.h
Unlimited objects configuration
```

<b>#3876</b>	3 weeks ago	fixed	config	Sebastian Huber	Sebastian Huber	8 days ago
Summary	Remove CONFIGURE_DISABLE_SMP_CONFIGURATION					
Description	The CONFIGURE_DISABLE_SMP_CONFIGURATION configuration option and rtems_configuration_is_smp_enabled() were added during the SMP support development cycle as a workaround to fix some testsuite failures in SMP configurations. Replace this configuration option with tests for specific conditions. The configuration option was undocumented.					
<b>#3881</b>	9 days ago	fixed	rtems	Sebastian Huber	Sebastian Huber	19 hours ago
Summary	Add API functions to map a task priority to/from a POSIX thread priority					
Description	Mapping task priorities to/from POSIX thread priorities is probably done in many applications. There seems to be no API to help doing this. Add the following API functions to map a task priority to/from a POSIX thread priority:					

**Description**  

```

/**
 * @brief Map a task priority to the corresponding POSIX thread priority.
 *
 * @param scheduler_id Identifier of the scheduler instance.
 * @param priority The task priority to map.
 * @param[out] posix_priority Pointer to a POSIX thread priority value.
 *
 * @retval RTEMS_SUCCESSFUL Successful operation.
 * @retval RTEMS_INVALID_ADDRESS The @a posix_priority parameter is @c NULL.
 * @retval RTEMS_INVALID_ID Invalid scheduler instance identifier.
 * @retval RTEMS_INVALID_PRIORITY Invalid task priority.
 */
rtems_status_code rtems_scheduler_map_to_posix_priority(
  rtems_id scheduler_id,
  rtems_task_priority priority,
  int *posix_priority
);

/**
 * @brief Map a POSIX thread priority to the corresponding task priority.
 *
 * @param scheduler_id Identifier of the scheduler instance.
 * @param posix_priority The POSIX thread priority to map.
 * @param[out] priority Pointer to a task priority value.
 *
 * @retval RTEMS_SUCCESSFUL Successful operation.
 * @retval RTEMS_INVALID_ADDRESS The @a priority parameter is @c NULL.
 * @retval RTEMS_INVALID_ID Invalid scheduler instance identifier.
 * @retval RTEMS_INVALID_PRIORITY Invalid POSIX thread priority.
 */
rtems_status_code rtems_scheduler_map_from_posix_priority(
  rtems_id scheduler_id,
  int posix_priority,
  rtems_task_priority *priority
);

```

#3882	8 days ago	fixed	posix	Sebastian Huber	Sebastian Huber	8 days ago
-------	------------	-------	-------	-----------------	-----------------	------------

**Summary**  
Add POSIX user environment pointer to TCB

**Description**  
The IO library uses a POSIX key to store an optional POSIX user environment pointer. This pulls in the POSIX keys support in every application configuration. Add a user environment pointer to the thread control block (TCB) instead. Applications which do not need the POSIX user environment will just get an overhead of one pointer per thread.

#3885	7 days ago	fixed	score	Sebastian Huber	Sebastian Huber	13 hours ago
-------	------------	-------	-------	-----------------	-----------------	--------------

**Summary**  
Context switch extension is broken in SMP configurations

The context switch extensions are called during `_Thread_Do_dispatch()`:

```

void _Thread_Do_dispatch( Per_CPU_Control *cpu_self, ISR_Level level )
{
  Thread_Control *executing;

  executing = cpu_self->executing;

  ...
  do {
    Thread_Control *heir;

    heir = _Thread_Get_heir_and_make_it_executing( cpu_self );
    ...
    _User_extensions_Thread_switch( executing, heir );
    ...
    _Context_Switch( &executing->Registers, &heir->Registers );
    ...
  } while ( cpu_self->dispatch_necessary );
  ...
}

```

**Description**

In uniprocessor configurations, the context switch extensions are called for all thread switches except the very first thread switch to the initialization thread. However, in SMP configurations, the context switch may be invalidated and updated in the low-level `_Context_Switch()` routine. See:

[https://docs.rtems.org/branches/master/c-user/symmetric\\_multiprocessing\\_services.html#thread-dispatch-details](https://docs.rtems.org/branches/master/c-user/symmetric_multiprocessing_services.html#thread-dispatch-details)

In case such an update happens, a thread executes on the processor which was not visible to the context switch extensions. This can confuse for example event record consumers which use events generated by a context switch extension.

Fixing this is not straight forward. The context switch extensions call must move after the low-level context switch. The problem here is that we may end up in `_Thread_Handler()`. Adding the context switch extensions call to `_Thread_Handler()` covers now also the thread switch to the initialization thread. We also have to save the last executing thread of the processor. Registers or the stack cannot be used for this purpose. We have to add it to the per-processor information. Existing extensions may be affected, since now context switch extensions use the stack of the heir thread.

Calling the thread switch extensions in the low level context switch is difficult since at this point an intermediate stack is used which is only large enough to enable servicing of interrupts.

#3893	3 days ago	fixed	tool/rsb	Chris Johns	Chris Johns	2 hours ago
-------	------------	-------	----------	-------------	-------------	-------------

**Summary**  
RSB staging changes have broken building a 3rd party package

The staging changes let a fully staged vertical stack to build however building the packages for an installed tool chain and BSP is broken.

**Description**

```

./source-builder/sb-set-builder --log=bbb-pkg.txt --prefix=/build/rtems/install/5 --host=arm-rtems5 --with-rtems-bsp=beagleboneblack 5/rtems-packages

```

tags  
5.1 release

Last modified on Nov 9, 2017, 6:38:58 AM