



## RTEMS - 6.1-rc2 Release Notes

20 February 2024

RTEMS 6 Series Release Notes

These notes cover the dot releases:

6.1



# RTEMS 6.1-rc2 Embedded Realtime Operating System

## Table of Content

- [RTEMS 6.1 Release Notes](#)
  - [RTEMS Improvements](#)
  - [API Changes](#)
    - [API Additions](#)
    - [API Implementation Improvements](#)
    - [API Deprecations](#)
    - [API Removals](#)
  - [SMP Support Improvements](#)
  - [Configuration Changes](#)
- [RTEMS Shell Improvements](#)
- [General](#)
- [Architectures](#)
- [BSPs and Device Drivers](#)
- [Newlib Changes](#)
- [Ecosystem](#)
- [RTEMS 6.1 Ticket Overview](#)
- [RTEMS 6.1 Ticket Summary](#)
- [RTEMS 6.1 Tickets By Category](#)
- [RTEMS 6.1 Tickets](#)

## RTEMS Release 6.1

### RTEMS 6.1 Release Notes

#### RTEMS Improvements

In this section, we discuss public API level changes as well as improvements to the implementation of those API routines.

Public API changes usually fall into one of the following categories:

- Addition of new methods
- Modifications to prototypes
- Deletion of obsoleted methods

Implementation improvements usually fall into one of the following categories:

- Algorithm improvements in execution time or memory usage
- Critical section reduction

#### API Changes

- If the processor set is not large enough to contain the processor set of the scheduler, then `rtems_scheduler_get_processor_set()` returns `RTEMS_INVALID_SIZE` instead of `RTEMS_INVALID_NUMBER`.
- If the processor set is not large enough to contain the processor affinity set of the task, then `rtems_task_get_affinity()` returns `RTEMS_INVALID_SIZE` instead of `RTEMS_INVALID_NUMBER`.

- If time-of-day argument is NULL, then `rtems_timer_fire_when()`, `rtems_timer_server_fire_when()`, and `rtems_task_wake_when()` return `RTEMS_INVALID_ADDRESS` instead of `RTEMS_INVALID_CLOCK`.
- The time-of-day arguments in `rtems_timer_fire_when()`, `rtems_timer_server_fire_when()`, and `rtems_task_wake_when()` were constified.
- If the entry point is NULL, then `rtems_task_start()` returns now `RTEMS_INVALID_ADDRESS`.
- If `rtems_task_delete()` is called from within interrupt context, then it returns now `RTEMS_CALLED_FROM_ISR`.
- The rate monotonic period statistics are no longer affected by `rtems_cpu_usage_reset()`.
- **Termios**
  - `txTaskCharsDequeued` has been added to `struct rtems_termios_tty`. With that the size of the structure changed. Libraries and applications that use the structure should be recompiled.
  - The `l_start` line discipline function now receives the number of characters that have been sent. It is safe to ignore the extra parameter for applications that don't need it.

## API Additions

- `RTEMS_ALIGN_UP()`
- `RTEMS_ALIGN_DOWN()`
- `rtems_get_build_label()`
- `rtems_get_target_hash()`
- `rtems_interrupt_clear()`
- `rtems_interrupt_entry_initialize()`
- `RTEMS_INTERRUPT_ENTRY_INITIALIZER()`
- `rtems_interrupt_entry_install()`
- `rtems_interrupt_entry_remove()`
- `rtems_interrupt_get_affinity()`
- `rtems_interrupt_get_attributes()`
- `rtems_interrupt_handler_install()`
- `rtems_interrupt_handler_iterate()`
- `rtems_interrupt_handler_remove()`
- `rtems_interrupt_is_pending()`
- `rtems_interrupt_raise()`
- `rtems_interrupt_raise_on()`
- `rtems_interrupt_server_action_prepend()`
- `rtems_interrupt_server_create()`
- `rtems_interrupt_server_delete()`
- `rtems_interrupt_server_entry_destroy()`
- `rtems_interrupt_server_entry_initialize()`
- `rtems_interrupt_server_entry_move()`
- `rtems_interrupt_server_entry_submit()`
- `rtems_interrupt_server_handler_install()`
- `rtems_interrupt_server_handler_iterate()`
- `rtems_interrupt_server_handler_remove()`
- `rtems_interrupt_server_initialize()`

- `rtems_interrupt_server_move()`
- `rtems_interrupt_server_request_destroy()`
- `rtems_interrupt_server_request_initialize()`
- `rtems_interrupt_server_request_set_vector()`
- `rtems_interrupt_server_request_submit()`
- `rtems_interrupt_server_resume()`
- `rtems_interrupt_server_set_affinity()`
- `rtems_interrupt_server_suspend()`
- `rtems_interrupt_set_affinity()`
- `rtems_interrupt_vector_disable()`
- `rtems_interrupt_vector_enable()`
- `rtems_interrupt_vector_is_enabled()`
- `RTEMS_MESSAGE_QUEUE_BUFFER()`
- `rtems_message_queue_construct()`
- `RTEMS_PARTITION_ALIGNMENT`
- `rtems_task_construct()`
- `RTEMS_TASK_STORAGE_SIZE()`
- `RTEMS_TASK_STORAGE_ALIGNMENT`

### API Implementation Improvements

- The Classic API signal processing was reworked to avoid possible infinite recursions. It is still strongly recommended to use the `RTEMS_NO_ASR` task mode for the signal handler.
- Zero size allocation results are now consistent accross directives, for example `malloc( 0 )` and `posix_memalign( &p, align, 0 )` return now a unique pointer (or `NULL` if the heap is empty). In POSIX, zero size memory allocations are implementation-defined behaviour. The implementation has two options:
  - <https://pubs.opengroup.org/onlinepubs/9699919799/functions/malloc.html>
  - [https://pubs.opengroup.org/onlinepubs/9699919799/functions/posix\\_memalign.html](https://pubs.opengroup.org/onlinepubs/9699919799/functions/posix_memalign.html)

Linux and FreeBSD return a unique pointer for zero size memory allocations. This approach is now also used in RTEMS as well throughout the memory allocation directives

### API Deprecations

- `rtems_iterate_over_all_threads()`. Use `rtems_task_iterate()` instead.
- `_Copyright_Notice` is deprecated. Use `rtems_get_copyright_notice()` instead.
- `_RTEMS_version` is deprecated. Use `rtems_get_version_string()` instead.
- `RTEMS_COMPILER_NO_RETURN_ATTRIBUTE` is deprecated. Use `RTEMS_NO_RETURN` instead.
- `RTEMS_COMPILER_PURE_ATTRIBUTE` is deprecated. Use `RTEMS_PURE` instead.
- `RTEMS_COMPILER_DEPRECATED_ATTRIBUTE` is deprecated. Use `RTEMS_DEPRECATED` instead.
- `RTEMS_COMPILER_UNUSED_ATTRIBUTE` is deprecated. Use `RTEMS_UNUSED` instead.
- `RTEMS_COMPILER_PACKED_ATTRIBUTE` is deprecated. Use `RTEMS_PACKED` instead.

### API Removals

- The obsoleted header file `<rtems/system.h>` was removed.
- The never implemented `rtems_interrupt_cause()` directive was removed.
- Support for the RTEMS thread model used by GCC versions prior to 6.1 was removed (for example `rtems_gxx_once()`).

- The obsolete `rtems_get_current_processor()` directive was removed. Use `rtems_scheduler_get_processor()` instead.
- The obsolete `rtems_get_processor_count()` directive was removed. Use `rtems_scheduler_get_processor_maximum()` instead.
- The obsolete `boolean` type was removed. Use `bool` instead.
- The obsolete `single_precision` type was removed. Use `float` instead.
- The obsolete `double_precision` type was removed. Use `double` instead.
- The obsolete `proc_ptr` type was removed. Use a proper function pointer type.
- The obsolete `rtems_context` type was removed.
- The obsolete `rtems_context_fp` type was removed.
- The obsolete `rtems_extension` type was removed. Use `void` instead.
- The obsolete `rtems_io_lookup_name()` type was removed. Use `stat()` instead.
- The obsolete `region_information_block` was removed. Use `Heap_Information_block` instead.
- The obsolete `rtems_thread_cpu_usage_t` type was removed. Use `struct timespec` instead.
- The obsolete `rtems_rate_monotonic_period_time_t` type was removed. Use `struct timespec` instead.
- The obsolete `RTEMS_MAXIMUM_NAME_LENGTH` define was removed. Use `sizeof(rtems_name)` instead.

## SMP Support Improvements

- The SMP scheduler framework was reworked to fix potential data corruption issues and priority group ordering violations.

## Configuration Changes

- TBD
- New configuration options:
  - `CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE`
  - `CONFIGURE_MINIMUM_TASKS_WITH_USER_PROVIDED_STORAGE`
- Renamed configuration options:
  - TBD
- Removed configuration options:
  - TBD

---

## RTEMS Shell Improvements

The following improvements were made to the RTEMS Shell:

- TBD

---

## General

- The obsolete `libmisc/serdbg` was removed. Use `libdebugger` instead. This functionality was not built as part of the 5 release series in anticipation of its removal.

---

## Architectures

Removed obsolete architectures:

- Epiphany
- PowerPC SPE

Obsoleted architectures:

- V850
  - SPARC64
  - SuperH (sh)
- 

## BSPs and Device Drivers

- General
    - TBD
  - New BSPs
    - arm/fvp
    - arm/imxrt
    - arm/stm32h7
  - Significant updates to existing BSPs
    - ARCH/BSP: TBD
  - Removal of obsoleted BSPs
    - powerpc/brs51
    - powerpc/brs61
    - powerpc/dp2
    - powerpc/haleakala
    - powerpc/mpc5566evb\_spe
    - powerpc/mpc56431\_dpu
    - powerpc/mpc56431\_evb
    - powerpc/mpc5674f\_ecu508\_app
    - powerpc/mpc5674f\_ecu508\_boot
    - powerpc/mpc5674fevb\_spe
    - powerpc/mpc5674f\_rsm6
  - Obsoleted BSPs
    - m68k/gen68302
    - m68k/ods68302
    - powerpc/mbx8xx
  - Drivers
    - TBD
- 

## Newlib Changes

- Add `futimens()` and `utimensat()`
- 

## Ecosystem

- Improved GCOV support for RTEMS and embedded systems in general. See GCC options `-fprofile-info-section` and `-fprofile-update=atomic`. The `libgcov` provides now the `__gcov_info_to_gcda()` function to dump the GCOV information.

## RTEMS 6.1 Ticket Overview

Total	Closed	In progress	New	Assigned	Percentage
572	530	0	7	31	93%

## RTEMS 6.1 Ticket Summary

ID	Status	Summary
<a href="#">1318</a>	closed	libcpu/shared is not helpful
<a href="#">1459</a>	closed	Add rtems_shell_main_monitor to cpukit/libmisc/shell/shell.h?
<a href="#">1593</a>	closed	RTEMS Sequenced Initialization API
<a href="#">1712</a>	closed	Add LWIP Support to RTEMS
<a href="#">1728</a>	closed	Patch for RTEMS-BSP m68k/mcf5225x
<a href="#">1815</a>	closed	_ISR_Nest_level should be protected with interrupts disabled in function _Watchdog_Insert
<a href="#">1820</a>	closed	sptestes/sp36: Improper buildsystem integration
<a href="#">2000</a>	closed	Re-add removed LINK_OBJS to MP tests
<a href="#">2071</a>	closed	The object-file suffixes for default-bsp-post-link in leaf.cfg don't work with make-exe...
<a href="#">2111</a>	closed	AVR needs avr-libc to compile RTEMS.
<a href="#">2114</a>	closed	statvfs for MS-DOS filesystem and 'df' command for shell
<a href="#">2189</a>	closed	Insufficient documentation for rtems_clock_get_tod()
<a href="#">2215</a>	closed	Duplicate code for TAR support
<a href="#">2269</a>	closed	x86 Context Switch Synchronization and SMP
<a href="#">2301</a>	closed	cpukit is built in BSP, and BSP custom, specific part of build tree but isnt built using BSP's spec file
<a href="#">2330</a>	closed	nios2 missing atomics, fails to link C++
<a href="#">2348</a>	closed	Timecounter: Add NTP support
<a href="#">2349</a>	closed	Timecounter: Add PPS support
<a href="#">2365</a>	closed	Task pre-emption disable is broken due to pseudo ISR tasks
<a href="#">2778</a>	closed	Error building RTEMS Source Builder recipe for libxml
<a href="#">2828</a>	closed	Remove libmisc/serdbg
<a href="#">2869</a>	closed	Remove support for 16-bit object identifiers
<a href="#">2871</a>	closed	Use bibtex references throughout the documentation
<a href="#">2872</a>	closed	Get rid of CONFIGURE_MAXIMUM_PTYS
<a href="#">2902</a>	closed	Port RTEMS to Microblaze
<a href="#">2971</a>	closed	Add fenv.h to newlib
<a href="#">2985</a>	closed	Add documentation for printf()
<a href="#">3143</a>	closed	Remove obsolete rtems_gxx_*() implementation
<a href="#">3199</a>	closed	New test framework
<a href="#">3230</a>	accepted	RSB does not report --rsb-file for patches correctly.
<a href="#">3250</a>	closed	Remove Use of bsp_specs
<a href="#">3269</a>	closed	Make the IRQ extensions API a standard API
<a href="#">3321</a>	closed	Improve console driver documentation
<a href="#">3414</a>	closed	Remove Makefiles from rtems-examples?
<a href="#">3420</a>	closed	Deprecate/obsolete rtems_io_lookup_name
<a href="#">3456</a>	closed	Add support for CPU counter timestamps
<a href="#">3566</a>	closed	Remove checks for Newlib features introduced during the RTEMS 5 development
<a href="#">3584</a>	closed	Remove types which are only available if RTEMS_DEPRECATED_TYPES is defined
<a href="#">3586</a>	closed	Remove deprecated proc_ptr definition
<a href="#">3588</a>	closed	Remove deprecated rtems_context
<a href="#">3590</a>	closed	Remove deprecated rtems_context_fp
<a href="#">3592</a>	closed	Remove deprecated region_information_block
<a href="#">3594</a>	closed	Remove deprecated rtems_thread_cpu_usage_t
<a href="#">3596</a>	closed	Remove deprecated rtems_rate_monotonic_period_time_t
<a href="#">3613</a>	closed	Remove m32c architecture port from upstream tools
<a href="#">3615</a>	closed	Convert Tools_Used Wiki page into Support Tools Selection with Criteria
<a href="#">3657</a>	closed	Add support for poll.h method - poll
<a href="#">3659</a>	closed	LEON3 kernel entry point is overwritten - secondary processors may enter into spurious handler
<a href="#">3689</a>	closed	bdbuf: Replace automatic read-ahead with rtems_bdbuf_peek()
<a href="#">3698</a>	closed	libdl failure on many PowerPC BSPs
<a href="#">3702</a>	closed	Space profile for RTEMS SMP
<a href="#">3704</a>	closed	Review and update Doxygen recommendations
<a href="#">3705</a>	closed	Software Design Document (SDD) for space profile
<a href="#">3706</a>	closed	Create a hierarchy of RTEMS software components using Doxygen groups
<a href="#">3707</a>	closed	Assign each code file to a Doxygen group
<a href="#">3715</a>	closed	Add Requirements Engineering chapter to RTEMS Software Engineering Handbook
<a href="#">3717</a>	closed	Add test guidelines chapter to RTEMS Software Engineering Handbook
<a href="#">3718</a>	closed	Add support for test plans
<a href="#">3719</a>	closed	Update libcrypt to latest FreeBSD to address Coverity Scan Issues
<a href="#">3726</a>	closed	Select a requirements engineering tool
<a href="#">3818</a>	closed	New build system
<a href="#">3828</a>	closed	Switch over to new build system
<a href="#">3846</a>	closed	Build system does not track the dependencies of start.o files
<a href="#">3847</a>	closed	Test programs are not re-linked if a start.o or linker command file changes
<a href="#">3853</a>	closed	Add and use project-wide glossary to documentation
<a href="#">3866</a>	closed	Add support for GCC 10 noinit attribute
<a href="#">3878</a>	closed	rtems06: All BSPs Fail to build with BSP Builder on rtems 6
<a href="#">3883</a>	closed	Trace linker is broken on small-data area targets
<a href="#">3886</a>	closed	Fail an RSB build with --mail option if a repo is not clean

ID	Status	Summary
3907	closed	3866: Does not daemonize
3910	closed	Add BSP for STM32H7
3924	closed	Test the application configuration options
3925	closed	Optimize work area initialization
3929	closed	Document use of virtualenv
3935	closed	Remove use of RTEMS_INLINE_ROUTINE in the RTEMS sources
3937	closed	Move content of bsp_specs to GCC
3941	closed	Remove epiphany architecture support
3942	closed	multiple definition of 'pci_indirect_functions'
3947	closed	fdt_rw.c: Unchecked return value (CID #1047324)
3951	closed	Remove obsolete powerpc BSPs
3957	closed	Review wiki/Developer for deletion
3959	closed	Add rtems_task_construct()
3962	closed	Licensing Requirements for Submissions Poorly Documented
3977	closed	Add unexplained-failure as option for Test Configuration Files
3978	closed	Move _RTEMS_version to implementation header file
3979	closed	Remove RTEMS_MAXIMUM_NAME_LENGTH
3980	closed	Remove deprecated <rtems/system.h>
3981	closed	Remove _Copyright_Notice from API header file
3982	closed	Test failures on BSPs with sbrk() support
3988	closed	Remove deprecated rtems_extension
3989	closed	Remove deprecated rtems_get_current_processor()
3990	closed	Remove deprecated rtems_get_processor_count()
3991	closed	Remove deprecated Thread typedef
3993	closed	Specify the RTEMS Classic API
3994	closed	Generate Doxygen markup for the application configuration options
3996	closed	fenv support is missing on powerpc
3997	closed	fenv support is missing on sparc
3998	closed	fenv support is missing on arm
4007	closed	Add rtems_message_queue_construct()
4018	closed	libcpusupport: Architecture defines are present outside CPU port
4020	closed	Change all version numbers to RTEMS 6 on the master branches
4025	closed	NFS Client is broken on 64-bit targets
4029	closed	i386: SMP-System hangs with non-consecutive APIC IDs
4031	closed	i386: ISR can overwrite its own stack during system initialization (cloned)
4032	closed	Make deferred free in malloc() support optional
4034	closed	Add rtems_interrupt_server_create() and rtems_interrupt_server_destroy() (cloned)
4036	closed	Track dependency command for the RSB
4037	closed	Python script distribution standardisation
4039	closed	arm/atsam/SC16IS752: Make interrupt server configurable (cloned)
4040	closed	coverhd.h remnants left to remove
4043	closed	Update software eng manual to rtems-central
4044	closed	Add RSB Track command
4045	closed	Remove RSB sb-builder command
4046	closed	Remove RSB sb-bootstrap command
4048	closed	Move RTEMS 5 BSP and package build sets and configs to RTEMS 6
4052	closed	[libbsd] e1000 driver not working for i386 based BSP in current rtems-libbsd master
4054	closed	RTEMS_BARRIER_AUTOMATIC_RELEASE and RTEMS_BINARY_SEMAPHORE options have the same value
4055	closed	bsps/xilinx-zynq: Flush TX-Buffer before initializing the zynq-uart
4061	closed	The reworked <rtems/confdefs.h> has a cyclic dependency with RTEMS_MULTIPROCESSING enabled (cloned)
4063	closed	Change to a simpler TFTP server for rtems-test
4065	closed	Typo in rtems-boot.ini "ubootdir" should be "ubootdir"
4066	closed	test running for too long
4067	closed	Libbsd build system does not separate kernel and user land include paths
4069	closed	d106 does not link on RISC-V
4070	closed	RISC-V Multiple Definition Error (many BSPs)
4072	assigned	testsuite: Add ticket ids for expected-fail and indeterminate states, add annotations
4074	closed	Add CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE
4076	closed	i386: bad asm in smp mode
4077	closed	Implement LibBSD module dependencies in the build system
4078	closed	GCC C++ compiler for powerpc defines _GNU_SOURCE as a built-in
4079	closed	build: i386/pc686/appstart.o is created more than once
4080	closed	build: Add start.o dependency to the executable link step
4081	closed	Remove Autoconf/Automake based build system
4084	closed	throwing std::runtime on PC BSP fails
4093	closed	bsps/pc386: Add missing license header
4095	assigned	Remove doc from rtems-tools
4097	closed	shell: CTRL-U sets the cursor to the wrong position (cloned)
4098	closed	All BSP bsets fail to build on master
4100	closed	arm/edb7312 Build Failure When SMP is Enabled
4101	closed	atsamv fails to build on master
4103	closed	BeagleBoard BSPs Fail to Build
4105	closed	Add RTEMS_PARTITION_ALIGNMENT
4107	closed	waf -j24 fails on powerpc/psim -- probable dependency issue
4108	closed	Review minimum and ensure it really is a minimum configuration
4110	closed	Ubuntu package list is broken
4115	closed	Cortex-A9 MPCore based BSPs should include the workaround for Errata 794072 and 845369
4116	closed	raspberrypi fails to build on waf and autoconf
4117	closed	lpc1768_mbed_ahb_ram_eth sp01 and others fail to link
4118	closed	Add clang variants for sparc BSPs
4120	closed	altcycv_devkit and imx7 fail to build all tests on master
4121	closed	lm3s3749 fails to build all tests on master
4122	closed	Change RTEMS_NO_RETURN to use C11 and C++11 standard means



ID	Status	Summary
<a href="#">4123</a>	closed	rtems-bsp-builder needs to be switched to look at waf info for BSPs
<a href="#">4124</a>	closed	rtems-bsp-builder needs to be switched to waf builds
<a href="#">4125</a>	assigned	Update wiki pages to reference waf not autoconf based build
<a href="#">4126</a>	closed	Remove legacy networking stack from rtems.git and place in a new repo
<a href="#">4127</a>	closed	x86_64/amd64 fails to build
<a href="#">4128</a>	closed	all griscv variants fail to build on master
<a href="#">4129</a>	closed	x86_64 not listed as architecture in components in Trac
<a href="#">4131</a>	closed	"fdisk DISK_NAME mount" in bdpart-mount.c uses non-existing file system type "msdos"
<a href="#">4134</a>	closed	rtemsspec: Support user-defined ordering of directives in header files (Doxygen)
<a href="#">4140</a>	closed	waf install of RTEMS breaks Makefile system in rtems-examples
<a href="#">4142</a>	closed	Sparse disk destroys data when it grows
<a href="#">4143</a>	closed	fileio - Stack too small for login with password
<a href="#">4145</a>	closed	rtems-source-builder: Update RTEMS Kernel Recipe to Use waf for RTEMS
<a href="#">4148</a>	closed	RFS bit map search buffer overflow
<a href="#">4155</a>	closed	Add a workaround for the LEON3FT RETT Restart errata: TN-0018
<a href="#">4157</a>	closed	pthread_spin_unlock() may corrupt the thread stack if RTEMS_PROFILING and RTEMS_SMP is enabled
<a href="#">4158</a>	closed	rtems_interrupt_server_delete() does not destroy the ISR lock of the server control
<a href="#">4164</a>	closed	Fix NVMe disk synchronization and media block handling
<a href="#">4166</a>	closed	rtems-bsp-builder: Add way to select rtems version (6 vs 7)
<a href="#">4167</a>	closed	Coverity Scan Does Not Run on rtems6
<a href="#">4175</a>	closed	Resolve warning during AArch64 build
<a href="#">4180</a>	closed	Add BSP for i.MXRT1050
<a href="#">4181</a>	closed	Add CONFIGURE_INIT_TASK_STORAGE_SIZE
<a href="#">4184</a>	closed	arm/bsps: Small MMU pages are rounded to 1 MiB
<a href="#">4192</a>	closed	bsp/xilinx_zynq: Enable support for small MMU pages
<a href="#">4193</a>	closed	devctl.h does not compile from C++ (cloned)
<a href="#">4194</a>	closed	RSB failed with mail subject: Build Linux: PASSED 6/rtems-arm on x86_64-linux-gnu
<a href="#">4195</a>	closed	Add gr740 support available in SIS 2.25 to the RTEMS Tester
<a href="#">4196</a>	closed	Improve gcov support provided by GCC for RTEMS
<a href="#">4197</a>	closed	testsuite: ts-validation-0 broken on AArch64 due to SIZE_MAX issues in the test design
<a href="#">4198</a>	closed	arm: Add multilib for Cortex-R52 processor
<a href="#">4200</a>	closed	Build system doco link in the User Guide is broken
<a href="#">4201</a>	closed	waf building out of source tree does not find all configured bsps
<a href="#">4202</a>	closed	Add BSP for ARM Fixed Virtual Platform with a Cortex-R52
<a href="#">4204</a>	closed	Make Termination Handler which Prints Exit Information Less Scary
<a href="#">4206</a>	closed	aarch64/xilinx_zynqmp_lp64 does not run with RTEMS_DEBUG enabled
<a href="#">4207</a>	closed	PZERO define in RTEMS is wrong
<a href="#">4209</a>	closed	STM32H743ZI Nucleo Console support not working without workaround
<a href="#">4212</a>	closed	libio leaks location clones
<a href="#">4214</a>	closed	nios2: Add thread-local storage support
<a href="#">4215</a>	closed	nios2: Add multilib with all custom floating-point instructions supported by GCC
<a href="#">4217</a>	closed	Change status code for nested obtain of MrsP semaphores
<a href="#">4218</a>	closed	aarch64 as internal error with spconfig01
<a href="#">4219</a>	closed	gdb master does not compile on CentOS 7
<a href="#">4221</a>	closed	dtc recipe issue -- dependency on yaml.h
<a href="#">4222</a>	closed	Add a per mount flag to not create a node on O_CREAT in open
<a href="#">4223</a>	closed	Missing "extern" in RTEMS_LINKER_ROSET_ITEM_ORDERED_DECLARE()
<a href="#">4225</a>	closed	Cobham Gaisler NOEL-V RISC-V 32- and 64-bit processor BSP
<a href="#">4226</a>	closed	Buildbot needs a tool chain update
<a href="#">4228</a>	closed	rtems_build_name() depends on the signedness of char type
<a href="#">4229</a>	closed	conf.py files need updated for sphinxcontrib-bibtex ver. 2.0.0 and greater
<a href="#">4230</a>	closed	Timeout for automatic barriers is broken
<a href="#">4231</a>	closed	MVME 2600/2700 has no console output
<a href="#">4237</a>	closed	consolesimpletask.c: Two Unchecked Return Values Spotted by Coverity
<a href="#">4238</a>	closed	Change motorola_powerpc bsp to support irq-generic
<a href="#">4239</a>	closed	PowerPC shared ISA IRQ support is broken
<a href="#">4240</a>	closed	rtems-debugger-target.c: Dereference before null check spotted by Coverity
<a href="#">4241</a>	closed	rtems-debugger-threads.c: Three Dereference before null check errors spotted by Coverity
<a href="#">4242</a>	closed	rtems-debugger-threads.c: Three Dereference before null check errors spotted by Coverity
<a href="#">4244</a>	closed	Possible infinite recursion in Classic API Signal handling
<a href="#">4245</a>	closed	Add PCI regions support to RTEMS nexus bus support
<a href="#">4246</a>	closed	Add libbsd DC NIC support to mvme2700 board
<a href="#">4250</a>	closed	b1553brm.c: Dereference before null check error spotted by Coverity
<a href="#">4251</a>	closed	b1553rt.c: Dereference before null check error spotted by Coverity
<a href="#">4252</a>	closed	grtc.c: Dereference before null check error spotted by Coverity
<a href="#">4253</a>	closed	grspw_pkt.c: Dereference before null check error spotted by Coverity
<a href="#">4254</a>	closed	shell.c: Dereference before null check error spotted by Coverity
<a href="#">4258</a>	closed	printertask.c: Unchecked return value errors spotted by Coverity
<a href="#">4259</a>	closed	grspw.c: Unchecked return value error spotted by Coverity
<a href="#">4260</a>	closed	record-client.c: Unchecked return value error spotted by Coverity
<a href="#">4261</a>	closed	getgrent.c: Unchecked return value error spotted by Coverity
<a href="#">4262</a>	closed	rtems-debugger-threads.c: Unchecked return value error spotted by Coverity
<a href="#">4264</a>	closed	Activate ehci_pci in rtems-libbsd (cloned)
<a href="#">4265</a>	closed	Add rtems_get_build_hash()
<a href="#">4267</a>	closed	Add rtems_get_target_hash()
<a href="#">4269</a>	closed	Add rtems_get_build_label()
<a href="#">4270</a>	closed	A failing task extension produces zombi objects and resource leaks
<a href="#">4277</a>	closed	grtc.c: Missing break in switch errors spotted by Coverity
<a href="#">4278</a>	closed	cpuusagetop.c: Missing break in switch errors spotted by Coverity
<a href="#">4279</a>	closed	pci_cfg_read.c: Missing break in switch error spotted by Coverity
<a href="#">4280</a>	closed	gen_uuid.c: Unchecked return value from library errors spotted by Coverity
<a href="#">4281</a>	closed	main_chmod.c: Unchecked return value from library error spotted by Coverity

<u>ID#</u>	<u>Status</u>	<u>Summary</u>
		Unchecked return value from library error spotted by Coverity
<a href="#">4283</a>	closed	gr_rasta_spw_router.c: Unchecked return value from library error spotted by Coverity
<a href="#">4284</a>	closed	gr_rasta_io.c: Unchecked return value from library error spotted by Coverity
<a href="#">4285</a>	closed	gr_leon4_n2x.c: Unchecked return value error from library error spotted by Coverity
<a href="#">4286</a>	closed	gr_rasta_tmtc.c: Unchecked return value from library error spotted by Coverity
<a href="#">4287</a>	closed	gr_rasta_adcdac.c: Unchecked return value from library error spotted by Coverity
<a href="#">4288</a>	closed	gr_701.c: Unchecked return value from library error spotted by Coverity
<a href="#">4289</a>	closed	gr_tmtc_1553.c: Unchecked return value from library error spotted by Coverity
<a href="#">4290</a>	closed	gr_cpci_gr740.c: Unchecked return value from library error spotted by Coverity
<a href="#">4291</a>	closed	main_help.c: Unchecked return value from library error spotted by Coverity
<a href="#">4292</a>	assigned	rtems-rfs-bitmaps.c: Useless call (CID 1399749)
<a href="#">4294</a>	closed	satcan.c: Unsigned compared against 0 error spotted by Coverity
<a href="#">4295</a>	closed	b1553brm.c: Unsigned compared against 0 error spotted by Coverity
<a href="#">4301</a>	closed	grcan.c: Unused value error spotted by Coverity
<a href="#">4302</a>	closed	Obsolete powerpc/haleakala board
<a href="#">4320</a>	closed	Add driver for cadence-spi device for xilinx based BSPs
<a href="#">4321</a>	closed	Add spi driver for AXI SPI ip core from Xilinx
<a href="#">4323</a>	closed	grrlib.can: introduce a new common CAN baud-rate timing calculating functions
<a href="#">4324</a>	closed	grrlib.grcanfd: extend the GRCAN driver with GRCANFD support
<a href="#">4326</a>	closed	objectextendinformation.c: Dereference after null check error spotted by Coverity
<a href="#">4329</a>	closed	main_rtrace.c: Dereference after null check error spotted by Coverity
<a href="#">4331</a>	closed	main_pci.c: Dereference after null check error spotted by Coverity
<a href="#">4336</a>	closed	Improve the workaround for the LEON3FT store-store errata: TN-0009 on master
<a href="#">4338</a>	closed	rtems_clock_set(): Cannot set future dates later than approximately 2105
<a href="#">4339</a>	closed	main_cp.c: Unused value error spotted by Coverity
<a href="#">4340</a>	closed	print-ls.c: Unused value error spotted by Coverity
<a href="#">4341</a>	closed	fastlz.c: Unused value error spotted by Coverity
<a href="#">4342</a>	closed	disp_hcms29xx.c: Unused value error spotted by Coverity
<a href="#">4345</a>	closed	Nexus Driver for Marvell mv643xx Ethernet Adapter (powerpc/beatnik BSP, MVME6100 board)
<a href="#">4346</a>	closed	Require RTEMS_PRIORITY for MrsP semaphores
<a href="#">4355</a>	closed	Remove leon3 test configurations which assume sis is built into gdb from rtems-test
<a href="#">4356</a>	closed	rtems_semaphore_set_priority() uses an invalid SMP lock
<a href="#">4358</a>	closed	Priority discipline is broken for semaphores and message queues in SMP configurations
<a href="#">4363</a>	closed	GDB does not build on Windows for MSYS2
<a href="#">4364</a>	assigned	rtems-test Fails to list failed tests to user
<a href="#">4365</a>	closed	main_cp.c: Ignore return value from stat()
<a href="#">4368</a>	closed	rtems--tools tool kit temp file constructor does nothing
<a href="#">4374</a>	closed	Handle symbol sets in covoar
<a href="#">4375</a>	closed	Add futimens() and utimensat()
<a href="#">4376</a>	closed	covoar/ReportsBase Coverage::GenerateReports() uses raw pointer to std::list
<a href="#">4377</a>	closed	covoar/Explanations Explanations::writeNotFound() NULL check of wrong variable
<a href="#">4378</a>	closed	covoar/symbol-sets add libuuid to symbol-sets.ini
<a href="#">4380</a>	closed	Update RTEMS POSIX Compliance Spreadsheet
<a href="#">4382</a>	closed	mingw - add flex to packages needed
<a href="#">4383</a>	closed	covoar keeps DWARF info in memory too long
<a href="#">4384</a>	closed	Add SMTP login to rtems-tools mailer
<a href="#">4386</a>	closed	covoar missing conditional branch instructions on ARM
<a href="#">4387</a>	closed	covoar marks taken/not taken incorrectly for AArch64
<a href="#">4388</a>	closed	Copy improved mailer.py from rtems-tools
<a href="#">4389</a>	closed	Undefined behaviour if the area size calculation in calloc() and rtems_calloc() overflows
<a href="#">4390</a>	closed	Make zero size allocation result consistent across directives
<a href="#">4391</a>	closed	SPARC GCC no longer needs sysconf(515) (_SC_STACK_PROT)
<a href="#">4392</a>	closed	rtems: Constify timer fire when directives
<a href="#">4393</a>	closed	rtems: Change rtems_task_get_affinity() status
<a href="#">4395</a>	closed	Workspace initialization is broken for arm/imx7 and arm/raspberrypi
<a href="#">4396</a>	closed	Add futimens() and utimensat()
<a href="#">4397</a>	closed	Make utime() use utimensat()
<a href="#">4398</a>	closed	Make utimes() use utimensat()
<a href="#">4399</a>	closed	Add tests for futimens() and utimensat()
<a href="#">4400</a>	closed	Change filesystem utime_h to utimens_h to support nanosecond granularity
<a href="#">4401</a>	closed	rtems: Change rtems_scheduler_get_processor_set() status
<a href="#">4402</a>	closed	rtemstoolkit/mailer.py option added twice
<a href="#">4403</a>	closed	rtems_timer_fire_when() returns wrong status code when wall_time argument is NULL
<a href="#">4406</a>	closed	rtems: Constify rtems_task_wake_when()
<a href="#">4410</a>	closed	rtems_task_start() does not check that the entry point is not equal to NULL (cloned)
<a href="#">4411</a>	closed	rtems_task_restart() should set the real priority to the initial priority
<a href="#">4412</a>	closed	Unexpected rtems_task_restart() behaviour if called from within interrupt context
<a href="#">4413</a>	closed	Allow pthread_cancel() from within interrupt context
<a href="#">4414</a>	closed	Return RTEMS_CALLED_FROM_ISR in rtems_task_delete()
<a href="#">4415</a>	closed	ReportsBase.cc: Division or modulo by float zero error spotted by Coverity
<a href="#">4416</a>	closed	rtems-exeinfo.cpp: Division or modulo by zero errors spotted by Coverity
<a href="#">4417</a>	closed	Explanations.cc: Resource leak error spotted by Coverity
<a href="#">4418</a>	closed	GcovData.cc: Resource leak error spotted by Coverity
<a href="#">4419</a>	closed	TraceReaderLogQEMU.cc: Resource leak error spotted by Coverity
<a href="#">4420</a>	closed	TraceWriterQEMU.cc: Resource leak error spotted by Coverity
<a href="#">4421</a>	closed	DesiredSymbols.cc: Resource leak error spotted by Coverity
<a href="#">4422</a>	closed	ReportsBase.cc: Resource leak error spotted by Coverity
<a href="#">4423</a>	closed	record-client.c: Unchecked return value error spotted by Coverity
<a href="#">4424</a>	closed	rtems-bin2c.c: Copy into fixed size buffer spotted by Coverity
<a href="#">4425</a>	closed	GcovFunctionData.cc: Copy into fixed size buffer errors spotted by Coverity
<a href="#">4426</a>	closed	clock_nanosleep() may use wrong clock for relative times
<a href="#">4427</a>	closed	GcovData.cc: Dereference after null check error spotted by Coverity

<u>id</u>	<u>status</u>	<u>summary</u>
<a href="#">4428</a>	closed	base.cc: Dereference after null check error spotted by Coverity
<a href="#">4430</a>	closed	DesiredSymbols.cc: Uninitialized pointer read error spotted by Coverity
<a href="#">4432</a>	closed	GcovFunctionData.cc: Uninitialized pointer field error spotted by coverity
<a href="#">4433</a>	closed	DesiredSymbols.h: Uninitialized pointer field error spotted by coverity
<a href="#">4434</a>	closed	record-filter-zlib.cc: Uninitialized pointer field error spotted by Coverity
<a href="#">4435</a>	closed	Thread cancellation may produce ready threads with an active thread timer
<a href="#">4437</a>	closed	powerpc/shared/sbrk.c: Do not reference errno
<a href="#">4438</a>	closed	powerpc/shared/irq/ppc-irq-legacy.c: Use rtems_malloc() not malloc()
<a href="#">4439</a>	closed	Open of /dev/console should only be in SysInit List if Console Enabled
<a href="#">4442</a>	closed	CID 1399721: Copy into fixed size buffer
<a href="#">4444</a>	closed	CID 1399727: Copy into fixed size buffer
<a href="#">4445</a>	closed	CID 1468684: Uninitialized scalar variable
<a href="#">4448</a>	closed	covoar reports uncovered ranges of size 1
<a href="#">4451</a>	closed	DesiredSymbols: Implement move assignment operator
<a href="#">4453</a>	closed	Global vs Local Attribute Unclear for SMP/Distributed MP
<a href="#">4454</a>	closed	bsps/i386: TSC calibration inaccurate
<a href="#">4455</a>	closed	bsps/i386: TSC calibration inaccurate
<a href="#">4458</a>	closed	Simplify trap table initialization
<a href="#">4460</a>	closed	CID 1437647: Explicit null dereferenced
<a href="#">4461</a>	closed	glibc: Register system console as "/dev/console"
<a href="#">4462</a>	closed	CID 1437638: Logically dead code
<a href="#">4463</a>	closed	rtems_condition_variable_signal() is implemented as a broadcast
<a href="#">4468</a>	closed	waf build system does not generate the same bspopts.h
<a href="#">4469</a>	closed	rtems-exeinfo.cpp: Not restoring ostream format errors spotted by Coverity
<a href="#">4470</a>	closed	CoverageMapBase.cc: Not restoring ostream format error spotted by Coverity
<a href="#">4471</a>	closed	ReportsHtml.cc: Not restoring ostream format error spotted by Coverity
<a href="#">4472</a>	closed	ReportsText.cc: Not restoring ostream format error spotted by Coverity
<a href="#">4473</a>	closed	AddressToLineMapper.h: Pointer to local outside scope error spotted by Coverity
<a href="#">4475</a>	closed	Add NFSv4 client support to libbsd
<a href="#">4482</a>	closed	Document kernel character I/O support in Classic API Guide
<a href="#">4483</a>	closed	GcovData.cc: Not restoring ostream format error spotted by Coverity
<a href="#">4484</a>	closed	GcovFunctionData.cc: Not restoring ostream format error spotted by Coverity
<a href="#">4485</a>	closed	GcovData.cc: Out-of-bounds acces errors spotted by Coverity
<a href="#">4486</a>	closed	TraceWriterQEMU.cc: String not null terminated issue spotted by Coverity
<a href="#">4487</a>	closed	GcovData.cc: Uninitialized scalar field error spotted by Coverity
<a href="#">4488</a>	closed	TraceWriterQEMU.cc: Uninitialized scalar variable issue spotted by Coverity
<a href="#">4489</a>	closed	waf configure's --rtems-config and build create an error
<a href="#">4490</a>	closed	rtems_partition_return_buffer() wrongly accepts buffers which are exactly at the buffer area end
<a href="#">4491</a>	closed	TraceWriterQEMU.cc: Buffer not null terminated issue spotted by Coverity
<a href="#">4492</a>	closed	ObjdumpProcessor.cc: Uninitialized pointer field
<a href="#">4499</a>	closed	rtems-exeinfo.cpp: Uninitialized scalar field error spotted by Coverity
<a href="#">4500</a>	closed	rld-dwarf.cpp: Uninitialized scalar field
<a href="#">4501</a>	closed	TraceConverter.cc: Uncaught exception issue spotted by Coverity
<a href="#">4502</a>	closed	rld-rap.cpp: Uncaught exception issue spotted by Coverity
<a href="#">4506</a>	closed	posix_devctl() should return the errno directly not -1 and set errno
<a href="#">4507</a>	closed	mount call retruns error number and it should return -1
<a href="#">4508</a>	closed	rtems_message_queue_receive(): flush() does not release waiting tasks
<a href="#">4509</a>	closed	Message queue priority dicipline is broken in SMP configurations
<a href="#">4510</a>	assigned	Fix ILP32 multilib variant in newlib for AArch64
<a href="#">4511</a>	closed	Count of postponed jobs is not set to zero for a newly created rate-monotonic period object
<a href="#">4513</a>	closed	Document parts of the Cache Manager in the Classic API Guide
<a href="#">4517</a>	closed	Build failures for MacOS
<a href="#">4518</a>	closed	RTEMS and LibBSD both provide competing pipe() interfaces
<a href="#">4519</a>	closed	record-main-ltng.cc: Out-of-bounds access
<a href="#">4522</a>	closed	Optimize red-black tree insert/extract
<a href="#">4524</a>	closed	Re-add lost capability for custom stack allocator to allocate IDLE thread stacks
<a href="#">4525</a>	closed	rtems-tld.cpp: Logically dead code error spotted by Coverity
<a href="#">4527</a>	closed	Add new directives to get all time values provided by the timehands
<a href="#">4528</a>	closed	rate monotonic: reset of CPU usage time not always detected
<a href="#">4531</a>	closed	Data corruption in SMP schedulers
<a href="#">4532</a>	closed	Priority inversion issues with MrsP locking protocol implementation
<a href="#">4533</a>	closed	libdebugger should only build for archs with a backend
<a href="#">4534</a>	closed	SMP EDF scheduler violates priority group ordering
<a href="#">4543</a>	closed	cannot build multiprocessor application on eclipse
<a href="#">4544</a>	closed	The last processor must not be removed if it is owned by a helping scheduler
<a href="#">4545</a>	closed	The SMP EDF scheduler can only support more restricted affinity sets of a thread
<a href="#">4546</a>	closed	A thread restart does not update the priority of related threads
<a href="#">4547</a>	assigned	dtc build failure on msys2 - all rtems6 target tools fail to build on Windows 10
<a href="#">4548</a>	closed	Add RTEMS version option to waf configure
<a href="#">4550</a>	closed	Add --rtems-version to rtems-test
<a href="#">4551</a>	closed	Workaround for GRLIB-TN-0011 required for sparc/leon3 BSPs in SMP configuration
<a href="#">4556</a>	closed	rtems_shell_main_mmove problem
<a href="#">4557</a>	closed	medit problem in RTEMS6 (was 4.11/5.1)
<a href="#">4560</a>	closed	Use thread-local storage for Newlib reentrancy objects
<a href="#">4566</a>	closed	Atomic store does not use the order parameter for C++
<a href="#">4569</a>	closed	aarch64 cache support does not provide rtems_cache_disable_data()
<a href="#">4572</a>	closed	Improve Clarity for New Clock Manager Directives
<a href="#">4581</a>	closed	Add AArch64 to Tier 1 BSPs
<a href="#">4583</a>	closed	rtems-bsp-builder: Do not vary on network
<a href="#">4585</a>	closed	Multiple Prototype Issues/Mismatches in rtems-examples from trace linker
<a href="#">4588</a>	closed	RTEMS Stack Checker Report Bad Access When Not Enabled
<a href="#">4607</a>	closed	support for SATA/AHCI drives
<a href="#">4612</a>	closed	Reverts aarch64 port in rtems6 and removes it from rtems7

ID	Status	Summary
<del>4614</del>	<del>closed</del>	<del>Deprecate sparcc4 port in rtems6 and remove in rtems7</del>
<del>4614</del>	<del>closed</del>	<del>Deprecate sh port in rtems6 and remove in rtems7</del>
4615	closed	Deprecate v850 port in rtems6 and remove in rtems7
4617	closed	Potential non-monotonic CLOCK_MONOTONIC
4619	closed	riscv/rv32iac: minimum sample test fails to build
4627	closed	Multitasking start is broken on SMP targets which do not restore the interrupt state during context switching
4629	closed	shell: Potential stack corruption in rtems_shell_init()
4631	closed	RSB fails to build gdb with Python 3.10 (and newer)
4632	closed	Error in rtems/thread.hpp with GCC 12
4634	closed	Fix hash for glib-2.48
4635	closed	untar on JFFS slow down
4639	closed	Error in imfs memfile when device is full
4641	closed	x86_64 elf_machdep header file missing body
4644	closed	wkspcace "failed allocations" increase with heap protection enabled (cloned)
4646	closed	Control buildsets using the --with-* command line option
4648	new	Documentation Needs to Use Version Variables not Hard-Coded Numbers
4650	closed	tcpdump: Fix dumping to file and reading from file (cloned)
4652	closed	if_atsam: Fix checksum offload, add multicast and VLAN support (cloned)
4654	closed	pfctl: Fix global state initialization (cloned)
4656	closed	sync() whould synchronize all file descriptors (cloned)
4658	closed	Fix build issue with riscv sample test
4661	closed	GCC 12 generates wrong code
4662	closed	Fix GCC 12 warnings
4666	closed	TFTP: Implement block and window size options
4667	closed	include/sys/_bitset.h defines struct bitset, pollutes namespace
4668	closed	Use thread-local storage in libstdc++
4669	closed	clock_nanosleep() uses the wrong clock to determine the start time point
4670	closed	Add option to build RTEMS with coverage instrumentation
4672	closed	Thread-local storage should be usable once an idle thread exists
4673	closed	Runtime loader exported symbols address size not consistent
4675	assigned	sleep should be a thread cancellation point
4677	closed	incorrect handling of "inactive_per_block" from "Objects_Information" structure (cloned)
4678	closed	System initialization time increased compared to RTEMS 4.11
4679	closed	Use priority inheritance for thread join
4680	closed	POSIX tasks cancelled through rtems_task_delete() should have an exit value of PTHREAD_CANCELED
4682	closed	Add AArch64 support to libdl
4684	closed	Support Versal DDRMC0 regions 0 and 1
4686	closed	Refactor shared code in Arm and AArch64
4689	closed	mips/jmr3904 Massive Number of Test Failures
4690	closed	CLOCK_REALTIME thread queue not updated as part of clock_settime call
4691	closed	Add support for FACE Technical Standard Restriction on POSIX Absolute Timers
4693	closed	Remove ILP32 aarch64/xilinx_versal_* BSPs
4694	closed	sptestests/sp37 fails to compile if RTEMS_SMP is not defined
4695	assigned	Automatic version numbers in the documentation
4697	closed	Documentation for libbsd Configure options
4700	closed	Fix instances of "is" operator used with literals
4701	closed	Relocatable write data is placed in read-only region on some BSPs
4702	assigned	Fix warnings for indexing past array bounds (primarily validation tests)
4703	closed	NetSNMP 5.7.2.1 Patch
4705	closed	Installed header clean up
4706	closed	Installed header break C++
4710	closed	RSB does not expand dir type macros correctly
4712	closed	powerpc: Add Altivec VRSERVE support
4713	closed	Make pthread_atfork follow FACE Technical Standard Behavior for Single Process Environments
4714	closed	Use waf for LwIP walk sources
4718	closed	Coverity issues in cpukit/libfs/src/ftps/ftpDriver.c
4724	closed	Git commit message format instructions
4726	closed	RSB decode exception stops build
4729	closed	Add 64bit address support to RTEMS FDT
4730	closed	rtems-source-builder doesn't generate tar archives for all packages any more
4732	closed	Set top in RSB version.py
4736	assigned	RISC-V - ISR_stack allocation and usage by harts > CONFIGURE_MAXIMUM_PROCESSORS
4741	closed	Fix GCC PR 107248
4744	closed	libdebugger arm backend does not single step
4746	closed	ArmV7-M SysTick clock driver uses off by one reload value
4750	closed	Linker discards RTEMS_SYSINIT_ITEM object
4751	closed	chmod problem in shell of RTEMS 6
4756	closed	Docs build system does not build singlehtml (cloned)
4759	closed	TLS support is broken for ARMv6
4760	reopened	RSB fatal error on missing hash checksums
4762	closed	Add Versal SDHCI Arasan driver to libbsd
4763	closed	Detect terminal size
4766	closed	Classic API User Guide Index has Functions without Parentheses
4767	assigned	Add rtems-lwip to release packages
4768	reopened	Use tarballs for stable versions development tools
4769	closed	config: Add CONFIGURE_RECORD_INTERRUPTS_ENABLED
4771	closed	Versal UART issues
4772	closed	Remove use of interval from rtems_task_wake_after() documentation
4775	closed	RISC-V: Default RV64 BSPs to medany
4778	closed	Deployed RSB does not find release version config
4782	closed	Correct Issues in Rate Monotonic Manager Background Section
4783	new	Fix issues when compiling dtc with Cygwin
4803	closed	Revert or Mark CAN API as experimental

ID	Status	Summary Statement in "cpu->heir"
<a href="#">4818</a>	closed	Hazardous cast
<a href="#">4821</a>	closed	Ubuntu Host Instructions Wrong
<a href="#">4822</a>	closed	Function returning unchanged function input
<a href="#">4826</a>	assigned	Software Engineering Guide has broken Reference
<a href="#">4828</a>	closed	Macro defined but magic number used instead
<a href="#">4832</a>	closed	CLANG flagged error
<a href="#">4833</a>	assigned	griib/pci/grpci2dma.c Warnings Require Insight to Resolve Properly
<a href="#">4834</a>	closed	close_editor problem of RTEMS4.13/5.1 (cloned)
<a href="#">4835</a>	closed	medit malloc problem of RTEMS (cloned)
<a href="#">4838</a>	closed	Fix for UART interrupt on aarch64 Versal
<a href="#">4842</a>	closed	SPARC/griib - Registers definitions wrongly defined when there are reserved bits
<a href="#">4843</a>	closed	Output value not assigned
<a href="#">4844</a>	assigned	Unchecked boundaries
<a href="#">4845</a>	closed	Global variable declared/defined in the wrong file
<a href="#">4847</a>	closed	Goto statements
<a href="#">4850</a>	closed	LEON3 - Variable not initialized in any file / missing #ifdefs
<a href="#">4855</a>	closed	Input validity unchecked
<a href="#">4857</a>	closed	RSB Recipe Missing %hash Does Not Fail
<a href="#">4858</a>	closed	GDB fails to build on any host with readline 8.2 or newer
<a href="#">4859</a>	closed	Update gdb to 12.1
<a href="#">4860</a>	closed	Waf Failure on CentOS 8 Stream
<a href="#">4861</a>	assigned	"Single HTML" links on docs.rtems.org lead to empty pages
<a href="#">4862</a>	assigned	score/ & bsp/: Unused input parameters
<a href="#">4863</a>	closed	Operations evaluation order.
<a href="#">4867</a>	closed	Clean up rtems-lwip uLan directory
<a href="#">4869</a>	closed	Add QSPI Flash Device API
<a href="#">4870</a>	assigned	Add features for QSPI Flash on Xilinx Versal
<a href="#">4872</a>	closed	GDB 13.1 does not build on FreeBSD 13.1
<a href="#">4874</a>	closed	Undefined behaviour
<a href="#">4875</a>	assigned	LEON3FT - Power-down workaround
<a href="#">4878</a>	closed	sptest/spsysinit01 sem_open call only has 3 parameters with O_CREAT flag (cloned)
<a href="#">4881</a>	closed	powerpc gas and ld warnings
<a href="#">4882</a>	closed	mvme2703 legacy network build failure
<a href="#">4884</a>	closed	I2C default ioctl handler does not handle set clock
<a href="#">4887</a>	closed	RTEMS Net Legacy does not build as a package in the RSB
<a href="#">4889</a>	closed	Remove file scanning from rtems-lwip
<a href="#">4892</a>	closed	MacOS tools build failures on Ventura and M series processors
<a href="#">4896</a>	closed	Makefile.inc exported BSP include path not a system include path
<a href="#">4899</a>	closed	BSP powerpc/qoriq_e6500_64 and powerpc/qoriq_e6500_32 fail to build
<a href="#">4900</a>	closed	PowerPC score warnings in score headers
<a href="#">4901</a>	closed	rtems_task_construct Documentation Missing Some Details
<a href="#">4902</a>	closed	Update zlib to version 1.2.13
<a href="#">4905</a>	closed	SuperCore _TOD_Adjust No Longer Referenced and Should be Removed
<a href="#">4906</a>	closed	libbsd not working on nucleo-h743ZI
<a href="#">4909</a>	closed	Multiple Protected Heap Functions are Ununused
<a href="#">4910</a>	assigned	RSB options for python selection
<a href="#">4912</a>	closed	Collect Compression Library Source in Single Place
<a href="#">4913</a>	closed	libbsd/ipsec-tools: Problems with more than 64 open files
<a href="#">4915</a>	closed	Building sphinx 7.0.1 fails
<a href="#">4920</a>	new	libdl does not support TLS
<a href="#">4921</a>	assigned	Tool versions for RTEMS 6.1 release
<a href="#">4923</a>	accepted	FPU context init/switch not working well on more than 2 tasks on Cortex-Mx/ARMv7-M platform
<a href="#">4924</a>	closed	Add Regulator Helper to RTEMS
<a href="#">4925</a>	assigned	Deal with GR740 errata: Level-2 Cache Issues H1 2023 (GRLIB-TN-0021)
<a href="#">4929</a>	new	RTEMS tools installs into \$PREFIX/share/rtems and not \$PREFIX/share/rtems6
<a href="#">4931</a>	new	User manual RSB BSP build examples need updating
<a href="#">4934</a>	closed	Update STM32 H7 HAL/LL drivers code
<a href="#">4935</a>	closed	7/rtems-mips get source fails
<a href="#">4940</a>	closed	Fix cache support for ARM926EJ-S processor
<a href="#">4942</a>	closed	Regulator warnings
<a href="#">4943</a>	closed	ARM unwind register is not being hooked
<a href="#">4944</a>	closed	libdl test dl09 fails on arm and aarch64
<a href="#">4945</a>	closed	rtems-test SIS support is broken
<a href="#">4947</a>	closed	Testsuite libtest tests not built with optimise or debug flags
<a href="#">4950</a>	closed	libdl test dl07 fails on PowerPC
<a href="#">4951</a>	closed	rtems-tools fail on FreeBSD to get number of cores
<a href="#">4953</a>	closed	Use of symbol addresses for arbitrary values may not work for some code models
<a href="#">4954</a>	closed	sparc: Simplify the clock driver and CPU counter support
<a href="#">4955</a>	closed	sparc: Potential stack corruption in uniprocessor configurations during start multitasking
<a href="#">4956</a>	assigned	Deadlock caused by locking inversion in JFFS2
<a href="#">4957</a>	assigned	spstdc17 warnings building i386/pc686
<a href="#">4959</a>	closed	rtems-test tftp does not a session timeout
<a href="#">4960</a>	new	User manual test documentation update
<a href="#">4961</a>	assigned	Document and test CONFIGURE_JFFS2_DELAYED_WRITE_TASK_PRIORITY
<a href="#">4962</a>	assigned	MicroBlaze BSPs modify carry flag before MSR is saved
<a href="#">4967</a>	closed	strtof leaks memory
<a href="#">4968</a>	assigned	Python 3.12 fix escape sequences and remove SafeConfigParser
<a href="#">4969</a>	closed	Update libibery sources in rtems-tools
<a href="#">4970</a>	closed	Fix C++ 17 deprecated functionality in rtems-tools
<a href="#">4971</a>	closed	Report that nested validation test cases did run
<a href="#">4973</a>	closed	Add RSB options to control a specific python

ID	Status	Summary
4974	closed	binutils build failed with '--host=x86_64-w64-mingw32'
4975	closed	Terminal row/col probe timeout too fast
4977	closed	tmux bug swaps lines and columns
4980	closed	Build documentation using sphinx 7.2
4982	assigned	Add support for TMS570LC4357 for the arm/tms570 BSP
4986	assigned	Improve CONFIGURE_TICKS_PER_TIMESLICE configuration and documentation
4991	assigned	RSB source and patch checksum updates
4993	assigned	Increase FD_SIZE to 256
550	closed	fcntl() fails to put a non-blocking socket into blocking mode

## RTEMS 6.1 Tickets By Category

### Owner

Owner	Closed	Total	Progress
Chris Johns <chrisj@...>	8	8	8/8
Ralf Corsepius	2	2	2/2
Sebastian Huber <sebastian.huber@...>	17	17	17/17
Chris Johns	87	73	73/73
joel	2	2	2/2
Joel Sherrill	32	33	32/32
Needs Funding	6	6	6/6
Gedare Bloom	11	11	11/11
	61	70	61/61
Sebastian Huber	174	182	174/174
chrisj@...	2	3	2/2
Hesham Almatary	1	2	1/1
joel@...	5	5	5/5
Kinsey Moore <kinsey.moore@...>	4	4	4/4
Jan Sommer <jan.sommer@...>	5	5	5/5
Joel Sherrill <joel@...>	9	9	9/9
Hesham Almatary <Hesham.Almatory@...>	1	1	1/1
Kinsey Moore	6	2	2/2
Ryan Long <ryan.long@...>	82	82	82/82
Jiri Gaisler	1	1	1/1
Frank Kuehndel <frank.kuehndel@...>	1	1	1/1
Daniel Hellstrom	6	7	6/6
Christian Mauderer	3	3	3/3
kgardas	2	3	2/2
Amar Takhar	1	1	1/1
Gedare Bloom <gedare@...>	1	1	1/1
Ryan Long <thisisryanlong@...>	1	1	1/1
Jan Sommer	4	4	4/4
Heinz Junkes <junkes@...>	1	1	1/1
Alex White	10	11	10/10
Hesham Almatary <hesham.almatory@...>	1	1	1/1
Utkarsh Verma <utkarsh@...>	1	1	1/1
Cedric Berger	0	0	0/0

### Type

Type	Closed	Total	Progress
defect	372	403	372/372
enhancement	115	124	115/115
task	38	40	38/38
project	5	5	5/5

### Priority

Priority	Closed	Total	Progress
high	5	8	5/5
normal	512	550	512/512
highest	4	5	4/4
low	7	7	7/7
lowest	2	2	2/2

### Component

Component	Closed	Total	Progress
build	23	23	23/23
score	42	43	42/42
doc	42	36	36/36
tool/rsb	19	27	19/19
admin	14	15	14/14
tool/newlib	6	5	5/5
network/legacy	5	5	5/5
bsps	51	52	51/51
test	19	17	17/17
tool/gcc	6	6	6/6
arch/aarch64	8	10	8/8
shell	10	10	10/10
config	4	5	4/4
fs	10	10	10/10
lib	38	38	38/38
unspecified	8	9	8/8
rtems	52	53	52/52
arch/m32c	1	1	1/1
posix	8	9	8/8
arch/sparc	14	17	14/14
lib/dl	8	9	8/8
lib/block	2	2	2/2
tool	69	75	69/69
network/libbsd	19	19	19/19
arch/mips	2	2	2/2
arch/epiphany	1	1	1/1
arch/powerpc	5	5	5/5
arch/arm	17	19	17/17
arch/i386	3	3	3/3
arch/riscv	3	4	3/3
tool/website	1	2	1/1
fs/rfs	1	2	1/1
arch/nios2	2	2	2/2
tool/binutils	2	2	2/2
tool/gdb	6	6	6/6
lib/debugger	7	7	7/7
arch/sh	1	1	1/1
arch/v850	1	1	1/1
arch/sparc64	1	1	1/1
fs/jffs2	1	2	1/1
arch/x86_64	1	1	1/1
network/lwip	3	3	3/3
dev	1	1	1/1
dev/spi	1	1	1/1
dev/i2c	1	1	1/1

## Severity

Severity	Closed	Total	Progress
normal	506	540	506/506
major	4	5	4/4
blocker	13	6	6/6
critical	5	5	5/5
minor	5	5	5/5
trivial	4	4	4/4

## Reporter

Reporter	Closed	Total	Progress
Chris Johns	83	98	83/83
cynt6007	2	2	2/2
shashvat jain	1	1	1/1
Helder Silva	1	1	1/1
Thomas Rauscher	1	1	1/1
zhangwenjie	1	1	1/1
Sebastian Huber	167	172	167/167
Joel Sherrill	77	84	77/77
Ralf Corsepius	3	3	3/3
mohamedosama94	1	1	1/1
Jeffrey Hill	1	1	1/1
Tanu Hari Dixit	1	1	1/1
Sambeet Panigrahi	1	1	1/1
Marçal Comajoan Cara	1	1	1/1
Martin Aberg	1	1	1/1
Ionut Vilsan	1	1	1/1
Gedare Bloom	6	6	6/6
Kinsey Moore	7	8	7/7
Jan Sommer	10	10	10/10
Heinz Junkes	1	1	1/1
Frank Kuehndel	9	9	9/9
Christian Mauderer	3	3	3/3
rmueller	1	1	1/1
Daniel Hellstrom	4	4	4/4
Ryan Long	91	94	91/91
GabrielMoyano	1	1	1/1
Till Straumann	1	1	1/1
Alex White	12	13	12/12
Harrison Gerber	5	5	5/5
kgardas	3	1	1/1
chenjin_zhong	5	5	5/5
ostyche	1	1	1/1
Alexandre Oliva	1	2	1/1
Adrian Varlan	1	1	1/1
Lucian-Raul Silistru	2	3	2/2
dsa93	1	1	1/1
Aaron N	3	4	3/3
jkillelea	1	1	1/1
Hesham Almatary	1	1	1/1
Daniel Páscoa	13	16	13/13
Jens Schweikhardt	0	0	0/0
Andrew Butterfield	1	1	1/1
Ning Yang	1	1	1/1
zhengxiaojun	0	0	0/0
Marcello Presulli	1	1	1/1
Marta Rybczynska	1	1	1/1
Matthew J Fletcher	1	1	1/1
Andrey Mozzhuhin	1	1	1/1

## Version

Version	Closed	Total	Progress
6	425	461	425/425
4.11	18	18	18/18
5	52	54	52/52
4.5	2	2	2/2
4.10	4	4	4/4
	28	32	28/28
4.9	1	1	1/1

## RTEMS 6.1 Tickets

### **1318 - libcpu/shared is not helpful**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/1318">https://devel.rtems.org/ticket/1318</a> ( <a href="https://devel.rtems.org/ticket/1318">https://devel.rtems.org/ticket/1318</a> )
<b>Id</b>	1318
<b>Reporter</b>	Ralf Corsepius
<b>Created</b>	22 September 2008 13:36:04
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	4.10
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	thomas.doerfler@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

IMO, libcpu/shared is not helpful

Either something is

- cpu-specific, then it should go into cpukit/score/cpu,
- general, then it should go into cpukit/
- bsp-dependent, then it should go into libbsp.

I would strongly suggest to reconsider libcpu/shared.

**Comment 1**

1. **Joel Sherrill**, Fri, 06 Aug 2010 21:32:22 GMT
2. **milestone**: changed from **4.10** to **4.11**

Moving to 4.11. Needs to be addressed but too much for a branch.

**Comment 2**

1. **Gedare Bloom**, Fri, 11 Apr 2014 19:29:33 GMT
2. **milestone**: changed from **4.11** to **4.12**

**Comment 3**

1. **Chris Johns**, Thu, 20 Nov 2014 03:31:07 GMT
2. **milestone**: changed from **4.12** to **4.11**

**Comment 4**

1. **Chris Johns**, Thu, 20 Nov 2014 07:22:20 GMT
2. **description**: modified (diff)
3. **milestone**: changed from **4.11** to **5.0**

This needs to be part of the source tree rearrangement.

**Comment 5**

1. **Sebastian Huber**, Tue, 05 Jan 2016 12:09:59 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**
4. **description**: modified (diff)

This directory contains only support code for the cache manager. I don't know a better place for these files. They cannot go into cpukit, since the cache manager is potentially BSP-dependent.

**Comment 6**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

---

**1459 - Add rtems\_shell\_main\_monitor to cpukit/libmisc/shell/shell.h?**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/1459">https://devel.rtems.org/ticket/1459</a> ( <a href="https://devel.rtems.org/ticket/1459">https://devel.rtems.org/ticket/1459</a> )
<b>Id</b>	1459
<b>Reporter</b>	Ralf Corsepius
<b>Created</b>	29 October 2009 06:18:16
<b>Modified</b>	29 November 2022 21:49:38
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.10
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	minor
<b>Keywords</b>	
<b>Cc</b>	chrisj@... vattam.santosh@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

rtems\_shell\_main\_monitor  
is a private function of  
cpukit/libmisc/shell/cmds.c

However, the way  
testsuites/libtests/monitor02/init.c  
uses it (as a public/exported function) to me reads as a strong indication that  
rtems\_shell\_main\_monitor()  
should be "made public" by declaring/prototyping it in  
cpukit/libmisc/shell/shell.h

**Comment 1**

1. **Santosh Vattam**, Thu, 24 Dec 2009 22:07:08 GMT
2. **cc: Santosh Vattam** added

**Comment 2**

1. **Joel Sherrill**, Fri, 25 Dec 2009 14:29:03 GMT
2. **owner:** changed from **Joel Sherrill** to **Chris Johns**

**Comment 3**

1. **Chris Johns**, Sat, 15 May 2010 06:42:03 GMT
2. **status:** changed from **new** to **assigned**
3. **milestone:** changed from **4.10** to **4.11**

Exporting this interface from the shell is a hack as well. The central issue is the purpose of the monitor now we have a shell. Should we consume the monitor into the shell and remove the duplicate code in RTEMS ? The monitor has stdin handling, terminal handling plus help formatting (which is much better than the shell's). I think these can all be merged into the shell and the monitor goes away.

I think this should be moved to the 4.11 milestone, which I have done, and we live with the current code for 4.10.

Once issue this raises is the pressure on the shell with all the files that are starting to appear in it. Maybe the monitor command remain in its directory.

**Comment 4**

1. **Joel Sherrill**, Sun, 23 Nov 2014 17:37:06 GMT
2. **summary:** changed from **Add rtems\_shell\_main\_monitor to cpukit/libmisc/shell/shell.h?** to **Make Monitor Commands first class citizens in shell**,
3. **description:** modified (diff)
4. **milestone:** changed from **4.11** to **5.0**

The monitor predates the shell. There is really no point in having two CLIs. The monitor commands are available in the shell but the integration is a hack. The monitor commands need to be made first class shell commands and the set for looking at objects enhanced to include more objects.

This may be a decent GSoC project.

**Comment 5**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

**Comment 6**

1. **Chris Johns**, Tue, 29 Nov 2022 21:49:38 GMT
2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**
4. **description:** modified (diff)

Fixed in 2011.

---

## 1593 - RTEMS Sequenced Initialization API

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/1593">https://devel.rtems.org/ticket/1593</a> ( <a href="https://devel.rtems.org/ticket/1593">https://devel.rtems.org/ticket/1593</a> )
<b>Id</b>	1593
<b>Reporter</b>	zhangwenjie
<b>Created</b>	27 June 2010 03:54:42
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	chrisj@... sebastian.huber@... 157724595@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

This is a part of GSOC2010 project RTEMS Sequenced Initialization. The attachment is the implement of RTEMS Sequenced Initialization API. More details are placed on the wiki <http://www.rtems.com/wiki/index.php/RTEMSSequencedInitialization>.

### Attachments:

- 
- 1 **zhangwenjie, Mon, 28 Jun 2010 16:19:41 GMT**  
attach: set to [sequenced\\_initialization\\_api.patch](https://devel.rtems.org/ticket/1593/sequenced_initialization_api.patch) ([https://devel.rtems.org/ticket/1593/sequenced\\_initialization\\_api.patch](https://devel.rtems.org/ticket/1593/sequenced_initialization_api.patch))
  - 2 **zhangwenjie, Sun, 04 Jul 2010 10:46:45 GMT**  
attach: set to [sequenced\\_initialization\\_api\\_and\\_test.patch](https://devel.rtems.org/ticket/1593/sequenced_initialization_api_and_test.patch) ([https://devel.rtems.org/ticket/1593/sequenced\\_initialization\\_api\\_and\\_test.patch](https://devel.rtems.org/ticket/1593/sequenced_initialization_api_and_test.patch))
  - 3 **zhangwenjie, Tue, 06 Jul 2010 13:37:23 GMT**  
attach: set to [sequence\\_api\\_test.patch](https://devel.rtems.org/ticket/1593/sequence_api_test.patch) ([https://devel.rtems.org/ticket/1593/sequence\\_api\\_test.patch](https://devel.rtems.org/ticket/1593/sequence_api_test.patch))
  - 4 **zhangwenjie, Sun, 18 Jul 2010 15:20:49 GMT**  
attach: set to [rtems\\_sysinit\\_size\\_compare.patch](https://devel.rtems.org/ticket/1593/rtems_sysinit_size_compare.patch) ([https://devel.rtems.org/ticket/1593/rtems\\_sysinit\\_size\\_compare.patch](https://devel.rtems.org/ticket/1593/rtems_sysinit_size_compare.patch))
  - 5 **zhangwenjie, Wed, 21 Jul 2010 14:49:00 GMT**  
attach: set to [rtems\\_sysinit\\_size\\_compare\\_PR2.patch](https://devel.rtems.org/ticket/1593/rtems_sysinit_size_compare_PR2.patch) ([https://devel.rtems.org/ticket/1593/rtems\\_sysinit\\_size\\_compare\\_PR2.patch](https://devel.rtems.org/ticket/1593/rtems_sysinit_size_compare_PR2.patch))
  - 6 **zhangwenjie, Wed, 21 Jul 2010 14:52:13 GMT**  
attach: set to [sis\\_bsp.patch](https://devel.rtems.org/ticket/1593/sis_bsp.patch) ([https://devel.rtems.org/ticket/1593/sis\\_bsp.patch](https://devel.rtems.org/ticket/1593/sis_bsp.patch))
  - 7 **zhangwenjie, Fri, 23 Jul 2010 14:52:26 GMT**  
attach: set to [rtems\\_sysinit\\_size\\_compare\\_new.patch](https://devel.rtems.org/ticket/1593/rtems_sysinit_size_compare_new.patch) ([https://devel.rtems.org/ticket/1593/rtems\\_sysinit\\_size\\_compare\\_new.patch](https://devel.rtems.org/ticket/1593/rtems_sysinit_size_compare_new.patch))
  - 8 **zhangwenjie, Fri, 23 Jul 2010 14:57:22 GMT**  
attach: set to [sis\\_bsp\\_v1.patch](https://devel.rtems.org/ticket/1593/sis_bsp_v1.patch) ([https://devel.rtems.org/ticket/1593/sis\\_bsp\\_v1.patch](https://devel.rtems.org/ticket/1593/sis_bsp_v1.patch))
  - 9 **zhangwenjie, Tue, 27 Jul 2010 14:10:56 GMT**  
attach: set to [sysinit\\_api.patch](https://devel.rtems.org/ticket/1593/sysinit_api.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_api.patch](https://devel.rtems.org/ticket/1593/sysinit_api.patch))
  - 10 **zhangwenjie, Tue, 27 Jul 2010 14:12:09 GMT**  
attach: set to [sysinit\\_testcase.patch](https://devel.rtems.org/ticket/1593/sysinit_testcase.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_testcase.patch](https://devel.rtems.org/ticket/1593/sysinit_testcase.patch))
  - 11 **zhangwenjie, Tue, 27 Jul 2010 14:13:37 GMT**  
attach: set to [sysinit\\_update\\_managers.patch](https://devel.rtems.org/ticket/1593/sysinit_update_managers.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_update\\_managers.patch](https://devel.rtems.org/ticket/1593/sysinit_update_managers.patch))
  - 12 **zhangwenjie, Tue, 27 Jul 2010 14:17:05 GMT**  
attach: set to [sysinit\\_testcase\\_v1.patch](https://devel.rtems.org/ticket/1593/sysinit_testcase_v1.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_testcase\\_v1.patch](https://devel.rtems.org/ticket/1593/sysinit_testcase_v1.patch))
  - 13 **zhangwenjie, Mon, 09 Aug 2010 15:39:10 GMT**  
attach: set to [sysinit\\_BSP.patch](https://devel.rtems.org/ticket/1593/sysinit_BSP.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_BSP.patch](https://devel.rtems.org/ticket/1593/sysinit_BSP.patch))
  - 14 **zhangwenjie, Mon, 09 Aug 2010 15:40:09 GMT**  
attach: set to [sysinit\\_api\\_v1.patch](https://devel.rtems.org/ticket/1593/sysinit_api_v1.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_api\\_v1.patch](https://devel.rtems.org/ticket/1593/sysinit_api_v1.patch))
  - 15 **zhangwenjie, Mon, 09 Aug 2010 15:40:42 GMT**  
attach: set to [sysinit\\_update\\_managers\\_v1.patch](https://devel.rtems.org/ticket/1593/sysinit_update_managers_v1.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_update\\_managers\\_v1.patch](https://devel.rtems.org/ticket/1593/sysinit_update_managers_v1.patch))
  - 16 **zhangwenjie, Mon, 09 Aug 2010 15:41:21 GMT**  
attach: set to [sysinit\\_testcase\\_v2.patch](https://devel.rtems.org/ticket/1593/sysinit_testcase_v2.patch) ([https://devel.rtems.org/ticket/1593/sysinit\\_testcase\\_v2.patch](https://devel.rtems.org/ticket/1593/sysinit_testcase_v2.patch))
- 

#### Comment 1

1. **zhangwenjie, Fri, 23 Jul 2010 14:52:26 GMT**
2. **attachments.isobsolete:** changed from 0 to 1, 1, 1

#### Comment 2

1. **zhangwenjie, Fri, 23 Jul 2010 14:57:22 GMT**
2. **attachments.isobsolete:** changed from 0 to 1

#### Comment 3

1. **zhangwenjie, Tue, 27 Jul 2010 14:10:56 GMT**
2. **attachments.isobsolete:** changed from 0 to 1

#### Comment 4

1. **zhangwenjie, Tue, 27 Jul 2010 14:12:09 GMT**
2. **attachments.isobsolete:** changed from 0 to 1

#### Comment 5

1. **zhangwenjie, Tue, 27 Jul 2010 14:13:37 GMT**
2. **attachments.isobsolete:** changed from 0 to 1

**Comment 6**

1. **zhangwenjie**, Tue, 27 Jul 2010 14:17:05 GMT
2. **attachments.isobsolete**: changed from **0** to **1**

**Comment 7**

1. **zhangwenjie**, Mon, 09 Aug 2010 15:39:10 GMT
2. **attachments.isobsolete**: changed from **0** to **1**

**Comment 8**

1. **zhangwenjie**, Mon, 09 Aug 2010 15:40:09 GMT
2. **attachments.isobsolete**: changed from **0** to **1**

**Comment 9**

1. **zhangwenjie**, Mon, 09 Aug 2010 15:40:42 GMT
2. **attachments.isobsolete**: changed from **0** to **1**

**Comment 10**

1. **zhangwenjie**, Mon, 09 Aug 2010 15:41:21 GMT
2. **attachments.isobsolete**: changed from **0** to **1**

**Comment 11**

1. **Sebastian Huber**, Wed, 11 Aug 2010 13:43:31 GMT

It is possible to include files within the SECTIONS scope in linker command files. We can use this to reduce the amount of copy & paste inside the linker command files. Example:

```
.rodata : {
  *(.rodata .rodata.* .gnu.linkonce.r.*) INCLUDE linkcmds_score_rodata
}
```

We can use this also for the "Special FreeBSD sysctl sections".

**Comment 12**

1. **Joel Sherrill**, Sun, 23 Nov 2014 16:48:07 GMT
2. **type**: changed from **defect** to **enhancement**
3. **description**: modified (diff)

**Comment 13**

1. **Gedare Bloom**, Mon, 24 Nov 2014 18:58:28 GMT
2. **version**: changed from **HEAD** to **4.11**

Replace Version=HEAD with Version=4.11 for the tickets with Milestone >= 4.11

**Comment 14**

1. **Sebastian Huber**, Thu, 27 Nov 2014 13:06:45 GMT
2. **milestone**: changed from **4.11** to **5.0**

**Comment 15**

1. **Sebastian Huber**, Mon, 15 Dec 2014 14:52:41 GMT
2. **description**: modified (diff)
3. **milestone**: changed from **4.11** to **5.0**

**Comment 16**

1. **Sebastian Huber**, Wed, 02 Sep 2015 12:52:44 GMT

2. **status:** changed from **new** to **closed**
3. **resolution:** set to **wontfix**

Obsoleted by #2408.

#### Comment 17

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

## 1712 - Add LWIP Support to RTEMS

<b>Link</b>	<a href="https://devel.rtems.org/ticket/1712">https://devel.rtems.org/ticket/1712</a> ( <a href="https://devel.rtems.org/ticket/1712">https://devel.rtems.org/ticket/1712</a> )
<b>Id</b>	1712
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	28 October 2010 15:14:22
<b>Modified</b>	16 December 2021 15:53:06
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	network/legacy
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	minor
<b>Keywords</b>	
<b>Cc</b>	ralf.corsepius@... thomas.doerfler@... chrisj@... sebastian.huber@...
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

This port was done by Marcello Presulli and has been in my inbox for a while. I think I have merged most of their BSP specific work but the lwip has been pending. They managed to run LWIP+SNMP and an application in something like 128K RAM

Here are some email fragments about it.

For now we have just finished to port the latest lwip-1.3.2 based on the latest rtems 4.9.4 version successfully including a test\_app for pings.  
We have stressed the stack with ping floods (packetsize 1400 Bytes interval ~150ms) about 250.000 sequences or more without packet losses and an average latency of 2ms.  
Additional we have adopted a new bsp target for the mcf5225x platform.

To lwip now:

we integrated it directly via the autoconfigure/automake process under the rtems cpukit/liblwip subtree and therefore it gets built with rtems when u configure it with --enable-networking=lwip appropriately.  
The driver on the other side we put it in libcpu/m68k/mcf5225x and it got built in the library context of the librtemsbsp.a.  
The driver has only 2 references on lwip headers ...

To the bsp:

The bsp we have adopted from mcf52223 and have created it as a own bsp-target=mcf5225x also via the autoconfig/automake mechanism.  
In the bsp itself i have modified the bsp\_get\_CPU\_clock\_speed() and some improvements in the console driver and PIT2 timer interrupt.  
The bsp\_start() we have defined as weak symbol so we don't have to touch the "empty" bsp\_start() of rtems coz it's platform-circuit specific you know.

#### Attachments:

1. **Joel Sherrill**, Thu, 28 Oct 2010 15:14:22 GMT  
**attach:** set to [mcf5225x+lwip.zip](https://devel.rtems.org/ticket/1712/mcf5225x+lwip.zip) (<https://devel.rtems.org/ticket/1712/mcf5225x+lwip.zip>)

#### Comment 1

1. **Joel Sherrill**, Thu, 28 Oct 2010 15:14:37 GMT
2. **cc: Sebastian Huber** added

#### Comment 2

1. **Joel Sherrill**, Thu, 28 Oct 2010 15:14:49 GMT
2. **cc: Chris Johns** added

#### Comment 3

1. **Joel Sherrill**, Thu, 28 Oct 2010 15:15:22 GMT
2. **cc: thomas.doerfler** added

#### Comment 4

1. **Joel Sherrill**, Thu, 28 Oct 2010 15:15:37 GMT
2. **cc: Ralf Corsepius** added

#### Comment 5

1. **Ralf Corsepius**, Tue, 02 Nov 2010 23:41:51 GMT

Replying to comment:8:

Sebastian, others,

I have had second thoughts about putting this in RTEMS. I agree that it would be better to submit the port to LWIP and let it live there.

IMO, this proposal is non-applicable, because a network stack's interactions are deeply woven with the OS.

Considering this, using an external networking stack introduces bootstrapping problems (== problems building rtems).

That said, to me, LWIP is a binary decision: Switch from BSD or LWIP resp. to forget about it - I am very strongly leaning towards the latter and consider all proposal so far to be beyond reason.

#### Comment 6

1. **Gedare Bloom**, Sat, 22 Nov 2014 14:28:21 GMT
2. **owner:** changed from **Eric Norum** to **Joel Sherrill**
3. **status:** changed from **new** to **assigned**
4. **version:** changed from **HEAD** to **4.11**
5. **description:** modified (diff)

#### Comment 7

1. **Gedare Bloom**, Sat, 22 Nov 2014 14:28:41 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **wontfix**

#### Comment 8

1. **Gedare Bloom**, Sat, 22 Nov 2014 14:29:10 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **wontfix** deleted
4. **milestone:** changed from **4.11** to **5.0**

#### Comment 9

1. **Pavel Pisa**, Sun, 20 Mar 2016 01:17:10 GMT

Some more LwIP pointers and ideas are expressed at next Wiki page

<https://devel.rtems.org/wiki/Packages/LWIP>

#### Comment 10

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

#### Comment 11

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:53:06 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**
4. **description:** modified (diff)

lwip is currently in its own repo and has better support. Closing.

**1728 - Patch for RTEMS-BSP m68k/mcf5225x**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/1728">https://devel.rtems.org/ticket/1728</a> ( <a href="https://devel.rtems.org/ticket/1728">https://devel.rtems.org/ticket/1728</a> )
<b>Id</b>	1728
<b>Reporter</b>	Marcello Presulli
<b>Created</b>	22 December 2010 08:12:53
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	4.9
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This patch is based on a "clean" RTEMS 4.9.4 and offers some modifications/enhancements for the BSP.

- Generic Exception Handler can be used instead of \_uhoh
- Flash Driver for the onboard flash including flash security
- DMA initializations can be used to substitute the whole termios, so we saved alot of code/memory size
- Bugfixes in fec for the lwip-port, the fec driver works now "optimized" with the lwip-port
- RTC driver routines which configures the RTC clock and time
- generic software trap handler capable of return values
- Bugfix in "old" bsp with MASKALL\_BIT when use RTEMS without console
- bugfixes and extensions in bsp header file "mcf5225x.h"
- generic dbg\_printk() which prints debug outputs directly via a dma channel

I hope someone have the time to merge it into the CVS head, it shouldn't be a real task i think.

**Attachments:**

- 
- 1 Sebastian Huber, Tue, 28 Jun 2016 12:49:33 GMT**  
**attach:** set to [rtems-4.9.4\\_embed-it-part-0.patch.bz2](https://devel.rtems.org/ticket/1728/rtems-4.9.4_embed-it-part-0.patch.bz2) ([https://devel.rtems.org/ticket/1728/rtems-4.9.4\\_embed-it-part-0.patch.bz2](https://devel.rtems.org/ticket/1728/rtems-4.9.4_embed-it-part-0.patch.bz2))
  - 2 Sebastian Huber, Tue, 28 Jun 2016 12:49:45 GMT**  
**attach:** set to [rtems-4.9.4\\_embed-it-part-1.patch.bz2](https://devel.rtems.org/ticket/1728/rtems-4.9.4_embed-it-part-1.patch.bz2) ([https://devel.rtems.org/ticket/1728/rtems-4.9.4\\_embed-it-part-1.patch.bz2](https://devel.rtems.org/ticket/1728/rtems-4.9.4_embed-it-part-1.patch.bz2))
- 

**Comment 1**

- 1. Marcello Presulli, Wed, 22 Dec 2010 08:12:53 GMT**

This patch is based on a "clean" RTEMS 4.9.4 and offers some modifications/enhancements for the BSP.

Generic Exception Handler can be used instead of \_uhoh Flash Driver for the onboard flash including flash security DMA initializations can be used to substitute the whole termios, so we saved alot of code/memory size Bugfixes in fec for the lwip-port, the fec driver works now "optimized" with the lwip-port RTC driver routines which configures the RTC clock and time generic software trap handler capable of return values Bugfix in "old" bsp with MASKALL\_BIT when use RTEMS without console bugfixes and extensions in bsp header file "mcf5225x.h" generic dbg\_printk() which prints debug outputs directly via a dma channel

I hope someone have the time to merge it into the CVS head, it shouldn't be a real task i think.

**Comment 2**

- 1. Sebastian Huber, Thu, 18 Dec 2014 09:26:44 GMT**
- priority:** changed from **normal** to **low**
- severity:** changed from **minor** to **normal**
- component:** changed from **patch - do not use** to **bsps**
- description:** modified (diff)
- milestone:** changed from **4.11** to **5.0**

Patch is missing.

**Comment 3**

- 1. Amar Takhar, Fri, 19 Dec 2014 13:21:12 GMT**

I looked in the Bugzilla DB and could not find a patch this is not a migration issue.



**Comment 4**

1. **Amar Takhar**, Fri, 19 Dec 2014 13:22:56 GMT

Also:

: host aspmx.l.google.com[74.125.129.27] said: 550 5.2.1 The email account that you tried to reach is disabled. i1si14392786pdk.67 - gsmtpl (in reply to RCPT TO command)

We should either close the ticket or find another way to contact the submitter.

**Comment 5**

1. **Amar Takhar**, Fri, 19 Dec 2014 13:44:25 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **invalid**

Closing as we cannot get ahold of the original submitter and do not have a patch. If anyone has a copy please attach it to the ticket.

**Comment 6**

1. **Sebastian Huber**, Tue, 28 Jun 2016 12:50:13 GMT

Add patches received by mail for reference.

**Comment 7**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

**1815 - \_ISR\_Nest\_level should be protected with interrupts disabled in function \_Watchdog\_Insert**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/1815">https://devel.rtems.org/ticket/1815</a> ( <a href="https://devel.rtems.org/ticket/1815">https://devel.rtems.org/ticket/1815</a> )
<b>Id</b>	1815
<b>Reporter</b>	Helder Silva
<b>Created</b>	15 June 2011 15:20:17
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

\_ISR\_Nest\_level should be protected with interrupts disabled in function \_Watchdog\_Insert, because another interrupt can occur after \_ISR\_Nest\_level is saved, causing inconsistency in the global variable.

**Comment 1**

1. **Helder Silva**, Thu, 16 Jun 2011 09:35:16 GMT

Yes, by swapping those 2 lines.

**Comment 2**

1. **Joel Sherrill**, Mon, 24 Nov 2014 14:59:19 GMT
2. **description**: modified (diff)

Was this fixed?

**Comment 3**

1. **Gedare Bloom**, Mon, 24 Nov 2014 18:58:28 GMT

2. **version:** changed from **HEAD** to **4.11**

Replace Version=HEAD with Version=4.11 for the tickets with Milestone >= 4.11

#### Comment 4

1. **Sebastian Huber**, Thu, 18 Dec 2014 10:11:08 GMT
2. **description:** modified (diff)
3. **milestone:** changed from **4.11** to **5.0**

I am not sure what the problem is. Interrupts are nested, so the code looks all right to me.

For SMP we have to re-write the watchdog stuff anyway and the `_Watchdog_Sync_level` and `_Watchdog_Sync_count` will go away.

#### Comment 5

1. **Sebastian Huber**, Tue, 05 Jan 2016 10:41:38 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **invalid**

There is no problem in pre 4.11 versions, since interrupts are nested. Version 4.11 and later use a different watchdog handler implementation.

#### Comment 6

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

## 1820 - sptests/sp36: Improper buildsystem integration

<b>Link</b>	<a href="https://devel.rtems.org/ticket/1820">https://devel.rtems.org/ticket/1820</a> ( <a href="https://devel.rtems.org/ticket/1820">https://devel.rtems.org/ticket/1820</a> )
<b>Id</b>	1820
<b>Reporter</b>	Ralf Corsepius
<b>Created</b>	20 June 2011 05:59:36
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

sptests/sp36 is improperly integrated into the rtems buildsystem.

sp36 is missing from SUBDIRS in sptests/Makefile.am, but is referenced in sptests/configure.ac, as well as the code is present in sp36/

sp36/ either should be activated (== added to SUBDIRS) or be fully removed.

#### Comment 1

1. **Ralf Corsepius**, Mon, 20 Jun 2011 05:59:36 GMT

sptests/sp36 is improperly integrated into the rtems buildsystem.

sp36 is missing from SUBDIRS in sptests/Makefile.am, but is referenced in sptests/configure.ac, as well as the code is present in sp36/

sp36/ either should be activated (== added to SUBDIRS) or be fully removed.

#### Comment 2

1. **Gedare Bloom**, Mon, 24 Nov 2014 18:58:28 GMT
2. **version:** changed from **HEAD** to **4.11**

Replace Version=HEAD with Version=4.11 for the tickets with Milestone >= 4.11

#### Comment 3

1. **Sebastian Huber**, Thu, 18 Dec 2014 10:15:27 GMT
2. **priority**: changed from **normal** to **low**
3. **description**: modified (diff)
4. **milestone**: changed from **4.11** to **5.0**

**Comment 4**

1. **Chris Johns**, Mon, 14 Aug 2017 00:32:35 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**

**Comment 5**

1. **Sebastian Huber**, Tue, 10 Oct 2017 06:46:55 GMT
2. **component**: changed from **testing** to **unspecified**

**Comment 6**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

---

**2000 - Re-add removed LINK\_OBJS to MP tests**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2000">https://devel.rtems.org/ticket/2000</a> ( <a href="https://devel.rtems.org/ticket/2000">https://devel.rtems.org/ticket/2000</a> )
<b>Id</b>	2000
<b>Reporter</b>	Marta Rybczynska
<b>Created</b>	6 January 2012 14:20:38
<b>Modified</b>	18 June 2021 08:39:30
<b>Owner</b>	Ralf Corsepius
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	joel.sherrill@... fred@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

PR1589 commit:  
2011-12-08 Joel Sherrill

PR 1589/build

- base\_mp/node1/Makefile.am, base\_mp/node2/Makefile.am, base\_sp/Makefile.am, capture/Makefile.am, cctest/Makefile.am, fileio/Makefile.am, hello/Makefile.am, iostream/Makefile.am, loopback/Makefile.am, minimum/Makefile.am, nsecs/Makefile.am, paranoia/Makefile.am, pppd/Makefile.am, ticker/Makefile.am, unlimited/Makefile.am: Remove obsolete optional manager capability.

and  
2011-12-08 Joel Sherrill

PR 1589/build

- mp01/node1/Makefile.am, mp01/node2/Makefile.am, mp02/node1/Makefile.am, mp02/node2/Makefile.am, mp03/node1/Makefile.am, mp03/node2/Makefile.am, mp04/node1/Makefile.am, mp04/node2/Makefile.am, mp05/node1/Makefile.am, mp05/node2/Makefile.am, mp06/node1/Makefile.am, mp06/node2/Makefile.am, mp07/node1/Makefile.am, mp07/node2/Makefile.am, mp08/node1/Makefile.am, mp08/node2/Makefile.am, mp09/node1/Makefile.am, mp09/node2/Makefile.am, mp10/node1/Makefile.am, mp10/node2/Makefile.am, mp11/node1/Makefile.am, mp11/node2/Makefile.am, mp12/node1/Makefile.am, mp12/node2/Makefile.am, mp13/node1/Makefile.am, mp13/node2/Makefile.am, mp14/node1/Makefile.am, mp14/node2/Makefile.am: Remove obsolete optional manager capability.

remove LINK\_OBJS from the MP tests. They do not compile anymore. This patch re-adds them.

**Attachments:**

- 
- 1 **Marta Rybczynska**, Fri, 06 Jan 2012 14:20:38 GMT  
**attach:** set to [build\\_patch\\_patch \(https://devel.rtems.org/ticket/2000/build\\_patch\\_patch\)](https://devel.rtems.org/ticket/2000/build_patch_patch)
- 

**Comment 1**

1. **Marta Rybczynska**, Fri, 06 Jan 2012 14:20:38 GMT

PR1589 commit: 2011-12-08 Joel Sherrill

PR 1589/build

base\_mp/node1/Makefile.am, base\_mp/node2/Makefile.am, base\_sp/Makefile.am, capture/Makefile.am, cdtest/Makefile.am, fileio/Makefile.am, hello/Makefile.am, iostream/Makefile.am, loopback/Makefile.am, minimum/Makefile.am, nsecs/Makefile.am, paranoia/Makefile.am, pppd/Makefile.am, ticker/Makefile.am, unlimited/Makefile.am: Remove obsolete optional manager capability.

and 2011-12-08 Joel Sherrill

PR 1589/build

mp01/node1/Makefile.am, mp01/node2/Makefile.am, mp02/node1/Makefile.am, mp02/node2/Makefile.am, mp03/node1/Makefile.am, mp03/node2/Makefile.am, mp04/node1/Makefile.am, mp04/node2/Makefile.am, mp05/node1/Makefile.am, mp05/node2/Makefile.am, mp06/node1/Makefile.am, mp06/node2/Makefile.am, mp07/node1/Makefile.am, mp07/node2/Makefile.am, mp08/node1/Makefile.am, mp08/node2/Makefile.am, mp09/node1/Makefile.am, mp09/node2/Makefile.am, mp10/node1/Makefile.am, mp10/node2/Makefile.am, mp11/node1/Makefile.am, mp11/node2/Makefile.am, mp12/node1/Makefile.am, mp12/node2/Makefile.am, mp13/node1/Makefile.am, mp13/node2/Makefile.am, mp14/node1/Makefile.am, mp14/node2/Makefile.am: Remove obsolete optional manager capability.

remove LINK\_OBJS from the MP tests. They do no compile anymore. This patch re-adds them.

**Comment 2**

1. **Marta Rybczynska**, Fri, 06 Jan 2012 14:21:16 GMT  
 2. **cc:** **Joel Sherrill** added

**Comment 3**

1. **Marta Rybczynska**, Fri, 06 Jan 2012 14:21:54 GMT  
 2. **cc:** **frederic.brault@...** added

**Comment 4**

1. **Gedare Bloom**, Mon, 24 Nov 2014 18:58:28 GMT  
 2. **version:** changed from **HEAD** to **4.11**

Replace Version=HEAD with Version=4.11 for the tickets with Milestone >= 4.11

**Comment 5**

1. **Sebastian Huber**, Thu, 18 Dec 2014 11:07:49 GMT  
 2. **priority:** changed from **normal** to **low**  
 3. **description:** modified (diff)  
 4. **milestone:** changed from **4.11** to **5.0**

**Comment 6**

1. **Chris Johns**, Mon, 14 Aug 2017 00:35:16 GMT  
 2. **version:** **4.11** deleted  
 3. **milestone:** changed from **5.0** to **Indefinite**

**Comment 7**

1. **Sebastian Huber**, Fri, 18 Jun 2021 08:39:30 GMT  
 2. **status:** changed from **new** to **closed**  
 3. **resolution:** set to **wontfix**  
 4. **milestone:** changed from **Indefinite** to **6.1**

Fixed by the new build system.

---

**2071 - The object-file suffixes for default-bsp-post-link in leaf.cfg don't work with make-exe...**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2071">https://devel.rtems.org/ticket/2071</a> ( <a href="https://devel.rtems.org/ticket/2071">https://devel.rtems.org/ticket/2071</a> )
<b>Id</b>	2071
<b>Reporter</b>	cynt6007
<b>Created</b>	21 June 2012 16:26:35
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Ralf Corsepius
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	major
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

Would it be proper to change the suffix of the input in default-bsp-post-link in rtems/make/leaf.cfg ?

Namely changing:

```
define default-bsp-post-link
```

- \$(NM) -g -n \$@ > \$(basename \$@).num
- \$(SIZE) \$@

```
endif
```

```
define default-bsp-post-link
+ $(NM) -g -n $@.o > $(basename $@).num
+ $(SIZE) $@.o
endif
```

I'm working on the application side of RTEMS (as opposed to the source), but here are the errors I encountered, what I did to find the problem, and the results.

I kept getting errors when I ran the BuildTests?.sh...

```
~/rtems-addon-packages/examples/openldap$
...
i386-rtems4.11-nm o-optimize/slapd-addel
i386-rtems4.11-nm: 'o-optimize/slapd-addel': No such file
...
~/rtems-addon-packages/examples/openldap$
...
i386-rtems4.11-size o-optimize/slapd-addel
i386-rtems4.11-size: 'o-optimize/slapd-addel': No such file
```

After looking at the Makefile it looks like they were called by: make-exe.

Doing

```
grep -r make-exe /opt
```

revealed make-exe is defined in /opt/rtems-4.11/make/leaf.cfg, which calls bsp-post-link, (which is exactly the stage of the build process giving errors).

According to man, nm and size work on object files. So, I changed the suffixes in /opt/rtems-4.11/make/leaf.cfg and the errors went away. After making the change, the following additional objects appeared in o-optimize:

\*.bin and \*.ralf, with an approximate size of 570,000. The sizes vary slightly...

If changing the suffixes in /opt/rtems-4.11/make/leaf.cfg makes sense, would it make sense to change them for rtems/make/leaf.cfg ? Also, there are other target.cfg's in the different bsp s that may have similar problems.

Thanks,  
Cynthia Rempel

## Comment 1

1. **cynt6007**, Thu, 21 Jun 2012 16:26:35 GMT

Would it be proper to change the suffix of the input in default-bsp-post-link in rtems/make/leaf.cfg ?

Namely changing:

```
define default-bsp-post-link
```

```
$(NM) -g -n $@ > $(basename $@).num $(SIZE) $@
```

```
endif
```

```
define default-bsp-post-link + $(NM) -g -n $@.o > $(basename $@).num + $(SIZE) $@.o endif
```

I'm working on the application side of RTEMS (as opposed to the source), but here are the errors I encountered, what I did to find the problem, and the results.

I kept getting errors when I ran the BuildTests?.sh...

```
~/rtems-addon-packages/examples/openldap$ ... i386-rtems4.11-nm o-optimize/slapd-addel i386-rtems4.11-nm: 'o-optimize/slapd-addel': No such file ...
~/rtems-addon-packages/examples/openldap$ ... i386-rtems4.11-size o-optimize/slapd-addel i386-rtems4.11-size: 'o-optimize/slapd-addel': No such file
```

After looking at the Makefile it looks like they were called by: make-exe.

Doing

```
grep -r make-exe /opt
```

revealed make-exe is defined in /opt/rtems-4.11/make/leaf.cfg, which calls bsp-post-link, (which is exactly the stage of the build process giving errors).

According to man, nm and size work on object files. So, I changed the suffixes in /opt/rtems-4.11/make/leaf.cfg and the errors went away. After making the change, the following additional objects appeared in o-optimize:

\*.bin and \*.ralf, with an approximate size of 570,000. The sizes vary slightly...

If changing the suffixes in /opt/rtems-4.11/make/leaf.cfg makes sense, would it make sense to change them for rtems/make/leaf.cfg ? Also, there are other target.cfg's in the different bsp s that may have similar problems.

Thanks, Cynthia Rempel

#### Comment 2

1. **cynt6007**, Thu, 21 Jun 2012 16:27:09 GMT
2. **severity**: changed from **normal** to **major**

#### Comment 3

1. **Gedare Bloom**, Mon, 24 Nov 2014 18:58:28 GMT
2. **version**: changed from **HEAD** to **4.11**

Replace Version=HEAD with Version=4.11 for the tickets with Milestone >= 4.11

#### Comment 4

1. **Sebastian Huber**, Thu, 18 Dec 2014 11:14:45 GMT
2. **description**: modified (diff)
3. **milestone**: changed from **4.11** to **5.0**

#### Comment 5

1. **Chris Johns**, Sun, 13 Aug 2017 23:41:42 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**

#### Comment 6

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

## 2111 - AVR needs avr-libc to compile RTEMS.

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2111">https://devel.rtems.org/ticket/2111</a> ( <a href="https://devel.rtems.org/ticket/2111">https://devel.rtems.org/ticket/2111</a> )
<b>Id</b>	2111
<b>Reporter</b>	cynt6007
<b>Created</b>	3 April 2013 03:46:56
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	config
<b>Status</b>	closed
<b>Resolution</b>	
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	joel.sherrill@... ralf.corsepius@... gedare@...
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The avr io.h header gives a warning that if not doing avr-libc, that if not heeded leads to many errors.

Need an avr-libc configuration file... should be a place-holding stub that states this is a problematic build.

Anyway, these are just some cans of worms... FYI

AVR has issues so deep it requires ~50 patches for binutils, ~60 patches for gcc, and has ~14 patches for avr-libc.

I suspect getting ONE functional AVR-RTEMS a major undertaking... I wonder if it might be worth exploring using ATMEL's prepatched toolchain for non-Ada builds... For Ada-builds, that's going to be another major undertaking...

Eric Weddington (at ATMEL) is recommending the use of their source for C, C++ builds... <http://distribute.atmel.no/tools/opensource/Atmel-AVR-Toolchain-3.4.1/avr/>

Although the Rolf Ebert (at AVR-Ada) have their own patch-set (using different tool versions) etc, which is making updating the AVR port so challenging... <http://sourceforge.net/projects/avr-ada/files/avr-ada/Source%20Dist/>

Their source-builder is located at:  
<avr-ada/tools/build/build-avr-ada.sh>

#### Comment 1

1. **Ralf Corsepius**, Thu, 04 Apr 2013 04:25:08 GMT
2. **cc: Ralf Corsepius** added

#### Comment 2

1. **Gedare Bloom**, Tue, 09 Apr 2013 16:21:34 GMT
2. **cc: Gedare Bloom** added

#### Comment 3

1. **Joel Sherrill**, Tue, 09 Apr 2013 17:13:00 GMT
2. **cc: Joel Sherrill** added

#### Comment 4

1. **Joel Sherrill**, Fri, 12 Apr 2013 23:16:03 GMT

Replying to comment:14:

... gcc won't build without a libc... (complains about 'limits.h') gcc-4.8.0 has an internal compiler error with avr-libc, and newlib is too big for AVR, so going back to gcc-4.7.2 with avr-libc... avr community maintains non-rtems targets, so using an avr target (as opposed to avr-rtems4.11)

This is OK. The avr GCC community needs to know this so they can decide what to do. Unfortunately as much as we would like all targets to upgrade in lockstep, it doesn't happen. We would need a more aggressive testing program to know this as early as possible and attempt to fix an issue. And we could still end up in this situation.

#### Comment 5

1. **Gedare Bloom**, Sat, 22 Nov 2014 13:14:06 GMT
2. **component:** changed from **RTEMS Configuration** to **cpukit**
3. **description:** modified (diff)
4. **milestone:** set to **5.0**

#### Comment 6

1. **Gedare Bloom**, Sat, 22 Nov 2014 13:14:56 GMT
2. **owner:** changed from **Chris Johns** to **Joel Sherrill**
3. **status:** changed from **new** to **assigned**

#### Comment 7

1. **Joel Sherrill**, Sat, 22 Nov 2014 16:12:07 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **invalid**

#### Comment 8

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

---

## 2114 - statvfs for MS-DOS filesystem and 'df' command for shell

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2114">https://devel.rtems.org/ticket/2114</a> ( <a href="https://devel.rtems.org/ticket/2114">https://devel.rtems.org/ticket/2114</a> )
<b>Id</b>	2114
<b>Reporter</b>	Andrey Mozzhuhin
<b>Created</b>	8 April 2013 19:17:41
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	sebastian.huber@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

I need statvfs for MS-DOS filesystem in my project. Share implementation and example shell command 'df' - like in GNU coreutils, but very simplified.

**Attachments:**

- 
- 1 **Andrey Mozzhuhin, Mon, 08 Apr 2013 19:17:41 GMT**  
**attach:** set to [msdos\\_statvfs.patch](https://devel.rtems.org/ticket/2114/msdos_statvfs.patch) ([https://devel.rtems.org/ticket/2114/msdos\\_statvfs.patch](https://devel.rtems.org/ticket/2114/msdos_statvfs.patch))
- 

**Comment 1**

- 1. **Sebastian Huber**, Wed, 10 Apr 2013 14:22:45 GMT
- 2. **cc: Sebastian Huber** added

Can you please add a proper license header to all new files. Please send patches to . It would be good to have a test case for the new feature. Please have a look at

<http://git.rtems.org/rtems/tree/testsuites/fstests/fsdosfssync01/init.c>

for an example test.

**Comment 2**

- 1. **Gedare Bloom**, Mon, 24 Nov 2014 18:58:28 GMT
- 2. **version:** changed from **HEAD** to **4.11**

Replace Version=HEAD with Version=4.11 for the tickets with Milestone >= 4.11

**Comment 3**

- 1. **Sebastian Huber**, Thu, 18 Dec 2014 12:26:56 GMT
- 2. **priority:** changed from **normal** to **low**
- 3. **milestone:** changed from **4.11** to **5.0**

**Comment 4**

- 1. **Chris Johns**, Mon, 14 Aug 2017 00:40:48 GMT
- 2. **status:** changed from **new** to **closed**
- 3. **resolution:** set to **invalid**

No activity.

**Comment 5**

- 1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
- 2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

---

**2189 - Insufficient documentation for rtems\_clock\_get\_tod()**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/2189">https://devel.rtems.org/ticket/2189</a> ( <a href="https://devel.rtems.org/ticket/2189">https://devel.rtems.org/ticket/2189</a> )
<b>Id</b>	2189
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	16 September 2014 06:33:52
<b>Modified</b>	29 September 2021 13:23:52
<b>Owner</b>	Needs Funding
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	highest
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	chrisj@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

It is not clear which date and time is returned by `rtems_clock_get_tod()`. For example which time zone is used. Is there a relation to UTC?

**Comment 1**

1. **Chris Johns**, Tue, 16 Sep 2014 07:29:53 GMT
2. **cc: Chris Johns** added

The timezone is the one you used when you set the time with the set call. If the time is not set this function returns `RTEMS_NOT_DEFINED`. It is assumed you set a suitable time in the first place and know the specific context of use.

**Comment 2**

1. **Gedare Bloom**, Fri, 19 Dec 2014 05:06:18 GMT
2. **priority**: changed from **normal** to **highest**

Bump priority to highest for tickets with a fix attached or seemingly simple fix proposed in the description or comments.

**Comment 3**

1. **Gedare Bloom**, Mon, 02 Mar 2015 20:42:45 GMT
2. **milestone**: changed from **4.11** to **4.11.1**

bump milestone

**Comment 4**

1. **Joel Sherrill**, Tue, 20 Oct 2015 23:05:06 GMT

This ticket does not have a patch attached or an obvious (to me) fix. What is the fix proposed?

**Comment 5**

1. **Sebastian Huber**, Wed, 21 Oct 2015 05:42:48 GMT

We need a more precise documentation of the time services. How are leap seconds handled for example? UNIX time vs. UTC.

**Comment 6**

1. **Sebastian Huber**, Tue, 24 Nov 2015 09:34:59 GMT

The wall clock time services lack documentation in general. What is the relation between `rtems_time_of_day` and the UNIX time as specified by IEEE Std 1003.1, 2013 Edition, 4.15 Seconds Since the Epoch (<http://pubs.opengroup.org/onlinepubs/9699919799/>). For example `_TOD_To_seconds()` does not use the expression in this standard document. This affects `rtems_timer_fire_when()`.

**Comment 7**

1. **Joel Sherrill**, Tue, 24 Nov 2015 16:22:54 GMT

Can you provide a specific link? That is to the top of the standard.

**Comment 8**

1. **Sebastian Huber**, Wed, 25 Nov 2015 06:49:43 GMT

4.15 Seconds Since the Epoch

[http://pubs.opengroup.org/onlinepubs/9699919799/basedefs/V1\\_chap04.html](http://pubs.opengroup.org/onlinepubs/9699919799/basedefs/V1_chap04.html)

See also

<http://www.madore.org/~david/computers/unix-leap-seconds.html>

#### Comment 9

1. **Sebastian Huber**, Thu, 26 Jan 2017 07:16:00 GMT
2. **milestone**: changed from **4.11.1** to **4.11.2**

#### Comment 10

1. **Sebastian Huber**, Wed, 15 Feb 2017 13:37:51 GMT
2. **owner**: changed from **Joel Sherrill** to **Needs Funding**
3. **status**: changed from **new** to **assigned**
4. **milestone**: changed from **4.11.2** to **Indefinite**

#### Comment 11

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords**: **qualification** added

#### Comment 12

1. **Sebastian Huber**, Wed, 29 Sep 2021 13:23:52 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**
4. **milestone**: changed from **Indefinite** to **6.1**

Documentation was improved for RTEMS 6.

## 2215 - Duplicate code for TAR support

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2215">https://devel.rtems.org/ticket/2215</a> ( <a href="https://devel.rtems.org/ticket/2215">https://devel.rtems.org/ticket/2215</a> )
<b>Id</b>	2215
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 December 2014 07:21:49
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

We have similar code in `rtems_tarfs_load()`, `Untar_FromMemory()` and `Untar_FromFile()`. These functions should instead use a common TAR archive iterator with specific visitor functions.

#### Comment 1

1. **Chris Johns**, Sun, 15 May 2016 23:09:35 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **duplicate**

Duplicate of #2415.

#### Comment 2

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

**2269 - x86 Context Switch Synchronization and SMP**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2269">https://devel.rtems.org/ticket/2269</a> ( <a href="https://devel.rtems.org/ticket/2269">https://devel.rtems.org/ticket/2269</a> )
<b>Id</b>	2269
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	13 February 2015 21:02:35
<b>Modified</b>	9 November 2017 06:26:42
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The x86 context switch code does not implement the "is executing" hand-off protocol used on the other ports. It should.

**Comment 1**

1. **Sebastian Huber**, Fri, 13 Feb 2015 21:05:44 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **duplicate**

<https://devel.rtems.org/ticket/2183>

How can we set the duplicate like on Bugzilla?

**Comment 2**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

---

**2301 - cpukit is built in BSP, and BSP custom, specific part of build tree but isnt built using BSP's spec file**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2301">https://devel.rtems.org/ticket/2301</a> ( <a href="https://devel.rtems.org/ticket/2301">https://devel.rtems.org/ticket/2301</a> )
<b>Id</b>	2301
<b>Reporter</b>	Jeffrey Hill
<b>Created</b>	13 March 2015 01:23:20
<b>Modified</b>	18 June 2021 08:42:56
<b>Owner</b>	Needs Funding
<b>Type</b>	enhancement
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	4.10
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	cpukit multilib custom spec
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The nios2 soft-core processor is probably a bit of a different beast because it has many options when the FPGA programming is configured. It is probably therefore not a good context for the use of multilibs, although it is possible to enable them.

For the nios2 RTEMS automated system configuration I must interrogate the Altera sopcinfo file to properly specify some of the nios2 cpu instance specific compiler flags such as `{-mhw-div, -mhw-mul, -mhw-mulx}`.

An easy way to do this is to build some custom tools that need to run `_only_on_the_host_` during the build. The source code for these BSP instance custom tools are easy to write if they include header files from the Altera generated HAL (`system.h`, `linker.h`), when they are built. The Altera HAL needs to also be generated, but not installed, during the gnu build. It seems that this is the way that Altera intends for users to learn about system configuration based on how often their file formats evolve, and also based on lack of documentation for their sopcinfo file. Nevertheless, for many reasons we don't include Altera generated header files into any RTEMS BSP or cpukit source code.

Currently this approach is difficult to fully implement because I must finish the interrogation for the CPU flags during the gnu build system configure phase when `CFLAGS_OPTIMIZE_V` and `CPU_FLAGS` are fetched from the custom `.cfg` file, and so I am unable to build some custom tools that need to run `_only_on_the_host_` during the build at that time.

However, during the preinstall phase it is easy to create a custom "bsp\_specs\_cpu" file like this.

```
*[cpuspecs]:
*[cpuspecs]: % {cpuspecs} -mhw-div
*[cpuspecs]: % {cpuspecs} -mhw-mul
*[cpuspecs]: % {cpuspecs} -mhw-mulx
```

Which could be used in "bsp\_specs" like this.

```
%rename cc1 old_cc1
%rename cc1plus old_cc1plus
%rename lib old_lib
%rename endfile old_endfile
%rename startfile old_startfile
%rename link old_link

%include

*cc1:
%{!qrtems: % {old_cc1} } \
%{qrtems*: % {old_cc1} } % {cpuspecs} }

*cc1plus:
%{!qrtems: % {old_cc1plus} } \
%{qrtems*: % {old_cc1plus} } % {cpuspecs} }

*lib:
%{!qrtems: % {old_lib} } \
%{!nostdlib: % {qrtems: --start-group -l rtemsbsp -l rtemscopy -l c -l gcc --end-group } \
%{!qno linkcmds: -T linkcmds %s`

*startfile:
%{!qrtems: % {old_startfile} } \
%{!nostdlib: % {qrtems: start0.o %s start1.o %s crt0.o %s }
```

```
crtbegin.o %s -e start -u exception_vector }
```

```
*link:
%{!qrtems: % {old_link} } % {qrtems: -dc -dp -N}

*endfile:
%{!qrtems: % {old_endfile} } % {qrtems: crtend.o %s crtn.o %s }
```

This works very nicely excepting that the cpukit isn't built specifying a spec file and so it could use the wrong instructions when generating code. Therefore its tempting to modify the RTEMS build like this.

```
cpukit/aclocal/gcc-specs.m4 | 20 ++++++
cpukit/aclocal/prog-cc.m4 | 8 ++++++
cpukit/automake/compile.am | 5 +++++
3 files changed, 33 insertions(+)
```

```
diff --git a/cpukit/aclocal/gcc-specs.m4 b/cpukit/aclocal/gcc-specs.m4
new file mode 100644
index 0000000..dd49bb9
--- /dev/null
+++ b/cpukit/aclocal/gcc-specs.m4
@@ -0,0 +1,20 @@
+dnl
+dnl $ld$
+dnl
+dnl Check whether the target compiler accepts -specs
+dnl
+
+AC_DEFUN([RTEMS_GCC_SPECS],
+[AC_REQUIRE([RTEMS_PROG_CC])
+AC_CACHE_CHECK([whether $CC accepts -specs,rtems_cv_gcc_specs,
+[
+rtems_cv_gcc_specs=no
+if test x"$GCC" = x"yes"; then
+ touch confspec
+ echo 'void f(){} >confstest.c
+ if test -z "$CC" -specs confspec -c confstest.c 2>&1";then
+rtems_cv_gcc_specs=yes
+ fi
+rm -f confspec confstest*
+ ]])
diff --git a/cpukit/aclocal/prog-cc.m4 b/cpukit/aclocal/prog-cc.m4
index e8b27b5..8dae5de 100644
--- a/cpukit/aclocal/prog-cc.m4
+++ b/cpukit/aclocal/prog-cc.m4
@@ -27,6 +27,14 @@
dnl check if the target compiler may use --pipe
```

```
RTEMS_GCC_PIPE
test "$rtems_cv_gcc_pipe" = "yes" && CC="$CC --pipe"
```

```
+dnl check if the compiler supports --specs
+RTEMS_GCC_SPECS
+
+AS_IF([test x"$rtems_cv_gcc_specs" = xyesh],
+[GCCSPECS="-B$(PROJECT_ROOT)/lib/ -B$(PROJECT_ROOT)/$RTEMS_BSP/lib/"
+GCCSPECS="$GCCSPECS -specs bsp_specs -qrtems_cpukit"])
+AC_SUBST(GCCSPECS)
+
```

```
# Append warning flags if CFLAGS wasn't set.
AS_IF([test "$GCC" = yes && test "$rtems_cv_CFLAGS_set" != set],
[CFLAGS="$CFLAGS -Wall"])
```

```
diff --git a/cpukit/automake/compile.am b/cpukit/automake/compile.am
index 3d81426..0e43494 100644
--- a/cpukit/automake/compile.am
+++ b/cpukit/automake/compile.am
@@ -2,6 +2,11 @@
```

```
## $Id$
##
```

```
+CC = @CC@ $(GCCSPECS)
+CXX = @CXX@ $(GCCSPECS)
+CPP = @CPP@ $(GCCSPECS)
+CCAS = @CCAS@ $(GCCSPECS)
+
```

```
AM_CPPFLAGS = @RTEMS_CPPFLAGS@
AM_CFLAGS =
AM_CCASFLAGS = @RTEMS_CCASFLAGS@
```

I am thinking that hopefully this wont break any existing CPU architecture and or BSP because of several reasons.

- 1) Perhaps typical BSPs included in RTEMS are only modifying the way that executables are linked, and we probably don't create executables during the cpukit build.
- 2) Probably most of the spec files are noop implementation if qrtems isnt specified, and for the cpu kit I specify -qrtems\_cpukit
- 3) I am specifying -qrtems\_cpukit so its easy to write a spec file that does different things when it is and isnt a cpukit build. We could I suppose also define -qrtems\_cpukit\_multilib in that specific situation, if it were important to break that situation out.

In any case this is what I currently have implemented and I will need to look for plan B before I can merge my nios2 support if this type of change looks like a bad idea.

I am therefore writing to the relevant RTEMS wizards for some guidance.

Thanks for your consideration.

#### Comment 1

1. **Jeffrey Hill**, Fri, 13 Mar 2015 01:38:00 GMT
2. **component**: changed from **Autoconf** to **build**

#### Comment 2

1. **Sebastian Huber**, Thu, 26 Jan 2017 07:16:00 GMT
2. **milestone**: changed from **4.11.1** to **4.11.2**

#### Comment 3

1. **Sebastian Huber**, Wed, 15 Feb 2017 13:37:51 GMT
2. **owner**: set to **Needs Funding**
3. **status**: changed from **new** to **assigned**
4. **milestone**: changed from **4.11.2** to **Indefinite**

#### Comment 4

1. **Sebastian Huber**, Fri, 18 Jun 2021 08:42:56 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **wontfix**
4. **milestone**: changed from **Indefinite** to **6.1**

BSP variants may be added in the new build system for each multilib.

## 2330 - nios2 missing atomics, fails to link C++

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2330">https://devel.rtems.org/ticket/2330</a> ( <a href="https://devel.rtems.org/ticket/2330">https://devel.rtems.org/ticket/2330</a> )
<b>Id</b>	2330
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	18 April 2015 15:19:25
<b>Modified</b>	18 June 2021 08:47:00
<b>Owner</b>	Needs Funding
<b>Type</b>	defect
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

```
nios2-rtems4.11-g++ -B./../../../../nios2_iss/lib/ -specs bsp_specs -qrtems -mno-hw-mul -mno-hw-div -O0 -g -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -mno-hw-mul -mno-hw-div -o cxx_iostream.exe init.o
/users/joel/rtems-4.11-work/tools/lib/gcc/nios2-rtems4.11/4.9.2/libstdc++.a(ios_inst.o): In function `atomic_add':
/users/joel/rtems-4.11-work/rtems-source-builder/rtems/build/nios2-rtems4.11-gcc-4.9.2-newlib-2.2.0.20150323-x86_64-linux-gnu-1/build/nios2-rtems4.11/libstdc++-v3/include/ext/atomicity.h:53: undefined reference to `sync_fetch_and_add_4'
/users/joel/rtems-4.11-work/rtems-source-builder/rtems/build/nios2-rtems4.11-gcc-4.9.2-newlib-2.2.0.20150323-x86_64-linux-gnu-1/build/nios2-rtems4.11/libstdc++-v3/include/ext/atomicity.h:53: undefined reference to `sync_fetch_and_add_4'
/users/joel/rtems-4.11-work/tools/lib/gcc/nios2-rtems4.11/4.9.2/libstdc++.a(ios_init.o): In function `exchange_and_add_dispatch':
/users/joel/rtems-4.11-work/rtems-source-builder/rtems/build/nios2-rtems4.11-gcc-4.9.2-newlib-2.2.0.20150323-x86_64-linux-gnu-1/build/nios2-rtems4.11/libstdc++-v3/include/ext/atomicity.h:49: undefined reference to `sync_fetch_and_add_4'
/users/joel/rtems-4.11-work/tools/lib/gcc/nios2-rtems4.11/4.9.2/libstdc++.a(ios_init.o): In function `atomic_add_dispatch':
/users/joel/rtems-4.11-work/rtems-source-builder/rtems/build/nios2-rtems4.11-gcc-4.9.2-newlib-2.2.0.20150323-x86_64-linux-gnu-1/build/nios2-rtems4.11/libstdc++-v3/include/ext/atomicity.h:53: undefined reference to `sync_fetch_and_add_4'
/users/joel/rtems-4.11-work/tools/lib/gcc/nios2-rtems4.11/4.9.2/libstdc++.a(ios_init.o): In function `exchange_and_add_dispatch':
/users/joel/rtems-4.11-work/rtems-source-builder/rtems/build/nios2-rtems4.11-gcc-4.9.2-newlib-2.2.0.20150323-x86_64-linux-gnu-1/build/nios2-rtems4.11/libstdc++-v3/include/ext/atomicity.h:49: undefined reference to `sync_fetch_and_add_4'
/users/joel/rtems-4.11-work/tools/lib/gcc/nios2-rtems4.11/4.9.2/libstdc++.a(locale_inst.o):/users/joel/rtems-4.11-work/rtems-source-builder/rtems/build/nios2-rtems4.11-gcc-4.9.2-newlib-2.2.0.20150323-x86_64-linux-gnu-1/build/nios2-rtems4.11/libstdc++-v3/include/ext/atomicity.h:49: more undefined references to `sync_fetch_and_add_4' follow
```

**Comment 1**

1. **Joel Sherrill**, Mon, 14 Nov 2016 17:46:06 GMT

Still happens on

nios2-rtems4.12-gcc (GCC) 6.2.1 20161110 (RTEMS 4.12, RSB 5469a486e1b67532e20c48e154c7263c59047be4, Newlib 2.4.0.20161025)

This is the only target left with this issue. Help would be appreciated in resolving this.

**Comment 2**

1. **Sebastian Huber**, Tue, 15 Nov 2016 06:36:42 GMT

From my point of view this is a GCC bug:

[https://gcc.gnu.org/bugzilla/show\\_bug.cgi?id=78357](https://gcc.gnu.org/bugzilla/show_bug.cgi?id=78357)

**Comment 3**

1. **Sebastian Huber**, Fri, 18 Nov 2016 07:00:52 GMT

Problem fixed in GCC 7. I wait for a back port to GCC 6.

**Comment 4**

1. **Sebastian Huber**, Thu, 26 Jan 2017 07:16:00 GMT
2. **milestone**: changed from **4.11.1** to **4.11.2**

**Comment 5**

1. **Sebastian Huber**, Wed, 15 Feb 2017 13:37:51 GMT
2. **owner**: set to **Needs Funding**
3. **status**: changed from **new** to **assigned**
4. **milestone**: changed from **4.11.2** to **Indefinite**

**Comment 6**

1. **Sebastian Huber**, Fri, 18 Jun 2021 08:47:00 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

4. **milestone**: changed from **Indefinite** to **6.1**

## 2348 - Timecounter: Add NTP support

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2348">https://devel.rtems.org/ticket/2348</a> ( <a href="https://devel.rtems.org/ticket/2348">https://devel.rtems.org/ticket/2348</a> )
<b>Id</b>	2348
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 May 2015 06:30:47
<b>Modified</b>	31 October 2023 11:45:12
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The FreeBSD timecounter implementation supports the NTP. This support is currently disabled in RTEMS.

### Comment 1

1. **Chris Johns**, Mon, 14 Aug 2017 00:08:25 GMT
2. **version: 4.11** deleted
3. **milestone**: changed from **5.0** to **Indefinite**

### Comment 2

1. **Chris Johns**, Wed, 27 Oct 2021 00:47:22 GMT

There needs to be an interface in the score to provide access to `ntp_update_second()`. The call may not be present in the kernel sources, it will mostly likely be provided by an application or an external library such as `libbsd.a`.

I suggest a file is added to the score that contains `ntp_update_second()` and that function checks a function pointer and if set the function is called. This brings `kern_tc.c` closer to upstream FreeBSD sources.

While on the topic of `kern_tc.c` and being as close to FB as we can, I think the RTEMS doxygen comments should be removed. We should maintain a common policy for imported sources like this.

### Comment 3

1. **Sebastian Huber**, Wed, 27 Oct 2021 05:37:47 GMT

Good timing, I recently updated `kern_tc.c` to the latest FreeBSD version:

<https://git.rtems.org/sebh/rtems.git/log/?h=timecounter-2021>

I just didn't send the patch set for review yet, since nobody commented on the new clock manager directives so far:

<https://lists.rtems.org/pipermail/devel/2021-October/069697.html>

The `kern_tc.c` is quite close to the original FreeBSD code and the Doxygen comment block on top of the file is not an issue.

In this patch set I removed the NTP code block since nobody was interested in NTP support in the last 6 years:

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=f85259b1edfff1d89c013c97510a9427825ea81b>

This enabled a performance optimization here:

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=04ed8d3c8cf88b7f1e3fb7ad78a91be1fefc396c>

The performance optimization is important for targets with slow 64-bit divisions (which are most RTEMS targets). If you want to add NTP support, then we have to restructure the FreeBSD code a bit. This can be integrated in FreeBSD. I can do this it just depends on how urgent it is.

In a first approach the proposed callback makes sense. If someone using lwIP needs NTP support, then we can add `kern_ntptime.c` to RTEMS.

### Comment 4

1. **Chris Johns**, Wed, 27 Oct 2021 06:33:28 GMT

Replying to Sebastian Huber:

Good timing, I recently updated `kern_tc.c` to the latest FreeBSD version:

It does seem so. :)

<https://git.rtems.org/sebh/rtems.git/log/?h=timecounter-2021>

I just didn't send the patch set for review yet, since nobody commented on the new clock manager directives so far:

I only suspected something was in the works because of the posts to FreeBSD hackers. It would be good to resolve the PTP support.

<https://lists.rtems.org/pipermail/devel/2021-October/069697.html>

I saw this but I did not look closely. I did not know it was a request for a new feature. I will add it to my list so sorry about that.

The kern\_tc.c is quite close to the original FreeBSD code and the Doxygen comment block on top of the file is not an issue.

Why the special exception here?

My focus for the leadership group, including you, is to set policies for this sort of thing and then having everyone accept and adhere to them. It is simpler and more democratic to do this. My concern is having a rule that creates an exceptions because it makes things complicated. I know this is a single file but there are other places where more code comes across and this is where things become confusing.

In this patch set I removed the NTP code block since nobody was interested in NTP support in the last 6 years:

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=f85259b1edfff1d89c013c97510a9427825ea81b>

It is needed. I have openly discuss this topic ...

<https://lists.rtems.org/pipermail/devel/2021-March/065608.html>

The PTP changes for RTEMS have only just been posted upstream ..

<https://github.com/ptpd/ptpd/pull/85>

Gabriel has done a fantastic job getting my hacks into a suitable state they would be pushed upstream.

This enabled a performance optimization here:

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=04ed8d3c8cf88b7f1e3fb7ad78a91be1f9c396c>

The performance optimization is important for targets with slow 64-bit divisions (which are most RTEMS targets). If you want to add NTP support, then we have to restructure the FreeBSD code a bit. This can be integrated in FreeBSD. I can do this it just depends on how urgent it is.

I have nothing to offer here and will happily be guided by you. I am sorry I have no time to spend looking at the detail.

In a first approach the proposed callback makes sense. If someone using lwIP needs NTP support, then we can add kern\_ntptime.c to RTEMS.

The support being added is LibBSD so I am not sure where kern\_ntptime.c is being added. Maybe Gabriel can be comment more on this.

#### **Comment 5**

1. **GabrielMoyano**, Wed, 27 Oct 2021 12:03:51 GMT

kern\_ntptime.c is ported from freebsd-org to freebsd in rtems-libbsd. The last commits of this branch <https://github.com/GabrielDai/rtems-libbsd/tree/ptpd> show the changes.

Regarding adding the function ntp\_update\_second() in score, do you know where the function pointer should be updated (to point to ntp\_update\_second() in kern\_ntptime.c)?

#### **Comment 6**

1. **Sebastian Huber**, Thu, 28 Oct 2021 05:25:49 GMT

Replying to Chris Johns:

Replying to Sebastian Huber:

The kern\_tc.c is quite close to the original FreeBSD code and the Doxygen comment block on top of the file is not an issue.

Why the special exception here?

My focus for the leadership group, including you, is to set policies for this sort of thing and then having everyone accept and adhere to them. It is simpler and more democratic to do this. My concern is having a rule that creates an exceptions because it makes things complicated. I know this is a single file but there are other places where more code comes across and this is where things become confusing.

There is not just one rule involved here. The timekeeping is an important service of an operating system. It should be visible in the internal documentation (Doxygen). The file history shows that there is no issue with keeping it in synchronization with FreeBSD.

#### **Comment 7**

1. **Sebastian Huber**, Thu, 28 Oct 2021 05:35:06 GMT

Replying to GabrielMoyano:

kern\_ntptime.c is ported from freebsd-org to freebsd in rtems-libbsd. The last commits of this branch <https://github.com/GabrielDai/rtems-libbsd/tree/ptpd> show the changes.

Regarding adding the function ntp\_update\_second() in score, do you know where the function pointer should be updated (to point to ntp\_update\_second() in kern\_ntptime.c)?



The callback for `ntp_update_second()` is currently not implemented. I would like to integrate my patch set which updates `kern_tc.c` to the latest FreeBSD version first. I would like to also try to rearrange the code a bit in the FreeBSD upstream. For `libbsd` my approach would be to add an internal API to `#include` which can be used to set the NTP callback in `kern_ntptime.c`.

### Comment 8

1. **Chris Johns**, Thu, 28 Oct 2021 07:47:23 GMT

Replying to Sebastian Huber:

Replying to Chris Johns:

Replying to Sebastian Huber:

The `kern_tc.c` is quite close to the original FreeBSD code and the Doxygen comment block on top of the file is not an issue.

Why the special exception here?

My focus for the leadership group, including you, is to set policies for this sort of thing and then having everyone accept and adhere to them. It is simpler and more democratic to do this. My concern is having a rule that creates an exceptions because it makes things complicated. I know this is a single file but there are other places where more code comes across and this is where things become confusing.

There is not just one rule involved here. The timekeeping is an important service of an operating system. It should be visible in the internal documentation (Doxygen). The file history shows that there is no issue with keeping it in synchronization with FreeBSD.

This is not about the history. The history of this file reflects the quality of the person currently doing the work and it is a very high standard. Expecting that standard everywhere is asking a lot. I think we need to document how we integrate external code and for that I was considering the following as the basis:

<https://git.rtems.org/rtems-libbsd/tree/CONTRIBUTING.md#n248>

I would be interested to understand how this score file or files like it could be handled by a rule or rules? A rule in the ticket may not be clean and suitable documentation however it provides me with a means to show what we consider as OK if you could provide this.

### Comment 9

1. **Sebastian Huber**, Thu, 28 Oct 2021 09:17:20 GMT

Replying to Chris Johns:

Replying to Sebastian Huber:

Replying to Chris Johns:

Replying to Sebastian Huber:

The `kern_tc.c` is quite close to the original FreeBSD code and the Doxygen comment block on top of the file is not an issue.

Why the special exception here?

My focus for the leadership group, including you, is to set policies for this sort of thing and then having everyone accept and adhere to them. It is simpler and more democratic to do this. My concern is having a rule that creates an exceptions because it makes things complicated. I know this is a single file but there are other places where more code comes across and this is where things become confusing.

There is not just one rule involved here. The timekeeping is an important service of an operating system. It should be visible in the internal documentation (Doxygen). The file history shows that there is no issue with keeping it in synchronization with FreeBSD.

This is not about the history. The history of this file reflects the quality of the person currently doing the work and it is a very high standard. Expecting that standard everywhere is asking a lot. I think we need to document how we integrate external code and for that I was considering the following as the basis:

<https://git.rtems.org/rtems-libbsd/tree/CONTRIBUTING.md#n248>

I would be interested to understand how this score file or files like it could be handled by a rule or rules? A rule in the ticket may not be clean and suitable documentation however it provides me with a means to show what we consider as OK if you could provide this.

The `libbsd` contributing rules make sense for `libbsd` which deals with a couple of hundred files and a semi-automatic synchronization support.

External files placed in the score should integrate into the score documentation and be maintainable. Here we need a bit more flexibility.

### Comment 10

1. **Sebastian Huber**, Thu, 28 Oct 2021 09:33:48 GMT

I updated the timecounter update branch to include support for an NTP update second handler:

<https://git.rtems.org/sebh/rtems.git/log/?h=timecounter-2021>

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=817437b6dda00764f368b2da9eeab67ec284a3bd>

I wait for some feedback on the FreeBSD mailing list before I send the patch set for review.

### Comment 11

1. **GabrielMoyano**, Thu, 28 Oct 2021 11:29:14 GMT

Replying to Sebastian Huber:

<file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html>

I updated the timecounter update branch to include support for an NTP update second handler:

<https://git.rtems.org/sebh/rtems.git/log/?h=timecounter-2021>

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=817437b6dda00764f368b2da9eeab67ec284a3bd>

This looks nice, thx. Now, I guess that one option is to call `_Timecounter_Set_NTP_update_second()` just before starting `ptpd`

I wait for some feedback on the FreeBSD mailing list before I send the patch set for review.

ok

### **Comment 12**

1. **Chris Johns**, Thu, 28 Oct 2021 22:57:18 GMT

Replying to Sebastian Huber:

Replying to Chris Johns:

Replying to Sebastian Huber:

Replying to Chris Johns:

Replying to Sebastian Huber:

The kern\_tc.c is quite close to the original FreeBSD code and the Doxygen comment block on top of the file is not an issue.

Why the special exception here?

My focus for the leadership group, including you, is to set policies for this sort of thing and then having everyone accept and adhere to them. It is simpler and more democratic to do this. My concern is having a rule that creates an exceptions because it makes things complicated. I know this is a single file but there are other places where more code comes across and this is where things become confusing.

There is not just one rule involved here. The timekeeping is an important service of an operating system. It should be visible in the internal documentation (Doxygen). The file history shows that there is no issue with keeping it in synchronization with FreeBSD.

This is not about the history. The history of this file reflects the quality of the person currently doing the work and it is a very high standard. Expecting that standard everywhere is asking a lot. I think we need to document how we integrate external code and for that I was considering the following as the basis:

<https://git.rtems.org/rtems-libbsd/tree/CONTRIBUTING.md#n248>

I would be interested to understand how this score file or files like it could be handled by a rule or rules? A rule in the ticket may not be clean and suitable documentation however it provides me with a means to show what we consider as OK if you could provide this.

The libbsd contributing rules make sense for libbsd which deals with a couple of hundred files and a semi-automatic synchronization support.

External files placed in the score should integrate into the score documentation and be maintainable. Here we need a bit more flexibility.

This makes sense. Should the documentation should be limited to a single block at the start of the file and else where in the file the LibBSD rules apply?

### **Comment 13**

1. **Sebastian Huber**, Mon, 15 Nov 2021 08:16:56 GMT

In `ffb8833d/rtems`:

```
score: Add _Timecounter_Set_NTP_update_second()
```

```
Allow the installation of an NTP update second handler which may be used by an NTP service.
```

```
Update #2348.
```

### **Comment 14**

1. **Sebastian Huber**, Mon, 15 Nov 2021 08:19:27 GMT

Replying to GabrielMoyano:

Replying to Sebastian Huber:

I updated the timecounter update branch to include support for an NTP update second handler:

<https://git.rtems.org/sebh/rtems.git/log/?h=timecounter-2021>

<https://git.rtems.org/sebh/rtems.git/commit/?h=timecounter-2021&id=817437b6dda00764f368b2da9eeab67ec284a3bd>

This looks nice, thx. Now, I guess that one option is to call `_Timecounter_Set_NTP_update_second()` just before starting `ptpd`

I wait for some feedback on the FreeBSD mailing list before I send the patch set for review.

ok

I checked in the patch set. The `kern_tc.c` is now fully synchronized with the latest FreeBSD version. You can now install an NTP update second handler via `_Timecounter_Set_NTP_update_second()` from `#include` .

#### Comment 15

1. **GabrielMoyano**, Mon, 15 Nov 2021 10:56:37 GMT

I checked in the patch set. The `kern_tc.c` is now fully synchronized with the latest FreeBSD version. You can now install an NTP update second handler via `_Timecounter_Set_NTP_update_second()` from `#include` .

Thank you very much Sebastian. Are the changes portable to the branch 5? Our development is based on that branch and it will be very nice to have them there too

#### Comment 16

1. **Sebastian Huber**, Mon, 15 Nov 2021 11:25:13 GMT

2. **version**: set to **4.11**

3. **milestone**: changed from **Indefinite** to **6.1**

#### Comment 17

1. **Sebastian Huber**, Mon, 15 Nov 2021 11:27:10 GMT

Replying to GabrielMoyano:

I checked in the patch set. The `kern_tc.c` is now fully synchronized with the latest FreeBSD version. You can now install an NTP update second handler via `_Timecounter_Set_NTP_update_second()` from `#include` .

Thank you very much Sebastian. Are the changes portable to the branch 5? Our development is based on that branch and it will be very nice to have them there too

I think the patch set is back portable to RTEMS 5 without breaking the ABI/API. Just clone this ticket and set the mile stone to 5.2. Then try to back port all the changes or a subset and send it for review. I have no time to work on it.

#### Comment 18

1. **GabrielMoyano**, Mon, 15 Nov 2021 11:40:42 GMT

I think the patch set is back portable to RTEMS 5 without breaking the ABI/API. Just clone this ticket and set the mile stone to 5.2. Then try to back port all the changes or a subset and send it for review. I have no time to work on it.

Thx. I'll do so. Here the ticket <https://devel.rtems.org/ticket/4549#ticket>

#### Comment 19

1. **Joel Sherrill**, Fri, 17 Dec 2021 17:02:43 GMT

Is this ticket ready to close?

#### Comment 20

1. **Sebastian Huber**, Mon, 21 Feb 2022 13:15:10 GMT

In 91057b3/rtems:

```
kern_ntptime.c: Import from FreeBSD
```

The file was imported from this repository:

<https://github.com/freebsd/freebsd.git>

This commit was used:

```
commit 3ec0dc367bff27c345ad83240625b2057af391b9 Author: Sebastian Huber Date: Mon Feb 7 14:16:16 2022 -0700
```

```
kern_ntptime.c: Remove ntp_init()
```

The `ntp_init()` function did set a couple of global objects to zero. These objects are in the `.bss` section and already initialized to zero during kernel or module loading.

Update #2348.

#### **Comment 21**

1. **Sebastian Huber**, Mon, 21 Feb 2022 13:15:14 GMT

In 8f1e8f8f/rtems:

```
kern_ntptime.c: Port to RTEMS
```

```
Remove previous adjtime() implementation.
```

Update #2348.

#### **Comment 22**

1. **Sebastian Huber**, Tue, 07 Jun 2022 06:54:14 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

#### **Comment 23**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:45:12 GMT
2. **keywords**: **qualification** added

## **2349 - Timecounter: Add PPS support**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2349">https://devel.rtems.org/ticket/2349</a> ( <a href="https://devel.rtems.org/ticket/2349">https://devel.rtems.org/ticket/2349</a> )
<b>Id</b>	2349
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 May 2015 06:33:02
<b>Modified</b>	31 October 2023 11:45:33
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

The FreeBSD timecounter implementation supports the RFC 2783 PPS-API. This support is currently disabled in RTEMS.

#### **Comment 1**

1. **Chris Johns**, Mon, 14 Aug 2017 00:08:39 GMT
2. **version**: **4.11** deleted
3. **milestone**: changed from **5.0** to **Indefinite**

#### **Comment 2**

1. **Sebastian Huber**, Mon, 23 May 2022 07:02:19 GMT
2. **milestone**: changed from **Indefinite** to **6.1**

#### **Comment 3**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:29 GMT

In 9b4212c7/rtems:

```
kern_ntptime.c: Disable freebsd features  
Update #2349.
```

#### **Comment 4**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:31 GMT

In a3930e8c/rtems:

```
kern_ntptime.c: Add lmax() qmin() definitions  
Update #2349.
```

#### **Comment 5**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:34 GMT

In bf61753a/rtems:

```
kern_tc.c: Add atomic dependencies required by the PPS API  
Update #2349.
```

#### **Comment 6**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:36 GMT

In 95c747d9/rtems:

```
kern_tc.c: Replace FreeBSD event mechanism by adding pointers to function  
Update #2349.
```

#### **Comment 7**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:39 GMT

In ac4ea53/rtems:

```
score: Rename tc_getfrequency()  
Rename tc_getfrequency() to _Timecounter_Get_frequency().  
Update #2349.
```

#### **Comment 8**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:41 GMT

In c34d3ae/rtems:

```
kern_tc.c: Add definitions required by PPS API  
Update #2349.
```

#### **Comment 9**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:43 GMT

In 13513b81/rtems:

```
kern_tc.c: Enable PPS API support  
Update #2349.
```

#### **Comment 10**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:45 GMT

In b304603b/rtems:

```
kern_ntptime.c: Add define in order to remove warning
Update #2349.
```

#### **Comment 11**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:48 GMT

In b3e4f58/rtems:

```
timepps.h: PPS_SYNC defined by default
Update #2349.
```

#### **Comment 12**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:50 GMT

In 5ccf960/rtems:

```
timecounter.h: Add _Timecounter_Discipline()
Update #2349.
```

#### **Comment 13**

1. **Gabriel Moyano**, Mon, 23 May 2022 07:04:52 GMT

In 6553bf4/rtems:

```
testsuites/sptestests: Add sppps01 test
Update #2349.
```

#### **Comment 14**

1. **Sebastian Huber**, Mon, 23 May 2022 07:04:54 GMT
2. **owner:** set to **Sebastian Huber <sebastian.huber@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 495f836/rtems:

```
score: Reformat for code coverage
Close #2349.
```

#### **Comment 15**

1. **Sebastian Huber**, Fri, 27 May 2022 09:25:53 GMT

In 044e8b6/rtems:

```
score: Fix pps_fetch()
Return early only if there was a timeout, otherwise return the PPS info.
Update #2349.
```

#### **Comment 16**

1. **Gabriel Moyano**, Fri, 27 May 2022 11:37:42 GMT

In 34ba0e5a/rtems:

```
sppps01: Improve default handler test
Update #2349.
```

#### **Comment 17**

1. **Gabriel Moyano**, Fri, 10 Jun 2022 09:06:14 GMT

In 11621c9c/rtems:

kern\_tc.c: Update pps\_event() for uniprocessor configurations

Since pps->capgen equal to zero is not a special value in uniprocessor configurations, there is no need to check for this condition.

Update #2349

#### **Comment 18**

1. **Sebastian Huber**, Thu, 23 Jun 2022 07:42:35 GMT

In 94df3a7a/rtems:

kern\_tc.c: Provide a weak hardpps() implementation

The real implementation of hardpps() is defined in kern\_ntptime.c. Use it only if the NTP support is needed by the application.

Update #2349.

#### **Comment 19**

1. **Gabriel Moyano**, Tue, 05 Jul 2022 13:10:33 GMT

In eefaf068/rtems:

sppps01: Add test case for early returns of pps\_event()

Update #2349.

#### **Comment 20**

1. **Sebastian Huber**, Wed, 13 Jul 2022 13:58:58 GMT

In 013e028/rtems:

sppps01: Fix test in SMP configurations

Update #2349.

#### **Comment 21**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:45:33 GMT
2. **keywords: qualification** added

## **2365 - Task pre-emption disable is broken due to pseudo ISR tasks**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2365">https://devel.rtems.org/ticket/2365</a> ( <a href="https://devel.rtems.org/ticket/2365">https://devel.rtems.org/ticket/2365</a> )
<b>Id</b>	2365
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 June 2015 13:18:57
<b>Modified</b>	26 July 2022 09:25:19
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.10
<b>Milestone</b>	6.1
<b>Priority</b>	lowest
<b>Severity</b>	critical
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

We have for example:

```

Scheduler_Void_or_thread_Scheduler_priority_Unblock (
const Scheduler_Control *scheduler,
Thread_Control *the_thread
)
{
Scheduler_priority_Context *context =
Scheduler_priority_Get_context( scheduler );
Scheduler_priority_Node *node = Scheduler_priority_Thread_get_node( the_thread );
Scheduler_priority_Ready_queue_enqueue(
&the_thread->Object.Node,
&node->Ready_queue,
&context->Bit_map
);
/* TODO: flash critical section? */
/*
* If the thread that was unblocked is more important than the heir,
* then we have a new heir. This may or may not result in a
* context switch.
*
* Normal case:
* If the current thread is preemptible, then we need to do
* a context switch.
* Pseudo-ISR case:
* Even if the thread isn't preemptible, if the new heir is
* a pseudo-ISR system task, we need to do a context switch.
*/
if ( the_thread->current_priority < _Thread_Heir->current_priority ) {
Scheduler_Update_heir(
the_thread,
the_thread->current_priority == PRIORITY_PSEUDO_ISR
);
}
SCHEDULER_RETURN_VOID_OR_NULL;
}

```

So the unblock event of a pseudo ISR task (MPCI or timer server) may pre-empt a task with disabled pre-emption. Suppose a higher priority task than the non-preemptible task is ready. Then this task gets scheduled once the pseudo ISR task blocks again.

### Comment 1

1. **Sebastian Huber**, Fri, 12 Jun 2015 12:00:01 GMT

In 0562060f074eea3fdcf5274aa3b7cbc8fe14993d/rtems:

```

sptestests/sptasknopreempt01: New test
Update #2365.

```

### Comment 2

1. **Sebastian Huber**, Fri, 12 Jun 2015 12:12:15 GMT
2. **description**: modified (diff)

### Comment 3

1. **Sebastian Huber**, Thu, 26 Jan 2017 07:16:00 GMT
2. **milestone**: changed from **4.11.1** to **4.11.2**

### Comment 4

1. **Sebastian Huber**, Wed, 15 Feb 2017 13:44:44 GMT
2. **owner**: set to **Needs Funding**
3. **status**: changed from **new** to **assigned**
4. **milestone**: changed from **4.11.2** to **Indefinite**

### Comment 5

1. **Sebastian Huber**, Fri, 15 Jul 2022 08:39:46 GMT
2. **owner**: changed from **Needs Funding** to **Sebastian Huber**
3. **status**: changed from **assigned** to **accepted**
4. **milestone**: changed from **Indefinite** to **6.1**

### Comment 6

1. **Sebastian Huber**, Tue, 26 Jul 2022 09:18:04 GMT

In f1eb94b/rtems-docs:

```

c-user: Do not mention pseudo-interrupt priority
Update #2365.

```

### Comment 7



1. **Sebastian Huber**, Tue, 26 Jul 2022 09:23:16 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In 7fe6d60/rtems:

```
score: Remove PRIORITY_PSEUDO_ISR thread priority
```

The uniprocessor schedulers had some special case logic for the PRIORITY\_PSEUDO\_ISR priority. Tasks with a priority of PRIORITY\_PSEUDO\_ISR were allowed to preempt a not preemptible task. If other higher priority task are made ready while a PRIORITY\_PSEUDO\_ISR task preempts a not preemptible task, then the other tasks run before the not preemptible task. This made the RTEMS\_NO\_PREEMPT mode ineffective.

Remove the PRIORITY\_PSEUDO\_ISR special case logic. This simplifies the uniprocessor schedulers. Move the uniprocessor-specific scheduler support to the new header file .

Close #2365.

#### Comment 8

1. **Sebastian Huber**, Tue, 26 Jul 2022 09:25:19 GMT
2. **keywords**: **qualification** added

## 2778 - Error building RTEMS Source Builder recipe for libxml

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2778">https://devel.rtems.org/ticket/2778</a> ( <a href="https://devel.rtems.org/ticket/2778">https://devel.rtems.org/ticket/2778</a> )
<b>Id</b>	2778
<b>Reporter</b>	Sambeet Panigrahi
<b>Created</b>	18 August 2016 06:48:24
<b>Modified</b>	29 November 2022 21:50:55
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	worksforme
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	RTEMS Source Builder, libxml
<b>Cc</b>	Sambeet Panigrahi
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

I wrote the three essential files for cross build of libxml for RTEMS, i.e. the .bset file (libxml.bset), the version specific configuration file (libxml2-2.7.8.cfg) and the build configuration file (libxml2-2.7.8.cfg). As per the FreeBSD ports I have placed it under textproc. However when the build configuration script is run, an error "config file is not found" occurs. I tried to cd into the directory by providing a bash script but that is also not working, an error "can't cd to .." appears.

#### Attachments:

1. **Sambeet Panigrahi**, Thu, 18 Aug 2016 06:53:05 GMT  
**attach**: set to [libxml2-2.7.8.cfg](https://devel.rtems.org/ticket/2778/libxml2-2.7.8.cfg) (<https://devel.rtems.org/ticket/2778/libxml2-2.7.8.cfg>)
2. **Sambeet Panigrahi**, Sat, 20 Aug 2016 07:55:37 GMT  
**attach**: set to [0001-Adding-libxml-package.patch](https://devel.rtems.org/ticket/2778/0001-Adding-libxml-package.patch) (<https://devel.rtems.org/ticket/2778/0001-Adding-libxml-package.patch>)
3. **Sambeet Panigrahi**, Sat, 20 Aug 2016 07:56:23 GMT  
**attach**: set to [0002-Changes-for-libxml.bset.patch](https://devel.rtems.org/ticket/2778/0002-Changes-for-libxml.bset.patch) (<https://devel.rtems.org/ticket/2778/0002-Changes-for-libxml.bset.patch>)
4. **Sambeet Panigrahi**, Sat, 20 Aug 2016 07:57:31 GMT  
**attach**: set to [0003-changes-to-resolve-config-file-not-found-error.patch](https://devel.rtems.org/ticket/2778/0003-changes-to-resolve-config-file-not-found-error.patch) (<https://devel.rtems.org/ticket/2778/0003-changes-to-resolve-config-file-not-found-error.patch>)
5. **Sambeet Panigrahi**, Sat, 20 Aug 2016 07:58:36 GMT  
**attach**: set to [0004-Added-the-.cfg-file.patch](https://devel.rtems.org/ticket/2778/0004-Added-the-.cfg-file.patch) (<https://devel.rtems.org/ticket/2778/0004-Added-the-.cfg-file.patch>)
6. **Sambeet Panigrahi**, Sat, 20 Aug 2016 08:04:44 GMT  
**attach**: set to [rsb-report-libxml2-2.7.8-2.txt](https://devel.rtems.org/ticket/2778/rsb-report-libxml2-2.7.8-2.txt) (<https://devel.rtems.org/ticket/2778/rsb-report-libxml2-2.7.8-2.txt>)

#### Comment 1

1. **Sambeet Panigrahi**, Sat, 20 Aug 2016 08:12:31 GMT
2. **owner**: changed from **Gedare Bloom** to **Chris Johns**
3. **status**: changed from **new** to **assigned**
4. **version**: changed from **4.11** to **4.12**

5. **milestone:** changed from **4.11.1** to **4.12**

There are a few more attachments for clarity. I have added the patches for the build set to reproduce my problem and a copy of the error report when I give the command

```
sambeet@Holmes ~/Documents/GitRepos?/sambeet161616/rtems-source-builder/rtems $ ../source-builder/sb-set-builder --log=log_libxml_log --
prefix=$HOME/NewRockPort/x86/Install/rtems/4.11.0-rc3/ --target=i386-rtems4.11 --with-rtems-bsp=pc486 textproc/libxml
```

#### Comment 2

1. **Sebastian Huber**, Thu, 11 May 2017 07:31:02 GMT
2. **milestone:** changed from **4.12** to **4.12.0**

#### Comment 3

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:27:14 GMT
2. **milestone:** changed from **4.12.0** to **5.1**

Milestone renamed

#### Comment 4

1. **Joel Sherrill**, Sun, 14 Oct 2018 00:43:39 GMT
2. **version:** changed from **5** to **6**
3. **milestone:** changed from **5.1** to **6.1**

Pushing milestone but would prefer if someone could look into this and fix it.

#### Comment 5

1. **Chris Johns**, Tue, 29 Nov 2022 21:50:55 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **worksforme**

If this is still broken please reopen.

## 2828 - Remove libmisc/serdbg

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2828">https://devel.rtems.org/ticket/2828</a> ( <a href="https://devel.rtems.org/ticket/2828">https://devel.rtems.org/ticket/2828</a> )
<b>Id</b>	2828
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 November 2016 21:45:43
<b>Modified</b>	10 February 2023 13:38:24
<b>Owner</b>	Needs Funding
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	thomas.doerfler Sebastian Huber
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

This is old code which should be replaced by the new debug server. Any hints or reusable in this for termios/serial port support can be retrieved from an old branch.

#### Comment 1

1. **Sebastian Huber**, Wed, 15 Feb 2017 14:20:42 GMT
2. **owner:** set to **Needs Funding**
3. **status:** changed from **new** to **assigned**
4. **milestone:** changed from **4.12** to **Indefinite**

#### Comment 2

1. **Joel Sherrill**, Tue, 10 Jan 2023 15:04:57 GMT
2. **cc:** **thomas.doerfler Sebastian Huber** added

3. **version:** changed from **5** to **6**
4. **component:** changed from **score** to **lib**
5. **milestone:** changed from **Indefinite** to **6.1**

This ticket is simple to implement but another person needs to confirm that it is time to remove the libmisc/serdbg code (<https://git.rtems.org/rtems/tree/cpukit/libmisc/serdbg>)

### Comment 3

1. **Joel Sherrill**, Fri, 10 Feb 2023 13:38:24 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 77e7bd9/rtems:

```
libmisc/serdbg: Remove obsolete serial debug
```

```
Closes #2828.
```

## 2869 - Remove support for 16-bit object identifiers

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2869">https://devel.rtems.org/ticket/2869</a> ( <a href="https://devel.rtems.org/ticket/2869">https://devel.rtems.org/ticket/2869</a> )
<b>Id</b>	2869
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	17 January 2017 13:04:40
<b>Modified</b>	26 January 2022 13:49:37
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The only target using 16-bit object identifiers is M32C. This optimization is not worth the trouble. Self-contained objects are much more attractive for low end systems.

### Comment 1

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

### Comment 2

1. **Joel Sherrill**, Fri, 17 Dec 2021 16:56:58 GMT

This has been implemented. Closing.

### Comment 3

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:49:37 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

## 2871 - Use bibtex references throughout the documentation

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2871">https://devel.rtems.org/ticket/2871</a> ( <a href="https://devel.rtems.org/ticket/2871">https://devel.rtems.org/ticket/2871</a> )
<b>Id</b>	2871
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	18 January 2017 10:25:55
<b>Modified</b>	25 October 2022 22:22:37
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description****Comment 1**

1. **Sebastian Huber**, Tue, 10 Oct 2017 06:06:29 GMT
2. **component**: changed from **Documentation** to **doc**

**Comment 2**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

**Comment 3**

1. **Joel Sherrill**, Fri, 17 Dec 2021 17:00:38 GMT

Has this been done? We don't have that may references.

**Comment 4**

1. **Joel Sherrill**, Tue, 25 Oct 2022 22:22:37 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

Classic API Guide has a generated references section now

---

**2872 - Get rid of CONFIGURE\_MAXIMUM\_PTYS**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2872">https://devel.rtems.org/ticket/2872</a> ( <a href="https://devel.rtems.org/ticket/2872">https://devel.rtems.org/ticket/2872</a> )
<b>Id</b>	2872
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 January 2017 12:07:26
<b>Modified</b>	17 December 2021 16:57:43
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Change the Termios PTY driver for Telnet to use the new Termios device API. This why the CONFIGURE\_MAXIMUM\_PTYS gets superfluous.

**Comment 1**

1. **Chris Johns**, Thu, 19 Jan 2017 22:45:33 GMT

Should the pty support the separated to allow reuse?

I am porting tinyssh can could use it.

### **Comment 2**

1. **Sebastian Huber**, Fri, 20 Jan 2017 09:21:40 GMT

The current PTY driver is a collection of hacks. It would be certainly good to overhaul it and make it generally useful.

### **Comment 3**

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone**: changed from **5.0** to **6.1**

Milestone renamed

### **Comment 4**

1. **Joel Sherrill**, Fri, 17 Dec 2021 16:57:43 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

This has been implemented.

## **2902 - Port RTEMS to Microblaze**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2902">https://devel.rtems.org/ticket/2902</a> ( <a href="https://devel.rtems.org/ticket/2902">https://devel.rtems.org/ticket/2902</a> )
<b>Id</b>	2902
<b>Reporter</b>	Tanu Hari Dixit
<b>Created</b>	6 February 2017 02:59:16
<b>Modified</b>	11 November 2021 17:54:41
<b>Owner</b>	Joel Sherrill
<b>Type</b>	project
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SoC, BSP
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

Port RTEMS to Microblaze

\_\_Students\_\_: Past, Present, and Potential Students

\_\_Status\_\_: The tools build from RSB properly, but GDB is not compatible with current XDM (Xilinx Debugging Module), Xilinx GDB version is working fine.

\_\_Introduction\_\_: A new architecture port, not just BSP. Include a BSP for GDB simulator. Also needs BSP for more complete HW on simulator.

\_\_Goal\_\_: Update the preliminary Microblaze port, complete clock timer support, merge into RTEMS, and continue to improve the BSP/port.

Some work has been initiated here [1] (By Joel Sherrill and Hesham ALMatary) to get hello world working. It has been tested on Atlys FPGA board [2]. The BSP can run virtually on every FPGA board the Xilinx tools support building MicroBlaze? on.

The work will need to be updated against the current RTEMS version and tools and then completed. There are multiple boards supported by qemu-system-microblaze. One of these should be suitable for completing the port including interrupts. It will require investigation to know if qemu includes networking support for the Microblaze but this is likely.

### **References**

- [1] <https://github.com/heshamelmatary/rtems-microblaze>
- [2] [www.digilentinc.com/atlys/](http://www.digilentinc.com/atlys/)

### **Comment 1**

1. **Chris Johns**, Mon, 06 Feb 2017 04:02:32 GMT
2. **type**: changed from **enhancement** to **project**

### **Comment 2**

1. **Gedare Bloom**, Thu, 02 Mar 2017 20:45:40 GMT
2. **keywords**: **BSP** added

**Comment 3**

1. **Chris Johns**, Mon, 14 Aug 2017 00:04:23 GMT
2. **version: 4.11** deleted

**Comment 4**

1. **Gedare Bloom**, Tue, 14 Jan 2020 20:53:20 GMT
2. **description:** modified (diff)

**Comment 5**

1. **Joel Sherrill**, Fri, 29 May 2020 12:58:33 GMT
2. **description:** modified (diff)

**Comment 6**

1. **Joel Sherrill**, Thu, 11 Nov 2021 17:54:41 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**
4. **milestone:** changed from **Indefinite** to **6.1**

A Microblaze port and BSP for the KCU105 (HW and Qemu) have been merged. LWIP and libbsd should be supported soon. Closing.

---

**2971 - Add fenv.h to newlib**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2971">https://devel.rtems.org/ticket/2971</a> ( <a href="https://devel.rtems.org/ticket/2971">https://devel.rtems.org/ticket/2971</a> )
<b>Id</b>	2971
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	3 April 2017 23:54:19
<b>Modified</b>	3 December 2021 20:16:07
<b>Owner</b>	Needs Funding
<b>Type</b>	defect
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	POSIX-Compliance
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

fenv.h is not present.

- <http://pubs.opengroup.org/onlinepubs/9699919799/>
- feclreaxcept, fegetenv, fegetexceptflag, fegetround, feholdexcept, feraiseexcept, fesetenv, fesetexceptflag, fesetround, fetestexcept, feupdateenv
- Cygwin has x86 implementation. FreeBSD should be source for ARM and some other architectures. The implementation is architecture specific.

When completed, see psxtests/Makefile.am and enable the fenv.h POSIX API Compliance Tests.

**Comment 1**

1. **Joel Sherrill**, Mon, 03 Apr 2017 23:54:51 GMT
2. **keywords: POSIX-Compliance** added

**Comment 2**

1. **Joel Sherrill**, Fri, 16 Mar 2018 18:37:28 GMT
2. **summary:** changed from **Add fenv,h to newlib** to **Add fenv.h to newlib**

**Comment 3**

1. **Joel Sherrill**, Thu, 06 Dec 2018 15:34:17 GMT
2. **owner:** set to **Needs Funding**
3. **status:** changed from **new** to **assigned**
4. **version: 5** deleted

5. **description:** modified (diff)**Comment 4**1. **ABR290B**, Thu, 06 Dec 2018 15:34:31 GMT

In da262164/rtems:

```

POSIX Signature Test for fenv.h (GCI 2018)
Updates #2971.

```

**Comment 5**1. **Eshan dhawan**, Sat, 06 Jun 2020 20:36:54 GMT

In e845873/rtems:

```

tests for fenv.h functions
added tests for fesetexceptflag(), fegetexceptflag(), fegetround(), fesetround().
In the test fegetround() does not return any flag other than FE_TONEAREST in tests. This is probably due to soft float.
The test complies successfully and returns assert at fegetround()
Other tests run without any errors tested on RISCV/rv32imac
The test prints nothing if runs successfully.
updates #2971
Signed-off-by: Eshan dhawan

```

**Comment 6**1. **Joel Sherrill**, Fri, 03 Dec 2021 20:16:07 GMT2. **status:** changed from **assigned** to **closed**3. **resolution:** set to **fixed**4. **milestone:** changed from **Indefinite** to **6.1**

fenv.h has been added to newlib for many architectures.

**2985 - Add documentation for printk()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/2985">https://devel.rtems.org/ticket/2985</a> ( <a href="https://devel.rtems.org/ticket/2985">https://devel.rtems.org/ticket/2985</a> )
<b>Id</b>	2985
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 April 2017 15:11:16
<b>Modified</b>	12 August 2021 12:30:29
<b>Owner</b>	chrisj@...
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

printk() and its variants should be documented in the Classic API User's Guide. I am not sure where though.

**Comment 1**1. **Sebastian Huber**, Thu, 11 May 2017 07:31:02 GMT2. **milestone:** changed from **4.12** to **4.12.0****Comment 2**1. **Sebastian Huber**, Thu, 08 Jun 2017 07:50:04 GMT2. **milestone:** changed from **4.12.0** to **Indefinite**

**Comment 3**

1. **Sebastian Huber**, Tue, 10 Oct 2017 06:06:29 GMT
2. **component**: changed from **Documentation** to **doc**

**Comment 4**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords**: **qualification** added

**Comment 5**

1. **Sebastian Huber**, Thu, 12 Aug 2021 12:30:29 GMT
2. **status**: changed from **new** to **closed**
3. **type**: changed from **defect** to **enhancement**
4. **resolution**: set to **fixed**
5. **milestone**: changed from **Indefinite** to **6.1**

This was fixed by #4482.

**3143 - Remove obsolete rtems\_gxx\_&#42() implementation**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3143">https://devel.rtems.org/ticket/3143</a> ( <a href="https://devel.rtems.org/ticket/3143">https://devel.rtems.org/ticket/3143</a> )
<b>Id</b>	3143
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 September 2017 11:35:01
<b>Modified</b>	27 January 2022 13:10:49
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3599, 3602

**Description**

GCC versions prior to 6.1 used a RTEMS thread model based on `rtems_gxx_*` functions. GCC version 6.1 or later uses the self-contained synchronization objects of Newlib for the RTEMS thread model.

Remove the obsolete implementation.

**Comment 1**

1. **Sebastian Huber**, Tue, 19 Sep 2017 11:40:43 GMT
2. **status**: changed from **assigned** to **accepted**

**Comment 2**

1. **Joel Sherrill**, Tue, 19 Sep 2017 12:01:26 GMT

Are all the tool targets now using a sufficiently new GCC to remove this?

**Comment 3**

1. **Sebastian Huber**, Tue, 19 Sep 2017 12:05:58 GMT
2. **milestone**: changed from **4.12.0** to **Indefinite**

Oh no, some targets still use GCC 4.8...

**Comment 4**

1. **Sebastian Huber**, Mon, 12 Nov 2018 06:44:18 GMT
2. **blockedby**: set to **3599**
3. **milestone**: changed from **Indefinite** to **5.1**



The removal of the m32c port removed the dependency on GCC 4.8.

#### Comment 5

1. **Sebastian Huber**, Mon, 12 Nov 2018 06:46:03 GMT
2. **blockedby**: changed from **3599** to **3599, 3602**

An update of the or1k tools will remove the dependency on GCC 4.9.

#### Comment 6

1. **Sebastian Huber**, Wed, 21 Nov 2018 07:12:33 GMT
2. **version**: changed from **5** to **6**
3. **milestone**: changed from **5.1** to **6.1**

Move milestone to allow RTEMS 5 builds with older GCCs.

#### Comment 7

1. **Sebastian Huber**, Thu, 27 Jan 2022 13:10:49 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In 2145e0c7/rtems:

Remove obsolete `rtems_gxx_*` implementation

GCC versions prior to 6.1 used a RTEMS thread model based on `rtems_gxx_*` functions. GCC version 6.1 or later uses the self-contained synchronization objects of Newlib for the RTEMS thread model.

Remove the obsolete implementation.

Close #3143.

## 3199 - New test framework

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3199">https://devel.rtems.org/ticket/3199</a> ( <a href="https://devel.rtems.org/ticket/3199">https://devel.rtems.org/ticket/3199</a> )
<b>Id</b>	3199
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 October 2017 10:12:46
<b>Modified</b>	29 September 2021 13:25:31
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3716
<b>Blocked by</b>	

#### Description

Requirements:

- Support for RTEMS and general POSIX systems such as Linux or FreeBSD
- Test output functions
  - `printf()` like
  - No floating point support by default
  - Optional floating point support
  - Non-blocking
  - Arbitrary context, e.g. during system start, before device drivers, in interrupt context
- Automatic test case registrations (constructors, linker set)
- Standard test case output, e.g. begin/end of test case message
- Ability to sort test cases at run-time
- Safe assert functions, e.g. `assert(a == b)` vs. `assert(a = b)` vs. `assert_eq(a, b)`
- Easy to write, e.g. avoid long namespace prefix `rtems_test_*`
- Support multiple threads
- No dependency on C++
- Context validation, context invariant validation (e.g. thread dispatch disable level, interrupt state, heap state)
- Test pattern support (e.g. spintercritical\*, parallel tests on SMP)

No ready to use framework exists which fulfils these requirements. We have to write something for RTEMS.

API proposal (header file):

```
T_eq(a, b)
T_gt(a, b)
T_printf(fmt, ...)
T_output_printf(putchar, fmt, ...)
T_output_string(putchar, s, n)
T_output_add_format_handler(handler, arg)
```

Example for T\_output\_add\_format():

```
#include
#include
typedef void (*T_putchar)(char c);
typedef size_t (*T_format_handler)(void *arg, T_putchar putchar, const char *fmt, const char *s, int *out);
int T_printf(const char *fmt, ...);
void T_output_printf(T_putchar putchar, const char *fmt, ...);
void T_output_string(T_putchar putchar, const char *s, size_t n);
void T_output_add_format_handler(T_format_handler handler, void *arg);
size_t T_output_float_handler(void *arg, T_putchar putchar, const char *fmt, const char *s, int *out)
{
    char buf[32];
    if (strncmp(fmt, "%f", 2) != 0) {
        return 0;
    }
    *out = snprintf(buf, sizeof(buf), "%f", s);
    if (*out > 0) {
        T_output_string(putchar, s, (size_t) *out);
    }
    return 2;
}
void f(void)
{
    T_output_add_format_handler(T_output_float_handler, NULL);
}
```

#### Attachments:

- 
- Sebastian Huber, Fri, 23 Nov 2018 10:26:10 GMT**  
attach: set to [t.tar.gz \(https://devel.rtems.org/ticket/3199/t.tar.gz\)](https://devel.rtems.org/ticket/3199/t.tar.gz)
  - Sebastian Huber, Thu, 06 Dec 2018 14:47:59 GMT**  
attach: set to [contributor.pdf \(https://devel.rtems.org/ticket/3199/contributor.pdf\)](https://devel.rtems.org/ticket/3199/contributor.pdf)
- 

#### Comment 1

- Chris Johns, Thu, 19 Oct 2017 20:44:08 GMT**

Have you seen TAP?

<http://testanything.org/> <http://testanything.org/tap-version-13-specification.html> <https://github.com/TestAnything/test-anything-protocol/blob/master/output/draft-vaidya-test-anything-protocol-00.txt>

I suggest we look at something that exists and see if it fits.

#### Comment 2

- Sebastian Huber, Sat, 28 Oct 2017 12:08:04 GMT**

In [f703e7f/rtems](#):

```
tests: Move rtems_test_printer definition
Statically initialize it to use printk().
Update #3170. Update #3199.
```

#### Comment 3

- Sebastian Huber, Sat, 28 Oct 2017 12:08:16 GMT**

In [7bec7f27/rtems](#):

```
rtems: Add rtems_print_printer_fprintf_putc()
Update #3170. Update #3199.
```

#### Comment 4

- Sebastian Huber, Sat, 28 Oct 2017 12:08:27 GMT**

In [73d892d8/rtems](#):

```
tests: Use rtems_test_printer
Update #3170. Update #3199.
```

#### Comment 5

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Sebastian Huber**, Sat, 28 Oct 2017 12:08:39 GMT

In 46ddc3c5/rtems:

```
tests: Use rtems_print_printer_fprintf_putc()
Use rtems_print_printer_fprintf_putc() instead of rtems_print_printer_printf() to output via rtems_putc().
Update #3170. Update #3199.
```

#### **Comment 6**

1. **Sebastian Huber**, Sat, 28 Oct 2017 12:08:51 GMT

In 7e10291/rtems:

```
tests: Use rtems_test_printer in general
Update #3170. Update #3199.
```

#### **Comment 7**

1. **Sebastian Huber**, Sat, 28 Oct 2017 12:09:02 GMT

In acc9d064/rtems:

```
tests: Remove obsolete TESTS_USE_PRINTK
Update #3170. Update #3199.
```

#### **Comment 8**

1. **Sebastian Huber**, Sat, 28 Oct 2017 12:09:15 GMT

In af43554/rtems:

```
tests: Remove TEST_INIT
The TEST_EXTERN is a used only by the system.h style tests and they use CONFIGURE_INIT appropriately.
Update #3170. Update #3199.
```

#### **Comment 9**

1. **Chris Johns**, Mon, 30 Oct 2017 05:31:17 GMT

In 2126438a/rtems:

```
testsuite: Add bspIo for a local printk.
Update #3170. Update #3199.
```

#### **Comment 10**

1. **Sebastian Huber**, Thu, 02 Nov 2017 13:25:12 GMT

In 0d796d6/rtems:

```
tests: Delete obsolete TESTS_USE_PRINTF
Update #3170. Update #3199.
```

#### **Comment 11**

1. **Sebastian Huber**, Thu, 02 Nov 2017 13:26:51 GMT

In 8c1f4064/rtems:

```
tests: Use printf() instead of fprintf()
Update #3170. Update #3199.
```

#### **Comment 12**

**1. Sebastian Huber, Mon, 06 Nov 2017 06:29:13 GMT**

In 1082798/rtems:

score: Add `_IO_Printf()` and `_IO_Vprintf()`

The previous `vprintk()` implementation had a questionable licence header, lacks support for the `'z'` and `'j'` format specifiers, is not robust against invalid format specifiers, uses a global variable for output. Replace it with a stripped down version of the FreeBSD kernel `kvprintf()` function.

The new implementation allows a low overhead `rtems_snprintf()` if necessary.

Update #3199. Close #3216.

**Comment 13****1. Sebastian Huber, Mon, 06 Nov 2017 06:29:25 GMT**

In ac28f15/rtems:

Add simple console driver

Update #3170. Update #3199.

**Comment 14****1. Sebastian Huber, Mon, 06 Nov 2017 06:29:41 GMT**

In c4b8b147/rtems:

tests: Use simple console driver

Update #3170. Update #3199.

**Comment 15****1. Sebastian Huber, Tue, 07 Nov 2017 06:09:15 GMT**

In 7b00c2fa/rtems:

tests: Use in all tests

Update #3170. Update #3199.

**Comment 16****1. Sebastian Huber, Tue, 07 Nov 2017 07:32:57 GMT**

In 32ceb38/rtems:

tests: Use

Update #3170. Update #3199.

**Comment 17****1. Chris Johns, Fri, 10 Nov 2017 02:42:58 GMT**

In 6f3fb8a/rtems:

cpukit: Add a Version API.

Provide functions to get the version string, major, minor and revision numbers and the version control identifier that is a unique tag for the version control system.

Update #3199.

**Comment 18****1. Chris Johns, Sat, 11 Nov 2017 05:24:06 GMT**

In e6df806/rtems:

tests: Use `ld` to map `(wrap) printf`, `puts` and `putchar` to tester functions.

Remove the macro defines and the need for `tmacro.h` by remapping the

symbols using ld's wrap option. Remove FLUSH\_OUTPUT, it was empty. Move rtems\_test\_exit to libmisc/testsupport as a function.  
Update #3199.

#### Comment 19

1. **Sebastian Huber**, Wed, 15 Nov 2017 07:10:55 GMT

In 62119d2/rtems:

d101, d102, d105: Fix unresolved printf symbol  
The link time wrap of printf leads to unresolved symbols in the loadable modules. This resulted in infinite loops and test timeouts.  
Use rtems\_printf() for output.  
Update #3199.

#### Comment 20

1. **Sebastian Huber**, Fri, 17 Nov 2017 05:55:31 GMT

In 727cf48/rtems:

sptestests/spversion01: Simplify configuration  
Update #3199.

#### Comment 21

1. **Sebastian Huber**, Mon, 05 Feb 2018 09:48:37 GMT

In d078405/rtems-docs:

CONFIGURE\_APPLICATION\_NEEDS\_SIMPLE\_CONSOLE\_DRIVER  
Close #3170. Update #3199.

#### Comment 22

1. **Sebastian Huber**, Mon, 04 Mar 2019 13:03:31 GMT
2. **status**: changed from **assigned** to **accepted**
3. **blocking**: set to **3716**

#### Comment 23

1. **Sebastian Huber**, Wed, 27 Mar 2019 06:29:28 GMT

In 6fe01e4b/rtems:

build: Move test support to librtmestest.a  
One reason to move the test support into a dedicated library are the standard output wrap\_\*() functions. They may conflict with application level wrappers.  
Update #3199.

#### Comment 24

1. **Sebastian Huber**, Wed, 27 Mar 2019 06:29:32 GMT

In cfcc2cbf/rtems:

Add RTEMS Test Framework  
Update #3199.

#### Comment 25

1. **Sebastian Huber**, Wed, 27 Mar 2019 06:29:37 GMT

In cbfc3415/rtems:

ttest01: New test  
This is an example test using the RTEMS Test Framework. It tests also the framework itself.

Add T FILE\_NAME command line define to get rid of the full file path. This is important to reduce the read-only data of test files and make them build system independent.

Update #3199.

#### **Comment 26**

1. **Sebastian Huber**, Wed, 27 Mar 2019 06:34:23 GMT

In c2e582d/rtems-docs:

eng: Add software test framework chapter

Update #3199.

#### **Comment 27**

1. **Sebastian Huber**, Fri, 11 Oct 2019 09:02:08 GMT

In f88025a/rtems:

ttest01: Adjust SPDX-License-Identifier

Update #3199.

#### **Comment 28**

1. **Sebastian Huber**, Fri, 11 Oct 2019 09:02:13 GMT

In b406d071/rtems:

libtest: Do all output in test runner

This ensures that lines are output atomically if they are produced by different other contexts, e.g. interrupts, other processors, other threads.

Update #3199.

#### **Comment 29**

1. **Sebastian Huber**, Fri, 11 Oct 2019 09:02:18 GMT

In feb27f9/rtems:

ttest01: Add more test cases

Update #3199.

#### **Comment 30**

1. **Sebastian Huber**, Fri, 11 Oct 2019 09:02:26 GMT

In b5e61f95/rtems:

libtest: Add more action events

This allows more control over the initialization and finalization run.

Update #3199.

#### **Comment 31**

1. **Sebastian Huber**, Fri, 11 Oct 2019 09:02:32 GMT

In e71f0a5/rtems:

ttest01: Check init/final run output

Update #3199.

#### **Comment 32**

1. **Sebastian Huber**, Mon, 10 Feb 2020 08:03:35 GMT

In 45a0f65/rtems-docs:

eng: Document test framework formatted output  
Update #3199.

### **Comment 33**

1. **Sebastian Huber**, Mon, 10 Feb 2020 08:03:37 GMT

In b6c61e3/rtems-docs:

eng: Mention test framework buffer configuration  
Update #3199.

### **Comment 34**

1. **Sebastian Huber**, Mon, 10 Feb 2020 12:49:18 GMT

In 76b3aea/rtems-docs:

eng: Grammar fix  
Update #3199.

### **Comment 35**

1. **Sebastian Huber**, Fri, 17 Jul 2020 09:23:51 GMT
2. **milestone**: changed from **Indefinite** to **6.1**

### **Comment 36**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:06:12 GMT

In 21fa28c/rtems-docs:

eng: Update test framework chapter  
Document the dynamic text fixtures, utility functions, and the interrupt test support. Reorder some sections and reword some paragraphs based on review comments.  
Update #3199.

### **Comment 37**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:57:50 GMT

In 9de8d61/rtems:

libtest: to  
Rename this header file to later move to . The main feature provided by is the output of standard test information which is consumed by the RTEMS Tester.  
Update #3199.

### **Comment 38**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:57:54 GMT

In 361404e8/rtems:

libtest: Move to  
Update #3199.

### **Comment 39**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:57:57 GMT

In e3e3b871/rtems:

```
libtest: Add T_busy()
```

```
Update #3199.
```

#### **Comment 40**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:00 GMT

In af92665/rtems:

```
libtest: Add T_get_one_clock_tick_busy()
```

```
Update #3199.
```

#### **Comment 41**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:04 GMT

In c081c68/rtems:

```
libtest: Add T_make_runner()
```

```
Update #3199.
```

#### **Comment 42**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:07 GMT

In 6b27e32/rtems:

```
libtest: Support custom scope messages via fixture
```

```
Update #3199.
```

#### **Comment 43**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:10 GMT

In cb3c6bdc/rtems:

```
libtest: Add push/pop fixture support
```

```
Update #3199.
```

#### **Comment 44**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:14 GMT

In 63e4278/rtems:

```
libtest: Add T_get_scope()
```

```
Update #3199.
```

#### **Comment 45**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:17 GMT

In 34e4df55/rtems:

```
libtest: Split POSIX Keys support
```

```
Update #3199.
```

#### **Comment 46**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:20 GMT

In 7781404/rtems:

```
libtest: Add T_stop()
```

```
Update #3199.
```



**Comment 47**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:24 GMT

In 35d9af69/rtems:

```
libtest: Add T_CHECK_FMT

Rename internal function T_check_true() to T_check() and use the new flag T_CHECK_FMT to indicate if a format string is present. This is a preparation step to make the format string optional.

Make the check context the first parameter.

The API remains the same.

Update #3199.
```

**Comment 48**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:27 GMT

In d702c9f4/rtems:

```
libtest: Make check message optional

This macro magic is in line with C11 and C++11, but limits the maximum count of arguments.

Update #3199.
```

**Comment 49**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:30 GMT

In 467ef5b4/rtems:

```
libtest: Add T_unreachable()

Update #3199.
```

**Comment 50**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:34 GMT

In dddc9a58/rtems:

```
libtest: Add quiet assert NULL pointer checks

Update #3199.
```

**Comment 51**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:37 GMT

In c9d2405/rtems:

```
libtest: Add rtems_test_run()

Update #3199.
```

**Comment 52**

1. **Sebastian Huber**, Thu, 23 Jul 2020 08:58:40 GMT

In cc3fd8fc/rtems:

```
libtest: Add T_interrupt_test()

Update #3199.
```

**Comment 53**

1. **Sebastian Huber**, Thu, 06 Aug 2020 17:16:12 GMT

In 32f1f747/rtems:

libtest: Fix T\_interrupt\_test() in SMP configs  
Update #3199.

#### **Comment 54**

1. **Sebastian Huber**, Fri, 07 Aug 2020 16:10:19 GMT

In f933b65/rtems:

libtest: Improve T\_check\_task\_context  
Update #3199.

#### **Comment 55**

1. **Sebastian Huber**, Mon, 10 Aug 2020 09:50:29 GMT

In 20c79bf/rtems:

libtest: Constify  
Update #3199.

#### **Comment 56**

1. **Sebastian Huber**, Tue, 11 Aug 2020 06:04:20 GMT

In c1354f0/rtems:

libtest: Add T\_thread\_switch\_record()  
Add support to record thread switch events. This can be used to check that a blocking operation results in the expected sequence of thread switches.  
Update #3199.

#### **Comment 57**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:18 GMT

In 5a8114c6/rtems:

libtest: Change fixture scope method  
Return the produced character count. There is no need for a NUL termination.  
Update #3199.

#### **Comment 58**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:21 GMT

In e67eff2/rtems:

libtest: Add output buffer drain and fill  
Update #3199.

#### **Comment 59**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:25 GMT

In a7af34d0/rtems:

libtest: Add T\_do\_is\_runner()  
Update #3199.

#### **Comment 60**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:28 GMT

In 5d614fd/rtems:

```
libtest: Add T_puts()  
Update #3199.
```

#### **Comment 61**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:31 GMT

In cbc1ba3/rtems:

```
libtest: Use line buffer in T_check()  
Update #3199.
```

#### **Comment 62**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:34 GMT

In 33eb113/rtems:

```
libtest: Add T_check_steps()  
Update #3199.
```

#### **Comment 63**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:37 GMT

In 5383d4db/rtems:

```
libtest: Add fixture steps  
Support a new test plan for each nested fixture.  
Update #3199.
```

#### **Comment 64**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:41 GMT

In 72960bc7/rtems:

```
libtest: Change T_step() and T_assert_step()  
Normally, the expected test step must be a compile time constant. Allow variable expected test steps for the T_step() and T_assert_step(). This can be used for parameterized test loops with individual fixtures.  
Remove the ability to use custom failure messages due to some implementation constraints.  
Update #3199.
```

#### **Comment 65**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:44 GMT

In 13acd90/rtems:

```
libtest: Use a destructor  
Do not set up a new test steps environment.  
Update #3199.
```

#### **Comment 66**

1. **Sebastian Huber**, Tue, 18 Aug 2020 05:15:47 GMT

In c7289484/rtems:

```
libtest: Add T_push_plan() and T_pop_plan()  
Update #3199.
```

**Comment 67**

1. **Sebastian Huber**, Mon, 31 Aug 2020 14:21:37 GMT

In d556af36/rtems:

bsps: Always install IPI in SMP configs

The inter-processor interrupt (IPI) may be used to process per-CPU jobs. See for example the blocked handler in `T_interrupt_test()`.

Update #3199.

**Comment 68**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:12 GMT

In 98d2adb/rtems:

libtest: Fix `T_thread_switch_record()`

If `RTEMS_DEBUG` is not defined, then we have to explicitly set the node off the chain.

Update #3199.

**Comment 69**

1. **Sebastian Huber**, Thu, 19 Nov 2020 07:39:42 GMT

In c542345/rtems:

libtest: Simplify "Load" environment reporting

Report all runtime measurement environments with a name only and encode the worker count of the "Load" environment in the name.

Update #3199.

**Comment 70**

1. **Sebastian Huber**, Thu, 19 Nov 2020 07:59:18 GMT

In cdbd72d/rtems-docs:

eng: Rename `ValidCache?` environment in `FullCache?`

This name better reflects the execution environment in which the cache is fully loaded with valid data unrelated to the body request handler.

Update #3199.

**Comment 71**

1. **Sebastian Huber**, Thu, 19 Nov 2020 07:59:20 GMT

In 0454ad7/rtems-docs:

eng: Simplify "Load" environment reporting

Report all runtime measurement environments with a name only and encode the worker count of the "Load" environment in the name.

Update #3199.

**Comment 72**

1. **Sebastian Huber**, Tue, 24 Nov 2020 06:40:45 GMT

In aa1c6dd/rtems:

libtest: Fix undefined `setjmp()` behaviour

Bug was introduced by `78baeb757957fa0807c30e6c4d21ae99c9639e6a`.

Update #3199.

**Comment 73**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT

2. **keywords:** **qualification** added

#### Comment 74

1. **Sebastian Huber**, Wed, 29 Sep 2021 13:25:31 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

The test framework is fully implemented.

### **3230 - RSB does not report --rsb-file for patches correctly.**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3230">https://devel.rtems.org/ticket/3230</a> ( <a href="https://devel.rtems.org/ticket/3230">https://devel.rtems.org/ticket/3230</a> )
<b>Id</b>	3230
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 November 2017 04:45:41
<b>Modified</b>	12 December 2019 23:32:22
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	accepted
<b>Resolution</b>	
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The reports from the RSB do not report the --rsb-file option correctly.

#### Comment 1

1. **Chris Johns**, Sun, 12 Nov 2017 04:46:01 GMT
2. **status:** changed from **assigned** to **accepted**

#### Comment 2

1. **Chris Johns**, Thu, 12 Dec 2019 23:32:22 GMT
2. **milestone:** changed from **5.1** to **6.1**

### **3250 - Remove Use of bsp\_specs**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3250">https://devel.rtems.org/ticket/3250</a> ( <a href="https://devel.rtems.org/ticket/3250">https://devel.rtems.org/ticket/3250</a> )
<b>Id</b>	3250
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 November 2017 19:27:53
<b>Modified</b>	12 September 2022 06:55:14
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3818, 3937

#### Description

The bsp\_specs file in each BSP directory is GCC specific and a barrier to supporting other compilers including clang/llvm. The bsp\_specs file is used in a variety of ways including some odd build system dependencies and this ticket is to track eliminating those uses and the direct use of bsp\_specs themselves for extending GCC options.

The primary use of the bsp\_specs file is to extend GCC's notion of what to link with. The bsp\_specs itself commonly specifies:

- start.o file
- program entry point

- crt[fin].o or crtbegin.o/crtend.o
- linker script
- Frequently, arguments which are implicitly passed to ld.

This is typical and from a recently added BSP:

```
%rename endfile old_endfile
%rename startfile old_startfile
%rename link old_link
*startfile:
%{!qrtems: %(old_startfile)} \
%{!nostdlib: %{qrtems: start.o%s crti.o%s crtbegin.o%s -e _start}}
*link:
%{!qrtems: %(old_link)} %{qrtems: -dc -dp -N}
*endfile:
%{!qrtems: %(old_endfiles)} %{qrtems: crtend.o%s crtn.o%s }
```

Note that it has the implicit "-dc -dp -N" arguments which are passed to ld.

The -dc and -dp options are equivalent and assign space to common symbols even with linking with -r. Why these two options are included is a mystery lost to time. Similarly the -N sets the .text and .data sections to be readable and writable and do NOT page align the data segment. This option is also a blast from the ancient past and likely should not be used.

The "-qrtems" option is used with this pattern when compiling and linking RTEMS programs:

```
-B${PREFIX}/${BSP}/lib/ -specs bsp_specs -qrtems
```

The -B says that the following directory is a system directory. It is treated as a "lib" directory and is also assumed to have an include/ subdirectory. They are added to the linker and include search paths, respectfully. The -specs option references the bsp\_specs and adds the -qrtems options which are then tripped by specifying -qrtems. Every part of this must be eliminated and performed in a manner that is more amenable to using a compiler other than GCC.

In order to eliminate the bsp\_specs, the arguments used in each BSP's version will have to be reviewed, made common, and then eliminated. A similar effort was performed when the BSP specific make-exe rules were eliminated from the "make/custom" files and a common pattern was put in place.

In addition to using the bsp\_specs to specify details about linking and include files, the build system has quite a few odd dependencies on the presence of bsp\_specs:

- all BSP configure.ac use bsp\_specs like this:

```
AC_CONFIG_SRCDIR([bsp_specs])
```

The idea was that this was a unique file to ensure the script was in the right directory. This can be changed to use a specific make/custom/\*.cfg file and not lose any integrity checking.

- all BSP Makefile.am have this:

```
dist project lib DATA = bsp_specs
```

That can just be removed when we don't use the file.

- ./aclocal/check-bsps.m4 uses it to see if it is BSP directory
- bootstrap uses it generate the list of BSP directories for the libbsp/\*/acinclude.m4 files
- Other references are either comments or obvious uses of it in

some invocation of GCC.

### Comment 1

1. **Joel Sherrill**, Tue, 19 Dec 2017 17:07:13 GMT

In b0b93c8a/rtems:

```
gensh4: Simplify bsp_specs
Updates #3250.
```

### Comment 2

1. **Chris Johns**, Mon, 05 Feb 2018 23:37:24 GMT
2. **component**: changed from **admin** to **build**

### Comment 3

1. **Sebastian Huber**, Mon, 06 Apr 2020 14:01:59 GMT
2. **blockedby**: set to **3818, 3937**

### Comment 4

1. **Sebastian Huber**, Tue, 26 Jan 2021 05:40:00 GMT
2. **milestone**: changed from **Indefinite** to **6.1**

The bsp\_specs are only used by the old build system and can be removed with along the old build system.

### Comment 5

1. **Sebastian Huber**, Thu, 28 Jan 2021 05:30:16 GMT

In b361eabd/rtems:

bsps: Replace bsp\_specs with an empty file

This fixes an issue with the latest tool chain which adds the default linker script in the endfile specification.

Update #3250.

#### **Comment 6**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords: qualification** added

#### **Comment 7**

1. **Sebastian Huber**, Tue, 21 Sep 2021 08:25:58 GMT
2. **owner:** set to **Sebastian Huber <sebastian.huber@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In db8f598/rtems:

build: Remove old build system

Close #3250. Close #4081.

#### **Comment 8**

1. **Sebastian Huber**, Mon, 12 Sep 2022 06:55:14 GMT

In 8f4543f/rtems-docs:

user: Mention that the bsp\_specs are gone

Update #3250.

---

## **3269 - Make the IRQ extensions API a standard API**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3269">https://devel.rtems.org/ticket/3269</a> ( <a href="https://devel.rtems.org/ticket/3269">https://devel.rtems.org/ticket/3269</a> )
<b>Id</b>	3269
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 January 2018 10:58:04
<b>Modified</b>	16 June 2023 05:30:18
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

The IRQ extensions API defined by is currently only implemented by some BSPs and not covered by test cases. It is not documented in the RTEMS Classic API Guide. Change the BSPs so that every BSP implements this API at least as a stub so that we can write tests for this API. Specify and document the API.

Extend the API to enable/disable specific interrupt vectors. The proposed functions for this are rtems\_interrupt\_mask() and rtems\_interrupt\_unmask().

Extend the API to raise/clear specific interrupt vectors. This allows to test specific interrupts. The proposed functions are rtems\_interrupt\_raise() and rtems\_interrupt\_clear().

Extend the API to set/get the interrupt vector priority.

Extend the API to get some information about a particular interrupt vector, e.g. if the raise/clear functions work, if it is possible to change the priority, etc.

#### **Comment 1**

1. **Sebastian Huber**, Thu, 04 Jan 2018 06:20:36 GMT

In 569fd50/rtems:

sparc: Remove BSP specifics from

Update #3254. Update #3260. Update #3269.

### Comment 2

1. **Sebastian Huber**, Mon, 13 May 2019 13:33:51 GMT
2. **summary:** changed from **Add functions to enable, disable, and clear interrupts to the IRQ extensions API** to **Make the IRQ extensions API a standard API**
3. **component:** changed from **dev** to **rtems**
4. **description:** modified (diff)
5. **version:** set to **5**
6. **milestone:** changed from **Indefinite** to **5.1**

### Comment 3

1. **Sebastian Huber**, Thu, 16 May 2019 07:59:21 GMT

In 45d0659/rtems:

```
bsps: Always build generic interrupt support
```

```
This makes it possible to write tests for the generic interrupt controller support.
```

```
Update #3269.
```

### Comment 4

1. **Sebastian Huber**, Fri, 05 Jul 2019 07:04:53 GMT

In e9c83b4/rtems:

```
bsps: Regenerate headers.am
```

```
Update #3269.
```

### Comment 5

1. **Sebastian Huber**, Thu, 19 Dec 2019 08:07:34 GMT
2. **milestone:** changed from **5.1** to **6.1**

### Comment 6

1. **Sebastian Huber**, Fri, 31 Jul 2020 05:01:26 GMT

In a3bcc79/rtems:

```
bsps/lm32: Use shared
```

```
Having a duplicate header with the shared includes is a build system inconsistency. You may use one header file to build the libraries and another one is installed (overwriting the other).
```

```
Update #3269.
```

### Comment 7

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** **qualification** added

### Comment 8

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:29:35 GMT

In 61d0be7/rtems:

```
bsps/irq: Remove BSP_INTERRUPT_NO_HEAP_USAGE
```

```
Remove the support for BSP_INTERRUPT_NO_HEAP_USAGE. This was only used by one BSP and provides no real benefit.
```

```
Update #3269.
```

### Comment 9



**1. Sebastian Huber, Thu, 24 Jun 2021 10:29:39 GMT**

In 4146d39/rtems:

`bsp/genmcf548x: Change BSP_INTERRUPT_VECTOR_MIN`

This BSP uses a customized implementation of the interrupt extension API. It was the only BSP which defined `BSP_INTERRUPT_VECTOR_MIN` to a value other than zero. Define it to zero and use a custom `bsp_interrupt_is_valid_vector()` function instead.

Update #3269.

**Comment 10****1. Sebastian Huber, Thu, 24 Jun 2021 10:29:42 GMT**

In 5210c7c/rtems:

`bsp/generic_orlk: Remove incomplete IRQ support`

Update #3269.

**Comment 11****1. Sebastian Huber, Thu, 24 Jun 2021 10:29:46 GMT**

In f3acb8b/rtems:

`bsps/irq: Assert BSP_INTERRUPT_VECTOR_MIN == 0`

After building all BSPs with this patch, this BSP-specific define can be removed to simplify the implementation.

Update #3269.

**Comment 12****1. Sebastian Huber, Thu, 24 Jun 2021 10:29:49 GMT**

In af73b7b6/rtems:

`bsps/irq: Remove BSP_INTERRUPT_VECTOR_MIN`

Remove `BSP_INTERRUPT_VECTOR_MIN` and unconditionally let interrupt vector numbers start with zero.

The `BSP_INTERRUPT_VECTOR_MIN == 0` invariant was tested by the previous commit and building all BSPs.

Update #3269.

**Comment 13****1. Sebastian Huber, Thu, 24 Jun 2021 10:29:53 GMT**

In 900a84c5/rtems:

`smcapture02: Fix use of BSP_INTERRUPT_VECTOR_MAX`

This define represents the last valid interrupt vector number.

Update #3269.

**Comment 14****1. Sebastian Huber, Thu, 24 Jun 2021 10:29:56 GMT**

In cd5573c/rtems:

`bsps/irq: Add BSP_INTERRUPT_VECTOR_COUNT``Assert BSP_INTERRUPT_VECTOR_MAX + 1 == BSP_INTERRUPT_VECTOR_COUNT.`

After building all BSPs with this patch, `BSP_INTERRUPT_VECTOR_MAX` can be removed and replaced by `BSP_INTERRUPT_VECTOR_COUNT`. The `BSP_INTERRUPT_VECTOR_COUNT` allows a default implementation which supports no interrupt vector at all. Using `COUNT` instead of `MAX` may avoid some interpretation issues, for example is the maximum value a valid vector number or not.

Update #3269.

**Comment 15****1. Sebastian Huber, Thu, 24 Jun 2021 10:30:00 GMT**

In 049e2b6/rtems:

```
bsps/irq: Remove BSP_INTERRUPT_VECTOR_NUMBER
Replace it with BSP_INTERRUPT_VECTOR_COUNT.
Update #3269.
```

#### **Comment 16**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:03 GMT

In 3fee6620/rtems:

```
bsps/irq: Use BSP_INTERRUPT_VECTOR_COUNT
Use BSP_INTERRUPT_VECTOR_COUNT instead of BSP_INTERRUPT_VECTOR_MAX.
Update #3269.
```

#### **Comment 17**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:07 GMT

In 94cf67c/rtems:

```
bsps/irq: Remove BSP_INTERRUPT_VECTOR_MAX
This define is no longer used.
Update #3269.
```

#### **Comment 18**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:10 GMT

In fdf2ee7/rtems:

```
bsps/irq: Default BSP_INTERRUPT_VECTOR_COUNT == 0
Change the default value of BSP_INTERRUPT_VECTOR_COUNT so that no interrupt vectors are supported and all related directives return RTEMS_INVALID_ID.
Update #3269.
```

#### **Comment 19**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:14 GMT

In 6b7a3858/rtems:

```
bsp/atsam: Fix BSP_INTERRUPT_VECTOR_COUNT
Fix an off by one error.
Update #3269.
```

#### **Comment 20**

1. **Sebastian Huber**, Mon, 12 Jul 2021 12:27:57 GMT

In c7b3df3f/rtems:

```
bsps/sparc: Improve interrupt affinity support
Fully support the interrupt extension API to set/get the interrupt affinity. Remove LEON3_irq_to_cpu which defined the interrupt to processor mapping in a BSP-specific way.
Update #3269.
```

#### **Comment 21**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:42:57 GMT

In efb3fc2/rtems:

```
bsps/irq: Move get/set affinity to separate file
```

Update #3269.

**Comment 22**1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:00 GMT

In 1b3b5b84/rtems:

bsps/irq: Canonicalize get/set affinity errors

Bring the error conditions and status in line with rtems\_task\_get\_affinity() and rtems\_task\_set\_affinity().

Update #3269.

**Comment 23**1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:04 GMT

In 04c2c08/rtems:

bsps/irq: Move handler iterate to separate file

Update #3269.

**Comment 24**1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:07 GMT

In ba937459/rtems:

rtems: Add rtems\_interrupt\_raise()

Add rtems\_interrupt\_raise\_on(). Document the currently not implemented rtems\_interrupt\_clear(). Remove the not implemented and badly named rtems\_interrupt\_cause() directive.

Update #3269.

**Comment 25**1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:11 GMT

In c4eafae2/rtems:

rtems: Generate

Use which just provides the data types and avoid a dependency on which contains the full chain implementation.

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3269. Update #3899. Update #3993.

**Comment 26**1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:14 GMT

In 5e33aec/rtems:

rtems: Add rtems\_interrupt\_get\_attributes()

Add a directive to query the attributes of an interrupt vector. This can be used for generic tests and system diagnostics.

Update #3269.

**Comment 27**1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:18 GMT

In 96265c8/rtems:

rtems: Add rtems\_interrupt\_vector\_enable()

Add rtems\_interrupt\_vector\_disable().

Update #3269.

**Comment 28**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:21 GMT

In 01e7c36/rtems:

```
rtems: Add rtems_interrupt_vector_is_enabled()
Update #3269.
```

#### **Comment 29**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:25 GMT

In faa4b636/rtems:

```
rtems: Add rtems_interrupt_is_pending()
Update #3269.
```

#### **Comment 30**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:28 GMT

In 4969af4/rtems:

```
rtems: Add RTEMS_FATAL_SOURCE_SPURIOUS_INTERRUPT
Add RTEMS_FATAL_SOURCE_SPURIOUS_INTERRUPT as the fatal source for spurious interrupts. Use the interrupt vector number of the spurious interrupt for the fatal code.
Update #3269.
```

#### **Comment 31**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:32 GMT

In 781213f9/rtems:

```
bsps/irq: Add rtems_interrupt_vector_is_enabled()
Add a default implementation which just returns RTEMS_UNSATISFIED for valid parameters.
Update #3269.
```

#### **Comment 32**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:35 GMT

In 9832652c/rtems:

```
bsps/irq: Add rtems_interrupt_raise()
Add rtems_interrupt_raise_on() and rtems_interrupt_clear().
Add a default implementation which just returns RTEMS_UNSATISFIED for valid parameters.
Update #3269.
```

#### **Comment 33**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:38 GMT

In eebecd0/rtems:

```
bsps/irq: Add rtems_interrupt_get_attributes()
Add a default implementation which clears the attributes to zero and just returns RTEMS_SUCCESSFUL for valid parameters.
Update #3269.
```

#### **Comment 34**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:42 GMT

In deb5afb/rtems:

```
bsps/irq: Add rtems_interrupt_is_pending()
```

Add a default implementation which just returns RTEMS\_UNSATISFIED.

Update #3269.

### **Comment 35**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:45 GMT

In bc86a5fa/rtems:

```
bsps/irq: bsp_interrupt_vector_enable()
```

Return a status code for bsp\_interrupt\_vector\_enable().

Update #3269.

### **Comment 36**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:48 GMT

In 32f5a195/rtems:

```
bsps/irq: bsp_interrupt_vector_disable()
```

Return a status code for bsp\_interrupt\_vector\_disable().

Update #3269.

### **Comment 37**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:52 GMT

In 23ec04c/rtems:

```
bsps/irq: bsp_interrupt_get_affinity()
```

Return a status code for bsp\_interrupt\_get\_affinity().

Update #3269.

### **Comment 38**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:56 GMT

In 85a3785/rtems:

```
bsps/irq: bsp_interrupt_set_affinity()
```

Return a status code for bsp\_interrupt\_set\_affinity().

Update #3269.

### **Comment 39**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:59 GMT

In fe6ce5ac/rtems:

```
bsps/irq: Implement new directives for GICv2/3
```

Update #3269.

### **Comment 40**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:02 GMT

In 09be98d/rtems:

```
sparc/irq: Implement new interrupt directives
```

Update #3269.

### **Comment 41**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:06 GMT

In 81358d7/rtems:

rtems: Add rtems\_interrupt\_entry\_install()

Add RTEMS\_INTERRUPT\_ENTRY\_INITIALIZER(), rtems\_interrupt\_entry\_initialize(), and rtems\_interrupt\_entry\_remove(). This allows to install interrupt handlers using user-provided storage as an alternative to rtems\_interrupt\_handler\_install() which has to allocate memory.

Update #3269.

#### **Comment 42**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:09 GMT

In 73fcbf4/rtems:

bsps/irq: Use rtems\_interrupt\_entry

Update #3269.

#### **Comment 43**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:13 GMT

In 63d9e84/rtems:

bsps/irq: Add bsp\_interrupt\_check\_and\_lock()

Return RTEMS\_INCORRECT\_STATE instead of RTEMS\_INTERNAL\_ERROR in case the interrupt support is not initialized. This is similar to rtems\_timer\_server\_fire\_after() for example.

Update #3269.

#### **Comment 44**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:16 GMT

In 70357f1/rtems:

bsps/irq: Move bsp\_interrupt\_handler\_is\_empty()

This function is only used by one BSP.

Update #3269.

#### **Comment 45**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:20 GMT

In e518323/rtems:

bsps/irq: Add rtems\_interrupt\_entry\_install()

Add rtems\_interrupt\_entry\_remove(). Split up irq-generic.c into several files. In particular, place all functions which use dynamic memory into their own file.

Add optional macros to let the BSP customize the vector installation after installing the first entry and the vector removal before removing the last entry:

bsp\_interrupt\_vector\_install() bsp\_interrupt\_vector\_remove()

Use These new Customization options in the m68k/genmcf548x BSP so re-use the generic interrupt controller support.

Update #3269.

#### **Comment 46**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:23 GMT

In b910e60/rtems:

bsp/raspberrypi: Add interrupt get/set affinity

Add default implementations for bsp\_interrupt\_get\_affinity() and bsp\_interrupt\_set\_affinity() which are required to link all tests in SMP configurations.

Update #3269.

#### **Comment 47**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:26 GMT

In f89cf8e8/rtems:

validation: Add CallWithinISR()

Update #3269.

#### **Comment 48**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:30 GMT

In 1465e78a/rtems:

validation: HasInterruptVectorEntriesInstalled?()

Update #3269.

#### **Comment 49**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:33 GMT

In bfec448/rtems:

validation: GetValidInterruptVectorNumber?()

Update #3269.

#### **Comment 50**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:37 GMT

In 9e1fc36/rtems:

validation: GetTestableInterruptVector?()

Update #3269.

#### **Comment 51**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:40 GMT

In e2894df/rtems:

validation: Test rtems\_interrupt\_get\_attributes()

Update #3269.

#### **Comment 52**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:44 GMT

In d8be2b97/rtems:

validation: rtems\_interrupt\_vector\_is\_enabled()

Update #3269.

#### **Comment 53**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:47 GMT

In 7a3e6c7/rtems:

validation: Test rtems\_interrupt\_vector\_enable()

Update #3269.

#### **Comment 54**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:50 GMT

In aa6c962/rtems:

```
validation: Test rtems_interrupt_vector_disable()
Update #3269.
```

**Comment 55**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:54 GMT

In 09960369/rtems:

```
validation: Test rtems_interrupt_entry_install()
Update #3269.
```

**Comment 56**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:44:57 GMT

In 7dbab6af/rtems:

```
validation: Test rtems_interrupt_entry_remove()
Update #3269.
```

**Comment 57**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:01 GMT

In 4341058/rtems:

```
validation: Test rtems_interrupt_raise()
Update #3269.
```

**Comment 58**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:04 GMT

In 1bf8139a/rtems:

```
validation: Test rtems_interrupt_clear()
Update #3269.
```

**Comment 59**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:07 GMT

In 163c1fd/rtems:

```
validation: Test rtems_interrupt_is_pending()
Update #3269.
```

**Comment 60**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:11 GMT

In 32c0cd8/rtems:

```
validation: Test rtems_interrupt_raise_on()
Update #3269.
```

**Comment 61**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:14 GMT

In aab3713/rtems:

```
validation: Test rtems_interrupt_get_affinity()
```



Update #3269.

**Comment 62**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:18 GMT

In 17fb5239/rtems:

```
validation: Test rtems_interrupt_set_affinity()
Update #3269.
```

**Comment 63**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:45:21 GMT

In 67c033d3/rtems:

```
validation: Test rtems_interrupt_handler_iterate()
Update #3269.
```

**Comment 64**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:50:33 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 056886f/rtems-docs:

```
c-user: Document interrupt manager extensions
Close #3269.
```

**Comment 65**

1. **Sebastian Huber**, Thu, 12 Aug 2021 19:07:44 GMT

In 75af5be/rtems:

```
bsp/leon3: Fix rtems_interrupt_is_pending()
Take the interrupt force register into account in all configurations.
Update #3269.
```

**Comment 66**

1. **Sebastian Huber**, Tue, 11 Jan 2022 15:41:33 GMT

In cbc9232/rtems:

```
bsp/qoriq: Implement Interrupt Manager directives
Update #3269.
```

**Comment 67**

1. **Sebastian Huber**, Wed, 16 Mar 2022 06:17:15 GMT

In 49f84b7/rtems-docs:

```
c-user: Improve interrupt set affinity handling
Update #3269.
```

**Comment 68**

1. **Sebastian Huber**, Wed, 16 Mar 2022 06:24:29 GMT

In ca4fa22e/rtems:

bsps/irq: Fix formatting  
Update #3269.

#### **Comment 69**

1. **Sebastian Huber**, Wed, 16 Mar 2022 06:24:33 GMT

In f311caf/rtems:

bsps/irq: Improve affinity set handling

Restrict the affinity set to the set of online processors. Make sure the affinity set for an interrupt vector contains at least one online processor.

Update #3269.

#### **Comment 70**

1. **Sebastian Huber**, Wed, 08 Jun 2022 08:20:07 GMT

In 9a69e430/rtems:

validation: Fix CallWithinISR()

Some BSPs require that Clear\_tm27\_intr() is called in the interrupt service routine.

Update #3269.

#### **Comment 71**

1. **Sebastian Huber**, Fri, 16 Jun 2023 05:30:14 GMT

In 83305f5/rtems:

pci: Do not use BSP-specific interrupt API

Update #3269.

#### **Comment 72**

1. **Sebastian Huber**, Fri, 16 Jun 2023 05:30:16 GMT

In 4e3e9df/rtems:

bsps: Remove uses of BSP-specific interrupt API

Update #3269.

#### **Comment 73**

1. **Sebastian Huber**, Fri, 16 Jun 2023 05:30:18 GMT

In 65b0ba4/rtems:

bsps/sparc: Deprecate BSP-specific interrupt API

Update #3269.

---

## **3321 - Improve console driver documentation**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3321">https://devel.rtems.org/ticket/3321</a> ( <a href="https://devel.rtems.org/ticket/3321">https://devel.rtems.org/ticket/3321</a> )
<b>Id</b>	3321
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	6 March 2018 12:14:57
<b>Modified</b>	26 January 2022 13:31:59
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

We have now three different standard console drivers. Improve the console driver configuration documentation to assist the user to select the right one.

**Comment 1**

1. **Sebastian Huber**, Tue, 06 Mar 2018 12:15:14 GMT
2. **owner**: set to **Sebastian Huber**
3. **status**: changed from **new** to **assigned**

**Comment 2**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:31:59 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Documentation was improved.

---

**3414 - Remove Makefiles from rtems-examples?**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3414">https://devel.rtems.org/ticket/3414</a> ( <a href="https://devel.rtems.org/ticket/3414">https://devel.rtems.org/ticket/3414</a> )
<b>Id</b>	3414
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	25 April 2018 23:52:20
<b>Modified</b>	29 November 2022 21:54:49
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	examples
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

It seems to be time to remove Makefile build support from examples-v2

**Comment 1**

1. **Chris Johns**, Sun, 14 Oct 2018 01:04:36 GMT
2. **status**: changed from **new** to **assigned**
3. **version**: changed from **5** to **6**
4. **milestone**: changed from **5.1** to **6.1**

Remove in 6.

**Comment 2**

1. **Chris Johns**, Wed, 18 Sep 2019 22:53:28 GMT
2. **keywords**: **examples** added

3. **summary:** changed from **Remove Makefiles from examples-v2?** to **Remove Makefiles from rtems-examples?**

Does the Makefile build work with the rtems-example master HEAD?

### Comment 3

1. **Joel Sherrill**, Thu, 19 Sep 2019 10:52:42 GMT

It did an couple of weeks ago

### Comment 4

1. **Chris Johns**, Fri, 20 Sep 2019 04:31:42 GMT

Replying to Joel Sherrill:

It did an couple of weeks ago

How up to date is the build, for example we have a libbsd and graphics example in the repo now?

### Comment 5

1. **Chris Johns**, Tue, 29 Nov 2022 21:54:49 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **invalid**

Makefile.inc is to be supported so examples with Makefiles makes sense to keep.

## 3420 - Deprecate/obsolete rtems\_io\_lookup\_name

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3420">https://devel.rtems.org/ticket/3420</a> ( <a href="https://devel.rtems.org/ticket/3420">https://devel.rtems.org/ticket/3420</a> )
<b>Id</b>	3420
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 April 2018 14:12:00
<b>Modified</b>	10 November 2022 21:06:05
<b>Owner</b>	joel
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

I have noted in the RTEMS Class that this method is only kept for legacy purposes for many years now. There is no real use in the tree now. Only the following:

```
$ grep -rl rtems_io_lookup_name .
./cpukit/include/adainclude/rtems-io.adb
./cpukit/include/rtems/io.h
./cpukit/libfs/src/imfs/ioman.c
./testsuites/sptests/sp21/sp21.scn
./testsuites/sptests/sp21/init.c
```

Deprecate in 5.1 and remove in 6.x or obsolete and just remove now?

### Comment 1

1. **Sebastian Huber**, Mon, 17 Sep 2018 11:49:12 GMT

I would not touch this function. It adds no overhead to applications which don't use it.

### Comment 2

1. **Chris Johns**, Sun, 14 Oct 2018 01:10:58 GMT
2. **owner:** set to **joel**
3. **status:** changed from **new** to **assigned**
4. **version:** changed from **5** to **6**
5. **milestone:** changed from **5.1** to **6.1**

**Comment 3**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:39 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In dc4879b/rtems:

```
rtems: Remove deprecated rtems_io_lookup_name()
Close #3420.
```

**Comment 4**

1. **Joel Sherrill**, Thu, 10 Nov 2022 21:06:05 GMT

In ecd8aec9/rtems:

```
Remove remnants of rtems_io_lookup_name
Updates #3420.
```

**3456 - Add support for CPU counter timestamps**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3456">https://devel.rtems.org/ticket/3456</a> ( <a href="https://devel.rtems.org/ticket/3456">https://devel.rtems.org/ticket/3456</a> )
<b>Id</b>	3456
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 June 2018 10:02:54
<b>Modified</b>	31 October 2023 11:46:21
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3961

---

**Description**

The original use case for the CPU counter was low level profiling of SMP synchronization primitives and busy wait loops for device drivers.

For low overhead timestamps the CPU counter may be also used, e.g. for tracing. To support timestamps, the CPU counter must increment monotonically within the whole range of the CPU counter data type, e.g. 32-bit unsigned integer. In addition, it should not be affected by power saving states of the processor.

**Comment 1**

1. **Sebastian Huber**, Tue, 19 Jun 2018 04:58:16 GMT

In 4c7b18e3/rtems:

```
Add RTEMS_SYSINIT_CPU_COUNTER
Add initialization step for the CPU counter support.
Update #3456.
```

**Comment 2**

1. **Sebastian Huber**, Tue, 19 Jun 2018 04:58:29 GMT

In 65f868c/rtems:

```
Add _CPU_Counter_frequency()
Add rtems counter_frequency() API function. Use it to initialize the counter value converter via the new system initialization step (RTEMS_SYSINIT_CPU_COUNTER). This decouples the counter implementation and the counter converter. It avoids an unnecessary pull in of the 64-bit integer division from libgcc.
Update #3456.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 19 Jun 2018 04:58:39 GMT

In 6d130e6/rtems-docs:

```
c-user: Document RTEMS_SYSINIT_CPU_COUNTER
Update #3456.
```

**Comment 4**

1. **Sebastian Huber**, Tue, 19 Jun 2018 04:58:41 GMT

In 762fa62/rtems:

```
arm: Simplify CPU counter support

Use the standard ARMv7-M systick module for the ARMv7-M CPU counter instead of DWT counter since the DWT counter is affected by power saving states.

Use an inline function for _CPU_Counter_difference() for all ARM BSPs.

Update #3456.
```

**Comment 5**

1. **Sebastian Huber**, Thu, 20 Sep 2018 05:28:13 GMT

In b3cf79b/rtems:

```
bsp/leon3: Fix typo which breaks the CPU counter
Update #3456.
```

**Comment 6**

1. **Sebastian Huber**, Fri, 07 Dec 2018 13:33:54 GMT

In 0a1f5df9/rtems:

```
Simplify _CPU_Counter_difference()

In order to simplify the use of CPU counter values it is beneficial to have monotonic increasing values within the range of the CPU counter ticks data type, e.g. 32-bit unsigned integer. This eases the use of CPU counter timestamps in external tools which do not know the details of the CPU counter hardware. The CPU counter is the fastest way to get a time on an RTEMS system.

Such a CPU counter may be also used as the timecounter. Use it on SPARC for this purpose to simplify the clock drivers.

Update #3456.
```

**Comment 7**

1. **Sebastian Huber**, Thu, 07 Feb 2019 07:48:53 GMT

In 0fb52ce/rtems:

```
bsps/arm: Fix generic timer frequency
Update #3456.
```

**Comment 8**

1. **Sebastian Huber**, Tue, 09 Apr 2019 05:32:17 GMT

In b8a0a496/rtems:

```
bsps/arm: Fix ARMv7-M CPU counter

Read the current counter value again after we know that we had an underflow.

Update #3456.
```

**Comment 9**

1. **Sebastian Huber**, Tue, 09 Apr 2019 06:11:42 GMT

In 222570a/rtems:

```
bsps/arm: Optimize ARMv7-M CPU counter
Update #3456.
```

#### **Comment 10**

1. **Sebastian Huber**, Thu, 19 Dec 2019 08:07:34 GMT
2. **milestone**: changed from **5.1** to **6.1**

#### **Comment 11**

1. **Christian Mauderer**, Mon, 20 Apr 2020 06:30:19 GMT
2. **blockedby**: set to **3961**

#### **Comment 12**

1. **Sebastian Huber**, Fri, 09 Sep 2022 05:46:03 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 270200e/rtems:

```
score: Remove _CPU_Counter_difference()
```

```
All CPU ports used the same _CPU_Counter_difference() implementation. Remove this CPU port interface and mandate a monotonically increasing CPU counter.
```

```
Close #3456.
```

#### **Comment 13**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:46:21 GMT
2. **keywords**: **qualification** added

## **3566 - Remove checks for Newlib features introduced during the RTEMS 5 development**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3566">https://devel.rtems.org/ticket/3566</a> ( <a href="https://devel.rtems.org/ticket/3566">https://devel.rtems.org/ticket/3566</a> )
<b>Id</b>	3566
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	22 October 2018 06:02:08
<b>Modified</b>	26 January 2022 13:36:18
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

Remove checks for O\_DIRECTORY, O\_CLOEXEC and O\_NOFOLLOW.

#### **Comment 1**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:36:18 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**
4. **component**: changed from **unspecified** to **build**

This was done as a side-effect of the new build system.

## **3584 - Remove types which are only available if RTEMS\_DEPRECATED\_TYPES is defined**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3584">https://devel.rtems.org/ticket/3584</a> ( <a href="https://devel.rtems.org/ticket/3584">https://devel.rtems.org/ticket/3584</a> )
<b>Id</b>	3584
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 12:36:56
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	

---

**Description**

The types

- `boolean`,
- `single_precision`,
- `double_precision`,
- `rtems_single`,
- `rtems_double`, and
- `rtems_boolean`.

are only available if `RTEMS_DEPRECATED_TYPES` is defined. They are deprecated for a long time. Remove them in this release.

**Comment 1**

1. **Sebastian Huber**, Thu, 08 Nov 2018 07:11:19 GMT

In a9767a07/rtems:

```
score: Use RTEMS_DEPRECATED for deprecated types
Update #3584.
```

**Comment 2**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 3**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:27:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 2adf328/rtems:

```
rtems: Remove support for RTEMS_DEPRECATED_TYPES
Close #3584.
```

**Comment 4**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
  2. **keywords**: **qualification** added
- 

**3586 - Remove deprecated `proc_ptr` definition**



---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3586">https://devel.rtems.org/ticket/3586</a> ( <a href="https://devel.rtems.org/ticket/3586">https://devel.rtems.org/ticket/3586</a> )
<b>Id</b>	3586
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 12:39:29
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3585

---

**Description****Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:19:05 GMT
2. **blocking**: set to **3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:27:14 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 53a5af2/rtems:

```
rtems: Remove deprecated proc_ptr definition
Close #3586.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
  2. **keywords**: **qualification** added
- 

**3588 - Remove deprecated rtems\_context**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3588">https://devel.rtems.org/ticket/3588</a> ( <a href="https://devel.rtems.org/ticket/3588">https://devel.rtems.org/ticket/3588</a> )
<b>Id</b>	3588
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 12:43:40
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3587

---

**Description****Comment 1**

1. **Sebastian Huber**, Wed, 07 Nov 2018 12:45:29 GMT
2. **blockedby**: changed from **3587** to **3587, 3589**

**Comment 2**

1. **Sebastian Huber**, Wed, 07 Nov 2018 12:45:47 GMT
2. **blockedby**: changed from **3587, 3589** to **3587**

**Comment 3**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 4**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:56 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In df2dac3/rtems:

```
rtems: Remove rtems_context
```

```
This type was deprecated in RTEMS 5.1.
```

```
Close #3588.
```

**Comment 5**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
2. **keywords**: **qualification** added

**3590 - Remove deprecated rtems\_context\_fp**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3590">https://devel.rtems.org/ticket/3590</a> ( <a href="https://devel.rtems.org/ticket/3590">https://devel.rtems.org/ticket/3590</a> )
<b>Id</b>	3590
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 12:47:08
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3589

**Description****Comment 1**

1. **Sebastian Huber**, Wed, 07 Nov 2018 12:49:28 GMT
2. **blockedby**: changed from **3589** to **3589, 3591**

**Comment 2**

1. **Sebastian Huber**, Wed, 07 Nov 2018 12:49:41 GMT
2. **blockedby**: changed from **3589, 3591** to **3589**

**Comment 3**

1. **Sebastian Huber**, Wed, 07 Nov 2018 12:50:54 GMT
2. **version**: changed from **5** to **6**
3. **milestone**: changed from **5.1** to **6.1**

**Comment 4**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT

2. **blocking**: set to **3993**

#### Comment 5

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:59 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In f8998f1/rtems:

```
rtems: Remove rtems_context_fp
This type was deprecated in RTEMS 5.1.
Close #3590.
```

#### Comment 6

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
2. **keywords**: **qualification** added

### **3592 - Remove deprecated region\_information\_block**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3592">https://devel.rtems.org/ticket/3592</a> ( <a href="https://devel.rtems.org/ticket/3592">https://devel.rtems.org/ticket/3592</a> )
<b>Id</b>	3592
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 12:50:21
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3591

#### **Description**

#### Comment 1

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

#### Comment 2

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:27:03 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 1546b1c0/rtems:

```
rtems: Remove region_information_block
This type was deprecated in RTEMS 5.1.
Close #3592.
```

#### Comment 3

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
2. **keywords**: **qualification** added

### **3594 - Remove deprecated rtems\_thread\_cpu\_usage\_t**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3594">https://devel.rtems.org/ticket/3594</a> ( <a href="https://devel.rtems.org/ticket/3594">https://devel.rtems.org/ticket/3594</a> )
<b>Id</b>	3594
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 12:53:29
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3593

---

**Description****Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:27:06 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 312fcf2/rtems:

```
rtems: Remove rtems_thread_cpu_usage_t
This type was deprecated in RTEMS 5.1.
Close #3594.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
  2. **keywords**: **qualification** added
- 

**3596 - Remove deprecated rtems\_rate\_monotonic\_period\_time\_t**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3596">https://devel.rtems.org/ticket/3596</a> ( <a href="https://devel.rtems.org/ticket/3596">https://devel.rtems.org/ticket/3596</a> )
<b>Id</b>	3596
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2018 13:01:09
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3595

---

**Description****Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:53 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 65dc040/rtems:

```
rtems: Remove rtems_rate_monotonic_period_time_t
This type was deprecated in RTEMS 5.1.
Close #3596.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
2. **keywords**: **qualification** added

**3613 - Remove m32c architecture port from upstream tools**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3613">https://devel.rtems.org/ticket/3613</a> ( <a href="https://devel.rtems.org/ticket/3613">https://devel.rtems.org/ticket/3613</a> )
<b>Id</b>	3613
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 November 2018 08:59:20
<b>Modified</b>	21 December 2021 15:11:17
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	arch/m32c
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3599

**Description**

The m32c architecture port was removed in RTEMS 5.1. Remove RTEMS-specific support in the upstream tools, e.g. Binutils and GCC.

**Comment 1**

1. **Sebastian Huber**, Mon, 19 Nov 2018 08:59:54 GMT
2. **blockedby**: set to **3599**

**Comment 2**

1. **Joel Sherrill**, Fri, 17 Dec 2021 16:10:41 GMT

Patch for GCC submitted: <https://gcc.gnu.org/pipermail/gcc-patches/2021-December/587094.html>

Nothing beyond pattern matching in stanzas in ld/configure.tgt and bfd/config.bfd. Asked on binutils mailing list if there is anything to do.

**Comment 3**

1. **Joel Sherrill**, Tue, 21 Dec 2021 15:08:30 GMT

GCC commit pushed here:

<https://gcc.gnu.org/g:1f56dbe2daaa5931356d0018c2c2c17bb4691d0e>

GCC WWW commit pushed here:

<https://gcc.gnu.org/git/?p=gcc-wwwdocs.git;a=commit;h=e8c01982ea7abc0acc0c4a52552ca8786abaa4fb>

Binutils-GDB commit pushed here:

<https://sourceware.org/git?p=binutils-gdb.git;a=commit;h=ae47e3097e9f0608490ed4a53c1710301d409ad1>

**Comment 4**

1. **Joel Sherrill**, Tue, 21 Dec 2021 15:11:17 GMT
2. **status**: changed from **assigned** to **closed**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

3. **resolution:** set to **fixed**

## **3615 - Convert Tools\_Used Wiki page into Support Tools Selection with Criteria**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3615">https://devel.rtems.org/ticket/3615</a> ( <a href="https://devel.rtems.org/ticket/3615">https://devel.rtems.org/ticket/3615</a> )
<b>Id</b>	3615
<b>Reporter</b>	shashvat jain
<b>Created</b>	22 November 2018 13:43:43
<b>Modified</b>	29 November 2022 21:44:27
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	normal
<b>Keywords</b>	Wiki
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Originally, this ticket requested that ToolStatus? and Tools\_Used wiki pages be addressed. ToolStatus? was horribly out of date and removed. This leaves Tools\_Used as a list of the tools used at a point in time. This list needs to be updated and grown into a Support Tools section of the Software Engineering Guide. Beyond a list of the tools and their use with RTEMS, it should discuss the attribute(s) that led to the tools selection.

Original ticket description below:

<https://devel.rtems.org/wiki/TBR/Review/ToolStatus> This page's data is very old and needs to be updated so that it can be added to the wiki with a link to the home page name "Development Tools".

All the data about the tools on the page must be updated to the latest used by RTEMS 5, this new page can either be added to the page [https://devel.rtems.org/wiki/Tools\\_Used](https://devel.rtems.org/wiki/Tools_Used) or be made into a separate page altogether. Advice on the placement of the new page is needed.

### Comment 1

1. **Gedare Bloom**, Thu, 22 Nov 2018 15:02:16 GMT
2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **assigned**

### Comment 2

1. **Joel Sherrill**, Thu, 22 Nov 2018 15:56:20 GMT

Given the age of this information, I would say delete the page and fix references. Is there anything of value left in it?

### Comment 3

1. **Chris Johns**, Fri, 23 Nov 2018 00:27:54 GMT

I can see no value in either page. Please delete the pages and close this ticket.

### Comment 4

1. **shashvat jain**, Fri, 23 Nov 2018 03:39:39 GMT

Does this wiki already has a "development tools" page, the information is quite old, is it worth deleting these and adding a new one which are updated?

### Comment 5

1. **Chris Johns**, Fri, 23 Nov 2018 03:51:02 GMT

Replying to shashvat jain:

Does this wiki already has a "development tools" page, the information is quite old, is it worth deleting these and adding a new one which are updated?

No it does have one. A wiki page for this type of thing for RTEMS is difficult to get right. The issues are:

Each version of RTEMS has a specific set of tools so a single page would not work. The tool matrix is complex with different versions of the various tools for different architectures and then differences for these for different hosts. You can see this by looking at the build output from the RSB on the build list, for example a recent ARM build (<https://lists.rtems.org/pipermail/build/2018-November/001318.html>) The last section is the build report that lists the files and patches. The term "Tools" covers the compiler and its tools plus it now it includes the various eco-system tools. The size of the page would be large and getting all the detail right would be an busy long term task.

### Comment 6

1. **shashvat jain**, Fri, 23 Nov 2018 06:09:02 GMT

Replying to Chris Johns:

Replying to shashvat jain:

Does this wiki already has a "development tools" page , the information is quite old , is it worth deleting these and adding a new one which are updated?

No it does have one. A wiki page for this type of thing for RTEMS is difficult to get right. The issues are:

Each version of RTEMS has a specific set of tools so a single page would not work. The tool matrix is complex with different versions of the various tools for different architectures and then differences for these for different hosts. You can see this my looking at the build output from the RSB on the build list, for example a recent ARM build (<https://lists.rtems.org/pipermail/build/2018-November/001318.html>) The last section is the build report that lists the files and patches. The term "Tools" covers the compiler and its tools plus it now it includes the various eco-system tools. The size of the page would be large and getting all the detail right would be an busy long term task.

1)We may add the page for the current version under development 5 2)Instead of a tool matrix , we can mention all the tools shared by architectures like gdb , gcc newlib , g++ , binutils , etc . 3)If the term tools covers so much then can we make a document covering everything about the compiler ? , if we spend some time and make it , the next step left would be just to update it timely when the version changes.

Do you think it is worth the time and effort of updating?

#### Comment 7

1. **Chris Johns**, Sun, 25 Nov 2018 00:08:37 GMT

Replying to shashvat jain:

1)We may add the page for the current version under development 5

What happens for RTEMS 6 or 7 etc?

2)Instead of a tool matrix , we can mention all the tools shared by architectures like gdb , gcc newlib , g++ , binutils , etc .

This changes all the time.

3)If the term tools covers so much then can we make a document covering everything about the compiler ? , if we spend some time and make it , the next step left would be just to update it timely when the version changes.

We have this in the documentation ...

<https://docs.rtems.org/branches/master/user/tools/index.html>

Do you think it is worth the time and effort of updating?

No I do not think it is worth updating. A better solution is add to the RSB a way to generate the reports we need.

Chris

#### Comment 8

1. **shashvat jain**, Sun, 25 Nov 2018 06:58:35 GMT

Replying to Chris Johns:

Replying to shashvat jain:

1)We may add the page for the current version under development 5

What happens for RTEMS 6 or 7 etc?

2)Instead of a tool matrix , we can mention all the tools shared by architectures like gdb , gcc newlib , g++ , binutils , etc .

This changes all the time.

3)If the term tools covers so much then can we make a document covering everything about the compiler ? , if we spend some time and make it , the next step left would be just to update it timely when the version changes.

We have this in the documentation ...

<https://docs.rtems.org/branches/master/user/tools/index.html>

Do you think it is worth the time and effort of updating?

No I do not think it is worth updating. A better solution is add to the RSB a way to generate the reports we need.

Chris

All my doubts are solved , I have no reason to stop you from closing this Ticket . Thank you

**Comment 9**

1. **Joel Sherrill**, Fri, 13 Dec 2019 15:31:06 GMT

I just removed <https://devel.rtems.org/wiki/TBR/Review/ToolStatus> since it had very out of date information.

[https://devel.rtems.org/wiki/Tools\\_Used](https://devel.rtems.org/wiki/Tools_Used) is a modest version of what we want in the Software Engineering Guide for documenting supporting tools.

**Comment 10**

1. **Joel Sherrill**, Fri, 13 Dec 2019 15:40:28 GMT

2. **summary**: changed from **[Wiki]Update data on development tools and Find a new home for it.** to **Convert Tools\_Used Wiki page into Support Tools Selection with Criteria**

3. **description**: modified (diff)

4. **milestone**: changed from **5.1** to **6.1**

**Comment 11**

1. **Chris Johns**, Tue, 29 Nov 2022 21:44:27 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **wontfix**

This should be in the User Guide.

**3657 - Add support for poll.h method - poll**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3657">https://devel.rtems.org/ticket/3657</a> ( <a href="https://devel.rtems.org/ticket/3657">https://devel.rtems.org/ticket/3657</a> )
<b>Id</b>	3657
<b>Reporter</b>	Marçal Comajoan Cara
<b>Created</b>	11 December 2018 16:35:18
<b>Modified</b>	3 December 2021 20:50:09
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	POSIX-Compliance
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

According to the RTEMS POSIX 1003.1 Compliance Guide, `poll()` from `poll.h` is not supported (<https://docs.rtems.org/branches/master/posix-compliance/posix-compliance.html#poll-h>)

PS: I wrote the test for POSIX API Signature Compliance Test and it compiled correctly but I suppose that some things are still not fully supported.

**Comment 1**

1. **Marçal Comajoan Cara**, Tue, 11 Dec 2018 19:23:39 GMT

In 6ab788d/rtems:

```
psxhdrs: Implement POSIX API Signature Compliance Tests for poll.h (GCI 2018)
poll.h implements poll() which is not supported by RTEMS according to the RTEMS POSIX 1003.1 Compliance Guide. See #3657.
This work was part of GCI 2018.
```

**Comment 2**

1. **Joel Sherrill**, Fri, 03 Dec 2021 20:50:09 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **fixed**

4. **milestone**: changed from **Indefinite** to **6.1**

`poll()` is in `rtems-libbsd`. Compliance spreadsheet updated.



**3659 - LEON3 kernel entry point is overwritten - secondary processors may enter into spurious handler**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3659">https://devel.rtems.org/ticket/3659</a> ( <a href="https://devel.rtems.org/ticket/3659">https://devel.rtems.org/ticket/3659</a> )
<b>Id</b>	3659
<b>Reporter</b>	Martin Aberg
<b>Created</b>	13 December 2018 14:55:49
<b>Modified</b>	29 September 2021 13:28:14
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

When linking a LEON3 RTEMS SMP application, the entry point in the ELF output file is set to the symbol "start".

"start" is the first entry in the trap table and directly jumps to "hard\_reset".

The boot CPU does the following in the boot\_card():

- Release other CPUs from power-down (but does not wait here)
- Some other initializations
- Overwrite trap entry 0 with spurious interrupt handler
- The rest

It means that the entry point is guaranteed to be valid for the first CPU entering the RTEMS kernel. But 1. and 3. above gives a race. non-first CPU:s will either enter the kernel properly or end up in the spurious interrupt handler depending on how quick it reaches the "start" label.

One example where this has been an issue is when secondary processors run for some time (self-tests) in a ROM boot loader before entering the RTEMS (ELF) entry point. It is convenient to use the ELF file entry point for all processors.

Possible solutions:

- a.  
Do not install spurious handler on trap table entry 0. For example by changing bsp/sparc/leon3/start/spurious.c:

```
- for ( trap=1 ; trap<256 ; trap++ ) {
+ for ( trap=0 ; trap<256 ; trap++ ) {
```

(This changes address 0 on GR740. So following a null function pointer may not end up in spurious trap anymore.)

- b.  
Change the SPARC ELF entry point. For example to the symbol hard\_reset.
- c.  
Document that the entry point for boot processor is "start" and entry point for other processors is "hard\_reset".

**Comment 1**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** qualification added

**Comment 2**

1. **Sebastian Huber**, Thu, 02 Sep 2021 05:57:51 GMT
2. **milestone:** set to 6.1

This was fixed by #4459. The trap table is now read-only.

**Comment 3**

1. **Sebastian Huber**, Wed, 29 Sep 2021 13:28:14 GMT
  2. **status:** changed from new to closed
  3. **resolution:** set to fixed
- 

**3689 - bdbuf: Replace automatic read-ahead with rtems\_bdbuf\_peek()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3689">https://devel.rtems.org/ticket/3689</a> ( <a href="https://devel.rtems.org/ticket/3689">https://devel.rtems.org/ticket/3689</a> )
<b>Id</b>	3689
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 February 2019 10:49:25
<b>Modified</b>	7 April 2021 05:04:32
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	lib/block
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The block device cache (bdbuf) tries to deduce a read ahead opportunity from the read access pattern. Using real world FAT file systems showed that this is not very reliable and the read ahead seldom happens. One way to fix this issue is let file systems give a hint to the block device cache that they will likely read a certain block in the future, e.g. the next block in a sequential file read. Remove the existing read ahead logic and add a new function `rtems_bdbuf_peek()` instead.

**Attachments:**

- 
- 1 **Sebastian Huber, Mon, 11 Feb 2019 10:49:48 GMT**  
**attach:** set to [0001-FIXME-bdbuf-Add-rtems\\_bdbuf\\_peek.patch](https://devel.rtems.org/ticket/3689/0001-FIXME-bdbuf-Add-rtems_bdbuf_peek.patch) ([https://devel.rtems.org/ticket/3689/0001-FIXME-bdbuf-Add-rtems\\_bdbuf\\_peek.patch](https://devel.rtems.org/ticket/3689/0001-FIXME-bdbuf-Add-rtems_bdbuf_peek.patch))
- 

**Comment 1**

1. **Chris Johns, Mon, 11 Feb 2019 11:03:03 GMT**

Why is the status returned from the peek in `fat_file_read` not checked?

**Comment 2**

1. **Sebastian Huber, Mon, 11 Feb 2019 11:04:30 GMT**

The data is not used yet. It is just a hint, maybe we should remove a return code from `rtems_bdbuf_peek()`.

**Comment 3**

1. **Chris Johns, Mon, 11 Feb 2019 11:09:51 GMT**

I would not remove the return code, it may be used in another file system.

**Comment 4**

1. **Sebastian Huber, Thu, 19 Dec 2019 08:07:34 GMT**  
 2. **milestone:** changed from **5.1** to **6.1**

**Comment 5**

1. **Christian Mauderer, Fri, 26 Mar 2021 13:28:22 GMT**

In [6ae79e6/rtems](#):

```
libblock: Add rtems_bdbuf_peek()
```

Adds a peek function that allows (for example) a file system to suggest the next blocks that should be used for read ahead. This can increase the read speed of fragmented files.

Update #3689

**Comment 6**

1. **Christian Mauderer, Fri, 26 Mar 2021 13:28:26 GMT**  
 2. **status:** changed from **assigned** to **closed**  
 3. **resolution:** set to **fixed**

In [fd639b8/rtems](#):

```
dosfs: Use peek support
```

This speeds up reading fragmented files.

Fix #3689

### Comment 7

1. **Sebastian Huber**, Wed, 07 Apr 2021 05:04:32 GMT

In b3364fc6/rtems:

```
libtests/block14: Fix warning
Fix warning:
testsuites/libtests/block14/init.c:198:8: warning: 'sc' may be used
```

```
uninitialized in this function [-Wmaybe-uninitialized]
```

Update #3689.

## 3698 - libdl failure on many PowerPC BSPs

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3698">https://devel.rtems.org/ticket/3698</a> ( <a href="https://devel.rtems.org/ticket/3698">https://devel.rtems.org/ticket/3698</a> )
<b>Id</b>	3698
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 February 2019 16:14:30
<b>Modified</b>	16 December 2021 22:18:34
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	worksforme
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The following BSPs do not build dl09:

```
powerpc-beatnik
powerpc-brs5l
powerpc-brs6l
powerpc-dp2
powerpc-haleakala
powerpc-icecube
powerpc-mcp750
powerpc-mpc8260ads
powerpc-mtx603e
powerpc-mvme2100
powerpc-mvme2307
powerpc-mvme3100
powerpc-mvme5500
powerpc-pm520_cr825
powerpc-pm520_ze30
powerpc-qemuprep-altivec
powerpc-qemuprep
powerpc-qorig_e6500_64
powerpc-ss555
powerpc-virtex4
powerpc-virtex5
```

They fail with this:

```

gmake[5]: Entering directory `/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemuprep-rtems/powerpc-
rtems5/c/qemuprep/testsuites/libtests'
powerpc-rtems5-gcc -mcpu=powerpc -mmultiple -mstring -mstrict-align -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-
prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -Wl,--gc-sections -mcpu=powerpc -mmultiple -
mstring -mstrict-align -B./../lib/libbsp/powerpc/motorola/powerpc -B/home/joel/rtems-work/rtems-
testing/rtems/rtems/bsps/powerpc/motorola/powerpc/start -specs bsp_specs -qrtems -L./../cpukit -L/home/joel/rtems-work/rtems-
testing/rtems/rtems/bsps/powerpc/shared/start -Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -o dl01.pre dl01/dl01-init.o
dl01/dl01-dl-load.o dl01-dl01-tar.o ./../lib/libbsp/powerpc/motorola/powerpc/librtemsbsp.a ./../cpukit/librtemscpu.a
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: ./../cpukit/librtemscpu.a(rtl-
mdreloc-powerpc.o): in function `get_sdata libdl_size':
/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemuprep-rtems/powerpc-
rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-mdreloc-powerpc.c:73: undefined reference to
`bsp_section_sdata libdl_begin'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: /home/joel/rtems-work/rtems-
testing/rtems/build-powerpc-qemuprep-rtems/powerpc-rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-
mdreloc-powerpc.c:73: undefined reference to `bsp_section_sdata libdl_end'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: /home/joel/rtems-work/rtems-
testing/rtems/build-powerpc-qemuprep-rtems/powerpc-rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-
mdreloc-powerpc.c:74: undefined reference to `bsp_section_sdata libdl_end'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: /home/joel/rtems-work/rtems-
testing/rtems/build-powerpc-qemuprep-rtems/powerpc-rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-
mdreloc-powerpc.c:74: undefined reference to `bsp_section_sdata libdl_end'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: ./../cpukit/librtemscpu.a(rtl-
mdreloc-powerpc.o): in function `get_sdata sbss_size':
/home/joel/rtems-work/rtems-testing/rtems/build-powerpc-qemuprep-rtems/powerpc-
rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-mdreloc-powerpc.c:63: undefined reference to
`bsp_section_sdata begin'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: /home/joel/rtems-work/rtems-
testing/rtems/build-powerpc-qemuprep-rtems/powerpc-rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-
mdreloc-powerpc.c:63: undefined reference to `bsp_section_sdata begin'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: /home/joel/rtems-work/rtems-
testing/rtems/build-powerpc-qemuprep-rtems/powerpc-rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-
mdreloc-powerpc.c:64: undefined reference to `bsp_section_sbss_end'
/home/joel/rtems-work/tools/5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld: /home/joel/rtems-work/rtems-
testing/rtems/build-powerpc-qemuprep-rtems/powerpc-rtems5/c/qemuprep/cpukit/../../../../rtems/c/src/../../../../cpukit/libdl/rtl-
mdreloc-powerpc.c:64: undefined reference to `bsp_section_sbss_end'
collect2: error: ld returned 1 exit status

```

### Comment 1

1. **Chris Johns**, Thu, 21 Feb 2019 21:35:03 GMT

Why do we have linkcmds.base and linkcmds.share in this arch and what are there differences? Why are the names similar?

I cannot find a any local readme type files explaining the reason there are two files. The git log entry for the addition of this file offers no insight.

At a guess the addition of mpc55xx as a new BSP required a new linkcmd file, which is fine, however an explanation on difference and rational would be helpful to me at this point.

### Comment 2

1. **Sebastian Huber**, Fri, 22 Feb 2019 10:04:59 GMT

The reason for this is excessive use of copy and paste in the past combined with the long history of the PowerPC port.

The bsp/powerpc/shared/start/linkcmds.base is similar to the bsp/arm/shared/start/linkcmds.base or bsp/riscv/shared/start/linkcmds.base. It uses memory regions and should be used for new BSPs.

The 64-bit PowerPC ELFv2 ABI has no small data area.

### Comment 3

1. **Chris Johns**, Sat, 23 Feb 2019 23:32:17 GMT

I now see there are a couple of other BSP specific linkcmds files all of which need to be modified.

I am now seeing:

```

gmake[5]: Entering directory '/opt/work/chris/rtems/kernel/bsps/psim/powerpc-rtems5/c/mpc5643l_dpu/testsuites/sptests'
powerpc-rtems5-gcc -mcpu=8540 -meabi -msdata=sysv -fno-common -msoft-float -mno-spe -mstrict-align -O2 -g -fno-keep-inline-
functions -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -
Wnested-externs -B./../lib/libbsp/powerpc/mpc55xxevb -B/opt/work/chris/rtems/kernel/rtems.git/bsps/powerpc/mpc55xxevb/start -
specs bsp_specs -qrtems -L./../cpukit -L/opt/work/chris/rtems/kernel/rtems.git/bsps/powerpc/shared/start -Wl,--wrap=printf -Wl,--
wrap=puts -Wl,--wrap=putchar -Wl,--gc-sections -o sp47.exe sp47/sp47-init.o ./../lib/libbsp/powerpc/mpc55xxevb/librtemsbsp.a
./../cpukit/librtemscpu.a
/opt/work/rtems5/lib/gcc/powerpc-rtems5/7.4.0/../../../../powerpc-rtems5/bin/ld:linkcmds.mpc55xx:18 cannot move location counter
backwards (from 00000000400165c0 to 0000000040010000)
collect2: error: ld returned 1 exit status
gmake[5]: *** [Makefile:5229: sp47.exe] Error 1

```

and this does not look related to what I have been working on. Is this test too big for this target?

### Comment 4

1. **Chris Johns**, Sat, 23 Feb 2019 23:59:32 GMT

Further investigation of the mpc5643l\_dpu BSP I see a lot of tests are failing to link. I think this BSP should have all tests disabled, sorry I have no capacity to maintaining this stuff.

What has changed in RTEMS to cause the tests to overflow the memory area? Is a bisect needed?

I will now look at adding regx support to the .tcfg files so wildcards can be supported. To exclude all tests:

```
rexclude *
```

can be used as a simple way to disable all tests. I may consider rexclude and rinclude as an order set of filters so:

```
rexclude *
rinclude samples/*
```

This syntax introduces the / delimiter so specific groups can be filtered.

**Comment 5**

1. **Sebastian Huber**, Mon, 25 Feb 2019 06:16:13 GMT

The reason for the recent link-time errors on some small memory BSPs is the change from workspace initialization to static allocation for the objects. I work on this already, but is a bit tedious. My approach is to add some general \*.tcfg files like this:

```
testsuites/testdata/disable-256k-data-or-more-tests.tcfg testsuites/testdata/disable-128k-data-or-more-tests.tcfg testsuites/testdata/disable-64k-data-or-more-tests.tcfg testsuites/testdata/disable-32k-data-or-more-tests.tcfg
```

**Comment 6**

1. **Chris Johns**, Wed, 26 Feb 2020 03:53:03 GMT
2. **milestone**: changed from **5.1** to **6.1**

**Comment 7**

1. **Chris Johns**, Sun, 07 Feb 2021 22:11:02 GMT

What is the status of this ticket?

**Comment 8**

1. **Chris Johns**, Sun, 07 Feb 2021 22:11:42 GMT
2. **owner**: **Chris Johns** deleted
3. **status**: changed from **assigned** to **new**

**Comment 9**

1. **Ryan Long**, Thu, 16 Dec 2021 22:18:11 GMT

Test built for the beatnik BSP

**Comment 10**

1. **Ryan Long**, Thu, 16 Dec 2021 22:18:34 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **workforme**

**3702 - Space profile for RTEMS SMP**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3702">https://devel.rtems.org/ticket/3702</a> ( <a href="https://devel.rtems.org/ticket/3702">https://devel.rtems.org/ticket/3702</a> )
<b>Id</b>	3702
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	26 February 2019 10:33:00
<b>Modified</b>	3 December 2021 05:54:40
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3701
<b>Blocked by</b>	

**Description**

Define a subset of RTEMS SMP functionality which is

- useful for space applications, and
- can be pre-qualified by project #3701.

To figure out the feature set carry out an online survey. In addition, do a workshop at ESA/ ESTEC premises (also accessible on-line via Skype for Business).

The space profile needs to be documented.

**Comment 1**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:30:45 GMT
2. **status**: changed from **assigned** to **accepted**

**Comment 2**

1. **Sebastian Huber**, Fri, 19 Nov 2021 14:44:03 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

The Technical Note: Space Profile is finalized:

<https://ftp.rtems.org/pub/rtems/people/sebh/tn-space-profile-r6-23062019.pdf>

Please note that the pre-qualified feature set of RTEMS is a proper superset of the space profile.

**Comment 3**

1. **Joel Sherrill**, Fri, 19 Nov 2021 14:56:54 GMT

Would it be possible to generate a document similar to the one you linked to which documents that superset? Asked another way, how could someone approaching RTEMS.org know the subset of RTEMS which has the supporting artifacts for pre-qualification?

**Comment 4**

1. **Sebastian Huber**, Fri, 19 Nov 2021 15:00:19 GMT

Yes, this is possible, but I think this belongs to another ticket. I am currently busy with integrating all my work in progress.

**Comment 5**

1. **Sebastian Huber**, Thu, 02 Dec 2021 11:10:16 GMT

Just for reference, a list of pre-qualified interfaces can be obtained via the `./specview.py --filter=api`.

```
Application Configuration Information
rtems_configuration_get_idle_task
rtems_configuration_get_idle_task_stack_size
rtems_configuration_get_interrupt_stack_size
rtems_configuration_get_maximum_barriers
rtems_configuration_get_maximum_extensions
rtems_configuration_get_maximum_message_queues
rtems_configuration_get_maximum_partitions
rtems_configuration_get_maximum_periods
rtems_configuration_get_maximum_processors
rtems_configuration_get_maximum_semaphores
rtems_configuration_get_maximum_tasks
rtems_configuration_get_maximum_timers
rtems_configuration_get_microseconds_per_tick
rtems_configuration_get_milliseconds_per_tick
rtems_configuration_get_nanoseconds_per_tick
rtems_configuration_get_stack_allocate_for_idle_hook
rtems_configuration_get_stack_allocate_hook
rtems_configuration_get_stack_allocator_avoids_work_space
rtems_configuration_get_stack_free_hook
rtems_configuration_get_ticks_per_timeslice
Barrier Manager
rtems_barrier_create
rtems_barrier_delete
rtems_barrier_ident
rtems_barrier_release
rtems_barrier_wait
Base Definitions
RTEMS_ALIAS
RTEMS_ALIGNED
RTEMS_ALIGNOF
RTEMS_ALIGN_DOWN
RTEMS_ALIGN_UP
RTEMS_ALLOC_ALIGN
RTEMS_ALLOC_SIZE
RTEMS_ARRAY_SIZE
RTEMS_COMPILER_MEMORY_BARRIER
RTEMS_CONCAT
RTEMS_CONTAINER_OF
RTEMS_DECLARE_GLOBAL_SYMBOL
RTEMS_DECONST
RTEMS_DEFINE_GLOBAL_SYMBOL
RTEMS_DEQUALIFY
RTEMS_DEQUALIFY_DEPTHX
RTEMS_DEVOLATILE
RTEMS_EXPAND
RTEMS_HAVE_MEMBER_SAME_TYPE
RTEMS_OBFUSCATE_VARIABLE
RTEMS_PREDICT_FALSE
RTEMS_PREDICT_TRUE
RTEMS_PRINTFLIKE
RTEMS_RETURN_ADDRESS
RTEMS_SECTION
RTEMS_STATIC_ASSERT
RTEMS_STRING
RTEMS_SYMBOL_NAME
RTEMS_TYPEOF_REFX
RTEMS_UNREACHABLE
RTEMS_WEAK_ALIAS
RTEMS_XCONCAT
RTEMS_XSTRING_C
and
POSIX
clock_nanosleep
fsl_memcpy
memset_posix
memalign
CPU Usage Reporting
rtems_cpu_usage_reset
Cache Manager
rtems_cache_disable_data
rtems_cache_disable_instruction
rtems_cache_enable_data
rtems_cache_enable_instruction
rtems_cache_flush_entire_data
rtems_cache_flush_multiple_data_lines
rtems_cache_get_data_cache_size
rtems_cache_get_data_line_size
rtems_cache_get_instruction_cache_size
rtems_cache_get_instruction_line_size
rtems_cache_get_maximal_line_size
rtems_cache_instruction_sync_after_code_change
rtems_cache_invalidate_entire_data
rtems_cache_invalidate_entire_instruction
rtems_cache_invalidate_multiple_data_lines
rtems_cache_invalidate_multiple_instruction_lines
Classic API Configuration
CONFIGURE_MAXIMUM_BARRIERS
CONFIGURE_MAXIMUM_MESSAGE_QUEUES
CONFIGURE_MAXIMUM_PARTITIONS
CONFIGURE_MAXIMUM_PERIODS
CONFIGURE_MAXIMUM_SEMAPHORES
CONFIGURE_MAXIMUM_TASKS
CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE
CONFIGURE_MAXIMUM_TIMERS
CONFIGURE_MAXIMUM_USER_EXTENSIONS
CONFIGURE_MINIMUM_TASKS_WITH_USER_PROVIDED_STORAGE
Classic API Initialization Task Configuration
CONFIGURE_INIT_TASK_ARGUMENTS
CONFIGURE_INIT_TASK_ATTRIBUTES
CONFIGURE_INIT_TASK_CONSTRUCT_STORAGE_SIZE
CONFIGURE_INIT_TASK_ENTRY_POINT
CONFIGURE_INIT_TASK_INITIAL_MODES
CONFIGURE_INIT_TASK_NAME
CONFIGURE_INIT_TASK_PRIORITY
CONFIGURE_RTEMS_INIT_TASKS_TABLE
Clock Manager
rtems_clock_get_boot_time
rtems_clock_get_boot_time_bintime
rtems_clock_get_boot_time_timeval
rtems_clock_get_monotonic
rtems_clock_get_monotonic_bintime
rtems_clock_get_monotonic_coarse
rtems_clock_get_monotonic_coarse_bintime
rtems_clock_get_monotonic_coarse_timeval
rtems_clock_get_monotonic_sbintime
rtems_clock_get_monotonic_timeval
rtems_clock_get_realtime
rtems_clock_get_realtime_bintime
rtems_clock_get_realtime_coarse
rtems_clock_get_realtime_coarse_bintime
rtems_clock_get_realtime_coarse_timeval
rtems_clock_get_realtime_timeval
rtems_clock_get_ticks_per_second
rtems_clock_get_ticks_since_boot
rtems_clock_get_tod
rtems_clock_get_device_driver_configuration
CONFIGURE_APPLICATION_DOES_NOT_NEED_CLOCK_DRIVER
CONFIGURE_APPLICATION_NEEDS_CLOCK_DRIVER
Directive Status Codes
rtems_are_statuses_equal
rtems_is_status_successful
rtems_status_text
Dynamic Memory Allocation
rtems_calloc
rtems_malloc
Event Manager
rtems_event_receive
rtems_event_send
Fatal Error Manager
rtems_fatal
Filesystem Configuration
CONFIGURE_APPLICATION_DISABLE_FILESYSTEM
General Scheduler Configuration
CONFIGURE_MAXIMUM_PRIORITY
CONFIGURE_SCHEDULER_ASSIGNMENTS
CONFIGURE_SCHEDULER_EDF_SMP
CONFIGURE_SCHEDULER_NAME
CONFIGURE_SCHEDULER_PRIORITY
General System Configuration
CONFIGURE_DISABLE_BSP_SETTINGS
CONFIGURE_DISABLE_NEWLIB_REENTRANCY
CONFIGURE_INITIAL_EXTENSIONS
CONFIGURE_INTERRUPT_STACK_SIZE
CONFIGURE_MAXIMUM_FILE_DESCRIPTOR
CONFIGURE_MAXIMUM_PROCESSORS
CONFIGURE_MICROSECONDS_PER_TICK
CONFIGURE_MINIMUM_TASK_STACK_SIZE
CONFIGURE_TICKS_PER_TIMESLICE
Idle Task Configuration
CONFIGURE_IDLE_TASK_BODY
CONFIGURE_IDLE_TASK_INITIALIZES_APPLICATION
CONFIGURE_IDLE_TASK_STACK_SIZE
Interrupt Manager
RTEMS_INTERRUPT_ENTRY_INITIALIZER
RTEMS_INTERRUPT_LOCK_DECLARE
RTEMS_INTERRUPT_LOCK_DEFINE
RTEMS_INTERRUPT_LOCK_INITIALIZER
RTEMS_INTERRUPT_LOCK_MEMBER
RTEMS_INTERRUPT_LOCK_REFERENCE
rtems_interrupt_clear
rtems_interrupt_entry_initialize
rtems_interrupt_entry_install
rtems_interrupt_entry_remove
rtems_interrupt_get_affinity
rtems_interrupt_get_attributes
rtems_interrupt_handler_iterate
rtems_interrupt_is_pending
rtems_interrupt_local_disable
rtems_interrupt_local_enable
rtems_interrupt_lock_acquire
rtems_interrupt_lock_acquire_isr
rtems_interrupt_lock_destroy
rtems_interrupt_lock_initialize
rtems_interrupt_lock_release
rtems_interrupt_lock_release_isr
rtems_interrupt_lock_raise
rtems_interrupt_lock_raise_on
rtems_interrupt_set_affinity
rtems_interrupt_vector_disable
rtems_interrupt_vector_enable
rtems_interrupt_vector_is_enabled
Kernel Character I/O Support
getchar
rtems_put_char
rtems_putc
Message Manager
RTEMS_MESSAGE_QUEUE_BUFFER
rtems_message_queue_broadcast
rtems_message_queue_construct
rtems_message_queue_delete
rtems_message_queue_flush
rtems_message_queue_get_number_pending
rtems_message_queue_id
rtems_message_queue_receive
rtems_message_queue_send
rtems_message_queue_urgent
Newlib
Futex
Wait
Futex
Wake
Mutex
Acquire
_Mutex_Acquire_timed
_Mutex_Release
_Mutex_Try_acquire
_Mutex_recursive_Acquire
_Mutex_recursive_Acquire_timed
_Mutex_recursive_Release
_Mutex_recursive_Try_acquire
Object Services
rtems_build_name
rtems_object_get_local_node
Partition Manager
rtems_partition_create
rtems_partition_delete
rtems_partition_get_buffer
rtems_partition_ident
rtems_partition_return_buffer
Rate-Monotonic Manager
rtems_rate_monotonic_cancel
rtems_rate_monotonic_create
rtems_rate_monotonic_delete
rtems_rate_monotonic_get_status
rtems_rate_monotonic_ident
rtems_rate_monotonic_period
Scheduler Manager
rtems_scheduler_add_processor
rtems_scheduler_get_maximum_priority
rtems_scheduler_get_processor
rtems_scheduler_get_processor_maximum
rtems_scheduler_get_processor_set
rtems_scheduler_ident
rtems_scheduler_ident_by_processor
rtems_scheduler_ident_by_processor_set
rtems_scheduler_remove_processor
Semaphore Manager
rtems_semaphore_create
rtems_semaphore_delete
rtems_semaphore_flush
rtems_semaphore_ident
rtems_semaphore_obtain
rtems_semaphore_release
rtems_semaphore_set_priority
Signal Manager
rtems_signal_catch
rtems_signal_send
Support Services
rtems_is_name_valid
rtems_name_to_characters
Task Manager
RTEMS_TASK_STORAGE_SIZE
rtems_task_construct
rtems_task_create
rtems_task_delete
rtems_task_exit
rtems_task_get_affinity
rtems_task_get_priority
rtems_task_get_scheduler
rtems_task_ident
rtems_task_is_suspended
rtems_task_iterate
rtems_task_mode
rtems_task_restart
rtems_task_resume
rtems_task_self
rtems_task_set_affinity
rtems_task_set_priority
rtems_task_set_scheduler
rtems_task_start
rtems_task_suspend
rtems_task_wake_after
rtems_task_wake_when
Task Modes
RTEMS_INTERRUPT_LEVEL
Task Stack Allocator Configuration
CONFIGURE_TASK_STACK_ALLOCATOR
CONFIGURE_TASK_STACK_ALLOCATOR_AVOIDS_WORK_SPACE
```

CONFIGURE\_TASK\_STACK\_ALLOCATOR\_FOR\_IDLE CONFIGURE\_TASK\_STACK\_DEALLOCATOR Timer Manager rtems\_timer\_cancel  
 rtems\_timer\_create rtems\_timer\_delete rtems\_timer\_fire\_after rtems\_timer\_fire\_when rtems\_timer\_ident rtems\_timer\_initiate\_server rtems\_timer\_reset  
 rtems\_timer\_server\_fire\_after rtems\_timer\_server\_fire\_when User Extensions Manager rtems\_extension\_create rtems\_extension\_delete  
 rtems\_extension\_ident

**Comment 6**

1. **Joel Sherrill**, Thu, 02 Dec 2021 22:15:47 GMT

I'm sure that list is right but wasn't there a small set of POSIX APIs which were candidates? I looked for `pthread_once()` which I expected but isn't there. Was thinking of the pthread APIs which were always on before the POSIX configuration was reworked -- once and keys.

**Comment 7**

1. **Sebastian Huber**, Fri, 03 Dec 2021 05:54:40 GMT

We considered to add POSIX keys and once, but we had no time left over to do this.

**3704 - Review and update Doxygen recommendations**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3704">https://devel.rtems.org/ticket/3704</a> ( <a href="https://devel.rtems.org/ticket/3704">https://devel.rtems.org/ticket/3704</a> )
<b>Id</b>	3704
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	26 February 2019 13:10:56
<b>Modified</b>	26 July 2023 05:05:47
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3705, 3706
<b>Blocked by</b>	

**Description**

Review and update the Doxygen recommendations.

Due to the removal of the pre-install build step we can now use Doxygen directly with header files in the source tree. It should be possible to generate documentation for all architectures and BSPs.

All code files (headers, C source, assembler) should have an `@file` entry belong to at least one Doxygen group (`@ingroup`).

There are a lot of source file in RTEMS (excluding test code and legacy network stack):

```
find bsp cpukit -name '*.chsS' | grep -v libnetworking | wc
4898      4898      187167
```

Creating the groups and categorizing all code file is a labour intensive work package. Therefore it should be discussed if the `@brief` and descriptions for files should be removed. The file content will be covered by groups and individual documentation.

The use of `@param` should be clarified. It is not clear if the `[in]`, `[out]` or `[in,out]` should be used. If they should be used, what they mean exactly.

**Comment 1**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:12:31 GMT

2. **blocking**: changed from **3701** to **3701, 3705**

**Comment 2**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:23:37 GMT

2. **blocking**: changed from **3701, 3705** to **3701, 3705, 3706**

**Comment 3**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:30:16 GMT

2. **blocking**: changed from **3701, 3705, 3706** to **3705, 3706**

**Comment 4**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:30:45 GMT

2. **status**: changed from **assigned** to **accepted**

**Comment 5**

1. **Sebastian Huber**, Thu, 04 Apr 2019 05:22:51 GMT

In fbe8a7a/rtems:

doxygen: Rework some Doxygen comments  
They are intended as examples in the RTEMS Software Engineering manual.  
Update #3704.

**Comment 6**

1. **Sebastian Huber**, Thu, 04 Apr 2019 05:40:37 GMT

In 1d48fb5/rtems-docs:

bsp-howto: Move BSP Doxygen recommendations  
Update #3704.

**Comment 7**

1. **Sebastian Huber**, Fri, 05 Apr 2019 05:47:11 GMT

In 8a8b95aa/rtems:

doxygen: Update \_Objects\_Build\_name()  
This is intended as an example in the RTEMS Software Engineering manual.  
Update #3704.

**Comment 8**

1. **Sebastian Huber**, Fri, 05 Apr 2019 07:40:39 GMT

In ef19112/rtems-docs:

eng: Rework Doxygen guidelines  
Update #3704.

**Comment 9**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:51:58 GMT
2. **milestone**: changed from **6.1** to **7.1**

**Comment 10**

1. **Sebastian Huber**, Wed, 26 Jul 2023 05:05:47 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**
4. **milestone**: changed from **7.1** to **6.1**

For RTEMS 6, the guidelines in <https://docs.rtems.org/branches/master/eng/coding-doxygen.html> are good enough.

---

**3705 - Software Design Document (SDD) for space profile**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/3705">https://devel.rtems.org/ticket/3705</a> ( <a href="https://devel.rtems.org/ticket/3705">https://devel.rtems.org/ticket/3705</a> )
<b>Id</b>	3705
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	26 February 2019 13:12:31
<b>Modified</b>	23 October 2023 08:57:53
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3701
<b>Blocked by</b>	3704, 3706, 3708

**Description**

A Software Design Document (SDD) is required by ECSS-E-ST-40C specified by Annex F. The plan is to use Doxygen for the software

- architecture, and
- detailed design.

How should links to from a software component (Doxygen group) to requirements be handled?

**Comment 1**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:23:37 GMT
2. **blockedby**: changed from **3704** to **3704, 3706**

**Comment 2**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:30:45 GMT
2. **status**: changed from **assigned** to **accepted**

**Comment 3**

1. **Sebastian Huber**, Tue, 26 Feb 2019 14:22:06 GMT
2. **blockedby**: changed from **3704, 3706** to **3704, 3706, 3708**

**Comment 4**

1. **Sebastian Huber**, Fri, 01 Mar 2019 10:01:45 GMT

In e6dd36ca/rtems:

```
bsp/gen5200: Remove offending @mainpage
Update #3705.
```

**Comment 5**

1. **Sebastian Huber**, Mon, 04 Mar 2019 06:54:54 GMT

In a6e39d4a/rtems:

```
Update Doxyfile to Doxygen 1.8.15

Generate Doxygen output in doc and ignore this directory in Git. Add RTEMS logo. The Doxygen documentation is now built using the
source tree. Just invoke "doxygen" in the top-level source directory.

The Doxyfile works also with at least Doxygen 1.8.13 and Doxygen 1.8.14.

Update #3705.
```

**Comment 6**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:52:11 GMT
2. **milestone**: changed from **6.1** to **7.1**

**Comment 7**

1. **Sebastian Huber**, Mon, 23 Oct 2023 08:55:24 GMT

In b8f1988/rtems:

doxygen: Replace and move main page

Replace the main page with a high level description of the RTEMS feature set similar to:

<https://docs.rtems.org/branches/master/user/overview/index.html#features>

The replaced content can be found in the RTEMS Classic API Guide:

<https://docs.rtems.org/branches/master/c-user/overview.html>[https://docs.rtems.org/branches/master/c-user/key\\_concepts.html](https://docs.rtems.org/branches/master/c-user/key_concepts.html)

Update #3705.

**Comment 8**

1. **Sebastian Huber**, Mon, 23 Oct 2023 08:57:53 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**
4. **milestone**: changed from **7.1** to **6.1**

The Doxygen support is now good enough for the pre-qualified feature set of RTEMS.

---

**3706 - Create a hierarchy of RTEMS software components using Doxygen groups**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3706">https://devel.rtems.org/ticket/3706</a> ( <a href="https://devel.rtems.org/ticket/3706">https://devel.rtems.org/ticket/3706</a> )
<b>Id</b>	3706
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	26 February 2019 13:23:37
<b>Modified</b>	26 July 2023 05:08:21
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3705, 3707
<b>Blocked by</b>	3704

---

**Description**

Create a hierarchy of RTEMS software components using Doxygen groups. Review the existing Doxygen groups (software components) first.

<https://docs.rtems.org/doxygen/branches/master/modules.html>

Grouping should be done by at BSP level architecture and then by BSP.

There should be a device driver group with subgroups for each device class and specific device drivers, e.g. a BSP-specific device driver belongs to a device class and BSP.

There should be groups for APIs, file systems, support libraries, super core, etc.

- Board Support Packages
- Device Drivers
  - Block Devices
    - Block Device Buffer Management
    - Block Device Disk Management
    - Block Device Management
      - XYZ Block Device
    - Block Device Partition Management
  - Cache
    - XYZ Cache Support
  - Console
    - Termios
      - XYZ Driver
  - Framebuffer
    - XYZ Driver
  - I2C
    - Bus Driver
      - XYZ Driver
    - Device Driver
      - XYZ Driver
  - Legacy I2C
  - Legacy Network
  - RTC
    - XYZ Driver
  - Serial Mouse
    - XYZ Driver
  - SPI

- Bus Driver
  - XYZ Driver
- Device Driver
  - XYZ Driver
- API
  - Classic
    - Tasks
  - Dynamic Loading
  - File Systems
  - Memory Management
  - Shell
  - Tracing
    - Event Recording
    - Capture Engine
- Internal
  - C Library Support
  - POSIX
  - Shell
  - Super Core
    - Thread Handler
    - CPU
      - ARM

**Comment 1**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:28:28 GMT
2. **blocking**: changed from **3705** to **3705, 3707**

**Comment 2**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:30:45 GMT
2. **status**: changed from **assigned** to **accepted**

**Comment 3**

1. **Sebastian Huber**, Mon, 04 Mar 2019 06:54:58 GMT

In 212663be/rtems:

```
bsps: Adjust architecture Doxygen groups
Use CamelCase as it is not used in our C code. Enables simple search and
replace. Prefix with "RTEMS" to aid deployment and integration. It aids
searching and sorting.
Update #3706.
```

**Comment 4**

1. **Sebastian Huber**, Mon, 04 Mar 2019 06:55:01 GMT

In 631ccd7/rtems:

```
bsp/altera-cyclone-v: Adjust Doxygen groups
Update #3706
```

**Comment 5**

1. **Sebastian Huber**, Fri, 08 Mar 2019 07:02:01 GMT

In c991ecec/rtems:

```
bsps: Adjust bsp.h Doxygen groups
Update #3706.
```

**Comment 6**

1. **Sebastian Huber**, Fri, 08 Mar 2019 07:02:05 GMT

In 828276b/rtems:

```
bsps: Adjust shared Doxygen groups
Update #3706.
```

**Comment 7**

1. **Sebastian Huber**, Fri, 08 Mar 2019 07:02:08 GMT

In 15359bb/rtems:

```
bsps/arm: Adjust CMSIS Doxygen groups
Update #3706.
```

#### **Comment 8**

1. **Sebastian Huber**, Fri, 08 Mar 2019 07:02:11 GMT

In f3db3835/rtems:

```
bsp/altera-cyclone-v: Add Doxygen groups
Add Doxygen groups for contributed code which would otherwise end up at the top level.
Update #3706.
```

#### **Comment 9**

1. **Sebastian Huber**, Fri, 08 Mar 2019 07:02:14 GMT

In cbf773d3/rtems:

```
bsp/atsam: Add Doxygen groups
Add Doxygen groups for contributed code which would otherwise end up at the top level (about 178 groups).
Update #3706.
```

#### **Comment 10**

1. **Sebastian Huber**, Fri, 08 Mar 2019 07:02:17 GMT

In 529b5868/rtems:

```
bsps: Adjust umon Doxygen groups
Update #3706.
```

#### **Comment 11**

1. **Sebastian Huber**, Wed, 13 Mar 2019 09:15:25 GMT
2. **description:** modified (diff)

#### **Comment 12**

1. **Sebastian Huber**, Tue, 26 Mar 2019 10:28:40 GMT

In 40d15f5/rtems:

```
score: Add implementation top-level group
Update #3706.
```

#### **Comment 13**

1. **Sebastian Huber**, Tue, 26 Mar 2019 10:28:44 GMT

In 5526527e/rtems:

```
score: Rename ScoreCPU Doxygen group
Update #3706.
```

#### **Comment 14**

1. **Sebastian Huber**, Tue, 26 Mar 2019 10:28:48 GMT

In 5a19915/rtems:

score: Add example CPU architecture group  
Update #3706.

#### **Comment 15**

1. **Sebastian Huber**, Tue, 26 Mar 2019 10:28:51 GMT

In abec398/rtems:

score: Add ARM CPU architecture group  
Update #3706.

#### **Comment 16**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:31:55 GMT

In eca13a8f/rtems:

doxygen: score: Add Blackfin CPU architecture group  
Update #3706.

#### **Comment 17**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:31:58 GMT

In 40b90a08/rtems:

doxygen: score: Add Epiphany CPU architecture group  
Update #3706.

#### **Comment 18**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:03 GMT

In d670ef9/rtems:

doxygen: score: Add i386 CPU architecture group  
Update #3706.

#### **Comment 19**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:07 GMT

In 9fa3561b/rtems:

doxygen: score: Add lm32 CPU architecture group  
Update #3706.

#### **Comment 20**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:11 GMT

In ee38c54/rtems:

doxygen: score: Change no\_cpu architecture group  
Groups CPUContext and CPUInterrupt are now defined with a unique name for this architecture group. Update #3706.

#### **Comment 21**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:15 GMT

In 0be1e54/rtems:

doxygen: score: Add m68k CPU architecture group

Update #3706.

#### **Comment 22**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:19 GMT

In f2e282d/rtems:

```
doxygen: score: Add Moxie CPU architecture group
Update #3706.
```

#### **Comment 23**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:22 GMT

In 92c2db64/rtems:

```
doxygen: score: Add nios2 CPU architecture group
Update #3706.
```

#### **Comment 24**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:26 GMT

In 39594416/rtems:

```
doxygen: score: Add or1k CPU architecture group
Update #3706.
```

#### **Comment 25**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:29 GMT

In 6ddbcbcb/rtems:

```
doxygen: score: Add powerpc CPU architecture group
Update #3706.
```

#### **Comment 26**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:32 GMT

In 71f9098/rtems:

```
doxygen: score: Add RISC-V CPU architecture group
Update #3706.
```

#### **Comment 27**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:35 GMT

In 2b37eca5/rtems:

```
doxygen: score: Add SuperH CPU architecture group
Update #3706.
```

#### **Comment 28**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:38 GMT

In 25afa79/rtems:

```
doxygen: score: Add SPARC CPU architecture group
Update #3706.
```

**Comment 29**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:42 GMT

In 2a50f87/rtems:

```
doxygen: score: Add SPARC64 CPU architecture group
Update #3706.
```

**Comment 30**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:45 GMT

In 9f8af67/rtems:

```
doxygen: score: Add V850 CPU architecture group
Update #3706.
```

**Comment 31**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:48 GMT

In 95c7603/rtems:

```
doxygen: score: Add x86-64 CPU architecture group
Update #3706.
```

**Comment 32**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:52 GMT

In 69d6671f/rtems:

```
doxygen: Reviewed cpukit/include/rtems/score
Update #3706.
```

**Comment 33**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:55 GMT

In 7a722e7/rtems:

```
doxygen: Reviewed cpukit/include/rtems/rtems
Update #3706.
```

**Comment 34**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:32:59 GMT

In b86148a/rtems:

```
doxygen: Reviewed cpukit/include/rtems/posix
Update #3706.
```

**Comment 35**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:33:02 GMT

In b07c721/rtems:

```
doxygen: Restructured cpukit/include/rtems/rtems
Update #3706.
```

**Comment 36**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:33:05 GMT

In 493c1e8/rtems:

```
doxygen: score: Put ARM Co-Processor 15 group in ARM
Update #3706.
```

#### **Comment 37**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:33:08 GMT

In 5342261/rtems:

```
doxygen: Added groups to IO library
Update #3706.
```

#### **Comment 38**

1. **Andreas Dachsberger**, Tue, 02 Apr 2019 05:33:12 GMT

In 058f637/rtems:

```
doxygen: score: Added ScoreRWLock to Score group
Update #3706.
```

#### **Comment 39**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:27:42 GMT

In 6644867/rtems:

```
doxygen: User Extensions Implementation group now in Internal->Classic
Update #3706.
```

#### **Comment 40**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:27:46 GMT

In ff1f374/rtems:

```
doxygen: Added Mainpage to RTEMSAPIClassic
Update #3706.
```

#### **Comment 41**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:27:49 GMT

In b7927ef/rtems:

```
doxygen: Added further groups to RTEMSAPI
Update #3706.
Associativity Routines, BSD Compatibility Support now part of RTEMSAPI
```

#### **Comment 42**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:27:53 GMT

In 0f02e6f/rtems:

```
doxygen: Added toplevel group for device drivers
Update #3706.
```

#### **Comment 43**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:27:56 GMT



In 529d251b/rtems:

doxygen: Added libmisc group and libmisc mouse group  
Update #3706.  
@ingroup for these groups already existed, but no @defgroup  
Further restructuring necessary

#### **Comment 44**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:27:59 GMT

In 1964b268/rtems:

doxygen: Added subgroup Generic to BSP->SPARC64  
Update #3706.

#### **Comment 45**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:03 GMT

In b2b7b58e/rtems:

doxygen: Added Management to Example CPU Architecture  
Update #3706.

#### **Comment 46**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:07 GMT

In 333bead/rtems:

doxygen: Removed XXX group  
Update #3706.  
Content was added to Classic Barrier Implementation

#### **Comment 47**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:11 GMT

In 4b841b3/rtems:

doxygen: Added some subgroups to IO Library  
Update #3706.  
Types and Mount, IO Internal, Kernel Print Support

#### **Comment 48**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:14 GMT

In 6b23763/rtems:

doxygen: Added Frame Buffer Device Driver Interface to Device Drivers  
Update #3706.

#### **Comment 49**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:18 GMT

In e78e7fe0/rtems:

doxygen: Added Version to API->Classic  
Update #3706.

**Comment 50**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:21 GMT

In 7cb1c2b0/rtems:

doxygen: Added I2C Driver to Device Drivers  
Update #3706.

**Comment 51**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:25 GMT

In b6b00917/rtems:

doxygen: Added some subgroups to API and IO  
I2C library, Media Manager and Profiling Support  
Update #3706.

**Comment 52**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:29 GMT

In f91da319/rtems:

doxygen: Put C Library Support and POSIX in Internal  
Update #3706.

**Comment 53**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:32 GMT

In 38a3b61/rtems:

doxygen: Put SPI Driver into group Device Drivers  
Update #3706.

**Comment 54**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:36 GMT

In 2a56a1cf/rtems:

doxygen: Real Time Clock Time of Day API Definition in BSP->Shared  
Update #3706.

**Comment 55**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:39 GMT

In 885c9a70/rtems:

doxygen: Put Print Support in IO  
Update #3706.

**Comment 56**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:43 GMT

In 2bc058d/rtems:

doxygen: Put Real-Timer Clock Driver Interface into group Device Drivers  
Update #3706.

**Comment 57**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:47 GMT

In b8cff58/rtems:

doxygen: Benchmark Timer Driver Interface now in Device Drivers  
Update #3706.

**Comment 58**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:50 GMT

In 74bfb1f/rtems:

doxygen: Time Test 27 now in Device Drivers  
Update #3706.

**Comment 59**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:54 GMT

In bd675f39/rtems:

doxygen: Mouse now in Device Drivers  
Update #3706.

**Comment 60**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:28:58 GMT

In 7e5ed6b/rtems:

doxygen: Print Support now in API->IO  
Update #3706.

**Comment 61**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:29:01 GMT

In 7155b5bc/rtems:

doxygen: Zero and Null Device Drivers now in Device Drivers  
Update #3706.

**Comment 62**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:29:05 GMT

In 57a076cd/rtems:

doxygen: Added subclasses to API  
Update #3706.  
RTEMS Application Loader, RTEMS Runtime Link Editor, Status Checks and Test Support

**Comment 63**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:29:09 GMT

In 51f8d73b/rtems:

doxygen: Added inttypes.h to Print Support  
Update #3706.

**Comment 64**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:29:13 GMT

In bddf938/rtems:

```
doxygen: Added RTEMS Test Framework to API
Update #3706.
```

**Comment 65**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:29:16 GMT

In c9bd696/rtems:

```
doxygen: New API subgroup Tracing
Update #3706.
```

**Comment 66**

1. **Andreas Dachsberger**, Thu, 04 Apr 2019 06:29:20 GMT

In 7b09032/rtems:

```
doxygen: Split up "libmisc" subgroups and removed libmisc
Update #3706.
```

**Comment 67**

1. **Sebastian Huber**, Thu, 04 Apr 2019 07:19:12 GMT

In 4c20da4/rtems:

```
doxygen: Rename Score* groups in RTEMSScore*
Update #3706
```

**Comment 68**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:52:41 GMT

In 93dcd2b/rtems:

```
doxygen: score: adjust doc in address.h to doxygen guidelines
Update #3706.
```

**Comment 69**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:52:44 GMT

In 76a9857c/rtems:

```
doxygen: score: adjust doc in apimutex.h to doxygen guidelines
Update #3706.
```

**Comment 70**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:52:48 GMT

In 3b977b86/rtems:

```
doxygen: score: adjust doc in basedefs.h to doxygen guidelines
Update #3706.
```

**Comment 71**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:52:52 GMT

In 827e260/rtems:

```
doxygen: score: adjust doc in chain.h to doxygen guidelines
Update #3706.
```

#### **Comment 72**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:52:55 GMT

In 0153acf2/rtems:

```
doxygen: score: adjust doc in chainimpl.h to doxygen guidelines
Update #3706.
```

#### **Comment 73**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:52:58 GMT

In 59de8ef/rtems:

```
doxygen: score: adjust doc in context.h to doxygen guidelines
Update #3706.
```

#### **Comment 74**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:01 GMT

In 4bb0f00/rtems:

```
doxygen: score: adjust doc in copyrt.h to doxygen guidelines
Also renamed the group SuperCoreCopyright? to RTEMSSuperCoreCopyright Update #3706.
```

#### **Comment 75**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:04 GMT

In 37ab908/rtems:

```
doxygen: score: adjust doc in corebarrier.h to doxygen guidelines
Update #3706.
```

#### **Comment 76**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:08 GMT

In 4bd8757/rtems:

```
doxygen: score: adjust doc in coremsg.h to doxygen guidelines
Update #3706.
```

#### **Comment 77**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:11 GMT

In 62128be0/rtems:

```
doxygen: score: added dox in assert.h according to doxygen guidelines
Update #3706.
```

#### **Comment 78**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:15 GMT

In accbe67/rtems:

doxygen: score: adjust doc in corebarrierimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 79**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:18 GMT

In 0865cd2/rtems:

doxygen: score: adjust doc in coremsgimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 80**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:21 GMT

In d369903/rtems:

doxygen: score: adjust doc in coremutex.h to doxygen guidelines  
Update #3706.

#### **Comment 81**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:25 GMT

In 86b05bf6/rtems:

doxygen: score: adjust doc in coremuteximpl.h to doxygen guidelines  
Update #3706.

#### **Comment 82**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:28 GMT

In d16a9019/rtems:

doxygen: score: adjust doc in corerwlockimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 83**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:32 GMT

In eab90bf/rtems:

doxygen: score: adjust doc in coresem.h to doxygen guidelines  
Update #3706.

#### **Comment 84**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:35 GMT

In d5b63c2/rtems:

doxygen: score: adjust doc in coresemimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 85**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:38 GMT

In 54733e6/rtems:

doxygen: score: adjust doc in cpustdatomic.h to doxygen guidelines  
Update #3706.

#### **Comment 86**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:41 GMT

In d69b7a5/rtems:

doxygen: score: adjust doc in freechain.h to doxygen guidelines  
Update #3706.

#### **Comment 87**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:45 GMT

In cf6ce4a/rtems:

doxygen: score: adjust doc in heap.h to doxygen guidelines  
Update #3706.

#### **Comment 88**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:48 GMT

In 4c99921/rtems:

doxygen: score: adjust doc in heapimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 89**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:51 GMT

In 0cdcb27/rtems:

Removed entry from Related Pages  
SAM V71 Xplained Ultra - Board explanation now in Modules->BSPs->ARM Update #3706.

#### **Comment 90**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:54 GMT

In 5ad74fd6/rtems:

doxygen: score: adjust doc in interr.h to doxygen guidelines  
Update #3706.

#### **Comment 91**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:53:58 GMT

In 24787d08/rtems:

doxygen: score: adjust doc in isr.h to doxygen guidelines  
Update #3706.

#### **Comment 92**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:01 GMT

In bb0ccc1/rtems:

doxygen: score: adjust doc in isrlevel.h to doxygen guidelines

Update #3706.

**Comment 93**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:04 GMT

In 318b70b/rtems:

```
doxygen: score: adjust doc in isrlock.h to doxygen guidelines
Update #3706.
```

**Comment 94**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:08 GMT

In 976c095/rtems:

```
doxygen: score: adjust doc in mpci.h to doxygen guidelines
Update #3706.
```

**Comment 95**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:11 GMT

In 57cd05cf/rtems:

```
doxygen: score: adjust doc in mpciimpl.h to doxygen guidelines
Update #3706.
```

**Comment 96**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:15 GMT

In 3da777e/rtems:

```
doxygen: score: adjust doc in mppkt.h to doxygen guidelines
Update #3706.
```

**Comment 97**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:18 GMT

In b817de6d/rtems:

```
doxygen: score: adjust doc in mrsp.h to doxygen guidelines
Update #3706.
```

**Comment 98**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:22 GMT

In 0b1bfab/rtems:

```
doxygen: score: adjust doc in mrspimpl.h to doxygen guidelines
Update #3706.
```

**Comment 99**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:25 GMT

In ae8be3f/rtems:

```
doxygen: score: adjust doc in object.h to doxygen guidelines
Update #3706.
```



**Comment 100**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:28 GMT

In c389f5b7/rtems:

```
doxygen: score: adjust doc in objectimpl.h to doxygen guidelines
Update #3706.
```

**Comment 101**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:32 GMT

In 316894e6/rtems:

```
doxygen: score: adjust doc in objectmp.h to doxygen guidelines
Update #3706.
```

**Comment 102**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:35 GMT

In 0bef82f/rtems:

```
doxygen: score: adjust doc in percpudata.h to doxygen guidelines
Update #3706.
```

**Comment 103**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:38 GMT

In 96d37510/rtems:

```
doxygen: score: adjust doc in prioritybitmap.h to doxygen guidelines
Update #3706.
```

**Comment 104**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:42 GMT

In 536458a/rtems:

```
doxygen: score: adjust doc in prioritybitmapimpl.h to doxygen guidelines
Update #3706.
```

**Comment 105**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:45 GMT

In 1d6e6b1f/rtems:

```
doxygen: score: adjust doc in priority.h to doxygen guidelines
Update #3706.
```

**Comment 106**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:48 GMT

In 35a07c4/rtems:

```
doxygen: score: adjust doc in priorityimpl.h to doxygen guidelines
Update #3706.
```

**Comment 107**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:52 GMT

In acdb99eb/rtems:

```
doxygen: score: adjust doc in processormask.h to doxygen guidelines
Update #3706.
```

#### **Comment 108**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:55 GMT

In ee8eb21/rtems:

```
doxygen: score: adjust doc in profiling.h to doxygen guidelines
Update #3706.
```

#### **Comment 109**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:54:59 GMT

In 1e6a7c7a/rtems:

```
doxygen: score: adjust doc in protectedheap.h to doxygen guidelines
Update #3706.
```

#### **Comment 110**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:02 GMT

In f61a3f85/rtems:

```
doxygen: score: adjust doc in rbtree.h to doxygen guidelines
Update #3706.
```

#### **Comment 111**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:05 GMT

In 334de12/rtems:

```
doxygen: score: adjust doc in rbtreeimpl.h to doxygen guidelines
Update #3706.
```

#### **Comment 112**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:09 GMT

In 65f19f0/rtems:

```
doxygen: score: adjust doc in schedulercbcs.h to doxygen guidelines
Update #3706.
```

#### **Comment 113**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:12 GMT

In 06821fa5/rtems:

```
doxygen: score: adjust doc in schedulercbcsimpl.h to doxygen guidelines
Update #3706.
```

#### **Comment 114**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:15 GMT

In f660691/rtems:

doxygen: score: adjust doc in scheduleredf.h to doxygen guidelines

Update #3706.

#### **Comment 115**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:18 GMT

In 6852f7e/rtems:

doxygen: score: adjust doc in scheduleredfimpl.h to doxygen guidelines

Update #3706.

#### **Comment 116**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:22 GMT

In e2d575c2/rtems:

doxygen: score: adjust doc in scheduler.h to doxygen guidelines

Update #3706.

#### **Comment 117**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:25 GMT

In 11e7893/rtems:

doxygen: score: adjust doc in schedulerimpl.h to doxygen guidelines

Update #3706.

#### **Comment 118**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:29 GMT

In d5548b65/rtems:

doxygen: score: adjust doc in schedulernode.h to doxygen guidelines

Update #3706.

#### **Comment 119**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:32 GMT

In 08901bf/rtems:

doxygen: score: adjust doc in schedulernodeimpl.h to doxygen guidelines

Update #3706.

#### **Comment 120**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:36 GMT

In 263fa5ef/rtems:

doxygen: score: adjust doc in schedulerpriorityaffinitymp.h to doxygen guidelines

Update #3706.

#### **Comment 121**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:39 GMT

In 4aed194/rtems:

doxygen: score: adjust doc in schedulerpriority.h to doxygen guidelines  
Update #3706.

#### **Comment 122**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:43 GMT

In ed6b2e0/rtems:

doxygen: score: adjust doc in schedulerpriorityimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 123**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:46 GMT

In 391f92b9/rtems:

doxygen: score: adjust doc in schedulerprioritysimp.h to doxygen guidelines  
Update #3706.

#### **Comment 124**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:49 GMT

In 776ec05/rtems:

doxygen: score: adjust doc in schedulerstimple.h to doxygen guidelines  
Update #3706.

#### **Comment 125**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:53 GMT

In d0839dd/rtems:

doxygen: score: adjust doc in schedulerredfsmp.h to doxygen guidelines  
Update #3706.

#### **Comment 126**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:56 GMT

In f8047f14/rtems:

doxygen: score: adjust doc in schedulerstimpleimpl.h to doxygen guidelines  
Update #3706.

#### **Comment 127**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:55:59 GMT

In 1bfdc06/rtems:

doxygen: score: adjust doc in schedulerstimplesmp.h to doxygen guidelines  
Update #3706.

#### **Comment 128**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:03 GMT

In ceff06f/rtems:

doxygen: score: adjust doc in schedulerstimp.h to doxygen guidelines

Update #3706.

**Comment 129**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:06 GMT

In 6a1734a3/rtems:

```
doxygen: score: adjust doc in schedulermpimpl.h to doxygen guidelines
Update #3706.
```

**Comment 130**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:09 GMT

In ee3351c/rtems:

```
doxygen: score: adjust doc in schedulerstrongapa.h to doxygen guidelines
Update #3706.
```

**Comment 131**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:13 GMT

In 6a9cb56/rtems:

```
doxygen: score: adjust doc in semaphoreimpl.h to doxygen guidelines
Update #3706.
```

**Comment 132**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:16 GMT

In d057bb29/rtems:

```
doxygen: score: adjust doc in smpbarrier.h to doxygen guidelines
Update #3706.
```

**Comment 133**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:20 GMT

In 79249a5/rtems:

```
doxygen: score: adjust doc in smpimpl.h to doxygen guidelines
Update #3706.
```

**Comment 134**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:24 GMT

In 9503db6/rtems:

```
doxygen: score: adjust doc in smplock.h to doxygen guidelines
Update #3706.
```

**Comment 135**1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:28 GMT

In 93afceb/rtems:

```
doxygen: score: adjust doc in smplockmcs.h to doxygen guidelines
Update #3706.
```

**Comment 136**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:31 GMT

In 2adc5f10/rtems:

```
doxygen: score: adjust doc in smplockseq.h to doxygen guidelines
Update #3706.
```

**Comment 137**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:34 GMT

In c624340e/rtems:

```
doxygen: score: adjust doc in smplockstats.h to doxygen guidelines
Update #3706.
```

**Comment 138**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:38 GMT

In 366dbf6/rtems:

```
doxygen: score: adjust doc in smplockticket.h to doxygen guidelines
Update #3706.
```

**Comment 139**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:41 GMT

In 0938899/rtems:

```
doxygen: score: adjust doc in stack.h to doxygen guidelines
Update #3706.
```

**Comment 140**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:45 GMT

In 0e829b26/rtems:

```
doxygen: score: adjust doc in stackimpl.h to doxygen guidelines
Update #3706.
```

**Comment 141**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:48 GMT

In fa3b4a2/rtems:

```
doxygen: score: adjust doc in stackimpl.h to doxygen guidelines
Update #3706.
```

**Comment 142**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:51 GMT

In 5ba93a5/rtems:

```
doxygen: score: adjust doc in statesimpl.h to doxygen guidelines
Update #3706.
```

**Comment 143**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:55 GMT

In 6af85ee6/rtems:

```
doxygen: score: adjust doc in sysstate.h to doxygen guidelines
Update #3706.
```

#### **Comment 144**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:56:58 GMT

In 7d93c447/rtems:

```
doxygen: score: adjust doc in threaddispatch.h to doxygen guidelines
Update #3706.
```

#### **Comment 145**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:02 GMT

In 5bb6ac9/rtems:

```
doxygen: score: adjust doc in thread.h to doxygen guidelines
Update #3706.
```

#### **Comment 146**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:05 GMT

In 3657cde/rtems:

```
doxygen: score: adjust doc in threadimpl.h to doxygen guidelines
Update #3706.
```

#### **Comment 147**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:09 GMT

In 8f89dc62/rtems:

```
doxygen: score: adjust doc in threadmp.h to doxygen guidelines
Update #3706.
```

#### **Comment 148**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:12 GMT

In f1507fb/rtems:

```
doxygen: score: adjust doc in threadq.h to doxygen guidelines
Update #3706.
```

#### **Comment 149**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:16 GMT

In b6bbe83/rtems:

```
doxygen: score: adjust doc in threadqimpl.h to doxygen guidelines
Update #3706.
```

#### **Comment 150**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:19 GMT

In 843879d0/rtems:

doxygen: score: adjust doc in timecounter.h to doxygen guidelines

Update #3706.

#### **Comment 151**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:22 GMT

In 3e98049/rtems:

doxygen: score: adjust doc in timecounterimpl.h to doxygen guidelines

Update #3706.

#### **Comment 152**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:26 GMT

In bded63fc/rtems:

doxygen: score: adjust doc in timespec.h to doxygen guidelines

Update #3706.

#### **Comment 153**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:29 GMT

In 1b5ba76/rtems:

doxygen: score: adjust doc in timestamp.h to doxygen guidelines

Update #3706.

#### **Comment 154**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:32 GMT

In 4a693e7/rtems:

doxygen: score: adjust doc in timestampimpl.h to doxygen guidelines

Update #3706.

#### **Comment 155**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:36 GMT

In 5c91b54b/rtems:

doxygen: score: adjust doc in tls.h to doxygen guidelines

Update #3706.

#### **Comment 156**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:39 GMT

In 5791a3c/rtems:

doxygen: score: adjust doc in todimpl.h to doxygen guidelines

Update #3706.

#### **Comment 157**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:42 GMT

In 7d2cc98/rtems:



```
doxygen: score: adjust doc in userextimpl.h to doxygen guidelines
Update #3706.
```

**Comment 158**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:45 GMT

In eb84cc3f/rtems:

```
doxygen: score: adjust doc in watchdog.h to doxygen guidelines
Update #3706.
```

**Comment 159**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:49 GMT

In c53ec8c4/rtems:

```
doxygen: score: adjust doc in watchdogimpl.h to doxygen guidelines
Update #3706.
```

**Comment 160**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:52 GMT

In 904c2312/rtems:

```
doxygen: score: adjust doc in watchdogticks.h to doxygen guidelines
Update #3706.
```

**Comment 161**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:55 GMT

In 7b90bb5/rtems:

```
doxygen: score: adjust doc in wkspace.h to doxygen guidelines
Update #3706.
```

**Comment 162**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:57:59 GMT

In 2463c10/rtems:

```
doxygen: score: adjust doc in muteximpl.h to doxygen guidelines
Update #3706.
```

**Comment 163**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:58:02 GMT

In 1bd608b/rtems:

```
doxygen: score: adjust doc in onceimpl.h to doxygen guidelines
Update #3706.
```

**Comment 164**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:58:05 GMT

In 3238c162/rtems:

```
doxygen: score: adjust doc in smp.h to doxygen guidelines
```

Update #3706.

**Comment 165**

1. **Andreas Dachsberger**, Mon, 13 May 2019 05:58:08 GMT

In f49618d/rtems:

```
doxygen: score: adjust doc in percpudata.h to doxygen guidelines
```

Update #3706.

**Comment 166**

1. **Sebastian Huber**, Wed, 02 Dec 2020 06:46:18 GMT

In e07088d9/rtems:

```
rtems: Canonicalize implementation Doxygen groups
```

```
Rename Classic API top-level group from Classic to RTEMSImplClassic. Use RTEMSImplClassic as a prefix for the subgroups. Change the group names to be in line with the API group names. Use common phrases for the group brief descriptions.
```

Update #3706.

**Comment 167**

1. **Sebastian Huber**, Wed, 02 Dec 2020 06:46:21 GMT

In c81ac0e/rtems:

```
score: Canonicalize Doxygen groups
```

```
Adjust group identifier and names to be in line with a common pattern. Use common phrases for the group brief descriptions.
```

Update #3706.

**Comment 168**

1. **Sebastian Huber**, Wed, 02 Dec 2020 06:46:27 GMT

In 6b5f22dc/rtems:

```
rtems: Canonicalize Doxygen @file comments
```

```
Use common phrases for the file brief descriptions.
```

Update #3706.

**Comment 169**

1. **Sebastian Huber**, Wed, 02 Dec 2020 06:46:31 GMT

In 9278f3d/rtems:

```
score: Canonicalize Doxygen @file comments
```

```
Use common phrases for the file brief descriptions.
```

Update #3706.

**Comment 170**

1. **Sebastian Huber**, Wed, 02 Dec 2020 06:46:34 GMT

In 3db9c820/rtems:

```
sapi: Canonicalize @defgroup and @file comments
```

```
Adjust group identifier and names to be in line with a common pattern. Use common phrases for the group and file brief descriptions.
```

Update #3706.

**Comment 171**

1. **Sebastian Huber**, Wed, 02 Dec 2020 06:46:37 GMT

In 70dbafb/rtems:

config: Canonicalize @defgroup and @file comments

Adjust group identifier and names to be in line with a common pattern. Use common phrases for the group and file brief descriptions.

Update #3706.

#### **Comment 172**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:13:58 GMT

In 226b90b4/rtems:

rtems: Fix Doxygen group memberships

Update #3706.

#### **Comment 173**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:15:50 GMT

In 5555c0c/rtems:

rtems: Fix Doxygen group name

Update #3706.

#### **Comment 174**

1. **Sebastian Huber**, Wed, 02 Dec 2020 10:35:07 GMT

In 1c60622/rtems:

score: Fix Doxygen group name

Update #3706.

#### **Comment 175**

1. **Sebastian Huber**, Wed, 02 Dec 2020 10:35:11 GMT

In 1fa3821/rtems:

score: Fix Doxygen group membership

Update #3706.

#### **Comment 176**

1. **Sebastian Huber**, Wed, 02 Dec 2020 12:05:27 GMT

In 295b05f9/rtems:

nfscclient: Rework Doxygen groups

Update #3706.

#### **Comment 177**

1. **Sebastian Huber**, Wed, 02 Dec 2020 12:05:30 GMT

In ab85383/rtems:

nfscclient: Remove from Doxygen output

The libnetworking is excluded from the Doxygen output. Exclude also the nfscclient source code, otherwise there are some orphaned Doxygen groups.

Update #3706.

#### **Comment 178**

1. **Sebastian Huber**, Wed, 02 Dec 2020 12:19:09 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

In 3393ff1d/rtems:

```
libfs: Fix Doxygen group placement
Update #3706.
```

#### **Comment 179**

1. **Sebastian Huber**, Wed, 02 Dec 2020 12:19:13 GMT

In ef0fe8e/rtems:

```
dosfs: Fix Doxygen group placement
Update #3706.
```

#### **Comment 180**

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:41:16 GMT

In dba2e690/rtems:

```
rtems: Canonicalize Doxygen in
Update #3706.
```

#### **Comment 181**

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:41:20 GMT

In 4c0b006/rtems:

```
rtems: Canonicalize Doxygen in
Update #3706.
```

#### **Comment 182**

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:41:24 GMT

In a950c135/rtems:

```
score: Add Hash Handler to group
Update #3706.
```

#### **Comment 183**

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:41:27 GMT

In 5a6f94d/rtems:

```
rtems: Add ASR implementation to existing group
Update #3706.
```

#### **Comment 184**

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:41:31 GMT

In 8b762a88/rtems:

```
scoe: Move workspace group definition
Define the group in the header file which is used by .
Update #3706.
```

#### **Comment 185**

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:41:36 GMT

In e9063644/rtems:

```
posix: Remove "RTEMS" from POSIX API group
Clarify group description.
Update #3706.
```

#### **Comment 186**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:55:14 GMT
2. **milestone**: changed from **6.1** to **7.1**

#### **Comment 187**

1. **Sebastian Huber**, Tue, 24 Jan 2023 10:26:29 GMT

In 6136e28b/rtems:

```
clockdrv: Add clock driver implementation group
Use standard wording in Clock Driver related files.
Update #3706.
```

#### **Comment 188**

1. **Sebastian Huber**, Tue, 24 Jan 2023 10:26:34 GMT

In d36070f/rtems:

```
intr: Add Interrupt Manager implementation group
The shared BSP interrupt controller support code actually implements parts of the Interrupt Manager.
Update #3706.
```

#### **Comment 189**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:02:05 GMT

In 97f5e1c/rtems:

```
bsp/leon3: Fix group memberships
Update #3706.
```

#### **Comment 190**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:40 GMT

In 58840ffb/rtems:

```
rtems: Add files to Doxygen groups
Provide basic Doxygen comments.
Update #3706. Update #3707.
```

#### **Comment 191**

1. **Sebastian Huber**, Wed, 26 Jul 2023 05:08:21 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**
4. **milestone**: changed from **7.1** to **6.1**

For RTEMS 6, the group hierarchy is good enough.

---

### **3707 - Assign each code file to a Doxygen group**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3707">https://devel.rtems.org/ticket/3707</a> ( <a href="https://devel.rtems.org/ticket/3707">https://devel.rtems.org/ticket/3707</a> )
<b>Id</b>	3707
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	26 February 2019 13:28:28
<b>Modified</b>	15 January 2024 09:36:58
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3706

**Description**

Assign each code file (header, C source, assembler) to a Doxygen group. Exclude the legacy network stack and test suites. For third-party code decide case by case. Use this template and place it at the top of the file:

```
/**
 * @file
 *
 * @ingroup RTEMSClassicTasks
 */
```

Do not use @brief and a file description.

**Comment 1**

1. **Sebastian Huber**, Tue, 26 Feb 2019 13:30:45 GMT
2. **status**: changed from **assigned** to **accepted**

**Comment 2**

1. **Sebastian Huber**, Thu, 28 Feb 2019 10:48:03 GMT

In feea03b6/rtems:

```
Remove explicit file names from @file
This makes the @file documentation independent of the actual file name.
Update #3707.
```

**Comment 3**

1. **Sebastian Huber**, Mon, 04 Mar 2019 06:55:05 GMT

In 9d41fca/rtems:

```
bsp/altera-cyclone-v: Adjust Doxygen file groups
Update #3707.
```

**Comment 4**

1. **Sebastian Huber**, Mon, 24 Oct 2022 11:23:06 GMT

In 468f21e/rtems:

```
bsps: Add Cache Manager implementation group
Update #3707.
```

**Comment 5**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:53:00 GMT
2. **milestone**: changed from **6.1** to **7.1**

**Comment 6**

1. **Sebastian Huber**, Thu, 16 Feb 2023 07:11:35 GMT

In bb465c8/rtems:

doxygen: Add Doxygen files to a group

Update #3707.

#### **Comment 7**

1. **Sebastian Huber**, Fri, 21 Jul 2023 05:33:09 GMT

In 5fb9ebfc/rtems:

doxygen: Document build system provided files

Update #3707.

#### **Comment 8**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:38 GMT

In f99f5ce/rtems:

libtest: Place files into a Doxygen group

Canonicalize the file headers.

Update #3707.

#### **Comment 9**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:40 GMT

In 58840ffb/rtems:

rtems: Add files to Doxygen groups

Provide basic Doxygen comments.

Update #3706. Update #3707.

#### **Comment 10**

1. **Frank Kühndel**, Wed, 26 Jul 2023 04:56:42 GMT

In 3e1521ee/rtems:

bsps/sparc: Add files to Doxygen groups

Update #3707.

#### **Comment 11**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:44 GMT

In 233c21a/rtems:

score: Add files to Doxygen groups

Update #3707.

#### **Comment 12**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:46 GMT

In 5ba465c0/rtems:

libcsupport: Add file to Doxygen group

Update #3707.

#### **Comment 13**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:48 GMT

In d3fe128d/rtems:

posix: Add files to Doxygen group  
Canonicalize brief descriptions.  
Update #3707.

#### **Comment 14**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:50 GMT

In ec1e500f/rtems:

timecounter: Add files to Doxygen group  
Update #3707.

#### **Comment 15**

1. **Sebastian Huber**, Wed, 26 Jul 2023 04:56:52 GMT

In 1bc5d3e4/rtems:

sys: Add files to Doxygen group  
Canonicalize brief descriptions.  
Update #3707.

#### **Comment 16**

1. **Sebastian Huber**, Wed, 26 Jul 2023 05:09:40 GMT
2. **milestone**: changed from **7.1** to **6.1**

For RTEMS 6, the group assignment of files is good enough.

#### **Comment 17**

1. **Sebastian Huber**, Fri, 28 Jul 2023 14:39:53 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

#### **Comment 18**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:36:58 GMT

In 8e8b9bc0/rtems:

bsp/tms570: Relicense to BSD-2-Clause  
Change license to BSD-2-Clause according to file history and contributor agreements. Add Doxygen file comments.  
Update #3053. Update #3707. Update #4982.

---

## **3715 - Add Requirements Engineering chapter to RTEMS Software Engineering Handbook**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/3715">https://devel.rtems.org/ticket/3715</a> ( <a href="https://devel.rtems.org/ticket/3715">https://devel.rtems.org/ticket/3715</a> )
<b>Id</b>	3715
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	4 March 2019 11:03:16
<b>Modified</b>	19 May 2023 05:25:41
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3703
<b>Blocked by</b>	

**Description**

The chapter should cover the following topics:

- Overview and introduction
- Evaluation of tools for requirements management
- Selected tool for requirements management
- Evaluation of data models and formats for the requirements
- Definition of data model and format actually used for the project (may overlap with tool)
- Requirements management workflow used in the project
- Requirements on requirements, e.g. derived from standards such as ECSS-E-ST-10-06C
- Requirement identifiers used to ensure traceability

**Comment 1**

1. **Sebastian Huber**, Mon, 04 Mar 2019 13:10:43 GMT
2. **status**: changed from **assigned** to **accepted**
3. **summary**: changed from **Add Requirements Engineering chapter to RTEMS Software Engineering Handbook** to **Add Requirements Engineering chapter to RTEMS Software Engineering Handbook**

**Comment 2**

1. **Chris Johns**, Mon, 04 Mar 2019 23:02:03 GMT

How does the quality of RTEMS and it's requirements depend on the evaluation and selection of the tools for requirement management? I can understand the quality of the requirements effecting the quality of RTEMS but not the tools used to capture them? Why have the process, ie a sort of log book, in the engineering handbook? I would have expected this document to contain the out come of the discovery process and not the process itself.

I am concerned adding these things just creates a liability for the project. Can an email archive can perform this task?

**Comment 3**

1. **Joel Sherrill**, Mon, 04 Mar 2019 23:06:15 GMT

I agree with Chris. A trade study of requirements tools shouldn't end up in the handbook. Perhaps our requirements for a tool.

open source supports format XXX for interchange supports links for requirement derivation ...

**Comment 4**

1. **Sebastian Huber**, Thu, 07 Mar 2019 07:34:38 GMT

Yes, maybe this is not the best place for the tool overview. I though it would be helpful in case someone asks in two years, why did you use this, have you considered that, etc.? Should I add a ticket for the tool selection instead?

**Comment 5**

1. **Chris Johns**, Thu, 07 Mar 2019 21:00:27 GMT

Replying to Sebastian Huber:

Yes, maybe this is not the best place for the tool overview. I though it would be helpful in case someone asks in two years, why did you use this, have you considered that, etc.?

A brief rational can be helpful, but the details can be distracting. I feel the simpler and more direct this document is the more effective it will be.

Should I add a ticket for the tool selection instead?

Yes, it can links to mailing lists discussions and attachments and it is easy to link too.

**Comment 6**

1. **Sebastian Huber**, Tue, 07 Jan 2020 09:14:04 GMT

In d412c5b/rtems-docs:

```
eng: Add Software Requirements Engineering chapter
Update #3715.
```

#### **Comment 7**

1. **Sebastian Huber**, Thu, 02 Apr 2020 07:47:16 GMT

In 6f0bc56/rtems-docs:

```
eng: Add glossary terms
Define the following terms:
  assembler language C language ELF interrupt service software component software unit
Clarify:
  task
Update #3715.
```

#### **Comment 8**

1. **Sebastian Huber**, Tue, 05 May 2020 05:37:31 GMT

In d4ba908/rtems-docs:

```
eng: Update requirements engineering chapter
Update requirements engineering chapter due to the removal of Doorstop as the requirements management tool.
Update the application configuration related specification items.
Update #3715.
```

#### **Comment 9**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:02:31 GMT

In 59312aa/rtems-docs:

```
eng: Split up requirements engineering chapter
This allows to more easily generate the specification item section with a script using specification items.
Update #3715.
```

#### **Comment 10**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:02:33 GMT

In 23ab40d/rtems-docs:

```
eng: Add generated documentation of spec items
The documentation of the specification items is generated by an RTEMS qualification tool from a specification of specification items.
Move non-generated content to "req-for-req.rst".
Update #3715.
```

#### **Comment 11**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:02:35 GMT

In 459326c/rtems-docs:

```
eng: Update requirements tooling section
Update #3715.
```

#### **Comment 12**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:02:37 GMT

In 9b269ad/rtems-docs:

eng: Add interface specification how-to  
Update #3715.

### **Comment 13**

1. **Sebastian Huber**, Mon, 08 Jun 2020 07:05:29 GMT

In f547988/rtems-docs:

eng: Simplify wording for specification items  
Update #3715.

### **Comment 14**

1. **Sebastian Huber**, Mon, 08 Jun 2020 07:05:31 GMT

In 0c43c52/rtems-docs:

eng: Add generic attribute key types  
Update #3715.

### **Comment 15**

1. **Sebastian Huber**, Mon, 08 Jun 2020 07:05:33 GMT

In 0213e8e/rtems-docs:

eng: Add a specification type for actions  
Add support to specify functional requirements for actions (functions or macros) via a transition map of pre-conditions to post-conditions. This will be the work horse for functional requirements. Generation of corresponding validation tests is supported.  
Update #3715.

### **Comment 16**

1. **Sebastian Huber**, Mon, 08 Jun 2020 07:05:35 GMT

In ca2f5e6/rtems-docs:

eng: Update specification how-to section  
Update #3715.

### **Comment 17**

1. **Sebastian Huber**, Wed, 10 Jun 2020 08:12:37 GMT

In db3892b/rtems-docs:

eng: Update action requirement specification  
Update #3715.

### **Comment 18**

1. **Sebastian Huber**, Wed, 17 Jun 2020 07:11:35 GMT

In 87a9478/rtems-docs:

eng: Clarify action requirement specification  
Update #3715.

### **Comment 19**

1. **Sebastian Huber**, Fri, 03 Jul 2020 08:34:03 GMT

In 1bd14cd/rtems-docs:

eng: Reformat to maximize the text width  
Remove extra "X" character in some labels.  
Update #3715.

#### **Comment 20**

1. **Sebastian Huber**, Fri, 03 Jul 2020 08:34:05 GMT

In 0c13e94/rtems-docs:

eng: Fix typo  
Update #3715.

#### **Comment 21**

1. **Sebastian Huber**, Tue, 28 Jul 2020 05:33:52 GMT

In fd2fc50/rtems-docs:

eng: Add requirement text to interface groups  
This allows to state the requirement for an interface group directly in the item.  
Update #3715.

#### **Comment 22**

1. **Sebastian Huber**, Tue, 28 Jul 2020 05:33:54 GMT

In f12cae1/rtems-docs:

eng: Add brief description to header file items  
Update #3715.

#### **Comment 23**

1. **Sebastian Huber**, Tue, 28 Jul 2020 05:33:56 GMT

In c259563/rtems-docs:

eng: Support N/A in the action transitions  
Sometimes the pre-conditions in an action requirement are not independent and it is necessary to mark pre-conditions as not applicable in a particular transition.  
Update #3715.

#### **Comment 24**

1. **Sebastian Huber**, Tue, 28 Jul 2020 05:33:58 GMT

In 3f9fa47/rtems-docs:

eng: Add ability to skip action transitions  
Sometimes the pre-conditions in an action requirement are not independent and it is necessary skip a certain set of pre-condition states. This should be used with care since no test code is run in these cases. There shall be a reason given why skipping a transition is justified.  
Update #3715.

#### **Comment 25**

1. **Sebastian Huber**, Tue, 28 Jul 2020 05:34:01 GMT

In 1bb6947/rtems-docs:

eng: Fix format of regular expressions  
Update #3715.

#### **Comment 26**

1. **Sebastian Huber**, Thu, 06 Aug 2020 07:12:00 GMT

In bac4398/rtems-docs:

```
eng: Fix typo
Update #3715.
```

#### **Comment 27**

1. **Sebastian Huber**, Thu, 06 Aug 2020 07:18:47 GMT

In e1e0408/rtems-docs:

```
eng: Partially revert previous commit
The previous commit contained more than just a typo fix. Remove this part.
Update #3715.
```

#### **Comment 28**

1. **Sebastian Huber**, Fri, 07 Aug 2020 04:44:14 GMT

In 83e13b7/rtems-docs:

```
eng: Add application config options how-to
Update #3715.
```

#### **Comment 29**

1. **Sebastian Huber**, Fri, 07 Aug 2020 05:15:28 GMT

In 3e8e301/rtems-docs:

```
eng: Add more variants of unspecified interfaces
Update #3715.
```

#### **Comment 30**

1. **Sebastian Huber**, Fri, 07 Aug 2020 05:15:31 GMT

In 5cb493e/rtems-docs:

```
eng: Add reference to unspecified interfaces
Update #3715.
```

#### **Comment 31**

1. **Sebastian Huber**, Thu, 20 Aug 2020 07:01:23 GMT

In 9633e98/rtems-docs:

```
eng: Add test case attributes
Update #3715.
```

#### **Comment 32**

1. **Sebastian Huber**, Thu, 20 Aug 2020 07:01:25 GMT

In 1a48655/rtems-docs:

```
eng: Remove test name attribute
Derive the test name from the item UID.
Update #3715.
```

#### **Comment 33**

1. **Sebastian Huber**, Thu, 20 Aug 2020 07:01:27 GMT

In 83a3522/rtems-docs:

```
eng: Add test header to test case
Update #3715.
```

#### **Comment 34**

1. **Sebastian Huber**, Thu, 20 Aug 2020 07:01:29 GMT

In 93938c7/rtems-docs:

```
eng: Unify test attribute keys
Update #3715.
```

#### **Comment 35**

1. **Sebastian Huber**, Thu, 20 Aug 2020 07:01:32 GMT

In 57fb30d/rtems-docs:

```
eng: Add automatically generated warning
Update #3715.
```

#### **Comment 36**

1. **Sebastian Huber**, Sun, 11 Oct 2020 13:20:43 GMT

In c18215c/rtems-docs:

```
eng: Move index-entries to all interfaces
Update #3715.
```

#### **Comment 37**

1. **Sebastian Huber**, Sun, 11 Oct 2020 13:20:45 GMT

In bcf4a95/rtems-docs:

```
eng: Add placement link role
Update #3715.
```

#### **Comment 38**

1. **Sebastian Huber**, Sat, 24 Oct 2020 10:15:38 GMT

In abc9c44/rtems-docs:

```
eng: Replace spec2doc.py with spec2modules.py
Update #3715.
```

#### **Comment 39**

1. **Sebastian Huber**, Mon, 09 Nov 2020 14:05:33 GMT

In f610291/rtems-docs:

```
eng: Add function attributes
Update #3715.
```

#### **Comment 40**

1. **Sebastian Huber**, Thu, 19 Nov 2020 10:24:36 GMT

In bbd8d4a/rtems-docs:

eng: Fix typo

Update #3715.

#### **Comment 41**

1. **Sebastian Huber**, Fri, 27 Nov 2020 08:17:00 GMT

In 4b03ff7/rtems-docs:

eng: Add performance specification items

Add items to specify runtime performance requirements.

Update #3715.

#### **Comment 42**

1. **Sebastian Huber**, Fri, 15 Jan 2021 05:40:59 GMT

In a08e672/rtems-docs:

eng: Add design group requirement item type

Update #3715.

#### **Comment 43**

1. **Sebastian Huber**, Mon, 08 Feb 2021 14:02:53 GMT

In 174444f/rtems-docs:

eng: Update test case item

Update #3715.

#### **Comment 44**

1. **Sebastian Huber**, Tue, 02 Mar 2021 07:29:25 GMT

In fcac22e/rtems-docs:

eng: Fix typo

Update #3715.

#### **Comment 45**

1. **Sebastian Huber**, Mon, 08 Mar 2021 07:29:24 GMT

In a4b3019/rtems-docs:

eng: Add how-to for action requirements

Update #3715.

#### **Comment 46**

1. **Sebastian Huber**, Mon, 08 Mar 2021 09:19:49 GMT

In e05df28/rtems-docs:

eng: Clarify how-to for action requirements

Update #3715.

#### **Comment 47**

1. **Sebastian Huber**, Thu, 11 Mar 2021 05:57:22 GMT

In 0518d94/rtems-docs:

eng: Clarify how-to for action requirements  
Update #3715.

#### **Comment 48**

1. **Sebastian Huber**, Thu, 11 Mar 2021 06:54:01 GMT

In bc0a857/rtems-docs:

eng: Clarify how-to for action requirements  
Bring how-to in line with current action requirements.  
Update #3715.

#### **Comment 49**

1. **Sebastian Huber**, Fri, 19 Mar 2021 07:20:33 GMT

In 239644b/rtems-docs:

eng: Update EARS syntax  
The document used the EARS syntax from 2009 which slightly changed in 2016, see "Listens Learned (8 Lessons Learned Applying EARS)".  
The optional pre-conditions moved to the state-driven pattern. This refined syntax fits better to the action requirements.  
Update #3715.

#### **Comment 50**

1. **Sebastian Huber**, Fri, 19 Mar 2021 07:20:35 GMT

In b580a6d/rtems-docs:

eng: Add build/appl config clauses to how-to  
Update #3715.

#### **Comment 51**

1. **Sebastian Huber**, Fri, 19 Mar 2021 07:20:37 GMT

In b40e043/rtems-docs:

eng: Document expressions in action requirements  
Update #3715.

#### **Comment 52**

1. **Sebastian Huber**, Fri, 19 Mar 2021 07:20:40 GMT

In 4476290/rtems-docs:

eng: Add example to action requirements how-to  
Update #3715.

#### **Comment 53**

1. **Sebastian Huber**, Tue, 27 Apr 2021 07:46:36 GMT

In 3fa9ed4/rtems-docs:

eng: Allow multiple interface references  
Update #3715.

#### **Comment 54**

1. **Sebastian Huber**, Thu, 29 Apr 2021 05:31:36 GMT



In 889a5ff/rtems-docs:

eng: Remove embedded constraints

Update #3715.

#### **Comment 55**

1. **Sebastian Huber**, Thu, 29 Apr 2021 05:31:39 GMT

In e263e84/rtems-docs:

eng: Add unit test link role

Update #3715.

#### **Comment 56**

1. **Sebastian Huber**, Thu, 29 Apr 2021 09:05:21 GMT

In b6cb057/rtems-docs:

eng: Remove scope from constraints

Use links instead of this special purpose attributes.

Update #3715.

#### **Comment 57**

1. **Sebastian Huber**, Thu, 29 Apr 2021 09:05:24 GMT

In a95c968/rtems-docs:

eng: Add test suite name

Update #3715.

#### **Comment 58**

1. **Sebastian Huber**, Fri, 30 Apr 2021 05:06:27 GMT

In aa0c495/rtems-docs:

eng: Remove text attribute from acfg options

Update #3715.

#### **Comment 59**

1. **Sebastian Huber**, Sat, 08 May 2021 08:27:49 GMT

In b797009/rtems-docs:

eng: Add unspecified interface groups

Update #3715.

#### **Comment 60**

1. **Sebastian Huber**, Tue, 03 Aug 2021 08:40:02 GMT

In 76b5b81/rtems-docs:

eng: Add freestanding test cases

Update #3715.

#### **Comment 61**

1. **Sebastian Huber**, Fri, 10 Sep 2021 14:26:52 GMT

In 7b2b1b4/rtems-docs:

eng: Simplify interface return specification  
Update #3715.

#### **Comment 62**

1. **Sebastian Huber**, Fri, 10 Sep 2021 14:26:54 GMT

In 9dd6135/rtems-docs:

eng: Add interface params/return to typedefs  
Update #3715.

#### **Comment 63**

1. **Sebastian Huber**, Fri, 10 Sep 2021 14:26:57 GMT

In 60e08fd/rtems-docs:

eng: Make interface definitions optional  
Update #3715.

#### **Comment 64**

1. **Sebastian Huber**, Fri, 10 Sep 2021 14:26:59 GMT

In 2df0d64/rtems-docs:

eng: Add hidden interface group membership  
Update #3715.

#### **Comment 65**

1. **Sebastian Huber**, Mon, 24 Jan 2022 14:28:03 GMT

In dd60a4a/rtems-docs:

eng: Add script usage to how-to  
Update #3715.

#### **Comment 66**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:00 GMT

In 889a498d/rtems-docs:

eng: Remove interface container item type  
Update #3715.

#### **Comment 67**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:01 GMT

In c812323/rtems-docs:

eng: Unify interface function and macro  
This allows the documentation of parameter and return types for macros.  
Update #3715.

#### **Comment 68**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:02 GMT

In 1d9f9af/rtems-docs:

eng: Add function implementation link role  
Update #3715.

#### **Comment 69**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:03 GMT

In c909228/rtems-docs:

eng: Refine unspecified interfaces  
Update #3715.

#### **Comment 70**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:05 GMT

In 4966ed0/rtems-docs:

eng: Remove appl config group member link role  
Update #3715.

#### **Comment 71**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:06 GMT

In b55c8bf/rtems-docs:

eng: Use type refinement for validation method  
Update #3715.

#### **Comment 72**

1. **Sebastian Huber**, Tue, 04 Oct 2022 06:29:07 GMT

In 4fdbb23/rtems-docs:

eng: Add memory benchmark type refinement  
Update #3715.

#### **Comment 73**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:52:47 GMT

2. **milestone**: changed from **6.1** to **7.1**

#### **Comment 74**

1. **Sebastian Huber**, Mon, 23 Jan 2023 06:38:37 GMT

In 0b0dd79/rtems-docs:

eng: Use a recommendation for requirement texts  
Update #3715.

#### **Comment 75**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:00 GMT

2. **milestone**: changed from **7.1** to **6.1**

#### **Comment 76**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:26 GMT

In 6dc190b/rtems-docs:

eng: Rework performance measurement items

Use links to specify runtime performance limits in target-specific items. Clarify wording.

Update #3715.

#### **Comment 77**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:27 GMT

In 5928d04/rtems-docs:

eng: Generalize external references

Use a common subtype for external references of interfaces and requirements. Add specializations for document and file references.

Update #3715.

#### **Comment 78**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:29 GMT

In c81a244/rtems-docs:

eng: Add conditional build dependencies

Update #3715.

#### **Comment 79**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:30 GMT

In 98172bc/rtems-docs:

eng: Use type refinement for validation method

Update #3715.

#### **Comment 80**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:31 GMT

In 77e8b56/rtems-docs:

eng: Add optional floating-point number type

Update #3715.

#### **Comment 81**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:32 GMT

In 7158449/rtems-docs:

eng: Update application configuration how-to

Change paths to be in line with the actual specification. Fix group membership link role.

Update #3715.

#### **Comment 82**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:34 GMT

In c69046e/rtems-docs:

eng: Remove obsolete type listing

Update #3715.

#### **Comment 83**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:35 GMT

In 2a5e59d/rtems-docs:

eng: Add design target item type  
Update #3715.

#### **Comment 84**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:36 GMT

In 8bc24e5/rtems-docs:

eng: Add proxy item type  
Update #3715.

#### **Comment 85**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:37 GMT

In 9a5fb29/rtems-docs:

eng: Remove ambiguous interface types  
Use an item proxy instead.  
Update #3715.

#### **Comment 86**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:39 GMT

In 63286a5/rtems-docs:

eng: Add an item type for not defined defines  
This helps to deduce that a missing define in the software design is intended.  
Update #3715.

#### **Comment 87**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:40 GMT

In 2fecb7a/rtems-docs:

eng: Make design group identifiers optional  
Update #3715.

#### **Comment 88**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:41 GMT

In 9c2498a/rtems-docs:

eng: Add unspecified header file item type  
Update #3715.

#### **Comment 89**

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:43 GMT

In 2e939ff/rtems-docs:

eng: Add register block specification types

A register block may be used to specify the interface of devices which contain registers associated with an integer address. Register blocks consist of register block members specified by the definition attribute. Register block members are either instances of registers specified by the registers attribute or instances of other register blocks specified by links with the "register-block-include" link role. Registers consists of bit fields. The register block members are placed into the address space of the device relative to the base address of the register block. Register member offsets and the register block size are specified in units of the address space granule.

Update #3715.

#### **Comment 90**

1. **Sebastian Huber**, Fri, 19 May 2023 05:25:41 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

The initial work for this chapter is now done. The specification of the specification items in rtems-central is in line with the rtems-docs repository. Further work in this area should be done under a new ticket.

---

## **3717 - Add test guidelines chapter to RTEMS Software Engineering Handbook**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3717">https://devel.rtems.org/ticket/3717</a> ( <a href="https://devel.rtems.org/ticket/3717">https://devel.rtems.org/ticket/3717</a> )
<b>Id</b>	3717
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	4 March 2019 12:25:45
<b>Modified</b>	23 October 2023 13:44:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3716
<b>Blocked by</b>	

---

### **Description**

The test guidelines chapter should cover the following topics:

- tools involved in testing
- test classification
- test organization
- how to plan tests
- how to write tests
- how to run tests
- how to report tests

### **Comment 1**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:53:19 GMT
2. **milestone**: changed from **6.1** to **7.1**

### **Comment 2**

1. **Sebastian Huber**, Mon, 26 Jun 2023 14:54:43 GMT

In bb19475/rtems-docs:

```
eng: Add guidelines for validation tests
```

```
Update #3717.
```

### **Comment 3**

1. **Sebastian Huber**, Mon, 23 Oct 2023 13:44:55 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**
4. **milestone**: changed from **7.1** to **6.1**

There is always room improvement, however, the guidelines in the how-to section should do it for now:

<https://docs.rtems.org/branches/master/eng/req/howto.html#>

---

## **3718 - Add support for test plans**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3718">https://devel.rtems.org/ticket/3718</a> ( <a href="https://devel.rtems.org/ticket/3718">https://devel.rtems.org/ticket/3718</a> )
<b>Id</b>	3718
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	4 March 2019 13:02:17
<b>Modified</b>	29 September 2021 13:31:41
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3716
<b>Blocked by</b>	

---

**Description**

Test plans are required by ECSS-Q-ST-40C:

- 5.5.3.2, Software unit testing, a.
- 5.5.4.1, Software integration test plan development
- 5.6.3.1, Development and documentation of a software validation specification with respect to the technical specification, a.

The test plans are a content of several documentation sets. Test plans are subject to verification activities:

- 5.8.3.6, Verification of software unit testing (plan and results)
- 5.8.3.7, Verification of software integration
- 5.8.3.8, Verification of software validation with respect to the technical specifications and the requirements baseline

It should be possible to create documents from individual test plan fragments for a particular test case. There are two approaches possible:

- Add the test plan directly to the test code in form of a specially formatted comment.
- Use separate files with a specific format for test plans.

The test plans should include a

- test identifier,
- test classification (unit, integration, validation),
- test steps,
- links to requirements, design, architecture, unit, component, etc.

It should be possible to verify that a test is executed according to the plan from the test output. For example the test plan could specify test steps. The test output could print the test steps. A tool could check that the test steps in the output and the plan are consistent.

**Comment 1**

1. **Sebastian Huber**, Wed, 29 Sep 2021 13:31:41 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Test cases are specified by specification items:

<https://docs.rtems.org/branches/master/eng/req/items.html#spectypetestcaseitemtype>

---

**3719 - Update libcrypt to latest FreeBSD to address Coverity Scan Issues**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3719">https://devel.rtems.org/ticket/3719</a> ( <a href="https://devel.rtems.org/ticket/3719">https://devel.rtems.org/ticket/3719</a> )
<b>Id</b>	3719
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 March 2019 18:58:44
<b>Modified</b>	31 October 2023 11:46:50
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Coverity issues 1018087, 1018088, 1018089, and 1018090 all appear to be addressed in the latest source code for libcrypt from FreeBSD. This code needs to be updated. This is one of the issues (1018087) in crypt-sha512.c from Scan but the same issues are in sha256.c

```

275     if (copied_key != NULL)
        CID 1018088: 'Constant' variable guards dead code (DEADCODE) [select issue]
276         memset(copied_key, '\0', key_len);
        null: At condition copied_salt != NULL, the value of copied_salt must be NULL.
        dead_error_condition: The condition copied_salt != NULL cannot be true.
277     if (copied_salt != NULL)
        CID 1018087 (#1 of 1): 'Constant' variable guards dead code (DEADCODE)
        dead_error_line: Execution cannot reach this statement: memset(copied_salt, 0, salt...
        Local variable copied_salt is assigned only once, to a constant value, making it effectively constant throughout its scope. If
        this is not the intent, examine the logic to see if there is a missing assignment that would make copied_salt not remain constant.
278         memset(copied_salt, '\0', salt_len);

```

#### Comment 1

1. **Sebastian Huber**, Thu, 19 Dec 2019 08:07:34 GMT
2. **milestone**: changed from **5.1** to **6.1**

#### Comment 2

1. **Sebastian Huber**, Fri, 09 Sep 2022 04:51:17 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

This should be fixed now.

#### Comment 3

1. **Sebastian Huber**, Thu, 22 Sep 2022 06:17:18 GMT

In ade8d99/rtems:

```

build: Install SHA header files
Update #3719.

```

#### Comment 4

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:46:50 GMT
2. **keywords**: **qualification** added

## 3726 - Select a requirements engineering tool

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3726">https://devel.rtems.org/ticket/3726</a> ( <a href="https://devel.rtems.org/ticket/3726">https://devel.rtems.org/ticket/3726</a> )
<b>Id</b>	3726
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	13 March 2019 06:37:47
<b>Modified</b>	18 June 2021 08:08:00
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3703
<b>Blocked by</b>	

#### Description

In order to ease the requirements engineering process (such a process doesn't exist currently, see #3715) select a supporting tool (or tools). Define tool selection criteria. Do a market survey. Use the following wiki page for this work:

Developer/RequirementsEngineering

#### Comment 1

1. **Sebastian Huber**, Fri, 18 Jun 2021 08:08:00 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

The work to select a requirements management tool was done:



## **3818 - New build system**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3818">https://devel.rtems.org/ticket/3818</a> ( <a href="https://devel.rtems.org/ticket/3818">https://devel.rtems.org/ticket/3818</a> )
<b>Id</b>	3818
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 November 2019 08:28:42
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3250
<b>Blocked by</b>	

---

### **Description**

Replace the existing Autoconf and Automake based build system with something new. Goals:

- Easier configuration of BSPs (BSP options)
- Easier to maintain (nobody understands the details of the existing build system)
- Faster builds (especially on Windows)
- Reusable build specifications (e.g. generate documentation for BSP options for the user manual)
- Validation of built artefacts (e.g. ensure that the objects are built as specified using the DWARF debug information)
- Support building of BSPs external to the project
- Customization of the build (e.g. build only a subset of the RTEMS functions)
- Support alternative compilers such as clang instead of GCC

Proposed solution:

- Use waf for the build system
- Specify the build through build specification items maintained by Doorstop

### **Comment 1**

1. **Sebastian Huber**, Thu, 07 Nov 2019 08:30:03 GMT
2. **description**: modified (diff)

### **Comment 2**

1. **Sebastian Huber**, Thu, 07 Nov 2019 08:30:40 GMT
2. **status**: changed from **assigned** to **accepted**

### **Comment 3**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:11 GMT

In 9f3c558/rtems:

```
tests: Remove superfluous SMPTESTS define
Update #3818.
```

### **Comment 4**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:15 GMT

In f32e119/rtems:

```
psxtests: Avoid build system defined defines
Update #3818.
```

### **Comment 5**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:18 GMT

In 150fbaf9/rtems:

```
psxtmtests: Avoid build system defined defines
Update #3818.
```

#### **Comment 6**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:22 GMT

In a467f59/rtems:

```
sptestests: Avoid build system defined defines
Update #3818.
```

#### **Comment 7**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:28 GMT

In 51765553/rtems:

```
sptestests: Remove obsolete semaphore consume driver
This driver is no longer used by a test program.
Update #3818.
```

#### **Comment 8**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:31 GMT

In 5ba4f383/rtems:

```
libttests: Avoid build system defined defines
Update #3818.
```

#### **Comment 9**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:34 GMT

In c89a5dc8/rtems:

```
samples: Avoid build system defined defines
Update #3818.
```

#### **Comment 10**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:40 GMT

In 34cbac1/rtems:

```
tmtests: Avoid build system defined defines
Update #3818.
```

#### **Comment 11**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:43 GMT

In eae263c/rtems:

```
mptests/mp14: Make MAX_LONG_TEST_DURATION constant
If there is a real need, it can be made a configuration option again.
Update #3818.
```

#### **Comment 12**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:46 GMT

In 786ae3f/rtems:

```
ada/samples: Avoid build system defined defines
Update #3818.
```

#### **Comment 13**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:50 GMT

In 0b520cb/rtems:

```
mptests: Avoid build system defined defines
Update #3818.
```

#### **Comment 14**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:53 GMT

In b88c7583/rtems:

```
fstests: Use tmacros.h instead of pmacros.h
This avoids an extra include path.
Update #3818.
```

#### **Comment 15**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:56 GMT

In 37d509b/rtems:

```
libtests: Remove superfluous include path
Update #3818.
```

#### **Comment 16**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:07:59 GMT

In 6da85f49/rtems:

```
block08: Use local include
Update #3818.
```

#### **Comment 17**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:08:03 GMT

In 1e343825/rtems:

```
tests: Simplify fatal error test support
Move system.h to shared init.c.
Update #3818.
```

#### **Comment 18**

1. **Sebastian Huber**, Tue, 12 Nov 2019 09:08:06 GMT

In 1a48cbf/rtems:

```
sptests: Avoid include path magic
Update #3818.
```

#### **Comment 19**

**1. Sebastian Huber, Tue, 12 Nov 2019 09:08:09 GMT**

In f515948/rtems:

```
ada/mptestests: Make them compile clean
Fix all warnings.
Update #3818.
```

**Comment 20****1. Sebastian Huber, Thu, 14 Nov 2019 10:49:27 GMT**

In 984d7443/rtems:

```
bsp/gumstix: Remove ON_SKYEYE Automake conditional
It is fine to build the drivers always.
Update #3818.
```

**Comment 21****1. Sebastian Huber, Thu, 14 Nov 2019 14:10:37 GMT**

In bc28b65/rtems:

```
bsp/beagle: Rename linker command file
This BSP family uses only one linker command file. Use the standard name.
Update #3818.
```

**Comment 22****1. Sebastian Huber, Thu, 14 Nov 2019 14:10:40 GMT**

In 41ab50e4/rtems:

```
bsp/t32mppc: Rename linker command file
This BSP family uses only one linker command file. Use the standard name.
Update #3818.
```

**Comment 23****1. Sebastian Huber, Fri, 15 Nov 2019 06:46:01 GMT**

In 9c601b00/rtems:

```
bsp/i386: Remove unused BSP_HAS_SMP
Update #3818.
```

**Comment 24****1. Sebastian Huber, Fri, 15 Nov 2019 06:46:04 GMT**

In b882b07/rtems:

```
Remove BSP_SMALL_MEMORY BSP option
Use the test state configuration instead.
Update #3818.
```

**Comment 25****1. Sebastian Huber, Fri, 15 Nov 2019 06:46:07 GMT**

In 75d9e79f/rtems:

```
bsp/lpc32xx: Remove unused TESTS_USE_PRINTK
```

Update #3818.

#### **Comment 26**

1. **Sebastian Huber**, Thu, 21 Nov 2019 07:06:00 GMT

In af321aa/rtems:

```
bsp/altcycv_devkit: Rename linker command file
This BSP family uses only one linker command file. Use the standard name.
Update #3818.
```

#### **Comment 27**

1. **Sebastian Huber**, Thu, 21 Nov 2019 07:06:04 GMT

In a52d6174/rtems:

```
bsp/imx7: Rename linker command file
This BSP family uses only one linker command file. Use the standard name.
Update #3818.
```

#### **Comment 28**

1. **Sebastian Huber**, Thu, 21 Nov 2019 07:06:11 GMT

In 38207a31/rtems:

```
Move feature macro before "config.h" include
This allows to use header includes in "config.h" to reduce the build configuration checks.
Update #3818.
```

#### **Comment 29**

1. **Sebastian Huber**, Thu, 21 Nov 2019 07:06:14 GMT

In f377998/rtems:

```
imfs: Add IMFS_make_linfile()
Update #3818.
```

#### **Comment 30**

1. **Sebastian Huber**, Mon, 25 Nov 2019 10:45:38 GMT

In 3e9f5a55/rtems:

```
bsp/gen83xx: Remove obsolete linker command file
Update #3818.
```

#### **Comment 31**

1. **Sebastian Huber**, Mon, 25 Nov 2019 10:45:42 GMT

In 05a32e15/rtems:

```
bsp/mpc55xxevb: Remove obsolete linker cmd file
Update #3818.
```

#### **Comment 32**

1. **Sebastian Huber**, Mon, 25 Nov 2019 10:45:45 GMT

In a0304e8d/rtems:

libtest: Output basename of source files

Output only the basename of source files to be independent of the build system source paths.

In the future it may be better to use the GCC `-fmacro-prefix-map` option. This option is available in GCC 8 and later. It is not yet available in clang.

Update #3818.

### **Comment 33**

1. **Sebastian Huber**, Mon, 25 Nov 2019 10:45:55 GMT

In 273e8b7/rtems:

libtests/tar0[12]:: Use static archive content

This simplifies the build process. Do not generate the archive content through the build system. Let the version control system deal with symbolic links.

Update #3818.

### **Comment 34**

1. **Sebastian Huber**, Mon, 25 Nov 2019 10:45:59 GMT

In 8f021bd/rtems:

libtests/dl\*: Do not generate files via "echo"

Add the static files to the repository. This simplifies the build.

Update #3818.

### **Comment 35**

1. **Sebastian Huber**, Mon, 25 Nov 2019 12:02:10 GMT

In 5c2e7104/rtems:

libtests: Use '-' for TAR file names

Use uniform pattern for all TAR file names. Use the dl\* tests as a template.

Update #3818.

### **Comment 36**

1. **Sebastian Huber**, Tue, 26 Nov 2019 07:35:02 GMT

In 4a05652/rtems:

libtests/dl\*: Rename source files

Rename source files to use a `%c -> %o` and `%cc -> %o` pattern. Use `*.cc` for C++ source files instead of `*.cpp` to be in line with other C++ source files.

Update #3818.

### **Comment 37**

1. **Sebastian Huber**, Wed, 27 Nov 2019 11:03:45 GMT

In 1fca1665/rtems:

testsuites/ada: Introduce `init.c` files

Provide an `init.c` for each Ada test instead of the `#include` magic which works only due to hand crafted include paths.

Update #3818.

### **Comment 38**

1. **Sebastian Huber**, Fri, 29 Nov 2019 18:13:05 GMT

In ae716da/rtems:

ada/sp19: Add m4 generated `sptest.adb`

Update #3818.

#### Comment 39

1. **Sebastian Huber**, Mon, 02 Dec 2019 06:47:45 GMT

In 8f6b7abd/rtems:

Move feature macro before "config.h" include

This allows to use header includes in "config.h" to reduce the build configuration checks.

Update #3818.

#### Comment 40

1. **Sebastian Huber**, Wed, 04 Dec 2019 06:43:57 GMT

In a6879a4/rtems:

testsuites: Remove rtems\_test\_pause\*()

The rtems\_test\_pause() and rtems\_test\_pause and screen\_number() macros had different implementations depending on the RTEMS\_TEST\_NO\_PAUSE define. This define was defined to 1 by default. The user was able to change this via the undocumented --disable-test-no-pause configure command line option.

Pausing tests and waiting for user input contradicts the goal of having automated test runs. Remove this feature.

Update #3818.

#### Comment 41

1. **Sebastian Huber**, Thu, 05 Dec 2019 06:52:52 GMT

In 1380c822/rtems:

bsp/xen: Use BSP options for all linkcmds vars

Update #3818.

#### Comment 42

1. **Sebastian Huber**, Fri, 13 Dec 2019 09:10:28 GMT

In f30dd1f/rtems:

mptests: Fix configuration

Update #3818.

#### Comment 43

1. **Sebastian Huber**, Tue, 25 Feb 2020 07:21:40 GMT

2. **version**: changed from **5** to **6**

3. **milestone**: changed from **5.1** to **6.1**

#### Comment 44

1. **Sebastian Huber**, Mon, 06 Apr 2020 14:01:59 GMT

2. **blocking**: set to **3250**

#### Comment 45

1. **Sebastian Huber**, Sun, 13 Sep 2020 12:01:52 GMT

In 449fc74/rtems-docs:

eng: Add BSP build system chapter

Update #3818.

#### Comment 46

1. **Sebastian Huber**, Sun, 13 Sep 2020 12:01:54 GMT

In 4ea43e3/rtems-docs:

```
user: Document BSP new build system
Update #3818.
```

#### **Comment 47**

1. **Sebastian Huber**, Mon, 14 Sep 2020 07:00:02 GMT

In f3f0370f/rtems:

```
build: Alternative build system based on waf
Update #3818.
```

#### **Comment 48**

1. **kgardas**, Mon, 14 Sep 2020 21:14:39 GMT

with new build system smp enabled build of pc686 fails. Linkage of samples fails with

```
/export/home/karel/sfw/rtems/6-tools-core2/lib/gcc/i386-rtems6/10.2.1/../../../../i386-rtems6/bin/ld: ./librtemsbsp.a(smp-
imps.c.10.o): in function `boot_cpu':
/export/home/karel/git/rtems/rtems-head/build/i386/pc686/../../../../bsps/i386/pc386/start/smp-imps.c:274: undefined reference to
`_binary_appstart_bin_start'
/export/home/karel/sfw/rtems/6-tools-core2/lib/gcc/i386-rtems6/10.2.1/../../../../i386-rtems6/bin/ld:
/export/home/karel/git/rtems/rtems-head/build/i386/pc686/../../../../bsps/i386/pc386/start/smp-imps.c:274: undefined reference to
`_binary_appstart_bin_size'
collect2: error: ld returned 1 exit status
```

that's due to fact this part of Makefile based build was not translated to the new build system:

```
appcpustart.$(OBJEXT): ../../../../../../bsps/i386/pc386/start/startAP.S
$(CPPASCOMPILE) $(AM_CPPFLAGS) -o $@ -c $<
appstart.$(OBJEXT): appcpustart.$(OBJEXT)
$(LD) -N \
-Ttext 0x70000 -e app_processor_start -nostdlib \
-o appstart_tmp.exe $<
$(OBJCOPY) -O binary appstart_tmp.exe appstart.bin
$(OBJCOPY) -I binary -O elf32-i386 -B i386 appstart.bin $@
```

besides this there is also error in files (getcpuid.c seems to be gone, bspsmc.c needs to be there):

```
diff --git a/spec/build/bsps/i386/pc386/objsmc.yml b/spec/build/bsps/i386/pc386/objsmc.yml
index af882cb425..9e83bd7a01 100644
--- a/spec/build/bsps/i386/pc386/objsmc.yml
+++ b/spec/build/bsps/i386/pc386/objsmc.yml
@@ -11,6 +11,7 @@ includes: []
install: []
links: []
source:
-- bsp/i386/pc386/start/getcpuid.c
+#- bsp/i386/pc386/start/getcpuid.c
+- bsp/i386/pc386/start/bspsmc.c
- bsp/i386/pc386/start/smp-imps.c
type: build
```

unfortunately so far I struggle with translating this to waf, probably should look for some waf doc or so. E.g. linking steps of appcpustart.o into appstart.o is what makes me trouble. Also I'm not able to find out how rtemsbsp lib is linked and its dependency specified...

#### **Comment 49**

1. **Sebastian Huber**, Tue, 15 Sep 2020 07:20:48 GMT

In 127c3ea5/rtems:

```
build: Fix i386/pc386 with SMP enabled
Update #3818.
```

#### **Comment 50**

1. **Sebastian Huber**, Tue, 15 Sep 2020 07:24:54 GMT

Replying to kgardas:

```
unfortunately so far I struggle with translating this to waf, probably should look for some waf doc or so. E.g. linking steps of appcpustart.o into appstart.o is
what makes me trouble. Also I'm not able to find out how rtemsbsp lib is linked and its dependency specified...
```

Thanks testing the new build system and for the bug report. I checked in a fix, could you please test if this fixes the issues on this BSP.

Working with waf is also not easy for me. Fortunately, we don't have that many areas in the build which need a special treatment like this. It was the first spot which needed to include a specially build object file in a library.

#### **Comment 51**



1. **kgardas**, Tue, 15 Sep 2020 08:02:05 GMT

Replying to Sebastian Huber:

Replying to kgardas:

unfortunately so far I struggle with translating this to waf, probably should look for some waf doc or so. E.g. linking steps of appcpustart.o into appstart.o is what makes me trouble. Also I'm not able to find out how rtemsbsp lib is linked and its dependency specified...

Thanks testing the new build system and for the bug report. I checked in a fix, could you please test if this fixes the issues on this BSP.

Working with waf is also not easy for me. Fortunately, we don't have that many areas in the build which need a special treatment like this. It was the first spot which needed to include a specially build object file in a library.

Build builds both no-SMP and SMP BSPs fine, but neither of them runs on neither qemu nor on real hardware. If you find helpful, then qemu connected gdb shows those 3 traces over few seconds of BSP run:

```

Program received signal SIGINT, Interrupt.
0x00008d54 in _RBTREE_Insert_inline (less=, key=, the_node=0x5ccc3d04, the_rbtree=0x736f4d74) at
../../../../cpukit/include/rtems/score/rbtree.h:523
523   while ( *link != NULL ) {
(gdb) where
#0 0x00008d54 in _RBTREE_Insert_inline (less=, key=, the_node=0x5ccc3d04, the_rbtree=0x736f4d74) at
../../../../cpukit/include/rtems/score/rbtree.h:523
#1 _Priority_Plain_insert (priority=0, node=0x5ccc3d04, aggregation=0xc031 ) at
../../../../cpukit/include/rtems/score/priorityimpl.h:417
#2 _Thread_queue_Priority_do_enqueue (heads=0xc031 , queue_context=0x6c6c6544, the_thread=0x74 <_establish_stack+19>,
queue=0x726f5020)
   at ../../../../cpukit/score/src/threadqops.c:484
#3 _Thread_queue_Queue_enqueue (enqueue=, initialize=, queue_context=0x6c6c6544, the_thread=0x74 <_establish_stack+19>,
queue=0x726f5020)
   at ../../../../cpukit/score/src/threadqops.c:96
#4 _Thread_queue_Priority_enqueue (queue=0x726f5020, the_thread=0x74 <_establish_stack+19>, queue_context=0x6c6c6544) at
../../../../cpukit/score/src/threadqops.c:566
#5 0x6c616972 in ?? ()
#6 0x00000000 in ?? ()
(gdb) c
Continuing.
^C
Program received signal SIGINT, Interrupt.
0x00008d48 in _Chain_Insert_unprotected (the_node=0x283d4 , after_node=0x9002d0ff) at
../../../../cpukit/include/rtems/score/chainimpl.h:666
666   before_node->previous = the_node;
(gdb) where
#0 0x00008d48 in _Chain_Insert_unprotected (the_node=0x283d4 , after_node=0x9002d0ff) at
../../../../cpukit/include/rtems/score/chainimpl.h:666
#1 _Chain_Prepnd_unprotected (the_node=0x283d4 , the_chain=0x9002d0ff) at ../../../../cpukit/include/rtems/score/chainimpl.h:737
#2 _Thread_queue_Queue_enqueue (enqueue=, initialize=, queue_context=0x6c6c6544, the_thread=0x74 <_establish_stack+19>,
queue=0x726f5020)
   at ../../../../cpukit/score/src/threadqops.c:95
#3 _Thread_queue_Priority_enqueue (queue=0x726f5020, the_thread=0x74 <_establish_stack+19>, queue_context=0x6c6c6544) at
../../../../cpukit/score/src/threadqops.c:566
#4 0x6c616972 in ?? ()
#5 0x00000000 in ?? ()
(gdb) c
Continuing.
^C
Program received signal SIGINT, Interrupt.
0x00008d54 in _RBTREE_Insert_inline (less=, key=, the_node=0x5ccc3d04, the_rbtree=0x736f4d74) at
../../../../cpukit/include/rtems/score/rbtree.h:523
523   while ( *link != NULL ) {
(gdb) where
#0 0x00008d54 in _RBTREE_Insert_inline (less=, key=, the_node=0x5ccc3d04, the_rbtree=0x736f4d74) at
../../../../cpukit/include/rtems/score/rbtree.h:523
#1 _Priority_Plain_insert (priority=0, node=0x5ccc3d04, aggregation=0xc031 ) at
../../../../cpukit/include/rtems/score/priorityimpl.h:417
#2 _Thread_queue_Priority_do_enqueue (heads=0xc031 , queue_context=0x6c6c6544, the_thread=0x74 <_establish_stack+19>,
queue=0x726f5020)
   at ../../../../cpukit/score/src/threadqops.c:484
#3 _Thread_queue_Queue_enqueue (enqueue=, initialize=, queue_context=0x6c6c6544, the_thread=0x74 <_establish_stack+19>,
queue=0x726f5020)
   at ../../../../cpukit/score/src/threadqops.c:96
#4 _Thread_queue_Priority_enqueue (queue=0x726f5020, the_thread=0x74 <_establish_stack+19>, queue_context=0x6c6c6544) at
../../../../cpukit/score/src/threadqops.c:566
#5 0x6c616972 in ?? ()
#6 0x00000000 in ?? ()
(gdb)

```

#### Comment 52

1. **Sebastian Huber**, Tue, 15 Sep 2020 08:09:11 GMT

Replying to kgardas: [...]

Build builds both no-SMP and SMP BSPs fine, but neither of them runs on neither qemu nor on real hardware. If you find helpful, then qemu connected gdb shows those 3 traces over few seconds of BSP run:

With the old build system both configuration work I guess?

What is the qemu command line to test this BSP?

#### Comment 53

1. **kgardas**, Tue, 15 Sep 2020 08:26:14 GMT

Replying to Sebastian Huber:

Replying to kgardas: [...]

Build builds both no-SMP and SMP BSPs fine, but neither of them runs on neither qemu nor on real hardware. If you find helpful, then qemu connected gdb shows those 3 traces over few seconds of BSP run:

With the old build system both configuration work I guess?

Yes, hello/smp works

What is the qemu command line to test this BSP?

```
qemu-system-i386 -m 128 -no-reboot -nographic -append "--video=off --console=/dev/com1" -kernel ./hello.exe
```

#### **Comment 54**

1. **Sebastian Huber**, Tue, 15 Sep 2020 11:33:18 GMT

In 3be23809/rtems:

```
build: Fix i386/pc386 ABI flags
Update #3818.
```

#### **Comment 55**

1. **Sebastian Huber**, Tue, 15 Sep 2020 11:33:22 GMT

In d9d31b3/rtems:

```
build: Add RELOCADDR to i386/pc386 options
Update #3818.
```

#### **Comment 56**

1. **Sebastian Huber**, Tue, 15 Sep 2020 13:14:56 GMT

In 8f424e45/rtems:

```
build: Fix i386/pc386 link of SMP start file
Update #3818.
```

#### **Comment 57**

1. **Sebastian Huber**, Tue, 15 Sep 2020 13:15:00 GMT

In 2a4ccc4/rtems:

```
bsp/pc386: Remove support for obsolete Binutils
Update #3818.
```

#### **Comment 58**

1. **Sebastian Huber**, Tue, 15 Sep 2020 13:16:33 GMT

Replying to kgardas:

Replying to Sebastian Huber:

Replying to kgardas: [...]

Build builds both no-SMP and SMP BSPs fine, but neither of them runs on neither qemu nor on real hardware. If you find helpful, then qemu connected gdb shows those 3 traces over few seconds of BSP run:

With the old build system both configuration work I guess?

Yes, hello/smp works

With the recent fixes I was able to run the tests on Qemu.

What is the qemu command line to test this BSP?

```
qemu-system-i386 -m 128 -no-reboot -nographic -append "---video=off --console=/dev/com1" -kernel ./hello.exe
```

#### **Comment 59**

1. **kgardas**, Tue, 15 Sep 2020 13:47:12 GMT

Replying to Sebastian Huber:

With the recent fixes I was able to run the tests on Qemu.

Thanks a lot for fast fixes! I can confirm running no-SMP hello and SMP smp01 on both qemu and real hardware. Thanks!

#### **Comment 60**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:15 GMT

In 845674e/rtems:

build: Fix mghttpd01 test exclude

Update #3818.

#### **Comment 61**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:18 GMT

In 11c1b862/rtems:

build: Allow test program item UIDs with a "-"

Update #3818.

#### **Comment 62**

1. **Sebastian Huber**, Sun, 20 Sep 2020 15:32:24 GMT

In 2b1a4ac/rtems:

build: Fix linker path

Use -B for the linker since some architectures use extra start files defined by the GCC specification and provided by the BSP, for example powerpc. Start files are not found by -L.

In the long run, the GCC defined start files should be provided by GCC. This is a GCC 11 topic.

Update #3818

#### **Comment 63**

1. **Sebastian Huber**, Mon, 21 Sep 2020 04:47:26 GMT

In d110e6e3/rtems:

bsp/gen83xx: Add missing source file

Update #3818.

#### **Comment 64**

1. **Sebastian Huber**, Fri, 25 Sep 2020 16:51:26 GMT

In 7392632/rtems:

build: Add RTEMS\_PROFILING

Update #3818.

#### **Comment 65**

1. **Sebastian Huber**, Fri, 25 Sep 2020 16:56:48 GMT

In 2fb86e2/rtems-docs:

user: Add migration hints from old build system  
Update #3818.

#### **Comment 66**

1. **Sebastian Huber**, Sun, 27 Sep 2020 07:40:41 GMT

In 9a27c9c/rtems:

build: Simplify get\_compiler()  
Update #3818.

#### **Comment 67**

1. **Sebastian Huber**, Sun, 27 Sep 2020 07:40:44 GMT

In b8d8401/rtems:

build: Fix enabled-by evaluation  
For the enabled-by evaluation we have to use the BSP name defined by the build specification and not the user.  
Update #3818.

#### **Comment 68**

1. **Sebastian Huber**, Sun, 27 Sep 2020 07:40:48 GMT

In 71ccc15/rtems:

build: Fix option default values  
For the option default values we have to use the BSP name defined by the build specification and not the user.  
Update #3818.

#### **Comment 69**

1. **Sebastian Huber**, Mon, 28 Sep 2020 04:21:56 GMT

In cbd4f54/rtems:

build: Add comment  
Update #3818.

#### **Comment 70**

1. **Sebastian Huber**, Wed, 30 Sep 2020 11:02:08 GMT

In 31c333d/rtems:

build: Include cpuopts.h in "config.h"  
The Autoconf/Automake? build system did something similar. This fixes the build of sigprogmask.c which uses RTEMS\_POSIX\_API and expects to get it defined via "config.h".  
Update #3818.

#### **Comment 71**

1. **Sebastian Huber**, Fri, 02 Oct 2020 14:30:05 GMT

In f53712a/rtems:

build: Use exact match by default for BSP names  
Update #3818.

#### **Comment 72**

1. **Sebastian Huber**, Wed, 07 Oct 2020 06:06:50 GMT

In 94b8d85b/rtems:

build: Fix BSP name

Update #3818.

### Comment 73

1. **Sebastian Huber**, Mon, 26 Apr 2021 12:06:12 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

The new build system is operational. Issues with the new build system should use new tickets.

### Comment 74

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT
2. **keywords**: **qualification** added

## 3828 - Switch over to new build system

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3828">https://devel.rtems.org/ticket/3828</a> ( <a href="https://devel.rtems.org/ticket/3828">https://devel.rtems.org/ticket/3828</a> )
<b>Id</b>	3828
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 December 2019 07:59:33
<b>Modified</b>	17 December 2021 14:19:10
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

During a four month period every RTEMS user is encouraged to test its BSPs of interest with the new build system. The user should use the following check list. Issues should be reported on devel@... or this ticket.

- Review the build system specification in the user manual. If something is unclear, please complain.
- Use ".waf bsp\_defaults" to get a list of options with default values for the BSPs of interest. Check that all options are present. Check the type of the options in the build specification (e.g. actions get-integer, get-boolean, get-string). Review the description of the options. Review the default values. Add sanity checks to options (e.g. actions assert-\*).
- Build the BSPs of interest with all tests enabled (BUILD\_TESTS = True). Review the ABI and linker options. Review the linker command files. Run the test on the boards.
- Build the BSPs of interest with different permutations of build options. Make sure a sample set of tests runs for each permutation.
- Check that all artefacts (libraries, header files, start files, linker command files, etc.) are properly installed.
- Check that you can build your applications and third-party libraries with the installed BSPs of interest.

### Comment 1

1. **Sebastian Huber**, Thu, 19 Dec 2019 08:21:07 GMT
2. **version**: changed from **5** to **6**
3. **milestone**: changed from **5.1** to **6.1**

### Comment 2

1. **Christian Mauderer**, Fri, 17 Dec 2021 08:01:03 GMT

RTEMS commit <https://git.rtems.org/rtems/commit?id=db8f598d56951cf43f22a5e325e0d23c8f7559f9> removed the old build system so this ticket is most likely done?

### Comment 3

1. **Joel Sherrill**, Fri, 17 Dec 2021 14:19:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Agreeing with Christian that this ticket is complete. Any issues with the waf build system now are being treated as bugs and the autotools one has been removed.

**3846 - Build system does not track the dependencies of start.o files**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3846">https://devel.rtems.org/ticket/3846</a> ( <a href="https://devel.rtems.org/ticket/3846">https://devel.rtems.org/ticket/3846</a> )
<b>Id</b>	3846
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	18 December 2019 09:36:04
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This defect relates to the new waf based build system.

Most start.o are generated from start.S files which use the C preprocessor. The start.o files are not re-generated if header files (e.g. cpuopts.h, bspopts.h) change. The problem is that the automatic dependency generation via the GCC -MMD flags doesn't work with the current asm rule:

```
def asm(self, bld, bic, source, target=None, deps=[], cppflags=[]):
    if target is None:
        target = os.path.splitext(source)[0] + ".o"
    bld(
        asflags=self.data["asflags"],
        before=["cstlib"],
        cppflags=cppflags + self.data["cppflags"],
        features="asm c",
        includes=bic.includes + self.data["includes"],
        rule="{CC} {ASFLAGS} {CPPFLAGS} {DEFINES_ST:DEFINES} {CPPPATH_ST:INCPATHS} -c {SRC[0]} -o {TGT}",
        source=[source] + deps,
        target=target,
    )
    return target
```

**Comment 1**

1. **Sebastian Huber**, Thu, 17 Sep 2020 06:58:03 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 4eea8d4/rtems:

build: Fix dependencies for start and asm files

Add a feature to enforce an explicit target file for assembler sources. Add a build start file node list and use it as a test program dependency.

The fix for #3846 and #4080 needs to be combined, because the fix for #3846 requires the removal of 'before=cstlib'. This patch fixes two issues:

The tracking of start file dependencies. Reflect that executables depend on the start files. We need a start.o file in the right path so that the linker can find it as specified by the linker script, and not for example a start.S.17.o file in some path. This part is addressed by the "explicit\_asm\_target" feature.

This build process extension

```
@after("apply_link") @feature("cprogram", "cxxprogram") def process_start_files(self):
```

```
    if getattr(self, "start_files", False):
        self.link_task.dep_nodes.extend(self.bld.start_files)
```

addresses 2.

Close #3846. Close #4080.

**Comment 2**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords:** qualification added
- 

**3847 - Test programs are not re-linked if a start.o or linker command file changes**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3847">https://devel.rtems.org/ticket/3847</a> ( <a href="https://devel.rtems.org/ticket/3847">https://devel.rtems.org/ticket/3847</a> )
<b>Id</b>	3847
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	18 December 2019 09:39:08
<b>Modified</b>	28 July 2022 07:17:35
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

The test programs are not re-linked if a start.o or linker command file changes. The dependency tracking doesn't know anything about the linker command files or GCC specification files. The start files are normally included through the linker command file START() directive. Somehow these dependencies must be manually added to the test programs.

#### Comment 1

1. **Sebastian Huber**, Thu, 28 Jul 2022 07:17:35 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **duplicate**

The start.o dependency tracking works, see #4080. For linkcmds issue see #4681.

---

### 3853 - Add and use project-wide glossary to documentation

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3853">https://devel.rtems.org/ticket/3853</a> ( <a href="https://devel.rtems.org/ticket/3853">https://devel.rtems.org/ticket/3853</a> )
<b>Id</b>	3853
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 January 2020 14:19:50
<b>Modified</b>	18 June 2021 09:46:18
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

See discussion:

<https://lists.rtems.org/pipermail/devel/2020-January/056728.html>

Approach A

Use c-user/glossary.rst as the project-wide glossary. Generate document-specific glossaries from this file and the use of :term: in the specific document. Add new waf target ".waf regenerate" to carry out the glossary generation.

Approach B

Move the glossary terms to the RTEMS specification (e.g. in the RTEMS sources "spec/glossary/\*.yml") and generate the glossary.rst for the documents with a script. This gives us more flexibility and removes the need for the special parser code, see:

<https://lists.rtems.org/pipermail/devel/2020-January/056811.html>

The AV-2 mentioned of the DoD Architecture Framework (DoDAF) wants the glossary terms in categories. We could add categories to the glossary specification items. This would be difficult with a master glossary in reST.

#### Comment 1

1. **Sebastian Huber**, Wed, 08 Jan 2020 06:38:00 GMT
2. **description**: modified (diff)

#### Comment 2

1. **Sebastian Huber**, Mon, 24 Feb 2020 13:58:46 GMT

In 03facda/rtems-docs:

```
c-user: Rework glossary
Define exactly one term per definition. Use references for alternative terms. Add :term: text roles to acronym definitions of glossary defined terms.
Update #3853.
```

### **Comment 3**

1. **Sebastian Huber**, Thu, 27 Feb 2020 12:15:10 GMT

In 732c570/rtems-docs:

```
c-user: Canonicalize two glossary acronyms
Add :term: text roles to acronym definitions of glossary defined terms.
Update #3853.
```

### **Comment 4**

1. **Sebastian Huber**, Mon, 02 Mar 2020 07:14:50 GMT

In 43b7eeb/rtems-docs:

```
c-user: Use four spaces per indent level
Four spaces per indent level is used in most files.
Update #3853.
```

### **Comment 5**

1. **Sebastian Huber**, Mon, 02 Mar 2020 07:14:52 GMT

In 834dcf5/rtems-docs:

```
c-user: Clarify return code related terms
Remove duplicate "return code" definition. Add all related terms and use references.
Update #3853.
```

### **Comment 6**

1. **Sebastian Huber**, Mon, 02 Mar 2020 07:14:54 GMT

In d2acba/rtems-docs:

```
c-user: Sort glossary terms
Update #3853.
```

### **Comment 7**

1. **Sebastian Huber**, Mon, 02 Mar 2020 07:14:56 GMT

In 9965922/rtems-docs:

```
c-user: Merge partition term definitions
Update #3853.
```

### **Comment 8**

1. **Sebastian Huber**, Mon, 02 Mar 2020 07:14:58 GMT

In bba4a8c/rtems-docs:

```
c-user: Add copyrights to glossary
Use the file history to derive the copyright information.
```



**Comment 9**

1. **Sebastian Huber**, Mon, 02 Mar 2020 07:15:00 GMT

In 7d05a3d/rtems-docs:

eng: Add glossary

Update #3853.

**Comment 10**

1. **Sebastian Huber**, Tue, 03 Mar 2020 06:19:02 GMT
2. **version**: changed from **5** to **6**
3. **milestone**: changed from **5.1** to **6.1**

A prototype for the RTEMS Specification Items and Qualification Tools is available here:

<https://git.rtems.org/sebh/rtems-qual.git/>

<https://github.com/sebhub/rtems-qual>

**Comment 11**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords**: **qualification** added

**Comment 12**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:46:18 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Glossary term handling is implemented in:

<https://git.rtems.org/rtems-central/>

**3866 - Add support for GCC 10 noinit attribute**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3866">https://devel.rtems.org/ticket/3866</a> ( <a href="https://devel.rtems.org/ticket/3866">https://devel.rtems.org/ticket/3866</a> )
<b>Id</b>	3866
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 February 2020 09:43:33
<b>Modified</b>	23 June 2021 07:16:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

In GCC 10 there is a new common variable attribute noinit:

<https://gcc.gnu.org/onlinedocs/gcc/Common-Variable-Attributes.html#index-noinit-variable-attribute>

<https://gcc.gnu.org/git/gitweb.cgi?p=gcc.git;a=commit;h=f0033821c1c9ba386a1983499a666d5759cdd943>

To support this, a change in the linker command files is necessary.

**Comment 1**

1. **Chris Johns**, Wed, 05 Feb 2020 21:47:47 GMT

Does clang have this support?

**Comment 2**

1. **Sebastian Huber**, Sun, 09 Feb 2020 16:40:17 GMT

clang doesn't support this attribute. I added an enhancement request for this:

[https://bugs.lvm.org/show\\_bug.cgi?id=44811](https://bugs.lvm.org/show_bug.cgi?id=44811)

As a workaround for clang and GCC < 10 you can use the section attribute. The key issue is to have support for .noinit section in the linker command files.

**Comment 3**

1. **Sebastian Huber**, Tue, 25 Feb 2020 07:22:23 GMT

2. **version**: changed from **5** to **6**

3. **milestone**: changed from **5.1** to **6.1**

**Comment 4**

1. **Sebastian Huber**, Sun, 02 May 2021 18:41:04 GMT

In a84bf96/rtems:

```
basedefs: Add RTEMS_NOINIT
Update #3866.
```

**Comment 5**

1. **Sebastian Huber**, Sun, 02 May 2021 18:41:08 GMT

In e10dec0/rtems:

```
bsps: Support RTEMS_NOINIT in linkcmds
Update #3866.
```

**Comment 6**

1. **Sebastian Huber**, Sun, 02 May 2021 18:41:12 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 2df9541/rtems:

```
spmisc01: Test RTEMS_NOINIT
Close #3866.
```

**Comment 7**

1. **Sebastian Huber**, Mon, 03 May 2021 12:05:34 GMT

In eb7c33ad/rtems:

```
bsps/riscv: Support RTEMS_NOINIT in linkcmds
Update #3866.
```

**Comment 8**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:16:03 GMT

2. **keywords**: **qualification** added

---

**3878 - rtems06: All BSPs Fail to build with BSP Builder on rtems 6**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3878">https://devel.rtems.org/ticket/3878</a> ( <a href="https://devel.rtems.org/ticket/3878">https://devel.rtems.org/ticket/3878</a> )
<b>Id</b>	3878
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	20 February 2020 14:12:10
<b>Modified</b>	16 December 2021 15:48:27
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	worksforme
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

I think there are a couple of places in an rtems6 build of RTEMS itself where rtems5 is being used from some hard-coded. Not sure what's up but here's the message to the build@ list.

<https://lists.rtems.org/pipermail/build/2020-February/010431.html>

From the post above, you only see that all failed. Looking at the build log from a single BSP, I see is early which doesn't cause a visible failure

```
gmake[4]: Entering directory `/home/joel/rtems-cron-6/b-jmr3904/mips-rtems6/c/jmr3904/make'
sed \
-e "s|[@]prefix[@]|/home/joel/rtems-cron-6/tools/6/bsp-install|" \
-e "s|[@]exec_prefix[@]|/home/joel/rtems-cron-6/tools/6/bsp-install/mips-rtems6|" \
-e "s|[@]pkgdatadir[@]|/home/joel/rtems-cron-6/tools/6/bsp-install/share/rtems5|" \
```

and this one which is error inducing.

```
: error trying to exec 'mips-rtems5-gcc': execvp: No such file or directory
error: compiling wrapper: Compiler error
gmake[5]: *** [dl08-sym.o] Error 10 ___
```

The first looks like a typo that isn't breaking anything but needs to be fixed.

The latter is some issue during the dl tests using rtems5 or it is hard-coded in a tool somewhere.

**Comment 1**

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:48:27 GMT
  2. **status:** changed from **assigned** to **closed**
  3. **resolution:** set to **worksforme**
- 

**3883 - Trace linker is broken on small-data area targets**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3883">https://devel.rtems.org/ticket/3883</a> ( <a href="https://devel.rtems.org/ticket/3883">https://devel.rtems.org/ticket/3883</a> )
<b>Id</b>	3883
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	25 February 2020 08:17:11
<b>Modified</b>	20 September 2020 15:32:28
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The trace linker generates some data, e.g. `__rtd_trace_names`. The arrays are not declared in a header file as arrays of unspecified size. So, in `rtems-trace-buffer-vars.c` the compiler assumes that the size one weakly defined defaults reside in the small-data area. This leads to linker errors with the strong definitions:

```

Waf: Entering directory `./scratch/git-rtems-examples/build/powerpc-rtems5-qoriq_e6500_32'
[22/29] Processing rtrace: build/powerpc-rtems5-qoriq_e6500_32/filesystem/fat_ramdisk/init.c.6.o build/powerpc-rtems5-
qoriq_e6500_32/filesystem/fat_ramdisk/fs-root-tar.c.6.o -> build/powerpc-rtems5-
qoriq_e6500_32/filesystem/fat_ramdisk/fat_ramdisk.texe
/opt/rtems/5/bin/powerpc-rtems5-gcc: /opt/rtems/5/lib64/gcc/powerpc-rtems5/7.5.0/../../../../powerpc-rtems5/bin/ld:
/opt/rtems/5/powerpc-rtems5/qoriq_e6500_32/lib/librtemscpu.a(rtems-trace-buffer-vars.o): the target (__rtld_trace_names) of a
R_PPC_SDAREL16 relocation is in the wrong output section (.data)
/opt/rtems/5/bin/powerpc-rtems5-gcc: /opt/rtems/5/powerpc-rtems5/qoriq_e6500_32/lib/librtemscpu.a(rtems-trace-buffer-vars.o): in
function `rtems_trace_names':
/opt/rtems/5/bin/powerpc-rtems5-gcc: /home/EB/sebastian_h/git-rtems-5/c/src/../../../../cpukit/libmisc/capture/rtems-trace-buffer-
vars.c:51:(.text.rtems_trace_names+0x2): relocation truncated to fit: R_PPC_SDAREL16 against symbol `__rtld_trace_names' defined in
.data.__rtld_trace_names section in /tmp/ccu6uaaa.o
/opt/rtems/5/bin/powerpc-rtems5-gcc: /opt/rtems/5/lib64/gcc/powerpc-rtems5/7.5.0/../../../../powerpc-rtems5/bin/ld:
/opt/rtems/5/powerpc-rtems5/qoriq_e6500_32/lib/librtemscpu.a(rtems-trace-buffer-vars.o): the target (__rtld_trace_signatures) of a
R_PPC_SDAREL16 relocation is in the wrong output section (.rodata)
/opt/rtems/5/bin/powerpc-rtems5-gcc: /opt/rtems/5/powerpc-rtems5/qoriq_e6500_32/lib/librtemscpu.a(rtems-trace-buffer-vars.o): in
function `rtems_trace_signatures':
/opt/rtems/5/bin/powerpc-rtems5-gcc: /home/EB/sebastian_h/git-rtems-5/c/src/../../../../cpukit/libmisc/capture/rtems-trace-buffer-
vars.c:81:(.text.rtems_trace_signatures+0x2): relocation truncated to fit: R_PPC_SDAREL16 against symbol `__rtld_trace_signatures'
defined in .rodata.  rtld trace signatures section in /tmp/ccu6uaaa.o

```

**Comment 1**

1. **Sebastian Huber**, Sun, 20 Sep 2020 15:16:15 GMT
2. **owner:** changed from **Needs Funding** to **Sebastian Huber**
3. **status:** changed from **assigned** to **accepted**
4. **milestone:** changed from **Indefinite** to **6.1**

**Comment 2**

1. **Sebastian Huber**, Sun, 20 Sep 2020 15:32:28 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 9f2a207/rtems:

```
capture: Move default trace data
```

Provide the default trace data in a separate file to avoid issues on targets with a small-data area.

Close #3883.

**3886 - Fail an RSB build with --mail option if a repo is not clean**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3886">https://devel.rtems.org/ticket/3886</a> ( <a href="https://devel.rtems.org/ticket/3886">https://devel.rtems.org/ticket/3886</a> )
<b>Id</b>	3886
<b>Reporter</b>	Chris Johns
<b>Created</b>	27 February 2020 22:40:21
<b>Modified</b>	12 August 2020 06:56:09
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Fail a build if a user has the --mail option to post the build results and repo is not clean. Public postings of results with local changes has no public value. Users cannot replicate the results if changes are not publically available.

What about a repo that is clean but has changes that are not pushed?

**Comment 1**

1. **Gedare Bloom**, Sun, 05 Apr 2020 04:53:01 GMT

What about for users that want to mail their builds to a non-public destination?

**Comment 2**

1. **Gedare Bloom**, Sun, 05 Apr 2020 04:53:43 GMT
2. **version:** changed from **5** to **6**
3. **milestone:** changed from **5.1** to **6.1**

**Comment 3**

1. **Chris Johns**, Wed, 12 Aug 2020 06:56:09 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Replying to Gedare Bloom:

What about for users that want to mail their builds to a non-public destination?

The user could make a local commit? If this does not matter then this ticket can be closed with wontfix.

**3897 - Dhcpd does not daemonize**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3897">https://devel.rtems.org/ticket/3897</a> ( <a href="https://devel.rtems.org/ticket/3897">https://devel.rtems.org/ticket/3897</a> )
<b>Id</b>	3897
<b>Reporter</b>	Ionut Vilsan
<b>Created</b>	4 March 2020 10:29:59
<b>Modified</b>	8 September 2022 08:15:06
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Background: the DHCP client is started using the rc.conf script. In the background a new task dedicated to the dhcp client is created and then the dhcp client takes over this task. This works fine, we can get IP from the dhcp server and then take part in network communication based on IPv4.

Problem: The dhcp client cannot be stopped any time. Any shell commands will never reach the dhcpd task, but rather it will instantiate a new dhcpd task which will take over the current task. E.g: in rtems console if you enter dhcpd -x, instead of killing the dhcpd task a new dhcpd task will be created which will run from the console. This means that the console cannot be used anymore.

There seems to be no way to communicate with the already created dhcpd task.

I took a look over the dhcpd in libbsd code and some of the features are turned off. Can someone give more details regarding this ?

**Comment 1**

1. **Sebastian Huber**, Fri, 03 Apr 2020 15:01:19 GMT
2. **priority**: changed from **high** to **normal**
3. **resolution**: set to **wontfix**
4. **status**: changed from **assigned** to **closed**
5. **component**: changed from **rtems** to **network/libbsd**
6. **severity**: changed from **major** to **normal**

The dhcpd is not intended to be started via a shell command. Maybe we should remove the shell command.

**Comment 2**

1. **Chris Johns**, Tue, 14 Apr 2020 22:47:44 GMT
2. **status**: changed from **closed** to **reopened**
3. **version**: set to **6**
4. **resolution**: **wontfix** deleted
5. **milestone**: set to **6.1**

Replying to Sebastian Huber:

The dhcpd is not intended to be started via a shell command. Maybe we should remove the shell command.

Reopening this bug. This is either a bug in dhcpd (my view) or the rc.conf support needs to be enhanced to correctly support it. The rc.conf model uses working commands that are wrapped. On FreeBSD the wrapping is using shell scripts and on RTEMS it is a C framework. Another solution is to enhance the shell to push a command into the back ground.

I have stated before now and I will repeat what I have said, rc.conf is the documented method to use libbsd. I know of no other documented method and I am reluctant to expose and support other methods built on RTEMS internal specifics. If other methods exist and are in use then it is those users who are at risk of things changing and breaking on them. We fell into this hole in the legacy stack and I do not wish to repeat doing that here.

**Comment 3**

1. **Joel Sherrill**, Tue, 14 Apr 2020 23:51:19 GMT

Can you file a new ticket for a general solution to spawning a daemon that this ticket will use? Reference this ticket in that one.

**Comment 4**

1. **Sebastian Huber**, Wed, 15 Apr 2020 04:45:06 GMT

The RTEMS shell and the RTEMS rc.conf parser are two different things. This bug here is about controlling (e.g. stopping) the dhcpcd from the RTEMS shell. The dhcpcd is intended to be started at most once and then run forever.

**Comment 5**

1. **Chris Johns**, Thu, 16 Apr 2020 03:32:27 GMT

Replying to Sebastian Huber:

The RTEMS shell and the RTEMS rc.conf parser are two different things.

Is the rc.conf support for dhcpcd using the shell? I am not sure and I have not looked.

This bug here is about controlling (e.g. stopping) the dhcpcd from the RTEMS shell. The dhcpcd is intended to be started at most once and then run forever.

Is this related to our implementation or the upstream sources?

**Comment 6**

1. **Sebastian Huber**, Thu, 08 Sep 2022 08:15:06 GMT

2. **status**: changed from **reopened** to **closed**

3. **resolution**: set to **wontfix**

The dhcpcd is intended to be started at most once and then run forever. This is a limitation of the libbsd port and related to the fact that RTEMS is a single process operating system.

**3910 - Add BSP for STM32H7**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3910">https://devel.rtems.org/ticket/3910</a> ( <a href="https://devel.rtems.org/ticket/3910">https://devel.rtems.org/ticket/3910</a> )
<b>Id</b>	3910
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 March 2020 08:31:22
<b>Modified</b>	31 July 2023 16:12:08
<b>Owner</b>	Sebastian Huber
<b>Type</b>	project
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add a BSP for the STM32H7 series. Import the HAL from [https://github.com/STMicroelectronics/stm32h7xx\\_hal\\_driver](https://github.com/STMicroelectronics/stm32h7xx_hal_driver). Add a VERSION file to allow future updates similar to <https://git.rtems.org/rtems/tree/cpukit/dtc/VERSION>. Add standard clock and console drivers.

**Comment 1**

1. **Sebastian Huber**, Thu, 02 Apr 2020 09:14:25 GMT

In 2c7cd34/rtems-docs:

eng: Add documentation guidelines

Start with templates for the application configuration options.

Remove "Format to be followed for making changes in this file" from c-user.

Update #3910.

**Comment 2**

1. **Mick**, Tue, 20 Oct 2020 15:29:55 GMT

Hi Sebastian, I was keen to use RTEMS on an STM32H7xx board and thought I would reach out and see how the effort was going. I'm not much of a C/C++ dev unfortunately but if there is anything I can do to assist please let me know.

Cheers,

Mick

**Comment 3**

1. **Sebastian Huber**, Wed, 21 Oct 2020 05:59:34 GMT

In 3fccdc95/rtems:

```
bsps/arm: Add support for MPU region alignment
Update #3910.
```

**Comment 4**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:39 GMT

In 2131228/rtems:

```
bsp/stm32h7: Import from STM32CubeMX-5.6.0
Update #3910.
```

**Comment 5**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:43 GMT

In 2cfc00/rtems:

```
bsp/stm32h7: Constify some functions
Update #3910.
```

**Comment 6**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:46 GMT

In 2f157e2/rtems:

```
bsp/stm32h7: Move include
This is necessary for libbsd compatibility.
Update #3910.
```

**Comment 7**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:49 GMT

In abb7858/rtems:

```
bsp/stm32h7: Enable LL drivers
Update #3910.
```

**Comment 8**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:53 GMT

In e4ba06f/rtems:

```
bsp/stm32h7: Disable unused functions
Update #3910.
```

**Comment 9**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:56 GMT

In c44e404/rtems:

bsp/stm32h7: Fix warnings  
Update #3910.

#### **Comment 10**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:14:59 GMT

In 99494370/rtems:

bsp/stm32h7: New BSP  
Update #3910.

#### **Comment 11**

1. **Sebastian Huber**, Tue, 27 Oct 2020 06:51:45 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 8fe0da2/rtems-docs:

user: Add arm/stm32h7  
Close #3910.

#### **Comment 12**

1. **Sebastian Huber**, Thu, 26 Nov 2020 07:37:19 GMT

In fe58f6ce/rtems:

bsp/stm32h7: Add and use BSP Doxygen group  
Update #3910.

#### **Comment 13**

1. **Karel Gardas**, Mon, 31 Jul 2023 16:11:55 GMT

In 4b3d799/rtems:

bsp/stm32h7: Disable unused functions  
Re-apply based on:

commit e4ba06f8b49da4334543f713ba437263c794d7ee Author: Sebastian Huber Date: Thu Apr 2 08:28:56 2020 +0200

bsp/stm32h7: Disable unused functions

Update #3910.

#### **Comment 14**

1. **Karel Gardas**, Mon, 31 Jul 2023 16:11:57 GMT

In ed35850/rtems:

bsp/stm32h7: Enable LL drivers  
Re-apply based on:

commit abb78587b6d1be08697810cdae31cd2dbe35ee4a Author: Sebastian Huber Date: Wed Apr 1 11:11:59 2020 +0200



```
bsp/stm32h7: Enable LL drivers
```

```
Update #3910.
```

**Comment 15**

1. **Karel Gardas**, Mon, 31 Jul 2023 16:12:06 GMT

In ba8ac65/rtems:

```
bsp/stm32h7: Add and use BSP Doxygen group
```

Inspired by:

```
commit fe58f6ce4bf1ff5e92d64b9fee0cb46b6ac06e64 Author: Sebastian Huber Date: Thu Nov 26 08:13:52 2020 +0100
```

```
bsp/stm32h7: Add and use BSP Doxygen group
```

```
Update #3910.
```

**Comment 16**

1. **Karel Gardas**, Mon, 31 Jul 2023 16:12:08 GMT

In f08f75f/rtems:

```
bsps/stm32h7: fix compilation issue after HAL update
```

Based on:

```
commit 99494370d6124ef5d773119fa59f5bac4bbf395f Author: Sebastian Huber Date: Wed Mar 4 12:34:34 2020 +0100
```

```
bsp/stm32h7: New BSP
```

```
Update #3910.
```

**3924 - Test the application configuration options**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3924">https://devel.rtems.org/ticket/3924</a> ( <a href="https://devel.rtems.org/ticket/3924">https://devel.rtems.org/ticket/3924</a> )
<b>Id</b>	3924
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 April 2020 08:35:24
<b>Modified</b>	8 September 2022 08:09:59
<b>Owner</b>	Sebastian Huber
<b>Type</b>	project
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3836

---

**Description**

There exists a specification of the application configuration options (work in progress) here:

<https://git.rtems.org/sebh/rtems-qual.git/tree/spec/acfg/opt/>

For the RTEMS Qualification project we have to test the implementation according to the specification (validation and unit tests).

A test plan needs to be developed. The tests should use the RTEMS Test Framework. Add C preprocessor error tests to the new build system, e.g. test #error and #warning directives.

**Comment 1**

1. **Sebastian Huber**, Thu, 02 Apr 2020 08:39:09 GMT
2. **description**: modified (diff)

**Comment 2**

1. **Sebastian Huber**, Thu, 08 Sep 2022 08:09:59 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

The pre-qualified application configurations are fully specified and validated.

**3925 - Optimize work area initialization**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3925">https://devel.rtems.org/ticket/3925</a> ( <a href="https://devel.rtems.org/ticket/3925">https://devel.rtems.org/ticket/3925</a> )
<b>Id</b>	3925
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 April 2020 08:48:23
<b>Modified</b>	26 January 2022 10:10:10
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	3838

**Description**

The new work area initialization introduced by #3838 introduces a dependency on `_Heap_Extend()` for all BSPs. The BSP knows how many memory areas it delivers to the system. It should provide also the RTEMS Workspace and C Program Heap initialization functions to the system so that an unnecessary pull in of `_Heap_Extend()` can be avoided.

**Comment 1**

1. **Sebastian Huber**, Wed, 26 Jan 2022 10:10:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

This was fixed by `d7205f0083f8dd0408404ce99c6eab9b8d120c7` and `3d0620b607ff6459fec9d30efc1e0589bbd010f9`.

**3929 - Document use of virtualenv**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3929">https://devel.rtems.org/ticket/3929</a> ( <a href="https://devel.rtems.org/ticket/3929">https://devel.rtems.org/ticket/3929</a> )
<b>Id</b>	3929
<b>Reporter</b>	Gedare Bloom
<b>Created</b>	4 April 2020 18:15:30
<b>Modified</b>	29 November 2022 22:04:28
<b>Owner</b>	Needs Funding
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The use of python virtualenv to build docs or use RSB has been suggested a few times. We should provide a brief sketch in our documentation about that utility.

For example, in modern versions of Arch Linux, python is now a shortcut to python3 from the python package. For tools that do not yet function in Python 3, users can set up a virtual environment with Python 2 as follows:

At a root terminal, install python2-virtualenv with pacman.

```
# pacman -S python2-virtualenv
```

Examples of other architectures and uses for virtualenv would round out a reasonable section in the user manual for Preparation.

#### Comment 1

1. **Chris Johns**, Tue, 29 Nov 2022 22:04:28 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

### 3935 - Remove use of RTEMS\_INLINE\_ROUTINE in the RTEMS sources

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3935">https://devel.rtems.org/ticket/3935</a> ( <a href="https://devel.rtems.org/ticket/3935">https://devel.rtems.org/ticket/3935</a> )
<b>Id</b>	3935
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	6 April 2020 07:08:19
<b>Modified</b>	31 October 2023 11:47:17
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

Replace all uses of RTEMS\_INLINE\_ROUTINE with "static inline". This makes it a bit easier for third-party tools to parse the RTEMS sources.

#### Comment 1

1. **Joel Sherrill**, Mon, 06 Apr 2020 13:20:41 GMT

Please cite where "static inline" became part of the C and C++ standards. Eons ago static inline meaning do not include method bodies in the generated object was a GNU extension. Other compilers had their own way of specifying this.

#### Comment 2

1. **Sebastian Huber**, Mon, 06 Apr 2020 13:25:42 GMT

This is C99. The default language version is C11 since a while.

#### Comment 3

1. **Joel Sherrill**, Mon, 06 Apr 2020 13:33:01 GMT

Citation please. Section and paragraph.

#### Comment 4

1. **Sebastian Huber**, Mon, 06 Apr 2020 13:40:56 GMT

I don't understand the problem, we use this for a long time:

```
/**
 * The following (in conjunction with compiler arguments) are used
 * to choose between the use of static inline functions and macro
 * functions. The static inline implementation allows better
 * type checking with no cost in code size or execution speed.
 */
#ifdef __GNUC__
#define RTEMS_INLINE_ROUTINE static __inline__
#else
#define RTEMS_INLINE_ROUTINE static inline
#endif
```

Wikipedia has some background information: [https://en.wikipedia.org/wiki/Inline\\_function](https://en.wikipedia.org/wiki/Inline_function)

#### Comment 5

1. **Sebastian Huber**, Mon, 19 Sep 2022 07:01:30 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In a660e9dc/rtems:

Do not use RTEMS\_INLINE\_ROUTINE

Directly use "static inline" which is available in C99 and later. This brings the RTEMS implementation closer to standard C.

Close #3935.

### Comment 6

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:47:17 GMT
2. **keywords: qualification** added

## 3937 - Move content of bsp\_specs to GCC

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3937">https://devel.rtems.org/ticket/3937</a> ( <a href="https://devel.rtems.org/ticket/3937">https://devel.rtems.org/ticket/3937</a> )
<b>Id</b>	3937
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	6 April 2020 13:59:39
<b>Modified</b>	29 November 2021 14:48:15
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	project
<b>Component</b>	tool/gcc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3250
<b>Blocked by</b>	

### Description

Move content of the bsp\_specs to GCC 10. Once this is done, update the tools and delete the bsp\_specs.

On powerpc this means we have to move the content of rtems\_crti.S to GCC. It may not be possible to back port this to GCC 10 and we may have to maintain this as a patch until GCC 11 is released.

Add support for nostartfiles and nodefaultlibs.

### Attachments:

1. **Sebastian Huber, Tue, 07 Apr 2020 07:35:34 GMT**  
**attach:** set to [0001-RTEMS-Improve-GCC-specification.patch](https://devel.rtems.org/ticket/3937/0001-RTEMS-Improve-GCC-specification.patch) (<https://devel.rtems.org/ticket/3937/0001-RTEMS-Improve-GCC-specification.patch>)
2. **Sebastian Huber, Wed, 08 Apr 2020 11:31:55 GMT**  
**attach:** set to [v2-0001-RTEMS-Improve-GCC-specification.patch](https://devel.rtems.org/ticket/3937/v2-0001-RTEMS-Improve-GCC-specification.patch) (<https://devel.rtems.org/ticket/3937/v2-0001-RTEMS-Improve-GCC-specification.patch>)

### Comment 1

1. **Joel Sherrill**, Mon, 06 Apr 2020 14:01:29 GMT  
 Dupe of #3250

### Comment 2

1. **Sebastian Huber**, Mon, 06 Apr 2020 14:01:59 GMT
2. **blocking:** set to **3250**

### Comment 3

1. **Sebastian Huber**, Mon, 06 Apr 2020 14:03:35 GMT

Replying to Joel Sherrill:

Dupe of #3250

I think this is a subtask.

### Comment 4

1. **Sebastian Huber**, Mon, 06 Apr 2020 14:49:54 GMT

Since -qrtems is not used to build GCC/Newlib. The rtems\_crti.S could probably stay in RTEMS.

**Comment 5**

1. **Joel Sherrill**, Mon, 06 Apr 2020 14:56:00 GMT

The only crti/crtn not provided by GCC are these for the PowerPC. They really should move. Whatever is being done is a hack left over from the days when we were unwilling to modify GCC.

```
$ find . -name rtems crt*
./bSPS/powerpc/shared/start/rtems_crti.S
./bSPS/powerpc/shared/start/rtems_crtn.S
```

"Remove hacks left over from when we were unwilling to modify GCC" should be the name of this ticket. :)

**Comment 6**

1. **Sebastian Huber**, Mon, 06 Apr 2020 14:58:38 GMT

I will try to get the RTEMS-only changes in GCC 10.2. This already requires release manager approval.

I am not sure if they are happy if I try to change standard powerpc files for RTEMS on a release branch.

**Comment 7**

1. **Sebastian Huber**, Tue, 07 Apr 2020 08:18:30 GMT

In b69f54d/rtems-source-builder:

```
6: Update unstable RTEMS 6 tool chain
Update #3937.
```

**Comment 8**

1. **Sebastian Huber**, Wed, 08 Apr 2020 11:34:34 GMT

In f6286ff/rtems-source-builder:

```
6: Update unstable RTEMS 6 tool chain
Update #3937.
```

**Comment 9**

1. **Sebastian Huber**, Fri, 22 Jan 2021 09:52:53 GMT

It turned out that the GCC specs processing is a bit more complicated and the current approach doesn't work:

<https://gcc.gnu.org/pipermail/gcc/2021-January/234728.html>

**Comment 10**

1. **Sebastian Huber**, Fri, 22 Jan 2021 11:59:20 GMT

Proposed workaround:

<https://gcc.gnu.org/pipermail/gcc-patches/2021-January/564101.html>

**Comment 11**

1. **Sebastian Huber**, Tue, 26 Jan 2021 05:38:50 GMT

2. **owner:** set to **Sebastian Huber** <[sebastian.huber@...](mailto:sebastian.huber@...)>

3. **status:** changed from **assigned** to **closed**

4. **resolution:** set to **fixed**

In ade0892/rtems-source-builder:

```
6: Update tool chain
Close #3937.
```

**Comment 12**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT

2. **keywords:** **qualification** added

**Comment 13**

1. **Joel Sherrill**, Mon, 29 Nov 2021 14:48:15 GMT

In dd70c81/rtems:

bsp\_specs: Delete last remnants of these.  
Updates #3937.

---

## **3941 - Remove epiphany architecture support**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3941">https://devel.rtems.org/ticket/3941</a> ( <a href="https://devel.rtems.org/ticket/3941">https://devel.rtems.org/ticket/3941</a> )
<b>Id</b>	3941
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 April 2020 10:09:05
<b>Modified</b>	7 July 2020 13:01:53
<b>Owner</b>	Hesham Almatary
<b>Type</b>	task
<b>Component</b>	arch/epiphany
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	4022
<b>Blocked by</b>	3974

---

### **Description**

I tried to build the epiphany BSP with GCC 10 recently and a lot internal compiler errors appeared. If it is not possible to build the BSP with a released GCC 10.1, then I suggest to remove this architecture. The GDB was never supported by the FSF upstream. To me this looks like an unmaintained architecture.

### **Comment 1**

1. **Hesham Almatary**, Wed, 08 Apr 2020 10:19:55 GMT

I think the development of the Ephipany architecture and its toolchain is already seized. In this case, yes I agree it should be deleted.

### **Comment 2**

1. **Sebastian Huber**, Wed, 08 Apr 2020 10:21:31 GMT

Ok, good. You can still use RTEMS 5 for it. If necessary, the port can be resurrected from this release.

### **Comment 3**

1. **Joel Sherrill**, Wed, 08 Apr 2020 12:07:31 GMT

You can't build rtems5 for epiphany. Mongoose.c has long caused an ICE. GCC has just gotten worse. Removing it after the release is ok by me.

### **Comment 4**

1. **Sebastian Huber**, Thu, 07 May 2020 04:36:41 GMT

2. **blockedby**: set to **3974**

### **Comment 5**

1. **Sebastian Huber**, Fri, 03 Jul 2020 05:42:51 GMT

2. **blocking**: set to **4022**

### **Comment 6**

1. **Sebastian Huber**, Sun, 05 Jul 2020 16:05:54 GMT

In 401b237/rtems:

epiphany: Remove support for this target

Due to an unmaintained toolchain (internal errors in GCC, no FSF GDB integration) the Epiphany architecture was obsoleted in RTEMS 5.1.

Update #3941.

**Comment 7**

1. **Sebastian Huber**, Sun, 05 Jul 2020 16:06:19 GMT

In 2df6f90/rtems-docs:

Reflect removal of the epiphany target  
Update #3941.

**Comment 8**

1. **Sebastian Huber**, Sun, 05 Jul 2020 16:06:39 GMT

In dcceead/rtems-tools:

Remove support for epiphany target  
Update #3941.

**Comment 9**

1. **Sebastian Huber**, Sun, 05 Jul 2020 16:07:55 GMT

In 7f79fe9/rtems-source-builder:

6/7: Remove support for epiphany target  
Update #3941.

**Comment 10**

1. **Sebastian Huber**, Sun, 05 Jul 2020 18:46:17 GMT

In d76e7c1/rtems:

build: Fix RTEMS\_CHECK\_NETWORKING  
Update #3941.

**Comment 11**

1. **Sebastian Huber**, Tue, 07 Jul 2020 13:01:53 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

I updated also the release notes.

**3942 - multiple definition of `pci\_indirect\_functions'**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3942">https://devel.rtems.org/ticket/3942</a> ( <a href="https://devel.rtems.org/ticket/3942">https://devel.rtems.org/ticket/3942</a> )
<b>Id</b>	3942
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 April 2020 10:14:16
<b>Modified</b>	29 November 2022 22:07:19
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/mips
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Building with GCC 10 showed a multiple definition error:

```
/build/rtems/6/lib/gcc/mips-rtems6/10.0.1/../../../../mips-rtems6/bin/ld: ./librtemsbsp.a(i8259.c.19.o):ramdisk/git-rtems-5/build/mips/malta/../../../../bsps/mips/malta/include/bsp/pci.h:113: multiple definition of `pci_indirect_functions'; ./librtemsbsp.a(vectorisrs.c.19.o):ramdisk/git-rtems-5/build/mips/malta/../../../../bsps/mips/malta/include/bsp/pci.h:113: first defined here
/build/rtems/6/lib/gcc/mips-rtems6/10.0.1/../../../../mips-rtems6/bin/ld: ./librtemsbsp.a(simple_access.c.19.o):ramdisk/git-rtems-5/build/mips/malta/../../../../bsps/mips/malta/include/bsp/pci.h:113: multiple definition of `pci_indirect_functions'; ./librtemsbsp.a(vectorisrs.c.19.o):ramdisk/git-rtems-5/build/mips/malta/../../../../bsps/mips/malta/include/bsp/pci.h:113: first defined here
/build/rtems/6/lib/gcc/mips-rtems6/10.0.1/../../../../mips-rtems6/bin/ld: ./librtemsbsp.a(pci.c.19.o):ramdisk/git-rtems-5/build/mips/malta/../../../../bsps/mips/malta/include/bsp/pci.h:113: multiple definition of `pci_indirect_functions'; ./librtemsbsp.a(vectorisrs.c.19.o):ramdisk/git-rtems-5/build/mips/malta/../../../../bsps/mips/malta/include/bsp/pci.h:113: first defined here
```

**Comment 1**

1. **Sebastian Huber**, Wed, 08 Apr 2020 10:14:54 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Gedare Bloom**, Fri, 17 Apr 2020 03:48:04 GMT
2. **version:** changed from 5 to 6
3. **milestone:** changed from 5.1 to 6.1

Bump to 6, gcc10 toolchain issue.

**Comment 3**

1. **Chris Johns**, Tue, 29 Nov 2022 22:07:19 GMT
2. **status:** changed from assigned to closed
3. **resolution:** set to fixed

Looks to be fixed. Please reopen if it is still a problem.

**3947 - fdt\_rw.c: Unchecked return value (CID #1047324)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3947">https://devel.rtems.org/ticket/3947</a> ( <a href="https://devel.rtems.org/ticket/3947">https://devel.rtems.org/ticket/3947</a> )
<b>Id</b>	3947
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	10 April 2020 15:33:05
<b>Modified</b>	19 July 2022 07:29:23
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverity, small, tasks
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

git blams says Sebastian.

```
*** CID 1047324: Error handling issues (CHECKED_RETURN)
/home/joel/rtems-work/rtems/cpukit/dtc/libfdt/fdt_rw.c: 351 in fdt_add_subnode_namelen()
345     if (offset >= 0)
346         return -FDT_ERR_EXISTS;
347     else if (offset != -FDT_ERR_NOTFOUND)
348         return offset;
349
350     /* Try to place the new node after the parent's properties */
>>> CID 1047324: Error handling issues (CHECKED_RETURN)
>>> Calling "fdt_next_tag" without checking return value (as is done elsewhere 7 out of 8 times).
351     fdt_next_tag(fdt, parentoffset, &nextoffset); /* skip the BEGIN_NODE */
352     do {
353         offset = nextoffset;
354         tag = fdt_next_tag(fdt, offset, &nextoffset);
355     } while ((tag == FDT_PROP) || (tag == FDT_NOP));
356
```

**Comment 1**

1. **Joel Sherrill**, Fri, 10 Apr 2020 15:34:56 GMT
2. **keywords:** coverity small tasks added

**Comment 2**



1. **Sebastian Huber**, Fri, 10 Apr 2020 20:13:59 GMT

Maybe this is already fixed in the upstream. Otherwise it should be reported.

### Comment 3

1. **Sebastian Huber**, Fri, 10 Apr 2020 20:15:16 GMT
2. **component**: changed from **admin** to **unspecified**
3. **milestone**: changed from **5.1** to **Indefinite**

### Comment 4

1. **Sebastian Huber**, Tue, 19 Jul 2022 07:29:23 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**
4. **component**: changed from **unspecified** to **lib**
5. **milestone**: changed from **Indefinite** to **6.1**

It is fixed for RTEMS 6.1 through updates from the dtc upstream. Fixing this in RTEMS 5 would require back porting several patches.

## 3951 - Remove obsolete powerpc BSPs

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3951">https://devel.rtems.org/ticket/3951</a> ( <a href="https://devel.rtems.org/ticket/3951">https://devel.rtems.org/ticket/3951</a> )
<b>Id</b>	3951
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 April 2020 15:44:13
<b>Modified</b>	26 January 2022 13:42:27
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	arch/powerpc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Remove powerpc BSPs for unsupported ISA variants (e.g. SPE and the embedded FPU). Remove powerpc BSPs for dead projects. This includes:

- brs5l
- brs6l
- dp2
- mpc5566evb\_spe
- mpc5643l\_dpu
- mpc5643l\_evb
- mpc5674f\_ecu508\_app
- mpc5674f\_ecu508\_boot
- mpc5674f\_evb\_spe
- mpc5674f\_rsm6

### Comment 1

1. **Sebastian Huber**, Sun, 05 Jul 2020 16:01:15 GMT

In 70b803b5/rtems:

```
bsps/powerpc: Remove SPE enabled variants
The PowerPC SPE support was removed from GCC.
Update #3951.
```

### Comment 2

1. **Sebastian Huber**, Sun, 05 Jul 2020 16:01:18 GMT

In 523551cc/rtems:

```
bsps/powerpc: Remove obsolete BSPs
Update #3951.
```

**Comment 3**

1. **Sebastian Huber**, Thu, 10 Dec 2020 07:32:48 GMT

In efda67b/rtems-tools:

```
config: Remove obsolete BSPs
```

```
Update #3951.
```

**Comment 4**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:42:27 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

**3957 - Review wiki/Developer for deletion**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3957">https://devel.rtems.org/ticket/3957</a> ( <a href="https://devel.rtems.org/ticket/3957">https://devel.rtems.org/ticket/3957</a> )
<b>Id</b>	3957
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	16 April 2020 23:51:14
<b>Modified</b>	15 December 2022 16:39:38
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	small, tasks, wiki
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

<https://devel.rtems.org/wiki/Developer> has minimal content. All should likely point to somewhere in the Users Guide now rather than the Wiki.

Also this page is a candidate for deletion. Verify the references and delete it. Check rtems.org also.

**Comment 1**

1. **Joel Sherrill**, Thu, 15 Dec 2022 16:39:38 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **fixed**

4. **milestone**: set to **6.1**

Done. Subtree removed and links now point to the Software Engineering Guide.

**3959 - Add rtems\_task\_construct()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3959">https://devel.rtems.org/ticket/3959</a> ( <a href="https://devel.rtems.org/ticket/3959">https://devel.rtems.org/ticket/3959</a> )
<b>Id</b>	3959
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	17 April 2020 06:55:13
<b>Modified</b>	2 September 2021 05:59:46
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

In RTEMS 5 a lot of development was done to allow a static allocation of resources provided by RTEMS and avoid the use of a heap. One missing piece is the support for statically allocated RTEMS tasks. The `rtems_task_create()` function allocates the task stack from a heap. We need an alternative function which allocates an RTEMS tasks with a user provided stack (similar to the POSIX threads).

There does need to be documentation on the allocation strategies, when to use, limitations, and particularly the use of `rtems-exeinfo` to get the TLS size. This is one case for sure where an RTEMS Tool needs explicit mention in both the API and configure option sections.

#### Proposed API:

```

/**
 * @brief This structure defines the configuration of a task constructed by
 * rtems_task_construct().
 */
typedef struct {
/**
 * @brief This member defines the name of the task.
 */
 rtems_name name;
/**
 * @brief This member defines the initial priority of the task.
 */
 rtems_task_priority initial_priority;
/**
 * @brief This member shall point to the task storage area begin.
 *
 * The task storage area will contain the task stack, the thread-local storage,
 * and the floating-point context on architectures with a separate
 * floating-point context.
 *
 * The task storage area begin address and size should be aligned by
 * #RTEMS_TASK_STORAGE_ALIGNMENT. To avoid memory waste, use RTEMS_ALIGNED()
 * and #RTEMS_TASK_STORAGE_ALIGNMENT to enforce the recommended alignment of a
 * statically allocated task storage area.
 */
 void *storage_area;
/**
 * @brief This member defines size of the task storage area in bytes.
 *
 * Use the RTEMS_TASK_STORAGE_SIZE() macro to determine the recommended task
 * storage area size.
 */
 size_t storage_size;
/**
 * @brief This member defines the maximum thread-local storage size supported
 * by the task storage area.
 *
 * Use RTEMS_ALIGN UP() and #RTEMS_TASK_STORAGE_ALIGNMENT to adjust the size to
 * meet the minimum alignment requirement of a thread-local storage area used
 * to construct a task.
 *
 * If the value is less than the actual thread-local storage size, then the
 * task construction by rtems_task_construct() fails.
 *
 * If the is less than the task storage area size, then the task construction
 * by rtems_task_construct() fails.
 *
 * The actual thread-local storage size is determined when the application
 * executable is linked. The ``rtems-exeinfo`` command line tool included in
 * the RTEMS Tools can be used to obtain the thread-local storage size and
 * alignment of an application executable.
 *
 * The application may configure the maximum thread-local storage size for all
 * threads explicitly through the #CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE
 * configuration option.
 */
 size_t maximum_thread_local_storage_size;
/**
 * @brief This member defines the optional handler to free the task storage
 * area.
 *
 * It is called on exactly two mutually exclusive occasions. Firstly, when the
 * task construction aborts due to a failed task create extension, or secondly,
 * when the task is deleted. It is called from task context under protection
 * of the object allocator lock. It is allowed to call free() in this handler.
 * If handler is NULL, then no action will be performed.
 */
 void ( *storage_free ) ( void * );
/**
 * @brief This member defines the initial modes of the task.
 */
 rtems_mode initial_modes;
/**
 * @brief This member defines the attributes of the task.
 */
 rtems_attribute attributes;
} rtems_task_config;
/**
 * @brief Constructs a task from the specified the task configuration.
 *
 * In contrast to tasks created by rtems_task_create(), the tasks constructed
 * by this directive use a user-provided task storage area. The task storage
 * area contains the task stack, the thread-local storage, and the
 * floating-point context on architectures with a separate floating-point
 * context.
 *
 * This directive is intended for applications which do not want to use the
 * RTEMS Workspace and instead statically allocate all operating system
 * resources. It is not recommended to use rtems_task_create() and
 * rtems_task_construct() together in an application. It is also not
 * recommended to use rtems_task_construct() for drivers or general purpose
 * libraries. The reason for these recommendations is that the task
 * configuration needs settings which can be only given with a through
 * knowledge of the application resources.
 *
 * An application based solely on static allocation can avoid any runtime
 * memory allocators. This can simplify the application architecture as well
 * as any analysis that may be required.
 *
 * The stack space estimate done by assumes that all tasks
 * are created by rtems_task_create(). The estimate can be adjusted to take
 * user-provided task storage areas into account through the
 * #CONFIGURE_MINIMUM_TASKS_WITH_USER_PROVIDED_STORAGE application
 * configuration option.
 *
 * #CONFIGURE_MINIMUM_TASKS_WITH_USER_PROVIDED_STORAGE
 */

```

```

* #ifndef CONFIGURE_MAXIMUM_TASKS should include tasks constructed by
* rtems_task_construct().
*
* @param config is the task configuration.
*
* @param[out] id is the pointer to an object identifier variable. The
* identifier of the constructed task object will be stored in this variable,
* in case of a successful operation.
*
* @retval ::RTEMS_SUCCESSFUL The requested operation was successful.
*
* @retval ::RTEMS_INVALID_ADDRESS The id parameter was NULL.
*
* @retval ::RTEMS_INVALID_NAME The task name was invalid.
*
* @retval ::RTEMS_INVALID_PRIORITY The initial task priority was invalid.
*
* @retval ::RTEMS_INVALID_SIZE The thread-local storage size is greater than
* the maximum thread-local storage size specified in the task configuration.
* The thread-local storage size is determined by the thread-local variables
* used by the application and #CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE.
*
* @retval ::RTEMS_INVALID_SIZE The task storage area was too small to provide
* a task stack of the configured minimum size, see
* #CONFIGURE_MINIMUM_TASK_STACK_SIZE. The task storage area contains the
* task stack, the thread-local storage, and the floating-point context on
* architectures with a separate floating-point context.
*
* @retval ::RTEMS_TOO_MANY There was no inactive task object available to
* construct a task.
*
* @retval ::RTEMS_TOO_MANY In multiprocessing configurations, there was no
* inactive global object available to construct a global task.
*
* @retval ::RTEMS_UNSATISFIED One of the task create extensions failed during
* the task construction.
*
* @retval ::RTEMS_UNSATISFIED In SMP configurations, the non-preemption mode
* was not supported.
*
* @retval ::RTEMS_UNSATISFIED In SMP configurations, the interrupt level mode
* was not supported.
*/
rtems_status_code rtems_task_construct(
  const rtems_task_config *config,
  rtems_id *id
);

```

**Attachments:****1 Sebastian Huber, Fri, 17 Apr 2020 07:32:59 GMT**

**attach:** set to [0001-rtems-Add-rtems\\_task\\_build\\_patch](https://devel.rtems.org/ticket/3959/0001-rtems-Add-rtems_task_build_patch) ([https://devel.rtems.org/ticket/3959/0001-rtems-Add-rtems\\_task\\_build\\_patch](https://devel.rtems.org/ticket/3959/0001-rtems-Add-rtems_task_build_patch))

**Comment 1****1. Sebastian Huber, Wed, 02 Sep 2020 16:03:13 GMT**

In 91c811a1/rtems:

score: Add \_Freechain\_Push()  
Update #3959.

**Comment 2****1. Sebastian Huber, Wed, 02 Sep 2020 16:03:17 GMT**

In 354c2b5/rtems:

score: Add  
Hide implementation details.  
Update #3959.

**Comment 3****1. Sebastian Huber, Wed, 02 Sep 2020 16:03:20 GMT**

In 159db411/rtems:

score: Use \_Freechain\_Push()  
The nodes are never NULL.  
Update #3959.

**Comment 4****1. Sebastian Huber, Wed, 02 Sep 2020 16:03:24 GMT**

In d817220/rtems:

score: Add `_Stack_Allocator_do_initialize()`

Do the stack allocator initialization and sanity check only if a user-provided stack allocator was configured. This avoids a dependency of `_Thread_Handler_initialization()` on the stack allocator.

Update #3959.

#### Comment 5

1. **Sebastian Huber**, Wed, 02 Sep 2020 16:03:27 GMT

In 2d551030/rtems:

score: Move `_Stack_Allocator_free` to separate file

This decouples the task stack allocation from the deallocation.

Update #3959.

#### Comment 6

1. **Sebastian Huber**, Wed, 02 Sep 2020 16:03:30 GMT

In aedd92d/rtems:

score: Add stack free handler to TCB

This avoids a dependency to the stack free function in the thread destruction.

Update #3959.

#### Comment 7

1. **Sebastian Huber**, Thu, 03 Sep 2020 04:33:56 GMT

2. **description:** modified (diff)

3. **summary:** changed from `Add rtems_task_build()` to `Add rtems_task_create_from_config()`

#### Comment 8

1. **Sebastian Huber**, Fri, 11 Sep 2020 13:47:33 GMT

In dd734d46/rtems:

score: Fix `_Thread_initialize()`

Fix an error cleanup path in SMP configurations to avoid a NULL pointer access.

Update #3959.

#### Comment 9

1. **Sebastian Huber**, Sun, 13 Sep 2020 08:25:35 GMT

2. **description:** modified (diff)

#### Comment 10

1. **Chris Johns**, Sun, 13 Sep 2020 23:03:33 GMT

The following are some suggested updates. It is hard to comment on stuff in the ticket header in a way that does not change it so I hope doing this is OK?

Updated ....

```
/**
 * @brief This structure defines a task configuration used to create
 *        a task with user provided storage.
 * This structure defines the configuration of a task created by
 * rtems_task_create_from_config().
 */
```

With this ...

```
* There are no alignment requirements for the task storage area. To avoid
* memory waste, use the #RTEMS_TASK_STORAGE_ALIGNMENT variable attribute to
* enforce the recommended alignment of the task storage area.
```

... I understand the alignment for a user is anything but internally the memory may be aligned and that will potentially create some waste. For example I could provide `0x1` as an address but the stack base or the start of the TLS may need to be aligned depending on the `arch`, `_TLS_Alignment`, or something. Does this need to be explained?

Updated ...

```
* It is called when the task creation aborts due to a failed task create
* extension or the task is deleted. It is called from task context under
* protection of the object allocator lock. It is allowed to call free() in
* this handler. The handler may be NULL to disable.
```

**Updated ...**

```
* @brief Creates a task from the specified the task configuration.
*
* In contrast to tasks created by rtems_task_create(), the tasks created by
* this directive use a user-provided task storage area. The task storage area
* contains the task stack, the thread-local storage, and the floating-point
* context on architectures with a separate floating-point context.
*
* It is recommended rtems_task_create() and rtems_task_create_from_config()
* are not used together in an application. This means
* rtems_task_create_from_config() is not recommended for drivers or libraries
* an application may use. This directive is intended for applications which
* do not want to use the RTEMS Workspace and instead statically allocate all
* operating system resources.
*
* An application based solely on static allocation can avoid any runtime
* memory allocators. This can simplify the application architecture as well
* as any analysis that may be required.
*
* The stack space estimate done by assumes that all tasks
* are created by rtems_task_create(). The estimate can be adjusted to take
* user-provided task storage areas into account through the
* #CONFIGURE_TASKS_CREATED_FROM_CONFIG application configuration option or a
* custom task stack allocator, see #CONFIGURE_TASK_STACK_ALLOCATOR.
*
* The #CONFIGURE_MAXIMUM_TASKS should includes tasks created with
* rtems task create from config().
```

**Comment 11**

1. **Sebastian Huber**, Mon, 14 Sep 2020 17:48:12 GMT

Yes, the storage internal alignment is something which needs to be better explained.

I think we should change `RTEMS_TASK_STORAGE_ALIGNMENT` to be just the alignment value and say that the maximum thread-local storage size shall have at least this alignment.

`CONTEXT_FP_SIZE` should be aligned by `RTEMS_TASK_STORAGE_ALIGNMENT`. For `RTEMS_TASK_STORAGE_ALIGNMENT` we should use `CPU_HEAP_ALIGNMENT`.

**Comment 12**

1. **Chris Johns**, Tue, 15 Sep 2020 02:50:02 GMT

Sure. What about adding "RTEMS\_TASK\_STORAGE\_ALIGNMENT will optimally use the provided storage"? We do not need to hand hold into the detail but we should hint at the best approach.

**Comment 13**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:22 GMT

In 641b31a4/rtems:

```
rtems: Add RTEMS_ALIGN_DOWN()
Update #3959. Update #4074.
```

**Comment 14**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:25 GMT

In dce1cdf1/rtems:

```
rtems: Add RTEMS_ALIGN_UP()
Update #3959. Update #4074.
```

**Comment 15**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:32 GMT

In 6942e5f/rtems:

```
rtems: Add rtems_task_construct()
```

In contrast to `rtems_task_create()` this function constructs a task with a user-provided task storage area. The new directive uses a configuration structure instead of individual parameters.

Add `RTEMS_TASK_STORAGE_SIZE()` to calculate the recommended size of a task storage area based on the task attributes and the size dedicated to the task stack and thread-local storage. This macro may allow future extensions without breaking the API.

Add application configuration option `CONFIGURE_MINIMUM_TASKS_WITH_USER_PROVIDED_STORAGE` to adjust RTEMS Workspace size estimate.

```
Update #3959.
```

**Comment 16**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:36 GMT

In ad22c65/rtems:

```
doxygen: Move top-level group definitions
Update #3959.
```

**Comment 17**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:39 GMT

In 139ffa2/rtems:

```
validation: Add general purpose test suite
Add a general purpose test suite for validation tests.
This is the first test suite generated from a specification item in the rtems-central repository.
Update #3959.
```

**Comment 18**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:42 GMT

In 3dd4cbb/rtems:

```
validation: rtems_task_construct() errors
This is the first test case generated from a specification item in the rtems-central repository.
Update #3959.
```

**Comment 19**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:14:45 GMT

In 28db972/rtems-docs:

```
c-user: CONFIGURE_MINIMUM_TASKS_WITH_USER_PROVIDED_STORAGE
Document this application configuration option.
Update #3959.
```

**Comment 20**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:17:25 GMT

2. **description**: modified (diff)

3. **summary**: changed from **Add rtems\_task\_create\_from\_config()** to **Add rtems\_task\_construct()**

**Comment 21**

1. **Sebastian Huber**, Thu, 17 Sep 2020 18:08:26 GMT

In 2f65e13/rtems:

```
rtems: Fix typo
Update #3959.
```

**Comment 22**

1. **Sebastian Huber**, Fri, 23 Apr 2021 06:25:33 GMT

In f14cf0c/rtems:

```
rtems: Check for NULL config in task construct
Since there are already excessive NULL pointer checks in the Classic API, do this also in rtems_task_construct().
Update #3959.
```

**Comment 23**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** **qualification** added

**Comment 24**

1. **Sebastian Huber**, Thu, 02 Sep 2021 05:59:46 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

The new directive was documented, implemented, and tested:

<https://docs.rtems.org/branches/master/c-user/task/directives.html#rtems-task-construct>

---

**3962 - Licensing Requirements for Submissions Poorly Documented**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3962">https://devel.rtems.org/ticket/3962</a> ( <a href="https://devel.rtems.org/ticket/3962">https://devel.rtems.org/ticket/3962</a> )
<b>Id</b>	3962
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	20 April 2020 18:32:47
<b>Modified</b>	1 May 2020 16:12:46
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	major
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The discussion of licensing for code/docs in RTEMS is a bit of a mess right now. After posting this issue to the mailing list (<https://lists.rtems.org/pipermail/devel/2020-April/059489.html>), Sebastian pointed out where the actual recommended text for code/docs was located.

SW Engineering Guide sections 6.3.1.2 (Licenses) and 11 (Licensing Requirements) are somewhat overlapping and duplicative. In addition, Gedare's old blog <http://gedare-csphd.blogspot.com/2013/05/software-licenses-with-rtems.html> is still a decent discussion of the underlying issues and goals even though we have moved to BSD-2 and Creative Commons for documentation since he wrote that in 2013.

The above references just describe the rationale and cite the licenses. For an example of what to put in the code, you have to visit <https://docs.rtems.org/branches/master/eng/coding-file-hdr.html#copyright-and-license-block>

I THINK a good solution would be to reference the Chapter 11 Licensing Requirements from the Coding Conventions chapter. And incorporate an updated version of Gedare's blog text.

**Comment 1**

1. **Chris Johns**, Sun, 26 Apr 2020 23:30:12 GMT

Is this being worked on for the RTEMS 5 release?

**Comment 2**

1. **Sebastian Huber**, Mon, 27 Apr 2020 12:14:01 GMT

Yes, this needs to be fixed, however, it is not release critical from my point of view. This stuff is important for new contributors and they should focus on the master. I would move the milestone to 6.1.

**Comment 3**

1. **Gedare Bloom**, Thu, 30 Apr 2020 03:36:35 GMT
2. **owner:** set to **Gedare Bloom**
3. **status:** changed from **new** to **accepted**
4. **milestone:** changed from **5.1** to **6.1**

**Comment 4**

1. **Joel Sherrill**, Fri, 01 May 2020 16:12:46 GMT
2. **status:** changed from **accepted** to **closed**



3. **resolution:** set to **fixed**

In 2d22d74/rtems-docs:

Rework RTEMS licensing discussions.

This now captures historical rationale along with cross-linking code templates with license guidelines.

Closes #3962.

## 3977 - Add unexplained-failure as option for Test Configuration Files

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3977">https://devel.rtems.org/ticket/3977</a> ( <a href="https://devel.rtems.org/ticket/3977">https://devel.rtems.org/ticket/3977</a> )
<b>Id</b>	3977
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	10 May 2020 16:34:31
<b>Modified</b>	29 November 2022 23:16:56
<b>Owner</b>	joel@...
<b>Type</b>	enhancement
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

RTEMS has many BSPs and it is a large amount of work to investigate each test execution that has an unexpected result. The tcfg files were initially created to just avoid trying build tests where the executable did not fit into target memory. That has grown to incorporate knowledge about which tests require human input and are not automated. This ticket is to add a new test state for "unexplained failure".

If a test has been investigated and has an explanation, it is a known failure. This could be associated with a ticket (e.g. dynamic loading or fenv not supported on an architecture) or just a comment explaining it (e.g. mips jmr3904 simulator trapping invalid memory accesses before the trap handler is tripped).

But many tests are currently just marked as failures because they do fail but no one has investigated and explained it. The addition of "unexplained failure" is to capture those. This will make it possible for someone looking to know they need investigating but are known to fail. Marking these as "known failure" permanently puts them in a category where they will not get looked at again.

This has two side-effects. The first is that we can have test results with no "unexpected failures." They are either known and explained or known and need investigation. This helps anyone looking at test results since there should be no unexpected failures. The second side-effect is that it hopefully captures the set of repeatedly failing tests and encourages us to investigate and file tickets or explain.

The milestone for this is NOT 5.x because this is moving the goalpost for test results. Release 5.x is the first with the body of test results data we have. The build@ mailing list has them and can be compared by any user interested. We also do not have a way to machine check results yet which would ease checking the test results for deviations.

Note: As an odd case, there are multiple BSPs where the executables can run on hardware or 1+ simulators. Sometimes the results vary across the target environment even for the same executable. This is at least something to consider as we want to have a trustworthy and checkable set of test results available.

### Comment 1

1. **Chris Johns**, Wed, 13 May 2020 01:32:55 GMT

For the record the TCFG files were created to manage the states for the tester. The change included excluding a test. The tester command had the state checks and handling added in April 2017. The test states were also added to rtems.git at this time so all states have been present and documented in README.testdata together. I also raised #2962 at the time to indicate we need to manage this before we release.

From my point of view and rtems-test nothing has changed. What was added did not set a policy for managing failures or the relationship to releasing and any failure, known, expected or otherwise is just a failure. The tester either expects to see a failure or it does not for accounting purposes only.

I have gone away and spent time looking at adding this state and the change feels wrong because this state and any like it are basically a logical OR of expected-fail and the tester does not care about a policy that manages this or arrives at the expected fail state. The end goal is to have ./waf test that runs all the tests on a configured test harness and waf returns a non-zero exit code for any regressions from the build's baseline. I doubt we have single BSP that does this on any test harness.

We should actively discourage specific test analysis from test results as they are simply a tool to account for a build's baseline. The result's stats should be bounded and consistent and provide a simple way to have a machine determine the state of a build.

I have posted a detailed alternative. For these to work we will need a workable set of policies for the management of test failures.

I think it is unrealistic to expect RTEMS to have 100% pass on all tests on all BSPs on all test platforms a BSP supports. There will be failures. There has been little or no analysis of existing tests that fail captured and accounted for so I dispute the assertion moving them to expected failures will stop any analysis. I believe the solution to this issue lies elsewhere.

I am fine with tests that have no analysis being left as unexpected failures but we need a way for buildbot or any other CI tool to run the test suite on selected profiles to know if a change has caused a regression. Any test failure in a clean clone from rtems.git breaks the ability to do this. This is the first thing we need to fix.

Transitioning from the current state to one where the tester can detect regressions requires some effort. It is unfair to instantly say "all commits to rtems.git must have no unexpected results for BSP XXX on YYYY" if this is the policy. I do think we need to select a few key BSPs and test harnesses that are required to have no unexpected results before a release can be made.

I would like to close this ticket and open a new one for the tester state changes. I suggest a ticket to document the unexpected results policy be created.

### Comment 2

1. **Chris Johns**, Fri, 25 Sep 2020 01:20:22 GMT

This ticket should be closed. Please close.

### Comment 3

1. **Chris Johns**, Tue, 29 Nov 2022 23:16:56 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **invalid**

## 3978 - Move `_RTEMS_version` to implementation header file

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3978">https://devel.rtems.org/ticket/3978</a> ( <a href="https://devel.rtems.org/ticket/3978">https://devel.rtems.org/ticket/3978</a> )
<b>Id</b>	3978
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2020 05:48:32
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3972
<b>Blocked by</b>	3970

### Description

The global variable `_RTEMS_version` was declared via `and` and may be used directly by application code. Applications should use `rtems_get_version_string()` instead. Move it to an implementation header file in RTEMS 6.

### Comment 1

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:24 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 9039011/rtems:

```
rtems: Move declartion of _RTEMS_version
Close #3978.
```

### Comment 2

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

## 3979 - Remove `RTEMS_MAXIMUM_NAME_LENGTH`

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3979">https://devel.rtems.org/ticket/3979</a> ( <a href="https://devel.rtems.org/ticket/3979">https://devel.rtems.org/ticket/3979</a> )
<b>Id</b>	3979
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2020 05:49:22
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3972, 3993
<b>Blocked by</b>	3971

**Description**

Remove this deprecated define.

**Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: changed from **3972** to **3972, 3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:28 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In b3686d7/rtems:

```
rtems: Remove RTEMS_MAXIMUM_NAME_LENGTH
```

Close #3979.

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

**3980 - Remove deprecated <rtems/system.h>**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3980">https://devel.rtems.org/ticket/3980</a> ( <a href="https://devel.rtems.org/ticket/3980">https://devel.rtems.org/ticket/3980</a> )
<b>Id</b>	3980
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2020 05:50:27
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3972

**Description**

This header file is included by and contains only deprecated or internal content. Remove this deprecated header file.

**Comment 1**

1. **Sebastian Huber**, Mon, 11 May 2020 06:15:27 GMT
2. **version**: changed from **5** to **6**
3. **milestone**: changed from **5.1** to **6.1**

**Comment 2**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 3**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:35 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 39c2e28/rtems:

rtems: Remove deprecated

Close #3980.

#### Comment 4

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords: qualification** added
- 

### 3981 - Remove \_Copyright\_Notice from API header file

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3981">https://devel.rtems.org/ticket/3981</a> ( <a href="https://devel.rtems.org/ticket/3981">https://devel.rtems.org/ticket/3981</a> )
<b>Id</b>	3981
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2020 06:25:06
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3973

---

#### Description

Remove \_Copyright\_Notice from API header file. Applications should use rtems\_get\_copyright\_notice() which is available since RTEMS 5.

#### Comment 1

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking: set to 3993**

#### Comment 2

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:32 GMT
2. **status: changed from assigned to closed**
3. **resolution: set to fixed**

In 479b2bf/rtems:

```
rtems: Remove _Copyright_Notice from API header
Close #3981.
```

#### Comment 3

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords: qualification** added
- 

### 3982 - Test failures on BSPs with sbrk() support

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3982">https://devel.rtems.org/ticket/3982</a> ( <a href="https://devel.rtems.org/ticket/3982">https://devel.rtems.org/ticket/3982</a> )
<b>Id</b>	3982
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	12 May 2020 06:57:23
<b>Modified</b>	10 February 2021 06:30:29
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

There are some test failures on BSPs with sbrk() support such as psim, for example psxpipe01:

```
#0 rtems_heap_extend_via_sbrk (heap=0x30468 < Malloc_Heap>, alloc_size=5) at
/home/EB/sebastian_h/src/rtems/c/src/../../cpukit/libcsupport/src/rtems_heap_extend_via_sbrk.c:41
#1 0x00005b48 in rtems_heap_allocate_aligned_with_boundary (size=size@entry=5, alignment=alignment@entry=0,
boundary=boundary@entry=0) at /home/EB/sebastian_h/src/rtems/c/src/../../cpukit/libcsupport/src/malloc_deferred.c:116
#2 0x00005930 in malloc (size=size@entry=5) at /home/EB/sebastian_h/src/rtems/c/src/../../cpukit/libcsupport/src/malloc.c:39
#3 0x0001b720 in malloc_r (ignored=ignored@entry=0x2fa68 < RTEMS_tasks_Objects+736>, size=size@entry=5) at
/home/EB/sebastian_h/src/rtems/c/src/../../cpukit/libcsupport/src/_malloc_r.c:26
#4 0x00015ff4 in _strdup_r (reent_ptr=0x2fa68 < RTEMS_tasks_Objects+736>, str=str@entry=0x1ce94 "/tmp") at ../../../../gcc-
7.5.0/newlib/libc/string/strdup_r.c:10
#5 0x00015fbc in strdup (str=str@entry=0x1ce94 "/tmp") at ../../../../gcc-7.5.0/newlib/libc/string/strdup.c:10
#6 0x00011470 in rtems_mkdir (path=path@entry=0x1ce94 "/tmp", mode=mode@entry=511) at
/home/EB/sebastian_h/src/rtems/c/src/../../cpukit/libcsupport/src/rtems_mkdir.c:133
#7 0x0000a7c8 in pipe (fildes=fildes@entry=0x36ce8) at
/home/EB/sebastian_h/src/rtems/c/src/../../cpukit/libfs/src/pipe/pipe.c:42
#8 0x000004a0 in Init (ignored=) at /home/EB/sebastian_h/src/rtems/c/src/../../testsuites/psxtests/psxpipe01/init.c:65
#9 0x0000c828 in Thread_Handler () at /home/EB/sebastian_h/src/rtems/c/src/../../cpukit/score/src/threadhandler.c:139
#10 0x0000c77c in Thread_Get (id, lock context=) at /home/EB/sebastian_h/src/rtems/c/src/../../cpukit/score/src/threadget.c:43
```

The problem is that an rtems\_heap\_greedy\_allocate() is ineffective due to the automatic heap extension.

**Comment 1**

1. **Chris Johns**, Mon, 08 Feb 2021 06:47:43 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 7ca3b28/rtems:

```
libcsupport: Have greedy allocations use consume extended memory
Call the heap extend handler until all memory has been
requested.
Closes #3982
```

**Comment 2**

1. **Chris Johns**, Mon, 08 Feb 2021 22:33:47 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

This ticket is being reopened and extended to cover other greedy implementation. There is also rtems\_workspace\_greedy\_allocate() and friends.

**Comment 3**

1. **Chris Johns**, Wed, 10 Feb 2021 06:30:29 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 03dff201/rtems:

```
libcsupport: Add sbrk greedy support to consume all sbrk memory
Move the heap sbrk code into a separate routine. Update heap and workspace greedy allocators to use the common
sbrk greedy support.
Closes #3982
```

**3988 - Remove deprecated rtems\_extension**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3988">https://devel.rtems.org/ticket/3988</a> ( <a href="https://devel.rtems.org/ticket/3988">https://devel.rtems.org/ticket/3988</a> )
<b>Id</b>	3988
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	28 May 2020 12:17:13
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	

---

**Description****Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:49 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 6a3fcd4/rtems:

```
rtems: Remove deprecated rtems_extension
```

```
This type was deprecated in RTEMS 5.1.
```

```
Close #3988.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords**: **qualification** added
- 

**3989 - Remove deprecated rtems\_get\_current\_processor()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3989">https://devel.rtems.org/ticket/3989</a> ( <a href="https://devel.rtems.org/ticket/3989">https://devel.rtems.org/ticket/3989</a> )
<b>Id</b>	3989
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	28 May 2020 13:28:09
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3731

---

**Description****Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:42 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In e4215e43/rtems:

```
rtems: Remove rtems_get_current_processor()
This function was deprecated in RTEMS 5.1.
Close #3989.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

**3990 - Remove deprecated rtems\_get\_processor\_count()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3990">https://devel.rtems.org/ticket/3990</a> ( <a href="https://devel.rtems.org/ticket/3990">https://devel.rtems.org/ticket/3990</a> )
<b>Id</b>	3990
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	28 May 2020 13:29:14
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	3993
<b>Blocked by</b>	3732

**Description****Comment 1**

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **blocking**: set to **3993**

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Jul 2020 05:26:46 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 13a4b880/rtems:

```
rtems: Remove rtems_get_processor_count()
This function was deprecated in RTEMS 5.1.
Close #3990.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

**3991 - Remove deprecated Thread typedef**





Examples for interface specification items are available here:

<https://git.rtems.org/sebh/rtems-qual.git/tree/spec/ifs/rtems/status>

You find an example for a generated header file here:

<https://git.rtems.org/sebh/rtems.git/tree/cpukit/include/rtems/rtems/status.h?h=qual>

The header files are generated by this script:

<https://git.rtems.org/sebh/rtems-qual.git/tree/spec2rtems.py>

As preliminary work, remove all RTEMS APIs deprecated in RTEMS 5.1.

Use and improve the Interface Specification How-To during the work on this ticket.

Carry out the following tasks for each header file:

- Add a interface specification item for each variable, typedef, enum, enumerator, define, macro, function, struct, and union.
- For each item analyse the change history using `git log -p --follow` to determine the copyright holders of the Doxygen markup. Use only Doxygen markup for the specification items from contributors which agreed on a dual-licensing (CC-BY-SA-4.0 OR BSD-2-Clause) in #3899. Use this information to provide copyright statements for the items. The API parts alone (e.g. function names, parameter names, type names, etc.) are not considered to be copyrightable information.
- Use the RTEMS documentation sources to document the API. Use only content from contributors which agreed on a dual-licensing (CC-BY-SA-4.0 OR BSD-2-Clause) in #3899.
- Add unspecified interface items for interfaces to the implementation, C language, compiler, user provided defines, build system provided defines, etc.
- Run the RTEMS test suite with all tests enabled and check for regressions (in particular new warnings).
- Create a commit for each header file and send it to the RTEMS mailing list for review.

#### Comment 1

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:16:17 GMT
2. **description**: modified (diff)
3. **blockedby**: set to **3584, 3588, 3590, 3592, 3594, 3596, 3686, 3979, 3980, 3981, 3988, 3989, 3990**

#### Comment 2

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:17:38 GMT
2. **blockedby**: changed from **3584, 3588, 3590, 3592, 3594, 3596, 3686, 3979, 3980, 3981, 3988, 3989, 3990** to **3584, 3588, 3590, 3592, 3594, 3596, 3979, 3980, 3981, 3988, 3989, 3990**

#### Comment 3

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:19:05 GMT
2. **blockedby**: changed from **3584, 3588, 3590, 3592, 3594, 3596, 3979, 3980, 3981, 3988, 3989, 3990** to **3584, 3586, 3588, 3590, 3592, 3594, 3596, 3979, 3980, 3981, 3988, 3989, 3990**

#### Comment 4

1. **Sebastian Huber**, Mon, 01 Jun 2020 11:46:42 GMT
2. **description**: modified (diff)

#### Comment 5

1. **Sebastian Huber**, Thu, 04 Jun 2020 12:32:13 GMT
2. **owner**: set to **Sebastian Huber**
3. **status**: changed from **assigned** to **accepted**
4. **description**: modified (diff)

#### Comment 6

1. **Sebastian Huber**, Thu, 04 Jun 2020 17:38:29 GMT
2. **description**: modified (diff)

#### Comment 7

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:43 GMT

In 16ee8cf/rtems-docs:

c-user: Split up semaphore manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 8**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:46 GMT

In ba6825c/rtems-docs:

c-user: Split up event manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 9**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:48 GMT

In 91f0f97/rtems-docs:

c-user: Split up barrier manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 10**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:50 GMT

In 86c39ef/rtems-docs:

c-user: Split up clock manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 11**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:52 GMT

In 623a9a1/rtems-docs:

c-user: Split up dual-ported memory manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 12**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:54 GMT

In 72295d4/rtems-docs:

c-user: Split up interrupt manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 13**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:57 GMT

In 980734f/rtems-docs:

c-user: Split up IO manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

#### **Comment 14**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:00:59 GMT

In c75ded2/rtems-docs:

c-user: Split up message manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

#### **Comment 15**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:01 GMT

In a4119a9/rtems-docs:

c-user: Split up partition manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

#### **Comment 16**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:03 GMT

In 082054b/rtems-docs:

c-user: Split up rate-monotonic manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

#### **Comment 17**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:05 GMT

In ae6b6fd/rtems-docs:

c-user: Split up region manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

#### **Comment 18**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:08 GMT

In e3523ed/rtems-docs:

c-user: Split up signal manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

#### **Comment 19**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:10 GMT

In ccb384b/rtems-docs:

c-user: Split up task manager

This makes it easier to automatically generate parts of the manager documentation in the future.  
Update #3993.

**Comment 20**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:12 GMT

In a99bbae/rtems-docs:

c-user: Split up timer manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

**Comment 21**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:14 GMT

In 80df4d6/rtems-docs:

c-user: Split up user extensions manager

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

**Comment 22**

1. **Sebastian Huber**, Thu, 03 Sep 2020 05:01:16 GMT

In ba9dfcf/rtems-docs:

c-user: Split up scheduling concepts

Introduce a background section.

This makes it easier to automatically generate parts of the scheduling concepts documentation in the future.

Update #3993.

**Comment 23**

1. **Sebastian Huber**, Fri, 18 Sep 2020 16:57:09 GMT

In 0b410b8a/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file history and documentation re-licensing agreement.

Update #3053. Update #3899. Update #3993.

**Comment 24**

1. **Sebastian Huber**, Thu, 08 Oct 2020 05:40:38 GMT

In f815d04/rtems:

rtems: Add "Generated from ..." comments

Improve file header comment.

Update #3993.

**Comment 25**

1. **Sebastian Huber**, Sun, 11 Oct 2020 13:27:04 GMT

In 4aae24d/rtems-docs:

c-user: Generate I/O Manager documentation

The manager documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. This header file was generated from the items by a script.

Update #3993.

**Comment 26**

**1. Sebastian Huber, Sun, 11 Oct 2020 14:07:39 GMT**

In 8111a6ba/rtems:

rtems: Generate

The manager documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. This header file was generated from the items by a script.

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 27****1. Sebastian Huber, Thu, 12 Nov 2020 06:47:02 GMT**

In ec4dcc0/rtems-docs:

c-user: Generate Event Manager documentation

The manager documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. This header file was generated from the items by a script.

Update #3993.

**Comment 28****1. Sebastian Huber, Thu, 12 Nov 2020 06:47:04 GMT**

In 530bc2b/rtems-docs:

c-user: Generate Partition Manager documentation

The manager documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. This header file was generated from the items by a script.

Update #3993.

**Comment 29****1. Sebastian Huber, Thu, 12 Nov 2020 07:55:26 GMT**

In 1af94608/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 30****1. Sebastian Huber, Thu, 12 Nov 2020 07:55:30 GMT**

In da44df3/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 31****1. Sebastian Huber, Thu, 12 Nov 2020 07:55:33 GMT**

In c0327d8/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 32****1. Sebastian Huber, Thu, 12 Nov 2020 07:55:37 GMT**

In e05b100/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 33**

1. **Sebastian Huber**, Thu, 12 Nov 2020 07:55:40 GMT

In 8de874b/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 34**

1. **Sebastian Huber**, Thu, 12 Nov 2020 07:55:44 GMT

In 9b4458e7/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 35**

1. **Sebastian Huber**, Thu, 12 Nov 2020 07:55:47 GMT

In f75e240/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 36**

1. **Sebastian Huber**, Thu, 12 Nov 2020 07:55:50 GMT

In 007ee13/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 37**

1. **Sebastian Huber**, Thu, 12 Nov 2020 07:55:54 GMT

In ecc6b2f/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 38**

1. **Sebastian Huber**, Thu, 12 Nov 2020 07:55:57 GMT

In 21af871/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

**Comment 39**

1. **Sebastian Huber**, Fri, 20 Nov 2020 13:27:03 GMT

In 05f06aa/rtems-docs:

c-user: Split up object services

This makes it easier to automatically generate parts of the module documentation in the future.

Update #3993.

**Comment 40**

1. **Sebastian Huber**, Tue, 01 Dec 2020 13:42:47 GMT

In 7995329/rtems:

rtems: Fix documentation in

Update #3993.

**Comment 41**

1. **Sebastian Huber**, Tue, 01 Dec 2020 13:46:11 GMT

In 284e8d0/rtems-docs:

c-user: Fix format in Partition Manager

Update #3993.

**Comment 42**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:20:08 GMT

In 29e6caa/rtems-docs:

c-user: Clarify rtems\_partition\_create()

The rtems\_partition\_create() returns an object identifier and not just a partition identifier.

Update #3993.

**Comment 43**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:20:10 GMT

In 346bbe6/rtems-docs:

c-user: Clarify rtems\_partition\_delete()

Move the PTCB sentence to the notes to be in line with rtems\_partition\_create().

Update #3993.

**Comment 44**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:20:44 GMT

In 8756d5c/rtems:

rtems: Clarify rtems\_partition\_create()

The rtems\_partition\_create() returns an object identifier and not just a partition identifier.

Update #3993.

**Comment 45**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:20:47 GMT

In 5a285e3/rtems:

rtems: Clarify rtems\_partition\_delete()  
Move the PTCB sentence to the notes to be in line with rtems\_partition\_create().  
Update #3993.

#### **Comment 46**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:31:31 GMT

In 66bcecf/rtems-docs:

c-user: Clarify invalid identifier descriptions  
Update #3993.

#### **Comment 47**

1. **Sebastian Huber**, Wed, 02 Dec 2020 07:34:30 GMT

In 1af4493/rtems:

rtems: Clarify invalid identifier descriptions  
Update #3993.

#### **Comment 48**

1. **Sebastian Huber**, Thu, 03 Dec 2020 06:25:06 GMT

In 65969c1/rtems:

rtems: Generate  
Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.  
Update #3899. Update #3993.

#### **Comment 49**

1. **Sebastian Huber**, Thu, 03 Dec 2020 06:25:18 GMT

In 768327d0/rtems:

rtems: Generate  
Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.  
Update #3899. Update #3993.

#### **Comment 50**

1. **Sebastian Huber**, Wed, 09 Dec 2020 08:20:55 GMT

In dad89ce/rtems-docs:

c-user: Generate Object Services documentation  
The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.  
Update #3993.

#### **Comment 51**

1. **Sebastian Huber**, Wed, 09 Dec 2020 08:20:57 GMT

In d716c79/rtems-docs:

c-user: Generate Timer Manager documentation  
The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.  
Update #3993.



**Comment 52**

1. **Sebastian Huber**, Wed, 27 Jan 2021 05:02:10 GMT

In b35ac99/rtems:

rtems: Add "Notes" paragraph header

Place the paragraphs in the same order as the directive documentation in the RTEMS Classic API Guide.

Update #3993.

**Comment 53**

1. **Sebastian Huber**, Wed, 03 Feb 2021 05:17:38 GMT

In 8a95e6f8/rtems:

rtems: Rework object services API

Add a "Constraints" paragraph to the documentation.

Provide prototypes for programming language bindings. Use the macro implementation to implement the corresponding functions.

Update #3993.

**Comment 54**

1. **Sebastian Huber**, Wed, 03 Feb 2021 05:17:47 GMT

In aa0060f4/rtems:

rtems: Clarify partition manager documentation

Unify the wording across similar directives of other managers. Add "Constraints" paragraph.

Update #3993.

**Comment 55**

1. **Sebastian Huber**, Wed, 03 Feb 2021 05:20:14 GMT

In 95e2f93/rtems-docs:

c-user: Clarify object services

Add a "Constraints" paragraph to the documentation. Use function prototypes for the directives.

Update #3993.

**Comment 56**

1. **Sebastian Huber**, Wed, 03 Feb 2021 05:20:16 GMT

In 66c9808/rtems-docs:

c-user: Clarify partition manager documentation

Unify the wording across similar directives of other managers. Add "CONSTRAINTS" section.

Update #3993.

**Comment 57**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:39 GMT

In 4d9b0b4/rtems-docs:

c-user: Clarify timer manager documentation

Unify the wording across similar directives of other managers. Add "CONSTRAINTS" section.

Update #3993.

**Comment 58**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:42 GMT

In 775380c/rtems-docs:

c-user: Clarify event manager documentation

Unify the wording across similar directives of other managers. Add "CONSTRAINTS" section.

Update #3993.

#### **Comment 59**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:46 GMT

In e357ccf/rtems-docs:

c-user: Clarify IO manager documentation

Unify the wording across similar directives of other managers.

Update #3993.

#### **Comment 60**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:48 GMT

In 261491f/rtems-docs:

c-user: Clarify object services documentation

Unify the wording across similar directives of other managers.

Update #3993.

#### **Comment 61**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:50 GMT

In 4e09c09/rtems-docs:

c-user: Add labels to the manager chapters

Update #3993.

#### **Comment 62**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:52 GMT

In a1c5d68/rtems-docs:

c-user: Add control block acronyms

Update #3993.

#### **Comment 63**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:55 GMT

In 6985800/rtems-docs:

c-user: Move deprecated/removed directives

This makes it easier to automatically generate parts of the manager documentation in the future.

Update #3993.

#### **Comment 64**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:57 GMT

In fd56f7e/rtems-docs:

c-user: Generate semaphore manager documentation

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 65**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:46:59 GMT

In 62718ad/rtems-docs:

```
c-user: Generate barrier manager documentation
```

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 66**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:47:02 GMT

In 4aead84/rtems-docs:

```
c-user: Generate user extensions manager docs
```

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 67**

1. **Sebastian Huber**, Wed, 17 Feb 2021 17:47:04 GMT

In a60c5b4/rtems-docs:

```
c-user: Generate clock manager documentation
```

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 68**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:26:45 GMT

In 2730599c/rtems:

```
rtems: Clarify event manager documentation
```

Unify the wording across similar directives of other managers. Add "CONSTRAINTS" section.

Update #3993.

**Comment 69**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:26:49 GMT

In f9dc44a/rtems:

```
rtems: Clarify timer manager documentation
```

Unify the wording across similar directives of other managers. Add "CONSTRAINTS" section.

Update #3993.

**Comment 70**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:26:52 GMT

In bf3b9f45/rtems:

```
rtems: Clarify partition manager documentation
```

Unify the wording across similar directives of other managers.

Update #3993.

**Comment 71**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:26:55 GMT

In 7a1828ac/rtems:

```
rtems: Clarify IO manager documentation
Unify the wording across similar directives of other managers.
Update #3993.
```

#### **Comment 72**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:26:59 GMT

In 97825da/rtems:

```
rtems: Clarify object services documentation
Unify the wording across similar directives of other managers.
Update #3993.
```

#### **Comment 73**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:27:02 GMT

In 0c4c035/rtems:

```
rtems: Generate
Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.
Update #3899. Update #3993.
```

#### **Comment 74**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:27:06 GMT

In 2768280/rtems:

```
rtems: Generate
Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.
Update #3899. Update #3993.
```

#### **Comment 75**

1. **Sebastian Huber**, Wed, 17 Feb 2021 19:27:10 GMT

In 407e351/rtems:

```
rtems: Generate
Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.
Update #3899. Update #3993.
```

#### **Comment 76**

1. **Sebastian Huber**, Fri, 19 Feb 2021 06:06:15 GMT

In c87d8c2/rtems-docs:

```
c-user: Generate signal manager documentation
The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The
documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.
Update #3993.
```

#### **Comment 77**

1. **Sebastian Huber**, Fri, 19 Feb 2021 06:09:24 GMT

In 8b1b9872/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 78**

1. **Sebastian Huber**, Mon, 19 Apr 2021 05:18:08 GMT

In 9bf0184/rtems-docs:

c-user: Document rtems\_semaphore\_obtain() errors

Update #3993.

### **Comment 79**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:44 GMT

In f3262d4/rtems-docs:

c-user: Split up initialization manager

This makes it easier to automatically generate parts of the module documentation in the future.

Update #3993.

### **Comment 80**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:46 GMT

In 62ca9c1/rtems-docs:

c-user: Split up fatal error manager

This makes it easier to automatically generate parts of the module documentation in the future.

Update #3993.

### **Comment 81**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:48 GMT

In 86b48fb/rtems-docs:

c-user: Split up multiprocessing manager

This makes it easier to automatically generate parts of the module documentation in the future.

Update #3993.

### **Comment 82**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:52 GMT

In 5a3cb76/rtems-docs:

c-user: Generate initialization manager docs

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

### **Comment 83**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:54 GMT

In d946f30/rtems-docs:

c-user: Generate fatal error manager docs

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 84**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:57 GMT

In a995620/rtems-docs:

```
c-user: Generate multiprocessing manager docs
```

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 85**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:13:59 GMT

In 03fc1d6/rtems-docs:

```
c-user: Generate dual-ported memory manager docs
```

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

**Comment 86**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:14:39 GMT

In 97ba94b/rtems:

```
rtems: Generate
```

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 87**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:14:43 GMT

In 71a2e7e/rtems:

```
rtems: Generate
```

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 88**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:14:47 GMT

In 0be4b882/rtems:

```
rtems: Generate
```

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 89**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:14:50 GMT

In e8be0047/rtems:

```
rtems: Generate
```

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

**Comment 90**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:14:54 GMT

In b229b4c/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

#### **Comment 91**

1. **Sebastian Huber**, Fri, 23 Apr 2021 06:32:43 GMT

In 61cbbd2/rtems-docs:

c-user: Generate rate-monotonic manager docs

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

#### **Comment 92**

1. **Sebastian Huber**, Fri, 23 Apr 2021 06:32:45 GMT

In 63a9e0c/rtems-docs:

c-user: Generate message manager documentation

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

#### **Comment 93**

1. **Sebastian Huber**, Fri, 23 Apr 2021 06:44:36 GMT

In 73a0175/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

#### **Comment 94**

1. **Sebastian Huber**, Fri, 23 Apr 2021 06:44:40 GMT

In de6e515/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

#### **Comment 95**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:02:58 GMT

In 0b9e307/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

#### **Comment 96**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:03:03 GMT

In b3d3186d/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 97**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:03:07 GMT

In a1679af3/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3899. Update #3993.

### **Comment 98**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:04:10 GMT

In f6b4337/rtems-docs:

c-user: Generate interrupt manager documentation

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

### **Comment 99**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:04:13 GMT

In 4a3259f/rtems-docs:

c-user: Generate scheduling concepts documentation

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

### **Comment 100**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:04:19 GMT

In 2ae3364/rtems-docs:

c-user: Generate task manager documentation

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

### **Comment 101**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:04:21 GMT

In 35cbb42/rtems-docs:

c-user: Generate region manager documentation

The documentation is a consolidation of the comments in Doxygen markup and the documentation sources in Sphinx markup. The documentation was transferred to interface specification items. The documentation source files were generated from the items by a script.

Update #3993.

### **Comment 102**

1. **Sebastian Huber**, Tue, 15 Jun 2021 05:47:59 GMT

In c70715b/rtems-docs:

c-user: Use a common phrase for pointer parameters

Mention the type of the pointer in the parameter description. Use the more general term "object" instead of "variable".

Update #3993.



**Comment 103**

1. **Sebastian Huber**, Tue, 15 Jun 2021 08:40:28 GMT

In 6abdd89/rtems:

Use a common phrase for pointer parameters

Mention the type of the pointer in the parameter description. Use the more general term "object" instead of "variable".

Update #3993.

**Comment 104**

1. **Sebastian Huber**, Tue, 27 Jul 2021 05:43:11 GMT

In c4eafae2/rtems:

rtems: Generate

Use which just provides the data types and avoid a dependency on which contains the full chain implementation.

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Update #3269. Update #3899. Update #3993.

**Comment 105**

1. **Sebastian Huber**, Mon, 02 Aug 2021 05:15:51 GMT

In d999f865/rtems:

rtems: Generate

Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.

Place the group into the I/O Manager group. Add all source files to the group.

Update #3899. Update #3993. Update #4482.

**Comment 106**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:27:56 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

Work is done.

**Comment 107**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:28:19 GMT
2. **keywords**: **qualification** added

**Comment 108**

1. **Sebastian Huber**, Tue, 04 Oct 2022 08:39:36 GMT

In cc43dc3e/rtems:

rtems: Clarify application config info API

Update #3993.

---

**3994 - Generate Doxygen markup for the application configuration options**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3994">https://devel.rtems.org/ticket/3994</a> ( <a href="https://devel.rtems.org/ticket/3994">https://devel.rtems.org/ticket/3994</a> )
<b>Id</b>	3994
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	1 June 2020 11:26:30
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The application configuration options are now available as specification items. From these items, the documentation in the RTEMS Classic API Guide is generated. The same approach can be used to generate Doxygen markup.

### Comment 1

1. **Sebastian Huber**, Fri, 07 Aug 2020 05:15:35 GMT

In db22500/rtems-docs:

```
c-user: Improve refs and formatting in appl config
The formatting is generated through references within the specification.
Update #3994.
```

### Comment 2

1. **Sebastian Huber**, Fri, 07 Aug 2020 05:15:37 GMT

In 63764a6/rtems-docs:

```
c-user: Add automatically generated warning
Update #3994.
```

### Comment 3

1. **Sebastian Huber**, Fri, 07 Aug 2020 05:24:30 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In e812f81/rtems:

```
Document application configuration options
Add a new directory for Doxygen-specific documentation content. Add a Doxygen only header file containing documentation of the application configuration options. The header file is generated from specification items.
Close #3994.
```

### Comment 4

1. **Sebastian Huber**, Thu, 08 Oct 2020 05:40:41 GMT

In e697baf/rtems:

```
doxygen: Add "Generated from ..." comments
Improve file header comment.
Update #3994.
```

### Comment 5

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

### **3996 - fenv support is missing on powerpc**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3996">https://devel.rtems.org/ticket/3996</a> ( <a href="https://devel.rtems.org/ticket/3996">https://devel.rtems.org/ticket/3996</a> )
<b>Id</b>	3996
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 June 2020 04:18:59
<b>Modified</b>	29 November 2022 22:10:19
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/powerpc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

The test program psxfenv01 fails on powerpc.

#### **Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:10:19 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Fixed in newlib in 2020.

---

### **3997 - fenv support is missing on sparc**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3997">https://devel.rtems.org/ticket/3997</a> ( <a href="https://devel.rtems.org/ticket/3997">https://devel.rtems.org/ticket/3997</a> )
<b>Id</b>	3997
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 June 2020 04:20:16
<b>Modified</b>	29 November 2022 22:10:47
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

The test program psxfenv01 fails on sparc.

#### **Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:10:47 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Fixed in newlib in 2020.

---

### **3998 - fenv support is missing on arm**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/3998">https://devel.rtems.org/ticket/3998</a> ( <a href="https://devel.rtems.org/ticket/3998">https://devel.rtems.org/ticket/3998</a> )
<b>Id</b>	3998
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 June 2020 04:20:45
<b>Modified</b>	29 November 2022 22:11:08
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The test program psxfenv01 fails on arm.

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:11:08 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Fixed in newlib in 2020.

---

**4007 - Add rtems\_message\_queue\_construct()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4007">https://devel.rtems.org/ticket/4007</a> ( <a href="https://devel.rtems.org/ticket/4007">https://devel.rtems.org/ticket/4007</a> )
<b>Id</b>	4007
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	17 June 2020 08:08:44
<b>Modified</b>	2 September 2021 06:00:40
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In RTEMS 5 a lot of development was done to allow a static allocation of resources provided by RTEMS and avoid the use of a heap. Similar to #3959 a new directive to build Classic API message queues without using the workspace is proposed:

```

/**
 * @brief The message queue configuration to construct a message queue.
 */
typedef struct {
/**
 * @brief The name of the message queue.
 */
 rtems_name name;
/**
 * @brief The count of the provided buffers.
 * This value defines the maximum number of pending messages.
 */
 size_t buffer_count;
/**
 * @brief The size of the provided buffers in bytes.
 */
 size_t buffer_size;
/**
 * @brief The array of count message buffers.
 * Each buffer shall have the size of the buffer_size member. The maximum
 * message size is buffer_size minus sizeof( rtems_message_queue_buffer ).
 */
 rtems_message_queue_buffer *buffers;
/**
 * @brief The attribute set of the message queue.
 */
 rtems_attribute attributes;
} rtems_message_queue_config;
/**
 * @brief Constructs a message queue according to the specified configuration.
 *
 * @param config The message queue configuration.
 * @param[out] id The message queue identifier of the new message queue.
 *
 * @retval RTEMS_SUCCESSFUL Successful operation.
 * @retval RTEMS_INVALID_ADDRESS The id parameter is @c NULL.
 * @retval RTEMS_INVALID_NAME The message queue name is invalid.
 * @retval RTEMS_TOO_MANY No message queue is available.
 */
 rtems_status_code rtems_message_queue_construct(
  const rtems_message_queue_config *config,
  rtems_id id
);

```

**Comment 1**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:18:59 GMT
2. **status:** changed from **assigned** to **accepted**
3. **description:** modified (diff)
4. **summary:** changed from **Add rtems\_message\_queue\_build()** to **Add rtems\_message\_queue\_construct()**

**Comment 2**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:19:28 GMT
2. **description:** modified (diff)

**Comment 3**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:17:56 GMT

In 3c025576/rtems:

```

score: Use RTEMS_ALIGN_UP()
Update #4007.

```

**Comment 4**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:17:59 GMT

In fe2cb7c4/rtems:

```

score: Fix allocation size calculation

The previous multiplication error check is broken on 64-bit machines. Use the recommended check from SEI CERT C Coding Standard,
"INT30-C. Ensure that unsigned integer operations do not wrap".

Make sure the message size computation does not overflow.

Update #4007.

```

**Comment 5**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:03 GMT

In 34dd90a5/rtems:

```

score: Gather message queue control initialization

```

Initialize the structure in a single code block after the error checks and calculations.  
Update #4007.

### **Comment 6**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:06 GMT

In 5bc7c37/rtems:

score: Improve `_CORE_message_queue_initialize()`  
Return a status code and differentiate between error conditions.  
Update #4007.

### **Comment 7**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:09 GMT

In 69b4fe59/rtems:

score: Simplify `CORE_message_queue_Buffer`  
Merge `CORE_message_queue_Buffer` structure into `CORE_message_queue_Buffer_control`.  
Use a zero-length array for the actual message buffer. This reduces the structure size on all targets.  
Update #4007.

### **Comment 8**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:13 GMT

In 2c09f54f/rtems:

score: Add  
Move the `CORE_message_queue_Buffer` definition to a separate header file to be able to use it independent of the remaining Message Queue Handler API.  
Change license to BSD-2-Clause according to file history.  
Update #3053. Update #4007.

### **Comment 9**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:16 GMT

In 24ea1ce/rtems:

rtems: Remove `Message_queue_Control::attribute_set`  
Add `Message_queue_Control::is_global` if `RTEMS_MULTIPROCESSING` is defined. This reduces the `Message_queue_Control` size in standard RTEMS configurations.  
Update #4007.

### **Comment 10**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:20 GMT

In 4a4f41e/rtems:

rtems: Add `rtems_message_queue_construct()`  
In contrast to message queues created by `rtems_message_queue_create()`, the message queues constructed by this directive use a user-provided message buffer storage area.  
Add `RTEMS_MESSAGE_QUEUE_BUFFER()` to define a message buffer type for message buffer storage areas.  
Update #4007.

### **Comment 11**

1. **Sebastian Huber**, Mon, 28 Sep 2020 05:18:23 GMT

In febc6604/rtems:

validation: Test rtems\_message\_queue\_construct()

Update #4007.

### **Comment 12**

1. **Sebastian Huber**, Fri, 23 Apr 2021 06:25:29 GMT

In 03747b50/rtems:

rtems: Check for NULL config in msgq construct

Since there are already excessive NULL pointer checks in the Classic API, do this also in rtems\_message\_queue\_construct().

Update #4007.

### **Comment 13**

1. **Sebastian Huber**, Tue, 11 May 2021 05:49:48 GMT

In ab5aeb1/rtems:

score: Rename \_Stack\_Free\_nothing()

Rename \_Stack\_Free\_nothing() in \_Objects\_Free\_nothing() to make it reusable for the message queue buffers.

Update #4007.

### **Comment 14**

1. **Sebastian Huber**, Tue, 11 May 2021 05:49:51 GMT

In c268766/rtems:

rtems: Use \_Objects\_Free\_nothing() for msg queues

Use \_Objects\_Free\_nothing() for rtems\_message\_queue\_construct() to avoid unreachable code in \_CORE\_message\_queue\_Close() in case only user-provided message buffers are used.

Update #4007.

### **Comment 15**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** **qualification** added

### **Comment 16**

1. **Sebastian Huber**, Thu, 02 Sep 2021 06:00:40 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

The new directive was documented, implemented, and tested:

<https://docs.rtems.org/branches/master/c-user/message/directives.html#rtems-message-queue-construct>

## **4018 - libcpusupport: Architecture defines are present outside CPU port**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4018">https://devel.rtems.org/ticket/4018</a> ( <a href="https://devel.rtems.org/ticket/4018">https://devel.rtems.org/ticket/4018</a> )
<b>Id</b>	4018
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	29 June 2020 15:29:40
<b>Modified</b>	30 June 2020 15:39:32
<b>Owner</b>	Kinsey Moore <kinsey.moore@...>
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The handler code for global constructors (threadhandler.c) and destructors (newlibc\_exit.c) uses compiler-provided architecture defines which should be limited to the CPU port as they are in other locations.

**Comment 1**

1. **Kinsey Moore**, Tue, 30 Jun 2020 07:46:41 GMT
2. **owner:** set to **Kinsey Moore** <kinsey.moore@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 48dd7b8c/rtems:

```
score: Add CPU_USE_LIBC_INIT_FINI_ARRAY
```

This introduces the CPU\_USE\_LIBC\_INIT\_FINI\_ARRAY define for use by CPU ports to determine which global constructor and destructor methods are used instead of placing architecture defines where they shouldn't be.

```
Close #4018
```

**Comment 2**

1. **Joel Sherrill**, Tue, 30 Jun 2020 13:43:29 GMT

Should this go on 5.x as well as 6?

**Comment 3**

1. **Kinsey Moore**, Tue, 30 Jun 2020 14:32:47 GMT

It could, but it doesn't actually cause a bug. It's just a style deficiency making new ports harder.

**Comment 4**

1. **Sebastian Huber**, Tue, 30 Jun 2020 15:39:32 GMT

In 3c78e93/rtems:

```
score: Clarify CPU_USE_LIBC_INIT_FINI_ARRAY option
```

```
Update #4018.
```

**4020 - Change all version numbers to RTEMS 6 on the master branches**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4020">https://devel.rtems.org/ticket/4020</a> ( <a href="https://devel.rtems.org/ticket/4020">https://devel.rtems.org/ticket/4020</a> )
<b>Id</b>	4020
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	30 June 2020 07:12:02
<b>Modified</b>	26 January 2022 13:42:45
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description****Comment 1**

1. **Sebastian Huber**, Tue, 30 Jun 2020 07:14:55 GMT

In b89e62f/rtems-source-builder:

```
Change version to RTEMS 6
```

```
Update #4020.
```



**Comment 2**

1. **Sebastian Huber**, Tue, 30 Jun 2020 07:20:48 GMT

In 37c36de/rtems:

```
Change version to RTEMS 6
Update #4020.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 30 Jun 2020 07:32:05 GMT

In 351bb7e/rtems-tools:

```
Change version to RTEMS 6
Update #4020.
```

**Comment 4**

1. **Sebastian Huber**, Tue, 30 Jun 2020 07:40:30 GMT

In 16f8cc4/rtems-docs:

```
Change version to RTEMS 6
Update #4020.
```

**Comment 5**

1. **Sebastian Huber**, Mon, 10 Aug 2020 09:49:47 GMT

In 6626ed50/rtems:

```
Doxyfile: Change version to 6.0.0
Update #4020.
```

**Comment 6**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:42:45 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

This is probably done.

**4025 - NFS Client is broken on 64-bit targets**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4025">https://devel.rtems.org/ticket/4025</a> ( <a href="https://devel.rtems.org/ticket/4025">https://devel.rtems.org/ticket/4025</a> )
<b>Id</b>	4025
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 July 2020 11:35:07
<b>Modified</b>	26 January 2022 13:44:40
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4024.

Comment 1

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:44:40 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

This was fixed by [03d7f76a810fe13c750afc3324f615b25fa7006b/rtems-libbsd].

---

**4029 - i386: SMP-System hangs with non-consecutive APIC IDs**

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4029">https://devel.rtems.org/ticket/4029</a> ( <a href="https://devel.rtems.org/ticket/4029">https://devel.rtems.org/ticket/4029</a> )
<b>Reporter</b>	Jan Sommer
<b>Created</b>	15 July 2020 15:48:17
<b>Modified</b>	16 July 2020 13:01:33
<b>Owner</b>	Jan Sommer <jan.sommer@...>
<b>Type</b>	defect
<b>Component</b>	arch/i386
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

If a processor enumerates its cores non-consecutively (e.g. 0,2,4,8 for a tested Intel Atom) the target cpu for IPIs is mapped wrongly.

Comment 1

1. **Jan Sommer**, Wed, 15 Jul 2020 15:48:35 GMT
2. **component**: changed from **admin** to **arch/i386**

Comment 2

1. **Jan Sommer**, Thu, 16 Jul 2020 13:01:33 GMT
2. **owner**: set to **Jan Sommer** <jan.sommer@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 9cb107c9/rtems:

```
bsps/pc386: Fix IPI for non-consecutive APICIDs
properly use the cpu <-> apic maps for IPIs
Closes #4029.
```

---

**4031 - i386: ISR can overwrite its own stack during system initialization (cloned)**

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4031">https://devel.rtems.org/ticket/4031</a> ( <a href="https://devel.rtems.org/ticket/4031">https://devel.rtems.org/ticket/4031</a> )
<b>Reporter</b>	Jan Sommer
<b>Created</b>	22 July 2020 12:38:21
<b>Modified</b>	29 July 2020 09:39:17
<b>Owner</b>	Jan Sommer <jan.sommer@...>
<b>Type</b>	defect
<b>Component</b>	arch/i386
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	major
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4030:

During testing the rtems-libbsd examples, we experienced GP exceptions from within the ISR from time to time during initialization.

When the init task is restored for the first time and the a pending interrupt is available, an ISR could overwrite its own return address if it is spawned between restoring the eflags register and restoring the esp register.

### Comment 1

1. **Jan Sommer**, Wed, 29 Jul 2020 09:39:17 GMT
2. **owner:** set to **Jan Sommer** <jan.sommer@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 21c7e3a/rtems:

```
i386: Fix possible race condition on first context restore
Make sure that the esp is restored before the eflags register.

When the init task is initially restored, system interrupts are activated when the eflags register is loaded. If the esp register still points to an address in the interrupt stack area (from early system initialization) the ISR might overwrite its own stack.

Closes #4031
```

## 4032 - Make deferred free in malloc() support optional

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4032">https://devel.rtems.org/ticket/4032</a> ( <a href="https://devel.rtems.org/ticket/4032">https://devel.rtems.org/ticket/4032</a> )
<b>Id</b>	4032
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	23 July 2020 11:54:48
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The free() implementation in RTEMS supports that allocated memory is freed in interrupt context. Since the heap is protected by a mutex, the frees issued in interrupt context cannot immediately be freed to the heap, instead they are placed on a deferred free list. This list is emptied by the core allocation function rtems\_heap\_allocate\_aligned\_with\_boundary(). This adds a dependency to free() in rtems\_heap\_allocate\_aligned\_with\_boundary(). In order to better support applications which only allocate memory and never free it, this dependency should be avoided. This can be done with a weak default implementation of \_Malloc\_Process\_deferred\_frees(). In the free() module a strong implementation can be provided.

### Comment 1

1. **Sebastian Huber**, Fri, 24 Jul 2020 05:14:22 GMT

In 6f94a83/rtems:

```
score: Add RTEMS_WEAK
Update #4032.
```

### Comment 2

1. **Sebastian Huber**, Fri, 24 Jul 2020 05:14:26 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 7746b0de/rtems:

```
malloc: Make deferred free support optional

Only include the deferred free support if free() is actually used by the application.

The free() implementation in RTEMS supports that allocated memory is freed in interrupt context. Since the heap is protected by a mutex, the frees issued in interrupt context cannot immediately be freed to the heap, instead they are placed on a deferred free list. This list is emptied by the core allocation function rtems_heap_allocate_aligned_with_boundary(). This adds a dependency to free() in rtems_heap_allocate_aligned_with_boundary(). In order to better support applications which only allocate memory and never free it, this dependency should be avoided. Provide a weak default implementation of _Malloc_Process_deferred_frees() for
```

```
rtems_heap_allocate_aligned_with_boundary(). In the free() module provide the strong implementation.
```

```
Close #4032.
```

### Comment 3

1. **Sebastian Huber**, Fri, 24 Jul 2020 05:32:01 GMT

In 4444094d/rtems:

```
spmisc01: Include missing header file
```

```
Update #4032.
```

### Comment 4

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords: qualification added**

## 4034 - Add rtems\_interrupt\_server\_create() and rtems\_interrupt\_server\_destroy() (cloned)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4034">https://devel.rtems.org/ticket/4034</a> ( <a href="https://devel.rtems.org/ticket/4034">https://devel.rtems.org/ticket/4034</a> )
<b>Id</b>	4034
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	31 July 2020 06:54:01
<b>Modified</b>	14 September 2020 07:00:08
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Cloned from #4033. In addition to the implementation add also unit tests.

### Comment 1

1. **Sebastian Huber**, Sat, 01 Aug 2020 09:56:10 GMT
2. **summary: changed from Add rtems\_interrupt\_server\_build() and rtems\_interrupt\_server\_destroy() (cloned) to Add rtems\_interrupt\_server\_create() and rtems\_interrupt\_server\_destroy() (cloned)**

### Comment 2

1. **Sebastian Huber**, Mon, 03 Aug 2020 06:52:57 GMT
2. **status: changed from assigned to closed**
3. **resolution: set to fixed**

In c60942ea/rtems:

```
rtms: Add rtems_interrupt_server_create()
```

```
Add rtems_interrupt_server_destroy().
```

Before this patch, the only way to create interrupt servers was rtems\_interrupt\_server\_initialize(). This function creates the default interrupt server and in SMP configurations additional interrupt servers for the additional processors. The interrupt server is heavily used by libbsd. This includes the epoch based reclamation which performs time consuming resource and memory deallocation work. This does not work well with time critical services, for example an UART over SPI or I2C. One approach to address this problem is to allow the application to create custom interrupt servers with the right priority and task properties. The interrupt server API accounted for this, however, it was not implemented before this patch.

```
Close #4034.
```

### Comment 3

1. **Sebastian Huber**, Mon, 03 Aug 2020 06:55:28 GMT
2. **status: changed from closed to reopened**

3. **resolution:** fixed deleted

Tests are pending.

#### Comment 4

1. **Sebastian Huber**, Mon, 14 Sep 2020 07:00:08 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 46477898/rtems:

irqs01/smpirqs01: New tests

Close #4034.

## 4036 - Track dependency command for the RSB

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4036">https://devel.rtems.org/ticket/4036</a> ( <a href="https://devel.rtems.org/ticket/4036">https://devel.rtems.org/ticket/4036</a> )
<b>Id</b>	4036
<b>Reporter</b>	Chris Johns
<b>Created</b>	1 August 2020 00:01:59
<b>Modified</b>	12 August 2020 01:11:35
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

Add a command to track dependencies in the RSB. Scan all the bset files and see what they include. Build a list of dependencies and also a list of those configs that are not referenced. The configs not references can be removed.

Errors in build sets can result in an invalid list so the scan needs to be clean. This is difficult when some build sets like rtems-defaults.bset are designed to be included and not used from the command line. As a result it generates an error. A list of these could be maintained or a tag added to the bset file to indicate it is not a top level build set file.

Removal of unreferenced configs can occur in the RBS because we use a branch model for releases.

#### Comment 1

1. **Joel Sherrill**, Sat, 01 Aug 2020 00:19:53 GMT

Is this going to result in a report that shows bsets and which source/patches they need?

Is it going to be something like this?

bset another bset source package diff1

Or is the goal to look at a set of bsets and see what isn't needed?

#### Comment 2

1. **Chris Johns**, Sat, 01 Aug 2020 02:51:05 GMT

It could and yes the goal was to remove the config files not referenced. Up to now I was only looking at the list but the tree could be captured. This is nice addition.

A bset that is top level is difficult to remove because we do not know if it is being used.

#### Comment 3

1. **Chris Johns**, Thu, 06 Aug 2020 02:51:46 GMT
2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **assigned**

Joel, is this what you wanted?

```

Include Tree(s) :
rtems/config/5/rtems-arm.bset
rtems/config/5/rtems-default.bset
bare/config/devel/expat-2.1.0-1.cfg
source-builder/config/base.cfg
source-builder/config/expat-2-1.cfg
rtems/config/5/rtems-autotools.bset
rtems/config/5/rtems-autotools-base.bset
rtems/config/rtems-base.bset
rtems/config/rtems-urls.bset
rtems/config/rtems-version.bset
rtems/config/tools/rtems-autoconf-2.69-1.cfg
bare/config/devel/autoconf-2.69-1.cfg
source-builder/config/autoconf-2-1.cfg
source-builder/config/base.cfg
source-builder/config/base.cfg
source-builder/config/checks.cfg
source-builder/config/versions.cfg
rtems/config/tools/rtems-automake-1.12.6-1.cfg
bare/config/devel/automake-1.12.6-1.cfg
source-builder/config/automake-1-1.cfg
source-builder/config/base.cfg
source-builder/config/base.cfg
source-builder/config/checks.cfg
source-builder/config/versions.cfg
rtems/config/5/rtems-autotools-internal.bset
rtems/config/5/rtems-autotools-base.bset
rtems/config/rtems-base.bset
rtems/config/rtems-urls.bset
rtems/config/rtems-version.bset
rtems/config/tools/rtems-autoconf-2.69-1.cfg
bare/config/devel/autoconf-2.69-1.cfg
source-builder/config/autoconf-2-1.cfg
source-builder/config/base.cfg
source-builder/config/base.cfg
source-builder/config/checks.cfg
source-builder/config/versions.cfg
rtems/config/tools/rtems-automake-1.12.6-1.cfg
bare/config/devel/automake-1.12.6-1.cfg
source-builder/config/automake-1-1.cfg
source-builder/config/base.cfg
source-builder/config/base.cfg
source-builder/config/checks.cfg
source-builder/config/versions.cfg
rtems/config/rtems-base.bset
rtems/config/rtems-urls.bset
rtems/config/rtems-version.bset
rtems/config/tools/rtems-binutils-2.34.cfg
source-builder/config/base.cfg
source-builder/config/binutils-2-1.cfg
source-builder/config/checks.cfg
source-builder/config/checks.cfg
rtems/config/tools/rtems-gcc-7.5.0-newlib-7947581.cfg
source-builder/config/base.cfg
source-builder/config/checks.cfg
source-builder/config/gcc-7.2-1.cfg
source-builder/config/gcc-common-1.cfg
source-builder/config/checks.cfg
rtems/config/tools/rtems-gdb-9.1-1.cfg
source-builder/config/base.cfg
source-builder/config/checks.cfg
source-builder/config/gdb-common-1.cfg
source-builder/config/checks.cfg
rtems/config/tools/rtems-tools-5-1.cfg
rtems/config/tools/rtems-tools-common-1.cfg

```

**Comment 4**

1. **Chris Johns**, Mon, 10 Aug 2020 23:03:11 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 1241819/rtems-source-builder:

```

sb/track: Add a command to track build sets.
Process a build set for a range of hosts and output a dependency
tree, the used build set and configuration files. Output the configuration files that are no referenced
Closes #4036

```

**Comment 5**

1. **Chris Johns**, Wed, 12 Aug 2020 01:11:35 GMT

In 967999b/rtems-docs:

```

user: Add the RSB sb-track command
Updates #4036

```

**4037 - Python script distribution standardisation**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4037">https://devel.rtems.org/ticket/4037</a> ( <a href="https://devel.rtems.org/ticket/4037">https://devel.rtems.org/ticket/4037</a> )
<b>Id</b>	4037
<b>Reporter</b>	Chris Johns
<b>Created</b>	1 August 2020 00:16:32
<b>Modified</b>	29 November 2022 23:00:51
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The RSB and Tools wrap python scripts in a shell script based wrapper that detects the installed version and uses it. Other python scripts in RTEMS do not. I would like to have a consistent model for all scripts.

PEP0394 discusses the issues and says a distro can decide not to provide a python command by default. It also says a virtualenv can be used to provide a consistent default environment.

Do we assume `#!/usr/bin/env python` will always work in our script and we make sure we are python2 and python3 clean for user installed commands?

If a user does not have a python command installed by default do we document how to install one or do we document using a virtualenv?

A simple shebang is cleaner for us to maintain however it added an extra dependency we need to document.

Note, development script and tools should follow the same model we decide on however they only need to support python3.

### Comment 1

1. **Chris Johns**, Sat, 01 Aug 2020 00:17:16 GMT

2. **summary:** changed from **Python script distrubution standardisation** to **Python script distribution standardisation**

### Comment 2

1. **Christian Mauderer**, Sun, 02 Aug 2020 09:00:11 GMT

2. **One important point:** : We start to use waf everywhere. waf starts with a `#!/usr/bin/env python`. So it assumes that python exists. That means as soon as a user wants to build something with waf he needs a python. I don't think that we want to provide a wrapper for waf?

I'm currently a bit undecided. Both methods have advantages and disadvantages.

Points that could be a reason `_not_` to use a wrapper:

Although you did a great job making it as simple as possible: A wrapper adds complexity. How many edge cases are missed in the wrappers? For example: If you try to call one of the source builder commands using a soft link in another directory, the `$(dirname $0)` of the wrapper will fail. Every supported system has to provide a `/bin/sh` and a `dirname` command. Can we be sure that's the case? What about Windows? If we enforce the wrapper we will always need a `mingw` or `msys` for Windows. If we remove it it might be possible to build RTEMS with only a python installation somewhen in the future (although you still need a cross-compiled `gcc` or `llvm`). Do we really want to support multiple python versions on the long term? It might start to get really complicated to test all relevant configurations. By the way: Does buildbot use python2, python3 or both?

Points that could be a good reason for using a wrapper:

Do all our scripts work with python3 already? The wrapper of the source builder currently defaults to python2. So most likely it is nearly untested with python3. I think I had trouble building `rtems-docs` with python3 in the past (and I always have been too lazy to fix them - sorry). That means that currently `_not_` everything is ready to work with all python versions. A wrapper could select the best one. But that also means we basically depend on `python2` and `python3` to be installed. We will have a really simple possibility to switch to python4 when it comes out. On systems without a python it will definitively make it simpler.

Background questions:

Do we know of distributions that don't provide a python (without version number) command?

### Comment 3

1. **Sebastian Huber**, Mon, 03 Aug 2020 07:16:27 GMT

openSUSE 15.2 installs Python 3 by default and Python 2 is `_not_` available by default. There is no "python" command by default, only "python3".

I think we should ask the waf community how they want to deal with this.

About a year ago I started a discussion about "Which Python version for new tool code?". It seems RHEL 7 was the only relevant distribution not providing a Python 3, but this changed during the discussion:

<https://lists.rtems.org/pipermail/devel/2019-August/055010.html>

CentOS 7.7 ships it also. Is there anything left which doesn't ship Python 3? If not, then why don't we change the shebang to `#!/usr/bin/env python3`?

### Comment 4

1. **Chris Johns**, Tue, 04 Aug 2020 07:37:25 GMT

We need to support long life versions of host systems and I have understood this to mean python2. As a result we need to make sure our user facing tools run on Python 2 and 3 for a while yet. This ticket is about how we handle this and not that choice.

The python command may not install by default but is there a package that does provide it?

The waf point is a valid one. We need a python command while it requires it. If that changes then we can consider what happens then. If you wish to ask please do so.

#### **Comment 5**

1. **Christian Mauderer**, Tue, 04 Aug 2020 09:11:31 GMT

Seems that I misinterpreted the intention of the ticket. You asked:

Do we assume `#!/usr/bin/env python` will always work in our script and we make sure we are python2 and python3 clean for user installed commands?

If a user does not have a python command installed by default do we document how to install one or do we document using a virtualenv?

A simple shebang is cleaner for us to maintain however it added an extra dependency we need to document.

From my point of view: As long as waf needs python, we can assume it for our scripts too. So we have to document that anyway as soon as we switch to waf for all core repos.

From what you wrote we have to make sure that our scripts work with python2 and python3 anyway. I would reject a python2 only version with it being no maintained anymore and slowly removed from distributions and you don't like a python3 only version.

The alternative would be to add a shell wrapper around waf too. But do we really want to maintain that with all edge cases? And again: That adds a fixed dependency to a shell. Without a wrapper we might be able to have packages for Windows that only contain a binary toolchain and a python installation. That could be useful for big teams that want to build the toolchain only on one host and distribute it in binary form to all developers.

#### **Comment 6**

1. **Chris Johns**, Wed, 05 Aug 2020 00:32:58 GMT

I tend to agree. I would like to first know if CentOS7 and openSUSE 15.2 to have a package to install python?

#### **Comment 7**

1. **Sebastian Huber**, Wed, 05 Aug 2020 04:49:05 GMT

On the waf issue tracker I found this:

<https://gitlab.com/ita1024/waf/-/issues/2259>

The suggested solution is to modify the shebang by hand for waf 2.\*.

On openSUSE 15.2 you have to install Python 2 to get a python command or add the symlink yourself as root.

My preferred solution would be to change all shebangs to `#!/usr/bin/env python3` and require all users of RTEMS to install Python 3.

#### **Comment 8**

1. **Chris Johns**, Wed, 05 Aug 2020 08:23:09 GMT

I have re-read PEP 394 and I am starting to think we should document and provide support for our users to run virtual environments. This is a recommendation in the PEP and I think it makes sense. As stated previously we need to support Python2 and Python3 for a period of time. Users restricted to Python2 should have a python command or they should have a virtualenv package for Python2. Python3 users should be on python3.6 or later and that has the venv module which gives them a python command.

I feel hard coding the version of python into the shebang restricts us and only creates further issues. Getting our users educated to use a virtual environment will pay off in the long term.

#### **Comment 9**

1. **Sebastian Huber**, Wed, 05 Aug 2020 08:30:03 GMT

I am not against using virtual environments, however, we should really evaluate if we want to support Python 2 in RTEMS 6. Maybe we should ask on the users mailing list if there are still host computer systems in use without a Python 3 support.

#### **Comment 10**

1. **Chris Johns**, Thu, 06 Aug 2020 00:20:26 GMT

A primary goal of RTEMS is to provide long life support for hardware and hosts.

I see the major issue with Python2 and Python3 as the shebang and python support rather than the coding. There are some basic things we need to do to support both but it is not a big deal. At this point in time I do not support just Python3.

As a result I prefer we focus on how we manage this situation. I believe virtual environments provide this. I see forcing the shebang to python3 as problematic long term.

#### **Comment 11**

1. **Sebastian Huber**, Thu, 06 Aug 2020 04:52:12 GMT

I still think we should try to learn a bit more about which hosts are in use by the RTEMS users. If there are still users around which are stuck with Python 2, then fine, otherwise we have one problem less.

How do you want to use the virtual environments? How is it set up? I have no experience in packaging and deploying Python projects. For me it would be a bit inconvenient if I have to activate a virtual environment just to run `./waf` to build RTEMS for example.



**Comment 12**

1. **Joel Sherrill**, Thu, 06 Aug 2020 14:06:17 GMT

Can we write a simple program as an alternative to env which answers the question of "which Python" in a way we want? rtems-which-python python[23] and let it answer the question?

I am opposed to forcing use of virtualenv but only encouraging it. It is a nice feature and I am using it but I only use it because the host doesn't have everything in a complete (Tex packaging) or current way. If the host is sufficient, it shouldn't be needed.

CentOS 7 does have a Python 3 but you have to install a "software collection" (<https://developers.redhat.com/products/softwarecollections/overview> for a description and list). This is the RedHat?? way of adding newer technologies as an option. This is what I have been doing on CentOS 7 combined with a virtualenv.

```
scl enable rh-python36 bash
```

I have been doing the Python 3 Software Collection plus a virtualenv for Sphinx to build the RTEMS documentation.

**Comment 13**

1. **Christian Mauderer**, Thu, 06 Aug 2020 14:12:46 GMT

CentOS 7 does have a Python 3 but you have to install a "software collection" (<https://developers.redhat.com/products/softwarecollections/overview> for a description and list). This is the RedHat?? way of adding newer technologies as an option.

That's a bit odd. There is a python3 in the "os" repo of CentOS 7: [http://mirror.centos.org/centos/7/os/x86\\_64/Packages/](http://mirror.centos.org/centos/7/os/x86_64/Packages/). That's the same repo where the kernel is (or at least a kernel). Is it possible that they added it?

**Comment 14**

1. **Chris Johns**, Thu, 06 Aug 2020 23:44:44 GMT

Using a virtual env, selecting an OS or a specific distribution of an OS, using python3 waf or adding a symlink yourself are all user choices. No one is forcing anyone to select any specific option and in fact I am concern we limit the choices in what we do. We also need to consider users may have other Python tools and commands and we need to make sure users can still run those tools.

The proposal I am putting forward is for user facing tools and scripts only and it is to shebang python only and we document a few of the approaches so it becomes a user choice. If you want to use CentOS with Python2 and python that is fine. If you want to install Python3 on CentOS that is no problem. If you use a bleeding edge Linux distro with a progressive set of packages and it only comes with Python3 that is also fine.

What I would like to avoid is us selecting a specific case and mandating it. This means we cannot force the shebang to python3 and we cannot explicitly exploit something in a virtual env.

Creating a specific env for us does not help other tools like waf.

**Comment 15**

1. **Christian Mauderer**, Fri, 07 Aug 2020 06:31:13 GMT

Maybe let me summarize a bit:

No one really fought for keeping the wrappers. Instead we should start documenting how to set up a good environment (either via virtualenv or installing directly on host systems). For our tools we should select a shebang that is used in all user facing tools. We have at least waf which uses just python in the shebang. So regardless what we chose: Our environment needs a python command as long as waf uses it. There is no consensus about which python version we should use for user facing tools. Maybe we should move that discussion to the mailing list like suggested multiple times?

I think the first three points answer the original question of the ticket? Did I miss something from the discussion?

The last point is definitively a controversial one. There are good reasons for both directions. But again: Maybe that should be discussed with a broader audience?

**Comment 16**

1. **Chris Johns**, Mon, 10 Aug 2020 06:06:10 GMT

Replying to Christian Mauderer:

I think the first three points answer the original question of the ticket? Did I miss something from the discussion?

I agree and no I do not think you have.

The last point is definitively a controversial one. There are good reasons for both directions. But again: Maybe that should be discussed with a broader audience?

I think there will be some push back to dropping Python2 right now and this will fade as time goes on.

**Comment 17**

1. **Christian Mauderer**, Mon, 10 Aug 2020 06:23:04 GMT

The last point is definitively a controversial one. There are good reasons for both directions. But again: Maybe that should be discussed with a broader audience?

I think there will be some push back to dropping Python2 right now and this will fade as time goes on.

There would be some advantages too. Maybe we should discuss an indicator that it is time to drop the python2 support (for example: as soon as waf does; or as soon as CentOS doesn't install it by default; or in 1 year; or ...) so that there is a clear plan and it isn't discussed again and again every few months. But like you said: That's not the topic of this ticket and I think it would be better to discuss this on the mailing list.

#### Comment 18

1. **Chris Johns**, Mon, 10 Aug 2020 06:50:14 GMT

Replying to Christian Mauderer:

The last point is definitively a controversial one. There are good reasons for both directions. But again: Maybe that should be discussed with a broader audience?

I think there will be some push back to dropping Python2 right now and this will fade as time goes on.

There would be some advantages too. Maybe we should discuss an indicator that it is time to drop the python2 support (for example: as soon as waf does; or as soon as CentOS doesn't install it by default; or in 1 year; or ...) so that there is a clear plan and it isn't discussed again and again every few months. But like you said: That's not the topic of this ticket and I think it would be better to discuss this on the mailing list.

I think the new build system and the qual project need to be done and we have releases with them. I think at the core of this issue is releases with python 2 and 3 and once we know how they are traveling it will become apparent what we can do.

I will remove the script support in the RSB and close this ticket when it is merged.

#### Comment 19

1. **Chris Johns**, Wed, 12 Aug 2020 01:11:32 GMT

In b71f7f69/rtems-docs:

```
user, README: Add Python script host set up information
Add Python3 and venv to the README Add a section on how to set up a host if the python command is
not available.
Update #4037
```

#### Comment 20

1. **Chris Johns**, Wed, 12 Aug 2020 03:20:12 GMT

2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **assigned**
4. **component:** changed from **admin** to **tool**

#### Comment 21

1. **Chris Johns**, Tue, 25 Aug 2020 23:59:31 GMT

2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 650c6f9/rtems-source-builder:

```
sb: Use shebang env python
Closes #4037
```

#### Comment 22

1. **Chris Johns**, Fri, 28 Aug 2020 00:13:54 GMT

2. **status:** changed from **closed** to **reopened**
3. **resolution: fixed** deleted

The rtems-tools.git repo needs to be changed to a shebang env python.

#### Comment 23

1. **Chris Johns**, Fri, 28 Aug 2020 01:48:45 GMT

In c51f634/rtems-source-builder:

```
sb: Fix the imports on Python2
Updates #4037
```

#### Comment 24

1. **Chris Johns**, Tue, 29 Nov 2022 23:00:51 GMT
2. **status**: changed from **reopened** to **closed**
3. **resolution**: set to **fixed**

The user of a virtualenv is to be used to manage various versions of Python.

## 4039 - arm/atsam/SC16IS752: Make interrupt server configurable (cloned)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4039">https://devel.rtems.org/ticket/4039</a> ( <a href="https://devel.rtems.org/ticket/4039">https://devel.rtems.org/ticket/4039</a> )
<b>Id</b>	4039
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	3 August 2020 07:45:54
<b>Modified</b>	5 August 2020 05:01:10
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Cloned from #4038.

### Comment 1

1. **Sebastian Huber**, Wed, 05 Aug 2020 05:01:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 1b421585/rtems:

```
arm/atsam: Make interrupt server configurable
```

The external UART over SPI device SC16IS752 uses the interrupt server for interrupt processing. The interrupt server is also heavily used by libbsd. The interrupt processing for the SC16IS752 is time critical and doesn't work if network traffic is processed at the same priority. With #4033 custom interrupt servers are available. Change `atsam_scl6is752_spi_create()` to support user-defined interrupt servers. Introduced `atsam_scl6is752_spi_config` to cut down the argument count of this function.

Close #4039.

## 4040 - coverhd.h remnants left to remove

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4040">https://devel.rtems.org/ticket/4040</a> ( <a href="https://devel.rtems.org/ticket/4040">https://devel.rtems.org/ticket/4040</a> )
<b>Id</b>	4040
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	3 August 2020 19:00:38
<b>Modified</b>	11 September 2020 13:54:33
<b>Owner</b>	joel@...
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

coverhd.h has been removed but there are as least two remnants to address:

- `tmoverhd` is not needed and still is present.
- (done) `m68k/mcf52235/README` references `coverhd.h`

```
$ grep -r coverhd ..
../rtems/bsps/m68k/mcf52235/README:* Update the coverhd.h (calling overheads) page 21 of the BSP guide
../rtems/bsps/m68k/mcf5225x/README:* Update the coverhd.h (calling overheads) page 21 of the BSP guide
```

**Comment 1**

1. **Joel Sherrill**, Thu, 10 Sep 2020 16:42:28 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

In e563e61/rtems:

Remove remaining references to coverhd.h  
Closes #4040.

**Comment 2**

1. **Joel Sherrill**, Thu, 10 Sep 2020 16:43:24 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution: fixed** deleted
4. **description**: modified (diff)

**Comment 3**

1. **Joel Sherrill**, Fri, 11 Sep 2020 13:54:33 GMT
2. **status**: changed from **reopened** to **closed**
3. **resolution**: set to **fixed**

In 5959b1e/rtems:

Remove tmoverhd which existed to produce the obsolete coverhd.h  
Closes #4040.

**4043 - Update software eng manual to rtems-central**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4043">https://devel.rtems.org/ticket/4043</a> ( <a href="https://devel.rtems.org/ticket/4043">https://devel.rtems.org/ticket/4043</a> )
<b>Id</b>	4043
<b>Reporter</b>	Chris Johns
<b>Created</b>	5 August 2020 00:25:24
<b>Modified</b>	7 August 2020 04:43:48
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

<https://docs.rtems.org/branches/master/eng/req/howto.html>  
Update to rtems-central

**Comment 1**

1. **Sebastian Huber**, Wed, 05 Aug 2020 04:38:33 GMT
2. **owner**: set to **Sebastian Huber**
3. **status**: changed from **new** to **assigned**

**Comment 2**

1. **Sebastian Huber**, Fri, 07 Aug 2020 04:43:48 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In e2abac7/rtems-docs:

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

eng: Refer to the rtems-central repository  
Close #4043.

---

## 4044 - Add RSB Track command

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4044">https://devel.rtems.org/ticket/4044</a> ( <a href="https://devel.rtems.org/ticket/4044">https://devel.rtems.org/ticket/4044</a> )
<b>Id</b>	4044
<b>Reporter</b>	Chris Johns
<b>Created</b>	10 August 2020 05:45:40
<b>Modified</b>	10 August 2020 06:16:48
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Add a comment to track the RSB build set and configuration files.

### Comment 1

1. **Chris Johns**, Mon, 10 Aug 2020 06:16:48 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **duplicate**

Duplicate of #4036.

---

## 4045 - Remove RSB sb-builder command

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4045">https://devel.rtems.org/ticket/4045</a> ( <a href="https://devel.rtems.org/ticket/4045">https://devel.rtems.org/ticket/4045</a> )
<b>Id</b>	4045
<b>Reporter</b>	Chris Johns
<b>Created</b>	10 August 2020 05:50:46
<b>Modified</b>	12 August 2020 01:11:27
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

This command is now always wrapped by the set builder. There is no need to use the command line with configuration files.

### Comment 1

1. **Chris Johns**, Mon, 10 Aug 2020 23:03:14 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 481bbd1/rtems-source-builder:

```
sb/builder: Remove sb-builder command
Closes #4045
```

**Comment 2**

1. **Chris Johns**, Wed, 12 Aug 2020 01:11:27 GMT

In 089f619/rtems-docs:

```
user: Remove RSB sb-builder command
Updates #4045
```

---

**4046 - Remove RSB sb-bootstrap command**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4046">https://devel.rtems.org/ticket/4046</a> ( <a href="https://devel.rtems.org/ticket/4046">https://devel.rtems.org/ticket/4046</a> )
<b>Id</b>	4046
<b>Reporter</b>	Chris Johns
<b>Created</b>	10 August 2020 05:52:21
<b>Modified</b>	12 August 2020 01:11:29
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Bootstrapping is going away with the new build system and until then the command in rtems.git should be used.

**Comment 1**

1. **Chris Johns**, Mon, 10 Aug 2020 23:03:16 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In a863b15/rtems-source-builder:

```
sb/bootstrap: Remove the sb-bootstrap command
Closes #4046
```

**Comment 2**

1. **Chris Johns**, Wed, 12 Aug 2020 01:11:29 GMT

In 441d2e1/rtems-docs:

```
user, eclipse: Remove RSB sb-bootstrap command
Update #4046
```

---

**4048 - Move RTEMS 5 BSP and package build sets and configs to RTEMS 6**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4048">https://devel.rtems.org/ticket/4048</a> ( <a href="https://devel.rtems.org/ticket/4048">https://devel.rtems.org/ticket/4048</a> )
<b>Id</b>	4048
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 August 2020 06:58:50
<b>Modified</b>	29 November 2022 22:17:01
<b>Owner</b>	Chris Johns
<b>Type</b>	task
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Move the BSP build sets with the related packages to RTEMS 6. Update the kernel and libbsd to point to RTEMS 6 commits.

Drop the tier build sets as these are not being used. They can be brought back if we need them.

**Comment 1**

1. **Chris Johns**, Sat, 15 Aug 2020 00:24:27 GMT

In 40af487/rtems-source-builder:

```
Move 5 build sets to 6
Move 5/bsps/* to bsp/* Update package build references from 5 to 6 Remove 5 build sets.
Update #4048
```

**Comment 2**

1. **Chris Johns**, Tue, 01 Sep 2020 01:46:06 GMT

In 5528b17/rtems-docs:

```
user: Change the BSP build set path
Updates #4048
```

**Comment 3**

1. **Chris Johns**, Tue, 29 Nov 2022 22:17:01 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **wontfix**

I am closing this as the rtems-deployment project and repo should now be used to manage BSPs and vertical stacks. The repo is currently in my personal area.

---

**4052 - [libbsd] e1000 driver not working for i386 based BSP in current rtems-libbsd master**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4052">https://devel.rtems.org/ticket/4052</a> ( <a href="https://devel.rtems.org/ticket/4052">https://devel.rtems.org/ticket/4052</a> )
<b>Id</b>	4052
<b>Reporter</b>	Jan Sommer
<b>Created</b>	14 August 2020 19:50:32
<b>Modified</b>	29 November 2022 23:18:19
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	2866
<b>Blocked by</b>	

---

**Description**

Current rtems-libbsd master branch fails to compile the e1000 driver for i386 based BSPs.

The corresponding patches from the 5-freebsd-12 branch need to be ported to master.

#### **Comment 1**

1. **kgardas**, Tue, 08 Sep 2020 15:31:23 GMT
2. **blocking**: set to **2866**

#### **Comment 2**

1. **Chris Johns**, Tue, 29 Nov 2022 23:18:19 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**

Please reopen with suitable patches for 6-freebsd-12

---

## **4054 - RTEMS\_BARRIER\_AUTOMATIC\_RELEASE and RTEMS\_BINARY\_SEMAPHORE options have the same value**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4054">https://devel.rtems.org/ticket/4054</a> ( <a href="https://devel.rtems.org/ticket/4054">https://devel.rtems.org/ticket/4054</a> )
<b>Id</b>	4054
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	17 August 2020 10:27:55
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

The RTEMS\_BARRIER\_AUTOMATIC\_RELEASE and RTEMS\_BINARY\_SEMAPHORE options have the same value. In order to better detect a misuse of option values (for example using RTEMS\_BINARY\_SEMAPHORE for rtems\_barrier\_create()), the options should have unique values.

#### **Comment 1**

1. **Sebastian Huber**, Wed, 19 Aug 2020 04:48:49 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 593a67f6/rtems:

```
rtems: Use unique option values
```

The RTEMS\_BARRIER\_AUTOMATIC\_RELEASE and RTEMS\_BINARY\_SEMAPHORE options had the same value. In order to better detect a misuse of option values (for example using RTEMS\_BINARY\_SEMAPHORE for rtems\_barrier\_create()), the options should have unique values.

Close #4054.

#### **Comment 2**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords**: **qualification** added
- 

## **4055 - bsp/xilinx-zynq: Flush TX-Buffer before initializing the zynq-uart**



---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4055">https://devel.rtems.org/ticket/4055</a> ( <a href="https://devel.rtems.org/ticket/4055">https://devel.rtems.org/ticket/4055</a> )
<b>Id</b>	4055
<b>Reporter</b>	Jan Sommer
<b>Created</b>	20 August 2020 07:11:39
<b>Modified</b>	22 August 2020 07:30:22
<b>Owner</b>	Jan Sommer <jan.sommer@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

We experienced that u-boot (at least from Xilinx repositories) does not wait until all its output has left the TX Buffer of the stdout uart, before handing over to the RTEMS application

This causes some garbage output at the begin of the RTEMS application in some cases and corrupts the test begin marker prohibiting rtems-test to recognize the test correctly.

Proposed fix is to let RTEMS wait until the TX Buffer of the uart is empty before configuring and using it.

**Comment 1**

1. **Jan Sommer**, Sat, 22 Aug 2020 07:29:38 GMT
2. **owner:** set to **Jan Sommer** <jan.sommer@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In b87efa7/rtems:

```
bsp/xilinx-zynq: Flush TX-Buffer before initializing uart
```

```
Closes #4055 Closes #4056
```

**Comment 2**

1. **Jan Sommer**, Sat, 22 Aug 2020 07:30:22 GMT

In 61ccb9c0/rtems:

```
bsp/xilinx-zynq: Flush TX-Buffer before initializing uart
```

```
Closes #4055 Closes #4056
```

---

## **4061 - The reworked <rtems/confdefs.h> has a cyclic dependency with RTEMS\_MULTIPROCESSING enabled (cloned)**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4061">https://devel.rtems.org/ticket/4061</a> ( <a href="https://devel.rtems.org/ticket/4061">https://devel.rtems.org/ticket/4061</a> )
<b>Id</b>	4061
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	21 August 2020 06:47:39
<b>Modified</b>	21 August 2020 06:57:49
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	config
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4060:

The changes for #3875 introduced a cyclic dependency between and .

#### Comment 1

1. **Sebastian Huber**, Fri, 21 Aug 2020 06:57:49 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 81efe37c/rtems:

```
confdefs: Fix cyclic dependency
Close #4061.
```

---

### 4063 - Change to a simpler TFTP server for rtems-test

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4063">https://devel.rtems.org/ticket/4063</a> ( <a href="https://devel.rtems.org/ticket/4063">https://devel.rtems.org/ticket/4063</a> )
<b>Id</b>	4063
<b>Reporter</b>	Chris Johns
<b>Created</b>	27 August 2020 04:54:24
<b>Modified</b>	31 August 2020 23:18:16
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

Add a simpler TFTP server that can have multiple instances on different ports running at once. Allowing more than one TFTP server to run at once is the first step to letting rtems-test run parallel hardware test jobs if the user has more one piece of hardware available for testing. Parallel hardware testing will speed up the time it takes to run the tests on target hardware.

This feature combined with the rtems-tftp-proxy lets a standard bootloader configuration be integrated into a parallel hardware test set up.

#### Comment 1

1. **Chris Johns**, Mon, 31 Aug 2020 23:18:16 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In eb36081/rtems-tools:

```
tester: Change to a simpler TFTP server
Add a simpler TFTP to allow parallel test hardware Remove the imported tftpy server
Closes #4063
```

---

### 4065 - Typo in rtems-boot.ini "ubootdiior" should be "ubootdir"

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4065">https://devel.rtems.org/ticket/4065</a> ( <a href="https://devel.rtems.org/ticket/4065">https://devel.rtems.org/ticket/4065</a> )
<b>Id</b>	4065
<b>Reporter</b>	Heinz Junkes
<b>Created</b>	28 August 2020 11:06:46
<b>Modified</b>	29 November 2022 23:21:57
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	rtems-boot-image
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

```

Typo in rtems-tools
misc/tools/config/rtems-boot.ini

diff rtems-boot.ini ./tools/misc/tools/config/rtems-boot.ini
55c55
< first_stage = %{ubootdir}/spl/boot.bin
---
| first_stage = %{ubootdir}/spl/boot.bin

```

**Attachments:****1 Heinz Junkes, Fri, 08 Apr 2022 07:36:06 GMT**

**attach:** set to [rtems-boot.ini.patch \(https://devel.rtems.org/ticket/4065/rtems-boot.ini.patch\)](https://devel.rtems.org/ticket/4065/rtems-boot.ini.patch)

**Comment 1**

1. **Heinz Junkes**, Fri, 08 Apr 2022 07:38:38 GMT
2. **version:** changed from **5** to **6**
3. **milestone:** changed from **5.1** to **6.1**

Update, is still in master (6?)

**Comment 2**

1. **Joel Sherrill**, Tue, 29 Nov 2022 23:21:57 GMT
2. **owner:** set to **Joel Sherrill <joel@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f29483d/rtems-tools:

```

rtems-boot.ini: Correct spelling of %{ubootdir}
Closes #4065.

```

**4066 - test running for too long**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4066">https://devel.rtems.org/ticket/4066</a> ( <a href="https://devel.rtems.org/ticket/4066">https://devel.rtems.org/ticket/4066</a> )
<b>Id</b>	4066
<b>Reporter</b>	Chris Johns
<b>Created</b>	28 August 2020 23:10:21
<b>Modified</b>	25 September 2020 01:16:43
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The spcache01 test on my PC test hardware is not finishing. It is looping generating output. Add a `__Test too long__` error count and end the test after 5 minutes.

**Comment 1**

1. **Sebastian Huber**, Sun, 30 Aug 2020 14:51:51 GMT

Which test case runs too long and why?

**Comment 2**

1. **Chris Johns**, Mon, 31 Aug 2020 03:27:33 GMT

Replying to Sebastian Huber:

Which test case runs too long and why?

The test is spcache01. I do not know the reason but I am using it to add support to handle a stuck test that loops for ever generating output.

#### **Comment 3**

1. **Sebastian Huber**, Mon, 31 Aug 2020 06:34:43 GMT

The spcache01 test program contains several test cases. If one of them loops forever, then there is a bug in the test or the cache support.

For the test runner wouldn't this be a timed out test?

#### **Comment 4**

1. **Chris Johns**, Mon, 31 Aug 2020 07:52:45 GMT

This ticket is about the tester being able to handle that case. The failure has highlighted a need for the tester to detect this, end the test and report the failure.

#### **Comment 5**

1. **Chris Johns**, Fri, 25 Sep 2020 01:16:43 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

## **4067 - Libbsd build system does not separate kernel and user land include paths**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4067">https://devel.rtems.org/ticket/4067</a> ( <a href="https://devel.rtems.org/ticket/4067">https://devel.rtems.org/ticket/4067</a> )
<b>Id</b>	4067
<b>Reporter</b>	Chris Johns
<b>Created</b>	2 September 2020 07:43:45
<b>Modified</b>	25 September 2020 01:16:16
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

FreeBSD has duplicates kernel and user land header files. LibBSD build system currently supports only one set of header include and the kernel and user land include paths.

#### **Comment 1**

1. **Chris Johns**, Fri, 25 Sep 2020 01:16:16 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

## **4069 - dl06 does not link on RISC**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4069">https://devel.rtems.org/ticket/4069</a> ( <a href="https://devel.rtems.org/ticket/4069">https://devel.rtems.org/ticket/4069</a> )
<b>Id</b>	4069
<b>Reporter</b>	Chris Johns
<b>Created</b>	6 September 2020 08:13:07
<b>Modified</b>	29 November 2022 23:03:11
<b>Owner</b>	Hesham Almatary <Hesham.Almataary@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

```
rtems-ld -r /home/jiri/src/rtems/riscvmp/riscv-rtems6/c/griscv \
-C riscv-rtems6-gcc -c "-march=rv32imafd -mabi=ilp32d" \
-O rap -b dl06.pre -e rtems main -s \
-o dl06.rap dl06-o1.o dl06-o2.o -lm
error: rap::object: Section index '0' not found: dl06-o1.o
Makefile:8528: recipe for target 'dl06.rap' failed
make[5]: *** [dl06.rap] Error 10
```

### Attachments:

- Jiri Gaisler, Sun, 06 Sep 2020 18:44:04 GMT**  
attach: set to [rld-rap.patch](https://devel.rtems.org/ticket/4069/rld-rap.patch) (<https://devel.rtems.org/ticket/4069/rld-rap.patch>)
- Jiri Gaisler, Tue, 08 Sep 2020 07:33:22 GMT**  
attach: set to [disable-dl-for-riscv.patch](https://devel.rtems.org/ticket/4069/disable-dl-for-riscv.patch) (<https://devel.rtems.org/ticket/4069/disable-dl-for-riscv.patch>)
- Chris Johns, Thu, 10 Sep 2020 05:07:34 GMT**  
attach: set to [0001-libdl-riscv-Support-misaligned-read-and-write-access.patch](https://devel.rtems.org/ticket/4069/0001-libdl-riscv-Support-misaligned-read-and-write-access.patch) (<https://devel.rtems.org/ticket/4069/0001-libdl-riscv-Support-misaligned-read-and-write-access.patch>)
- Chris Johns, Thu, 10 Sep 2020 23:28:09 GMT**  
attach: set to [riscv-rtl-empty-symbols.diff](https://devel.rtems.org/ticket/4069/riscv-rtl-empty-symbols.diff) (<https://devel.rtems.org/ticket/4069/riscv-rtl-empty-symbols.diff>)
- Chris Johns, Fri, 11 Sep 2020 08:24:12 GMT**  
attach: set to [v2-0001-libdl-riscv-Fix-RISCV-issues-with-libdl-tests.patch](https://devel.rtems.org/ticket/4069/v2-0001-libdl-riscv-Fix-RISCV-issues-with-libdl-tests.patch) (<https://devel.rtems.org/ticket/4069/v2-0001-libdl-riscv-Fix-RISCV-issues-with-libdl-tests.patch>)

### Comment 1

- Jiri Gaisler, Sun, 06 Sep 2020 18:46:49 GMT**

By re-applying Hesham's earlier patch (above), dl06 builds again. The program fails however on griscv bsp:

```
* BEGIN OF TEST libdl (RTL) 6 * * TEST VERSION: 6.0.0.aedd92d1477df0025821b77c06b2f2b2dc7aaf67 * TEST STATE: EXPECTED_PASS ___*
TEST BUILD: RTEMS_NETWORKING RTEMS_POSIX_API RTEMS_SMP ___* TEST TOOLS: 10.2.1 20200904 (RTEMS 6, RSB
47f32b8b1a597b5ed3475722bdc155249ef51115, Newlib a0d7982)
```

```
load: /dl06.rap dlopen failed: offset past end of file: offset=11716 size=11716
```

```
* FATAL * fatal source: 5 (RTEMS_FATAL_SOURCE_EXIT) fatal code: 0 (0x00000000) RTEMS version:
6.0.0.aedd92d1477df0025821b77c06b2f2b2dc7aaf67 RTEMS tools: 10.2.1 20200904 (RTEMS 6, RSB 47f32b8b1a597b5ed3475722bdc155249ef51115,
Newlib a0d7982) executing thread ID: 0x08a010001 executing thread name: U11
```

I guess this is not the intended behavior ...?

### Comment 2

- Hesham Almatary, Sun, 06 Sep 2020 21:12:01 GMT**
- owner:** set to **Hesham Almatary <Hesham.Almataary@...>**
- status:** changed from **new** to **closed**
- resolution:** set to **fixed**

In 764ea578/rtems:

```
htif_console_handler is defined in htif.c
closes #4069.
```

### Comment 3

- Hesham Almatary, Mon, 07 Sep 2020 14:00:52 GMT**
- status:** changed from **closed** to **reopened**

3. **resolution: fixed** deleted

The HTIF fix doesn't fix this error. The new run-time error (after Jiri applied my patch) is probably because of:

- 1) Some relocations not being supported in libdl/RISC-V implementation (e.g., RELAX) 2) I haven't tested/supported RAP format when I ported libdl for RISC-V.

**Comment 4**1. **Chris Johns**, Tue, 08 Sep 2020 07:26:07 GMT

If Jiri's patch builds dl06 then it can be pushed. The patch looks reasonable.

**Comment 5**1. **Jiri Gaisler**, Tue, 08 Sep 2020 07:32:41 GMT

The patch fixes the build of dl06, but several of the dlxx test then will fail during execution. If we push this patch, the the dl test must be marked as expected-fail for RISC-V. I would think that disabling building of dl tests is cleaner, see new suggested patch.

**Comment 6**1. **Chris Johns**, Wed, 09 Sep 2020 02:11:01 GMT

Replying to Jiri Gaisler:

The patch fixes the build of dl06, but several of the dlxx test then will fail during execution. If we push this patch, the the dl test must be marked as expected-fail for RISC-V.

Tagging the tests with expected-fail is my preferred approach.

I would think that disabling building of dl tests is cleaner, see new suggested patch.

I do not support doing this. Disabling or excluding tests because they fail hides the failures and does not encourage fixes. Why should RISC-V be treated as special? I feel disabling tests sends the wrong message.

I assume they passed once so regressions like this happen. I suspect if you wind back the tool sets to a previous version the tests might pass. Should tools upgrades be linked to regressions? I do not think that would be helpful.

**Comment 7**1. **Chris Johns**, Wed, 09 Sep 2020 04:06:29 GMT

I built the tests and dl01 to dl04 pass and dl05 to dl09 fail. I tried to have a look at dl05 however gdb reported:

```
(gdb) target remote :1234
Remote debugging using :1234
Truncated register 52 in remote 'g' packet
```

then disconnected me from sis.

**Comment 8**1. **Jiri Gaisler**, Wed, 09 Sep 2020 07:35:50 GMT

Replying to Chris Johns:

I built the tests and dl01 to dl04 pass and dl05 to dl09 fail. I tried to have a look at dl05 however gdb reported:

```
(gdb) target remote :1234
Remote debugging using :1234
Truncated register 52 in remote 'g' packet
```

then disconnected me from sis.

Make sure you use the extended-remote target, and riscv-rtems5-sis:

```
$ riscv-rtems5-sis -gdb . .
```

```
$ riscv-rtems6-gdb ./riscv-rtems6/c/griscv/testsuites/psxtests/psxfenv01.exe
```

```
$ (gdb) tar extended-remote localhost:1234 Remote debugging using localhost:1234 0x00000000 in ?? () (gdb) load Loading section .start, size 0xa8 lma 0x40000000 Loading section .text, size 0x15138 lma 0x400000a8 Loading section .rodata, size 0x1c1d lma 0x400151e0 Loading section .eh_frame, size 0x68 lma 0x40016e00 Loading section .init_array, size 0x4 lma 0x40016e68 Loading section .fini_array, size 0x4 lma 0x40016e6c Loading section .rtemsroset, size 0x74 lma 0x40016e70 Loading section .data, size 0x490 lma 0x40016ee8 Loading section .sdata, size 0xac lma 0x40017380 Start address 0x40000000, load size 95261 Transfer rate: 4429 KB/sec, 237 bytes/write. (gdb) run
```

**Comment 9**1. **Chris Johns**, Thu, 10 Sep 2020 01:50:07 GMT

Replying to Jiri Gaisler:

Replying to Chris Johns:

I built the tests and dl01 to dl04 pass and dl05 to dl09 fail. I tried to have a look at dl05 however gdb reported:

```
(gdb) target remote :1234
Remote debugging using :1234
Truncated register 52 in remote 'g' packet
```

then disconnected me from sis.

Make sure you use the extended-remote target, and riscv-rtems5-sis:

```
$ riscv-rtems5-sis -gdb .
```

I built it using the devel/sis RSB package and I only got an sis executable installed.

```
$ ../source-builder/sb-set-builder --list-bsets | grep sis
  devel/sis.bset
$ ls /opt/work/rtems/6/bin/ | grep sis
sis
sparc-rtems6-sis
```

I checked the build log and there is no riscv-rtems[56]-sis installed. I see a sparc-rtems-sis installed. Where do the those come from?

I will push a change to the RSB to build 2.22.

```
$ riscv-rtems6-gdb ./riscv-rtems6/c/griscv/testsuites/psxtests/psxfenv01.exe
```

```
$ (gdb) tar extended-remote localhost:1234
```

I added -riscv to the sis command line and it works. It must have been defaulting to the sparc simulation.

Note, the -riscv option is spelt wrong in the usage help.

### Comment 10

1. **Chris Johns**, Thu, 10 Sep 2020 04:17:07 GMT

I have looked into the crash in dl05 and it is a misaligned access because the rela record has an offset of 7. You can see this here:

```
$ riscv-rtems6-readelf -r riscv-rtems6/c/griscv/testsuites/libtests/dl05-o5.o
[snip]
Relocation section '.rela.gcc_except_table.exception_dl' at offset 0x8b98 contains 58 entries:
  Offset      Info      Type           Sym.Value   Sym. Name + Addend
00000007     00006423  R_RISCV_ADD32   0000002c    .LEHBO + 0
[snip]
```

This is a relocation record for exception table.

I have added reloc tracing to the RISCv backend the reloc that crashes is:

```
rtl: reloc base rel(/dl05-o5.o): ADD32: where=0x4006cc67, *where=0xdedeeded, addend=0x0, base 0x4006cc60
```

The \*where=0xdedeeded can be ignored, the value is invalid because the address was detected as odd.

I do not know the RISCv so does the write needs to be smarter or is the problem else where.

I am wondering if a number of other crashes are the same or a similar issue.

### Comment 11

1. **Chris Johns**, Thu, 10 Sep 2020 05:08:43 GMT

The patch lets things get further along however there are other issues with the libdl tests 5 thru 9. I have no more time available to look into this.

### Comment 12

1. **Jiri Gaisler**, Thu, 10 Sep 2020 07:21:02 GMT

Replying to Chris Johns:

Replying to Jiri Gaisler:

Replying to Chris Johns:

I built the tests and dl01 to dl04 pass and dl05 to dl09 fail. I tried to have a look at dl05 however gdb reported:

```
(gdb) target remote :1234
Remote debugging using :1234
Truncated register 52 in remote 'g' packet
```

then disconnected me from sis.

Make sure you use the extended-remote target, and riscv-rtems5-sis:

```
$ riscv-rtems5-sis -gdb .
```

I built it using the devel/sis RSB package and I only got an sis executable installed.

```
$ ../source-builder/sb-set-builder --list-bsets | grep sis
devel/sis.bset
$ ls /opt/work/rtems/6/bin/ | grep sis
sis
sparc-rtems6-sis
```

I checked the build log and there is no riscv-rtems[56]-sis installed. I see a sparc-rtems-sis installed. Where do those come from?

I will push a change to the RSB to build 2.22.

```
$ riscv-rtems6-gdb ./riscv-rtems6/c/griscv/testsuites/psxtests/psxfenv01.exe
```

```
$ (gdb) tar extended-remote localhost:1234
```

I added -riscv to the sis command line and it works. It must have been defaulting to the sparc simulation.

Note, the -riscv option is spelt wrong in the usage help.

I have updated RSB to also build sis for RISC-V. This was previously done only for rtems5, not rtems6.

### Comment 13

1. **Chris Johns**, Thu, 10 Sep 2020 23:25:33 GMT

Replying to Jiri Gaisler:

I have updated RSB to also build sis for RISC-V. This was previously done only for rtems5, not rtems6.

Thanks. Does this install as riscv-rtems6-sis?

### Comment 14

1. **Jiri Gaisler**, Fri, 11 Sep 2020 06:49:07 GMT

Replying to Chris Johns:

Replying to Jiri Gaisler:

I have updated RSB to also build sis for RISC-V. This was previously done only for rtems5, not rtems6.

Thanks. Does this install as riscv-rtems6-sis?

Yes, that is the whole idea with this patch... :-)

### Comment 15

1. **Chris Johns**, Fri, 11 Sep 2020 07:06:23 GMT

Replying to Jiri Gaisler:

Yes, that is the whole idea with this patch... :-)

Being able to have the SIS available like this when a RISC-V tool chain is built is fantastic. Thank you for your support and the tool.

### Comment 16

1. **Jiri Gaisler**, Fri, 11 Sep 2020 07:08:33 GMT

The riscv-rtl-empty-symbols.diff patch gives me the following failures:

Failures:

```
dl01.exe dl02.exe dl05.exe dl08.exe
```

User Input:



```
dl10.exe monitor.exe termios.exe top.exe
```

dl01, dl02 and dl08 now times-out rather than fails....

#### Comment 17

1. **Chris Johns**, Fri, 11 Sep 2020 07:36:26 GMT

Yeah, something is wrong with the patch. I was seeing an unresolved symbol with a symbol name of "" being added and as you can imagine it is never resolved.

#### Comment 18

1. **Chris Johns**, Fri, 11 Sep 2020 08:07:21 GMT

I am starting to suspect the issue is the R\_RISCV\_RELAX reloc records and the call sites. The simplest approach is to ignore those relocs and just use 32bit destinations or implement the 21bit relative offset if the target is in range.

The RISCV relax approach is nicer to libdl than the ARM or PowerPC trampoline support.

#### Comment 19

1. **Chris Johns**, Fri, 11 Sep 2020 08:26:15 GMT

dl05 has an issue in the unwind tables somewhere. An object's tables are added to the base tables so you can throw in a module and catch it elsewhere. dl06 is a RAP thing which requires some work to sort out.

#### Comment 20

1. **Hesham Almatary**, Tue, 15 Sep 2020 07:17:20 GMT

Thanks, Chris for your fixes! I applied the last patch and tried to test rv64imafdc\_medany on QEMU, but dl01 fails in run-time triggering an exception while loading the object. I'll debug that issue.

#### Comment 21

1. **Chris Johns**, Tue, 29 Nov 2022 23:03:11 GMT

2. **status**: changed from **reopened** to **closed**

3. **resolution**: set to **fixed**

please reopen if it is still failing.

## 4070 - RISC-V Multiple Definition Error (many BSPs)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4070">https://devel.rtems.org/ticket/4070</a> ( <a href="https://devel.rtems.org/ticket/4070">https://devel.rtems.org/ticket/4070</a> )
<b>Id</b>	4070
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	6 September 2020 17:56:32
<b>Modified</b>	16 December 2021 15:40:50
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/riscv
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

This error appears to occur on all RISC-V BSPs which do not fail at the dynamic loading rap section 0 error. I assume that eventually they may all hit this. List of BSPs failing below message.

```
/home/joel/rtems-cron-6/tools/6/lib/gcc/riscv-rtems6/10.2.1/../../../../riscv-rtems6/bin/ld: /home/joel/rtems-cron-6/rtems/bsp/riscv/riscv/include/dev/serial/htif.h:48: multiple definition of `htif_console_handler'; /home/joel/rtems-cron-6/rtems/bsp/riscv/riscv/include/dev/serial/htif.h:48: first defined here
/home/joel/rtems-cron-6/tools/6/lib/gcc/riscv-rtems6/10.2.1/../../../../riscv-rtems6/bin/ld: /home/joel/rtems-cron-6/rtems/bsp/riscv/riscv/include/dev/serial/htif.h:48: multiple definition of `htif_console_handler'; /home/joel/rtems-cron-6/rtems/bsp/riscv/riscv/include/dev/serial/htif.h:48: first defined here
mv -f cctest/.deps/cctest-init.Tpo cctest/.deps/cctest-init.Po
```

```
rv32iac_spike
rv32imac_spike
rv32imafc_spike
rv32imafdc_spike
rv32imafd_spike
```

rv32im\_spike  
 rv32i\_spike  
 rv64imac\_medany\_spike  
 rv64imac\_spike  
 rv64imafdc\_medany\_spike  
 rv64imafdc\_spike  
 rv64imafd\_medany\_spike  
 rv64imafd\_spike

**Comment 1**

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:40:50 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

Works now

---

**4072 - testsuite: Add ticket ids for expected-fail and indeterminate states, add annotations**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4072">https://devel.rtems.org/ticket/4072</a> ( <a href="https://devel.rtems.org/ticket/4072">https://devel.rtems.org/ticket/4072</a> )
<b>Id</b>	4072
<b>Reporter</b>	Chris Johns
<b>Created</b>	9 September 2020 00:21:59
<b>Modified</b>	27 July 2023 16:37:38
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	blocker
<b>Keywords</b>	test rtems-test
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

- Require a ticket id be present for any expected-fail and indeterminate test states.
- Parse the ticket number from the .tcgf file and pass into the test.
- Have rtems-test obtain the ticket number from the test when run and provide the ticket number in the results.
- Add annotations for tests. The list is to be provided by Joel.

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:18:54 GMT
2. **priority**: changed from **normal** to **high**
3. **severity**: changed from **normal** to **blocker**

**Comment 2**

1. **Chris Johns**, Thu, 29 Jun 2023 23:34:15 GMT

This is now updated in the spec YAML files.

**Comment 3**

1. **Kinsey Moore**, Thu, 29 Jun 2023 23:40:04 GMT

I have some to handle for AArch64 and ARM and any BSPs that run specifically on QEMU.

**Comment 4**

1. **Kinsey Moore**, Mon, 10 Jul 2023 13:49:21 GMT

In f46c15f/rtems:

```
spec: Add QEMU test annotations

QEMU is known to fail certain tests intermittently due to clock tick delivery issues. This defines those tests as intermittent for BSPs
intended to run on QEMU alone.

Updates #4922 Updates #4072
```

**Comment 5**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Kinsey Moore**, Mon, 10 Jul 2023 13:52:26 GMT

The above commit takes care of all the indeterminate test states that I'm aware of in the AArch64 realm.

#### Comment 6

1. **Kinsey Moore**, Thu, 27 Jul 2023 16:37:38 GMT

The only indeterminate test state is now documented properly. These are the remaining files that have a test state of expected-fail:

spec/build/bsps/tst-xfail-intr.yml (validation-intr for powerpc/psim) spec/build/bsps/i386/pc386/tst-xfail-val.yml (various validation tests for i386/pc386)  
spec/build/bsps/tst-xfail-dl06.yml (dl06 for arm/imx7) spec/build/bsps/tst.yml (psxfenv01 for all arches)

---

## 4074 - Add CONFIGURE\_MAXIMUM\_THREAD\_LOCAL\_STORAGE\_SIZE

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4074">https://devel.rtems.org/ticket/4074</a> ( <a href="https://devel.rtems.org/ticket/4074">https://devel.rtems.org/ticket/4074</a> )
<b>Id</b>	4074
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 September 2020 13:17:40
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	config
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

This configuration option can be used to reserve space for the dynamic linking of modules with thread-local storage objects. See also:

<https://lists.rtems.org/pipermail/devel/2020-September/061867.html>

#### Comment 1

1. **Sebastian Huber**, Thu, 10 Sep 2020 13:20:30 GMT
2. **description:** modified (diff)

#### Comment 2

1. **Chris Johns**, Fri, 11 Sep 2020 07:09:20 GMT

In f86a0ce/rtems-tools:

```
linkers/exeinfo: Output TLS data
Updates #4074
```

#### Comment 3

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:22 GMT

In 641b31a4/rtems:

```
rtems: Add RTEMS_ALIGN_DOWN()
Update #3959. Update #4074.
```

#### Comment 4

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:25 GMT

In dce1cdf1/rtems:

```
rtems: Add RTEMS_ALIGN_UP()
Update #3959. Update #4074.
```

**Comment 5**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:09:29 GMT

In c312f31/rtems:

```
CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE

Add this application configuration option. This configuration option can be used to reserve space for the dynamic linking of modules
with thread-local storage objects.

Add RTEMS_TASK_STORAGE_ALIGNMENT to define the minium alignment of a thread-local storage size.

Update #4074.
```

**Comment 6**

1. **Sebastian Huber**, Thu, 17 Sep 2020 16:14:43 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In a5fe9aa/rtems-docs:

```
c-user: CONFIGURE_MAXIMUM_THREAD_LOCAL_STORAGE_SIZE

Document this application configuration option.

Close #4074.
```

**Comment 7**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT

2. **keywords**: **qualification** added

**4076 - i386: bad asm in smp mode**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4076">https://devel.rtems.org/ticket/4076</a> ( <a href="https://devel.rtems.org/ticket/4076">https://devel.rtems.org/ticket/4076</a> )
<b>Id</b>	4076
<b>Reporter</b>	Gedare Bloom
<b>Created</b>	12 September 2020 04:58:58
<b>Modified</b>	12 September 2020 15:13:14
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	arch/i386
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

A note for me (or someone) to make the fix outlined on the mailing list.

```
cpuakit/score/cpu/i386/include/rtems/asm.h:157 movb
imps_apic_cpu_map(\\REG),\\REG /* CPU ID in REG */
```

The assembler is right to complain. movb has to target one of the 1-byte mnemonics, so this should be %al for the LSB of %eax. One needs to check through this logic carefully, but I think the right thing to do here is:

```
movzbl imps_apic_cpu_map(\\REG),\\REG
```

That should do the trick. Can you test it locally?

Sure! Builds fine and testsuite testing reveals:

**Comment 1**

1. **Gedare Bloom**, Sat, 12 Sep 2020 14:26:07 GMT

2. **version**: changed from **5** to **6**

3. **description:** modified (diff)
4. **milestone:** changed from **5.1** to **6.1**

**Comment 2**

1. **Joel Sherrill**, Sat, 12 Sep 2020 14:55:37 GMT

This should be fixed on the 5 branch as well for safety.

**Comment 3**

1. **Gedare Bloom**, Sat, 12 Sep 2020 15:13:14 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 9f096f4/rtems:

```
i386/score: fix assembly mnemonic
Closes #4076.
```

**4077 - Implement LibBSD module dependencies in the build system**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4077">https://devel.rtems.org/ticket/4077</a> ( <a href="https://devel.rtems.org/ticket/4077">https://devel.rtems.org/ticket/4077</a> )
<b>Id</b>	4077
<b>Reporter</b>	Chris Johns
<b>Created</b>	14 September 2020 05:39:34
<b>Modified</b>	25 September 2020 01:17:15
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The build system has a partially implemented module dependency system. Complete the implementation. Control tests being built. If a test depends on a module and the module is disabled do not build the test.

Add dependency checking to the freebsd-to-rtems.py command. If the module definition is not consistent generate an error.

**Comment 1**

1. **Chris Johns**, Fri, 25 Sep 2020 01:17:15 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

**4078 - GCC C++ compiler for powerpc defines \_GNU\_SOURCE as a built-in**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4078">https://devel.rtems.org/ticket/4078</a> ( <a href="https://devel.rtems.org/ticket/4078">https://devel.rtems.org/ticket/4078</a> )
<b>Id</b>	4078
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 September 2020 06:51:45
<b>Modified</b>	8 September 2022 05:31:33
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/powerpc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

For example:

```
powerpc-rtems6-g++ -E -P -v -dD empty.cc 2>&1 | grep GNU_SOURCE
```

Yields:

```
/opt/rtems/6/libexec/gcc/powerpc-rtems6/10.2.1/cc1plus -E -quiet -v -P -D_GNU_SOURCE -Dmpc750 empty.cc -dD
#define GNU_SOURCE 1
```

This is a GCC configuration bug. The reason is that the RTEMS GCC configuration includes gnu-user.h.

**Comment 1**

1. **Sebastian Huber**, Mon, 14 Sep 2020 06:52:17 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Joel Sherrill**, Mon, 14 Sep 2020 12:53:32 GMT

I agree that this isn't right. We shouldn't be implicitly defining anything that enables extended APIs.

How did you spot this?

**Comment 3**

1. **Sebastian Huber**, Mon, 14 Sep 2020 15:19:38 GMT

I noticed this during the tests of the new build system. The powerpc is the only RTEMS target which defines `_GNU_SOURCE`.

**Comment 4**

1. **Chris Johns**, Tue, 15 Sep 2020 03:19:01 GMT

Replying to Joel Sherrill:

How did you spot this?

I have updated rtems-exeinfo to optionally output the full flags used to build an object file.

```
$ rtems-exeinfo -O --full-flags `find . -name hello.exe`
```

This is the output from hello.exe for the psim showing a mix of options:

```
| wctomb.c : -mcpu=603e -mcpu=603e -g -O2 -fno-builtin -ffunction-sections -fdata-sections
| wctomb_r.c : -mcpu=603e -mcpu=603e -g -O2 -fno-builtin -ffunction-sections -fdata-sections
| wkspac.c : -mcall-sysv -meabi -mcpu=603e -msdata=sysv -g -O2 -fno-common -fno-keep-inline-functions -
ffunction-sections -fdata-sections
| wkspacisunifieddefault.c : -mcall-sysv -meabi -mcpu=603e -msdata=sysv -g -O2 -fno-common -fno-keep-inline-functions -
ffunction-sections -fdata-sections
| write.c : -mcall-sysv -meabi -mcpu=603e -msdata=sysv -g -O2 -fno-common -fno-keep-inline-functions -
ffunction-sections -fdata-sections
| write_r.c : -mcall-sysv -meabi -mcpu=603e -msdata=sysv -g -O2 -fno-common -fno-keep-inline-functions -
ffunction-sections -fdata-sections
| wsetup.c : -mcpu=603e -mcpu=603e -g -O2 -fno-builtin -ffunction-sections -fdata-sections
```

And there is the pc686 BSP with LibBSD showing the i386 issue:

```

| tzset.c : -mtune=pentiumpro -march=i386 -g -O2 -fno-builtin -ffunction-sections -fdata-sections
| tzset_r.c : -mtune=pentiumpro -march=i386 -g -O2 -fno-builtin -ffunction-sections -fdata-sections
| tzvars.c : -mtune=pentiumpro -march=i386 -g -O2 -fno-builtin -ffunction-sections -fdata-sections
| u_strerror.c : -mtune=pentiumpro -march=i386 -g -O2 -fno-builtin -ffunction-sections -fdata-sections
| uart_bus_pci.c : -mtune=pentiumpro -march=pentium -g -O2 -ffunction-sections -fdata-sections
| udp6_usrreq.c : -mtune=pentiumpro -march=pentium -g -O2 -ffunction-sections -fdata-sections -fno-strict-
aliasing -ffreestanding -fno-common
| udp_usrreq.c : -mtune=pentiumpro -march=pentium -g -O2 -ffunction-sections -fdata-sections -fno-strict-
aliasing -ffreestanding -fno-common
| uenvgetgroups.c : -mtune=pentiumpro -march=pentium -g -O2 -ffunction-sections -fdata-sections
| uipc_accf.c : -mtune=pentiumpro -march=pentium -g -O2 -ffunction-sections -fdata-sections -fno-strict-
aliasing -ffreestanding -fno-common
| uipc_domain.c : -mtune=pentiumpro -march=pentium -g -O2 -ffunction-sections -fdata-sections -fno-strict-
aliasing -ffreestanding -fno-common

```

I think preprocessor flags are not captured.

#### Comment 5

1. **Sebastian Huber**, Thu, 08 Sep 2022 05:31:33 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

Fixed in GCC 10, 11, 12, and 13.

### 4079 - build: i386/pc686/appstart.o is created more than once

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4079">https://devel.rtems.org/ticket/4079</a> ( <a href="https://devel.rtems.org/ticket/4079">https://devel.rtems.org/ticket/4079</a> )
<b>Id</b>	4079
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 September 2020 13:20:08
<b>Modified</b>	15 September 2020 18:08:01
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

In this build specification item

<https://git.rtems.org/rtems/tree/spec/build/bsps/i386/pc386/objsmptest.yml>

is an error:

```

* Node /home/EB/sebastian_h/git-rtems-6/build/i386/pc686/appstart.o is created more than once. The task generators are:
1. bld(target=['appstart.o'], idx=14, tg_idx_count=14, meths=['check_err_features', 'check_err_order', 'process_rule',
'process_source'], rule='${OBJCOPY} -I binary -O elf32-i386 -B i386 ${SRC} ${TGT}', _name='appstart.o', source=[],
path=/home/EB/sebastian_h/git-rtems-6, posted=True, features=[]) in /home/EB/sebastian_h/git-rtems-6
2. bld(target='/bsps/i386/pc386/objsmptest', idx=15, tmp_use_objects=False, tg_idx_count=15, meths=['check_err_features',
'check_err_order', 'process_rule', 'process_source'], tmp_use_stlib=True, _name='/bsps/i386/pc386/objsmptest', source=
[/home/EB/sebastian_h/git-rtems-6/build/i386/pc686/appstart.o], tmp_use_var='', path=/home/EB/sebastian_h/git-rtems-6, posted=True,
typ='objects', features=[]) in /home/EB/sebastian_h/git-rtems-6
If you think that this is an error, set no_errcheck out on the task instance

```

All what we have to do is to add a specially produced appstart.o to librtmsbsp.a.

#### Comment 1

1. **Sebastian Huber**, Tue, 15 Sep 2020 18:08:01 GMT
2. **owner:** set to **Sebastian Huber** <sebastian.huber@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 9979042/rtems:

```

build: Fix multiple defintion error for i386/pc386
Make the objcopy an bld.objects() task generator.
Close #4079.

```

### 4080 - build: Add start.o dependency to the executable link step

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4080">https://devel.rtems.org/ticket/4080</a> ( <a href="https://devel.rtems.org/ticket/4080">https://devel.rtems.org/ticket/4080</a> )
<b>Id</b>	4080
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	16 September 2020 06:00:52
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

RTEMS is a real-time operating system and the applications using RTEMS end up in a single executable which contains also the full system initialization. The linker uses a start file to determine what should be linked into the executable. The start file is also built by the build system, however, it is only indirectly referenced via a linker script, for example:

<https://git.rtems.org/rtems/tree/bsps/arm/shared/start/linkcmds.base#n28>

So, every executable depends on the start file (start.o usually). If start.o changes, then the executable needs to be re-linked. Also the start file needs the name expected by the linker script, for example not start.S.17.o.

The start files are build with this commands:

<https://git.rtems.org/rtems/tree/wscript#n535>

<https://git.rtems.org/rtems/tree/wscript#n244>

Somehow we have to add a dependency on start.o to every executable.

To experiment with the build system use the following commands to set it up:

```
cd $HOME
mkdir rtems-sdk
mkdir rtems-sdk/src
cd rtems-sdk/src
git clone git://git.rtems.org/rtems.git
git clone git://git.rtems.org/rtems-source-builder.git rsb
cd rsb/rtems
../source-builder/sb-set-builder --prefix=$HOME/rtems-sdk/6 6/rtems-sparc
cd ../../rtems
echo "[sparc/leon3]" > config.ini
./waf configure --prefix=$HOME/rtems-sdk/6
./waf
```

The host must be capable to build GCC and needs the Python development support (header files) installed.

## Comment 1

1. **Sebastian Huber**, Wed, 16 Sep 2020 07:04:51 GMT
2. **description:** modified (diff)

## Comment 2

1. **Sebastian Huber**, Thu, 17 Sep 2020 06:58:03 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 4eea8d4/rtems:

```
build: Fix dependencies for start and asm files

Add a feature to enforce an explicit target file for assembler sources. Add a build start file node list and use it as a test program dependency.

The fix for #3846 and #4080 needs to be combined, because the fix for #3846 requires the removal of 'before=cstlib?'. This patch fixes two issues:
The tracking of start file dependencies. Reflect that executables depend on the start files.
We need a start.o file in the right path so that the linker can find it as specified by the linker script, and not for example a start.S.17.o file in some path. This part is addressed by the "explicit_asm_target" feature.
```

This build process extension

```
@after("apply_link") @feature("cprogram", "cxxprogram") def process_start_files(self):
```

```
    if getattr(self, "start_files", False):
        self.link_task.dep_nodes.extend(self.bld.start_files)
```

addresses 2.

Close #3846. Close #4080.



**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords: qualification** added
- 

**4081 - Remove Autoconf/Automake based build system**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4081">https://devel.rtems.org/ticket/4081</a> ( <a href="https://devel.rtems.org/ticket/4081">https://devel.rtems.org/ticket/4081</a> )
<b>Id</b>	4081
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	17 September 2020 06:05:47
<b>Modified</b>	29 November 2021 15:00:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	task
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	4468

---

**Description**

Remove Autoconf/Automake? based build system after a testing phase of the waf based build system. The planned date to remove the old build system is 1st November 2020.

For a status of the new build system see:

<https://devel.rtems.org/wiki/Release/6/Waf%20BSP%20Checklist>

**Comment 1**

1. **Chris Johns**, Thu, 17 Sep 2020 06:11:14 GMT

What will happen to <https://git.rtems.org/rtems/tree/c/ACKNOWLEDGEMENTS> ?

**Comment 2**

1. **Sebastian Huber**, Thu, 17 Sep 2020 06:13:04 GMT

Move it to the top-level or the documentation?

**Comment 3**

1. **Chris Johns**, Thu, 17 Sep 2020 06:15:26 GMT

Sorry, I do not know. It is out of date but historically important. I think this is one for Joel.

I could not see anything else in the c tree.

**Comment 4**

1. **Chris Johns**, Fri, 26 Feb 2021 07:18:57 GMT

The `motorola_powerpc` bootloader is looks like it is linking in some fake rom code and in the autoconf build system that is conditional on it being a qemu build.

**Comment 5**

1. **Chris Johns**, Wed, 14 Jul 2021 04:27:43 GMT
2. **keywords: wafblocker** added

**Comment 6**

1. **Chris Johns**, Wed, 14 Jul 2021 04:28:20 GMT
2. **blockedby: set to 4468**

**Comment 7**

1. **Joel Sherrill**, Mon, 13 Sep 2021 21:42:26 GMT

2. **summary:** changed from **Remove Autoconf/Aotomake based build system** to **Remove Autoconf/Automake based build system**

**Comment 8**

1. **Joel Sherrill**, Mon, 13 Sep 2021 21:45:41 GMT

Any objections to removing this now? :)

The RTEMS kernel recipe is still broken but that's about the end of it.

**Comment 9**

1. **Joel Sherrill**, Sun, 19 Sep 2021 16:42:08 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In a178eba/rtems-source-builder:

```
Remove automake/autoconf from rtems 6 tools
These are unneeded with the waf build system.
Closes #4081.
```

**Comment 10**

1. **Sebastian Huber**, Tue, 21 Sep 2021 08:25:58 GMT

In db8f598/rtems:

```
build: Remove old build system
Close #3250. Close #4081.
```

**Comment 11**

1. **Joel Sherrill**, Mon, 29 Nov 2021 15:00:03 GMT

In e945e3fc/rtems:

```
*/aclocal/*: Remove remnants of autoconf/automae build system
Updates #4081.
```

**4084 - throwing std::runtime on PC BSP fails**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4084">https://devel.rtems.org/ticket/4084</a> ( <a href="https://devel.rtems.org/ticket/4084">https://devel.rtems.org/ticket/4084</a> )
<b>Id</b>	4084
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 September 2020 19:46:08
<b>Modified</b>	1 October 2020 15:23:45
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/gcc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	Chris Johns Michael Davidsaver
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Copied from #2830 for new release milestone. The solution is to update gcc/config/i386/t-rtems. Whether for gcc 10 or gcc master is the difference on this CR versus #2830 which had to be to gcc 7 as a patch via the RSB.

Throwing a std::runtime() exception locks up.

The lock up is in the exception clean up handler where the exception object is destructed. The destructor loops destructing the std::string object. The path ends up in libstdc++-v3/include/ext/atomicity.h line 48 or exchange\_and\_add.

At a guess it would seem like the C++ atomics on i386 is broken or fragile.

UPDATE: This was broken when gcc i386 eliminated -mcpu in favor of -march/-mtune. The multilibs were built with -mtune and not -march.

**Attachments:**

- 
- 1 **Joel Sherrill, Mon, 21 Sep 2020 20:17:06 GMT**  
**attach:** set to [gcc-10-i386march-1.diff](https://devel.rtems.org/ticket/4084/gcc-10-i386march-1.diff) (<https://devel.rtems.org/ticket/4084/gcc-10-i386march-1.diff>)
- 

**Comment 1**

1. **Michael Davidsaver, Mon, 21 Sep 2020 21:14:32 GMT**

In 1ea1c9c/rtems-source-builder:

```
patch gcc i386 multiarch
```

Add patch to change from mtune to march when building multilibs. The mtune argument tunes or optimizes for a specific CPU model but does not ensure the generated code is appropriate for the CPU model. Prior to this patch, i386 compatible code was always generated but tuned for later models.

This is the same fix as #2830 but applying to gcc 10.

Updates #4084.

**Comment 2**

1. **Joel Sherrill, Mon, 21 Sep 2020 21:17:08 GMT**

Post for GCC 10 and master posted <https://gcc.gnu.org/pipermail/gcc-patches/2020-September/554430.html>

**Comment 3**

1. **Joel Sherrill, Mon, 21 Sep 2020 21:17:50 GMT**  
 2. **cc: Chris Johns Michael Davidsaver** added

**Comment 4**

1. **Joel Sherrill, Thu, 01 Oct 2020 15:23:45 GMT**  
 2. **status:** changed from **new** to **closed**  
 3. **resolution:** set to **fixed**

I applied the GCC patch to the master and 10 release branch.

<https://gcc.gnu.org/git/?p=gcc.git;a=commit;h=63a32847b0e8d14ae1eafe047ea43441f6e3a11c>

---

**4093 - bsps/pc386: Add missing license header**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4093">https://devel.rtems.org/ticket/4093</a> ( <a href="https://devel.rtems.org/ticket/4093">https://devel.rtems.org/ticket/4093</a> )
<b>Id</b>	4093
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	23 September 2020 13:24:57
<b>Modified</b>	23 September 2020 13:25:51
<b>Owner</b>	Jan Sommer < <a href="mailto:jan.sommer@...">jan.sommer@...</a> >
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

bspsmp.c is missing a licence header.

**Comment 1**

1. **Jan Sommer, Wed, 23 Sep 2020 13:25:51 GMT**  
 2. **owner:** set to **Jan Sommer** <[jan.sommer@...](mailto:jan.sommer@...)>  
 3. **status:** changed from **new** to **closed**

4. **resolution:** set to **fixed**

In 1f77518/rtems:

bsps/pc386: Add missing license header  
Closes #4093.

**4095 - Remove doc from rtems-tools**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4095">https://devel.rtems.org/ticket/4095</a> ( <a href="https://devel.rtems.org/ticket/4095">https://devel.rtems.org/ticket/4095</a> )
<b>Id</b>	4095
<b>Reporter</b>	Chris Johns
<b>Created</b>	24 September 2020 23:53:13
<b>Modified</b>	22 June 2023 21:21:57
<b>Owner</b>	Kinsey Moore
<b>Type</b>	task
<b>Component</b>	tool
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

This directory is not used and needs to go. I will push the change directly to the repo to avoid the clutter a review would generate as most of the files and imported.

**Comment 1**

1. **Joel Sherrill**, Thu, 03 Mar 2022 22:54:55 GMT

Is this done? Easy to close?

**Comment 2**

1. **Joel Sherrill**, Wed, 28 Dec 2022 19:51:02 GMT

Please check if this can be closed.

**Comment 3**

1. **Gedare Bloom**, Mon, 23 Jan 2023 20:41:52 GMT

<https://git.rtems.org/rtems-tools/tree/doc>

Still exists.

**Comment 4**

1. **Joel Sherrill**, Thu, 09 Feb 2023 16:04:32 GMT

I think that much of the content in rtems-tools/doc is NOT in the Users Guide. The discussion of the RTEMS Tester in the Users Guide takes a different view and appears to never show how to use it which is the focus of much of this documentation. I don't think this is a simple remove some files.

**Comment 5**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:21:57 GMT

2. **owner:** changed from **Chris Johns** to **Kinsey Moore**

**4097 - shell: CTRL-U sets the cursor to the wrong position (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4097">https://devel.rtems.org/ticket/4097</a> ( <a href="https://devel.rtems.org/ticket/4097">https://devel.rtems.org/ticket/4097</a> )
<b>Id</b>	4097
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	28 September 2020 12:13:46
<b>Modified</b>	28 September 2020 12:17:27
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

Cloned from #4096:

This patch fixes a tiny bug in the command line editing of the RTEMS shell. Typing CTRL-U in the shell should remove all characters left of the cursor. After pressing CTRL-U, the current implementation does wrongly place the cursor at the end of the line instead at its beginning. To reproduce the bug, start the shell and type 'abc123' (no ):

```
~/src/rtems $ qemu-system-arm -net none -nographic -M realview-pbx-a9 -m 256M -kernel
build/arm/realview_pbx_a9_qemu/testsuites/libtests/dl10.exe
*** BEGIN OF TEST libdl (RTL) 10 ***
*** TEST VERSION: 6.0.0.d9bdf166644f612dd628fe4951c12c6f8e94ba5f
*** TEST STATE: USER_INPUT
*** TEST BUILD: RTEMS_DEBUG RTEMS_NETWORKING RTEMS_POSIX_API RTEMS_SMP
*** TEST TOOLS: 10.2.1 20200904 \
(RTEMS 6, RSB 31f936a7b74d60bda609a9960c6e1a705ba54974, Newlib a0d7982)
RTL (libdl) commands: dl, rtl
RTEMS Shell on /dev/foobar. Use 'help' to list commands.
SHLL [/] # abc123
```

Then move the cursor onto the '1' by hitting three times the key. Next type -U:

```
SHLL [/] # 123
```

Note that the cursor is at the end of the line (after '3') instead of correctly at the beginning (on the '1'), now. Continuing typing 'echo ' incorrectly results in the output:

```
SHLL [/] # 123echo 123
```

The patch changes this behavior so that the cursor in the second last step will be on the '1' and typing 'echo ' will then correctly reflected as:

```
SHLL [/] # echo 123
```

## Comment 1

1. **Frank Kühndel**, Mon, 28 Sep 2020 12:17:27 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In ffc928b/rtems:

Fixing bug in line editing of the shell with CTRL-U.

This patch fixes a tiny bug in the command line editing of the RTEMS shell. Typing CTRL-U in the shell should remove all characters left of the cursor. After pressing CTRL-U, the current implementation does wrongly place the cursor at the end of the line instead at its beginning.

To reproduce the bug, start the shell and type 'abc123' (no ):

```
~/src/rtems $ qemu-system-arm -net none -nographic -M realview-pbx-a9 \
```

```
-m 256M -kernel build/arm/realview_pbx_a9_qemu/testsuites/libtests/dl10.exe

_* BEGIN OF TEST libdl (RTL) 10 _* _* TEST VERSION: 6.0.0.d9bdf166644f612dd628fe4951c12c6f8e94ba5f _* TEST STATE:
USER_INPUT _* TEST BUILD: RTEMS_DEBUG RTEMS_NETWORKING RTEMS_POSIX_API RTEMS_SMP _* TEST TOOLS: 10.2.1 20200904 \

(RTEMS 6, RSB 31f936a7b74d60bda609a9960c6e1a705ba54974, Newlib a0d7982)

RTL (libdl) commands: dl, rtl

RTEMS Shell on /dev/foobar. Use 'help' to list commands. SHLL / # abc123
```

Then move the cursor onto the '1' by hitting three times the key. Next type -U:

```
SHLL / # 123
```

Note that the cursor is at the end of the line (after '3') instead of correctly at the beginning (on the '1'), now.  
Continuing typing 'echo ' incorrectly results in the output:

```
SHLL / # 123echo 123
```

The patch changes this behavior so that the cursor in the second last step will be on the '1' and typing 'echo ' will then correctly reflected as:

```
SHLL / # echo 123
```

Close #4097.

## 4098 - All BSP bsets fail to build on master

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4098">https://devel.rtems.org/ticket/4098</a> ( <a href="https://devel.rtems.org/ticket/4098">https://devel.rtems.org/ticket/4098</a> )
<b>Id</b>	4098
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	28 September 2020 20:59:40
<b>Modified</b>	16 December 2021 16:50:18
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

On the master building for RTEMS 6, all of the BSP bsets fail like this:

```
RTEMS Source Builder - Set Builder, 6 (ed5030bc24db)
Build Set: 6/bsps/xilinx_zynq_zedboard
error: no build set file found: 6/bsps/xilinx_zynq_zedboard.bset
Mailing report: build@rtems.org
Traceback (most recent call last):
  File "../source-builder/sb-set-builder", line 25, in
    sb.setbuilder.run()
  File "/home/joel/rtems-cron-6/rtems-source-builder/source-builder/sb/setbuilder.py", line 735, in run
    b.build(deps, mail = mail)
  File "/home/joel/rtems-cron-6/rtems-source-builder/source-builder/sb/setbuilder.py", line 633, in build
    if sizes valid:
UnboundLocalError: local variable 'sizes valid' referenced before assignment
```

### Comment 1

1. **Ryan Long**, Thu, 16 Dec 2021 16:50:18 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

## 4100 - arm/edb7312 Build Failure When SMP is Enabled

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4100">https://devel.rtems.org/ticket/4100</a> ( <a href="https://devel.rtems.org/ticket/4100">https://devel.rtems.org/ticket/4100</a> )
<b>Id</b>	4100
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	29 September 2020 17:14:49
<b>Modified</b>	1 October 2020 20:05:57
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

This is from the edb7312 but may apply to others. Build is still underway and this is a common file.

```
'''gmake[4]: Entering directory `/home/joel/rtems-cron-6/b-edb7312/arm-rtems6/c/edb7312/cpukit'
depbase=`echo score/src/percpu.o | sed 's|[^/]*$|.deps/&;s|\.o$||'`;
arm-rtems6-gcc --pipe -DHAVE_CONFIG_H -I. -I/home/joel/rtems-cron-6/b-edb7312/arm-rtems6/c/edb7312/include -I/home/joel/rtems-cron-6/rtems/cpukit/include -I/home/joel/rtems-cron-6/rtems/cpukit/score/cpu/arm/include -mcpu=arm7tdmi -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT score/src/percpu.o -MD -MP -MF $depbase.Tpo -c -o score/src/percpu.o ../../../../../../rtems/c/src/../../../../cpukit/score/src/percpu.c &&\
mv -f $depbase.Tpo $depbase.Po
{standard input}: Assembler messages:
{standard input}:157: Error: selected processor does not support `sev' in ARM mode
{standard input}:347: Error: selected processor does not support `wfe' in ARM mode
{standard input}:525: Error: selected processor does not support `wfe' in ARM mode
gmake[4]: *** [score/src/percpu.o] Error 1
```

**Comment 1**

1. **Joel Sherrill**, Tue, 29 Sep 2020 21:51:16 GMT

I am not going through every failing ARM BSP but the csb337 family also fails similarly.

**Comment 2**

1. **Sebastian Huber**, Wed, 30 Sep 2020 05:51:04 GMT

This BSP doesn't support SMP.

**Comment 3**

1. **Joel Sherrill**, Wed, 30 Sep 2020 12:59:39 GMT

Why are these not configure time failures in waf and not build time failures?

**Comment 4**

1. **Sebastian Huber**, Wed, 30 Sep 2020 13:05:06 GMT

This was also not a configure time error in the old build system I guess. The information if a BSP supports SMP is not explicitly available in the build specification. This information is currently present in the RTEMS Tools: config/rtems-bsps-arm.ini. This can be changed of course.

**Comment 5**

1. **Sebastian Huber**, Thu, 01 Oct 2020 20:05:57 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

Fixed by recent commit.

**4101 - atsamv fails to build on master**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4101">https://devel.rtems.org/ticket/4101</a> ( <a href="https://devel.rtems.org/ticket/4101">https://devel.rtems.org/ticket/4101</a> )
<b>Id</b>	4101
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	29 September 2020 19:45:27
<b>Modified</b>	1 October 2020 20:10:15
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This may also fail on 5.

```
$ ./rtems/configure --target=arm-rtems6 --enable-rtemsbsp=atsamv --prefix=/home/joel/rtems-cron-6/tools/6/bsp-install --disable-networking --enable-posix --enable-smp --disable-multiprocessing --disable-rtems-debug --disable-profiling --enable-tests --enable-cxx --enable-maintainer-mode
```

```
arm-rtems6-gcc --pipe -DHAVE_CONFIG_H -I. -I/home/joel/rtems-cron-6/b-atsamv/arm-rtems6/c/atsamv/include -I/home/joel/rtems-cron-6/rtems/cpukit/include -I/home/joel/rtems-cron-6/rtems/cpukit/score/cpu/arm/include -mthumb -mcpu=cortex-m7 -mfpu=fpv5-d16 -mfloat-abi=hard -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -MT libcsupport/src/error.o -MD -MP -MF $depbasedir/objdir/src/error.o
../../../../../../../../rtems/c/src/../../../../cpukit/libcsupport/src/error.c &&\
mv -f $depbasedir/objdir/src/error.o $depbasedir/objdir/
In file included from /home/joel/rtems-cron-6/rtems/cpukit/include/rtems/score/threaddispatch.h:21,
                 from /home/joel/rtems-cron-6/rtems/cpukit/include/rtems/score/objectimpl.h:29,
                 from /home/joel/rtems-cron-6/rtems/cpukit/include/rtems/score/threadimpl.h:31,
                 from ../../../../../../rtems/c/src/../../../../cpukit/libcsupport/src/error.c:16:
/home/joel/rtems-cron-6/rtems/cpukit/include/rtems/score/percpu.h:439:3: error: unknown type name 'CPU_interrupt_frame'
 439 | CPU_interrupt_frame Interrupt_frame;
      | ^~
      | ~~~~~
```

**Comment 1**

1. **Joel Sherrill**, Tue, 29 Sep 2020 21:53:17 GMT

I am not going through every failing ARM BSP but spot checking shows that this impacts the lpc176x family also.

**Comment 2**

1. **Joel Sherrill**, Tue, 29 Sep 2020 22:03:41 GMT
2. **description:** modified (diff)

**Comment 3**

1. **Sebastian Huber**, Wed, 30 Sep 2020 05:51:40 GMT

These BSPs don't support SMP.

**Comment 4**

1. **Joel Sherrill**, Wed, 30 Sep 2020 12:59:08 GMT

And why is this not a more obvious configure time problem in waf?

I would report the failures against waf but since it uses the same build directory all the time, I can't rebuild those until all the builds fail and it is just now getting to mips.

**Comment 5**

1. **Sebastian Huber**, Thu, 01 Oct 2020 20:08:10 GMT

Fixed by recent commit.

**Comment 6**

1. **Sebastian Huber**, Thu, 01 Oct 2020 20:10:15 GMT
  2. **status:** changed from **new** to **closed**
  3. **resolution:** set to **fixed**
- 

**4103 - BeagleBoard BSPs Fail to Build**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4103">https://devel.rtems.org/ticket/4103</a> ( <a href="https://devel.rtems.org/ticket/4103">https://devel.rtems.org/ticket/4103</a> )
<b>Id</b>	4103
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	29 September 2020 22:03:16
<b>Modified</b>	1 October 2020 20:09:48
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

This may also fail on 5.

```
./rtems/configure --target=arm-rtems6 --enable-rtemsbsp=beagleboardorig --prefix=/home/joel/rtems-cron-6/tools/6/bsp-install --disable-networking --enable-posix --enable-smp --disable-multiprocessing --disable-rtems-debug --disable-profiling --enable-tests --enable-cxx --enable-maintainer-mode
```

```
arm-rtems6-gcc -mcpu=cortex-a8 -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -B./../lib/libbsp/arm/beagle -B/home/joel/rtems-cron-6/rtems/bsps/arm/beagle/start -specs bsp specs -grtems -L./../cpukit -L/home/joel/rtems-cron-6/rtems/bsps/arm/shared/start -Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -Wl,--gc-sections -o base_sp.exe base_sp/base_sp-init.o base_sp/base_sp-apptask.o ./../lib/libbsp/arm/beagle/librtemsbsp.a ./../cpukit/librtemscpu.a ./../cpukit/librtemstest.a /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: ./../cpukit/librtemscpu.a(threadstart.o): in function `Thread_Dispatch_request': /home/joel/rtems-cron-6/rtems/cpukit/include/rtems/score/threaddispatch.h:245: undefined reference to `CPU_SMP_Send_interrupt' /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: ./../cpukit/librtemscpu.a(smp.o): in function `SMP_Handler_initialize': /home/joel/rtems-cron-6/b-beagleboardorig/arm-rtems6/c/beagleboardorig/cpukit/./../rtems/c/src/./../cpukit/score/src/smp.c:135: undefined reference to `CPU_SMP_Initialize' /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: ./../cpukit/librtemscpu.a(smp.o): in function `SMP_Start_processors': /home/joel/rtems-cron-6/b-beagleboardorig/arm-rtems6/c/beagleboardorig/cpukit/./../rtems/c/src/./../cpukit/score/src/smp.c:78: undefined reference to `CPU_SMP_Start_processor' /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: ./../cpukit/librtemscpu.a(smp.o): in function `SMP_Handler_initialize': /home/joel/rtems-cron-6/b-beagleboardorig/arm-rtems6/c/beagleboardorig/cpukit/./../rtems/c/src/./../cpukit/score/src/smp.c:151: undefined reference to `CPU_SMP_Finalize_initialization' /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: /home/joel/rtems-cron-6/b-beagleboardorig/arm-rtems6/c/beagleboardorig/cpukit/./../rtems/c/src/./../cpukit/score/src/smp.c:135: undefined reference to `CPU_SMP_Initialize' /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: ./../cpukit/librtemscpu.a(smp.o): in function `SMP_Send_message': /home/joel/rtems-cron-6/b-beagleboardorig/arm-rtems6/c/beagleboardorig/cpukit/./../rtems/c/src/./../cpukit/score/src/smp.c:221: undefined reference to `CPU_SMP_Send_interrupt' /home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/./../arm-rtems6/bin/ld: ./../cpukit/librtemscpu.a(threadstartmultitasking.o): in function `Thread_Start_multitasking': /home/joel/rtems-cron-6/b-beagleboardorig/arm-rtems6/c/beagleboardorig/cpukit/./../rtems/c/src/./../cpukit/score/src/threadstartmultitasking.c:44: undefined reference to `CPU_SMP_Prepare_start_multitasking' collect2: error: ld returned 1 exit status
gmake[5]: *** [base_sp.exe] Error 1
```

## Comment 1

1. **Chris Johns**, Wed, 30 Sep 2020 03:13:48 GMT

The BBB is a single core SoC and so the SMP option has no meaning.

## Comment 2

1. **Sebastian Huber**, Thu, 01 Oct 2020 20:09:48 GMT

2. **status:** changed from **new** to **closed**

3. **resolution:** set to **fixed**

Fixed by recent commit.

## 4105 - Add RTEMS\_PARTITION\_ALIGNMENT

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4105">https://devel.rtems.org/ticket/4105</a> ( <a href="https://devel.rtems.org/ticket/4105">https://devel.rtems.org/ticket/4105</a> )
<b>Id</b>	4105
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	30 September 2020 11:55:29
<b>Modified</b>	2 September 2021 06:03:19
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The storage area for partitions is usually statically allocated. Add RTEMS\_PARTITION\_ALIGNMENT so that these areas can meet the minimum alignment required by rtems\_partition\_create().

This is related to #4013.

**Comment 1**

1. **Sebastian Huber**, Wed, 07 Oct 2020 06:11:41 GMT

In 97e9728/rtems:

```
rtems: Add RTEMS_PARTITION_ALIGNMENT
Update #4105.
```

**Comment 2**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords: qualification** added

**Comment 3**

1. **Sebastian Huber**, Thu, 02 Sep 2021 06:03:19 GMT
  2. **status:** changed from **assigned** to **closed**
  3. **resolution:** set to **fixed**
- 

**4107 - waf -j24 fails on powerpc/psim -- probable dependency issue**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4107">https://devel.rtems.org/ticket/4107</a> ( <a href="https://devel.rtems.org/ticket/4107">https://devel.rtems.org/ticket/4107</a> )
<b>Id</b>	4107
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 September 2020 19:08:05
<b>Modified</b>	1 October 2020 05:47:05
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

While experimenting with -j options since waf defaults to fewer jobs than I have been using with make, I tripped across this failure on powerpc/psim which I assume is a missing dependency somewhere:

```

[1561/4127] Linking build/powerpc/psim/testsuites/fstests/fsjffs2gc01.exe
[1562/4127] Linking build/powerpc/psim/testsuites/fstests/fsclose01.exe
[1563/4127] Linking build/powerpc/psim/libdebugger.a
[1564/4127] Linking build/powerpc/psim/libz.a
[1565/4127] Compiling testsuites/fstests/fslink/test.c
/home/joel/rtems-work/tools/6/lib/gcc/powerpc-rtems6/10.2.1/../../../../powerpc-rtems6/bin/ld: cannot find -ljffs2
collect2: error: ld returned 1 exit status
../../../../testsuites/fstests/fsdosfsname01/init.c: In function 'test_creating_invalid_directories':
../../../../testsuites/fstests/fsdosfsname01/init.c:430:19: warning: '%s' directive output may be truncated writing up to 6424 bytes
into a region of size 257 [-Wformat-truncation=]
  430 |         "%s/%s",
      |         ^~
../../../../testsuites/fstests/fsdosfsname01/init.c:428:5: note: 'sprintf' output between 6 and 6430 bytes into a destination of size
262
  428 |         sprintf( dirname,
      |         ^~~~~~
  429 |                 sizeof( dirname ),
      |                 ~~~~~~
  430 |                 "%s/%s",
      |                 ~~~~~~
  431 |                 MOUNT_DIR,
      |                 ~~~~~~
  432 |                 DIRECTORY_NAMES_INVALID[index] );
      |                 ~~~~~~
../../../../cpukit/mghttpd/mongoose.c: In function 'handle_request':
../../../../cpukit/mghttpd/mongoose.c:1919:45: warning: '.gz' directive output may be truncated writing 3 bytes into a region of size
between 1 and 255 [-Wformat-truncation=]
 1919 |         sprintf(gz_path, sizeof(gz_path), "%s.gz", buf);
      |         ^~~~~
../../../../cpukit/mghttpd/mongoose.c:1919:7: note: 'sprintf' output between 4 and 258 bytes into a destination of size 255
 1919 |         sprintf(gz_path, sizeof(gz_path), "%s.gz", buf);
      |         ^~~~~
Waf: Leaving directory `/home/joel/rtems-work/rtems/build/powerpc/psim'
Build failed
-> task in 'testsuites/fstests/fsjffs2gc01.exe' failed with exit status 1 (run with -v to display more information)

```

INI file was:

```

[powerpc/psim]
# Selects the compiler used to build the BSP (allowed values are "gcc" and
# "clang"). Please note that the values of some options depend on the compiler
# selection and changing the compiler may lead to unpredictable behaviour if
# these options are not adjusted as well. Use the --rtems-compiler command line
# option to get the default values for a particular compiler via
# ./waf bsp_defaults.
COMPILER = gcc
# Flags passed to the library archiver
ARFLAGS = crD
# Warning flags passed to the C and C++ compiler
WARNING_FLAGS = -Wall
# Warning flags passed to the C compiler
CC_WARNING_FLAGS = -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs
# Warning flags passed to the C++ compiler
CXX_WARNING_FLAGS =
# Enable the Ada support
RTEMS_ADA__ = False
# Enable the RTEMS internal debug support
RTEMS_DEBUG = False
# Enable the Driver Manager startup
RTEMS_DRVMgr_STARTUP = False
# Enable the message passing based multiprocessing support (MPCI); do
# not confuse this with the SMP support
RTEMS_MULTIPROCESSING = False
# Enable the legacy TCP/IP network support
RTEMS_NETWORKING = False
# Enable the Newlib C library support
RTEMS_NEWLIB = True
# Enable the para-virtualization support
RTEMS_PARAVIRT = False
# Enable support for POSIX signals
RTEMS_POSIX_API = True
# Enable the SMP lock profiling support
RTEMS_PROFILING = False
# Enable the Symmetric Multiprocessing (SMP) support
RTEMS_SMP = False
# Build the Ada test programs (may be also enabled by BUILD_TESTS)
BUILD_ADATESTS = False
# Build the test programs
BUILD_TESTS = True
# Build the benchmark programs (may be also enabled by BUILD_TESTS)
BUILD_BENCHMARKS = False
# Build the file system test programs (may be also enabled by
# BUILD_TESTS)
BUILD_FSTESTS = False
# Build the library test programs (may be also enabled by BUILD_TESTS)
BUILD_LIBTESTS = False
# Build the MPCI test programs (may be also enabled by BUILD_TESTS)
BUILD_MPTESTS = False
# Build the POSIX test programs (may be also enabled by BUILD_TESTS)
BUILD_PXTESTS = False
# Build the POSIX timing test programs (may be also enabled by
# BUILD_TESTS)
BUILD_PXMTTESTS = False
# Build the Rheelstone benchmark programs (may be also enabled by
# BUILD_TESTS)
BUILD_RHEALSTONE = False
# Build the sample programs (may be also enabled by BUILD_TESTS)
BUILD_SAMPLES = True
# Build the SMP test programs (may be also enabled by BUILD_TESTS)
BUILD_SMPTESTS = False
# Build the single-processor test programs (may be also enabled by
# BUILD_TESTS)
BUILD_SPTTESTS = False
# Build the timing test programs (may be also enabled by BUILD_TESTS)
BUILD_TMTESTS = False
# Build the validation test programs (may be also enabled by
# BUILD_TESTS)
BUILD_VALIDATIONTESTS = False
# Optimization flags passed to the C and C++ compiler
OPTIMIZATION_FLAGS = -O2 -g -fdata-sections -ffunction-sections
# ABI flags
ABI_FLAGS = -Dppc603e -meabi -mcpu=603e -msdata=sysv
# This sets a mode where the time runs as fast as possible when a
# clock ISR occurs while the IDLE thread is executing. This can
# significantly reduce simulation times.
CLOCK_DRIVER_USE_FAST_IDLE = True
# If defined then the BSP may reduce the available memory size
# initially. This can be useful for debugging (reduce the core size)
# or dynamic loading (std gcc text offsets/jumps are < +/-32M). Note
# that the policy can still be defined by the application (see sbrk.c,
# BSP_sbrk_policy). By undefining CONFIGURE_MALLOC_BSP_SUPPORTS_SBRK
# this feature is removed and a little memory is saved.
CONFIGURE_MALLOC_BSP_SUPPORTS_SBRK = True
# If defined, then the PowerPC specific code in RTEMS will use some of
# the special purpose registers to slightly optimize interrupt
# response time. The use of these registers can conflict with other
# tools like debuggers.
PPC_USE_SPRG = False
# This defines the base address of the exception table. NOTE: Vectors
# are actually at 0xFFFF0000 but file starts at offset.
PPC_VECTOR_FILE_BASE = 0xffff0100
# If defined to a non-zero value, prints the some information in case
# of a fatal error.
BSP_VERBOSE_FATAL_EXTENSION = 1
# Flags passed to the linker (GNU ld)
LDFLAGS = -Wl,--gc-sections
# Install the legacy application Makefile framework.
INSTALL_LEGACY_MAKEFILES = True
# If defined to a non-zero value, prints the exception context when an
# unexpected exception occurs.
BSP_PRINT_EXCEPTION_CONTEXT = 1
# If defined to a non-zero value, reset the board when the application
# exits.
BSP_RESET_BOARD_AT_EXIT = 1
# If defined to a non-zero value, print a message and wait until
# pressed before resetting board when application exits.
BSP_PRESS_KEY_FOR_RESET = 0

```

**Comment 1**

1. Joel Sherrill, Wed, 30 Sep 2020 19:08:19 GMT
2. owner: set to Sebastian Huber

3. **status:** changed from **new** to **assigned**

#### Comment 2

1. **Sebastian Huber**, Thu, 01 Oct 2020 05:39:30 GMT

In 9628dfd/rtems-docs:

```
eng: Clarify stlib build attribute
Update #4107.
```

#### Comment 3

1. **Sebastian Huber**, Thu, 01 Oct 2020 05:47:05 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 16b29af2/rtems:

```
build: Fix build dependencies of JFFS2 tests
Close #4107.
```

---

## **4108 - Review minimum and ensure it really is a minimum configuration**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4108">https://devel.rtems.org/ticket/4108</a> ( <a href="https://devel.rtems.org/ticket/4108">https://devel.rtems.org/ticket/4108</a> )
<b>Id</b>	4108
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	1 October 2020 16:25:45
<b>Modified</b>	8 September 2022 14:29:37
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

Does minimum actually reflect what you think is the smallest possible configuration now? That as always the test's purpose -- to have a single that was the smallest we thought we could produce. It seems all your changes that it needs a review for tweaks to the configuration.

Inspecting the size of this test should tell you the smallest executable possible on this BSP with the current configuration settings.

There is a version in rtems-examples/misc which will either need to be synchronized or deleted.

This needs to be checked on 5 and 6.

#### Comment 1

1. **Joel Sherrill**, Thu, 01 Oct 2020 16:25:56 GMT
2. **owner:** changed from **joel@...** to **Sebastian Huber**
3. **status:** changed from **new** to **assigned**

#### Comment 2

1. **Sebastian Huber**, Thu, 01 Oct 2020 17:08:50 GMT
2. **version:** changed from **5** to **6**
3. **milestone:** changed from **5.2** to **6.1**

#### Comment 3

1. **Sebastian Huber**, Thu, 08 Sep 2022 14:29:37 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 120c857e/rtems:

minimum: Do not use unified work areas

The CONFIGURE\_UNIFIED\_WORK\_AREAS option pulls in a system initialization handler which initializes the unified heap.

Close #4108.

---

## 4110 - Ubuntu package list is broken

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4110">https://devel.rtems.org/ticket/4110</a> ( <a href="https://devel.rtems.org/ticket/4110">https://devel.rtems.org/ticket/4110</a> )
<b>Id</b>	4110
<b>Reporter</b>	Chris Johns
<b>Created</b>	2 October 2020 02:33:59
<b>Modified</b>	22 December 2021 15:28:57
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The list found here:

<https://docs.rtems.org/branches/master/user/hosts/posix.html#xubuntu>

failed with libpython-dev. A Linux user needs to check this and update the list.

### Comment 1

1. **Chris Johns**, Fri, 02 Oct 2020 02:39:02 GMT

I suggest adding:

```
sudo apt-get install python3-venv
python3 -m venv py
./py/bin/activate
```

because there is no python command

### Comment 2

1. **Ryan Long**, Wed, 22 Dec 2021 15:28:57 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 4e22dfe/rtems-docs:

Update package list for Ubuntu

Updated the latest version referenced of Ubuntu to 20.04, updated package list, and identified what packages need to still be installed afterwards to pass sb-check.

Closes #4110

---

## 4115 - Cortex-A9 MPCore based BSPs should include the workaround for Errata 794072 and 845369

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4115">https://devel.rtems.org/ticket/4115</a> ( <a href="https://devel.rtems.org/ticket/4115">https://devel.rtems.org/ticket/4115</a> )
<b>Id</b>	4115
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 October 2020 09:37:01
<b>Modified</b>	16 October 2020 04:39:17
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4114:

The workaround may be already set up by the bootloader. Not having the workaround applied may lead to system crashes, so make sure the BSP does it during system startup.

**Comment 1**

1. **Sebastian Huber**, Fri, 02 Oct 2020 09:37:11 GMT
2. **owner:** set to **Sebastian Huber**
3. **status:** changed from **new** to **assigned**

**Comment 2**

1. **Sebastian Huber**, Mon, 05 Oct 2020 06:47:22 GMT
2. **description:** modified (diff)
3. **summary:** changed from **Cortex-A9 MPCore based BSPs should include the workaround for Errata 845369 (cloned)** to **Cortex-A9 MPCore based BSPs should include the workaround for Errata 794072 and 845369**

**Comment 3**

1. **Sebastian Huber**, Fri, 16 Oct 2020 04:39:13 GMT

In e7b878e/rtems:

```
bsps/arm: Workaround for Errata 845369
Add a workaround for Cortex-A9 Errata 845369: Under Very Rare Timing Circumstances Transition into Streaming Mode Might Create Data Corruption.
Update #4115.
```

**Comment 4**

1. **Sebastian Huber**, Fri, 16 Oct 2020 04:39:17 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In cf16821/rtems:

```
bsps/arm: Add workaround for Errata 794072
Add a workaround for Cortex-A9 Errata 845369: A short loop including a DMB instruction might cause a denial of service on another which executes a CP15 broadcast operation.
Close #4115.
```

**4116 - raspberrypi fails to build on waf and autoconf**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4116">https://devel.rtems.org/ticket/4116</a> ( <a href="https://devel.rtems.org/ticket/4116">https://devel.rtems.org/ticket/4116</a> )
<b>Id</b>	4116
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	2 October 2020 14:15:32
<b>Modified</b>	7 October 2020 05:45:58
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

This may apply to 5 as well but I didn't check.

The following configurations for pi didn't build:

```

FAILED (2) autoconf build of arm raspberrypi (SMP/NOMP/DEBUG/PROFILE)
FAILED (1) waf build of arm raspberrypi (SMP/NOMP/DEBUG/PROFILE)
FAILED (2) autoconf build of arm raspberrypi (SMP/NOMP/DEBUG/NOPROFILE)
FAILED (1) waf build of arm raspberrypi (SMP/NOMP/DEBUG/NOPROFILE)
FAILED (2) autoconf build of arm raspberrypi (SMP/NOMP/NODEBUG/PROFILE)
FAILED (1) waf build of arm raspberrypi (SMP/NOMP/NODEBUG/PROFILE)
FAILED (2) autoconf build of arm raspberrypi (SMP/NOMP/NODEBUG/NOPROFILE)
FAILED (1) waf build of arm raspberrypi (SMP/NOMP/NODEBUG/NOPROFILE)

```

This one of the configure commands:

```

../rtems/configure --target=arm-rtems6 --enable-rtemsbsp=raspberrypi --prefix=/home/joel/rtems-cron-6/tools/6/bsp-install --
disable-networking --enable-posix --enable-smp --disable-multiprocessing --enable-rtems-debug --enable-profiling --enable-tests --
enable-cxx --enable-maintainer-mode

```

And this is the failure:

```

gmake[4]: Entering directory `/home/joel/rtems-cron-6/b-raspberrypi/arm-rtems6/c/raspberrypi/cpukit'
$depbase=$echo score/cpu/arm/cpu_asm.o | sed 's|[^/]*$|.deps/&|;s|\.o$||';\
arm-rtems6-gcc --pipe -DHAVE_CONFIG_H -I. -I/home/joel/rtems-cron-6/b-raspberrypi/arm-rtems6/c/raspberrypi/include -
I/home/joel/rtems-cron-6/rtems/cpukit/include -I/home/joel/rtems-cron-6/rtems/cpukit/score/cpu/arm/include -DASM -mcpu=arm1176jzf-
s -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -
Wnested-externs -mcpu=arm1176jzf-s -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-
declaration -Wstrict-prototypes -Wnested-externs -MT score/cpu/arm/cpu_asm.o -MD -MP -MF $depbase.Tpo -c -o score/cpu/arm/cpu_asm.o
../../../../../../../../rtems/c/src/../../../../cpukit/score/cpu/arm/cpu_asm.S &&\
mv -f $depbase.Tpo $depbase.Po
../../../../../../../../rtems/c/src/../../../../cpukit/score/cpu/arm/cpu_asm.S: Assembler messages:
../../../../../../../../rtems/c/src/../../../../cpukit/score/cpu/arm/cpu_asm.S:75: Error: selected processor does not support `dmb' in ARM mode
../../../../../../../../rtems/c/src/../../../../cpukit/score/cpu/arm/cpu_asm.S:93: Error: selected processor does not support `dmb' in ARM mode
gmake[4]: *** [score/cpu/arm/cpu_asm.o] Error 1

```

### Comment 1

1. **Joel Sherrill**, Tue, 06 Oct 2020 22:22:02 GMT
2. **keywords:** wafblocker added

Confirming this still fails in all autoconf and waf builds with SMP enabled.

### Comment 2

1. **Joel Sherrill**, Tue, 06 Oct 2020 22:22:13 GMT
2. **owner:** set to **Sebastian Huber**
3. **status:** changed from **new** to **assigned**

### Comment 3

1. **Sebastian Huber**, Wed, 07 Oct 2020 05:45:58 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In ca9b2e3/rtems:

```

build: Remove raspberrypi from RTEMS_SMP
Close #4116.

```

## 4117 - lpc1768\_mbed\_ahb\_ram\_eth sp01 and others fail to link



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4117">https://devel.rtems.org/ticket/4117</a> ( <a href="https://devel.rtems.org/ticket/4117">https://devel.rtems.org/ticket/4117</a> )
<b>Id</b>	4117
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	2 October 2020 15:50:32
<b>Modified</b>	5 October 2020 17:34:48
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

This fails on both waf and autoconf. This is troubling because the test is sp01 which should build and link.

Did not check if this also applies to 5 branch.

```
../rtems/configure --target=arm-rtems6 --enable-rtemsbsp=lpc1768 mbed_ahb_ram_eth --prefix=/home/joel/rtems-cron-6/tools/6/bsp-
install --disable-networking --enable-posix --disable-smp --disable-multiprocessing --disable-rtems-debug --disable-profiling --
enable-tests --enable-cxx --enable-maintainer-mode
```

Fails with:

```
arm-rtems6-gcc -mthumb -mcpu=cortex-m3 -O2 -ggdb3 -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-
function-declaration -Wstrict-prototypes -Wnested-externs -B../../../../lib/libbsp/arm/lpc176x -B/home/joel/rtems-cron-
6/rtems/bsps/arm/lpc176x/start -specs bsp_specs -qrtems -L../../../../cpukit -L/home/joel/rtems-cron-6/rtems/bsps/arm/shared/start -
Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -Wl,--gc-sections -o sp01.exe sp01/sp01-init.o sp01/sp01-task1.o
../../../../lib/libbsp/arm/lpc176x/librtemsbsp.a ../../../../../../cpukit/librtemscpu.a ../../../../../../cpukit/librtemstest.a
/home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/../../../../arm-rtems6/bin/ld: sp01.exe section `.bss' will not fit in
region `RAM_AHB1'
/home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/../../../../arm-rtems6/bin/ld: region `RAM_AHB1' overflowed by 2324 bytes
collect2: error: ld returned 1 exit status
gmake[5]: *** [sp01.exe] Error 1
```

### Comment 1

1. **Joel Sherrill**, Fri, 02 Oct 2020 15:50:49 GMT
2. **owner:** set to **Sebastian Huber**
3. **status:** changed from **new** to **assigned**

### Comment 2

1. **Sebastian Huber**, Fri, 02 Oct 2020 15:52:59 GMT

Are you sure it fails with waf?

```
spec/build/bsps/arm/lpc176x/tstlpc1768mbedahbrameth.yml: sp01: exclude
```

### Comment 3

1. **Joel Sherrill**, Fri, 02 Oct 2020 16:39:29 GMT

Because waf uses the same build tree, I can't reproduce the waf build until the complete sweep finishes. It is a lost feature not to have the ability to have the build tree vary from build to build. :(

Anyway, this is what I have in the build log. Maybe you can reproduce more:

```
grep FAILED all-bsps-log.txt | grep lpc1768_mbed_ahb_ram_eth
FAILED (2) autoconf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/DEBUG/PROFILE)
FAILED (1) waf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/DEBUG/PROFILE)
FAILED (2) autoconf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/DEBUG/NOPROFILE)
FAILED (1) waf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/DEBUG/NOPROFILE)
FAILED (2) autoconf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/NODEBUG/PROFILE)
FAILED (1) waf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/NODEBUG/PROFILE)
FAILED (2) autoconf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/NODEBUG/NOPROFILE)
FAILED (1) waf build of arm lpc1768_mbed_ahb_ram_eth (NOSMP/NOMP/NODEBUG/NOPROFILE)
```

Please go ahead and add sp01 to the tcfg so the builds can get closer to matching. There was also at least one other test that didn't fit into the memory. We must achieve parity before the switchover. Minor issues must be addressed in the autoconf side. Major ones we will work around (like the smp/mp option).

### Comment 4

1. **Sebastian Huber**, Mon, 05 Oct 2020 17:34:48 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In a9995f1/rtems:

```
bsp/lpc176x: Fix memory map
```

Due to the static allocation of operating system resources the .bss section needs more space than the .work section.

Close #4117.

## 4118 - Add clang variants for sparc BSPs

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4118">https://devel.rtems.org/ticket/4118</a> ( <a href="https://devel.rtems.org/ticket/4118">https://devel.rtems.org/ticket/4118</a> )
<b>Id</b>	4118
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	2 October 2020 15:53:11
<b>Modified</b>	2 October 2020 15:55:17
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

There are clang variants for RISV-V BSPs but not SPARC BSPs even though clang is supported on them.

If there are other architectures with clang support, I don't know.

### Comment 1

1. **Sebastian Huber**, Fri, 02 Oct 2020 15:55:17 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**

There is no need to add clang BSPs. The new build system has an option to select the compiler.

## 4120 - altcycv\_devkit and imx7 fail to build all tests on master

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4120">https://devel.rtems.org/ticket/4120</a> ( <a href="https://devel.rtems.org/ticket/4120">https://devel.rtems.org/ticket/4120</a> )
<b>Id</b>	4120
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	3 October 2020 21:40:21
<b>Modified</b>	5 October 2020 10:01:00
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

This appears to not happen with waf but it needs to be resolved or we don't have parity to achieve a switchover.

Happens to at least two BSPs. Not sure if more until all arm BSP configurations finish.

Configuration:

```
./rtems/configure --target=arm-rtems6 --enable-rtemsbsp=altcycv_devkit --prefix=/home/joel/rtems-cron-6/tools/6/bsp-install --
disable-networking --enable-posix --enable-smp --disable-multiprocessing --enable-rtems-debug --enable-profiling --enable-tests --
enable-cxx --enable-maintainer-mode
```

Results in:

```

arm-rtems6-gcc -DHAVE_CONFIG_H -I. -I../../../../../../../../rtems/c/src/../../../../testsuites/smptests -I. -I/home/joel/rtems-cron-6/b-
altcy cv devkit/arm-rtems6/c/altcy cv devkit/include -I/home/joel/rtems-cron-6/rtems/cpukit/include -I/home/joel/rtems-cron-
6/rtems/cpukit/score/cpu/arm/include -I/home/joel/rtems-cron-6/b-altcy cv devkit/arm-rtems6/c/altcy cv devkit/lib/libbsp/arm/altera-
cyclone-v/include -I/home/joel/rtems-cron-6/rtems/bsps/include -I/home/joel/rtems-cron-6/rtems/bsps/arm/include -I/home/joel/rtems-
cron-6/rtems/bsps/arm/altera-cyclone-v/include -DT FILE_NAME="init.c" -
I../../../../../../../../rtems/c/src/../../../../testsuites/smptests/./support/include -march=armv7-a -mthumb -mfpu=neon -mfloat-abi=hard -
mtune=cortex-a9 -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-
prototypes -Wnested-externs -MT smpmulticast01/smpmulticast01-init.o -MD -MP -MF smpmulticast01/.deps/smpmulticast01-init.Tpo -c -o
smpmulticast01/smpmulticast01-init.o `test -f 'smpmulticast01/init.c' || echo
'../../../../../../../../rtems/c/src/../../../../testsuites/smptests/'`smpmulticast01/init.c
../../../../../../../../rtems/c/src/../../../../testsuites/smptests/smpmulticast01/init.c:37:10: fatal error: rtems/testopts.h: No such file or
directory
   37 | #include
      | ^~~~~~
compilation terminated.
gmake[5]: *** [smpmulticast01/smpmulticast01-init.o] Error 1

```

**Comment 1**

1. **Joel Sherrill**, Sat, 03 Oct 2020 21:46:42 GMT
2. **description:** modified (diff)
3. **summary:** changed from `altcy cv devkit famils to build all tests on master` to `altcy cv devkit and imx7 fail to build all tests on master`

**Comment 2**

1. **Sebastian Huber**, Mon, 05 Oct 2020 10:01:00 GMT
2. **status:** changed from `assigned` to `closed`
3. **resolution:** set to `fixed`

In 2c367617/rtems:

build: Add testopts.h to configure script

Close #4120.

**4121 - Im3s3749 fails to build all tests on master**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4121">https://devel.rtems.org/ticket/4121</a> ( <a href="https://devel.rtems.org/ticket/4121">https://devel.rtems.org/ticket/4121</a> )
<b>Id</b>	4121
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	4 October 2020 01:24:57
<b>Modified</b>	5 October 2020 17:34:51
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

FAILED (2) autoconf build of arm Im3s3749 (NOSMP/NOMP/DEBUG/PROFILE)  
 FAILED (1) waf build of arm Im3s3749 (NOSMP/NOMP/DEBUG/PROFILE)  
 FAILED (2) autoconf build of arm Im3s3749 (NOSMP/NOMP/DEBUG/NOPROFILE)  
 FAILED (1) waf build of arm Im3s3749 (NOSMP/NOMP/DEBUG/NOPROFILE)

```

../../../../rtems/configure --target=arm-rtems6 --enable-rtemsbsp=lm3s3749 OPERATION COUNT=10 --prefix=/home/joel/rtems-cron-6/tools/6/bsp-
install --disable-networking --enable-posix --disable-smp --disable-multiprocessing --enable-rtems-debug --enable-profiling --
enable-tests --enable-cxx --enable-maintainer-mode

```

```

arm-rtems6-gcc -mthumb -mcpu=cortex-m3 -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-
declaration -Wstrict-prototypes -Wnested-externs -B../../../../lib/libbsp/arm/lm3s69xx -B/home/joel/rtems-cron-
6/rtems/bsps/arm/lm3s69xx/start -specs bsp_specs -qrtems -L../../../../cpukit -L/home/joel/rtems-cron-6/rtems/bsps/arm/shared/start -
Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -Wl,--gc-sections -o math.exe math/math-init.o math/math-domath.o -lm
../../../../lib/libbsp/arm/lm3s69xx/librtemsbsp.a ../../cpukit/librtemsbsp.a ../../cpukit/librtemstest.a
/home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/../../../../arm-rtems6/bin/ld: math.exe section `.rodata' will not fit in
region `ROM INT'
/home/joel/rtems-cron-6/tools/6/lib/gcc/arm-rtems6/10.2.1/../../../../arm-rtems6/bin/ld: region `ROM INT' overflowed by 2872 bytes

```

**Comment 1**

1. **Sebastian Huber**, Mon, 05 Oct 2020 17:34:51 GMT
2. **status:** changed from `assigned` to `closed`
3. **resolution:** set to `fixed`

In 83278070/rtems:

build: Add test excludes for RTEMS\_DEBUG  
Close #4121.

## 4122 - Change RTEMS\_NO\_RETURN to use C11 and C++11 standard means

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4122">https://devel.rtems.org/ticket/4122</a> ( <a href="https://devel.rtems.org/ticket/4122">https://devel.rtems.org/ticket/4122</a> )
<b>Id</b>	4122
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	6 October 2020 06:04:45
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

C11 has a `_Noreturn` keyword and C++11 has a `noreturn?` attribute. The standards are a bit less flexible than the GNU attribute with respect to the position of the attribute.

### Comment 1

1. **Sebastian Huber**, Sat, 10 Oct 2020 12:01:39 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In d7a48e1/rtems:

```
rtems: Improve RTEMS_NO_RETURN attribute
Provide RTEMS_NO_RETURN also in case RTEMS_DEBUG is defined to prevent errors like this:
error: no return statement in function returning non-void [-Werror=return-type]
Use C11 and C++11 standard means to declare a no-return function.
Close #4122.
```

### Comment 2

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** **qualification** added

## 4123 - rtems-bsps needs to be switched to look at waf info for BSPs

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4123">https://devel.rtems.org/ticket/4123</a> ( <a href="https://devel.rtems.org/ticket/4123">https://devel.rtems.org/ticket/4123</a> )
<b>Id</b>	4123
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	6 October 2020 18:06:02
<b>Modified</b>	5 November 2020 20:16:18
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

rtems-bsps depends on autoconf. It must be fixed to depend on waf BSP configuration information before we can switch from autoconf.

#### Comment 1

1. **Chris Johns**, Wed, 07 Oct 2020 00:19:24 GMT

The rtems-bsps command needs to have some python code to read the spec YAML files. This is currently in the wscript along with the generated pickle data optimisation. I would like to have a common piece of python code in the spec directory rtems-bsps and wscript can share so the generated data can be shared.

The rtems-bsps code needs to use the same pickled data waf uses. Without this rtems-bsps would suffer the same performance issues waf had early in it's development that lead to the generation solution. Invoking rtems-bsps may result in the same regeneration message waf produces but that is OK.

A common python module for wscript and rtems-bsps follows the model used in the spec data where something is defined once and reused. I believe there is code in rtems-central that could be exported (copied into rtems.git) and used but I have not looked into this. The exporting could be handled in a similar way to the generation procedures in place for documentation and headers.

#### Comment 2

1. **Sebastian Huber**, Thu, 05 Nov 2020 20:16:18 GMT
2. **owner:** set to **Sebastian Huber** <sebastian.huber@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 4cd885c/rtems:

```
rtems-bsps: Use build specification items
Close #4123.
```

---

## **4124 - rtems-bsp-builder needs to be switched to waf builds**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4124">https://devel.rtems.org/ticket/4124</a> ( <a href="https://devel.rtems.org/ticket/4124">https://devel.rtems.org/ticket/4124</a> )
<b>Id</b>	4124
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	6 October 2020 18:06:59
<b>Modified</b>	25 May 2021 17:41:39
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

rtems-bsp-tester depends on autoconf. It must be fixed to depend on waf BSP configuration information before we can switch from autoconf.

#### Comment 1

1. **Chris Johns**, Wed, 07 Oct 2020 00:21:02 GMT

Do you mean rtems-bsp-builder?

#### Comment 2

1. **Joel Sherrill**, Tue, 18 May 2021 14:19:30 GMT
2. **summary:** changed from **rtems-bsp-tester needs to be switched to waf builds** to **rtems-bsp-builder needs to be switched to waf builds**

#### Comment 3

1. **Ryan Long**, Tue, 25 May 2021 17:41:39 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 527848d/rtems-tools:

rtems-bsp-builder: Change to waf build system

Closes #4124

## 4125 - Update wiki pages to reference waf not autoconf based build

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4125">https://devel.rtems.org/ticket/4125</a> ( <a href="https://devel.rtems.org/ticket/4125">https://devel.rtems.org/ticket/4125</a> )
<b>Id</b>	4125
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	6 October 2020 18:27:32
<b>Modified</b>	29 November 2022 23:23:25
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Since configure is a horrible thing to search for, I searched for "enable-rtems" in the wiki. The results are <https://devel.rtems.org/search?q=enable-rtems&noquickjump=1&wiki=on> and show about 20 pages that need review.

Some may be ok since they are historical on GSoC projects but others will need updating. Some are BSP pages which really should be converted to the Users Guide and updated.

We have an ongoing effort to reduce the wiki and some of these pages may be good candidates. Let's use this as an excuse to do some clean up.

### Comment 1

1. **Joel Sherrill**, Tue, 06 Oct 2020 18:27:51 GMT
2. **summary:** changed from **Update wiki to reference waf** to **Update wiki pages to reference waf not autoconf based build**

### Comment 2

1. **Sebastian Huber**, Mon, 02 Nov 2020 18:48:43 GMT

I don't think this is a blocker to remove the old build system. The user manual is the source of reference.

### Comment 3

1. **Chris Johns**, Tue, 29 Nov 2022 23:23:25 GMT
  2. **owner:** set to **Joel Sherrill**
  3. **status:** changed from **new** to **assigned**
- 

## 4126 - Remove legacy networking stack from rtems.git and place in a new repo

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4126">https://devel.rtems.org/ticket/4126</a> ( <a href="https://devel.rtems.org/ticket/4126">https://devel.rtems.org/ticket/4126</a> )
<b>Id</b>	4126
<b>Reporter</b>	Chris Johns
<b>Created</b>	6 October 2020 23:58:25
<b>Modified</b>	16 December 2021 15:36:46
<b>Owner</b>	
<b>Type</b>	task
<b>Component</b>	network/legacy
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Remove the legacy networking stack from rtems.git and place it in new top level repo rtems-legacy-network.git.

The initial tasks are:

- Move the code to a new repo
- Add rtems\_waf support to build it
- Clean out BSP references to network interfaces or drivers
- Merge in the network demos repo

#### Comment 1

1. **Chris Johns**, Wed, 07 Oct 2020 00:08:03 GMT
2. **description:** modified (diff)

#### Comment 2

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:36:46 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

Already done.

## 4127 - x86\_64/amd64 fails to build

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4127">https://devel.rtems.org/ticket/4127</a> ( <a href="https://devel.rtems.org/ticket/4127">https://devel.rtems.org/ticket/4127</a> )
<b>Id</b>	4127
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 October 2020 13:36:06
<b>Modified</b>	10 October 2020 12:02:52
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

This is with waf and autoconf on master.

Short versions of failing configurations:

```
FAILED (2) autoconf build of x86_64 amd64 (NOSMP/NOMP/DEBUG/PROFILE)
FAILED (1) waf build of x86_64 amd64 (NOSMP/NOMP/DEBUG/PROFILE)
FAILED (2) autoconf build of x86_64 amd64 (NOSMP/NOMP/DEBUG/NOPROFILE)
FAILED (1) waf build of x86_64 amd64 (NOSMP/NOMP/DEBUG/NOPROFILE)
```

This is the error:

```
In file included from ../../../../testsuites/libtests/termios11/init.c:2:
../../../../testsuites/libtests/termios11/./termios10/termios10impl.h: In function 'POSIX_Init':
../../../../testsuites/libtests/termios11/./termios10/termios10impl.h:171:1: error: no return statement in function returning non-void [-Werror=return-type]
  171 | }
      | ^
ccl: some warnings being treated as errors
In file included from ../../../../testsuites/libtests/termios10/init.c:1:
../../../../testsuites/libtests/termios10/termios10impl.h: In function 'POSIX_Init':
../../../../testsuites/libtests/termios10/termios10impl.h:171:1: error: no return statement in function returning non-void [-Werror=return-type]
  171 | }
      | ^
```

This is the waf ini file for this specific build:

```

[x86_64/amd64]
# Selects the compiler used to build the BSP (allowed values are "gcc" and
# "clang"). Please note that the values of some options depend on the compiler
# selection and changing the compiler may lead to unpredictable behaviour if
# these options are not adjusted as well. Use the --rtems-compiler command line
# option to get the default values for a particular compiler via
# ./waf bsp_defaults.
COMPILER = gcc
# Flags passed to the library archiver
ARFLAGS = crD
# Warning flags passed to the C and C++ compiler
WARNING_FLAGS = -Wall
# Warning flags passed to the C compiler
CC_WARNING_FLAGS = -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs
# Warning flags passed to the C++ compiler
CXX_WARNING_FLAGS =
# Enable the Ada support
RTEMS_ADA__ = False
# Enable the RTEMS internal debug support
RTEMS_DEBUG = True
# Enable the Driver Manager startup
RTEMS_DRVMgr_STARTUP = False
# Enable the legacy TCP/IP network support
RTEMS_NETWORKING = False
# Enable the Newlib C library support
RTEMS_NEWLIB = True
# Enable the para-virtualization support
RTEMS_PARAVIRT = False
# Enable support for POSIX signals
RTEMS_POSIX_API = True
# Enable the SMP lock profiling support
RTEMS_PROFILING = False
# Build the Ada test programs (may be also enabled by BUILD_TESTS)
BUILD_ADATESTS = False
# Build the test programs
BUILD_TESTS = True
# Build the benchmark programs (may be also enabled by BUILD_TESTS)
BUILD_BENCHMARKS = False
# Build the file system test programs (may be also enabled by
# BUILD_TESTS)
BUILD_FSTESTS = False
# Build the library test programs (may be also enabled by BUILD_TESTS)
BUILD_LIBTESTS = False
# Build the MPCIC test programs (may be also enabled by BUILD_TESTS)
BUILD_MPTESTS = False
# Build the POSIX test programs (may be also enabled by BUILD_TESTS)
BUILD_PXTESTS = False
# Build the POSIX timing test programs (may be also enabled by
# BUILD_TESTS)
BUILD_PXMTTESTS = False
# Build the Rheelstone benchmark programs (may be also enabled by
# BUILD_TESTS)
BUILD_RHEALSTONE = False
# Build the sample programs (may be also enabled by BUILD_TESTS)
BUILD_SAMPLES = True
# Build the SMP test programs (may be also enabled by BUILD_TESTS)
BUILD_SMPTESTS = False
# Build the single-processor test programs (may be also enabled by
# BUILD_TESTS)
BUILD_SPTTESTS = False
# Build the timing test programs (may be also enabled by BUILD_TESTS)
BUILD_TMTESTS = False
# Build the validation test programs (may be also enabled by
# BUILD_TESTS)
BUILD_VALIDATIONTESTS = False
# Sets the test verbosity of the RTEMS Test Framework. Valid values
# are "Verbose", "Normal", and "Quiet". For normal test runs you can
# use a verbosity of "Normal". If you need a more detailed output,
# then you can set it to "Verbose". For example, in case a regression
# occurred. Reducing the verbosity level can significantly reduce the
# test duration especially on targets with a slow serial output
# device. All verbosity levels produce enough output to notice failed
# test cases. In particular, the begin and end of test information is
# not affected by the verbosity level.
RTEMS_TEST_VERBOSITY = Normal
# Optimization flags passed to the C and C++ compiler
OPTIMIZATION_FLAGS = -O2 -g -fdata-sections -ffunction-sections
# ABI flags
ABI_FLAGS = -mno-red-zone -mcmmodel=large -Werror=return-type
# If defined to a non-zero value, prints the some information in case
# of a fatal error.
BSP_VERBOSE_FATAL_EXTENSION = 1
# Flags passed to the linker (GNU ld)
LDFLAGS = -Wl,--gc-sections
# Install the legacy application Makefile framework.
INSTALL_LEGACY_MAKEFILES = True
# If defined to a non-zero value, prints the exception context when an
# unexpected exception occurs.
BSP_PRINT_EXCEPTION_CONTEXT = 1
# If defined to a non-zero value, reset the board when the application
# exits.
BSP_RESET_BOARD_AT_EXIT = 1
# If defined to a non-zero value, print a message and wait until
# pressed before resetting board when application exits.
BSP_PRESS_KEY_FOR_RESET = 0

```

### Comment 1

1. **Sebastian Huber**, Wed, 07 Oct 2020 13:37:24 GMT

This would be fixed by:

<https://lists.rtems.org/pipermail/devel/2020-October/062577.html>

### Comment 2

1. **Sebastian Huber**, Sat, 10 Oct 2020 12:02:52 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**



## 4128 - all griscv variants fail to build on master

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4128">https://devel.rtems.org/ticket/4128</a> ( <a href="https://devel.rtems.org/ticket/4128">https://devel.rtems.org/ticket/4128</a> )
<b>Id</b>	4128
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 October 2020 13:52:16
<b>Modified</b>	10 October 2020 12:01:36
<b>Owner</b>	Jiri Gaisler
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Looks to be independent of waf or autoconf or configuration settings since a code issue in the BSP:

```
../../../../../../../../rtems/c/src/lib/libbsp/riscv/griscv/../../../../../../../../bsps/riscv/griscv/clock/clockdrv.c: In function
'glib_clock_initialize':
../../../../../../../../rtems/c/src/lib/libbsp/riscv/griscv/../../../../../../../../bsps/riscv/griscv/clock/clockdrv.c:174:10: warning:
implicit declaration of function 'glib_irqmp_has_timestamp' [-Wimplicit-function-declaration]
 174 |     if (!glib_irqmp_has_timestamp(irqmp_ts)) {
      |         ^~~~~~
../../../../../../../../rtems/c/src/lib/libbsp/riscv/griscv/../../../../../../../../bsps/riscv/griscv/clock/clockdrv.c:174:10: warning:
nested extern declaration of 'glib_irqmp_has_timestamp' [-Wnested-externs]
../../../../../../../../rtems/c/src/lib/libbsp/riscv/griscv/../../../../../../../../bsps/riscv/griscv/clock/clockdrv.c:175:17: error:
'GRLIB_FATAL_CLOCK_NO_IRQMP_TIMESTAMP_SUPPORT' undeclared (first use in this function); did you mean
'LEON3_FATAL_CLOCK_NO_IRQMP_TIMESTAMP_SUPPORT'?
 175 |         bsp_fatal(GRLIB_FATAL_CLOCK_NO_IRQMP_TIMESTAMP_SUPPORT);
      |         ^~~~~~
      |         LEON3_FATAL_CLOCK_NO_IRQMP_TIMESTAMP_SUPPORT
../../../../../../../../rtems/c/src/lib/libbsp/riscv/griscv/../../../../../../../../bsps/riscv/griscv/clock/clockdrv.c:175:17: note: each
undeclared identifier is reported only once for each function it appears in
gmake[6]: *** [clockdrv.o] Error 1
```

### Attachments:

- 
- 1 Joel Sherrill, Wed, 07 Oct 2020 15:36:19 GMT  
**attach:** set to [0001-bsps-include-bsp-fatal.h-Add-GRLIB-specific-fatal-er.patch](https://devel.rtems.org/ticket/4128/0001-bsps-include-bsp-fatal.h-Add-GRLIB-specific-fatal-er.patch) (<https://devel.rtems.org/ticket/4128/0001-bsps-include-bsp-fatal.h-Add-GRLIB-specific-fatal-er.patch>)
- 

### Comment 1

1. Joel Sherrill, Wed, 07 Oct 2020 15:38:09 GMT

With the attached patch, it builds further but fails with this which appears to be triggered because SMP is enabled (configure command below):

```
riscv-rtems6-gcc -march=rv32imafd -mabi=ilp32d -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-
function-declaration -Wstrict-prototypes -Wnested-externs -B../../../../lib/libbsp/riscv/griscv -B/home/joel/rtems-cron-
6/rtems/bsps/riscv/griscv/start -specs bsp_specs -qrtems -L../../../../cpukit -L/home/joel/rtems-cron-6/rtems/bsps/riscv/shared/start -
Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -Wl,--gc-sections -o base_sp.exe base_sp/base_sp-init.o base_sp/base_sp-
apptask.o ../../lib/libbsp/riscv/griscv/librtemsbsp.a ../../cpukit/librtemscpu.a ../../cpukit/librtemstest.a
/home/joel/rtems-cron-6/tools/6/lib/gcc/riscv-rtems6/10.2.1/../../../../riscv-rtems6/bin/ld:
../../../../lib/libbsp/riscv/griscv/librtemsbsp.a(clockdrv.o): in function 'glib_clock_initialize':
/home/joel/rtems-cron-6/b-griscv/riscv-
rtems6/c/griscv/lib/libbsp/riscv/griscv/../../../../../../../../rtems/c/src/lib/libbsp/riscv/griscv/../../../../../../../../bsps/riscv/gr
iscv/clock/clockdrv.c:167: undefined reference to 'glib_irqmp_has_timestamp'
collect2: error: ld returned 1 exit status
gmake[5]: *** [base_sp.exe] Error 1
```

The configuration is:

```
../../../../configure --target=riscv-rtems6 --enable-rtemsbsp=griscv --prefix=/home/joel/rtems-cron-6/tools/6/bsp-install --disable-
networking --enable-posix --enable-smp --disable-multiprocessing --enable-rtems-debug --enable-profiling --enable-tests --enable-
cxx --enable-maintainer-mode
```

### Comment 2

1. Joel Sherrill, Wed, 07 Oct 2020 15:38:22 GMT
2. **owner:** set to Jiri Gaisler
3. **status:** changed from new to assigned

### Comment 3

1. Jiri Gaisler, Thu, 08 Oct 2020 07:44:57 GMT

Replying to Joel Sherrill:

I don't get this far, my compilation fails on:

```
riscv-rtems6-gcc -march=rv32imafd -mabi=ilp32d -O2 -g -ffunction-sections -fdata-sections -Wall -Wmissing-prototypes -Wimplicit-function-declaration -Wstrict-prototypes -Wnested-externs -B./../lib/libbsp/riscv/griscv -B/home/jiri/ibm/src/rtems/rtems/bsps/riscv/griscv/start -specs bsp_specs -qrtems -L./../cpukit -L/home/jiri/ibm/src/rtems/rtems/bsps/riscv/shared/start -Wl,--wrap=printf -Wl,--wrap=puts -Wl,--wrap=putchar -Wl,--gc-sections -o base_sp.exe base_sp/base_sp-init.o base_sp/base_sp-apptask.o ./../lib/libbsp/riscv/griscv/librtemsbsp.a ./../cpukit/librtemscpu.a ./../cpukit/librtemstest.a /home/jiri/src/rtems/6/bin/./lib/gcc/riscv-rtems6/10.2.1/./../lib/riscv-rtems6/bin/ld: ./../cpukit/librtemscpu.a(free.o): in function `free': /home/jiri/ibm/src/rtems/rtems/c/src/./../cpukit/libcsupport/src/free.c:79: undefined reference to `RTEMS_Malloc_Heap'
```

I updated rsb and rtems from git head and re-built the tool-chain today ...

#### Comment 4

1. **Sebastian Huber**, Sat, 10 Oct 2020 12:01:36 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In e1a0e0c3/rtems:

```
glibc: Add and use irqmp_has_timestamp()
Replace leon3_irqmp_has_timestamp() with irqmp_has_timestamp() and move it to glibc.h.
Close #4128.
```

## 4129 - x86\_64 not listed as architecture in components in Trac

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4129">https://devel.rtems.org/ticket/4129</a> ( <a href="https://devel.rtems.org/ticket/4129">https://devel.rtems.org/ticket/4129</a> )
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 October 2020 13:55:05
<b>Modified</b>	17 December 2021 14:23:53
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/website
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	Karel Gardas
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

Just needs to be added.

#### Comment 1

1. **Joel Sherrill**, Fri, 17 Dec 2021 14:23:53 GMT
2. **cc:** **Karel Gardas** added
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

Added the component and cc'ed Karel so he would know about it. :)

## 4131 - "fdisk DISK\_NAME mount" in bdpart-mount.c uses non-existing file system type "msdos"

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4131">https://devel.rtems.org/ticket/4131</a> ( <a href="https://devel.rtems.org/ticket/4131">https://devel.rtems.org/ticket/4131</a> )
<b>Id</b>	4131
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	7 October 2020 14:27:18
<b>Modified</b>	12 October 2020 11:19:08
<b>Owner</b>	Frank Kühndel <frank.kuehndel@...>
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	minor
<b>Keywords</b>	fdisk shell bdpart mount bdpart-mount.c msdos
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

The function `rtems_bdpart_mount()` seems to be only used by the 'fdisk' shell command to mount all partitions of a disk with a single command:

```
fdisk DISK_NAME mount
    mounts the file system of each partition of the disk
fdisk DISK_NAME unmount
    unmounts the file system of each partition of the disk
```

The whole command does not work because in file `cpukit/libblock/src/bdpart-mount.c` line 103 specifies the file system type of each partition to be "msdos". Yet, "msdos" does not exist. The name must be "dosfs".

Beside of this fundamental problem, there are more issues with the code in `bdpart-mount.c`:

- 1) The function returns `RTEMS_SUCCESSFUL` despite the mount always fails.
- 2) The reason for errors is not written to the terminal.
- 3) The directory `'/mnt'` is created but not deleted later on (failure or not).
- 3) There is no documentation about this special 'fdisk' feature in the RTEMS Shell Guide. ('fdisk' is mentioned but its documentation is a bit short).
- 4) Only "msdos" formatted partitions can be mounted and all partitions are mounted read only. This is hard coded and cannot be changed by options. Moreover, there is no information about this to the user of the shell (i.e. using 'fdisk' mount requires insider knowledge).

How to reproduce:

- 1) For testing I use the 'testsuites/samples/fileio/init.c' sample and since I do not know the 'root' password, the password must be removed from that file to login as 'root' without password:

```
index 86b34b99dd..51507f9a53 100644
--- a/testsuites/samples/fileio/init.c
+++ b/testsuites/samples/fileio/init.c
@@ -563,8 +563,7 @@ static void fileio_start_shell(void)
    writeFile(
        "/etc/passwd",
        0644,
        "root:$6$$FuPohn1lx6lhW2qqlnmWvZQLJ8Thr/09I7ESTdb9VbnTon5.65"
        "/Vh2Mqa6FoKXwT0nHS/O7F0KfrDc6Svb/sH.:0:0:root:::/bin/sh\n"
+       "root.:0:0:root:::/bin/sh\n"
        "rtems:1:1:RTEMS Application:::/bin/sh\n"
        "test:$1$$oPulXt2Pw0ngIc7LyDHqul:2:2:test account:::/bin/sh\n"
        "tty:*:3:3:tty owner:::/bin/false\n"
```

- 2) I run the fileio sample using `qemu`:

```
cd rtems
env QEMU_AUDIO_DRV="none" qemu-system-arm -net none -nographic -M realview-pbx-a9 -m 256M -kernel
build/arm/realview/pbx/a9/qemu/testsuites/samples/fileio.exe
```

- 3) Type any key to stop the timer and enter the sample tool. Type 's' to enter the shell, login as 'root' with empty password.
- 4) Type the following shell commands (they create a RAM disk, partition it, register it, format it and try to mount it):

```
mkrd
fdisk /dev/rda fat32 16 write mbr
fdisk /dev/rda register
mkdos /dev/rda1
fdisk /dev/rda mount
```

- 5) The last line above is the command which fails - without an error message. There exists a `'/mnt'` directory but no `'/mnt/rda1'` directory as it should be:

```
ls -la /mnt
```

6) If you change line 103 of 'cpukit/libblock/src/bdpart-mount.c' from "msdos" to "dosfs", compile and build the executable and re-run the above test, '/mnt/rda1' exists (but the file system is mounted read-only).

### Comment 1

1. **Frank Kühndel**, Mon, 12 Oct 2020 11:19:08 GMT
2. **owner:** set to **Frank Kühndel** <frank.kuehndel@...>
3. **status:** changed from **assigned** to **closed**
4. **resolution:** set to **fixed**

In a479686/rtems:

shell: Remove not functioning fdisk mount/unmount

The shell has an 'fdisk' command which has sub-commands 'mount' and 'unmount'. These two sub-commands have a bug which causes them to be not able to mount anything. This proposed patch removes the buggy file cpukit/libblock/src/bdpart-mount.c and the mount/unmount commands from 'fdisk' as bug fix. The 'fdisk' command itself is not removed. The reasons for removing the sub-commands (instead of fixing the issue) are:

1) The bug has been introduced on 2010-May-31 with commit

29e92b090c8bc35745aa5c89231ce806bcb11e57. Since ten years no one can use this feature, nor has anybody complained about it.

2) Besides of the 'fdisk' 'mount' sub-command, the shell has the

usual 'mount' and 'unmount' commands which can serve as substitutes.

3) There are additional minor issues (see further down) which needed to

be addressed when the file will be kept.

What follows below is the precise bug description.

The bug is in function rtems\_bdpart\_mount() which is only be used by the 'fdisk' shell command to mount all partitions of a disk with a single command:

```
fdisk DISK_NAME mount
```

mounts the file system of each partition of the disk

```
fdisk DISK_NAME unmount
```

unmounts the file system of each partition of the disk

The whole command does not work because in file cpukit/libblock/src/bdpart-mount.c line 103 specifies the file system type of each partition to be "msdos". Yet, "msdos" does not exist. The name must be "dosfs".

Beside of this fundamental problem, there are more issues with the code in bdpart-mount.c:

1) The function returns RTEMS\_SUCCESSFUL despite the mount always fails.

2) The reason for errors is not written to the terminal.

3) The directory '/mnt' is created but not deleted later on (failure or not).

3) There is no documentation about this special 'fdisk' feature in the

RTEMS Shell Guide ('fdisk' is mentioned but its documentation is a bit short):  
[https://docs.rtems.org/branches/master/shell/file\\_and\\_directory.html#fdisk-format-disk](https://docs.rtems.org/branches/master/shell/file_and_directory.html#fdisk-format-disk)

4) Only "msdos" formatted partitions can be mounted and all partitions

are mounted read-only. This is hard coded and cannot be changed by options. Moreover, there is no information about this to the user of the shell (i.e. using 'fdisk' mount requires insider knowledge).

How to reproduce:

1) For testing, I use the 'testsuites/samples/fileio.exe' sample with qemu:

```
cd rtems env QEMU_AUDIO_DRV="none" qemu-system-arm -net none -nographic \
-M realview-pbx-a9 -m 256M -kernel \
build/arm/realview_pbx_a9_qemu/testsuites/samples/fileio.exe
```

2) Type any key to stop the timer and enter the sample tool.

Type 's' to enter the shell, login as 'root' with the password shown in the terminal.

3) Type the following shell commands (they create a RAM disk,

partition it, register it, format it and try to mount it):

```
mkrd fdisk /dev/rda fat32 16 write mbr fdisk /dev/rda register mkdos /dev/rda1 fdisk /dev/rda mount
```

4) The last line above is the command which fails - without an error message. There exists a '/mnt' directory but no '/mnt/rda1' directory as it should be:

```
ls -la /mnt
```

5) If you change line 103 of 'cpukit/libblock/src/bdpart-mount.c'

from "msdos" to "dosfs", compile and build the executable and re-run the above test, '/mnt/rda1' exists (but the file system is mounted read-only).

Close #4131

## 4134 - rtemsspec: Support user-defined ordering of directives in header files (Doxygen)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4134">https://devel.rtems.org/ticket/4134</a> ( <a href="https://devel.rtems.org/ticket/4134">https://devel.rtems.org/ticket/4134</a> )
<b>Id</b>	4134
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 October 2020 06:17:56
<b>Modified</b>	11 October 2020 14:21:50
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Currently, the generated interfaces in header files are defined by their dependencies and a topological sorting (alphabetical order is applied to unrelated interfaces). In order to be in line with the Sphinx documentation it would be nice to apply also the user-defined ordering specified in groups.

### Comment 1

1. **Sebastian Huber**, Sun, 11 Oct 2020 13:21:13 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3f3e088/rtems-central:

```
interface: Improve ordering
```

Close #4134.

### Comment 2

1. **Sebastian Huber**, Sun, 11 Oct 2020 14:21:50 GMT
2. **milestone**: changed from **Indefinite** to **6.1**

## 4140 - waf install of RTEMS breaks Makefile system in rtems-examples

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4140">https://devel.rtems.org/ticket/4140</a> ( <a href="https://devel.rtems.org/ticket/4140">https://devel.rtems.org/ticket/4140</a> )
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	9 October 2020 22:19:19
<b>Modified</b>	10 October 2020 11:50:54
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

This boils down to `bsp_specs` being referenced in `Makefile.inc` and it no longer being at the install point. This can be worked around by copying an empty file to the install location for `bsp_specs` enough to compile the programs but I assume that the `-B...` list of arguments needs to be replaced

Properly the BSP compile flags need to be processed into the installed `target.cfg` and the line with `-B...` modified as needed in `gcc-target-default.cfg`.

```
i386-rtems6-gcc --pipe -B/home/joel/rtems-work/tools/6/bsp-install/i386-rtems6/pc686/lib/ -specs bsp_specs -qrtems -Wall -mtune=pentiumpro -march=pentium -c -o o-optimize/test.o test.c
i386-rtems6-gcc: fatal error: cannot read spec file 'bsp_specs': No such file or directory
compilation terminated.
make: *** [o-optimize/test.o] Error 1
[joel@localhost hello_world_c]$ cp /dev/null /home/joel/rtems-work/tools/6/bsp-install/i386-rtems6/pc686/lib/bsp_specs
[joel@localhost hello_world_c]$ RTEMS_MAKEFILE_PATH=/home/joel/rtems-work/tools/6/bsp-install/i386-rtems6/pc686/ make clean all
rm -f a.out core mon.out gmon.out
rm -f -r
rm -f -r a.out *.o *.BAK Depends-o-optimize.tmp
rm -f -r o-optimize o-debug
test -d o-optimize || mkdir o-optimize
i386-rtems6-gcc --pipe -B/home/joel/rtems-work/tools/6/bsp-install/i386-rtems6/pc686/lib/ -specs bsp_specs -qrtems -Wall -mtune=pentiumpro -march=pentium -c -o o-optimize/test.o test.c
i386-rtems6-gcc --pipe -B/home/joel/rtems-work/tools/6/bsp-install/i386-rtems6/pc686/lib/ -specs bsp_specs -qrtems -Wall -mtune=pentiumpro -march=pentium -qrtems -Wl,-Ttext,0x00100000 -mtune=pentiumpro -march=pentium -Wl,--gc-sections -L/home/joel/rtems-work/rtems/bSPs/i386/shared/start -L/home/joel/rtems-work/rtems/bSPs/i386/pc386/start -mtune=pentiumpro -march=pentium -o o-optimize/hello.exe o-optimize/test.o
i386-rtems6-nm -g -n o-optimize/hello.exe > o-optimize/hello.num
i386-rtems6-size o-optimize/hello.exe
  text    data    bss     dec     hex filename
151790   9628   33056  194474  2f7aa o-optimize/hello.exe
```

### Comment 1

1. **Sebastian Huber**, Sat, 10 Oct 2020 11:50:54 GMT
2. **owner**: set to **Sebastian Huber** <sebastian.huber@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 6ca00e61/rtems:

```
build: Fix legacy Makefile support
Close #4140.
```

## 4142 - Sparse disk destroys data when it grows

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4142">https://devel.rtems.org/ticket/4142</a> ( <a href="https://devel.rtems.org/ticket/4142">https://devel.rtems.org/ticket/4142</a> )
<b>Id</b>	4142
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	12 October 2020 06:08:50
<b>Modified</b>	12 October 2020 06:23:10
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	lib/block
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The `qsort()` in `sparse_disk_get_new_block()` may move the appended key which invalidates the pointer.

**Comment 1**

1. **Sebastian Huber**, Mon, 12 Oct 2020 06:23:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In b434dc1/rtems:

```
libblock: Fix sparse disk
```

```
The qsort() in sparse_disk_get_new_block() may move the appended key which invalidates the pointer.
```

```
Close #4142.
```

**4143 - fileio - Stack too small for login with password**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4143">https://devel.rtems.org/ticket/4143</a> ( <a href="https://devel.rtems.org/ticket/4143">https://devel.rtems.org/ticket/4143</a> )
<b>Id</b>	4143
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	12 October 2020 13:17:05
<b>Modified</b>	12 October 2020 13:49:36
<b>Owner</b>	joel@...
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	minor
<b>Keywords</b>	fileio,stack,password,login,root
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

When I use the 'shell' from the fileio sample with the command below:

```
env QEMU_AUDIO_DRV="none" \
qemu-system-arm -no-reboot -net none -nographic -M realview-pbx-a9 -m 256M \
-kernel build/arm/realview/pbx_a9/qemu/testsuites/samples/fileio.exe
```

The executable crashes with an "BLOWN STACK!!!" as soon as I try to login as 'root' with password. (The logins without password work fine.) Increasing the stack size of the affected thread a bit (to 5 times `RTEMS_MINIMUM_STACK_SIZE`) solves the issue.

How to reproduce:

- Start the fileio sample in QEMU with the above command.
- Type a key to stop the timer.
- Type "s" to enter the shell.
- Login as "root" with the password printed to the terminal.
- In the line with the first shell prompt, the text "BLOWN STACK!!!" appears unexpectedly followed by further crash information.

```
[...]
/dev/foobar login: root
Password:
RTEMS Shell on /dev/foobar. Use 'help' to list commands.
SHLL [/] # BLOWN STACK!!!
task control block: 0x00205278
[...]
```

My config.ini was

```
[arm/realview_pbx_a9_qemu]
RTEMS_DEBUG = True
RTEMS_NETWORKING = True
RTEMS_POSIX_API = True
RTEMS_SMP = True
BUILD_TESTS = True
```

RTEMS origin.master at 558a19d3adff6a3ecf678f94408b48becbcb9fb

#### Comment 1

1. **Frank Kühndel**, Mon, 12 Oct 2020 13:49:36 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

In ec13365/rtems:

testsuites/samples/fileio - Increase of stack size

When I use the 'shell' from the fileio sample with the command below:

```
env QEMU_AUDIO_DRV="none" \ qemu-system-arm -no-reboot -net none -nographic -M realview-pbx-a9 \ -m 256M \ -kernel
build/arm/realview_pbx_a9_qemu/testsuites/samples/fileio.exe
```

The executable crashes with an "BLOWN STACK!!!" as soon as I try to login as 'root' with password. (The logins without password work fine.) Increasing the stack size of the affected thread a bit solves the issue. Hence, I suggest this patch.

My config.ini was

```
[arm/realview_pbx_a9_qemu] RTEMS_DEBUG = True RTEMS_NETWORKING = True RTEMS_POSIX_API = True RTEMS_SMP = True BUILD_TESTS = True
```

RTEMS origin.master at a479686c112144119866391ceb21c48be6a3eca9

Close #4143

## 4145 - rtems-source-builder: Update RTEMS Kernel Recipe to Use waf for RTEMS

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4145">https://devel.rtems.org/ticket/4145</a> ( <a href="https://devel.rtems.org/ticket/4145">https://devel.rtems.org/ticket/4145</a> )
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	14 October 2020 16:57:11
<b>Modified</b>	9 November 2021 17:06:43
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

kernel configuration builds using autoconf-based build system. Needs to be switched to waf. Hopefully contained to rtems-kernel-common.cfg.

#### Comment 1

1. **Joel Sherrill**, Wed, 14 Oct 2020 17:17:25 GMT
2. **summary:** changed from **rtems-source-builder: RTEMS Kernel Recipe** to **rtems-source-builder: Update RTEMS Kernel Recipe to Use waf for RTEMS**

#### Comment 2

1. **Chris Johns**, Mon, 09 Nov 2020 04:54:19 GMT

This is not as easy as I thought it might be. Let me explain ...

The config.ini file hides some important detail the RSB needs. The RSB currently names the package as:

```
rtems- $\{$ rtems version $\}$ - $\{$ target $\}$ - $\{$ rtems bsp $\}$ - $\{$ host $\}$ - $\{$ release $\}$ 
```

The target and BSP are in the build config file and a config file could build a mix of architectures breaking this naming.



The simplest approach is to take the arguments provided to the RSB and create a config.ini file but this would be limiting where complex BSP options are needed.

I could check if the --with-rtems-bspopts option is a path and that could be a list of specific BSP options appended into the BSP specific area.

Should the following options print a depreciate warning:

```
--with-rtems-legacy-network --with-rtems-cxx
```

I am not sure about --with-rtems-posix. I think it should be removed and POSIX always be enabled.

### Comment 3

1. **Ryan Long**, Tue, 09 Nov 2021 17:06:43 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In def9347/rtems-source-builder:

```
rtems-kernel: Implement kernel recipe using waf
```

Closes #4145

## 4148 - RFS bit map search buffer overflow

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4148">https://devel.rtems.org/ticket/4148</a> ( <a href="https://devel.rtems.org/ticket/4148">https://devel.rtems.org/ticket/4148</a> )
<b>Id</b>	4148
<b>Reporter</b>	Chris Johns
<b>Created</b>	15 October 2020 06:12:13
<b>Modified</b>	16 October 2020 23:54:50
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	fs/rfs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The bit search create writes past the end of its buffer. See:

<https://lists.rtems.org/pipermail/devel/2020-October/062701.html>

### Comment 1

1. **Chris Johns**, Fri, 16 Oct 2020 23:54:50 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In f514092/rtems:

```
libfs/rfs: Check search bit map end on last bit
Do not write past the last location of the search bit map
when it is being created.
Closes #4148
```

## 4155 - Add a workaround for the LEON3FT RETT Restart errata: TN-0018

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4155">https://devel.rtems.org/ticket/4155</a> ( <a href="https://devel.rtems.org/ticket/4155">https://devel.rtems.org/ticket/4155</a> )
<b>Id</b>	4155
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	16 October 2020 05:47:11
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

See also:

<https://www.gaisler.com/doc/antrn/GRLIB-TN-0018.pdf>

**Comment 1**

1. **Daniel Hellstrom**, Fri, 16 Oct 2020 14:58:41 GMT

This is the proposed GCC10 patch for master, it should be applied for RSB/sparc too.

<https://lists.rtems.org/pipermail/devel/2020-October/062837.html>

**Comment 2**

1. **Sebastian Huber**, Fri, 16 Oct 2020 15:12:09 GMT

The patch looks fine.

**Comment 3**

1. **Daniel Hellstrom**, Sun, 07 Mar 2021 15:29:16 GMT

The GCC patch has been accepted upstreams into master and GCC-10 branch:

<https://gcc.gnu.org/git/?p=gcc.git;a=commit;h=4b690f161b82e428dbe648075da215daa52be0ea> <https://gcc.gnu.org/git/?p=gcc.git;a=commit;h=1aed3f059ebd08ffe1346ac7ecf8e8606359875>

**Comment 4**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:57 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In b2da982/rtems:

```
leon,tn-0018: work around GRLIB-TN-0018 errata
```

```
Overview =====
```

The errata is worked around in the kernel without requiring toolchain modifications. It is triggered the JMPL/RETT return from trap instruction sequence never generated by the compiler and. There are also other conditions that must be true to trigger the errata, for example the instruction that the trap returns to has to be a JMPL instruction. The errata can only be triggered if certain data is corrected by ECC (inflicted by radiation), thus it can not be triggered under normal operation. For more information see:

[www.gaisler.com/notes](http://www.gaisler.com/notes)

```
Affected RTEMS target BSPs:
GR712RC UT699 UT700/699E
The work around is enabled by defining FIX_LEON3_TN0018 at build time. After applying the following GCC patch, GCC will set the define
when compiling for an affected multilib:
GR712RC (-mcpu=leon3 -mfix-gr712rc) UT700/UT699E (-mcpu=leon3 -mfix-ut700) UT699 (-mcpu=leon -mfix-ut699)
When building for another multilib and TN0018 is still required, it is possible to enable it on the RTEMS kernel configure line using
the TARGET_CFLAGS (-DFIX_LEON3FT_TN0018) or other by other means.
```

```
The following GCC patch sets FIX_LEON3FT_TN0018 for the affected RTEMS multilibs:
```

```
diff --git a/gcc/config/sparc/rtemself.h b/gcc/config/sparc/rtemself.h index 6570590..ddec98c 100644 --- a/gcc/config/sparc/rtemself.h
+++ b/gcc/config/sparc/rtemself.h @@ -33,6 +33,8 @@
```

```

builtin_assert ("system=rtems");          \ if (sparc_fix_b2bst)          \
    builtin_define ("FIX_LEON3FT_B2BST"); \
+   if (sparc_fix_gr712rc sparc_fix_ut700 sparc_fix_ut699) \ +   builtin_define ("FIX_LEON3FT_TN0018"); \
}
\
while (0)

```

Workaround Implementation =====

In general there are two approaches that the workaround uses:

- A) avoid ECC restarting the RETT instruction
- B) avoid returning from trap to a JMWL instruction

Where A) comes at a higher performance cost than B), so B) is used where possible. B) can be achieved for certain returns from trap handlers if trap entry is controlled by assembly, such as system calls.

A) A special JMWL/RETT sequence where instruction cache is disabled temporarily to avoid RETT containing ECC errors, and reading of RETT source registers to "clean" them from incorrect ECC just before RETT is executed.

B) The work around prevents JMWL after system calls (TA instruction) and modifies assembly code on return from traps jumping back to application code. Note that for some traps the trapped instruction is always re-executed and can therefore not trigger the errata, for example the SAVE instruction causing window overflow or an float instruction causing FPU disabled trap.

RTEMS SPARC traps workaround implementation:

NAME	NOTE	TRAP	COMMENT
window overflow	1 - 0x05	always returns to a SAVE window underflow	1 - 0x06 always returns to a RESTORE interrupt
traps	2 - 0x10..1f	special rett sequence workaround syscall	3 - 0x80 shutdown system - never returns ABI flush
windows	2 - 0x83	special rett sequence workaround syscall irqdis	4 - 0x89 syscall irqen 4 - 0x8A
syscall_irqdis_fp	1 - 0x8B	always jumps back to FP instruction	syscall_lazy_fp_switch 5 - 0x04 A) jumps back to FP instruction, or to

B) `_Internal_error()` starting with SAVE

Notes: 1) no workaround needed because trap always returns to non-JMWL instruction 2) workaround implemented by special rett sequence 3) no workaround needed because system call never returns 4) workaround implemented by inserting NOP in system call generation. Thus

fall into 1) when workaround is enabled and no trap handler fix needed.

5) trap handler branches into both 1) and returning to `_Internal_error()`

which starts with a SAVE and besides since it shuts down the system that RETT should never be in cache (only executed once) so fix not necessary in this case.

Any custom trap handlers may also have to be updated. To simplify that, helper work around assembly code in macros are available in a separate include file .

Close #4155.

**Comment 5**

1. Sebastian Huber, Wed, 23 Jun 2021 07:07:55 GMT
2. keywords: qualification added

**4157 - pthread\_spin\_unlock() may corrupt the thread stack if RTEMS\_PROFILING and RTEMS\_SMP is enabled**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4157">https://devel.rtems.org/ticket/4157</a> ( <a href="https://devel.rtems.org/ticket/4157">https://devel.rtems.org/ticket/4157</a> )
<b>Id</b>	4157
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 October 2020 15:33:11
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The call to `_SMP_lock_Stats_register_or_max_section_time()` registers a dummy statistics block which resides on the thread stack.

**Comment 1**

1. **Sebastian Huber**, Mon, 19 Oct 2020 15:33:52 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 2b9fb314/rtems:

```
posix: Fix pthread_spin_unlock()

Prevent a call to _SMP_lock_Stats_register_or_max_section_time(). This fixes a thread stack corruption in case RTEMS_PROFILING and RTEMS_SMP is enabled.

Close #4157.
```

**Comment 2**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords**: **qualification** added
- 

**4158 - rtems\_interrupt\_server\_delete() does not destroy the ISR lock of the server control**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4158">https://devel.rtems.org/ticket/4158</a> ( <a href="https://devel.rtems.org/ticket/4158">https://devel.rtems.org/ticket/4158</a> )
<b>Id</b>	4158
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 October 2020 15:44:02
<b>Modified</b>	19 October 2020 15:45:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This leads to memory corruption if RTEMS\_PROFILING and RTEMS\_SMP is enabled.

**Comment 1**

1. **Sebastian Huber**, Mon, 19 Oct 2020 15:45:03 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In bb4e534/rtems:

bsps: Fix rtems\_interrupt\_server\_delete()

The ISR lock must be destroyed to prevent memory corruption if RTEMS\_PROFILING and RTEMS\_SMP is enabled.

Close #4158.

---

## **4164 - Fix NVMe disk synchronization and media block handling**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4164">https://devel.rtems.org/ticket/4164</a> ( <a href="https://devel.rtems.org/ticket/4164">https://devel.rtems.org/ticket/4164</a> )
<b>Id</b>	4164
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	27 October 2020 05:24:03
<b>Modified</b>	27 October 2020 05:28:05
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

### **Comment 1**

1. **Sebastian Huber**, Tue, 27 Oct 2020 05:28:05 GMT
  2. **status**: changed from **assigned** to **closed**
  3. **resolution**: set to **fixed**
- 

## **4166 - rtems-bsp-builder: Add way to select rtems version (6 vs 7)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4166">https://devel.rtems.org/ticket/4166</a> ( <a href="https://devel.rtems.org/ticket/4166">https://devel.rtems.org/ticket/4166</a> )
<b>Id</b>	4166
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	28 October 2020 13:04:23
<b>Modified</b>	29 November 2022 23:25:39
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

When testing the RTEMS master, one can use the rtems6 or rtems7 tools. The rtems-bsp-builder is hard-coded to rtems6. As part of doing this, the version should be in the email subject and report so that similar reports can be distinguished.

### **Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 23:25:39 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **duplicate**

Duplicate of #3671

---

## **4167 - Coverity Scan Does Not Run on rtems6**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4167">https://devel.rtems.org/ticket/4167</a> ( <a href="https://devel.rtems.org/ticket/4167">https://devel.rtems.org/ticket/4167</a> )
<b>Id</b>	4167
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	28 October 2020 16:14:14
<b>Modified</b>	9 February 2022 14:52:58
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This is a ticket to note that Coverity does not appear to like the gcc version going from one to two digits. Since the Coverity Scan support for free users is minimal, I asked on the GCC mailing list if anyone had insight (<https://gcc.gnu.org/pipermail/gcc/2020-October/234073.html>).

This is completely outside our control and this is just a tracking ticket to note that Coverity Scan reports will be run against the 5 branch until this is fixed. This will likely be of limited use since rtems 5 is stable and changes are minimal compared to the rtems master.

If it really is a two digit major issue (unconfirmed if this works for gcc 9), I could do Coverity builds using a special toolchain based on gcc 9.

**Comment 1**

1. **Joel Sherrill**, Thu, 29 Oct 2020 15:19:10 GMT

I have done some more analysis which I reported in the GCC mailing list thread. I build sparc-rtems6 tools using gcc 7, 8, 9, and 10. Coverity worked using GCC 7, 8, and 9 but not 10 using the autoconf build since that made it more similar to gcc 7 on rtems5. It required uninstalling Coverity and reinstalling each time I switched GCC versions. There must be some residual configuration left between runs which this addresses.

I did try the waf build with gcc 7, 9, and 10. Same behavior as with the autoconf build.

The questions going forward are:

Is there a way to make Coverity aware of a bug like this? Support for the open source projects using Coverity Scan is minimal. Do we want to switch to the master for Coverity runs? This would require me using a special gcc9 build. The code on rtems5 is stable and any fixes/changes are much more likely to be on the master so I tend to lean to switching.

This is going to be an issue until Coverity updates the binary for Scan to support GCC 10.

**Comment 2**

1. **Joel Sherrill**, Thu, 16 Dec 2021 20:02:55 GMT

2. **type:** changed from **defect** to **enhancement**

Coverity Scan has been running on RTEMS for a while now. Closing.

**Comment 3**

1. **Joel Sherrill**, Wed, 09 Feb 2022 14:52:58 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

Didn't get closed last time.

---

**4175 - Resolve warning during AArch64 build**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4175">https://devel.rtems.org/ticket/4175</a> ( <a href="https://devel.rtems.org/ticket/4175">https://devel.rtems.org/ticket/4175</a> )
<b>Id</b>	4175
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	10 November 2020 15:40:39
<b>Modified</b>	16 November 2020 16:17:43
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

When compiling under the ILP32 multilib variant, the build generates a warning related to the saved stack pointer. This resolves the warning by sizing the saved stack pointer appropriately instead of it always being 64bits long.

**Attachments:****1 Kinsey Moore, Tue, 10 Nov 2020 15:46:16 GMT**

**attach:** set to [0001-score-aarch64-Size-saved-SP-register-for-ABI.patch](https://devel.rtems.org/ticket/4175/0001-score-aarch64-Size-saved-SP-register-for-ABI.patch) (<https://devel.rtems.org/ticket/4175/0001-score-aarch64-Size-saved-SP-register-for-ABI.patch>)

**Comment 1**

1. **Kinsey Moore**, Tue, 10 Nov 2020 20:21:23 GMT
2. **component:** changed from **admin** to **arch/aarch64**

**Comment 2**

1. **Kinsey Moore**, Mon, 16 Nov 2020 16:17:43 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

**4180 - Add BSP for i.MXRT1050**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4180">https://devel.rtems.org/ticket/4180</a> ( <a href="https://devel.rtems.org/ticket/4180">https://devel.rtems.org/ticket/4180</a> )
<b>Id</b>	4180
<b>Reporter</b>	Christian Mauderer
<b>Created</b>	17 November 2020 10:16:50
<b>Modified</b>	17 December 2021 07:40:16
<b>Owner</b>	Christian Mauderer
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Add a BSP for the i.MXRT1050 series. The default settings for the BSP will run on the IMXRT1050-EVKB evaluation board.

**Comment 1**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:54:42 GMT

In e00f443/rtems:

```
imx: Move imx_iomux to arm/shared
Update #4180
```

**Comment 2**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:54:45 GMT

In 6cece585/rtems:

```
bsps/imx: Move imx-gpio to arm/shared
Update #4180
```

**Comment 3**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:54:49 GMT

In b169095c/rtems:

cpu/armv7m: Add table based init for ARMV7M\_MPU

Modify the MPU functions of the stm32h7 BSP to be table based and available for all ARMV7M BSPs.

Update #4180

#### **Comment 4**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:54:53 GMT

In 48f6a6c/rtems:

bsp/imxrt: Import files from MCUXpresso SDK V2.8.5

The following files have been imported:

```
cp ${SDK}/boards/evkbimxrt1050/project_template/clock_config.c nxp/boards/evkbimxrt1050 cp
${SDK}/boards/evkbimxrt1050/project_template/clock_config.h include/fsl_clock_config.h cp
${SDK}/boards/evkbimxrt1050/project_template/dcd.c start/flash-dcd.c cp ${SDK}/boards/evkbimxrt1050/project_template/pin_mux.c
nxp/boards/evkbimxrt1050 cp ${SDK}/boards/evkbimxrt1050/project_template/pin_mux.h include/fsl_pin_mux.h cp
${SDK}/boards/evkbimxrt1050/xip/evkbimxrt1050_flexspi_nor_config.h include/fsl_flexspi_nor_config.h cp
${SDK}/devices/MIMXRT1052/MIMXRT1052.h include cp ${SDK}/devices/MIMXRT1052/MIMXRT1052_features.h include cp
${SDK}/devices/MIMXRT1052/drivers/fsl_*.c nxp/devices/MIMXRT1052/drivers cp ${SDK}/devices/MIMXRT1052/drivers/fsl_*.h include cp
${SDK}/devices/MIMXRT1052/fsl_device_registers.h include cp ${SDK}/devices/MIMXRT1052/system_MIMXRT1052.h include/ cp
${SDK}/devices/MIMXRT1052/xip/fsl_flexspi_nor_boot.c nxp/devices/MIMXRT1052/xip/fsl_flexspi_nor_boot.c cp
${SDK}/devices/MIMXRT1052/xip/fsl_flexspi_nor_boot.h include
```

Update #4180

#### **Comment 5**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:54:56 GMT

In 8abf858c/rtems:

bsp/imxrt: Fix warnings for imported files

Update #4180

#### **Comment 6**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:54:59 GMT

In 57b5b29c/rtems:

bsp/imxrt: Adapt imported files

Update #4180

#### **Comment 7**

1. **Christian Mauderer**, Fri, 20 Nov 2020 07:55:03 GMT

In 7141afbb/rtems:

bsp/imxrt: Add new BSP

Update #4180

#### **Comment 8**

1. **Christian Mauderer**, Fri, 20 Nov 2020 08:07:53 GMT

In e95d992/rtems-docs:

user/bsps: Add imxrt

Update #4180

#### **Comment 9**

1. **Christian Mauderer**, Mon, 14 Dec 2020 11:54:55 GMT

In b63a187/rtems:

bsps/imxrt: Split up dts.

This allows simpler creation of own dts files for custom boards.



Update #4180

**Comment 10**1. **Christian Mauderer**, Mon, 14 Dec 2020 11:54:59 GMT

In 9b3def2/rtems:

`bsps/arm/imx*`: Fix location of shared headers

When moving the headers from the imx BSP to the shared area, the wrong directory has been selected. This patch fixes that problem.

Update #4180

**Comment 11**1. **Christian Mauderer**, Mon, 14 Dec 2020 11:55:02 GMT

In eb2b915/rtems:

`cpu/armv7m`: Fix table based init for ARMV7M\_MPU

Somehow the table index has been missing in the latest patch version. With that, the configuration for the first region has been applied multiple times.

Update #4180

**Comment 12**1. **Christian Mauderer**, Mon, 14 Dec 2020 11:55:29 GMT

In 2cf3076/rtems-docs:

`user/bsp/imxrt`: Information for custom FDT

Update #4180

**Comment 13**1. **Christian Mauderer**, Thu, 21 Jan 2021 09:26:38 GMT

In 22e9dafb/rtems:

`bsps/imxrt`: Use standard names to avoid warnings

If spi or i2c slaves are "connected" to the spi or i2c bus, the device tree compiler complains if the busses are not named spi or i2c.

Update #4180

**Comment 14**1. **Christian Mauderer**, Thu, 21 Jan 2021 09:26:42 GMT

In 301bbc3/rtems:

`bsps/shared`: Copy fsl-edma from mpc55xx

This is a preparation for making the driver universal.

Update #4180

**Comment 15**1. **Christian Mauderer**, Thu, 21 Jan 2021 09:26:45 GMT

In a434cc8/rtems:

`bsps/shared`: Adapt fsl-edma driver for imxrt

Note: The changes have been done with portability in mind. The driver should (in theory) be able to replace the original one in the MPC BSPs too. For full compatibility an adaption layer and especially a test would be necessary. Because both are missing, don't integrate it into the MPC BSP now.

Update #4180

**Comment 16**

1. **Christian Mauderer**, Thu, 21 Jan 2021 09:26:48 GMT

In d9794a1/rtems:

bsps/imxrt: Add DMA numbers to dtsi

Also currently no driver uses these numbers, it is useful for applications that want to use the DMA.

Update #4180

### **Comment 17**

1. **Christian Mauderer**, Thu, 21 Jan 2021 09:26:55 GMT

In 36b4e8c/rtems:

bsps/imxrt: Add ioctl to LPSPI to get registers

This allows an application to get the registers of the LPSPI. That is useful for applications that want to use DMA for a very specialized and highly optimized communication.

Update #4180

### **Comment 18**

1. **Christian Mauderer**, Mon, 17 May 2021 07:13:13 GMT

In 08e4e6f2/rtems:

bsps/imxrt: Fix documentation error

Update #4180

### **Comment 19**

1. **Christian Mauderer**, Mon, 17 May 2021 07:13:16 GMT

In c3056666/rtems:

bsps/imxrt: Reduce devicetree size

Remove symbols that would be necessary for overlays and decrease padding that would be necessary for adding stuff during run-time.

Update #4180

### **Comment 20**

1. **Christian Mauderer**, Mon, 17 May 2021 07:13:20 GMT

In 988cc1a/rtems:

bsps/imxrt: Add addresses and interrupts to dts

Add addresses and interrupts for most internal peripherals to the dts. The additional aliases make it possible for an application to easily access these informations.

Update #4180

### **Comment 21**

1. **Christian Mauderer**, Mon, 17 May 2021 07:13:23 GMT

In 691fec40/rtems:

bsps/imxrt: Fix OCRAM, ITCM and DTCM sizes

The sizes are configurable via fuses or per software via some registers. At the moment the registers are not changed. Changing the registers destroys data stored in the RAM areas (like application code or data). So either the fuses or some bootloader should be used to set them before the application starts.

This also adds an OCRAM only linker command file.

Update #4180

### **Comment 22**

1. **Christian Mauderer**, Mon, 17 May 2021 07:13:27 GMT

In 15e26f4/rtems:

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

bsps/imxrt: Enable DMA clock  
The EDMA is intialized so make sure the the clock is initialized too.  
Update #4180

### **Comment 23**

1. **Christian Mauderer**, Fri, 28 May 2021 06:27:33 GMT

In a3ebe17/rtems-docs:

bsps/imxrt: Remove superfluous options from dtc  
The -@ option adds symbols that are used when applying an overlay. RTEMS doesn't support overlays or re-parsing of device trees. So the symbols only increase the size of the binary.  
The same is true for the padding. It would be useful if the device tree is changed during run time which is not supported in RTEMS.  
Update #4180

### **Comment 24**

1. **Christian Mauderer**, Fri, 02 Jul 2021 11:51:06 GMT

In 95a38dd/rtems:

bsps/imxrt: Allow different ARM PLL setting  
Update #4180

### **Comment 25**

1. **Christian Mauderer**, Fri, 02 Jul 2021 11:51:10 GMT

In 0d3453a4/rtems:

bsps/imxrt: Simplify linkcmds and make it flexible  
Calling the memory FLASH and EXTRAM instead of FLEXSPI and SDRAM makes it simpler to support other types of external RAM. This patch also removes some of the calculations and improves names and documentation to avoid pitfalls. It removes a unnecessary memory definition.  
Update #4180

### **Comment 26**

1. **Christian Mauderer**, Fri, 02 Jul 2021 11:53:08 GMT

In 72ae964/rtems-docs:

user/bsps/imxrt: Info about ARM PLL frequency  
Update #4180

### **Comment 27**

1. **Christian Mauderer**, Thu, 02 Sep 2021 06:38:40 GMT

In e495633/rtems:

bsps/imxrt: Improve SPI driver  
It wasn't possible to keep the CS line low between multiple message descriptors in one transfer. This patch reworks the driver so that it is possible.  
Update #4180

### **Comment 28**

1. **Christian Mauderer**, Fri, 17 Dec 2021 07:39:50 GMT

The base BSP works since quite some time now. Further changes to this BSP are improvements. Therefore closing this ticket now.

### **Comment 29**

1. **Christian Mauderer**, Fri, 17 Dec 2021 07:40:16 GMT

2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

## 4181 - Add CONFIGURE\_INIT\_TASK\_STORAGE\_SIZE

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4181">https://devel.rtems.org/ticket/4181</a> ( <a href="https://devel.rtems.org/ticket/4181">https://devel.rtems.org/ticket/4181</a> )
<b>Id</b>	4181
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 November 2020 07:31:23
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Currently, the Classic API initialization task is created with `rtems_task_create()`. In order to better support applications which use the new `rtems_task_construct()` directive add a configuration options which constructs the Classic API initialization task with `rtems_task_construct()`:

```

/* Generated from spec:/acfg/if/init-task-storage-size */
/**
 * @brief This configuration option is an integer define.
 *
 * The value of this configuration option defines the task storage size of the
 * Classic API initialization task. If this configuration option is specified,
 * then the Classic API initialization task is constructed by
 * rtems_task_construct() instead of using rtems_task_create().
 *
 * @par Default Value
 * The default value is 0.
 *
 * @par Value Constraints
 * @parblock
 * The value of this configuration option shall satisfy all of the following
 * constraints:
 *
 * * It shall be greater than or equal to #CONFIGURE_MINIMUM_TASK_STACK_SIZE.
 *
 * * It shall be defined using RTEMS_TASK_STORAGE_SIZE().
 * @endparblock
 *
 * @par Notes
 * @parblock
 * A task storage area of the specified size is defined by the configuration
 * for the Classic API initialization task. The
 *
 * * #CONFIGURE_INIT_TASK_STACK_SIZE and
 *
 * * ``CONFIGURE_INIT_TASK_STORAGE_SIZE``
 *
 * configuration options are mutually exclusive.
 * @endparblock
 */
#define CONFIGURE_INIT_TASK_STORAGE_SIZE

```

### Comment 1

1. **Sebastian Huber**, Fri, 27 Nov 2020 07:47:03 GMT

In bc175a1/rtems:

```

Avoid INTERNAL_ERROR_RTEMS_INIT_TASK_ENTRY_IS_NULL

Replace a runtime check with a compile time assertion. This makes the INTERNAL_ERROR_RTEMS_INIT_TASK_ENTRY_IS_NULL obsolete.

Update #4181.

```

### Comment 2

1. **Sebastian Huber**, Fri, 27 Nov 2020 07:47:07 GMT

In 657e30c1/rtems:

```

config: CONFIGURE_INIT_TASK_CONSTRUCT_STORAGE_SIZE

In order to better support applications which use the new rtems_task_construct() directive add the
CONFIGURE_INIT_TASK_CONSTRUCT_STORAGE_SIZE configuration option. If this option is specified, then the Classic API initialization task
is constructed with rtems_task_construct().

Update #4181.

```

**Comment 3**

1. **Sebastian Huber**, Fri, 27 Nov 2020 07:47:13 GMT

In 06386fc7/rtems:

Use CONFIGURE\_INIT\_TASK\_CONSTRUCT\_STORAGE\_SIZE  
Update #4181.

**Comment 4**

1. **Sebastian Huber**, Fri, 27 Nov 2020 08:16:58 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 00b3444/rtems-docs:

c-user: CONFIGURE\_INIT\_TASK\_CONSTRUCT\_STORAGE\_SIZE  
Document new configuration option CONFIGURE\_INIT\_TASK\_CONSTRUCT\_STORAGE\_SIZE.  
Close #4181.

**Comment 5**

1. **Sebastian Huber**, Fri, 27 Nov 2020 08:52:57 GMT

In 6e566bad/rtems:

config: CONFIGURE\_INIT\_TASK\_CONSTRUCT\_STORAGE\_SIZE  
Fix the documentation.  
Update #4181.

**Comment 6**

1. **Sebastian Huber**, Sat, 12 Dec 2020 12:53:44 GMT

In fcd9618a/rtems:

config: Fix invalid static assertions in C

Expressions in static assertions must be integral constant expressions. In integral constant expressions the use of address constant expressions is not allowed.

In static initializers the address constant expressions are allowed. Introduce a new macro `_CONFIGURE_ASSERT_NOT_NULL()` which leads to a compile time error if the second parameter is NULL. It generates error messages like this if for example

```
#define CONFIGURE_INIT_TASK_ENTRY_POINT NULL
```

is provided by the application:

```
cpukit/include/rtems/confdefs/inittask.h:51:26: error: size of unnamed array is negative
```

```
51 |     ( _type ) sizeof( int[ ( _value ) != NULL ? 1 : -1 ] ) )
```

```
|
```

```
cpukit/include/rtems/confdefs/inittask.h:170:3: note: in expansion of macro '_CONFIGURE_ASSERT_NOT_NULL'
```

```
170 |     _CONFIGURE_ASSERT_NOT_NULL(
```

```
| ~
```

This fix relates to CID 1470570 (PARSE\_ERROR).

Update #4181.

**Comment 7**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT

2. **keywords**: **qualification** added

**4184 - arm/bsps: Small MMU pages are rounded to 1 MiB**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4184">https://devel.rtems.org/ticket/4184</a> ( <a href="https://devel.rtems.org/ticket/4184">https://devel.rtems.org/ticket/4184</a> )
<b>Id</b>	4184
<b>Reporter</b>	Jan Sommer
<b>Created</b>	24 November 2020 08:33:45
<b>Modified</b>	15 December 2020 10:26:14
<b>Owner</b>	Jan Sommer <jan.sommer@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The function `arm_cp15_start_set_translation_table_entries` rounds the end address of a section up to 1 MiB even if small 4kiB pages are used (i.e. `ARM_MMU_USE_SMALL_PAGES` enabled).

Will submit a patch which only rounds the end address to 4kiB boundary.

**Comment 1**

1. **Jan Sommer**, Wed, 02 Dec 2020 12:38:22 GMT

To keep track of it during the Christmas break: The patch is here:

<https://lists.rtems.org/pipermail/devel/2020-November/063461.html>

**Comment 2**

1. **Jan Sommer**, Fri, 11 Dec 2020 05:54:46 GMT
2. **owner:** set to **Jan Sommer** <jan.sommer@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 1a7afb5/rtems:

```
bsps/arm: Fix MMU small pages support
For small tables only round to the next 4kiB instead of 1MiB
Close #4184.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 15 Dec 2020 10:26:14 GMT

In 0deeb02/rtems:

```
bsps/arm: Fix MMU configuration
Update #4184.
```

---

**4192 - bsp/xilinx\_zynq: Enable support for small MMU pages**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4192">https://devel.rtems.org/ticket/4192</a> ( <a href="https://devel.rtems.org/ticket/4192">https://devel.rtems.org/ticket/4192</a> )
<b>Id</b>	4192
<b>Reporter</b>	Jan Sommer
<b>Created</b>	27 November 2020 13:34:57
<b>Modified</b>	16 December 2021 16:11:44
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	minor
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Enable the xilinx\_zynq based BSPs to support the configuration of the MMU to use small 4 kiB pages.

By default 1 MB pages will be used. The 4 kiB pages have to be enabled with the ARM\_MMU\_USE\_SMALL\_PAGES configuration option.

**Comment 1**

1. **Jan Sommer**, Fri, 27 Nov 2020 13:45:49 GMT

Patch submitted: <https://lists.rtems.org/pipermail/devel/2020-November/063517.html>

**Comment 2**

1. **Kinsey Moore**, Thu, 16 Dec 2021 16:11:44 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

This should have been closed with commit cadbd7d15086b76dc4e5dd199e47b68d40006e6d

---

**4193 - devctl.h does not compile from C++ (cloned)**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4193">https://devel.rtems.org/ticket/4193</a> ( <a href="https://devel.rtems.org/ticket/4193">https://devel.rtems.org/ticket/4193</a> )
<b>Id</b>	4193
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	1 December 2020 13:48:43
<b>Modified</b>	1 December 2020 13:49:24
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	tool/newlib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4174:

The closing boilerplate of the C++ extern C wrapper is out of order with another #endif and the resulting code does not compile.

The attached patch addresses this but it needs to be merged to newlib and the RSB updated before this ticket closed.

**Comment 1**

1. **Sebastian Huber**, Tue, 01 Dec 2020 13:49:24 GMT
2. **owner**: set to **Sebastian Huber** <sebastian.huber@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In c576ec2/rtems-source-builder:

```
6/7: Update unstable RTEMS 6/7 tool chain
```

[Close #4193.](#)

## 4194 - RSB failed with mail subject: Build Linux: PASSED 6/rtems-arm on x86\_64-linux-gnu

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4194">https://devel.rtems.org/ticket/4194</a> ( <a href="https://devel.rtems.org/ticket/4194">https://devel.rtems.org/ticket/4194</a> )
<b>Id</b>	4194
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	1 December 2020 18:17:15
<b>Modified</b>	16 December 2021 15:47:03
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	worksforme
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

```
error: config error: gdb-common-1.cfg:99: "gdb: python: header file not found: python2.7/Python.h, please install"
Build FAILED
Mailing report: build@rtems.org
```

The mail subject should indicated that the build failed.

### Comment 1

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:47:03 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **worksforme**

Haven't seen a failed build with an incorrect header recently.

## 4195 - Add gr740 support available in SIS 2.25 to the RTEMS Tester

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4195">https://devel.rtems.org/ticket/4195</a> ( <a href="https://devel.rtems.org/ticket/4195">https://devel.rtems.org/ticket/4195</a> )
<b>Id</b>	4195
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 December 2020 09:16:21
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

### Comment 1

1. **Sebastian Huber**, Wed, 02 Dec 2020 09:39:10 GMT

In 97fe5bf/rtems-tools:

```
tester: Add support for sparc/gr740 BSP
```

Update #4195.

### Comment 2

1. **Sebastian Huber**, Wed, 02 Dec 2020 09:42:28 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



In 675e73f/rtems-source-builder:

```
devel/sis: Update to 2.25
Update #4195.
```

### **Comment 3**

1. **Sebastian Huber**, Wed, 02 Dec 2020 09:42:30 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In d79b044/rtems-source-builder:

```
6/7: Update to the latest rtems-tools
Close #4195.
```

### **Comment 4**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** **qualification** added

## **4196 - Improve gcov support provided by GCC for RTEMS**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4196">https://devel.rtems.org/ticket/4196</a> ( <a href="https://devel.rtems.org/ticket/4196">https://devel.rtems.org/ticket/4196</a> )
<b>Id</b>	4196
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 December 2020 09:38:15
<b>Modified</b>	29 June 2022 09:29:52
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	tool/gcc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	4670
<b>Blocked by</b>	

### **Description**

If we want to use gcov in RTEMS to get code coverage in all system states, then we need some tweaks in GCC:

<https://gcc.gnu.org/pipermail/gcc/2020-November/234164.html>

The linker set based gcov information registration is already included in GCC:

<https://gcc.gnu.org/onlinedocs/gcc/Instrumentation-Options.html#index-fprofile-info-section>

There is a discussion about how the gcov information can be transferred from the embedded system to the host:

<https://gcc.gnu.org/pipermail/gcc-patches/2020-November/559342.html>

The following patch set was integrated in GCC 13:

<https://gcc.gnu.org/pipermail/gcc-patches/2022-April/593536.html>

<https://gcc.gnu.org/onlinedocs/gcc/Freestanding-Environments.html#Freestanding-Environments>

### **Attachments:**

- 
- 1 **Sebastian Huber, Wed, 02 Dec 2020 09:54:29 GMT**  
attach: set to [0001-gcov-Add-fprofile-info-section-support.patch](https://devel.rtems.org/ticket/4196/0001-gcov-Add-fprofile-info-section-support.patch) (https://devel.rtems.org/ticket/4196/0001-gcov-Add-fprofile-info-section-support.patch)
  - 2 **Sebastian Huber, Wed, 21 Jul 2021 09:44:53 GMT**  
attach: set to [0001-gcov-Fix-use-of-profile-info-section.patch](https://devel.rtems.org/ticket/4196/0001-gcov-Fix-use-of-profile-info-section.patch) (https://devel.rtems.org/ticket/4196/0001-gcov-Fix-use-of-profile-info-section.patch)
  - 3 **Sebastian Huber, Wed, 21 Jul 2021 09:45:10 GMT**  
attach: set to [0002-gcov-Add-gcov-info-to-gdca.patch](https://devel.rtems.org/ticket/4196/0002-gcov-Add-gcov-info-to-gdca.patch) (https://devel.rtems.org/ticket/4196/0002-gcov-Add-gcov-info-to-gdca.patch)
  - 4 **Sebastian Huber, Wed, 21 Jul 2021 13:33:53 GMT**  
attach: set to [0001-Remove-wrong-bail-out-in-prune\\_topn\\_counter.patch](https://devel.rtems.org/ticket/4196/0001-Remove-wrong-bail-out-in-prune_topn_counter.patch) (https://devel.rtems.org/ticket/4196/0001-Remove-wrong-bail-out-in-prune\_topn\_counter.patch)
  - 5 **Sebastian Huber, Fri, 06 Aug 2021 15:24:11 GMT**  
attach: set to [0001-Back-port-gcov-info-to-gcda-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-gcov-info-to-gcda-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-gcov-info-to-gcda-to-GCC-10.patch)
  - 6 **Sebastian Huber, Mon, 09 Aug 2021 15:29:56 GMT**  
attach: set to [0001-Back-port-v2-of-gcov-info-to-gcda-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v2-of-gcov-info-to-gcda-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v2-of-gcov-info-to-gcda-to-GCC-10.patch)
  - 7 **Sebastian Huber, Mon, 09 Aug 2021 18:44:12 GMT**  
attach: set to [0001-Back-port-v3-of-gcov-info-to-gcda-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v3-of-gcov-info-to-gcda-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v3-of-gcov-info-to-gcda-to-GCC-10.patch)
  - 8 **Sebastian Huber, Mon, 30 Aug 2021 08:48:43 GMT**  
attach: set to [0001-Back-port-v4-of-gcov-info-to-gcda-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v4-of-gcov-info-to-gcda-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v4-of-gcov-info-to-gcda-to-GCC-10.patch)
  - 9 **Sebastian Huber, Mon, 30 Aug 2021 12:02:33 GMT**  
attach: set to [0001-Back-port-v5-of-gcov-info-to-gcda-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v5-of-gcov-info-to-gcda-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v5-of-gcov-info-to-gcda-to-GCC-10.patch)
- 
- 1 **Sebastian Huber, Tue, 03 May 2022 06:13:16 GMT**  
0  
attach: set to [0001-Back-port-v1-of-gcov-tool-merge-stream-to-GCC-12.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v1-of-gcov-tool-merge-stream-to-GCC-12.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v1-of-gcov-tool-merge-stream-to-GCC-12.patch)
  - 1 **Sebastian Huber, Tue, 21 Jun 2022 07:15:58 GMT**  
1  
attach: set to [0001-Back-port-v6-of-gcov-improvements-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v6-of-gcov-improvements-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v6-of-gcov-improvements-to-GCC-10.patch)
  - 1 **Sebastian Huber, Wed, 29 Jun 2022 07:19:49 GMT**  
2  
attach: set to [0001-Back-port-v7-of-gcov-improvements-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v7-of-gcov-improvements-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v7-of-gcov-improvements-to-GCC-10.patch)
  - 1 **Sebastian Huber, Wed, 29 Jun 2022 08:31:28 GMT**  
3  
attach: set to [0001-Back-port-v8-of-gcov-improvements-to-GCC-10.patch](https://devel.rtems.org/ticket/4196/0001-Back-port-v8-of-gcov-improvements-to-GCC-10.patch) (https://devel.rtems.org/ticket/4196/0001-Back-port-v8-of-gcov-improvements-to-GCC-10.patch)
- 

**Comment 1**

- 1. **Sebastian Huber, Wed, 02 Dec 2020 10:24:27 GMT**

In 1d9f5d0/rtems-source-builder:

```
6: Add support for gcov info section
Update #4196.
```

**Comment 2**

- 1. **Sebastian Huber, Fri, 18 Jun 2021 09:24:45 GMT**
- 2. **keywords:** qualification added

**Comment 3**

- 1. **Sebastian Huber, Fri, 06 Aug 2021 05:33:18 GMT**

The `__gcov_info_to_gcda()` function is now integrated in GCC:

<https://gcc.gnu.org/git/?p=gcc.git;a=commit;h=9124bbe1857f0d3a3015d6461d5f8d04f07cab85>

**Comment 4**

- 1. **Sebastian Huber, Fri, 06 Aug 2021 16:39:49 GMT**
- 2. **status:** changed from **assigned** to **closed**
- 3. **resolution:** set to **fixed**

In 6c0d7b6/rtems-source-builder:

```
6: Back port gcov_info_to_gcda() to GCC 10
Close #4196.
```

**Comment 5**

- 1. **Sebastian Huber, Mon, 09 Aug 2021 15:21:01 GMT**

There are issues with multi-threaded programs:

<https://gcc.gnu.org/pipermail/gcc/2021-August/237058.html>

#### **Comment 6**

1. **Sebastian Huber**, Mon, 09 Aug 2021 15:59:04 GMT

In ca5c27d/rtems-source-builder:

6: Back port v2 of gcov\_info\_to\_gcda() to GCC 10  
Update #4196.

#### **Comment 7**

1. **Sebastian Huber**, Mon, 09 Aug 2021 19:05:23 GMT

In ec495e0/rtems-source-builder:

6: Back port v3 of gcov\_info\_to\_gcda() to GCC 10  
Update #4196.

#### **Comment 8**

1. **Sebastian Huber**, Wed, 01 Sep 2021 15:50:46 GMT

In a1f7b3b/rtems-source-builder:

6: Back port v5 of gcov\_info\_to\_gcda() to GCC 10  
Update #4196.

#### **Comment 9**

1. **Sebastian Huber**, Tue, 03 May 2022 06:01:44 GMT

2. **description**: modified (diff)

#### **Comment 10**

1. **Sebastian Huber**, Wed, 04 May 2022 05:47:29 GMT

In 22e32ec/rtems-source-builder:

7: Back port gcov-tool merge-stream to GCC 12  
Update #4196.

#### **Comment 11**

1. **Sebastian Huber**, Tue, 21 Jun 2022 14:16:49 GMT

In cf0914f/rtems-source-builder:

6: Back port v6 of gcov improvements to GCC 10  
Update #4196.

#### **Comment 12**

1. **Sebastian Huber**, Tue, 28 Jun 2022 06:38:43 GMT

2. **blocking**: set to **4670**

#### **Comment 13**

1. **Sebastian Huber**, Wed, 29 Jun 2022 09:29:52 GMT

In 9474bb8/rtems-source-builder:

6: Back port v8 of gcov improvements to GCC 10

## **4197 - testsuite: ts-validation-0 broken on AArch64 due to SIZE\_MAX issues in the test design**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4197">https://devel.rtems.org/ticket/4197</a> ( <a href="https://devel.rtems.org/ticket/4197">https://devel.rtems.org/ticket/4197</a> )
<b>Id</b>	4197
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	2 December 2020 20:28:40
<b>Modified</b>	4 March 2021 08:12:53
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

The ts-validation-0 test is broken on AArch64 LP64 ABI due to issues with unexpected values of SIZE\_MAX. I was not familiar enough with the test architecture in use to debug it properly. This test passes under the ILP32 ABI due to the 32bit pointers and differing value of SIZE\_MAX.

### **Comment 1**

1. **Chris Johns**, Mon, 15 Feb 2021 06:51:39 GMT

Which test architecture are you referring too?

### **Comment 2**

1. **Sebastian Huber**, Mon, 15 Feb 2021 09:36:48 GMT

This is a general 64-bit issue.

### **Comment 3**

1. **Kinsey Moore**, Mon, 15 Feb 2021 14:39:48 GMT

We actually found some time to dive into this recently and, as expected, it's just a one-line tweak to fix it. I'll post a patch shortly.

Chris, The test architecture I'm referring to is how the validation test sets up a large battery of repetitive checks.

### **Comment 4**

1. **Sebastian Huber**, Thu, 04 Mar 2021 08:12:53 GMT
2. **status**: changed from **new** to **closed**
3. **version**: set to **6**
4. **resolution**: set to **fixed**
5. **milestone**: set to **6.1**

Fixed by 8fe59be236e7f2047adb6e393639bbf56bbd996d.

---

## **4198 - arm: Add multilib for Cortex-R52 processor**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4198">https://devel.rtems.org/ticket/4198</a> ( <a href="https://devel.rtems.org/ticket/4198">https://devel.rtems.org/ticket/4198</a> )
<b>Id</b>	4198
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	3 December 2020 07:59:08
<b>Modified</b>	26 January 2022 10:01:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This processor uses the ARMv8-R instruction set.

**Comment 1**

1. **Sebastian Huber**, Thu, 03 Dec 2020 19:34:38 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 9ef9956/rtems-source-builder:

```
6/7: Add multilib for ARM Cortex-R52 processor
Close #4198.
```

**Comment 2**

1. **Sebastian Huber**, Fri, 04 Dec 2020 06:16:30 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

There is an issue with the memchr() implementation provided by Newlib:

```
File: /opt/rtems/6/lib/gcc/arm-rtems6/10.2.1/../../../../arm-rtems6/lib/thumb/cortex-r52/hard/libc.a(lib_a-memchr.o)
Attribute Section: aeabi
File Attributes
Tag_CPU_name: "7-A"
Tag_CPU_arch: v7
Tag_CPU_arch_profile: Application
Tag_ARM_ISA_use: Yes
Tag_THUMB_ISA_use: Thumb-2
Tag_FP_arch: VFPv3
Tag_Advanced SIMD_arch: NEONv1
```

**Comment 3**

1. **Sebastian Huber**, Tue, 15 Dec 2020 09:35:09 GMT

In 96c1e17/rtems-source-builder:

```
6/7: Update unstable RTEMS 6/7 tool chain
This update includes a fix for the ARM Cortex-R52 support in Newlib.
Update #4198.
```

**Comment 4**

1. **Sebastian Huber**, Wed, 26 Jan 2022 10:01:55 GMT
  2. **status:** changed from **reopened** to **closed**
  3. **resolution:** set to **fixed**
- 

**4200 - Build system doco link in the User Guide is broken**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4200">https://devel.rtems.org/ticket/4200</a> ( <a href="https://devel.rtems.org/ticket/4200">https://devel.rtems.org/ticket/4200</a> )
<b>Id</b>	4200
<b>Reporter</b>	Chris Johns
<b>Created</b>	9 December 2020 00:59:36
<b>Modified</b>	29 November 2022 23:26:11
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

<https://docs.rtems.org/branches/master/user/bld/index.html#commands>

The "RTEMS Software Engineering" guide link at the end of this section is to a .rst file.

I think cross-doc links is broken no matter how you attempt to solve this, ie PDF files will never work.

**Comment 1**

1. **Chris Johns**, Wed, 09 Dec 2020 01:02:36 GMT

There are cross doco links in the engineering manual. These are also broken.

**Comment 2**

1. **Chris Johns**, Tue, 29 Nov 2022 23:26:11 GMT
  2. **status**: changed from **new** to **closed**
  3. **resolution**: set to **fixed**
- 

**4201 - waf building out of source tree does not find all configured bsps**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4201">https://devel.rtems.org/ticket/4201</a> ( <a href="https://devel.rtems.org/ticket/4201">https://devel.rtems.org/ticket/4201</a> )
<b>Id</b>	4201
<b>Reporter</b>	Chris Johns
<b>Created</b>	9 December 2020 01:46:10
<b>Modified</b>	29 November 2022 23:27:25
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

config.ini is:

```
[DEFAULT]
BUILD_TESTS = False
RTEMS_DEBUG = True
RTEMS_POSIX_API = True
[arm/beagleboneblack]
[arm/xilinx_zynq_a9_qemu]
[i386/pc686]
[powerpc/mvme2307]
```

And configure is:

```

$ /opt/work/chris/rtems/kernel/rtems.git/waf \
  --top=/opt/work/chris/rtems/kernel/rtems.git \
  --out=build configure \
  --rtems-config=config.ini \
  --prefix=/opt/work/chris/rtems/nfs/6
Setting top to : /opt/work/chris/rtems/kernel/rtems.git
Setting out to : /opt/work/chris/rtems/nfs/bsps/build
Configure board support package (BSP) : powerpc/mvme2307
Checking for program 'powerpc-rtems6-gcc' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-gcc
Checking for program 'powerpc-rtems6-g++' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-g++
Checking for program 'powerpc-rtems6-ar' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-ar
Checking for program 'powerpc-rtems6-ld' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-ld
Checking for program 'ar' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-ar
Checking for program 'g++, c++' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-g++
Checking for program 'ar' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-ar
Checking for program 'gas, gcc' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-gcc
Checking for program 'ar' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-ar
Checking for program 'gcc, cc' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-gcc
Checking for program 'ar' : /opt/work/chris/rtems/nfs/6/bin/powerpc-rtems6-ar
Checking for asm flags '-MMD' : yes
Checking for c flags '-MMD' : yes
Checking for cxx flags '-MMD' : yes
Checking for program 'rtems-bin2c' : /opt/work/chris/rtems/nfs/6/bin/rtems-bin2c
Checking for program 'gzip' : /usr/bin/gzip
Checking for program 'rtems-ld' : /opt/work/chris/rtems/nfs/6/bin/rtems-ld
Checking for program 'rtems-syms' : /opt/work/chris/rtems/nfs/6/bin/rtems-syms
Checking for program 'xz' : /usr/bin/xz
'configure' finished successfully (0.245s)

```

The same config.ini in the source tree finds all configured bsps.

Being able to cleanly sandbox builds is a feature of the autotools build system.

#### Comment 1

1. **Sebastian Huber**, Wed, 09 Dec 2020 05:55:53 GMT

I guess the issue is that it finds a "config.ini" in the source tree since this is the current working directory of the wscript process.

For a discussion of out of tree builds see:

<https://lists.rtems.org/pipermail/devel/2020-November/063066.html>

#### Comment 2

1. **Chris Johns**, Tue, 29 Nov 2022 23:27:25 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

## 4202 - Add BSP for ARM Fixed Virtual Platform with a Cortex-R52

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4202">https://devel.rtems.org/ticket/4202</a> ( <a href="https://devel.rtems.org/ticket/4202">https://devel.rtems.org/ticket/4202</a> )
<b>Id</b>	4202
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	9 December 2020 13:31:40
<b>Modified</b>	22 September 2022 05:55:24
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

#### Comment 1

1. **Sebastian Huber**, Wed, 09 Dec 2020 16:32:14 GMT

In 9ce47a5/rtems:

```

bsps: Add SMP support to ARM GICv3
Update #4202.

```

#### Comment 2

1. **Sebastian Huber**, Thu, 10 Dec 2020 08:08:19 GMT

In 9955487d/rtems:

arm: Support Armv8 in  
Update #4202.

### **Comment 3**

1. **Sebastian Huber**, Thu, 10 Dec 2020 08:08:22 GMT

In e68827e/rtems:

arm/cache-cp15: Support Armv8  
Update #4202.

### **Comment 4**

1. **Sebastian Huber**, Thu, 10 Dec 2020 08:08:26 GMT

In 5efa15b/rtems:

bsps/arm: Unify ARM Generic Timer options  
Update #4202.

### **Comment 5**

1. **Sebastian Huber**, Thu, 10 Dec 2020 08:08:29 GMT

In bd7bef52/rtems:

bsps/arm: Support system level ARM Generic Timer  
Update #4202.

### **Comment 6**

1. **Sebastian Huber**, Thu, 10 Dec 2020 08:08:32 GMT

In 617aeaf5/rtems:

bsps/arm: Move BSP\_START\_IN\_HYP\_SUPPORT option  
Clarify documentation.  
Update #4202.

### **Comment 7**

1. **Sebastian Huber**, Thu, 10 Dec 2020 15:19:15 GMT

In b6925e1/rtems:

bsps: Fix GICv3 arm\_gic\_trigger\_sgi()  
Use the targets parameter to determine the targets of the SGI. Change targets parameter type to 32-bit to ease the parameter passing. GICv3 supports up to 16 targets.  
Update #4202.

### **Comment 8**

1. **Sebastian Huber**, Thu, 10 Dec 2020 15:19:18 GMT

In 105e520/rtems:

bsps: Remove ARM GIC SGI target filter  
Remove the target filter for software-generated interrupts since this feature is not supported by the affinity routing in GICv3.  
Update #4202.

### **Comment 9**



1. **Sebastian Huber**, Thu, 17 Dec 2020 14:32:46 GMT

In 747fb65/rtems:

```
bsps: Add GICv3 arm_gic_irq_processor_count()
Update #4202.
```

#### **Comment 10**

1. **Sebastian Huber**, Thu, 17 Dec 2020 14:32:50 GMT

In b5aceef/rtems:

```
bsps: Remove gicvx_interrupt_dispatch()
Avoid one level of indirection.
Update #4202.
```

#### **Comment 11**

1. **Sebastian Huber**, Thu, 17 Dec 2020 14:32:53 GMT

In a299c4fe/rtems:

```
arm: Optimize arm_interrupt_disable()
Update #4202.
```

#### **Comment 12**

1. **Sebastian Huber**, Wed, 23 Dec 2020 09:26:50 GMT

In be5eee57/rtems:

```
libdebugger: Fix for Armv8-R
This architecture variant has no MMU.
Update #4202.
```

#### **Comment 13**

1. **Sebastian Huber**, Wed, 23 Dec 2020 09:26:54 GMT

In 39ef7e5/rtems:

```
bsps: Fix includes
Update #4202.
```

#### **Comment 14**

1. **Sebastian Huber**, Wed, 23 Dec 2020 09:26:57 GMT

In 6944cd10/rtems:

```
arm: Add header file for AArch32 System Registers
Update #4202.
```

#### **Comment 15**

1. **Sebastian Huber**, Wed, 23 Dec 2020 09:27:00 GMT

In 854ea2b/rtems:

```
arm: Add support for Arm PMSAv8-32
Update #4202.
```

#### **Comment 16**

**1. Sebastian Huber, Wed, 23 Dec 2020 09:27:03 GMT**

In 272534e/rtems:

`bsps/arm: Set VBAR in start.S`Set the VBAR to the vector table in the start section before `bsp_start_hook_0()` is called to earlier handle exceptions in RTEMS.Set the VBAR to the normal vector table in `start.S` for the main processor. Secondary processors set it in `bsp_start_hook_0()`.

Update #4202.

**Comment 17****1. Sebastian Huber, Wed, 23 Dec 2020 09:27:07 GMT**

In 76a1a53/rtems:

`bsps/arm: Invalidate branch predictors earlier`

Make sure the branch predictors are invalidated before the first branch is executed.

Update #4202.

**Comment 18****1. Sebastian Huber, Wed, 23 Dec 2020 09:27:10 GMT**

In 46a3c04/rtems:

`bsps/arm: Remove optional start hook arguments`

The start hook arguments are not used by a BSP. Removing them avoids the need for a stack during the very early system initialization.

Update #4202.

**Comment 19****1. Sebastian Huber, Wed, 23 Dec 2020 09:27:13 GMT**

In b32fd227/rtems:

`bsps/arm: Add arm-data-cache-loop-set-way.h`

This makes it possible to reuse this loop.

Update #4202.

**Comment 20****1. Sebastian Huber, Wed, 23 Dec 2020 09:27:17 GMT**

In e164df5e/rtems:

`bsps/arm: Clear SCTL[R, I, A, C] in start.S`

Initialize the data and unified cache levels. Invalidate the instruction cache levels.

Update #4202.

**Comment 21****1. Sebastian Huber, Wed, 23 Dec 2020 09:27:20 GMT**

In 23d9223a/rtems:

`bsps/arm: Invalidate TLB in start.S`

Update #4202.

**Comment 22****1. Sebastian Huber, Wed, 23 Dec 2020 09:27:23 GMT**

In 9f3a08e/rtems:

`bsps: Use header file for GIC architecture support`

This avoids a function call overhead in the interrupt dispatching.  
Update #4202.

### **Comment 23**

1. **Sebastian Huber**, Wed, 23 Dec 2020 09:27:27 GMT

In 016bcb3/rtems:

bsps/arm: Rely on initialized vector table  
The `arm_cp15_set_exception_handler()` is a complicated function which should be avoided if possible.  
Update #4202.

### **Comment 24**

1. **Sebastian Huber**, Wed, 23 Dec 2020 09:27:30 GMT

In 81c7f5be/rtems:

arm/fvp: New BSP  
This BSP supports the Arm Fixed Virtual Platform. Only the Cortex-R52 processor configuration is supported by the BSP. It should be easy to add support for other variants if needed.  
Update #4202.

### **Comment 25**

1. **Sebastian Huber**, Mon, 04 Jan 2021 05:12:11 GMT

In 90342fe/rtems-tools:

tester: Add support for `arm/fvp_cortex_r52` BSP  
Update #4202.

### **Comment 26**

1. **Sebastian Huber**, Mon, 04 Jan 2021 09:59:30 GMT

In 1e9c608/rtems-source-builder:

6/7: Update to the latest `rtems-tools`  
Update #4202.

### **Comment 27**

1. **Sebastian Huber**, Mon, 07 Jun 2021 07:41:26 GMT

In 2d1c494f/rtems:

arm/fvp: Remove unused GICv2 BSP option  
Update #4202.

### **Comment 28**

1. **Sebastian Huber**, Mon, 07 Jun 2021 07:41:29 GMT

In 55ce66ca/rtems:

arm/fvp: Fix integer from pointer without a cast  
Update #4202.

### **Comment 29**

1. **Sebastian Huber**, Wed, 16 Jun 2021 15:49:05 GMT

In f89a527/rtems:

arm: Fix parameter use in AARCH32\_PMSA\_MEM\_ATTR()  
Update #4202.

### **Comment 30**

1. **Sebastian Huber**, Tue, 29 Jun 2021 12:59:30 GMT

In 13b18d12/rtems:

arm: Disable alignment check in PMSA init  
Disable the alignment check through SCTLRA in \_AArch32\_PMSA\_Initialize().  
Update #4202.

### **Comment 31**

1. **Sebastian Huber**, Tue, 29 Jun 2021 12:59:34 GMT

In b357680/rtems:

arm: Fix AArch32 memory attribute defines  
Update #4202.

### **Comment 32**

1. **Sebastian Huber**, Tue, 29 Jun 2021 12:59:37 GMT

In 9b84adb/rtems:

arm: Fix AARCH32\_PMSA\_ATTR\_XN value  
Update #4202.

### **Comment 33**

1. **Sebastian Huber**, Tue, 29 Jun 2021 12:59:41 GMT

In bb9a4b8/rtems:

arm: For AArch32 use non-shareable memory  
The Cortex-R52 does not support cache coherency and the shareable memory attribute. If a region is configured to be shareable, then it falls back to use non-cacheable memory.  
Update #4202.

### **Comment 34**

1. **Sebastian Huber**, Tue, 30 Nov 2021 07:11:55 GMT

In 7fec89e2/rtems:

arm: Fix AARCH32\_PMSA\_DATA\_READ\_WRITE\_CACHED  
Fix definition of AARCH32\_PMSA\_DATA\_READ\_WRITE\_CACHED. Since AARCH32\_PMSA\_ATTR\_AP\_EL1\_RW\_EL0\_NO is zero, this fix is only cosmetic.  
Update #4202.

### **Comment 35**

1. **Sebastian Huber**, Tue, 30 Nov 2021 07:11:59 GMT

In 73305a1/rtems:

arm: Add AARCH32\_PMSA\_DATA\_READ\_WRITE\_DEFAULT  
Add default memory attributes for read-write data. The actual attributes depend on the RTEMS\_SMP build option.  
Update #4202.

### **Comment 36**

1. **Sebastian Huber**, Wed, 08 Jun 2022 07:04:47 GMT

In 0b9497a/rtems:

arm: Fix PMSA region mapping with 0x0 end address

A section may span up to the end of the address range. In this case the end address is zero. Use the base address to check if a region should be before another region.

Update #4202.

### **Comment 37**

1. **Sebastian Huber**, Wed, 08 Jun 2022 07:04:49 GMT

In c93f0f01/rtems:

arm: Fix PMSA regions for contiguous sections

Sections with identical attributes may be contiguous with a respective begin and end address which is not on a minimum region boundary. The begin address is aligned down to the region base address. The end address is aligned up to the region end address. Account for this in the check for contiguous sections.

Update #4202.

### **Comment 38**

1. **Sebastian Huber**, Fri, 09 Sep 2022 05:41:43 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 13be9a2/rtems-docs:

user: Document arm/fvp BSP

Close #4202.

### **Comment 39**

1. **Sebastian Huber**, Thu, 22 Sep 2022 05:55:24 GMT

In f6e7c627/rtems:

bsps/arm: Mark functions in start.S

Add the function type to `_start()` and `bsp_start_hook_0_done()` so that the linker can generate ARM/Thumb interworking code.

Update #4202.

---

## **4204 - Make Termination Handler which Prints Exit Information Less Scary**

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4204">https://devel.rtems.org/ticket/4204</a> ( <a href="https://devel.rtems.org/ticket/4204">https://devel.rtems.org/ticket/4204</a> )
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	9 December 2020 23:54:18
<b>Modified</b>	16 December 2021 15:39:48
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

This task is change the default termination handler to print successful exit when the cause was `exit(0)`. It scares users to see it and requires explanation.

### **Comment 1**

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:39:48 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

This was implemented by Chris Johns.

---

## **4206 - aarch64/xilinx\_zynqmp\_ip64 does not run with RTEMS\_DEBUG enabled**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4206">https://devel.rtems.org/ticket/4206</a> ( <a href="https://devel.rtems.org/ticket/4206">https://devel.rtems.org/ticket/4206</a> )
<b>Id</b>	4206
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	22 December 2020 12:45:04
<b>Modified</b>	5 March 2021 14:06:35
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

qemu-system-aarch64 -serial null -serial mon:stdio -machine xlnx-zcu102 -m 4096 -kernel build/aarch64/xilinx\_zynqmp\_ip64/testsuites/samples/ticker.exe -nographic

```
*** FATAL ***
fatal source: 7 (RTEMS_FATAL_SOURCE_ASSERT)
fatal code: 1074874896 (0x40114a10)
RTEMS version: 6.0.0.644cd68d8ce0044f78f095a648bfe4c1567f351b
RTEMS tools: 10.2.1 20201215 (RTEMS 6, RSB 6d0bff0eb6ed35d180491614b976277d5469a302, Newlib 6cc47c4)
executing thread ID: 0x08a010001
executing thread name: UI1
assertion "cpu_self->thread_dispatch_disable_level == 1" failed: file
"/home/EB/sebastian h/src/rtems/cpukit/score/src/threadhandler.c", line 120, function: Thread Handler
```

### **Comment 1**

1. **Sebastian Huber**, Tue, 22 Dec 2020 12:45:23 GMT
2. **owner:** set to **Joel Sherrill**

### **Comment 2**

1. **Sebastian Huber**, Fri, 05 Mar 2021 14:06:35 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 61d688bf/rtems:

```
aarch64: Fix context switch
The Per_CPU_Control::isr_dispatch_disable is a 32-bit integer.
Close #4206.
```

---

## **4207 - PZERO define in RTEMS is wrong**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4207">https://devel.rtems.org/ticket/4207</a> ( <a href="https://devel.rtems.org/ticket/4207">https://devel.rtems.org/ticket/4207</a> )
<b>Id</b>	4207
<b>Reporter</b>	Chris Johns
<b>Created</b>	23 December 2020 19:07:30
<b>Modified</b>	7 January 2021 22:54:34
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Our libbsd support in RTEMS defines PZERO to be zero. FreeBSD defines PZERO to be (PRI\_MIN\_KERN + 20) and PRI\_MIN\_KERN is 80.

The `__sleep()` call uses bits allocated above the bits used to hold the highest priority to signal things to do. The PDROP (0x200) bit causes a lock to be dropped before sleeping and not reclaimed after.

Setting PZERO to 0 breaks FreeBSD code in libbsd because calls that end up in `__sleep()` can incorrectly have the PDROP bit set. A grep of FreeBSD shows how this happens:

```
(void) nfsmsleep(&lp->nfslock_lock, mutex,
                PZERO - 1, "nfsv4qr", NULL);
```

```
error = msleep(msgqptr, &msg_mtx, (PZERO - 4) | PCATCH,
              msgsnd, hz);
```

This examples shows how either side is used...

```
selwakeuppri(&tp->tun rsel, PZERO + 1);
```

### Comment 1

1. **Chris Johns**, Wed, 23 Dec 2020 19:23:03 GMT
2. **description:** modified (diff)
3. **summary:** changed from **PZERO define in newlib is wrong** to **PZERO define in RTEMS is wrong**

### Comment 2

1. **Chris Johns**, Thu, 07 Jan 2021 22:54:34 GMT
2. **owner:** set to **Chris Johns <chrisj@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 7696533/rtems:

```
cpukit: Merge FreeBSD values for the priorities
```

```
It seems we need valid values or assumptions in the FreeBSD about these values breaks some of the code.
```

```
Closes #4207
```

## 4209 - STM32H743ZI Nucleo Console support not working without workaround

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4209">https://devel.rtems.org/ticket/4209</a> ( <a href="https://devel.rtems.org/ticket/4209">https://devel.rtems.org/ticket/4209</a> )
<b>Id</b>	4209
<b>Reporter</b>	rmueller
<b>Created</b>	2 January 2021 14:39:38
<b>Modified</b>	29 November 2022 22:51:15
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	stm32
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

I think here is still some issue with the HUART3 console support, at least for the STM32H743ZI-Nucleo board.

I solves the issue by calling some hardware initializaton functions and override void HAL\_UART\_MspInit(UART\_HandleTypeDef\* huart) like this:

```
#include "hardware_init.h"
#include
#include
void hardware_init() {
  MX_USART3_UART_Init(115200);
}
/**
 * ST-LINK UART3
 * CN5 pins on board
 */
UART_HandleTypeDef huart3;
GPIO_InitTypeDef gpio_uart_init_struct;
void MX_USART3_UART_Init(uint32_t baudRate)
{
  __HAL_RCC_USART3_CONFIG(RCC_USART3CLKSOURCE_HSI);
  __HAL_RCC_GPIOC_CLK_ENABLE();
  __HAL_RCC_USART3_CLK_ENABLE();
  int result;
  huart3.Instance = USART3;
  huart3.Init.BaudRate = baudRate;
  huart3.Init.WordLength = UART_WORDLENGTH_8B;
  huart3.Init.StopBits = UART_STOPBITS_1;
  huart3.Init.Parity = UART_PARITY_NONE;
  huart3.Init.Mode = UART_MODE_TX_RX;
  huart3.Init.HwFlowCtl = UART_HWCONTROL_NONE;
  huart3.Init.OverSampling = UART_OVERSAMPLING_16;
  huart3.Init.OneBitSampling = UART_ONE_BIT_SAMPLE_DISABLE;
  huart3.Init.ClockPrescaler = UART_PRESCALER_DIV1;
  //huart3.Init.FIFOMode = UART_FIFOMODE_DISABLE;
  //huart3.Init.TXFIFOThreshold = UART_TXFIFO_THRESHOLD_1_8;
  //huart3.Init.RXFIFOThreshold = UART_RXFIFO_THRESHOLD_1_8;
  huart3.AdvancedInit.AdvFeatureInit = UART_ADVFEATURE_NO_INIT;
  // we can't do error handling (simple print out first) here because UART3 is our print interface
  result = HAL_UART_Init(&huart3);
  if(result == HAL_OK) {
    printf("\rUART3 configured successfully!\r\n");
  }
}
// Will be called by HAL_UART_Init
void HAL_UART_MspInit(UART_HandleTypeDef* huart) {
  /*Configure GPIO pins : PD8 PD9 */
  gpio_uart_init_struct.Pin = GPIO_PIN_8|GPIO_PIN_9;
  gpio_uart_init_struct.Mode = GPIO_MODE_AF_PP;
  gpio_uart_init_struct.Pull = GPIO_NOPULL;
  gpio_uart_init_struct.Speed = GPIO_SPEED_FREQ_LOW;
  gpio_uart_init_struct.Alternate = GPIO_AF7_USART3;
  HAL_GPIO_Init(GPIOC, &gpio_uart_init_struct);
}
```

I then call hardware\_init() from my main application and after that, printf is working properly. Maybe the problem is also related to using the Nucleo board?

Kind Regards  
Robin

**Attachments:**

- 1 **rmueller, Sat, 02 Jan 2021 14:41:11 GMT**  
attach: set to [hardware\\_init.c \(https://devel.rtems.org/ticket/4209/hardware\\_init.c\)](https://devel.rtems.org/ticket/4209/hardware_init.c)
- 2 **rmueller, Sat, 02 Jan 2021 14:42:08 GMT**  
attach: set to [hardware\\_init.h \(https://devel.rtems.org/ticket/4209/hardware\\_init.h\)](https://devel.rtems.org/ticket/4209/hardware_init.h)
- 3 **rmueller, Mon, 04 Jan 2021 15:16:22 GMT**  
attach: set to [nucleo-stm32.patch \(https://devel.rtems.org/ticket/4209/nucleo-stm32.patch\)](https://devel.rtems.org/ticket/4209/nucleo-stm32.patch)
- 4 **rmueller, Tue, 05 Jan 2021 22:50:06 GMT**  
attach: set to [nucleo-stm32-patch2.patch \(https://devel.rtems.org/ticket/4209/nucleo-stm32-patch2.patch\)](https://devel.rtems.org/ticket/4209/nucleo-stm32-patch2.patch)
- 5 **rmueller, Wed, 06 Jan 2021 11:46:55 GMT**  
attach: set to [stm32h7-doc.patch \(https://devel.rtems.org/ticket/4209/stm32h7-doc.patch\)](https://devel.rtems.org/ticket/4209/stm32h7-doc.patch)

**Comment 1**

1. **rmueller, Sat, 02 Jan 2021 18:33:13 GMT**

I found the UART config in console-uart3.c

```
static const stm32h7_uart_config stm32h7_usart3_config = {
  .gpio = {
    .regs = GPIOB,
    .config = {
      .Pin = GPIO_PIN_9 | GPIO_PIN_10,
      .Mode = GPIO_MODE_AF_PP,
      .Pull = GPIO_NOPULL,
      .Speed = GPIO_SPEED_FREQ_LOW,
      .Alternate = GPIO_AF7_USART3
    }
  },
  .irq = USART3_IRQn,
  .device_index = 2
};
```

and tried to replace it with this:



```
static const stm32h7_uart_config stm32h7_usart3_config = {
    .gpio = {
        .regs = GPIOD,
        .config = {
            .Pin = GPIO_PIN_8 | GPIO_PIN_9,
            .Mode = GPIO_MODE_AF_PP,
            .Pull = GPIO_NOPULL,
            .Speed = GPIO_SPEED_FREQ_LOW,
            .Alternate = GPIO_AF7_USART3
        }
    },
    .irq = USART3_IRQn,
    .device_index = 2
};
```

Recompiled the BSP but it still is not working without the workaround from above. If I call printf, the function also never exits and something appears to be broken.. I don't really know why..

#### Comment 2

1. **Sebastian Huber**, Sun, 03 Jan 2021 10:14:39 GMT

The clocks are not initialized by the current console driver.

For a custom board initialization, you can provide the data structures defined in `bsps/arm/stm32h7/start/stm32h7-config.c` in your application configuration.

#### Comment 3

1. **rmueller**, Mon, 04 Jan 2021 15:19:13 GMT

Thanks, it works now. I am not sure, maybe I did not rebuild the BSP properly. I supplied a patch for this particular STM32H7 board configuration so users just have to set an option in `config.ini` to true for the STM32H743ZI-Nucleo board.

Kind Regards Robin

#### Comment 4

1. **Sebastian Huber**, Mon, 04 Jan 2021 18:23:47 GMT

In `affc8de/rtems`:

```
bsp/stm32h7: Split start configuration
This allows applications to individually provide configuration structures.
Update #4209.
```

#### Comment 5

1. **Sebastian Huber**, Mon, 04 Jan 2021 18:23:50 GMT

In `6600585f/rtems`:

```
bsp/stm32h7: Split console configuration
This allows applications to individually provide configuration structures.
Update #4209.
```

#### Comment 6

1. **Sebastian Huber**, Thu, 08 Sep 2022 14:31:42 GMT

There were some updates to the BSP. Is this issue still open?

#### Comment 7

1. **Chris Johns**, Tue, 29 Nov 2022 22:25:20 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**
4. **component**: changed from **admin** to **arch/arm**

Closing as the patches have not been applied.

If these changes are still valid please reopen and apply the attached patches.

#### Comment 8

1. **Chris Johns**, Tue, 29 Nov 2022 22:44:32 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution**: **fixed** deleted

The patches have been confirmed as suitable to be applied.

**Comment 9**

1. **Chris Johns**, Tue, 29 Nov 2022 22:44:50 GMT
2. **owner**: changed from **Sebastian Huber** to **Joel Sherrill**
3. **status**: changed from **reopened** to **assigned**

**Comment 10**

1. **Joel Sherrill**, Tue, 29 Nov 2022 22:51:15 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **invalid**

Neither patch is applying cleanly for me. Please update them, reopen the ticket, and attach them.

**4212 - libio leaks location clones**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4212">https://devel.rtems.org/ticket/4212</a> ( <a href="https://devel.rtems.org/ticket/4212">https://devel.rtems.org/ticket/4212</a> )
<b>Id</b>	4212
<b>Reporter</b>	Chris Johns
<b>Created</b>	7 January 2021 07:00:21
<b>Modified</b>	29 November 2022 22:27:24
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

rtems\_filesystem\_location\_copy overwrites a location that may have been cloned via the ops handler leaking the destination node. If a file system has allocated resources in a location node when cloned it will leak. I assume there is a free for every clone?

An example of a leak is to mount of file system under IMFS and then open a file under the mounted file system. The path eval restart in the IMFS will clone a node and then open will:

```
rtems_filesystem_eval_path_extract_currentloc( &ctx, &iop->pathinfo );
rtems_filesystem_eval_path_cleanup( &ctx );
```

The ctx contains a cloned location.

Allocating resources to a location may be required because of the limited available file system fields and the opaque nature of the fields or a file system may have data it locks or reference counts and that needs to be managed.

I do not fully understand the semantics around the location object and while I could guess at a fix there are a number functions related to locations and a large number of use cases that I would not know if my fix is OK. For example should the copy function free the destination location and then clone the source location or should it just free the destination location or should all the places a copy is done be updated to manage the free and cloning based on the context? Or is the issue in the open call and the lines pasted here be swapped?

**Comment 1**

1. **Sebastian Huber**, Thu, 07 Jan 2021 08:16:42 GMT

Do we have this resource leak with one of the current file systems? If yes, could you please add test case for this resource leak.

**Comment 2**

1. **Chris Johns**, Thu, 07 Jan 2021 22:20:27 GMT

Replying to Sebastian Huber:

Do we have this resource leak with one of the current file systems?

Yes I believe there is a leak with open as stated above.

If yes, could you please add test case for this resource leak.

A test is a good idea however as stated I do not understand the \_\_locations\_\_ struct and the eval code in libio. I could create a test and provide a fix and break an existing file system.

Maybe the following will help explain why I am confused:

Is this simply a bug in open? Does ...

```

rtems_filesystem_eval_path_cleanup( &ctx );
rtems_filesystem_eval_path_extract_currentloc( &ctx, &iop->pathinfo );

```

... resolve the leak? Does that create another leak and so should the code be ...

```

rtems_filesystem_eval_path_cleanup( &ctx );
rtems_filesystem_eval_path_extract_currentloc( &ctx, &iop->pathinfo );
rtems_filesystem_eval_path_cleanup( &ctx );

```

... ? Would fixing the copy also resolve this leak? I have no idea which of these is right solution because I do not understand how this is suppose to work. The call `rtems_filesystem_location_copy()` does not `free` the resource. The only doco with this function says it is a bitwise copy yet the resource will be added to the corresponding mount. This is confusing because the resource is accounted for yet it does not perform a deep copy of the contents when the file system is required to provide an interface to do this.

### Comment 3

1. **Sebastian Huber**, Fri, 08 Jan 2021 05:28:40 GMT

I am not sure if we have an unintentional resource leak in `open()` with the current file systems. I would be good to have a test case. The purpose of `open()` is to create a location for a file which is released to the system through a call to `close()`. If errors happen during the path evaluation, the `rtems_filesystem_eval_path_error()` should be called which uses `rtems_filesystem_location_detach()` if necessary.

### Comment 4

1. **Chris Johns**, Sat, 09 Jan 2021 01:24:43 GMT

I agree we need a test, there is no objection here. I will look at this when I have time.

The bug is in the eval restart call in the IMFS. When a mount point is found the eval restart call clones the root loc. The open code ends up calling copy which wipes the clone out. A test is needed to expose the leak.

Putting the test case side, I would like to know if the copy should be deep? The test could then check for it being shallow or deep.

### Comment 5

1. **Sebastian Huber**, Mon, 11 Jan 2021 05:25:37 GMT

From looking at the code, I don't see an issue in the restart code:

```

void rtems_filesystem_eval_path_restart(
  rtems_filesystem_eval_path_context_t *ctx,
  rtems_filesystem_global_location_t **newstartloc_ptr
)
{
  free_location(&ctx->currentloc);
  rtems_filesystem_instance_unlock(&ctx->startloc->location);
  rtems_filesystem_global_location_assign(
    &ctx->startloc,
    rtems_filesystem_global_location_obtain(newstartloc_ptr)
  );
  rtems_filesystem_instance_lock(&ctx->startloc->location);
  rtems_filesystem_location_clone(&ctx->currentloc, &ctx->startloc->location);
}

```

It first frees the current location and then continues with a clone of the new start location. A test case would definitely help.

The locations are just pointers which are registered in the system. I think the documentation of `rtems_filesystem_location_copy()` is in line with its implementation.

### Comment 6

1. **Chris Johns**, Tue, 12 Jan 2021 01:36:02 GMT

It might have been the optimiser had not shown the path in the debugger and I was seeing something else. A review of this and then the path clean up in `open` does seem OK. The struct vnode counts will highlight an issue once I have that integrated. When I saw the problem and noted it I did not see the free but I saw the copy.

### Comment 7

1. **Joel Sherrill**, Fri, 17 Dec 2021 17:05:49 GMT

Is this still an issue?

### Comment 8

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:54:33 GMT

2. **owner:** set to **Chris Johns**

3. **status:** changed from **new** to **assigned**

Please close if possible.

### Comment 9

1. **Chris Johns**, Tue, 29 Nov 2022 22:27:24 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **invalid**

Please reopen if this is still a valid issue.

## 4214 - nios2: Add thread-local storage support

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4214">https://devel.rtems.org/ticket/4214</a> ( <a href="https://devel.rtems.org/ticket/4214">https://devel.rtems.org/ticket/4214</a> )
<b>Id</b>	4214
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 January 2021 08:26:31
<b>Modified</b>	9 June 2022 13:58:28
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/nios2
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

### Comment 1

1. **Joel Sherrill**, Fri, 08 Jan 2021 13:54:58 GMT

Could you add a link to where the ABI for this is defined? Last time I looked for what the mechanics were for TLS for various architectures, I didn't find it for many. Is there a generic mechanism in GCC I have missed?

### Comment 2

1. **Sebastian Huber**, Fri, 08 Jan 2021 14:07:45 GMT

It is a pretty standard approach:

[https://www.intel.com/content/dam/www/programmable/us/en/pdfs/literature/hb/nios2/n2cpu\\_nii51016.pdf](https://www.intel.com/content/dam/www/programmable/us/en/pdfs/literature/hb/nios2/n2cpu_nii51016.pdf)

### Comment 3

1. **Joel Sherrill**, Fri, 08 Jan 2021 15:51:24 GMT

Great! I am sure you will include that link and summarize the pertinent info in the CPU Guide.

### Comment 4

1. **Sebastian Huber**, Mon, 01 Feb 2021 06:21:24 GMT

In c968b27/rtems:

```
nios2: Add TLS support
Update #4214.
```

### Comment 5

1. **Sebastian Huber**, Thu, 09 Jun 2022 13:58:28 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 5a7acfc/rtems-docs:

```
cpu-supplement: Mention that nios2 supports TLS
Close #4214.
```

## 4215 - nios2: Add multilib with all custom floating-point instructions supported by GCC

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4215">https://devel.rtems.org/ticket/4215</a> ( <a href="https://devel.rtems.org/ticket/4215">https://devel.rtems.org/ticket/4215</a> )
<b>Id</b>	4215
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 January 2021 10:19:47
<b>Modified</b>	29 June 2022 09:05:49
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/nios2
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

See Table 13. "Floating Point Custom Instruction 2 Operation Summary" in the Nios II Custom Instruction User Guide:

[https://www.intel.com/content/dam/www/programmable/us/en/pdfs/literature/ug/ug\\_nios2\\_custom\\_instruction.pdf](https://www.intel.com/content/dam/www/programmable/us/en/pdfs/literature/ug/ug_nios2_custom_instruction.pdf)

**Attachments:****1 Sebastian Huber, Sun, 17 Jan 2021 18:47:18 GMT**

**attach:** set to [0001-nios2-Remove-custom-instruction-warnings.patch](https://devel.rtems.org/ticket/4215/0001-nios2-Remove-custom-instruction-warnings.patch) (<https://devel.rtems.org/ticket/4215/0001-nios2-Remove-custom-instruction-warnings.patch>)

---

**Comment 1****1. Sebastian Huber, Sat, 16 Jan 2021 16:57:12 GMT**

Changes for GCC 11:

<https://gcc.gnu.org/git?p=gcc.git;a=commit;h=7e02426ba0cc4f97ed347f963a6409b32c3c0c88> <https://gcc.gnu.org/git?p=gcc.git;a=commit;h=4214e23992487ecacba70575bf88af11288f557f> <https://gcc.gnu.org/git?p=gcc.git;a=commit;h=5e5d56919dd544a530445cfd8c3f6264f3d706f3>

**Comment 2****1. Sebastian Huber, Sun, 17 Jan 2021 20:19:05 GMT**

In e6f29b3/rtems-source-builder:

```
6: Add FPH2 multilib for nios2
```

```
Update #4215.
```

**Comment 3****1. Sebastian Huber, Wed, 29 Jun 2022 09:05:49 GMT**

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

It is available through the RSB provided GCC 12.

---

**4217 - Change status code for nested obtain of MrsP semaphores**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4217">https://devel.rtems.org/ticket/4217</a> ( <a href="https://devel.rtems.org/ticket/4217">https://devel.rtems.org/ticket/4217</a> )
<b>Id</b>	4217
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 January 2021 09:36:07
<b>Modified</b>	29 September 2021 14:12:22
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Return RTEMS\_INCORRECT\_STATE to indicate a nested obtain since this is a kind of deadlock. This status code is also used for other deadlocks.

**Comment 1**

1. **Sebastian Huber**, Thu, 21 Jan 2021 09:11:11 GMT

In 8ee22b2/rtems:

```
mrsp: Change error status for a nested seize
```

```
Return STATUS_DEADLOCK (RTEMS_INCORRECT_STATE) to indicate a nested seize since this is a kind of deadlock. This status code is also used for other deadlocks.
```

```
Update #4217.
```

**Comment 2**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** qualification added

**Comment 3**

1. **Sebastian Huber**, Wed, 29 Sep 2021 14:12:22 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

Documentation was also adjusted.

**4218 - aarch64 as internal error with spconfig01**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4218">https://devel.rtems.org/ticket/4218</a> ( <a href="https://devel.rtems.org/ticket/4218">https://devel.rtems.org/ticket/4218</a> )
<b>Id</b>	4218
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	20 January 2021 18:11:24
<b>Modified</b>	19 October 2021 13:49:43
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool/binutils
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This is to track [https://sourceware.org/bugzilla/show\\_bug.cgi?id=27217](https://sourceware.org/bugzilla/show_bug.cgi?id=27217) where there are more details on the actual failure.

This impacts spconfig01 and spmisc01 on all aarch64 BSPs.

**Comment 1**

1. **Joel Sherrill**, Fri, 22 Jan 2021 15:23:01 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Ryan Long**, Tue, 19 Oct 2021 13:49:43 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In e04fddc/rtems-source-builder:

```
rtems-binutils: Update to 2.37 and update head
```

```
Update to binutils 2.37 for RTEMS 6 to fix an issue when building tests for AArch64. Also updated the commit and hash for binutils in rtems-binutils-head.
```

Closes #4218

## 4219 - gdb master does not compile on CentOS 7

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4219">https://devel.rtems.org/ticket/4219</a> ( <a href="https://devel.rtems.org/ticket/4219">https://devel.rtems.org/ticket/4219</a> )
<b>Id</b>	4219
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	20 January 2021 18:12:41
<b>Modified</b>	22 January 2021 15:22:22
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/gdb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

There is a enumerated type and method with the same name. The CentOS 7 gdb does not like this. This ticket is to track the upstream ticket [https://sourceware.org/bugzilla/show\\_bug.cgi?id=27219](https://sourceware.org/bugzilla/show_bug.cgi?id=27219)

### Comment 1

1. **Joel Sherrill**, Fri, 22 Jan 2021 15:22:13 GMT

Fixed and RSB bumped.

### Comment 2

1. **Joel Sherrill**, Fri, 22 Jan 2021 15:22:22 GMT
  2. **status**: changed from **new** to **closed**
  3. **resolution**: set to **fixed**
- 

## 4221 - dtc recipe issue -- dependency on yaml.h

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4221">https://devel.rtems.org/ticket/4221</a> ( <a href="https://devel.rtems.org/ticket/4221">https://devel.rtems.org/ticket/4221</a> )
<b>Id</b>	4221
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	22 January 2021 19:52:32
<b>Modified</b>	18 November 2021 17:05:44
<b>Owner</b>	kgardas
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

This shows up on FreeBSD and may just be a matter of me not knowing the right package to install. Which yaml development package should be loaded. But it does fail.

```
CC fstree.o
  CC livetree.o
  CC treesource.o
gmake: *** No rule to make target 'yaml.h', needed by 'yamltree.o'. Stop.
shell cmd failed: /bin/sh -ex /usr/home/joel/rtems-cron-6/rtems-source-builder/rtems/build/dtc-1.6.0-x86_64-freebsd12.2-1/do-build
error: building dtc-1.6.0-x86_64-freebsd12.2-1
Suggestions appreciated.
See error report: rsb-report-dtc-1.6.0-x86_64-freebsd12.2-1.txt
```

### Comment 1

1. **Chris Johns**, Sat, 23 Jan 2021 23:32:28 GMT

```
$ find /usr/local/include -name yaml.h
/usr/local/include/yaml.h
$ pkg which /usr/local/include/yaml.h
/usr/local/include/yaml.h was installed by package libyaml-0.2.2
```

A patch to the user manual would be welcome

#### Comment 2

1. **Chris Johns**, Sat, 23 Jan 2021 23:33:27 GMT
2. **description:** modified (diff)

#### Comment 3

1. **Sebastian Huber**, Mon, 25 Jan 2021 05:44:59 GMT
2. **owner:** set to **Sebastian Huber <sebastian.huber@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In c709017/rtems:

```
Fix RTEMS_LINKER_ROSET_ITEM_ORDERED_DECLARE()
Add "extern" similar to RTEMS_LINKER_RWSET_ITEM_ORDERED_DECLARE().
Close #4221.
```

#### Comment 4

1. **Sebastian Huber**, Mon, 25 Jan 2021 05:46:44 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

Sorry, wrong number in commit.

#### Comment 5

1. **kgardas**, Sat, 13 Nov 2021 11:45:48 GMT
2. **owner:** changed from **Sebastian Huber <sebastian.huber@...>** to **kgardas**
3. **status:** changed from **reopened** to **accepted**

This is a bug in dtc 1.6.0 which shows when yaml library is installed on FreeBSD. I already created a patch for it just to realize that 1.6.1 contains the same fix. Working on dtc-1.6.0 -> 1.6.1 update patch.

#### Comment 6

1. **Karel Gardas**, Thu, 18 Nov 2021 17:05:44 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In f2a8973/rtems-source-builder:

```
RSB: update dtc 1.6.0 -> dtc 1.6.1
Fixes #4221
```

Note: the patch updates only dtc 1.6.0 occurrences. It leaves all other dtc (1.4.x) usages as they are just to not break anything which depends on older dtc versions.

---

## 4222 - Add a per mount flag to not create a node on O\_CREAT in open



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4222">https://devel.rtems.org/ticket/4222</a> ( <a href="https://devel.rtems.org/ticket/4222">https://devel.rtems.org/ticket/4222</a> )
<b>Id</b>	4222
<b>Reporter</b>	Chris Johns
<b>Created</b>	23 January 2021 23:41:29
<b>Modified</b>	8 February 2021 02:12:49
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

The libio rtems filesystem eval\_path\_context\_t context uses a token left after a path evaluation to indicate the path to the leaf node is valid and the path leaf does not exist. System calls such as mknod, mkdir and open uses this to return EEXIST or in the case of open to create a S\_IFREG node for a file. Some file systems do not support creating an S\_IFREG node and the open handler is required to do this.

[An aside, libio should leave the EEXIST detection to the file system and its evaluation handlers. The EEXIST error is one of many that could be returned yet it is specifically singled out using a fragile interface of a path token remaining. Anyway back to the change ... ]

The open call has:

```
if ( rtems_filesystem_eval_path_has_token( &ctx ) ) {
    create_regular_file( &ctx, mode );
}
```

and create\_regular\_file makes a node:

```
rv = rtems_filesystem_mknod(
    currentLoc,
    token,
    tokenlen,
    S_IFREG | mode,
    0
);
```

then wipes the evaluation context of any real and valid flags and settings:

```
rtems_filesystem_eval_path_set_flags( ctx, 0 );
rtems_filesystem_eval_path_set_path( ctx, token, tokenlen );
rtems_filesystem_eval_path_continue( ctx );
```

then continues the path evaluation. The continues path evaluation is suppose to find the new node. If a file system does not support making a regular file node and the mknod call is stubbed out to lie about making the node continuing the path evaluation fails with a not found error. I cannot see a way to code around this with the current libio code.

I propose adding a bool flag called no\_reg\_make\_node to the rtems\_filesystem\_mount\_table\_entry\_t struct that defaults to false. If true open does not call create\_regular\_file.

## Comment 1

1. **Chris Johns**, Mon, 25 Jan 2021 02:06:21 GMT
2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **accepted**

## Comment 2

1. **Chris Johns**, Mon, 08 Feb 2021 02:12:49 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 822cad89/rtems:

```
libcsupport: Add no_regular_file_mknod as a mount option to the mount table
Add the bool flag no_regular_file_mknod to the mount table so a file
system can indicate creating regular files is not done by
use the mknod handler. The file system will handle creating a
file node in the open handler. Note, the mount option is an enum which means there is only one
exclusive option supported. As a result no encapsulation is
provided and file systems need to set no_regular_file_mknod directly.
Closes #4222
```

## 4223 - Missing "extern" in RTEMS\_LINKER\_ROSET\_ITEM\_ORDERED\_DECLARE()

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4223">https://devel.rtems.org/ticket/4223</a> ( <a href="https://devel.rtems.org/ticket/4223">https://devel.rtems.org/ticket/4223</a> )
<b>Id</b>	4223
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	25 January 2021 05:43:09
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The fix for #3865 contains a typo. In RTEMS\_LINKER\_ROSET\_ITEM\_ORDERED\_DECLARE() there is a missing "extern".

**Comment 1**

1. **Sebastian Huber**, Mon, 25 Jan 2021 05:47:20 GMT

Fixed by c709017efba6de38225afc697a5ed2381cc12071.

**Comment 2**

1. **Sebastian Huber**, Mon, 25 Jan 2021 05:47:30 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT

2. **keywords**: **qualification** added

**4225 - Cobham Gaisler NOEL-V RISC-V 32- and 64-bit processor BSP**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4225">https://devel.rtems.org/ticket/4225</a> ( <a href="https://devel.rtems.org/ticket/4225">https://devel.rtems.org/ticket/4225</a> )
<b>Id</b>	4225
<b>Reporter</b>	Daniel Hellstrom
<b>Created</b>	27 January 2021 15:19:04
<b>Modified</b>	6 September 2022 14:08:36
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

To add a BSP configurations for Cobham Gaisler's NOEL-V processor IP. The NOEL-V processor is compliant with the open RISC-V 32/64-bit ISA. Depending on the soft-core IP configuration different RISC-V extensions may or may not be available, a matching RTEMS BSP build configuration must be selected accordingly. Similar to Cobham Gaisler's LEON3/4/5 processor designs, the NOEL-V is also a part of GRLIB providing building blocks such as I/O peripherals and L2-cache etc. that is typically used with the processor in SoC solutions. For more information about GRLIB and the current state and road-map of NOEL-V:

- <https://www.gaisler.com/grlib>
- <https://www.gaisler.com/noel-v>

The NOEL-V and GRLIB are available either under open-source GPL or commercial license. Demonstration designs with pre-built bit-streams, DTS/DTB, user's manuals, quick-start guides, etc. are freely available for the FPGA development boards listed under the NOEL-V page above. For example:

- Arty A7: Artix-7 FPGA Development Board (<https://www.gaisler.com/NOEL-ARTYA7>)
- PolarFire? FPGA Splash Kit (<https://www.gaisler.com/NOEL-PF>)
- Xilinx Kintex UltraScale? FPGA KCU105 Evaluation Kit (<https://www.gaisler.com/NOEL-XCKU>)

All the above demonstration designs have the same base memory layout and peripherals based on GRLIB. A DTS/DTB is needed to describe the system for RTEMS. The first BSP implementation targets only a minimal system with Memory Controller, Processor, IRQ Controller and Timer (RISC-V plic, clint, mtime). Thus the GRLIB drivers based on the driver manager is not needed to run RTEMS on NOEL-V.

The free GRMON eval hardware debugger can be used with the above demonstration designs to initialize, upload RTEMS images, execute RTEMS and debug the new NOEL-V BSPs.

### Comment 1

1. **Daniel Hellstrom**, Mon, 08 Feb 2021 19:48:28 GMT

Patches are now posted here:

<https://lists.rtems.org/pipermail/devel/2021-February/064343.html>

### Comment 2

1. **Joel Sherrill**, Thu, 10 Feb 2022 22:19:41 GMT

Pinging after chatting with Daniel. Hopefully updated patches will show up in the next few weeks.

### Comment 3

1. **Martin Aberg**, Tue, 06 Sep 2022 14:08:36 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In 9ec9be83/rtems:

bsp/riscv: Add NOEL-V BSP

Added support for Cobham Gaisler NOEL-V systems. The NOEL-V support is implemented as a riscv BSP. Both 32-bit and 64-bit processor systems are supported. Cobham Gaisler's NOEL-V RISC-V processor IP is described here:

<https://www.gaisler.com/NOELV>

Compatible with the following NOEL-V FPGA example design ranges available from Cobham Gaisler. Follow the links for free bit-streams, DTS/DTB, user's manuals and quick-start guides:

NOEL-ARTYA7-EX (<https://www.gaisler.com/NOEL-ARTYA7>) NOEL-PF-EX (<https://www.gaisler.com/NOEL-PF>) NOEL-XCKU-EX (<https://www.gaisler.com/NOEL-XCKU>)

Uses the shared GRLIB APBUART console driver "apbuart\_termios.c". APBUART devices are probed using device tree.

Closes #4225.

## 4226 - Buildbot needs a tool chain update

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4226">https://devel.rtems.org/ticket/4226</a> ( <a href="https://devel.rtems.org/ticket/4226">https://devel.rtems.org/ticket/4226</a> )
<b>Id</b>	4226
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	28 January 2021 05:52:42
<b>Modified</b>	29 November 2022 22:29:15
<b>Owner</b>	Amar Takhar
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

On 28/01/2021 06:37, buildbot@... wrote:

The Buildbot has detected a failed build on builder CHECK sparc/erc32 FreeBSD 10.1-STABLE GCC 7.3.0 POSIX while building rtems.  
Full details are available at:

<https://buildbot.rtems.org/#builders/20/builds/440>

Buildbot URL: <https://buildbot.rtems.org/>

Worker for this Build: build-1

Build Reason:  
Blamelist: Sebastian Huber

BUILD FAILED: make (failure)

Sincerely,

-The Buildbot

The Buildbot needs a tool chain update. It still uses GCC 7.5. For RTEMS 6, GCC 10 is required (RSB ade089253e70d75105a8311844f82f6d20cc30a8).

#### Comment 1

1. **Amar Takhar**, Sun, 31 Jan 2021 08:22:00 GMT

I'm updating this now.

#### Comment 2

1. **Amar Takhar**, Mon, 01 Feb 2021 07:01:22 GMT

All the tools are updated I'll wait to see if the builds pass before closing this.

#### Comment 3

1. **Sebastian Huber**, Mon, 01 Feb 2021 09:37:38 GMT

Thanks for the update, but something went wrong:

checking for sparc-rtems5-gcc... no configure: error: no acceptable cc found in \$PATH

<https://buildbot.rtems.org/#builders/20/builds/446>

#### Comment 4

1. **Sebastian Huber**, Mon, 01 Feb 2021 09:39:33 GMT

The problem is the configure command line:

```
configure: running /bin/sh '././rtems-snap-test-6.0.0-2021-02-01_093250-05da65c/c/configure' '--prefix=/opt/rtems-6' '--host=sparc-rtems5' '--build=x86_64-unknown-freebsd10.1' '--target=sparc-rtems5' '--enable-rtemsbsp=erc32' '--enable-posix' '--enable-tests' '--with-target-subdir=sparc-rtems5' '--exec-prefix=/opt/rtems-6/sparc-rtems5' '--includedir=/opt/rtems-6/sparc-rtems5/include' '--cache-file=/dev/null' '--srcdir=././rtems-snap-test-6.0.0-2021-02-01_093250-05da65c/c'
```

It should use "sparc-rtems6". It would be also good to use the new build system instead of the old one.

#### Comment 5

1. **Chris Johns**, Tue, 29 Nov 2022 22:29:15 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **invalid**

We are getting errors on each repo push because buildbot's sockets are not accessible. Please reopen once buildbot is available and able to be used.

## 4228 - rtems\_build\_name() depends on the signedness of char type

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4228">https://devel.rtems.org/ticket/4228</a> ( <a href="https://devel.rtems.org/ticket/4228">https://devel.rtems.org/ticket/4228</a> )
<b>Id</b>	4228
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	2 February 2021 14:35:42
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The rtems\_build\_name() is implemented by:

```
\c
#define _Objects_Build_name( _C1, _C2, _C3, _C4 ) \
```

```
( (uint32_t)(_C1) << 24 | \
  (uint32_t)(_C2) << 16 | \
  (uint32_t)(_C3) << 8 | \
  (uint32_t)(_C4) )
```

If the name is build from four "char" components, then the result depends on the signedness of the char type. The macro should first cast the chars to uint8\_t.

**Comment 1**

1. **Sebastian Huber**, Wed, 03 Feb 2021 05:17:44 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 98549e45/rtems:

```
score: _Objects_Build_name() signed/unsigned char
Change _Objects_Build_name() so that the result is independent of the signedness of char.
Close #4228.
```

**Comment 2**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords:** **qualification** added
- 

**4229 - conf.py files need updated for sphinxcontrib-bibtex ver. 2.0.0 and greater**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4229">https://devel.rtems.org/ticket/4229</a> ( <a href="https://devel.rtems.org/ticket/4229">https://devel.rtems.org/ticket/4229</a> )
<b>Id</b>	4229
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 February 2021 15:18:51
<b>Modified</b>	18 February 2021 20:03:47
<b>Owner</b>	Gedare Bloom <gedare@...>
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

I followed the instructions in the README, but I still ran across this error. I was able to get around it by specifying the version of sphinxcontrib-bibtex to be 1.0.0. This fix might probably needs to be applied to the 5 release branch as well.

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

Command line output

```
Checking for 'sphinxcontrib.bibtex' : not found (see README.txt)
The configuration failed
(complete log in /home/rlong/nta-workspace/nta-docs/build/config.log)
```

Output in \${TOP}/build/config.log

```
err: WARNING: Since v2.0, Sphinx uses "index" as master_doc by default. Please add "master_doc = 'contents'" to your conf.py.
found
-----
Checking for 'sphinxcontrib.bibtex'
[1/1] Processing ^[[01;34mbuild/.conf_check_70571fadfd25a3c4e29a4087f18cfa38/testbuild/contents.rst^[[0m
/home/rlong/nta-workspace/nta-docs/sphinx/bin/sphinx-build -b html -D extensions=sphinxcontrib.bibtex -C . out
out: Running Sphinx v3.4.3
making output directory... done
err:
Extension error:
You must configure the bibtex_bibfiles setting
from /home/rlong/nta-workspace/nta-docs/user: Test does not build: Traceback (most recent call last):
  File "/home/rlong/nta-workspace/nta-docs/.waf3-2.0.19-1f3c580272b15a03d2566843c5fe872a/waflib/Configure.py", line 333, in
run_build
  bld.compile()
  File "/home/rlong/nta-workspace/nta-docs/.waf3-2.0.19-1f3c580272b15a03d2566843c5fe872a/waflib/Build.py", line 176, in compile
  raise Errors.BuildError(self.producer.error)
waflib.Errors.BuildError: Build failed
-> task in '' failed with exit status 2 (run with -v to display more information)
not found (see README.txt)
from /home/rlong/nta-workspace/nta-docs/user: The configuration failed
```

**Comment 1**

1. **Gedare Bloom**, Thu, 18 Feb 2021 20:03:47 GMT
2. **owner:** set to **Gedare Bloom** <gedare@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 4563bb6/rtems-docs:

```
common: use bibtex_bibfiles for newer bibtex
Closes #4229.
```

**4230 - Timeout for automatic barriers is broken**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4230">https://devel.rtems.org/ticket/4230</a> ( <a href="https://devel.rtems.org/ticket/4230">https://devel.rtems.org/ticket/4230</a> )
<b>Id</b>	4230
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 February 2021 12:57:52
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

A barrier wait timeout at an automatic barrier doesn't decrement the count of waiting threads.

**Comment 1**

1. **Sebastian Huber**, Sat, 06 Feb 2021 19:56:40 GMT

In 2b5ce23b/rtems:

```
score: Constify Thread_queue_First_operation
Update #4230.
```

**Comment 2**

1. **Sebastian Huber**, Sat, 06 Feb 2021 19:56:43 GMT

In 9477d9ae/rtems:

score: Make FIFO thread queue ops public  
Update #4230.

**Comment 3**

1. **Sebastian Huber**, Sat, 06 Feb 2021 19:56:47 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 96ea09ac/rtems:

score: Add barrier thread queue operations  
This fixes a missing decrement of the number of waiting threads during a barrier wait timeout.  
Close #4230.

**Comment 4**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** **qualification** added

**4231 - MVME 2600/2700 has no console output**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4231">https://devel.rtems.org/ticket/4231</a> ( <a href="https://devel.rtems.org/ticket/4231">https://devel.rtems.org/ticket/4231</a> )
<b>Id</b>	4231
<b>Reporter</b>	Chris Johns
<b>Created</b>	6 February 2021 19:33:47
<b>Modified</b>	7 February 2021 23:26:16
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

A single character is output then nothing further. Tests output using the printk but sponconsole01 fails.  
It seems there is a problem with the UART driver interrupts.

**Comment 1**

1. **Chris Johns**, Sat, 06 Feb 2021 23:07:27 GMT

The issue is the wrong `BSP_PCI_ISA_BRIDGE_IRQ` value was being passed to the `openpic_enable_irq()` call in `bsps/powerpc/shared/irq/openpic_i8259_irq.c`. The define is offset by the max ISA bus IRQ value and the openpic call expects IRQ values relative to its signals, ie 0.

**Comment 2**

1. **Chris Johns**, Sun, 07 Feb 2021 23:26:16 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 450e238/rtems:

powerpc/shared: ISA bus bridge fails to enable the openpic irq  
The call to enable the openpic irq for the ISA bridge fails because the IRQ used is offset by the ISA bus signals and the openpic call expects an IRQ relative to its signals. Add the MVME 2600/2700 to the list of boards with an ISA bridge.  
Closes #4231

**4237 - consolesimpletask.c: Two Unchecked Return Values Spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4237">https://devel.rtems.org/ticket/4237</a> ( <a href="https://devel.rtems.org/ticket/4237">https://devel.rtems.org/ticket/4237</a> )
<b>Id</b>	4237
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 February 2021 18:19:32
<b>Modified</b>	12 February 2021 23:13:50
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1437625: Unchecked return value from call to `rtems_task_create()`.  
 CID 1472765: Unchecked return value from call to `rtems_task_start()`.

Snippet from Coverity output.

```

234 IMFS_add_node( "/dev", &cons->Node, NULL );
235
CID 1437625 (#1 of 1): Unchecked return value (CHECKED_RETURN)
1. check_return: Calling rtems_task_create without checking return value (as is done elsewhere 22 out of 25 times).
236 rtems_task_create(
237     rtems_build_name('C', 'O', 'N', 'S'),
238     RTEMS_MAXIMUM_PRIORITY - 1,
239     RTEMS_MINIMUM_STACK_SIZE,
240     RTEMS_DEFAULT_ATTRIBUTES,
241     RTEMS_DEFAULT_MODES,
242     &cons->task
243 );
244
CID 1472765: Unchecked return value (CHECKED_RETURN) [select issue]
245 rtems_task_start(
246     cons->task,
247     _Console_simple_task_Task,
248     (rtems_task_argument) cons
249 );
250}

```

**Comment 1**

1. Joel Sherrill, Fri, 12 Feb 2021 20:16:29 GMT
2. **description:** modified (diff)
3. **summary:** changed from **Fix CID #1437625 to consolesimpletask.c: Unchecked Return Value (CID #1437625)**

**Comment 2**

1. Joel Sherrill, Fri, 12 Feb 2021 20:20:26 GMT
2. **description:** modified (diff)
3. **summary:** changed from **consolesimpletask.c: Unchecked Return Value (CID #1437625) to consolesimpletask.c: Two Unchecked Return Values (CID #1437625 and #1472765)**

**Comment 3**

1. Joel Sherrill, Fri, 12 Feb 2021 20:31:47 GMT
2. **summary:** changed from **consolesimpletask.c: Two Unchecked Return Values (CID #1437625 and #1472765) to consolesimpletask.c: Two Unchecked Return Values Spotted by Coverity**

**Comment 4**

1. Ryan Long, Fri, 12 Feb 2021 23:13:50 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 14f5a05/rtems:

```

consolesimpletask.c: Fix Two Unchecked Return Values (CID #1437625 and #1472765)

CID 1437625: Unchecked return value from call to rtems_task_create(). CID 1472765: Unchecked return value from call to
rtems_task_start().

Closes #4237.

```



**4238 - Change motorola\_powerpc bsp to support irq-generic**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4238">https://devel.rtems.org/ticket/4238</a> ( <a href="https://devel.rtems.org/ticket/4238">https://devel.rtems.org/ticket/4238</a> )
<b>Id</b>	4238
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 February 2021 19:27:53
<b>Modified</b>	15 February 2021 21:14:33
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Update the motorola\_powerpc to support irq-generic moving the IRQ management to the IRQ server. This enables libbsd support for interrupts.

**Comment 1**

1. **Chris Johns**, Mon, 15 Feb 2021 21:14:33 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In e1676c1/rtems:

```
Update motorola power to irq-generic interrupt management
Add support to the BSP to enable irq-generic management Update the powerpc shared irq code to support irq-generic. This
is an opt in option for existing powerpc bsp. This change
should be simpler now Fix a number of issues in ISA IRQ controller handling by porting
fixes from the i386 (PC) BSP
Closes #4238 Closes #4239
```

---

**4239 - PowerPC shared ISA IRQ support is broken**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4239">https://devel.rtems.org/ticket/4239</a> ( <a href="https://devel.rtems.org/ticket/4239">https://devel.rtems.org/ticket/4239</a> )
<b>Id</b>	4239
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 February 2021 19:35:08
<b>Modified</b>	15 February 2021 21:14:33
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	i8258 irq interrupt
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The PowerPC shared ISA IRQ management in i8259s.c is broken. It fails to handle:

- Interrupt acknowledgements for the slave controller when the master has a lower priority pending interrupt acknowledge the slave and the master controllers
- The nesting support to suspend and resume an interrupt does not correctly handle the enable/disable
- The initialise of an interrupt does not handle any pending request
- Locks up when using with the IRQ server which is executing the handler in a task context

All these issues have been fixed in the i386 BSP however the code between is not shared as the i386 BSP has BSP specific IRQ management code as well.

**Comment 1**

1. **Chris Johns**, Fri, 12 Feb 2021 19:35:28 GMT
2. **owner:** set to **Chris Johns**

3. **status:** changed from **new** to **accepted**

### Comment 2

1. **Chris Johns**, Mon, 15 Feb 2021 21:14:33 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In e1676c1/rtems:

Update motorola\_power to irq-generic interrupt management  
 Add support to the BSP to enable irq-generic management Update the powerpc shared irq code to support irq-generic. This is an opt in option for existing powerpc bsps. This change should be simpler now Fix a number of issues in ISA IRQ controller handling by porting fixes from the i386 (PC) BSP  
 Closes #4238 Closes #4239

## 4240 - rtems-debugger-target.c: Dereference before null check spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4240">https://devel.rtems.org/ticket/4240</a> ( <a href="https://devel.rtems.org/ticket/4240">https://devel.rtems.org/ticket/4240</a> )
<b>Id</b>	4240
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 February 2021 20:55:29
<b>Modified</b>	12 February 2021 23:13:53
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1468682: swbreaks is assigned a value dereferenced from target before it has been verified that target is not null.

```

173 rtems debugger target*      target = rtems debugger->target;
    deref_ptr: Directly dereferencing pointer target.
174 rtems debugger_target_swbreak* swbreaks = target->swbreaks.block;
175 size_t                          swbreak_size;
176 uint8_t*                        loc = (void*) addr;
177 size_t                          i;
178 int                              r;
179
CID 1468682 (#1 of 1): Dereference before null check (REVERSE_NULL)check_after_deref: Null-checking target suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
180 if (target == NULL || swbreaks == NULL || kind != target->breakpoint_size) {
181     errno = EIO;
182     return -1;
183 }
```

### Comment 1

1. **Ryan Long**, Fri, 12 Feb 2021 23:13:53 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

In 3f4cdd8/rtems:

rtems-debugger-target.c: Fix Dereference before null check (CID #1468682)  
 CID 1468682: swbreaks is assigned a value dereferenced from target before it has been verified that target is not null.  
 Closes #4240.

## 4241 - rtems-debugger-threads.c: Three Dereference before null check errors spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4241">https://devel.rtems.org/ticket/4241</a> ( <a href="https://devel.rtems.org/ticket/4241">https://devel.rtems.org/ticket/4241</a> )
<b>Id</b>	4241
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 February 2021 21:29:34
<b>Modified</b>	12 February 2021 23:13:56
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

CID 1468681: Dereference before null check in `rtems_debugger_thread_continue()`.  
 CID 1468690: Dereference before null check in `rtems_debugger_thread_system_resume()`.  
 CID 1468694: Dereference before null check in `rtems_debugger_thread_find_index()`.

```
430 rtems_debugger_threads* threads = rtems_debugger->threads;
431 rtems_debugger_thread* current;
432 int r = 0;
deref_ptr_in_call: Dereferencing pointer threads. [show details]
433 current = rtems_debugger_thread_current(threads);
CID 1468681 (#1 of 1): Dereference before null check (REVERSE_NULL)check after_deref: Null-checking threads suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
434 if (threads != NULL && current != NULL) {
```

```
347 rtems_debugger_threads* threads = rtems_debugger->threads;
348 rtems_debugger_thread* current;
349 int r = 0;
deref_ptr_in_call: Dereferencing pointer threads. [show details]
350 current = rtems_debugger_thread_current(threads);
CID 1468690 (#1 of 1): Dereference before null check (REVERSE_NULL)check after_deref: Null-checking threads suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
351 if (threads != NULL && current != NULL) {
```

```
150 rtems_debugger_threads* threads = rtems_debugger->threads;
deref_ptr_in_call: Dereferencing pointer threads. [show details]
151 rtems_debugger_thread* current = rtems_debugger_thread_current(threads);
152 int r = -1;
CID 1468694 (#1 of 1): Dereference before null check (REVERSE_NULL)check after_deref: Null-checking threads suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
153 if (threads != NULL) {
```

## Comment 1

1. **Ryan Long**, Fri, 12 Feb 2021 23:13:56 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

In f65d3384/rtems:

```
rtems-debugger-threads.c: Fix three Dereference before null check errors

CID 1468681: Dereference before null check in rtems_debugger_thread_continue(). CID 1468690: Dereference before null check in
rtems_debugger_thread_system_resume(). CID 1468694: Dereference before null check in rtems_debugger_thread_find_index().

Closes #4241.
```

## 4242 - rtems-debugger-threads.c: Three Dereference before null check errors spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4242">https://devel.rtems.org/ticket/4242</a> ( <a href="https://devel.rtems.org/ticket/4242">https://devel.rtems.org/ticket/4242</a> )
<b>Id</b>	4242
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 February 2021 21:30:58
<b>Modified</b>	12 February 2021 21:32:49
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1468681: Dereference before null check in rtems\_debugger\_thread\_continue().  
 CID 1468690: Dereference before null check in rtems\_debugger\_thread\_system\_resume().  
 CID 1468694: Dereference before null check in rtems\_debugger\_thread\_find\_index().

```
430 rtems_debugger_threads* threads = rtems_debugger->threads;
431 rtems_debugger_thread* current;
432 int r = 0;
deref_ptr_in_call: Dereferencing pointer threads. [show details]
433 current = rtems_debugger_thread_current(threads);
CID 1468681 (#1 of 1): Dereference before null check (REVERSE_NULL)check after_deref: Null-checking threads suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
434 if (threads != NULL && current != NULL) {
```

```
347 rtems_debugger_threads* threads = rtems_debugger->threads;
348 rtems_debugger_thread* current;
349 int r = 0;
deref_ptr_in_call: Dereferencing pointer threads. [show details]
350 current = rtems_debugger_thread_current(threads);
CID 1468690 (#1 of 1): Dereference before null check (REVERSE_NULL)check after_deref: Null-checking threads suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
351 if (threads != NULL && current != NULL) {
```

```
150 rtems_debugger_threads* threads = rtems_debugger->threads;
deref_ptr_in_call: Dereferencing pointer threads. [show details]
151 rtems_debugger_thread* current = rtems_debugger_thread_current(threads);
152 int r = -1;
CID 1468694 (#1 of 1): Dereference before null check (REVERSE_NULL)check after_deref: Null-checking threads suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
153 if (threads != NULL) {
```

**Comment 1**

1. **Joel Sherrill**, Fri, 12 Feb 2021 21:32:49 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **duplicate**

**4244 - Possible infinite recursion in Classic API Signal handling**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4244">https://devel.rtems.org/ticket/4244</a> ( <a href="https://devel.rtems.org/ticket/4244">https://devel.rtems.org/ticket/4244</a> )
<b>Id</b>	4244
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 February 2021 06:46:56
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Due to implementation flaws, there may be an infinite recursion in the signal processing even if ASR mode is disabled during signal processing. The problem is that rtems\_task\_mode() is used to set up and tear down the ASR-specific task mode. This needs to be changed to set the modes under protection of the right locks and using a loop instead of recursion to schedule the next ASR processing step if needed.

**Comment 1**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:27 GMT

In f38c0de4/rtems:

```
validation: Add Validation1 test suite
Update #4244.
```

**Comment 2**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:31 GMT

In 3e7d658/rtems:

```
validation: Add signal manager tests
Update #4244.
```

**Comment 3**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:34 GMT

In fea848b/rtems:

```
score: Change thread action locking

Require that the corresponding lock is acquired before the action handler returns. This helps to avoid recursion in the signal processing.

Update #4244.
```

**Comment 4**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:37 GMT

In f9a59164/rtems:

```
score: Add _Thread_Append_post_switch_action()
Update #4244.
```

**Comment 5**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:41 GMT

In 600360d/rtems:

```
rtems: Remove unused _Modes_Mask_changed()
Update #4244.
```

**Comment 6**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:44 GMT

In 9d5d73b/rtems:

```
rtems: Remove unused _Modes_Change()
Update #4244.
```

**Comment 7**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:47 GMT

In a52e5d9/rtems:

```
rtems: Remove unused ASR_Information::nest_level
Update #4244.
```

**Comment 8**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:51 GMT

In 74ca8b7/rtems:

```
rtems: Move _Signal_Action_handler()
Move _Signal_Action_handler() and signal MP initialization to rtems_signal_send(). The goal is to make _Signal_Action_handler() a
static function in a follow up patch.
Update #4244.
```

**Comment 9**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:54 GMT

In f6a97f5/rtems:

```
rtems: Simplify signal handling
Remove superfluous ASR_Information::signals_posted. Move code out of trivial inline functions.
Update #4244.
```

**Comment 10**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:25:57 GMT

In b207b37/rtems:

```
posix: Remove superfluous check
The api pointer is never NULL.
Update #4244.
```

**Comment 11**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:26:00 GMT

In 1739bd2/rtems:

```
rtems: Remove _Modes_Set_interrupt_level()
This call just obfuscated the call to _ISR_Set_level().
Update #4244.
```

**Comment 12**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:26:04 GMT

In 8778a0e/rtems:

```
rtems: New errors for rtems_signal_catch()
Ensure that no invalid modes are set during ASR processing.
Update #4244.
```

**Comment 13**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:26:07 GMT

In 08adc0d/rtems:

```
rtems: Add _Modes_Apply_timeslice_to_thread()
Update #4244.
```

**Comment 14**

1. **Sebastian Huber**, Sat, 20 Feb 2021 14:26:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In a7e180b/rtems:

rtems: Avoid potential recursion in ASR handling

Do the mode changes necessary for the ASR processing directly under protection of the thread state lock to avoid the recursive calls to thread dispatching done in rtems\_task\_mode().

Close #4244.

### **Comment 15**

1. **Sebastian Huber**, Fri, 19 Mar 2021 16:08:37 GMT

In 53bd5e32/rtems:

rtems: Relax mode checks in rtems\_signal\_catch()

Check only for invalid modes if a valid handler is presented to rtems\_signal\_catch(). When NULL is used for the handler, ASR processing is disabled and the mode is not used.

Update #4244.

### **Comment 16**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT

2. **keywords: qualification** added

## **4245 - Add PCI regions support to RTEMS nexus bus support**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4245">https://devel.rtems.org/ticket/4245</a> ( <a href="https://devel.rtems.org/ticket/4245">https://devel.rtems.org/ticket/4245</a> )
<b>Id</b>	4245
<b>Reporter</b>	Chris Johns
<b>Created</b>	15 February 2021 21:28:56
<b>Modified</b>	22 September 2021 01:05:13
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	powerpc libbsd pci mapping
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

The RTEMS Nexus bus support in LibBSD assumes a linear address map with a 1:1 address mapping between the PCI bus master and CPU. Some target hardware has a different PCI bus master address space to the CPU memory address space.

- Provide a BSP means to enable PCI support in machine/bus.h in LibBSD
- Update powerpc/motorola\_powerpc to support cache coherent memory
- Change any PowerPC internal calls that clash with the Linux IO interface used in LibBSD. The PowerPC shared BSP calls have a different call signature

### **Comment 1**

1. **Chris Johns**, Tue, 16 Feb 2021 20:31:57 GMT

In 6e3c6e04/rtems:

powerpc/io: Make [out/in] le and be calls conditional  
 These calls clash with the Linux IO header in LibBSD. Making these conditional here means BSPs build and the imported Linux header is untouched.  
 Updates #4245

### **Comment 2**

1. **Chris Johns**, Tue, 16 Feb 2021 20:32:01 GMT

In 23aad64/rtems:

powerpc/motorola\_powerpc: Enable bus PCI support in LibBSD

Updates #4245

**Comment 3**

1. **Chris Johns**, Tue, 16 Feb 2021 20:32:05 GMT

In 026eb3db/rtems:

powerpc/motorola\_powerpc: Add cache coherent memory to the allocator

Updates #4245 Updates #4243

**Comment 4**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:07 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3f1e128/rtems-libbsd:

rtemsbsd/bus: Add PCI support to the nexus bus  
 Add PCI IO region support Add support map buffers to PCI address space Add BSP conditional IO space support. Some PC implementations have PCI IO space mapped differently to memory space and this needs to be reflected in the busspace. Include bsp.h to pick per BSP configuration.  
 Closes #4245

**Comment 5**

1. **Chris Johns**, Wed, 22 Sep 2021 01:05:13 GMT

In cfef84a0/rtems:

powerpc/io: Make [out/in] le and be calls conditional  
 These calls clash with the Linux IO header in LibBSD. Making these conditional here means BSPs build and the imported Linux header is untouched.  
 Updates #4245

**4246 - Add libbsd DC NIC support to mvme2700 board**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4246">https://devel.rtems.org/ticket/4246</a> ( <a href="https://devel.rtems.org/ticket/4246">https://devel.rtems.org/ticket/4246</a> )
<b>Id</b>	4246
<b>Reporter</b>	Chris Johns
<b>Created</b>	16 February 2021 01:07:47
<b>Modified</b>	29 November 2022 22:29:45
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add support for the Tulip NIC to LibBSD for the MVME 2700 (the mvme2307 bsp).

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:29:45 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

Added and working.

**4250 - b1553brm.c: Dereference before null check error spotted by Coverity**



---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4250">https://devel.rtems.org/ticket/4250</a> ( <a href="https://devel.rtems.org/ticket/4250">https://devel.rtems.org/ticket/4250</a> )
<b>Id</b>	4250
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 February 2021 20:43:31
<b>Modified</b>	19 February 2021 20:06:12
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1399829: Dereference before null check in brm\_control().

```

rtems_libio_ioctl_args_t *ioarg = (rtems_libio_ioctl_args_t *) arg;
deref_ptr: Directly dereferencing pointer ioarg.
997   unsigned int *data = ioarg->buffer;
998   struct bc_msg *cmd_list = (struct bc_msg *) ioarg->buffer;
999   brm_priv *brm;
1000  struct drvmgr_dev *dev;
1001  rtems_device_driver ret;
1002  int len, msgLen;
1003
1004  FUNCDBG("brm_control[%d]: [%i,%i]\n", minor, major, minor);
1005
1006  if ( drvmgr_get_dev(&b1553brm_drv_info.general, minor, &dev) ) {
1007      return RTEMS_UNSATISFIED;
1008  }
1009  brm = (brm_priv *)dev->priv;
1010
1011  CID 1399829 (#1 of 1): Dereference before null check (REVERSE_INULL)check_after_deref: Null-checking ioarg suggests that it may
be null, but it has already been dereferenced on all paths leading to the check.
1011  if (!ioarg) {

```

**Comment 1**

1. **Ryan Long**, Fri, 19 Feb 2021 20:06:12 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In eff3d7c/rtems:

```

b1553brm.c: Fix Dereference before null check (CID #1399829)
CID 1399829: Dereference before null check in brm_control().
Closes #4250

```

**4251 - b1553rt.c: Dereference before null check error spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4251">https://devel.rtems.org/ticket/4251</a> ( <a href="https://devel.rtems.org/ticket/4251">https://devel.rtems.org/ticket/4251</a> )
<b>Id</b>	4251
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 February 2021 20:46:40
<b>Modified</b>	19 February 2021 20:06:16
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1399830: Dereference before null check in rt\_control().

```

621  rtems libio_ioctl_args_t *ioarg = (rtems_libio_ioctl_args_t *)arg;
    deref_ptr: Directly dereferencing pointer ioarg.
622  unsigned int *data = ioarg->buffer;
623
624  rt_priv *rt;
625  struct drvmgr_dev *dev;
626
627  FUNCDBG("rt_control[%d]: [%i,%i]\n", minor, major, minor);
628
629  if ( drvmgr_get_dev(&b1553rt_drv_info.general, minor, &dev) ) {
630      return RTEMS_UNSATISFIED;
631  }
632  rt = (rt_priv *)dev->priv;
633
    CID 1399830 (#1 of 1): Dereference before null check (REVERSE_NULL)check_after_deref: Null-checking ioarg suggests that it may
    be null, but it has already been dereferenced on all paths leading to the check.
634  if (!ioarg) {

```

**Comment 1**

1. **Ryan Long**, Fri, 19 Feb 2021 20:06:16 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 4edcdf43/rtems:

```

b1553rt.c: Fix Deference before null check (CID #1399830)
CID 1399830: Dereference before null check in rt_control().
Closes #4251

```

**4252 - grtc.c: Dereference before null check error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4252">https://devel.rtems.org/ticket/4252</a> ( <a href="https://devel.rtems.org/ticket/4252">https://devel.rtems.org/ticket/4252</a> )
<b>Id</b>	4252
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 February 2021 20:50:40
<b>Modified</b>	19 February 2021 20:06:20
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399840: Dereference before null check in grtc\_ioctl().

```

1534  rtems libio_ioctl_args_t *ioarg = (rtems_libio_ioctl_args_t *)arg;
    deref_ptr: Directly dereferencing pointer ioarg.
1535  unsigned int *data = ioarg->buffer;
1536  int status, frm_len, i, ret;
1537  struct grtc_ioc_buf_params *buf_arg;
1538  struct grtc_ioc_config *cfg;
1539  struct grtc_ioc_hw_status *hwregs;
1540  struct grtc_ioc_pools_setup *pocfg;
1541  struct grtc_ioc_assign_frm_pool *poassign;
1542  struct grtc_frame *frm, *frms;
1543  struct grtc_frame_pool *pool;
1544  struct grtc_list *frmlist;
1545  struct grtc_ioc_stats *stats;
1546  unsigned int mem;
1547  IRQ_LOCAL_DECLARE(oldLevel);
1548
1549  FUNCDBG();
1550
1551  if ( drvmgr_get_dev(&grtc_drv_info.general, minor, &dev) ) {
1552      return RTEMS_INVALID_NUMBER;
1553  }
1554  pDev = (struct grtc_priv *)dev->priv;
1555
    CID 1399840 (#1 of 1): Dereference before null check (REVERSE_NULL)check_after_deref: Null-checking ioarg suggests that it may
    be null, but it has already been dereferenced on all paths leading to the check.
1556  if (!ioarg)

```

**Comment 1**

1. **Ryan Long**, Fri, 19 Feb 2021 20:06:20 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**

**4. resolution: set to fixed**

In 1fd56a96/rtems:

```
grtc.c: Fix Dereference before null check (CID #1399840)
CID 1399840: Dereference before null check in grtc_ioctl().
Closes #4252
```

**4253 - grspw\_pkt.c: Dereference before null check error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4253">https://devel.rtems.org/ticket/4253</a> ( <a href="https://devel.rtems.org/ticket/4253">https://devel.rtems.org/ticket/4253</a> )
<b>Id</b>	4253
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 February 2021 20:54:52
<b>Modified</b>	19 February 2021 20:06:24
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399846: Dereference before null check in grspw\_addr\_ctrl().

```
657     struct grspw_priv *priv = d;
    deref_ptr: Directly dereferencing pointer priv.
658     struct grspw_regs *regs = priv->regs;
659     unsigned int ctrl, nodeaddr;
660     SPIN_IRQFLAGS(irqflags);
661     int i;
662
    CID 1399846 (#1 of 1): Dereference before null check (REVERSE_NULL)check_after_deref: Null-checking priv suggests that it may be
    null, but it has already been dereferenced on all paths leading to the check.
663     if (!priv || !cfg)
```

**Comment 1**

1. **Ryan Long**, Fri, 19 Feb 2021 20:06:24 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In fac1ff1/rtems:

```
grspw_pkt.c: Fix Dereference before null check (CID #1399846)
CID 1399846: Dereference before null check in grspw_addr_ctrl().
Closes #4253
```

**4254 - shell.c: Dereference before null check error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4254">https://devel.rtems.org/ticket/4254</a> ( <a href="https://devel.rtems.org/ticket/4254">https://devel.rtems.org/ticket/4254</a> )
<b>Id</b>	4254
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 February 2021 21:00:54
<b>Modified</b>	18 February 2021 19:39:33
<b>Owner</b>	Ryan Long <thisisryanlong@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1467420: Dereference before null check in rtems\_shell\_line\_editor().

```

322 int      in_fileno = fileno(in);
      deref_ptr_in_call: Dereferencing pointer out.
323 int      out_fileno = fileno(out);
324
325 /*
326  * Only this task can use this file descriptor because calling
327  * fileno will block if another thread call made a call on this
328  * descriptor.
329  */
      CID 1467420 (#1 of 1): Dereference before null check (REVERSE_INULL)check_after_deref: Null-checking out suggests that it may be
      null, but it has already been dereferenced on all paths leading to the check.
330 output = (out && isatty(in_fileno));

```

**Comment 1**

1. **Ryan Long**, Thu, 18 Feb 2021 19:39:33 GMT
2. **owner:** set to **Ryan Long** <thisisryanlong@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In fa25b73/rtems:

```

shell.c: Fix Dereference before null check (CID #1467420)
CID 1467420: Dereference before null check in rtems_shell_line_editor().
Closes #4254

```

**4258 - printertask.c: Unchecked return value errors spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4258">https://devel.rtems.org/ticket/4258</a> ( <a href="https://devel.rtems.org/ticket/4258">https://devel.rtems.org/ticket/4258</a> )
<b>Id</b>	4258
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 February 2021 20:55:06
<b>Modified</b>	26 February 2021 22:56:18
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399710: Unchecked return value in printer\_task().

```

138     switch ( buffer->action_kind ) {
139         case ACTION_WRITE:
140             write( fd, &buffer->data[ 0 ], buffer->action_data.size );
141             printer_task_append_buffer( ctx, &ctx->free_buffers, buffer );
142         4. Breaking from switch.
143         8. Breaking from switch.
144         15. Breaking from switch.
145         break;
146     case ACTION_DRAIN:
147         CID 1399710 (#1 of 1): Unchecked return value (CHECKED_RETURN)19. check_return: Calling fsync without checking return value (as is
done elsewhere 4 out of 5 times).
148         fsync(fd);

```

**Comment 1**

1. **Ryan Long**, Fri, 19 Feb 2021 21:47:12 GMT
2. **summary:** changed from **printertask.c: Unchecked return value spotted by Coverity** to **printertask.c: Unchecked return value errors spotted by Coverity**

CID 1472764: Unchecked return value in rtems\_print\_printer\_task().

```

183     ctx->buffer_size -= sizeof( printer_task_buffer );
184
185     printer->context = ctx;
186     printer->printer = printer_task_printer;
187
188     CID 1472764 (#1 of 1): Unchecked return value (CHECKED_RETURN)3. check_return: Calling rtems_task_start without checking return
value (as is done elsewhere 22 out of 25 times).
189     rtems task start( ctx->task, printer task, (rtems task argument) ctx );

```

**Comment 2**

1. **Ryan Long**, Fri, 26 Feb 2021 22:56:18 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 1b322a6/rtems:

printertask.c: Fix Unchecked return value (CID #1399710)

CID 1399710: Unchecked return value in printer\_task(). CID 1472764: Unchecked return value in rtems\_print\_printer\_task().

Closes #4258

**4259 - grspw.c: Unchecked return value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4259">https://devel.rtems.org/ticket/4259</a> ( <a href="https://devel.rtems.org/ticket/4259">https://devel.rtems.org/ticket/4259</a> )
<b>Id</b>	4259
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 February 2021 21:06:23
<b>Modified</b>	5 March 2021 20:19:43
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399781: Unchecked return value in grspw\_device\_init().

```

551     if ( value )
552         pDev->bd_dma_area = value->i;
553
554     13. Condition grspw buffer alloc(pDev), taking false branch.
555     if (grspw_buffer_alloc(pDev))
556         return RTEMS_NO_MEMORY;
557
558     /* Create semaphores */
559     CID 1399781 (#2 of 2): Unchecked return value (CHECKED_RETURN)14. check_return: Calling rtems_semaphore_create without checking
return value (as is done elsewhere 15 out of 17 times).
560     rtems semaphore create(

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:19:43 GMT

2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 1eaf4e46/rtems:

```
grspw.c: Fix Unchecked return value (CID #1399781)
CID 1399781: Unchecked return value in grspw_device_init().
Closes #4259
```

## **4260 - record-client.c: Unchecked return value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4260">https://devel.rtems.org/ticket/4260</a> ( <a href="https://devel.rtems.org/ticket/4260">https://devel.rtems.org/ticket/4260</a> )
<b>Id</b>	4260
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 February 2021 21:16:24
<b>Modified</b>	26 February 2021 22:56:22
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

CID 1456677: Unchecked return value in resolve\_hold\_back().

```
191 for ( index = begin_index; index < per_cpu->item_index; ++index ) {
192     const rtems_record_item_64 *item;
193
194     item = &per_cpu->items[ index ];
CID 1456677 (#1 of 1): Unchecked return value (CHECKED_RETURN)12. check_return: Calling visit without checking return value (as is
done elsewhere 4 out of 5 times).
195     visit( ctx, item->event, item->data );
```

### **Comment 1**

1. **Ryan Long**, Fri, 26 Feb 2021 22:56:22 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In be3b87d/rtems:

```
record-client.c: Fix Unchecked return value (CID #1456677)
CID 1456677: Unchecked return value in resolve_hold_back().
Closes #4260
```

## **4261 - getgrent.c: Unchecked return value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4261">https://devel.rtems.org/ticket/4261</a> ( <a href="https://devel.rtems.org/ticket/4261">https://devel.rtems.org/ticket/4261</a> )
<b>Id</b>	4261
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 February 2021 21:24:15
<b>Modified</b>	26 February 2021 22:56:25
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1459004: Unchecked return value in endgrent().

```

102 if (ctx->fp != NULL) {
103     fclose(ctx->fp);
104 }
105
106 free(ctx);
    CID 1459004 (#1 of 1): Unchecked return value (CHECKED_RETURN)3. check_return: Calling pthread_setspecific without checking
return value (as is done elsewhere 5 out of 6 times).
107 pthread_setspecific(grp key, NULL);

```

**Comment 1**

1. **Ryan Long**, Fri, 26 Feb 2021 22:56:25 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In e5e58da/rtems:

```
getgrent.c: Fix Unchecked return value error (CID #1459004)
```

```
CID 1459004: Unchecked return value in endgrent().
```

```
Closes #4261
```

**4262 - rtems-debugger-threads.c: Unchecked return value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4262">https://devel.rtems.org/ticket/4262</a> ( <a href="https://devel.rtems.org/ticket/4262">https://devel.rtems.org/ticket/4262</a> )
<b>Id</b>	4262
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 February 2021 21:36:14
<b>Modified</b>	26 February 2021 22:56:29
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1468688: Unchecked return value in snapshot\_thread().

```

262     else {
263         rtems_status_code sc;
264         sc = rtems_task_suspend(id);
265         if (sc != RTEMS_SUCCESSFUL && sc != RTEMS_ALREADY_SUSPENDED) {
266             rtems_debugger_printf("error: rtems-db: thread: suspend: %08" PRIx32 " ": %s\n",
267                                   id, rtems_status_text(sc));
268             r = -1;
269         }
270     }
271
272     /*
273     * Read the target registers into the thread register array.
274     */
    CID 1468688 (#1 of 1): Unchecked return value (CHECKED_RETURN)17. check_return: Calling rtems_debugger_target_read_regs without
checking return value (as is done elsewhere 4 out of 5 times).
275     rtems_debugger_target_read_regs(thread);

```

**Comment 1**

1. **Ryan Long**, Fri, 26 Feb 2021 22:56:29 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

In e2002659/rtems:

```

rtems-debugger-threads.c: Fix Unchecked return value error (CID #1468688)
CID 1468688: Unchecked return value in snapshot_thread().
Closes #4262

```

**4264 - Activate ehci\_pci in rtems-libbsd (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4264">https://devel.rtems.org/ticket/4264</a> ( <a href="https://devel.rtems.org/ticket/4264">https://devel.rtems.org/ticket/4264</a> )
<b>Id</b>	4264
<b>Reporter</b>	GabrielMoyano
<b>Created</b>	22 February 2021 11:46:03
<b>Modified</b>	9 March 2021 10:36:41
<b>Owner</b>	Jan Sommer
<b>Type</b>	enhancement
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4263:

Import ehci\_pci from freebsd-org using freebsd-to-rtems.py

**Comment 1**

1. **Jan Sommer**, Mon, 08 Mar 2021 17:17:56 GMT
2. **component:** changed from **admin** to **network/libbsd**

**Comment 2**

1. **Jan Sommer**, Tue, 09 Mar 2021 10:35:11 GMT
2. **owner:** set to **Jan Sommer**
3. **status:** changed from **new** to **accepted**

**Comment 3**

1. **Jan Sommer**, Tue, 09 Mar 2021 10:36:22 GMT

Fixed with <https://git.rtems.org/rtems-libbsd/commit/?id=aee7b9291ca7f8cb2748dad94a89200326bbb17b> and <https://git.rtems.org/rtems-libbsd/commit/?id=6-freebsd-12&id=5b50a5181a6327db2613b010b0117a6286ff54a6>

**Comment 4**

1. **Jan Sommer**, Tue, 09 Mar 2021 10:36:41 GMT
2. **status:** changed from **accepted** to **closed**



## 3. resolution: set to fixed

**4265 - Add rtems\_get\_build\_hash()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4265">https://devel.rtems.org/ticket/4265</a> ( <a href="https://devel.rtems.org/ticket/4265">https://devel.rtems.org/ticket/4265</a> )
<b>Id</b>	4265
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	23 February 2021 09:38:48
<b>Modified</b>	23 November 2021 13:52:54
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Add a function to report a hash value of the build environment in the test suite results.

```

/* Generated from spec:/rtems/config/if/get-build-hash */
/**
 * @ingroup RTEMSAPIConfig
 *
 * @brief Gets the RTEMS build hash.
 *
 * The build hash is calculated from all key-value pairs of the build
 * environment. Local file system paths in the values do not contribute to the
 * hash value.
 *
 * @return Returns the pointer to the RTEMS build hash.
 *
 * @par Notes
 * The build hash can be used to distinguish test suite results obtained from
 * different build environments.
 *
 * @par Constraints
 * @parblock
 * The following constraints apply to this directive:
 *
 * * The directive may be called from within any runtime context.
 *
 * * The directive will not cause the calling task to be preempted.
 * @endparblock
 */
const char *rtems_get_build_hash( void );

```

**Comment 1**

1. **Chris Johns**, Wed, 24 Feb 2021 04:01:12 GMT

Is there a list that defines all key-value pairs in the build environment?

**Comment 2**

1. **Sebastian Huber**, Wed, 24 Feb 2021 07:04:45 GMT

Yes, you can iterate over `conf.env`:

wscript

```
diff --git a/wscript b/wscript
index 6626fafb74..84b845dce4 100755
```

```

a b __def get_compiler(conf, cp, variant): __ 13591359 return value 13601360 13611361 1362def generate_build_hash(conf): 1363 import hashlib 1364
import base64 1365 1366 build_hash = "" 1367 for key in sorted(conf.env): 1368 build_hash = build_hash + key + str(conf.env[key]) 1369 for discard in [ 1370
conf.env.PREFIX, 1371 conf.bldnode.make_node(conf.env.VARIANT).abspath(), 1372 conf.path.abspath(), 1373 ]: 1374 build_hash =
build_hash.replace(discard, "") 1375 state = hashlib.sha256() 1376 state.update(build_hash.encode("utf-8")) 1377 conf.define("RTEMS_BUILD_HASH",
base64.urlsafe_b64encode(state.digest())) 1378 conf.write_config_header( 1379 conf.env.VARIANT + "/cpukit/include/rtems/build-hash.h" 1380) 1381 1382
13621383def configure_variant(conf, cp, bsp_map, path_list, top_group, variant): 13631384 conf.msg("Configure board support package (BSP)", variant,
color="YELLOW") 13641385 ... .. __def configure_variant(conf, cp, bsp_map, path_list, top_group, variant):__ 13911412 conf.fatal("No such base BSP:
'{}'.format(variant)) 13921413 bsp_item.configure(conf, cic) 13931414 1394 options = set([o[0].upper() for o in cp.items(variant)]) 1415 options =
set([o[0].upper() for o in cp.items(variant)]) 13951416 for o in options.difference(cic.options): 13961417 conf.msg("Unknown configuration option", o.upper(),
color="RED") 1418 __generate_build_hash(conf) 13971419 13981420 13991421def check_forbidden_options(ctx, opts):

```

An alternative would be to explicitly add (or remove) build options.

**Comment 3**

1. **Chris Johns**, Thu, 25 Feb 2021 00:32:31 GMT

This captures a user's environment variables?

**Comment 4**

1. **Sebastian Huber**, Thu, 25 Feb 2021 07:22:20 GMT

There are always means to sabotage something. We don't recommend the use of environment variables and a waf configure warns about them. I will add a note that environment variables are not recommended and not used for the build hash.

**Comment 5**

1. **Sebastian Huber**, Thu, 25 Feb 2021 15:13:58 GMT

As discussed on the mailing list I tried the following approach. Iterate over all start files and libraries generated by the build and then create a hash of all executable sections. Then we recompile one object with a command line define with the build hash and replace this object in librtmscpu.a. Unfortunately, this exceeds my waf skills at the moment. I think it is feasible, but you really have to know how to adjust the waf tasks through meta programming.

**Comment 6**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords: qualification** added

**Comment 7**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:52:54 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **wontfix**

The rtems\_get\_build\_hash() was dropped in favour of #4269.

**4267 - Add rtems\_get\_target\_hash()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4267">https://devel.rtems.org/ticket/4267</a> ( <a href="https://devel.rtems.org/ticket/4267">https://devel.rtems.org/ticket/4267</a> )
<b>Id</b>	4267
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	24 February 2021 07:20:40
<b>Modified</b>	4 October 2022 08:19:19
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add a function to report a hash value characterizing the target system in the test suite results.

```

/* Generated from spec:/rtems/config/if/get-target-hash */
/**
 * @ingroup RTEMSAPIConfig
 *
 * @brief Gets the RTEMS target hash.
 *
 * The target hash is calculated from BSP-specific values which characterize a
 * target system.
 *
 * @return Returns the pointer to the RTEMS target hash.
 *
 * @par Notes
 * @parblock
 * For example, the device tree, settings of the memory controller, a serial
 * number of a chip may be used to calculate the target hash.
 *
 * The target hash can be used to distinguish test suite results obtained from
 * different target systems.
 * @endparblock
 *
 * @par Constraints
 * @parblock
 * The following constraints apply to this directive:
 *
 * * The directive may be called from within any runtime context.
 *
 * * The directive will not cause the calling task to be preempted.
 * @endparblock
 */
const char *rtems_get_target_hash( void );

```

**Comment 1**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:06 GMT

In 5f8bc83/rtems:

```
score: Add _IO_Base64url()  
Update #4267.
```

#### **Comment 2**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:09 GMT

In dea125d0/rtems:

```
score: Add Hash Handler  
Update #4267.
```

#### **Comment 3**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:13 GMT

In fb17af2/rtems:

```
rtems: Add rtems_get_target_hash()  
Update #4267.
```

#### **Comment 4**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:16 GMT

In bc6ffc3/rtems:

```
Add system initialization step for target hash  
Update #4267.
```

#### **Comment 5**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:20 GMT

In 7480c34/rtems:

```
bsps: Add default rtems_get_target_hash()  
Update #4267.
```

#### **Comment 6**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:24 GMT

In 74eff26c/rtems:

```
libtest: Report target hash  
Update #4267.
```

#### **Comment 7**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:57:31 GMT

In 2428a8ca/rtems:

```
build: Install  
Update #4267.
```

#### **Comment 8**

1. **Sebastian Huber**, Thu, 22 Apr 2021 05:46:34 GMT

In 29ce290/rtems-docs:

bsp-howto: Add target hash chapter

Update #4267.

**Comment 9**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords: qualification** added

**Comment 10**

1. **Sebastian Huber**, Tue, 04 Oct 2022 08:19:19 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 0fc5c03/rtems-docs:

c-user: Add application config info directives

Close #4267. Close #4269.

**4269 - Add rtems\_get\_build\_label()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4269">https://devel.rtems.org/ticket/4269</a> ( <a href="https://devel.rtems.org/ticket/4269">https://devel.rtems.org/ticket/4269</a> )
<b>Id</b>	4269
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	25 February 2021 15:16:01
<b>Modified</b>	4 October 2022 08:19:19
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add the following directive:

```

/* Generated from spec:/rtems/config/if/get-build-label */
/**
 * @ingroup RTEMSAPIConfig
 *
 * @brief Gets the RTEMS build label.
 *
 * The build label is a user-provided string defined by the build
 * configuration.
 *
 * @return Returns the pointer to the RTEMS build label.
 *
 * @par Notes
 * The build label can be used to distinguish test suite results obtained from
 * different build configurations. A use case is to record test results with
 * performance data to track performance regressions. For this a database of
 * performance limits is required. The build label and the target hash
 * obtained from rtems_get_target_hash() can be used as a key to obtain
 * performance limits.
 *
 * @par Constraints
 * @parblock
 * The following constraints apply to this directive:
 *
 * * The directive may be called from within any runtime context.
 *
 * * The directive will not cause the calling task to be preempted.
 * @endparblock
 */
const char *rtems_get_build_label( void );

```

**Comment 1**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:25:58 GMT

In d8bfa5a/rtems:

rtems: Add rtems\_get\_build\_label()  
Update #4269.

**Comment 2**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:02 GMT

In da8ad67e/rtems:

libtest: Report build label  
Update #4269.

**Comment 3**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords: qualification** added

**Comment 4**

1. **Sebastian Huber**, Tue, 04 Oct 2022 08:19:19 GMT
2. **status: changed from assigned to closed**
3. **resolution: set to fixed**

In Ofc5c03/rtems-docs:

c-user: Add application config info directives  
Close #4267. Close #4269.

**4270 - A failing task extension produces zombi objects and resource leaks**

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4270">https://devel.rtems.org/ticket/4270</a> ( <a href="https://devel.rtems.org/ticket/4270">https://devel.rtems.org/ticket/4270</a> )
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	25 February 2021 17:40:21
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

In `_Thread_Initialize()` we have this code:

```
_Objects_Open_u32( &information->Objects, &the_thread->Object, config->name );
/*
 * We assume the Allocator Mutex is locked and dispatching is
 * enabled when we get here. We want to be able to run the
 * user extensions with dispatching enabled. The Allocator
 * Mutex provides sufficient protection to let the user extensions
 * run safely.
 */
extension_status = _User_extensions_Thread_create( the_thread );
if ( extension_status )
    return true;
```

If an extension fails, then the thread object is not closed. Also the delete extensions are not called. If a later create extension fails, the earlier create extensions may have allocated resources which could be freed by a corresponding delete extension.

**Comment 1**

1. **Sebastian Huber**, Fri, 26 Feb 2021 07:51:50 GMT
2. **description: modified (diff)**

**Comment 2**

1. **Sebastian Huber**, Fri, 26 Feb 2021 08:26:30 GMT
2. **status**: changed from **assigned to closed**
3. **resolution**: set to **fixed**

In 1ac4a85/rtems:

```
score: Fix thread initialization
```

```
Close the thread object if a thread create extension fails. Also call the delete extension to avoid resource leaks in early extensions if a late extension fails.
```

```
Close #4270.
```

### Comment 3

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

## 4277 - grtc.c: Missing break in switch errors spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4277">https://devel.rtems.org/ticket/4277</a> ( <a href="https://devel.rtems.org/ticket/4277">https://devel.rtems.org/ticket/4277</a> )
<b>Id</b>	4277
<b>Reporter</b>	Ryan Long
<b>Created</b>	1 March 2021 20:22:13
<b>Modified</b>	5 March 2021 20:19:46
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1399761: Missing break in switch in process\_dma().  
 CID 1399765: Missing break in switch in process\_dma().  
 CID 1399766: Missing break in switch in process\_dma().  
 CID 1399777: Missing break in switch in process\_dma().

#### CID 1399761

```
1366         pDev->frm = NULL;
1367         pDev->frame_state = FRM_STATE_HDR;
1368
1369         CID 1399761: Missing break in switch (MISSING_BREAK) [select issue]
1370         fallthrough: The above case falls through to this one.
1371         case FRM_STATE_HDR:
1372         DBG2("FRAME STATE HDR\n");
```

#### CID 1399765

```
1450         pDev->frame_state = FRM_STATE_PAYLOAD;
1451         pDev->frm = frm;
1452
1453         case FRM_STATE_PAYLOAD:
1454         DBG2("FRAME STATE PAYLOAD\n");
```

#### CID 1399766

```
1450         pDev->frame_state = FRM_STATE_PAYLOAD;
1451         pDev->frm = frm;
1452
1453         CID 1399766 (#1 of 1): Missing break in switch (MISSING_BREAK)
1454         unterminated_case: The case for value FRM_STATE_PAYLOAD is not
1455         terminated by a break statement.
1456         case FRM_STATE_PAYLOAD:
1457         DBG2("FRAME STATE PAYLOAD\n");
```

#### CID 1399767

```
1354         switch( pDev->frame_state ) {
1355         CID 1399767 (#1 of 1): Missing break in switch (MISSING_BREAK)
1356         unterminated_case: The case for value FRM_STATE_NONE is not
1357         terminated by a break statement.
1358         case FRM_STATE_NONE:
1359         DBG2("FRAME STATE_NONE\n");
1360
1361         /* Find Start of next frame by searching for 0x01 */
1362         ret = grtc_hw_find_frm(pDev);
1363         if ( ret != 0 ) {
1364             /* Frame start not found */
1365             return 0;
1366         }
1367
1368         /* Start of frame found, Try to copy header */
1369         pDev->frm = NULL;
1370         pDev->frame_state = FRM_STATE_HDR;
```

**Comment 1**

1. **Ryan Long**, Mon, 01 Mar 2021 20:48:04 GMT
2. **summary**: changed from **grtc.c: Missing break in switch error spotted by Coverity** to **grtc.c: Missing break in switch errors spotted by Coverity**

**Comment 2**

1. **Ryan Long**, Fri, 05 Mar 2021 20:19:46 GMT
2. **owner**: set to **Ryan Long** <ryan.long@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 13d6fae/rtems:

```
grtc.c: Fix four Missing break in switch Coverity errors

CID 1399761: Missing break in switch in process_dma(). CID 1399765: Missing break in switch in process_dma(). CID 1399766: Missing break in switch in process_dma(). CID 1399777: Missing break in switch in process_dma().

Closes #4277
```

**4278 - cpusagetop.c: Missing break in switch errors spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4278">https://devel.rtems.org/ticket/4278</a> ( <a href="https://devel.rtems.org/ticket/4278">https://devel.rtems.org/ticket/4278</a> )
<b>Id</b>	4278
<b>Reporter</b>	Ryan Long
<b>Created</b>	1 March 2021 21:01:48
<b>Modified</b>	5 March 2021 20:19:50
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399726: Missing break in switch in task\_usage().  
 CID 1399728: Missing break in switch in task\_usage().  
 CID 1399742: Missing break in switch in task\_usage().

CID 1399726

```
233         continue;
CID 1399726 (#1 of 1): Missing break in switch (MISSING_BREAK)unterminated_case: The case for value 2U is not terminated by a
break statement.
234         case RTEMS_TOP_SORT_CURRENT_PRI:
235             if (
236                 _Thread_Get_priority( thread )
237                 > _Thread_Get_priority( data->tasks[j] )
238             ) {
239                 continue;
240             }
fallthrough: The above case falls through to this one.
```

CID 1399728

```
230         continue;
CID 1399728 (#1 of 1): Missing break in switch (MISSING_BREAK)unterminated_case: The case for value 1U is not terminated by a
break statement.
231         case RTEMS_TOP_SORT_REAL_PRI:
232             if (thread->Real_priority.priority > data->tasks[j]->Real_priority.priority)
233                 continue;
fallthrough: The above case falls through to this one.
234         case RTEMS TOP SORT CURRENT PRI:
```

CID 1399742

```
226         continue;
CID 1399742 (#1 of 1): Missing break in switch (MISSING_BREAK)unterminated_case: The case for value 3U is not terminated by a
break statement.
227         case RTEMS TOP SORT TOTAL:
228             if (CPU_usage_Equal_to(&usage, &data->zero) ||
229                 CPU_usage_Less_than(&usage, &data->usage[j]))
230                 continue;
fallthrough: The above case falls through to this one.
231         case RTEMS TOP SORT REAL PRI:
```

**Comment 1**

1. **Ryan Long**, Mon, 01 Mar 2021 21:19:34 GMT
2. **summary:** changed from `cpuusagetop.c` to `cpuusagetop.c: Missing break in switch errors spotted by Coverity`

**Comment 2**

1. **Ryan Long**, Fri, 05 Mar 2021 20:19:50 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from `new` to `closed`
4. **resolution:** set to `fixed`

In c7eb89f8/rtems:

```
cpuusagetop.c: Fix three Missing break in switch Coverity errors
```

```
CID 1399726: Missing break in switch in task_usage(). CID 1399728: Missing break in switch in task_usage(). CID 1399742: Missing break in switch in task_usage().
```

Closes #4278

**4279 - pci\_cfg\_read.c: Missing break in switch error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4279">https://devel.rtems.org/ticket/4279</a> ( <a href="https://devel.rtems.org/ticket/4279">https://devel.rtems.org/ticket/4279</a> )
<b>Id</b>	4279
<b>Reporter</b>	Ryan Long
<b>Created</b>	1 March 2021 21:25:50
<b>Modified</b>	5 March 2021 20:20:00
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399723: Missing break in switch in `pci_read_addressable()`.

```
70     switch (type) {
71     case PCI_RES_IO:
72         range0 = &bus->dev.resources[BRIDGE_RES_IO];
73         break;
74     case PCI_RES_MEM:
75         range1 = &bus->dev.resources[BRIDGE_RES_MEM];
76         fallthrough: The above case falls through to this one.
77     case PCI_RES_MEMIO:
78         break;
79     }
80     if (range0 && range1)
81         pci_read_addressable(bus, range0, range1, &res);
82     return res;
83 }
```

CID 1399723 (#1 of 1): Missing break in switch (MISSING\_BREAK)unterminated\_case: The case for value 3 is not terminated by a break statement.

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:00 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from `new` to `closed`
4. **resolution:** set to `fixed`

In 0d33d10/rtems:

```
pci_cfg_read.c: Fix Missing break in switch (CID #1399723)
```

```
CID 1399723: Missing break in switch in pci_read_addressable().
```

Closes #4279

**4280 - gen\_uuid.c: Unchecked return value from library errors spotted by Coverity**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4280">https://devel.rtems.org/ticket/4280</a> ( <a href="https://devel.rtems.org/ticket/4280">https://devel.rtems.org/ticket/4280</a> )
<b>Id</b>	4280
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 14:26:44
<b>Modified</b>	28 May 2021 17:29:41
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1049146: Unchecked return value from library in get\_clock().  
 CID 1049147: Unchecked return value from library in get\_random\_fd().

## CID 1049146

```

427         rewind(state_f);
428         fl.l_type = F_UNLCK;
CID 1049146 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)18. check_return: Calling fcntl(state_fd, 8, &fl)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
429         fcntl(state_fd, F_SETLK, &fl);
430     }
431
432     *clock_high = clock_reg >> 32;

```

## CID 1049147

```

167         if (i >= 0)
CID 1049147 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)5. check_return: Calling fcntl(fd, 2, i | 1) without
checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
168             fcntl(fd, F_SETFD, i | FD_CLOEXEC);
169     }

```

**Comment 1**

1. **Ryan Long**, Mon, 08 Mar 2021 20:56:17 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 597e4f4/rtems:

```
gen_uuid.c: Fix two Unchecked return value from library errors
```

```
CID 1049146: Unchecked return value from library in get_clock(). CID 1049147: Unchecked return value from library in get_random_fd().
```

```
Closes #4280
```

**Comment 2**

1. **Joel Sherrill**, Wed, 24 Mar 2021 13:03:24 GMT

In 62bbb0c/rtems:

```
gen_uuid.c: Revert previous patch (597e4f476568a225d14dfaff02074cf269ad62ac)
```

The patch was:

```
gen_uuid.c: Fix two Unchecked return value from library errors
```

```
CID 1049146: Unchecked return value from library in get_clock(). CID 1049147: Unchecked return value from library in
get_random_fd().
```

```
Reopen #4280
```

**Comment 3**

1. **Joel Sherrill**, Wed, 24 Mar 2021 13:06:13 GMT
2. **status:** changed from **closed** to **reopened**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

3. **resolution: fixed** deleted

The fix was incorrect. It did not include the rtems assert.h header. Assuming the paths were testable, it would be checking return values on fcntl() commands that RTEMS does not support.

A more likely approach is to ifndef rtems the unsupported fcntl's and see how that goes.

It is unclear if there was communication with the upstream project which would have been needed.

**Comment 4**

1. **Ryan Long**, Fri, 28 May 2021 17:29:41 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In a187b09/rtems:

```
gen_uuid.c: Ignore return values from fcntl()
CID 1049146: Unchecked return value from library in get_clock(). CID 1049147: Unchecked return value from library in get_random_fd().
Closes #4280
```

**4281 - main\_chmod.c: Unchecked return value from library error spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4281">https://devel.rtems.org/ticket/4281</a> ( <a href="https://devel.rtems.org/ticket/4281">https://devel.rtems.org/ticket/4281</a> )
<b>Id</b>	4281
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 14:30:30
<b>Modified</b>	8 March 2021 20:56:21
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1063856: Unchecked return value from library in rtems\_shell\_main\_chmod().

```
55 for (n=2 ; n < argc ; n++)
56   CID 1063856 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)4. check_return: Calling chmod(argv[n++], mode) without
checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
56   chmod(argv[n++], mode);
57
58 return 0;
59}
```

**Comment 1**

1. **Ryan Long**, Mon, 08 Mar 2021 20:56:21 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 8e34aa3/rtems:

```
main_chmod.c: Fix Unchecked return value from library (CID #1063856)
CID 1063856: Unchecked return value from library in rtems_shell_main_chmod().
Closes #4281
```

**4282 - pwdgrp.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4282">https://devel.rtems.org/ticket/4282</a> ( <a href="https://devel.rtems.org/ticket/4282">https://devel.rtems.org/ticket/4282</a> )
<b>Id</b>	4282
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:01:37
<b>Modified</b>	23 March 2021 17:02:15
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1255518: Unchecked return value from library in pwdgrp\_init().

```

65 /*
66  * Do the best to create this directory.
67  */
CID 1255518 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)1. check_return: Calling mkdir("/etc", 493U) without
checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
68 mkdir("/etc", S_IRWXU | S_IRGRP | S_IXGRP | S_IROTH | S_IXOTH);

```

**Comment 1**

1. **Ryan Long**, Mon, 08 Mar 2021 20:56:24 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 55ba229/rtems:

```

pwdgrp.c: Fix Unchecked return value from library (CID #1255518)
CID 1255518: Unchecked return value from library in pwdgrp_init().
Closes #4282

```

**Comment 2**

1. **Joel Sherrill**, Tue, 23 Mar 2021 13:45:55 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

It turns out that at least /etc can be created in multiple places depending on the RTEMS application structure. It was discussed that a standard mechanism is needed to address additional base file system directories. Ticket #4354 has been created for that which allows this issue to be strictly about the Coverity issue.

Changing the `_Assert` which was used to (void) mkdir should be sufficient to close this ticket again. Improvements to the base file system directory create can occur under #4354

**Comment 3**

1. **Ryan Long**, Tue, 23 Mar 2021 17:02:15 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 37fc651/rtems:

```

pwdgrp.c: Remove _Assert. /etc may already exist
Removed the _Assert unused_variable_equals macro due to /etc having already been created by the network stack initialization or an
initial filesystem image.
Closes #4282

```

**4283 - gr\_rasta\_spw\_router.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4283">https://devel.rtems.org/ticket/4283</a> ( <a href="https://devel.rtems.org/ticket/4283">https://devel.rtems.org/ticket/4283</a> )
<b>Id</b>	4283
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:06:11
<b>Modified</b>	5 March 2021 20:19:53
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1399760: Unchecked return value from library in `gr_rasta_spw_router_init1()`.

```

412     priv->prefix[14] += dev->minor_drv;
CID 1399760 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
413     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
414     priv->prefix[15] = '/';
415     priv->prefix[16] = '\0';
416

```

### Comment 1

1. **Ryan Long**, Fri, 05 Mar 2021 20:19:53 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 04436013/rtems:

```

gr_rasta_spw_router.c: Fix Unchecked return value from library (CID #1399760)
CID 1399760: Unchecked return value from library in gr_rasta_spw_router_init1().
Closes #4283

```

## 4284 - gr\_rasta\_io.c: Unchecked return value from library error spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4284">https://devel.rtems.org/ticket/4284</a> ( <a href="https://devel.rtems.org/ticket/4284">https://devel.rtems.org/ticket/4284</a> )
<b>Id</b>	4284
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:09:01
<b>Modified</b>	5 March 2021 20:19:56
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1399763: Unchecked return value from library in `gr_rasta_io_init1()`.

```

575     strcpy(priv->prefix, "/dev/rastaio0");
576     priv->prefix[12] += dev->minor_drv;
CID 1399763 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
577     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
578     priv->prefix[13] = '/';
579     priv->prefix[14] = '\0';

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:19:56 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In b84ce61/rtems:

```
gr_rasta_io.c: Fix Unchecked return value from library (CID #1399763)
CID 1399763: Unchecked return value from library in gr_rasta_io_init1().
Closes #4284
```

**4285 - gr\_leon4\_n2x.c: Unchecked return value error from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4285">https://devel.rtems.org/ticket/4285</a> ( <a href="https://devel.rtems.org/ticket/4285">https://devel.rtems.org/ticket/4285</a> )
<b>Id</b>	4285
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:16:14
<b>Modified</b>	5 March 2021 20:20:03
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399767: Unchecked return value error from library in gr\_cpcci\_leon4\_n2x\_init1().

```
495     strcpy(priv->prefix, "/dev/leon4n2x0");
496     priv->prefix[13] += dev->minor_drv;
CID 1399767 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
497     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
498     priv->prefix[14] = '/';
499     priv->prefix[15] = '\0';
```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:03 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 570b558/rtems:

```
gr_leon4_n2x.c: Fix Unchecked return value from library (CID #1399767)
CID 1399767: Unchecked return value error from library in gr_cpcci_leon4_n2x_init1().
Closes #4285
```

**4286 - gr\_rasta\_tmtc.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4286">https://devel.rtems.org/ticket/4286</a> ( <a href="https://devel.rtems.org/ticket/4286">https://devel.rtems.org/ticket/4286</a> )
<b>Id</b>	4286
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:23:14
<b>Modified</b>	5 March 2021 20:20:06
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399771: Unchecked return value from library in `gr_rasta_tmtc_init1()`.

```

588     strcpy(priv->prefix, "/dev/rastatmtc0");
589     priv->prefix[14] += dev->minor_drv;
CID 1399771 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
590     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
591     priv->prefix[15] = '/';
592     priv->prefix[16] = '\0';

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:06 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 17d525b5/rtems:

```

gr_rasta_tmtc.c: Fix Unchecked return value from library (CID #1399771)
CID 1399771: Unchecked return value from library in gr_rasta_tmtc_init1().
Closes #4286

```

**4287 - gr\_rasta\_adcdac.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4287">https://devel.rtems.org/ticket/4287</a> ( <a href="https://devel.rtems.org/ticket/4287">https://devel.rtems.org/ticket/4287</a> )
<b>Id</b>	4287
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:29:21
<b>Modified</b>	5 March 2021 20:20:10
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399780: Unchecked return value from library in `gr_rasta_adcdac_init1()`.

```

396     strcpy(priv->prefix, "/dev/rastaadcdac0");
397     priv->prefix[16] += dev->minor_drv;
CID 1399780 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
398     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
399     priv->prefix[17] = '/';
400     priv->prefix[18] = '\0';

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:10 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 91e38f8/rtems:

```
gr_rasta_adcdac.c: Fix Unchecked return value from library (CID #1399780)
CID 1399780: Unchecked return value from library in gr_rasta_adcdac_init1().
Closes #4287
```

**4288 - gr\_701.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4288">https://devel.rtems.org/ticket/4288</a> ( <a href="https://devel.rtems.org/ticket/4288">https://devel.rtems.org/ticket/4288</a> )
<b>Id</b>	4288
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:35:32
<b>Modified</b>	5 March 2021 20:20:13
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399783: Unchecked return value from library in gr701\_init1().

```
331     strcpy(priv->prefix, "/dev/gr701_0");
332     priv->prefix[11] += dev->minor_drv;
CID 1399783 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
333     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
334     priv->prefix[12] = '/';
335     priv->prefix[13] = '\0';
```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:13 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 4c0d9c5a/rtems:

```
gr_701.c: Unchecked return value from library (CID #1399783)
CID 1399783: Unchecked return value from library in gr701_init1().
Closes #4288
```

**4289 - gr\_tmtd\_1553.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4289">https://devel.rtems.org/ticket/4289</a> ( <a href="https://devel.rtems.org/ticket/4289">https://devel.rtems.org/ticket/4289</a> )
<b>Id</b>	4289
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:38:33
<b>Modified</b>	5 March 2021 20:20:16
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399785: Unchecked return value from library in `gr_tmtc_1553_init1()`.

```

315     strcpy(priv->prefix, "/dev/tmtc1553_0");
316     priv->prefix[14] += dev->minor_drv;
CID 1399785 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
317     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
318     priv->prefix[15] = '/';
319     priv->prefix[16] = '\0';

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:16 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 5f0a7ceb/rtems:

```

gr_tmtc_1553.c: Unchecked return value from library (CID #1399785)
CID 1399785: Unchecked return value from library in gr_tmtc_1553_init1().
Closes #4289

```

**4290 - gr\_cpci\_gr740.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4290">https://devel.rtems.org/ticket/4290</a> ( <a href="https://devel.rtems.org/ticket/4290">https://devel.rtems.org/ticket/4290</a> )
<b>Id</b>	4290
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:41:07
<b>Modified</b>	5 March 2021 20:20:19
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1437630: Unchecked return value from library in `gr_cpci_gr740_inti1()`.

```

472     strcpy(priv->prefix, "/dev/gr740_0");
473     priv->prefix[11] += dev->minor_drv;
CID 1437630 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
474     mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
475     priv->prefix[12] = '/';
476     priv->prefix[13] = '\0';

```



**Comment 1**

1. **Ryan Long**, Tue, 02 Mar 2021 18:22:21 GMT
2. **summary:** changed from **gr\_cpi\_gr740.c: Unchecked return value from library error spotted by Coverity** to **gr\_cpci\_gr740.c: Unchecked return value from library error spotted by Coverity**

**Comment 2**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:19 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f8047788/rtems:

```
gr_cpci_gr740.c: Unchecked return value from library (CID #1437630)
CID 1437630: Unchecked return value from library in gr_cpci_gr740_init1().
Closes #4290
```

**4291 - main\_help.c: Unchecked return value from library error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4291">https://devel.rtems.org/ticket/4291</a> ( <a href="https://devel.rtems.org/ticket/4291">https://devel.rtems.org/ticket/4291</a> )
<b>Id</b>	4291
<b>Reporter</b>	Ryan Long
<b>Created</b>	2 March 2021 15:49:21
<b>Modified</b>	28 May 2021 17:29:48
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1437650: Unchecked return value from library in rtems\_shell\_help().

```
472 strcpy(priv->prefix, "/dev/gr740_0");
473 priv->prefix[11] += dev->minor drv;
CID 1437630 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)2. check_return: Calling mkdir(priv->prefix, 511U)
without checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
474 mkdir(priv->prefix, S_IRWXU | S_IRWXG | S_IRWXO);
475 priv->prefix[12] = '/';
476 priv->prefix[13] = '\0';
```

**Comment 1**

1. **Ryan Long**, Tue, 02 Mar 2021 18:31:51 GMT

Accidentally put in the wrong reference to the error in the source.

```
121 if (lines && (line > lines)) {
CID 1437650 (#2 of 2): Unchecked return value from library (CHECKED_RETURN)7. check_return: Calling getchar() without checking
return value. This library function may fail and return an error code.
122 printf("Press any key to continue...");getchar();
123 printf("\n");
```

**Comment 2**

1. **Ryan Long**, Mon, 08 Mar 2021 20:56:27 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In fbab832/rtems:

```
main_help.c: Unchecked return value from library (CID #1437650)
```

CID 1437650: Unchecked return value from library in rtems\_shell\_help().  
Closes #4291

**Comment 3**

1. **Ryan Long**, Wed, 10 Mar 2021 17:49:17 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution**: **fixed** deleted

**Comment 4**

1. **Ryan Long**, Tue, 30 Mar 2021 15:11:17 GMT

Another issue was found at line 150 after submitting the first patch

```
150     printf("Press any key to continue...");
      CID 1437650 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)29. check_return: Calling getchar() without checking
return value. This library function may fail and return an error code.
151     getchar();
```

**Comment 5**

1. **Ryan Long**, Fri, 28 May 2021 17:29:48 GMT
2. **status**: changed from **reopened** to **closed**
3. **resolution**: set to **fixed**

In 2deba02/rtems:

```
main_help.c: Do not care what char is returned by getchar()
CID 1437650: Unchecked return value from library in rtems_shell_help().
Closes #4291
```

**4292 - rtems-rfs-bitmaps.c: Useless call (CID 1399749)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4292">https://devel.rtems.org/ticket/4292</a> ( <a href="https://devel.rtems.org/ticket/4292">https://devel.rtems.org/ticket/4292</a> )
<b>Id</b>	4292
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	3 March 2021 21:04:09
<b>Modified</b>	3 March 2021 21:04:21
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	fs/rfs
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Coverity Scan spotted this in rtems-rfs-bitmaps.c as CID 1399749). On the face of it, Scan appears to be correct but this issue should be reviewed by the original author of this code.

```
}
623     else
624     {
625         bits          = *map;
626         available = rtems_rfs_bitmap_element_bits ();
627     }
628
629     if (rtems_rfs_bitmap_match (bits, RTEMS_RFS_BITMAP_ELEMENT_SET))
CID 1399749 (#1 of 1): Useless call (USELESS_CALL)
side effect_free: Calling rtems_rfs_bitmap_set(*search_map, bit) is only useful for its return value, which is ignored. [show
details]
630     rtems_rfs_bitmap_set (*search_map, bit);
631     else
632     {
```

**Comment 1**

1. **Joel Sherrill**, Wed, 03 Mar 2021 21:04:21 GMT
2. **owner**: set to **Chris Johns**
3. **status**: changed from **new** to **assigned**

**4294 - satcan.c: Unsigned compared against 0 error spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4294">https://devel.rtems.org/ticket/4294</a> ( <a href="https://devel.rtems.org/ticket/4294">https://devel.rtems.org/ticket/4294</a> )
<b>Id</b>	4294
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 March 2021 15:03:12
<b>Modified</b>	5 March 2021 20:20:23
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1399768: Unsigned compared against 0 in satcan\_ioctl().

```

303         DBG("SatCAN: ioctl: masking register %d, with value %x\n\r",
304             regmod->reg, regmod->val);
unsigned_compare: This less-than-zero comparison of an unsigned value is never true. regmod->reg < 0U.
305         if (regmod->reg < 0)
306             return RTEMS_INVALID_NAME;
307         else if (regmod->reg <= SATCAN_FILTER_STOP)

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:23 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 1f29ee4/rtems:

```

satcan.c: Fix Unsigned compared against 0 (CID #1399768)
CID 1399768: Unsigned compared against 0 in satcan_ioctl().
Closes #4294

```

**4295 - b1553brm.c: Unsigned compared against 0 error spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4295">https://devel.rtems.org/ticket/4295</a> ( <a href="https://devel.rtems.org/ticket/4295">https://devel.rtems.org/ticket/4295</a> )
<b>Id</b>	4295
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 March 2021 15:08:42
<b>Modified</b>	5 March 2021 20:20:26
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1399773: Unsigned compared against 0 in brm\_write().

```

983         rw_args->bytes_moved = count;
984
CID 1399773 (#1 of 1): Unsigned compared against 0 (NO_EFFECT)unsigned_compare: This greater-than-or-equal-to-zero comparison of
an unsigned value is always true. count >= 0U.
985         if (count >= 0) {
986             return RTEMS_SUCCESSFUL;
987         }

```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:26 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In c57079a/rtems:

```
b1553brm.c: Fix Unsigned compared against 0 (CID #1399773)
CID 1399773: Unsigned compared against 0 in brm_write().
Closes #4295
```

**4301 - grcan.c: Unused value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4301">https://devel.rtems.org/ticket/4301</a> ( <a href="https://devel.rtems.org/ticket/4301">https://devel.rtems.org/ticket/4301</a> )
<b>Id</b>	4301
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 March 2021 18:43:12
<b>Modified</b>	5 March 2021 20:20:29
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1437613: Unused value in grcan\_set\_sfilter().

```
1788      /* disable TX/RX SYNC filtering */
      CID 1437613 (#1 of 1): Unused value (UNUSED_VALUE) assigned_value: Assigning value 4294967295ULL to pDev->sfilter.mask here, but
that stored value is overwritten before it can be used.
1789      pDev->sfilter.mask = 0xffffffff;
      value_overwrite: Overwriting previous write to pDev->sfilter.mask with value 0ULL.
1790      pDev->sfilter.mask = 0;
```

**Comment 1**

1. **Ryan Long**, Fri, 05 Mar 2021 20:20:29 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f762b7c2/rtems:

```
grcan.c: Fix Unused value (CID #1437613)
CID 1437613: Unused value in grcan_set_filter(). This fix was recommended by Daniel Hellstrom (daniel@...).
Closes #4301
```

**4302 - Obsolete powerpc/haleakala board**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4302">https://devel.rtems.org/ticket/4302</a> ( <a href="https://devel.rtems.org/ticket/4302">https://devel.rtems.org/ticket/4302</a> )
<b>Id</b>	4302
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	4 March 2021 19:40:49
<b>Modified</b>	19 January 2022 17:53:04
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	arch/powerpc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This BSP was merged in 1995 and there has been no mention of it recently. There do not appear to be any recent modifications to this BSP that are not part of a generic sweep of BSPs.

Removing this will reduce the number of BSPs which need modification to account for changes being introduced to support libbsd bus interface properly on PowerPC.

**Comment 1**

1. **Joel Sherrill**, Tue, 21 Dec 2021 15:04:49 GMT
2. **owner:** set to **Joel Sherrill** <joel@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In e92bc254/rtems:

```
Remove powerpc/haleakala board
Closes #4302.
```

**Comment 2**

1. **Joel Sherrill**, Wed, 19 Jan 2022 17:53:04 GMT

In f228227/rtems-tools:

```
rtems-bsps-powerpc.ini: Remove powerpc/haleakala
Updates #4302.
```

**4320 - Add driver for cadence-spi device for xilinx based BSPs**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4320">https://devel.rtems.org/ticket/4320</a> ( <a href="https://devel.rtems.org/ticket/4320">https://devel.rtems.org/ticket/4320</a> )
<b>Id</b>	4320
<b>Reporter</b>	Jan Sommer
<b>Created</b>	9 March 2021 10:41:19
<b>Modified</b>	10 March 2021 19:14:17
<b>Owner</b>	Jan Sommer
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Implement a spidev compatible driver for using the cadence-spi device of the Zynq devices in standard SPI mode.

**Comment 1**

1. **Jan Sommer**, Tue, 09 Mar 2021 10:41:30 GMT
2. **owner**: set to **Jan Sommer**
3. **status**: changed from **new** to **accepted**

**Comment 2**

1. **Jan Sommer**, Wed, 10 Mar 2021 19:13:54 GMT

In cc825d0/rtems:

```
bsps/xilinx_zynq: Add SPI driver for cadence-spi
Updates #4320
```

**Comment 3**

1. **Jan Sommer**, Wed, 10 Mar 2021 19:14:06 GMT

In 06129897/rtems:

```
bsps/xilinx_zynq: Add SPI driver to waf
Updates #4320
```

**Comment 4**

1. **Jan Sommer**, Wed, 10 Mar 2021 19:14:17 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In 9223931/rtems:

```
bsps/xilinx_zynq: Add SPI driver to autotools build
Closes #4320
```

**4321 - Add spi driver for AXI SPI ip core from Xilinx**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4321">https://devel.rtems.org/ticket/4321</a> ( <a href="https://devel.rtems.org/ticket/4321">https://devel.rtems.org/ticket/4321</a> )
<b>Id</b>	4321
<b>Reporter</b>	Jan Sommer
<b>Created</b>	9 March 2021 10:43:23
<b>Modified</b>	30 March 2021 15:03:39
<b>Owner</b>	Jan Sommer
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add a spidev compatible driver for the xilinx axi quad spi ip core for standard SPI mode

**Comment 1**

1. **Jan Sommer**, Tue, 09 Mar 2021 10:43:36 GMT
2. **owner**: set to **Jan Sommer**
3. **status**: changed from **new** to **accepted**

**Comment 2**

1. **Jan Sommer**, Tue, 30 Mar 2021 15:03:14 GMT

In 70667b55/rtems:

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

bsps/xilinx\_zynq: Add SPI driver for xilinx-axi-spi  
Updates #4321

**Comment 3**

1. **Jan Sommer**, Tue, 30 Mar 2021 15:03:27 GMT

In 7a1edf11/rtems:

bsps/shared: Add Xilinx-AXI SPI driver to waf  
Updates #4321

**Comment 4**

1. **Jan Sommer**, Tue, 30 Mar 2021 15:03:39 GMT

2. **status:** changed from **accepted** to **closed**

3. **resolution:** set to **fixed**

In 33fd915/rtems:

bsps/xilinx\_zynq: Add Xilinx AXI SPI driver to autotools build  
Closes #4321

**4323 - grlib,can: introduce a new common CAN baud-rate timing calculating functions**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4323">https://devel.rtems.org/ticket/4323</a> ( <a href="https://devel.rtems.org/ticket/4323">https://devel.rtems.org/ticket/4323</a> )
<b>Id</b>	4323
<b>Reporter</b>	Daniel Hellstrom
<b>Created</b>	9 March 2021 14:30:14
<b>Modified</b>	11 March 2021 16:52:08
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

There is no point in having two different implementations specific per GRLIB CAN device driver (OCCAN and GRCAN). Instead we can use the common CAN timing definitions and translate that into the device specific parameters using a new common calculation function.

**Comment 1**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:01 GMT

In cff99cf/rtems:

leon,can: introduce common CAN baud-rate calculation function  
Reimplemented the baud-rate algorithm from scratch to cope with GRCAN, GRCANFD and OC\_CAN devices.  
Update #4323.

**Comment 2**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:05 GMT

In 4d192207/rtems:

leon,grcan: use common CAN baud-rate calculation routine  
Update #4323.

**Comment 3**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:08 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 65237ba0/rtems:

```
leon,occan: use common CAN baud-rate calculation routine
Close #4323.
```

**4324 - grlib,grcanfd: extend the GRCAN driver with GRCANFD support**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4324">https://devel.rtems.org/ticket/4324</a> ( <a href="https://devel.rtems.org/ticket/4324">https://devel.rtems.org/ticket/4324</a> )
<b>Id</b>	4324
<b>Reporter</b>	Daniel Hellstrom
<b>Created</b>	9 March 2021 14:31:37
<b>Modified</b>	11 March 2021 16:52:21
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The new GRCAN\_FD IP supports CAN FD standard and is mostly backwards compatible with GRCAN SW interface. It introduces support for CAN-FD frames and a new bit-rate timing registers for new baud-rate.

The GRCAN driver have been extended to support the GRCANFD IP using the same API. Device IP-core specific functions are split into different files (grcanstd.c and grcanfd.c).

(this was fixed in 5 branch, see ticket #4307).

**Comment 1**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:11 GMT

In b98d6b67/rtems:

```
grlib: added 64-bit read no-cache function
Update #4324.
```

**Comment 2**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:14 GMT

In 43c903a1/rtems:

```
leon,grcan: added support for GRCANFD
```

The new GRCAN\_FD IP supports CAN FD standard and is mostly backwards compatible with GRCAN SW interface. The GRCAN driver have been extended to support the GRCANFD IP using the same driver.

Additional functions have been added that uses a new CAN FD frame format and read/write/baud-rate functions that supports both GRCANFD and GRCAN. To keep the SW API fully backwards compatible with GRCAN, the old functions remain.

```
Update #4324.
```

**Comment 3**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:18 GMT

In 9c76ca0/rtems:

```
leon,grcanfd: split out GRCANFD specific support in separate file
Update #4324.
```



**Comment 4**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:21 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 9bf8a9d/rtems:

```
leon,grcan: split out GRCAN non-FD specific support in separate file
Close #4324.
```

**4326 - objectextendinformation.c: Dereference after null check error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4326">https://devel.rtems.org/ticket/4326</a> ( <a href="https://devel.rtems.org/ticket/4326">https://devel.rtems.org/ticket/4326</a> )
<b>Id</b>	4326
<b>Reporter</b>	Ryan Long
<b>Created</b>	10 March 2021 13:56:34
<b>Modified</b>	29 April 2021 15:27:08
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 26033: Dereference after null check in `_Objects_Extend_information()`.

```
172     if ( old_maximum > extend_count ) {
173         /*
174          * Copy each section of the table over. This has to be performed as
175          * separate parts as size of each block has changed.
176          */
177         CID 26033 (#1 of 1): Dereference after null check (FORWARD_NULL)11. var_deref_model: Passing null pointer information-
>object_blocks to memcpy, which dereferences it.
177         memcpy(
178             object_blocks,
179             information->object_blocks,
180             block_count * sizeof( *object_blocks )
181         );
```

**Comment 1**

1. **Ryan Long**, Thu, 29 Apr 2021 15:27:08 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In cdf66529/rtems:

```
objectextendinformation.c: Ensure information->object_blocks is not NULL
CID 26033: Dereference after null check in _Objects_Extend_information().
Closes #4326
```

**4329 - main\_rtrace.c: Dereference after null check error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4329">https://devel.rtems.org/ticket/4329</a> ( <a href="https://devel.rtems.org/ticket/4329">https://devel.rtems.org/ticket/4329</a> )
<b>Id</b>	4329
<b>Reporter</b>	Ryan Long
<b>Created</b>	10 March 2021 18:42:23
<b>Modified</b>	29 April 2021 15:27:12
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399709: Dereference after null check in rtems\_trace\_buffering\_shell\_save().

```

6. var_compare_op: Comparing buf to null implies that buf might be null.
472  if (!buf)
473  {
474      close (out);
475      printf ("error: no memory\n");
476  }
477
CID 1399709 (#1 of 1): Dereference after null check (FORWARD_NULL)7. var_deref_model: Passing null pointer buf to memset, which
dereferences it.
478  memset (buf, 0, SAVE BUF SIZE);

```

**Comment 1**

1. **Ryan Long**, Thu, 29 Apr 2021 15:27:12 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 8cf30c4/rtems:

main\_rtrace.c: Add error return when malloc fails

CID 1399709: Dereference after null check in rtems\_trace\_buffering\_shell\_save().

Closes #4329

**4331 - main\_pci.c: Dereference after null check error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4331">https://devel.rtems.org/ticket/4331</a> ( <a href="https://devel.rtems.org/ticket/4331">https://devel.rtems.org/ticket/4331</a> )
<b>Id</b>	4331
<b>Reporter</b>	Ryan Long
<b>Created</b>	10 March 2021 19:06:50
<b>Modified</b>	10 February 2023 15:01:17
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399716: Dereference after null check in shell\_pci\_infodev().

```

10. var_compare_op: Comparing bus to null implies that bus might be null.
358  if (!bus) {
CID 1399716 (#1 of 1): Dereference after null check (FORWARD_NULL)11. var_deref_op: Dereferencing null pointer bus.
359      printf(" AT BUS:          0x%x via Host Bridge\n", bus->num);
360  } else {

```

**Comment 1**

1. **Ryan Long**, Wed, 10 Mar 2021 19:27:59 GMT

2. **owner:** set to **Daniel Hellstrom**
3. **status:** changed from **new** to **assigned**

**Comment 2**

1. **Joel Sherrill**, Fri, 10 Feb 2023 15:01:17 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

Commit had typo and closed the wrong ticket.

In 26e1610/rtems:

(The changeset message doesn't reference this ticket)

**4336 - Improve the workaround for the LEON3FT store-store errata: TN-0009 on master**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4336">https://devel.rtems.org/ticket/4336</a> ( <a href="https://devel.rtems.org/ticket/4336">https://devel.rtems.org/ticket/4336</a> )
<b>Id</b>	4336
<b>Reporter</b>	Daniel Hellstrom
<b>Created</b>	11 March 2021 15:16:45
<b>Modified</b>	11 March 2021 16:52:53
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

See also:

<https://www.gaisler.com/doc/antrn/GRLIB-TN-0009.pdf>

Some areas were already fixed by #3057.  
RTEMS-5 branch ticket #4154.

**Comment 1**

1. **Daniel Cederman**, Thu, 11 Mar 2021 16:51:40 GMT

In 0cae482a/rtems:

```
sparc: Remove sequences that the B2BST scan script warns about
Update #4336.
```

**Comment 2**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:50 GMT

In acad761/rtems:

```
sparc,leon: avoid triggering TN-0009 bad sequence
Update #4336.
```

**Comment 3**

1. **Daniel Hellstrom**, Thu, 11 Mar 2021 16:52:53 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 89d90c0/rtems:

```
sparc,leon: avoid triggering LEON3FT errata TN-0009
Close #4336.
```

**4338 - rtems\_clock\_set(): Cannot set future dates later than approximately 2105**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4338">https://devel.rtems.org/ticket/4338</a> ( <a href="https://devel.rtems.org/ticket/4338">https://devel.rtems.org/ticket/4338</a> )
<b>Id</b>	4338
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	12 March 2021 13:52:51
<b>Modified</b>	20 July 2022 07:39:37
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	rtems_clock_set, 2514, _TOD_To_seconds, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Short Problem Description

RTEMS Classic API Guide says:

RTEMS can represent time points of this clock in nanoseconds ranging from 1988-01-01T00:00:00.000000000Z to 2514-05-31T01:53:03.999999999Z.

- Yet, years larger than roughly 2105 to 2110 cannot be set (or at least the date should be wrong but this never occurred in my tests).

The possible RETURN VALUES are RTEMS\_SUCCESSFUL, RTEMS\_INVALID\_ADDRESS, RTEMS\_INVALID\_CLOCK

- Yet, rtems\_clock\_set() can return status RTEMS\_INVALID\_NUMBER, too. (Only for such dates in the far future.)

How To Replicate?

Call rtems\_clock\_set() with this time\_of-day:

```
{
```

```
    year = 2514,
    month = 5,
    day = 31,
    hour = 1,
    minute = 53,
    second = 3,
    ticks = 995
```

```
}
```

The return value will be RTEMS\_INVALID\_NUMBER.

Bugs in \_TOD\_To\_seconds()

cpukit/rtems/src/clockset.c: rtems\_clock\_set() calls

- cpukit/rtems/src/clocktodvalidate.c: \_TOD\_Validate() and
- cpukit/rtems/src/clocktodtoseconds.c: \_TOD\_To\_seconds() and
- cpukit/score/src/coretodset.c: \_TOD\_Set()

First issue:

\_TOD\_To\_seconds() converts the time\_of\_day structure into seconds using a variable time of type uint32\_t. This simply overflows when in comes close to year 2110.

Debugger output at the end of \_TOD\_To\_seconds():

```
(gdb) print the_tod->year
$16 = 2104
(gdb) print time
$17 = 4233686400
```

with a higher year:

```
(gdb) print the_tod->year
$28 = 2514
(gdb) print *the_tod
$31 = {
  year = 2514,
  month = 5,
  day = 31,
  hour = 1,
  minute = 53,
  second = 3,
  ticks = 995
}
(gdb) print time
$29 = 192272
```

Second issue:

`_TOD_To_seconds()` can (most likely) not handle the leap year issues of the years 2200, 2300, 2400, 2500 because it has dedicated code for the 2100 case only:

```
/* The year 2100 is not a leap year */
if ( time
    >= (TOD_SECONDS_AT_2100_03_01_00_00 - TOD_SECONDS_1970_THROUGH_1988) ) {
    time -= TOD_SECONDS_PER_DAY;
}
```

`_TOD_Check_time_of_day_and_run_hooks()` causes `STATUS_INVALID_NUMBER`

`cpukit/score/src/coretodset.c: _TOD_Set()` calls

- `cpukit/score/src/coretodset.c: _TOD_Check_time_of_day_and_run_hooks()`

in this code snippet (note return status):

```
status = _TOD_Check_time_of_day_and_run_hooks( tod );
if ( status != STATUS_SUCCESSFUL ) {
    _TOD_Release( lock_context );
    return status;
}
```

`_TOD_Check_time_of_day_and_run_hooks( tod )` can return status `STATUS_INVALID_NUMBER` which is not documented for `rtems_clock_set()`. The small time in seconds value 192272 from the integer overrun discussed above triggers the middle if clause:

```
static Status_Control _TOD_Check_time_of_day_and_run_hooks(
    const struct timespec *tod
)
{
    if ( ! Watchdog_Is_valid_timespec( tod ) ) {
        return STATUS_INVALID_NUMBER;
    }
    if ( tod->tv_sec < TOD_SECONDS_1970_THROUGH_1988 ) {
        return STATUS_INVALID_NUMBER;
    }
    if ( _Watchdog_Is_far_future_timespec( tod ) ) {
        return STATUS_INVALID_NUMBER;
    }
    return _TOD_Hook_Run( TOD_ACTION_SET_CLOCK, tod );
}
```

Final Notes

- I found #2665 and #2548 but I do not say these are relevant here.
- #define `WATCHDOG_MAX_SECONDS 0x3fffffff` in `cpukit/include/rtems/score/watchdogimpl.h` covers 17179869183 seconds which are some 544 years
- `_TOD_Check_time_of_day_and_run_hooks()` seems to be only used by `_TOD_Set()` but `_TOD_Set()` has three users.
- I did not check whether the inverse conversation (`rtems_clock_get_tod()`) works for dates which are centuries in the future.

### Comment 1

1. **Joel Sherrill**, Fri, 12 Mar 2021 14:02:46 GMT

Will switching to `time_t` instead of `uint32_t` largely resolve this?

I think you might have missed some Classic API methods which might overflow. I think anything using `uint32_t` or `rtems_interval` related to seconds or ticks over long intervals is suspect. I spotted these:

`rtems_clock_get_seconds_since_epoch()` uses `rtems_interval`. `rtems_clock_get_ticks_since_boot()` also uses `rtems_interval` but I think this overflows sooner than we'd like

I think the Classic API time of day structure is OK.

### Comment 2

1. **Frank Kuehndel**, Fri, 12 Mar 2021 15:30:38 GMT

`time_t` - I presume 64 bit - will avoid the overflow in `_TOD_To_seconds()` but ... there are still the not correctly handled far away leap years. ... there is `STATUS_INVALID_NUMBER` (Should not occur when the overflow is fixed. Yet, I do not like such incorrect code even if it should not trigger.) Overruns in `rtems_clock_get_ticks_since_boot()` are OK because the Classic API Guide says:

With a 1ms clock tick, this counter overflows after 50 days since boot. This is the historical measure of uptime in an RTEMS system. The newer service `rtems_clock_get_uptime()` is another and potentially more accurate way of obtaining similar information.

At other functions like `rtems_clock_get_seconds_since_epoch()` I had not have a look, yet.

### Comment 3

1. **Joel Sherrill**, Fri, 12 Mar 2021 15:51:58 GMT

OK. I was unclear but I was asking if it is time to move `rtems_interval` to 64-bits. This would address the historical ticks since boot and other intervals being 32 bits. The limit also applied to `rtems_task_wake_after()` and other APIs using `rtems_interval` for number of ticks.

### Comment 4

1. **Sebastian Huber**, Fri, 12 Mar 2021 16:25:14 GMT

Could we please separate the 32-bit `rtems_interval` issues from this ticket.

If we need a 64-bit division we should think about limiting the time of day to the year 2104. If it is just a multiplication and a couple of leap year fixes, then we should keep the full watchdog range.

### Comment 5

1. **Frank Kuehndel**, Wed, 21 Apr 2021 05:19:03 GMT

In 7bbbe42/rtems:

```
clock:_TOD_To_seconds(): Fix year 2514 overflow
```

This patch fixes issue #4338 by changing `_TOD_Validate()` to only accept years till 2105. This requires another patch to change the documentation of `rtems_clock_set()` and other affected API functions (indicating the end date is 2105 not 2514).

I tried to support till year 2514 but it turned out that this needs changing the Timer Manager too. That in turn would mean to change `_TOD_Seconds_since_epoch(void)` from 32 to 64 bit. Sebastian pointed out that a naive extension leads to trouble with 32 bit processors. He deemed a safe re-implementation too costly performance wise considering that year 2106 is far away and current binaries using RTEMS Classic API are unlikely to be in use by 2106.

The constant `TOD_SECONDS_AT_2100_03_01_00_00` in `cpukit/rtems/src/clocktodtoseconds.c` happens to be wrong by 1 hour. When setting the date 2100-Feb-28 23:59:59 and then reading the date again you will find yourself in 2100-Feb-27.

Update #4338

### Comment 6

1. **Frank Kuehndel**, Thu, 06 May 2021 13:20:56 GMT

Update on status:

This is fixed in code. What is missing is to update the documentation (i.e. removing the 2514-05-31T01:53:03.999999999Z in favor of 2104-12-31T23:59:59.999999999Z in Classic API and may be explaining that the internal clock will run beyond this limit and POSIX API can work with dates beyond 2105). A colleague of mine promised to do that.

### Comment 7

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords: qualification** added

### Comment 8

1. **Sebastian Huber**, Mon, 06 Sep 2021 10:25:56 GMT

In ad41c179/rtems:

```
score: Change TOD_LATEST_YEAR to 2099
```

This simplifies the implementation a bit. Declare `_TOD_Days_to_date[]` in `.`. Make `_TOD_Days_per_month[]` and `_TOD_Days_since_last_leap_year[]` static.

Update #4338.

### Comment 9

1. **Sebastian Huber**, Mon, 06 Sep 2021 10:27:18 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 081ec5d/rtems-docs:

```
c-user: Document time of day constraints
```

Close #4338.

### Comment 10

1. **Sebastian Huber**, Mon, 06 Sep 2021 10:40:03 GMT

In c0435b5e/rtems:

```
rtems: Document time of day constraints
```

Update #4338.

### Comment 11

1. **Sebastian Huber**, Wed, 20 Jul 2022 07:39:37 GMT

In d4c21e5/rtems:

```
ada/sp09: The year 2100 cannot be set
```

Update #4338.

**4339 - main\_cp.c: Unused value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4339">https://devel.rtems.org/ticket/4339</a> ( <a href="https://devel.rtems.org/ticket/4339">https://devel.rtems.org/ticket/4339</a> )
<b>Id</b>	4339
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 March 2021 16:29:10
<b>Modified</b>	8 April 2021 23:02:06
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1255344: Unused value in copy().

```

315         case FTS_DC:                                /* Warn, continue. */
316             warnx("%s: directory causes a cycle", curr->fts_path);
CID 1255344 (#5 of 5): Unused value (UNUSED_VALUE)assigned_value: Assigning value from rval to badcp here, but that stored value
is overwritten before it can be used.
317             badcp = rval = 1;
318             continue;

```

**Comment 1**

1. **Ryan Long**, Thu, 08 Apr 2021 23:02:06 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In fbc76440/rtems:

```

main_cp.c: Unused value (CID #1255344)
CID 1255344: Unused value in copy().
Closes #4339

```

**4340 - print\_ls.c: Unused value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4340">https://devel.rtems.org/ticket/4340</a> ( <a href="https://devel.rtems.org/ticket/4340">https://devel.rtems.org/ticket/4340</a> )
<b>Id</b>	4340
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 March 2021 16:45:41
<b>Modified</b>	8 April 2021 23:02:09
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1255346: Unused value in rtems\_shell\_ls\_printacol

```

327         if (col >= numcols) {
CID 1255346 (#1 of 1): Unused value (UNUSED_VALUE)assigned_value: Assigning value from col to chcnt here, but that stored value is
overwritten before it can be used.
328             chcnt = col = 0;
329             (void)putchar('\n');
330         }
value_overwrite: Overwriting previous write to chcnt with value from printaname(globals, p, dp->s_inode, ((globals->f_humanize &&
0) ? dp->s_size : dp->s_block)).
331         chcnt = printaname(globals, p, dp->s_inode,

```

**Comment 1**

1. **Ryan Long**, Thu, 08 Apr 2021 23:02:09 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 0b23660/rtems:

```
print-ls.c: Unused value (CID #1255346)
CID 1255346: Unused value in rtems_shell_ls_printacol().
Closes #4340
```

**4341 - fastlz.c: Unused value error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4341">https://devel.rtems.org/ticket/4341</a> ( <a href="https://devel.rtems.org/ticket/4341">https://devel.rtems.org/ticket/4341</a> )
<b>Id</b>	4341
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 March 2021 16:47:57
<b>Modified</b>	8 April 2021 23:02:13
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399751: Unused value in fastlz2\_compress().

```
219     if(ip[0] == ip[-1] && FASTLZ_READU16(ip-1)==FASTLZ_READU16(ip+1))
220     {
221         distance = 1;
222         CID 1399751 (#1 of 1): Unused value (UNUSED_VALUE)assigned_pointer: Assigning value from ip + 3 to ip here, but that stored value
is overwritten before it can be used.
222         ip += 3;
```

**Comment 1**

1. **Ryan Long**, Thu, 08 Apr 2021 23:02:13 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 09d811b/rtems:

```
fastlz.c: Unused value (CID #1399751)
CID 1399751: Unused value in fastlz2_compress().
Closes #4341
```

**4342 - disp\_hcms29xx.c: Unused value error spotted by Coverity**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4342">https://devel.rtems.org/ticket/4342</a> ( <a href="https://devel.rtems.org/ticket/4342">https://devel.rtems.org/ticket/4342</a> )
<b>Id</b>	4342
<b>Reporter</b>	Ryan Long
<b>Created</b>	12 March 2021 16:50:51
<b>Modified</b>	8 April 2021 23:02:16
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399752: Unused value in disp\_hcms29xx\_update\_task().

```
598     if (rc == RTEMS_SUCCESSFUL) {
        CID 1399752 (#1 of 1): Unused value (UNUSED_VALUE) returned value: Assigning value from rtems_semaphore_release(softc_ptr-
>disp_param.trns_sema_id) to rc here, but that stored value is overwritten before it can be used.
599     rc = rtems_semaphore_release(softc_ptr->disp_param.trns_sema_id);
600 }
```

**Comment 1**

1. **Ryan Long**, Thu, 08 Apr 2021 23:02:16 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 3cd58bd/rtems:

```
disp_hcms29xx.c: Unused value (CID #1399752)
CID 1399752: Unused value in disp_hcms29xx_update_task().
Closes #4342
```

**4345 - Nexus Driver for Marvell mv643xx Ethernet Adapter (powerpc/beatnik BSP, MVME6100 board)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4345">https://devel.rtems.org/ticket/4345</a> ( <a href="https://devel.rtems.org/ticket/4345">https://devel.rtems.org/ticket/4345</a> )
<b>Id</b>	4345
<b>Reporter</b>	Till Straumann
<b>Created</b>	16 March 2021 09:37:03
<b>Modified</b>	7 March 2022 09:43:45
<b>Owner</b>	Heinz Junkes <junkes@...>
<b>Type</b>	enhancement
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

This pull request implements a nexus driver (on top of the 5-freebsd-12 branch) for the Marvell 643xx ethernet adapter which is used on the MVME6100 board (powerpc/beatnik BSP).

Note that this driver builds on top of the low-level driver which is part of the beatnik BSP and requires a patch to the rtems bsp which was submitted in a related ticket.

**Comment 1**

1. **Sebastian Huber**, Mon, 07 Mar 2022 09:42:58 GMT
2. **milestone:** changed from **5.1** to **6.1**

**Comment 2**

1. **Heinz Junkes**, Mon, 07 Mar 2022 09:43:24 GMT

In de0badf/rtems-libbsd:

```
if_mve: Add MV643XX Ethernet driver
Update #4345.
```

### **Comment 3**

1. **Heinz Junkes**, Mon, 07 Mar 2022 09:43:45 GMT
2. **owner:** set to **Heinz Junkes** <junkes@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 878713b/rtems-libbsd:

```
if_mve: Add MV643XX Ethernet driver
Close #4345.
```

---

## **4346 - Require RTEMS\_PRIORITY for MrsP semaphores**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4346">https://devel.rtems.org/ticket/4346</a> ( <a href="https://devel.rtems.org/ticket/4346">https://devel.rtems.org/ticket/4346</a> )
<b>Id</b>	4346
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	16 March 2021 13:25:03
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

The MrsP semaphores are a generalization the priority ceiling semaphores for SMP configurations. Priority ceiling semaphores are required to use the priority task wait queue discipline. Require this discipline also for MrsP semaphores.

### **Comment 1**

1. **Sebastian Huber**, Wed, 17 Mar 2021 09:48:57 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3a66586/rtems:

```
rtems: Allow RTEMS_PRIORITY for MrsP semaphores
```

```
In order to improve the compatibility of RTEMS 5.2 with future version of RTEMS which fixed #4346 allow MrsP semaphores to be created with RTEMS_PRIORITY.
```

```
Close #4347.
```

### **Comment 2**

1. **Sebastian Huber**, Wed, 17 Mar 2021 09:51:43 GMT

Issue was fixed by 0965b7c8b7956846167f43b813d68f8b5f2a60a1.

### **Comment 3**

1. **Sebastian Huber**, Wed, 17 Mar 2021 13:01:43 GMT

In f2bbea6/rtems-docs:

c-user: Update semaphore example

Update #4346.

**Comment 4**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords: qualification** added
- 

**4355 - Remove leon3 test configurations which assume sis is built into gdb from rtems-test**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4355">https://devel.rtems.org/ticket/4355</a> ( <a href="https://devel.rtems.org/ticket/4355">https://devel.rtems.org/ticket/4355</a> )
<b>Id</b>	4355
<b>Reporter</b>	Ryan Long
<b>Created</b>	23 March 2021 15:55:39
<b>Modified</b>	23 March 2021 20:05:29
<b>Owner</b>	joel@...
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

When trying to run the tests with rtems-test on leon3, every test was invalid except for minimum. rtems-test is still using sis through gdb when it should be using the dedicated sis executable.

**Comment 1**

1. **Ryan Long**, Tue, 23 Mar 2021 20:05:29 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

In 64ad86c/rtems-tools:

```
bsps/sparc: Remove INI files using SIS in GDB
```

Removed the INI files that use the "target sim" option since the SIS sparc simulator in GDB is no longer used with RTEMS. A newer version of SIS is built separately.

Closes #4355

---

**4356 - rtems\_semaphore\_set\_priority() uses an invalid SMP lock**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4356">https://devel.rtems.org/ticket/4356</a> ( <a href="https://devel.rtems.org/ticket/4356">https://devel.rtems.org/ticket/4356</a> )
<b>Id</b>	4356
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	23 March 2021 17:14:03
<b>Modified</b>	15 November 2021 11:39:10
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

If the priority of a locked priority ceiling mutex is set, the used SMP lock sequence is invalid.

**Comment 1**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** qualification added

**Comment 2**

1. **Sebastian Huber**, Mon, 15 Nov 2021 11:39:10 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In ee57a7f1/rtems:

```
score: Fix _CORE_ceiling_mutex_Set_priority()
```

```
We have to use a second thread queue context to acquire and release the thread wait lock.
```

```
Close #4356.
```

**4358 - Priority discipline is broken for semaphores and message queues in SMP configurations**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4358">https://devel.rtems.org/ticket/4358</a> ( <a href="https://devel.rtems.org/ticket/4358">https://devel.rtems.org/ticket/4358</a> )
<b>Id</b>	4358
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	25 March 2021 08:08:58
<b>Modified</b>	2 September 2021 05:53:41
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The priority queues in clustered scheduling configurations use a per scheduler priority queue rotation to ensure FIFO fairness across schedulers. This mechanism is implemented in the thread queue surrender operation. Unfortunately some semaphore and message queue directives use wrongly the thread queue extract operation.

**Comment 1**

1. **Sebastian Huber**, Fri, 18 Jun 2021 09:24:45 GMT
2. **keywords:** qualification added

**Comment 2**

1. **Sebastian Huber**, Thu, 02 Sep 2021 05:48:04 GMT

In 9c0591f1/rtems:

```
score: Fix priority discipline handling
```

```
The priority queues in clustered scheduling configurations use a per scheduler priority queue rotation to ensure FIFO fairness across schedulers. This mechanism is implemented in the thread queue surrender operation. Unfortunately some semaphore and message queue directives used wrongly the thread queue extract operation. Fix this through the use of _Thread_queue_Surrender().
```

```
Update #4358.
```

**Comment 3**

1. **Sebastian Huber**, Thu, 02 Sep 2021 05:53:41 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

Message queues were fixed by #4509.

**4363 - GDB does not build on Windows for MSYS2**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4363">https://devel.rtems.org/ticket/4363</a> ( <a href="https://devel.rtems.org/ticket/4363">https://devel.rtems.org/ticket/4363</a> )
<b>Id</b>	4363
<b>Reporter</b>	Chris Johns
<b>Created</b>	28 March 2021 06:08:46
<b>Modified</b>	29 November 2022 22:34:32
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/gdb
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The details are in the GDB bug ...

[https://sourceware.org/bugzilla/show\\_bug.cgi?id=27657](https://sourceware.org/bugzilla/show_bug.cgi?id=27657)

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:34:32 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **wontfix**

Not sure if this is valid. Please reopen if it is broken.

---

**4364 - rtems-test Fails to list failed tests to user**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4364">https://devel.rtems.org/ticket/4364</a> ( <a href="https://devel.rtems.org/ticket/4364">https://devel.rtems.org/ticket/4364</a> )
<b>Id</b>	4364
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	28 March 2021 15:51:47
<b>Modified</b>	28 March 2021 15:51:47
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

rtems-test does not report the set of failed tests to the user at the conclusion of its run. It only gives a summary by category. They ARE in the log file. I assume this is a minor issue now that I have spotted the pattern.

I assume this also applies to 5 but I spotted it on 6 during the recent heavy round of manual testing.

---

**4365 - main\_cp.c: Ignore return value from stat()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4365">https://devel.rtems.org/ticket/4365</a> ( <a href="https://devel.rtems.org/ticket/4365">https://devel.rtems.org/ticket/4365</a> )
<b>Id</b>	4365
<b>Reporter</b>	Ryan Long
<b>Created</b>	30 March 2021 14:44:30
<b>Modified</b>	28 May 2021 17:29:44
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 26051: Unchecked return value from library in main\_cp().

```

257         if (Rflag && (Lflag || Hflag))
CID 26051 (#1 of 1): Unchecked return value from library (CHECKED_RETURN)34. check_return: Calling stat(*argv, &tmp_stat) without
checking return value. This library function may fail and return an error code. [Note: The source code implementation of the
function has been overridden by a builtin model.]
258         stat(*argv, &tmp_stat);

```

**Comment 1**

1. **Ryan Long**, Fri, 28 May 2021 17:29:44 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f29b312e/rtems:

```

main_cp.c: Ignore return value from stat()
CID 26051: Unchecked return value from library in main_cp().
Closes #4365

```

**4368 - rtems--tools tool kit temp file constructor does nothing**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4368">https://devel.rtems.org/ticket/4368</a> ( <a href="https://devel.rtems.org/ticket/4368">https://devel.rtems.org/ticket/4368</a> )
<b>Id</b>	4368
<b>Reporter</b>	Chris Johns
<b>Created</b>	31 March 2021 03:26:34
<b>Modified</b>	1 April 2021 17:43:50
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

A change to add an overloaded constructor ...

<https://git.rtems.org/rtems-tools/commit/?id=420d7a13672991a1480d06ac02190f2976b9253b>

does not do anything. The body of the constructor is empty.

Thinking about this I think the change is not right because the code depends on liberty make temp call to find the temp directory and that is designed to crate safe temp files.

I am now wondering how the code was tested? The files registered are not known to the clean up handler that runs on exit.

**Comment 1**

1. **Alex White**, Thu, 01 Apr 2021 17:43:50 GMT

2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

This patch set up the interfaces used in the "covoar: Add option to create named objdumps" patch that I sent. We determined that patch was not needed given its hacked-togetherness along with future speedups that we had in mind which would make it obsolete anyway.

This patch should have been removed from the set to be committed, but I forgot to send out a notice to exclude it. Sorry for the confusion.

This commit should be reverted.

## 4374 - Handle symbol sets in covoar

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4374">https://devel.rtems.org/ticket/4374</a> ( <a href="https://devel.rtems.org/ticket/4374">https://devel.rtems.org/ticket/4374</a> )
<b>Id</b>	4374
<b>Reporter</b>	Alex White
<b>Created</b>	5 April 2021 17:59:13
<b>Modified</b>	7 April 2021 15:35:06
<b>Owner</b>	Alex White
<b>Type</b>	task
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The covoar tool should be changed to handle all symbol sets for a coverage run rather than being called by coverage.py for each symbol set.

Currently, coverage.py calls covoar once for each symbol set found in the symbol-sets.ini configuration file. This leads to a lot of redundancy. For each symbol set, covoar has to process the objdumps and the coverage information of all the executables even though they do not change.

Changing covoar to process all symbol sets and generate reports in one invocation will result in a large speedup.

This will also require a minor modification to coverage.py to generate the correct .ini file and only call covoar once.

### Comment 1

1. **Alex White**, Mon, 05 Apr 2021 18:00:17 GMT
2. **owner:** set to **Alex White**
3. **status:** changed from **new** to **accepted**

### Comment 2

1. **Alex White**, Tue, 06 Apr 2021 19:22:58 GMT

In b02600a/rtems-tools:

```
covoar: Split symbols by symbol set
```

This changes the way covoar organizes the symbols. Instead of treating all symbols as one set, covoar is now aware of multiple symbol sets and tracks statistics for each set. It now also generates reports for each symbol set.

This change relieves the caller of covoar of the responsibility of managing the symbol sets. As a result, covoar can minimize the work done for each symbol set, yielding a significant speedup.

Updates #4374

### Comment 3

1. **Alex White**, Tue, 06 Apr 2021 19:23:00 GMT

In b3fcd10/rtems-tools:

```
coverage.py: Call covoar once
```

Updates #4374

### Comment 4

1. **Alex White**, Wed, 07 Apr 2021 15:35:06 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In de185fe/rtems-tools:

covoar: Use range-based for loops in ReportsBase?

Some of the loops in the ReportsBase::Write\* methods contained both regular and range-based for loops. This changes them to use only range-based for loops.

Closes #4374

## **4375 - Add futimens() and utimensat()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4375">https://devel.rtems.org/ticket/4375</a> ( <a href="https://devel.rtems.org/ticket/4375">https://devel.rtems.org/ticket/4375</a> )
<b>Id</b>	4375
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	5 April 2021 17:59:27
<b>Modified</b>	16 December 2021 15:54:33
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	file system
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

RTEMS currently only supports utimes() which is marked as Legacy in the POSIX standard. Support needs to be added for futimens() and utimensat() per the following specification:

<https://pubs.opengroup.org/onlinepubs/9699919799/functions/futimens.html>

utimes() only has second granularity on its times. The newer methods greatly improve on that even if many of the RTEMS file systems do not support nanosecond times on the file access, create, etc timestamps.

The following changes have been identified:

- The utimes file handler entry will need to be replaced with a handler geared to the futimens() API.
- File systems will have to be updated to account for the new handler.
- Existing methods like utimes() will have to be adjusted to be implemented in terms of the futimens() style method.
- File system test cases will have to be added to the fstests.

### **Comment 1**

1. **Joel Sherrill**, Tue, 06 Apr 2021 13:30:26 GMT
2. **keywords:** SoC removed

### **Comment 2**

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:54:33 GMT
2. **status:** changed from **new** to **closed**
3. **type:** changed from **defect** to **enhancement**
4. **resolution:** set to **fixed**

This was implemented and this ticket should have been closed.

## **4376 - covoar/ReportsBase Coverage::GenerateReports() uses raw pointer to std::list**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4376">https://devel.rtems.org/ticket/4376</a> ( <a href="https://devel.rtems.org/ticket/4376">https://devel.rtems.org/ticket/4376</a> )
<b>Id</b>	4376
<b>Reporter</b>	Alex White
<b>Created</b>	5 April 2021 18:29:36
<b>Modified</b>	22 December 2021 14:35:57
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covoar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The Coverage::GenerateReports() function uses a variable of type std::list to store the ReportsBase-derived classes used to generate the reports. The function should use an std::vector instead.

An std::vector is the preferred container type in this case because the constant-time insertion and removal properties of std::list are not needed. The smart pointer type std::unique\_ptr is preferred over ReportsBase\* because it eliminates the need for manual pointer deletion at the end of the function.

**Comment 1**

1. **Joel Sherrill**, Mon, 05 Apr 2021 18:35:16 GMT
2. **keywords:** covoar added
3. **component:** changed from **admin** to **tool**
4. **description:** modified (diff)
5. **summary:** changed from **covoar/ReportsBase Coverage::GenerateReports() uses raw pointer std::list to covoar/ReportsBase Coverage::GenerateReports() uses raw pointer to std::list**

**Comment 2**

1. **Ryan Long**, Wed, 22 Dec 2021 14:35:57 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 8167ad2/rtems-tools:

```
ReportsBase?: Change raw pointer to unique_ptr
```

Replaced raw pointer used with ReportsBase?-derived classes to make code cleaner and make it to where pointers do not have to be manually deleted.

Closes #4376

**4377 - covoar/Explanations Explanations::writeNotFound() NULL check of wrong variable**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4377">https://devel.rtems.org/ticket/4377</a> ( <a href="https://devel.rtems.org/ticket/4377">https://devel.rtems.org/ticket/4377</a> )
<b>Id</b>	4377
<b>Reporter</b>	Alex White
<b>Created</b>	5 April 2021 18:54:03
<b>Modified</b>	7 April 2021 20:36:39
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covoar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The Explanations::writeNotFound() method contains two NULL checks for the fileName variable. The second check should be checking if notFoundFile is NULL because it relates to the error being reported in the true case.

It appears that this was a simple mistake that was never caught until now.

#### Comment 1

1. **Alex White**, Wed, 07 Apr 2021 15:21:05 GMT
2. **owner**: set to **Alex White**
3. **status**: changed from **new** to **accepted**

#### Comment 2

1. **Joel Sherrill**, Wed, 07 Apr 2021 15:23:52 GMT

Didn't this get caught as part of reviewing a Coverity issue? Please cite one.

#### Comment 3

1. **Alex White**, Wed, 07 Apr 2021 15:26:54 GMT

No, it got caught as part of my testing. It may have also been a Coverity issue, but I ran into a NULL pointer dereference with this.

#### Comment 4

1. **Joel Sherrill**, Wed, 07 Apr 2021 15:49:26 GMT

CID #1399602 is about a NULL reference in the same method which traces back to the incorrect variable being checked. Coverity didn't realize it was the wrong variable but did find something wrong that could lead to a NULL pointer dereference.

Check me and please cite it in the ticket and git commit message.

#### Comment 5

1. **Alex White**, Wed, 07 Apr 2021 20:36:39 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In e84b9f3/rtems-tools:

```
covoar: Fix NULL check of wrong variable (CID #1399602)
```

```
CID 1399602: Dereference null return value in Explanations::writeNotFound().
```

```
In Explanations::writeNotFound() there were two NULL checks of the fileName variable where only one is needed. The second check has been changed to a NULL check of notFoundFile to match the original intent.
```

```
Closes #4377
```

## **4378 - covoar/symbol-sets add libuuid to symbol-sets.ini**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4378">https://devel.rtems.org/ticket/4378</a> ( <a href="https://devel.rtems.org/ticket/4378">https://devel.rtems.org/ticket/4378</a> )
<b>Id</b>	4378
<b>Reporter</b>	Alex White
<b>Created</b>	5 April 2021 18:58:31
<b>Modified</b>	18 May 2021 14:22:19
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covoar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

libuuid should be added to the list of symbol sets in the symbol-sets.ini configuration file.

#### Comment 1

1. **Alex White**, Tue, 18 May 2021 14:22:19 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

## 4380 - Update RTEMS POSIX Compliance Spreadsheet

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4380">https://devel.rtems.org/ticket/4380</a> ( <a href="https://devel.rtems.org/ticket/4380">https://devel.rtems.org/ticket/4380</a> )
<b>Id</b>	4380
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	6 April 2021 21:25:18
<b>Modified</b>	7 April 2021 18:58:39
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

There have been additions to RTEMS and the tracking spreadsheet now includes FACE Technical Standard, Edition 3.1

### Comment 1

1. **Joel Sherrill**, Wed, 07 Apr 2021 18:58:39 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In b43fe70/rtems-docs:

```
posix-compliance: Update tracking spreadsheet to v12
```

The new version of the API tracking spreadsheet includes FACE Technical Standard, Edition 3.1 as well as a few additions to what RTEMS supports. The generation script and discussion of standards was updated to reflect the inclusion of a new Edition of the FACE Technical Standard.

Closes #4380.

---

## 4382 - mingw - add flex to packages needed

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4382">https://devel.rtems.org/ticket/4382</a> ( <a href="https://devel.rtems.org/ticket/4382">https://devel.rtems.org/ticket/4382</a> )
<b>Id</b>	4382
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 April 2021 23:12:00
<b>Modified</b>	30 November 2022 23:26:28
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

New install of msys2 and pacman instructions in manual missed flex.

### Comment 1

1. **Chris Johns**, Tue, 29 Nov 2022 22:37:38 GMT
2. **owner**: set to **Joel Sherrill**

### Comment 2

1. **Joel Sherrill**, Wed, 30 Nov 2022 23:26:28 GMT

2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 5a54847/rtems-docs:

```
user/hosts/windows.rst: flex needs to be installed for msys2
Closes #4382.
```

## 4383 - covoar keeps DWARF info in memory too long

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4383">https://devel.rtems.org/ticket/4383</a> ( <a href="https://devel.rtems.org/ticket/4383">https://devel.rtems.org/ticket/4383</a> )
<b>Id</b>	4383
<b>Reporter</b>	Alex White
<b>Created</b>	8 April 2021 17:50:07
<b>Modified</b>	17 June 2021 21:05:39
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covoar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

To get covoar working again, the ELF and DWARF info cleanup was moved from the ExecutableInfo constructor to the ExecutableInfo destructor. Without this change, covoar would report the locations of symbols as unknown:-1. This is because the DWARF info is used later in the ExecutableInfo::getSourceAndLine() method with a call to debug.get\_source().

This caused a new issue: the ELF and DWARF info is now held in memory for the life of the program. This causes very high memory usage when running covoar, more than 10 GB for some BSPs.

A quick and dirty solution is to find what is being referenced in debug.get\_source() and preserve it after debug.end() is called. It appears that refraining from calling cus.clear() in rld::dwarf::file::end() would be a good place to start. Additionally, the rld::dwarf::sources class will likely need to be changed to copy out the DWARF source file info.

### Comment 1

1. **Alex White**, Thu, 08 Apr 2021 17:50:19 GMT
2. **owner:** set to **Alex White**
3. **status:** changed from **new** to **accepted**

### Comment 2

1. **Alex White**, Thu, 17 Jun 2021 21:05:37 GMT

In a88be93/rtems-tools:

```
covoar: Store only the file name in ExecutableInfo?
```

```
This changes the ExecutableInfo? class to only store the executable file's name rather than an entire instance of rld::files::object.
This allows the rld::files::object to be cleaned up in the ExecutableInfo? constructor.
```

```
Updates #4383
```

### Comment 3

1. **Alex White**, Thu, 17 Jun 2021 21:05:39 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In ac56fce/rtems-tools:

```
covoar: Store address-to-line info outside of DWARF
```

```
This adds the AddressToLineMapper? class and supporting classes to assume responsibility of tracking address-to-line information.
```

```
This allows the DWARF library to properly cleanup all of its resources and leads to significant memory savings.
```

```
Closes #4383
```

**4384 - Add SMTP login to rtems-tools mailer**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4384">https://devel.rtems.org/ticket/4384</a> ( <a href="https://devel.rtems.org/ticket/4384">https://devel.rtems.org/ticket/4384</a> )
<b>Id</b>	4384
<b>Reporter</b>	Alex White
<b>Created</b>	12 April 2021 18:34:08
<b>Modified</b>	14 April 2021 14:32:23
<b>Owner</b>	Alex White
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The ability to provide a username and password to perform an SMTP login should be added so that rtems-test results can be mailed via an external SMTP server that requires authentication.

The following additional command line options should be enough to make it work:

```
--smtp-port
--smtp-user
--smtp-password
```

The mail-related command line options should be filtered from the mailed logs so that credentials do not get leaked.

**Comment 1**

1. **Alex White**, Mon, 12 Apr 2021 18:34:20 GMT
2. **owner**: set to **Alex White**
3. **status**: changed from **new** to **accepted**

**Comment 2**

1. **Alex White**, Mon, 12 Apr 2021 18:36:29 GMT

Replying to Alex White:

The following additional command line options should be enough to make it work: --smtp-port --smtp-user --smtp-password

Additionally, a --smtp-use-gitconfig option to use the information found in ~/.gitconfig would be nice.

**Comment 3**

1. **Alex White**, Tue, 13 Apr 2021 21:45:02 GMT

In 1a575af/rtems-tools:

```
rtemstoolkit/mailler.py: Return full smtp-host arg value
This fixes mail.smtp_host() so that it returns the full argument value rather than just the second character.
Updates #4384
```

**Comment 4**

1. **Alex White**, Tue, 13 Apr 2021 21:45:04 GMT

In 92f7f67/rtems-tools:

```
rtemstoolkit: Filter mail options from log output
This filters mail-related options out before logging the command line options. This is needed to prevent leaking potentially sensitive information via logs and emails.
Updates #4384
```

**Comment 5**

1. **Alex White**, Tue, 13 Apr 2021 21:45:06 GMT

In 3b1407f/rtems-tools:

rtemstoolkit/mailler.py: Add SMTP login options

This adds more options so that the user can authenticate with the SMTP server.

Updates #4384

#### **Comment 6**

1. **Alex White**, Wed, 14 Apr 2021 14:32:23 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In 82b752a/rtems-tools:

rtemstoolkit/mailler.py: Add --use-gitconfig option

This adds the option to pull mail-related configuration values from the user's git configuration.

Closes #4384

### **4386 - covoar missing conditional branch instructions on ARM**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4386">https://devel.rtems.org/ticket/4386</a> ( <a href="https://devel.rtems.org/ticket/4386">https://devel.rtems.org/ticket/4386</a> )
<b>Id</b>	4386
<b>Reporter</b>	Alex White
<b>Created</b>	16 April 2021 14:36:58
<b>Modified</b>	16 April 2021 22:29:01
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covoar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

Two ARM instructions, cbz and cbnz, are not being treated as conditional branch instructions by covoar currently. They should be added to the list of conditional branch instructions in Target\_arm.

#### **Comment 1**

1. **Alex White**, Fri, 16 Apr 2021 14:37:50 GMT
2. **owner**: set to **Alex White**
3. **status**: changed from **new** to **accepted**

#### **Comment 2**

1. **Alex White**, Fri, 16 Apr 2021 22:29:01 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In 292363d/rtems-tools:

covoar/Target\_arm: Add cbz and cbnz as branch instructions

This adds cbz and cbnz as conditional branch instructions for ARM as they appear to have been missed.

Closes #4386

### **4387 - covoar marks taken/not taken incorrectly for AArch64**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4387">https://devel.rtems.org/ticket/4387</a> ( <a href="https://devel.rtems.org/ticket/4387">https://devel.rtems.org/ticket/4387</a> )
<b>Id</b>	4387
<b>Reporter</b>	Alex White
<b>Created</b>	16 April 2021 18:11:01
<b>Modified</b>	16 April 2021 22:29:05
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covovar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The AArch64 annotated assembly produced by covovar reveals that branches that are never taken are marked "ALWAYS TAKEN" and branches that are always taken are marked "NEVER TAKEN".

It appears that this is caused by incorrect return values in TargetBase::qemuTakenBit() and TargetBase::qemuNotTakenBit(). These methods should be overridden in Target\_aarch64 so that the return values are switched.

**Comment 1**

1. **Alex White**, Fri, 16 Apr 2021 18:11:12 GMT
2. **owner:** set to **Alex White**
3. **status:** changed from **new** to **accepted**

**Comment 2**

1. **Alex White**, Fri, 16 Apr 2021 22:29:05 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 0c4884a/rtems-tools:

```
covovar/Target_aarch64: Swap QEMU taken/not taken bits
```

```
This overrides the TargetBase behavior to allow branches to be marked correctly as either taken or not taken.
```

```
Closes #4387
```

**4388 - Copy improved mailer.py from rtems-tools**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4388">https://devel.rtems.org/ticket/4388</a> ( <a href="https://devel.rtems.org/ticket/4388">https://devel.rtems.org/ticket/4388</a> )
<b>Id</b>	4388
<b>Reporter</b>	Alex White
<b>Created</b>	19 April 2021 17:37:41
<b>Modified</b>	26 May 2021 21:34:44
<b>Owner</b>	Alex White
<b>Type</b>	enhancement
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The mailer.py script from rtems-tools has had various improvements made to it that have been left out of the mailer.py script in rtems-source-builder.

The mailer.py in rtems-source-builder should be made to mirror the mailer.py script in rtems-tools so that it incorporates the same improvements.

**Comment 1**

1. **Alex White**, Mon, 19 Apr 2021 17:37:51 GMT
2. **owner:** set to **Alex White**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

3. **status:** changed from **new** to **accepted**

#### Comment 2

1. **Alex White**, Wed, 26 May 2021 21:34:44 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 4e6dc64/rtems-source-builder:

```
sb: Merge mailer changes from rtems-tools
This adds the improved mailer.py script from rtems-tools.
Closes #4388
```

### **4389 - Undefined behaviour if the area size calculation in calloc() and rtems\_calloc() overflows**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4389">https://devel.rtems.org/ticket/4389</a> ( <a href="https://devel.rtems.org/ticket/4389">https://devel.rtems.org/ticket/4389</a> )
<b>Id</b>	4389
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 April 2021 18:32:51
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

#### Comment 1

1. **Sebastian Huber**, Wed, 21 Apr 2021 05:03:30 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 51defd92/rtems:

```
Fix calloc() behaviour in case of overflow
The multiplication to calculate the length of the memory area to allocate may overflow. Return NULL in case of an overflow.
Close #4389.
```

#### Comment 2

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** **qualification** added

### **4390 - Make zero size allocation result consistent across directives**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4390">https://devel.rtems.org/ticket/4390</a> ( <a href="https://devel.rtems.org/ticket/4390">https://devel.rtems.org/ticket/4390</a> )
<b>Id</b>	4390
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 April 2021 18:37:10
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

There is a special case in `malloc()` which results in a `malloc(0) == NULL` invariant. This special case should move to `rtems_heap_allocate_aligned_with_boundary()` to have a consistent behaviour across the API level memory allocation directives.

**Comment 1**

1. **Sebastian Huber**, Tue, 20 Apr 2021 18:37:24 GMT
2. **summary:** changed from **Make zero size allocation result consistent across directives** to **Make zero size allocation result consistent across directives**

**Comment 2**

1. **Joel Sherrill**, Tue, 20 Apr 2021 22:41:58 GMT

This is an area of undefined behavior per POSIX. It might be worth considering having this be a debug failure.

<https://pubs.opengroup.org/onlinepubs/009695399/functions/malloc.html>

**Comment 3**

1. **Sebastian Huber**, Wed, 21 Apr 2021 04:43:41 GMT

It is not undefined behaviour in the latest POSIX edition:

<https://pubs.opengroup.org/onlinepubs/9699919799/functions/malloc.html>

It is implementation-defined behaviour. The implementation has two options. The RTEMS `malloc(0)` returns NULL. Linux seems to return a unique pointer.

The `rtems_memalign(&p, 8, 0)` returns a unique pointer. I think this `size == 0` behaviour should be consistent in RTEMS.

**Comment 4**

1. **Sebastian Huber**, Tue, 04 May 2021 11:08:10 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In `d692c62d/rtems`:

```
Make zero size allocation result consistent
```

```
The zero size allocations had no consistent behaviour in RTEMS. For example, malloc(0) returned NULL and posix_memalign(&p, align, 0) returned in p a unique pointer (or NULL if no memory is available). In POSIX, zero size memory allocations are Implementation-defined behaviour. The implementation has two options:
```

```
https://pubs.opengroup.org/onlinepubs/9699919799/functions/malloc.html
```

```
https://pubs.opengroup.org/onlinepubs/9699919799/functions/posix\_memalign.html
```

```
Linux and FreeBSD return a unique pointer for zero size memory allocations. Use this approach for RTEMS as well throughout the memory allocation directives
```

```
Close #4390.
```

**Comment 5**

1. **Sebastian Huber**, Thu, 06 May 2021 13:15:09 GMT

In `2c5199b/rtems`:

```
Return NULL for zero size allocations
```

```
In POSIX, zero size memory allocations are implementation-defined behaviour. The implementation has two options:
```

<https://pubs.opengroup.org/onlinepubs/9699919799/functions/malloc.html>

[https://pubs.opengroup.org/onlinepubs/9699919799/functions/posix\\_memalign.html](https://pubs.opengroup.org/onlinepubs/9699919799/functions/posix_memalign.html)

Linux and FreeBSD return a unique pointer for zero size memory allocations. Return NULL on RTEMS to more likely catch the use of a zero size memory area by erroneous applications.

Update #4390.

### Comment 6

1. **Sebastian Huber**, Fri, 07 May 2021 05:08:44 GMT

In c46d125/rtems:

Check the alignment in `posix_memalign()` earlier

Make sure all conditions to do a proper memory allocation are satisfied before a zero size memory allocation is performed.

Update #4390.

### Comment 7

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** qualification added

## 4391 - SPARC GCC no longer needs sysconf(515) (\_SC\_STACK\_PROT)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4391">https://devel.rtems.org/ticket/4391</a> ( <a href="https://devel.rtems.org/ticket/4391">https://devel.rtems.org/ticket/4391</a> )
<b>Id</b>	4391
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	23 April 2021 20:22:39
<b>Modified</b>	9 June 2021 16:52:40
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	enhancement
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

In reviewing Ryan's rework of psx13, Gedare asked why there was a test for `sysconf(515)` conditionally compiled for SPARC. The answer was GCC needed it. But investigated showed that GCC has not had code to call this for over 20 years. It was removed per this commit.

```
commit ac4904440b4733f461bcd2c45915f502b0345f80
Author: Alexandre Oliva
Date: Mon Jan 24 00:47:38 2000 +0000
    sol2-sld-64.h (TRANSFER FROM TRAMPOLINE): Moved...
    * config/sparc/sol2-sld-64.h (TRANSFER FROM TRAMPOLINE): Moved...
    * config/sparc/sol2.h: ... here.
From-SVN: r31578
```

This ticket is to remove the code from `posix/src/sysconf.c` and update `psx13` accordingly.

### Comment 1

1. **Ryan Long**, Wed, 09 Jun 2021 16:52:40 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f83676d/rtems:

`sysconf`: Remove `sysconf(515)`

GCC originally needed this 20 years ago. No longer needed, so it is being removed.

Closes #4391

## 4392 - rtems: Constify timer fire when directives

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4392">https://devel.rtems.org/ticket/4392</a> ( <a href="https://devel.rtems.org/ticket/4392">https://devel.rtems.org/ticket/4392</a> )
<b>Id</b>	4392
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	27 April 2021 17:33:36
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The time of day pointer can be made constant in the timer fire when directives.

**Comment 1**

1. **Sebastian Huber**, Tue, 27 Apr 2021 17:34:49 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 2684f2a3/rtems:

```
rtems: Constify timer fire when directives
Close #4392.
```

**Comment 2**

1. **Sebastian Huber**, Wed, 28 Apr 2021 07:04:08 GMT

In de8fe65/rtems-docs:

```
c-user: Constify timer fire when directives
Update #4392.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords**: qualification added
- 

**4393 - rtems: Change rtems\_task\_get\_affinity() status**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4393">https://devel.rtems.org/ticket/4393</a> ( <a href="https://devel.rtems.org/ticket/4393">https://devel.rtems.org/ticket/4393</a> )
<b>Id</b>	4393
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	27 April 2021 17:37:41
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In case the processor set is not large enough to contain the processor affinity set of the task return RTEMS\_INVALID\_SIZE instead of RTEMS\_INVALID\_NUMBER. This is more in line with other directives since the issue is related to the size of an object.

**Comment 1**

1. **Sebastian Huber**, Tue, 27 Apr 2021 17:53:19 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 4b7c77b/rtems:

```
rtems: Change rtems_task_get_affinity() status

In case the processor set is not large enough to contain the processor affinity set of the task return RTEMS_INVALID_SIZE instead of
RTEMS_INVALID_NUMBER. This is more in line with other directives since the issue is related to the size of an object.

Close #4393.
```

**Comment 2**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

**4395 - Workspace initialization is broken for arm/imx7 and arm/raspberrypi**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4395">https://devel.rtems.org/ticket/4395</a> ( <a href="https://devel.rtems.org/ticket/4395">https://devel.rtems.org/ticket/4395</a> )
<b>Id</b>	4395
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	29 April 2021 11:38:47
<b>Modified</b>	29 April 2021 11:43:04
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4394:

The ARMV7\_CP15\_START\_WORKSPACE\_ENTRY\_INDEX has a wrong value. The bug was introduced by the fix for #4185.

**Comment 1**

1. **Sebastian Huber**, Thu, 29 Apr 2021 11:43:04 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 263e00b/rtems:

```
bsps/arm: ARMV7_CP15_START_WORKSPACE_ENTRY_INDEX

Change the ARMV7_CP15_START_WORKSPACE_ENTRY_INDEX value to be in line with the workspace entry in ARMV7_CP15_START_DEFAULT_SECTIONS.

Close #4395.
```

**4396 - Add futimens() and utimensat()**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4396">https://devel.rtems.org/ticket/4396</a> ( <a href="https://devel.rtems.org/ticket/4396">https://devel.rtems.org/ticket/4396</a> )
<b>Id</b>	4396
<b>Reporter</b>	Ryan Long
<b>Created</b>	29 April 2021 18:29:12
<b>Modified</b>	28 May 2021 21:29:11
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Implement the futimens and utimensat APIs

**Comment 1**

1. **Ryan Long**, Fri, 28 May 2021 21:29:11 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 335f705/rtems:

```
libcsupport: Added futimens() and utimensat()
Created futimens.c and utimensat.c to add support for the POSIX methods futimens() and utimensat().
utime() and utimes() are considered obsolete by POSIX, but RTEMS will continue to support them.
Closes #4396
```

---

**4397 - Make utime() use utimensat()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4397">https://devel.rtems.org/ticket/4397</a> ( <a href="https://devel.rtems.org/ticket/4397">https://devel.rtems.org/ticket/4397</a> )
<b>Id</b>	4397
<b>Reporter</b>	Ryan Long
<b>Created</b>	29 April 2021 18:30:34
<b>Modified</b>	28 May 2021 21:29:14
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Make utime use the utimensat API

**Comment 1**

1. **Ryan Long**, Fri, 28 May 2021 21:29:14 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In bb704123/rtems:

```
libcsupport: Implement utime() in terms of utimensat()
utime() now calls utimensat() to update file access and modification timestamps.
```

Updated license.

Closes #4397

## 4398 - Make utimes() use utimensat()

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4398">https://devel.rtems.org/ticket/4398</a> ( <a href="https://devel.rtems.org/ticket/4398">https://devel.rtems.org/ticket/4398</a> )
<b>Id</b>	4398
<b>Reporter</b>	Ryan Long
<b>Created</b>	29 April 2021 18:31:18
<b>Modified</b>	28 May 2021 21:29:18
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Make utimes use the utimensat API

### Comment 1

1. **Ryan Long**, Fri, 28 May 2021 21:29:18 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In ea881bf/rtems:

```

libcsupport: Implement utimes() in terms of utimensat()
utimes() now calls utimensat() to update file access and modification timestamps.
Updated license.
Closes #4398

```

---

## 4399 - Add tests for futimens() and utimensat()

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4399">https://devel.rtems.org/ticket/4399</a> ( <a href="https://devel.rtems.org/ticket/4399">https://devel.rtems.org/ticket/4399</a> )
<b>Id</b>	4399
<b>Reporter</b>	Ryan Long
<b>Created</b>	29 April 2021 18:50:00
<b>Modified</b>	28 May 2021 21:29:21
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Create tests to test the futimens() and utimensat() APIs

### Comment 1

1. **Ryan Long**, Fri, 28 May 2021 21:29:21 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**

4. **resolution:** set to **fixed**

In 6171a88/rtems:

```
psx13: Added tests for utimensat() and futimens()
Improved tests for utime() and utimes() and update license.
Close #4399
```

**4400 - Change filesystem utime\_h to utimens\_h to support nanosecond granularity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4400">https://devel.rtems.org/ticket/4400</a> ( <a href="https://devel.rtems.org/ticket/4400">https://devel.rtems.org/ticket/4400</a> )
<b>Id</b>	4400
<b>Reporter</b>	Ryan Long
<b>Created</b>	29 April 2021 19:09:39
<b>Modified</b>	28 May 2021 21:29:25
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Change utime\_h to utimens\_h for the new nanosecond granularity APIs

**Comment 1**

1. **Ryan Long**, Fri, 28 May 2021 21:29:25 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In ea41722c/rtems:

```
Change filesystem utime_h handler to utimens_h
Also updated licenses.
Closes #4400 Updates #3899
```

**4401 - rtems: Change rtems\_scheduler\_get\_processor\_set() status**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4401">https://devel.rtems.org/ticket/4401</a> ( <a href="https://devel.rtems.org/ticket/4401">https://devel.rtems.org/ticket/4401</a> )
<b>Id</b>	4401
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 May 2021 11:33:35
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

In case the processor set is not large enough to contain the processor set of the scheduler return RTEMS\_INVALID\_SIZE instead of RTEMS\_INVALID\_NUMBER. This is more in line with other directives since the issue is related to the size of an object.

A similar change was done in #4393.

**Comment 1**

1. **Sebastian Huber**, Thu, 06 May 2021 13:15:03 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 48898b3/rtems:

```
rtems: rtems_scheduler_get_processor_set() status
```

In case the processor set is not large enough to contain the processor set owned by the scheduler return RTEMS\_INVALID\_SIZE instead of RTEMS\_INVALID\_NUMBER. This is more in line with other directives since the issue is related to the size of an object.

Close #4401.

**Comment 2**

1. **Sebastian Huber**, Fri, 07 May 2021 06:09:35 GMT

In 6822af7/rtems:

```
rtems: rtems_scheduler_get_processor_set() docs
```

Document changed error status.

Update #4401.

**Comment 3**

1. **Sebastian Huber**, Fri, 07 May 2021 06:19:33 GMT

In e8cd4d3/rtems-docs:

```
c-user: rtems_scheduler_get_processor_set()
```

Document changed error status.

Update #4401.

**Comment 4**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

**4402 - rtemstoolkit/mailer.py option added twice**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4402">https://devel.rtems.org/ticket/4402</a> ( <a href="https://devel.rtems.org/ticket/4402">https://devel.rtems.org/ticket/4402</a> )
<b>Id</b>	4402
<b>Reporter</b>	Alex White
<b>Created</b>	5 May 2021 14:00:34
<b>Modified</b>	10 May 2021 16:47:35
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

In the `add_arguments` function, the intent is that the first two options are added to the arguments before the rest of them are iterated and added. The iteration of the remaining options, however, starts with the first option when it should start with the second.

Additionally, the order of keys in a dictionary cannot be relied on for all versions of Python we support. The dictionary should be changed to an `OrderedDict` to preserve key order to facilitate iteration.

**Comment 1**

1. **Alex White**, Wed, 05 May 2021 14:00:46 GMT



2. **owner:** set to **Alex White**
3. **status:** changed from **new** to **accepted**

**Comment 2**

1. **Alex White**, Mon, 10 May 2021 16:47:35 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In f18e6d8/rtems-tools:

```
rtemstoolkit/mailler.py: Fix option ordering for add_arguments
```

```
The ordering of keys cannot be guaranteed in a dictionary. This changes the options iteration to no longer rely on key ordering.
```

```
Closes #4402
```

**4403 - rtems\_timer\_fire\_when() returns wrong status code when wall\_time argument is NULL**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4403">https://devel.rtems.org/ticket/4403</a> ( <a href="https://devel.rtems.org/ticket/4403">https://devel.rtems.org/ticket/4403</a> )
<b>Id</b>	4403
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	6 May 2021 14:16:59
<b>Modified</b>	12 May 2021 04:41:26
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	trivial
<b>Keywords</b>	rtems_timer_fire_when, RTEMS_INVALID_CLOCK, wall_time
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The `__RTEMS Classic API Guide__` (<https://docs.rtems.org/branches/master/c-user/timer/directives.html#rtems-timer-fire-when>) elaborates for `rtems_timer_fire_when()`:

RTEMS\_INVALID\_ADDRESS

The `wall_time` parameter was NULL.

RTEMS\_INVALID\_CLOCK

The time of day was invalid.

Yet, calling `rtems_timer_fire_when()` with `wall_time = NULL` and all other parameters valid results in `RTEMS_INVALID_CLOCK`. Have a look into `cpukit/rtems/src/timercreate.c` function `_Timer_Fire_when()` to see the cause for this behavior.

I attach two patches:

- `sptimer_err01.patch` -- extends an existing test to reproduce this issue
- `timercreate.patch` -- fixes the issue

There are at least two ways to handle this bug and I do not want to decide which way to choose:

- Change the documentation
- Change the code

For the records:

```
RTEMS_VERSION = 6.0.0
remote origin = git://git.rtems.org/rtems.git
commit HEAD = 2c5199bb049efe8e29cd12461dc57bd6e30388e8 (HEAD -> master, origin/master, origin/HEAD)
config.ini =
[arm/realview_pbx_a9_qemu]
RTEMS_DEBUG = True
RTEMS_NETWORKING = True
RTEMS_POSIX_API = True
RTEMS_SMP = True
BUILD_TESTS = True
NEWLIB_VERSION = 3.2.0
SOURCE_BUILDER = Set Builder, 6 (5e449fb5c2cb)
GCC_VERSION = arm-rtems6-gcc (GCC) 10.2.1 20210309 (RTEMS 6, RSB 5e449fb5c2cb6812a238f9f9764fd339cbbf05c2, Newlib d10d0d9)
BINUTILS_VERSION = GNU ld (GNU Binutils) 2.36.1.20210309
```

**Attachments:**

**1 Frank Kuehndel, Thu, 06 May 2021 14:18:12 GMT**

**attach:** set to [sptimer\\_err01.patch \(https://devel.rtems.org/ticket/4403/sptimer\\_err01.patch\)](https://devel.rtems.org/ticket/4403/sptimer_err01.patch)

**2 Frank Kuehndel, Thu, 06 May 2021 14:19:12 GMT**

**attach:** set to [timercreate.patch \(https://devel.rtems.org/ticket/4403/timercreate.patch\)](https://devel.rtems.org/ticket/4403/timercreate.patch)

**Comment 1****1. Frank Kuehndel, Wed, 12 May 2021 04:41:26 GMT**

**2. status:** changed from **assigned** to **closed**

**3. resolution:** set to **fixed**

In 3af2dc7/rtems:

```
_TOD_Validate(): Fix incorrect return code

This patch fixes bug #4403. Directives
rtems_timer_fire_when() rtems_timer_server_fire_when() rtems_task_wake_when()
are documented to return RTEMS_INVALID_ADDRESS when their time-of-day argument is NULL. But actually they return RTEMS_INVALID_CLOCK.
To fix the issue this patch changes _TOD_Validate() to return a status code instead of just true/false.

Close #4403
```

**4406 - rtems: Constify rtems\_task\_wake\_when()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4406">https://devel.rtems.org/ticket/4406</a> ( <a href="https://devel.rtems.org/ticket/4406">https://devel.rtems.org/ticket/4406</a> )
<b>Id</b>	4406
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2021 11:40:31
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The time of day pointer can be made constant in this directive.

**Comment 1****1. Sebastian Huber, Wed, 12 May 2021 19:27:04 GMT**

**2. status:** changed from **assigned** to **closed**

**3. resolution:** set to **fixed**

In 523867d/rtems:

```
rtems: Constify rtems_task_wake_when()

Add a parameter to _TOD_Validate() to disable the validation of the ticks member.

There are two reasons for this change. Firstly, in rtems_task_wake_when() was a double check for time_buffer == NULL (one in
rtems_task_wake_when() and one in _TOD_Validate()). Secondly, the ticks member is ignored by rtems_task_wake_when(). This was done with
a write of zero to the ticks member and thus a modification of the user-provided structure. Now the structure is no longer modified.
Using a mask parameter is quite efficient. You just have to load an immediate value and there are no additional branches in
_TOD_Validate().

Close #4406.
```

**Comment 2****1. Sebastian Huber, Wed, 12 May 2021 19:32:26 GMT**

In 2588e8b/rtems-docs:

```
c-user: Constify rtems_task_wake_when()

Update #4406.
```

**Comment 3**

1. **Sebastian Huber**, Fri, 14 May 2021 06:10:25 GMT

In 45a34953/rtems:

```
rtems: Add TOD_Ticks_validation
Replace defines with an enum.
Update #4406.
```

**Comment 4**

1. **Sebastian Huber**, Mon, 17 May 2021 06:05:46 GMT

In 98cb84e/rtems:

```
arm/altera-cyclone-v: Fix compile error
Update #4406.
```

**Comment 5**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords: qualification** added

**4410 - rtems\_task\_start() does not check that the entry point is not equal to NULL (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4410">https://devel.rtems.org/ticket/4410</a> ( <a href="https://devel.rtems.org/ticket/4410">https://devel.rtems.org/ticket/4410</a> )
<b>Id</b>	4410
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 May 2021 07:13:01
<b>Modified</b>	14 May 2021 07:23:40
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4409:

Bug was introduced by commit 33829ce155069462ba410d396da431386369ed08 related to #2555.

**Comment 1**

1. **Sebastian Huber**, Fri, 14 May 2021 07:23:40 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In b87d2a6/rtems:

```
rtems: Check entry point in rtems_task_start()
Close #4410.
```

**4411 - rtems\_task\_restart() should set the real priority to the initial priority**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4411">https://devel.rtems.org/ticket/4411</a> ( <a href="https://devel.rtems.org/ticket/4411">https://devel.rtems.org/ticket/4411</a> )
<b>Id</b>	4411
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 May 2021 11:58:30
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The `rtems_task_restart()` directive should set the real priority to the initial priority. If another task is restarted this is only under certain conditions. The RTEMS 4.5.0 behaviour was to unconditionally set the real priority to the initial priority during a task restart.

**Comment 1**

1. **Sebastian Huber**, Fri, 14 May 2021 12:46:18 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Sebastian Huber**, Fri, 14 May 2021 15:05:27 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In b9083c55/rtems:

```
rtems: Always set the real priority during restart
Unconditionally set the real priority of the task to its initial priority during a task restart.
Close #4411.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
  2. **keywords:** **qualification** added
- 

**4412 - Unexpected rtems\_task\_restart() behaviour if called from within interrupt context**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4412">https://devel.rtems.org/ticket/4412</a> ( <a href="https://devel.rtems.org/ticket/4412">https://devel.rtems.org/ticket/4412</a> )
<b>Id</b>	4412
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 May 2021 12:49:57
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In `rtems_task_restart()` there is a check if the executing thread is restarted. However, in interrupt context, this simple check results in an internal error `INTERNAL_ERROR_BAD_THREAD_DISPATCH_DISABLE_LEVEL` if the executing thread is restarted. Check also if an ISR is in progress to make sure the thread restart works within interrupt context.

**Comment 1**

1. **Joel Sherrill**, Fri, 14 May 2021 13:01:36 GMT

This service is not documented as being allowed from an ISR. Only task suspend and resume are documented as allowed. I assume by "works" you mean that it returns an error without an internal error.

#### Comment 2

1. **Sebastian Huber**, Fri, 14 May 2021 13:08:57 GMT

The `rtems_task_restart()` works well if called from within interrupt context if you use `_ISR_Is_in_progress()` to determine a self restart. This directive doesn't use a mutex internally only ISR locks.

#### Comment 3

1. **Sebastian Huber**, Fri, 14 May 2021 15:05:31 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 73ebf9a/rtems:

```
rtems: Fix task restart within interrupt context

rtems_task_restart() may be called from within interrupt context. So checking only that the thread to restart is equal to the executing thread is insufficient to determine a self restart. We have to also check that no ISR is in progress. Merge _Thread_Restart_other() and _Thread_Restart_self() into one _Thread_Restart() since they share a lot of common code.

Close #4412.
```

#### Comment 4

1. **Sebastian Huber**, Wed, 26 May 2021 12:41:27 GMT

In de694b75/rtems:

```
score: Direct thread dispatch in a self restart

Commit 73ebf9a27ed5cd0fd3e0dc0da98345d7faa610a2 accidentally removed the direct thread dispatch in a self thread restart. In case of a self restart (always in task context) the directive shall not return. If this is not possible due to a bad thread dispatch disable level, then a fatal error shall occur.

Update #4412.
```

#### Comment 5

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

## 4413 - Allow pthread\_cancel() from within interrupt context

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4413">https://devel.rtems.org/ticket/4413</a> ( <a href="https://devel.rtems.org/ticket/4413">https://devel.rtems.org/ticket/4413</a> )
<b>Id</b>	4413
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 May 2021 15:39:21
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The `pthread_cancel()` does not immediately delete resources if invoked for threads other than the executing thread. With minor changes it may be called also from within interrupt context.

#### Comment 1

1. **Sebastian Huber**, Fri, 14 May 2021 16:35:56 GMT
2. **description**: modified (diff)

3. **summary:** changed from **Allow rtems\_task\_delete() and pthread\_cancel() from within interrupt context** to **Allow pthread\_cancel() from within interrupt context**

#### Comment 2

1. **Sebastian Huber**, Wed, 26 May 2021 12:41:20 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 29187be/rtems:

```
posix: Allow pthread_cancel() from within ISRs
Close #4413.
```

#### Comment 3

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** **qualification** added

### 4414 - Return RTEMS\_CALLED\_FROM\_ISR in rtems\_task\_delete()

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4414">https://devel.rtems.org/ticket/4414</a> ( <a href="https://devel.rtems.org/ticket/4414">https://devel.rtems.org/ticket/4414</a> )
<b>Id</b>	4414
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 May 2021 16:52:47
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

Calling rtems\_task\_delete() from within interrupt context has an unpredictable behaviour. It depends on which thread is interrupted. Return an error status instead.

#### Comment 1

1. **Sebastian Huber**, Wed, 26 May 2021 12:41:13 GMT

In b81d1ffd/rtems:

```
rtems: Return RTEMS_CALLED_FROM_ISR
If rtems_task_delete() is called from within interrupt context, then return RTEMS_CALLED_FROM_ISR. This makes the behaviour predictable.
Update #4414.
```

#### Comment 2

1. **Sebastian Huber**, Thu, 27 May 2021 05:08:57 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 2509b62/rtems-docs:

```
c-user: Document new rtems_task_delete() error
Close #4414.
```

#### Comment 3

1. **Sebastian Huber**, Thu, 27 May 2021 05:13:14 GMT

In 2fdd00f/rtems:

```
rtems: Document new rtems_task_delete() error
Update #4414.
```

#### **Comment 4**

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords: qualification** added

## **4415 - ReportsBase.cc: Division or modulo by float zero error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4415">https://devel.rtems.org/ticket/4415</a> ( <a href="https://devel.rtems.org/ticket/4415">https://devel.rtems.org/ticket/4415</a> )
<b>Id</b>	4415
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 14:47:47
<b>Modified</b>	29 June 2021 21:01:09
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

CID 1503709: Division or modulo by float zero in WriteSummaryReport?().

```
485 percentage = (double) notExecuted;
    CID 1503709 (#1 of 1): Division or modulo by float zero (DIVIDE_BY_ZERO)7. divide by zero: In expression percentage /=
(double)totalBytes, division by expression totalBytes which may be zero has undefined behavior.
486 percentage /= (double) totalBytes;
487 percentage *= 100.0;
```

#### **Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:51:04 GMT
2. **keywords: Coverity** added

#### **Comment 2**

1. **Ryan Long**, Tue, 29 Jun 2021 21:01:09 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In fbf313/rtems-tools:

```
ReportsBase?.cc: Remove possible division by zero
CID 1503709: Division or modulo by float zero
Closes #4415
```

## **4416 - rtems-exeinfo.cpp: Division or modulo by zero errors spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4416">https://devel.rtems.org/ticket/4416</a> ( <a href="https://devel.rtems.org/ticket/4416">https://devel.rtems.org/ticket/4416</a> )
<b>Id</b>	4416
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 15:29:32
<b>Modified</b>	29 June 2021 21:01:12
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1503008: Division or modulo by zero in output\_inlined().

```
CID 1503008 (#1 of 1): Division or modulo by zero (DIVIDE_BY_ZERO)9. divide_by_zero: In expression funcs_inlined.size() * 100UL /
total_size, division by expression total_size which may be zero has undefined behavior.
801     std::cout << "inlined funcs : " << funcs_inlined.size () << std::endl
802     << "    total funcs : " << total << std::endl
803     << " % inline funcs : " << (funcs_inlined.size () * 100) / total << '%'
804     << std::endl
```

CID 1503015: Division or modulo by zero in output\_inlined().

```
CID 1503015 (#1-2 of 2): Division or modulo by zero (DIVIDE_BY_ZERO)18. divide_by_zero: In expression inlined_size * 100UL /
total_size, division by expression total_size which may be zero has undefined behavior.
805     << "    total size : " << total_size << std::endl
806     << "    inline size : " << inlined_size << std::endl
807     << " % inline size : " << (inlined_size * 100) / total_size << '%'
808     << std::endl;
```

### Comment 1

1. **Ryan Long**, Tue, 18 May 2021 15:52:11 GMT
2. **keywords:** Coverity added

### Comment 2

1. **Ryan Long**, Tue, 29 Jun 2021 21:01:12 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 7d3b8ac/rtems-tools:

rtems-exeinfo.cpp: Fix division by zero errors

CID 1503008: Division or modulo by zero CID 1503015: Division or modulo by zero

Closes #4416

## 4417 - Explanations.cc: Resource leak error spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4417">https://devel.rtems.org/ticket/4417</a> ( <a href="https://devel.rtems.org/ticket/4417">https://devel.rtems.org/ticket/4417</a> )
<b>Id</b>	4417
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 16:17:31
<b>Modified</b>	4 June 2021 17:23:17
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description



CID 1399608: Resource leak in load().

```
CID 1399608 (#1 of 1): Resource leak (RESOURCE_LEAK)9. leaked_storage: Variable explain going out of scope leaks the storage it points to.
```

**Comment 1**1. **Ryan Long**, Mon, 17 May 2021 16:21:48 GMT

Replying to Ryan Long:

CID 1399608: Resource leak in load().

```
CID 1399608 (#1 of 1): Resource leak (RESOURCE_LEAK)9. leaked_storage: Variable explain going out of scope leaks the storage it points to.
```

Also, CID 1399611: Resource leak in load().

```
48 while ( 1 ) {
   4. alloc_fn: Storage is returned from allocation function operator new.
   5. var assign: Assigning: e = storage returned from new Coverage::Explanation.
   CID 1399611 (#2 of 2): Resource leak (RESOURCE_LEAK)21. overwrite_var: Overwriting e in e = new Coverage::Explanation leaks the storage that e points to.
49     e = new Explanation;
```

**Comment 2**1. **Ryan Long**, Tue, 18 May 2021 15:53:42 GMT2. **keywords:** Coverity added**Comment 3**1. **Ryan Long**, Fri, 04 Jun 2021 17:23:17 GMT2. **owner:** set to **Ryan Long** <ryan.long@...>3. **status:** changed from **new** to **closed**4. **resolution:** set to **fixed**

In 9f4887c/rtems-tools:

Explanations.cc: Fix resource leaks

CID 1399608: Resource leak in load(). CID 1399611: Resource leak in load().

Closes #4417

**4418 - GcovData.cc: Resource leak error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4418">https://devel.rtems.org/ticket/4418</a> ( <a href="https://devel.rtems.org/ticket/4418">https://devel.rtems.org/ticket/4418</a> )
<b>Id</b>	4418
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 16:20:07
<b>Modified</b>	4 June 2021 17:23:22
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399610: Resource leak in readFrame().

```
250 newFunction = new GcovFunctionData;
   5. noescape: Resource newFunction is not freed or pointed-to in readFunctionFrame. [show details]
   6. Condition !this->readFunctionFrame(header, gcovFile, newFunction), taking true branch.
251     if ( !readFunctionFrame(header, gcovFile, newFunction) ){
252         fprintf( stderr, "Error while reading FUNCTION from gcov file...\n" );
   CID 1399610 (#1 of 1): Resource leak (RESOURCE_LEAK)7. leaked_storage: Variable newFunction going out of scope leaks the storage it points to.
253         return false;
254     }
```

**Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:54:12 GMT
2. **keywords:** Coverity added

**Comment 2**

1. **Ryan Long**, Fri, 04 Jun 2021 17:23:22 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 08d9f37/rtems-tools:

```
GcovData?.cc: Fix resource leak
CID 1399610: Resource leak in readFrame().
Closes #4418
```

**4419 - TraceReaderLogQEMU.cc: Resource leak error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4419">https://devel.rtems.org/ticket/4419</a> ( <a href="https://devel.rtems.org/ticket/4419">https://devel.rtems.org/ticket/4419</a> )
<b>Id</b>	4419
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 16:28:49
<b>Modified</b>	4 June 2021 17:23:19
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399615: Resource leak in processFile().

```
113 //
114 // Discard Header section
115 //
116 6. noescape: Resource logFile is not freed or pointed-to in ReadUntilFound. [show details]
117 7. Condition !ReadUntilFound(logFile, "-----"), taking true branch.
118 if (! ReadUntilFound( logFile, QEMU_LOG_SECTION_END ) ) {
119     fprintf( stderr, "Unable to locate end of log file header\n" );
120     CID 1399615 (#2 of 2): Resource leak (RESOURCE_LEAK)8. leaked_storage: Variable logFile going out of scope leaks the storage it
121     points to.
122     return false;
123 }
```

**Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:54:42 GMT
2. **keywords:** Coverity added

**Comment 2**

1. **Ryan Long**, Fri, 04 Jun 2021 17:23:19 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In dfe012d/rtems-tools:

```
TraceReaderLogQEMU.cc: Fix resource leak
CID 1399615: Resource leak in processFile().
Closes #4419
```

**4420 - TraceWriterQEMU.cc: Resource leak error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4420">https://devel.rtems.org/ticket/4420</a> ( <a href="https://devel.rtems.org/ticket/4420">https://devel.rtems.org/ticket/4420</a> )
<b>Id</b>	4420
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 16:35:57
<b>Modified</b>	4 June 2021 17:23:24
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399621: Resource leak in writeFile().

```

5. noescape: Resource traceFile is not freed or pointed-to in fwrite.
116   status = ::fwrite( &header, sizeof(trace_header), 1, traceFile );
6. Condition status != 1, taking true branch.
117   if (status != 1) {
118       std::cerr << "Unable to write header to " << file << std::endl;
CID 1399621 (#1 of 1): Resource leak (RESOURCE_LEAK)7. leaked_storage: Variable traceFile going out of scope leaks the storage it
points to.
119   return false;

```

**Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:55:13 GMT
2. **keywords:** Coverity added

**Comment 2**

1. **Ryan Long**, Fri, 04 Jun 2021 17:23:24 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In a0b54f0/rtems-tools:

```

TraceWriterQEMU.cc: Fix resource leak
CID 1399621: Resource leak in writeFile().
Closes #4420

```

**4421 - DesiredSymbols.cc: Resource leak error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4421">https://devel.rtems.org/ticket/4421</a> ( <a href="https://devel.rtems.org/ticket/4421">https://devel.rtems.org/ticket/4421</a> )
<b>Id</b>	4421
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 16:48:44
<b>Modified</b>	4 June 2021 17:23:26
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1503018: Resource leak in load().

```

13. alloc_fn: Storage is returned from allocation function operator new.
14. noEscape: Resource new Coverage::SymbolInformation is not freed or pointed-to in operator =. [show details]
CID 1503018 (#2 of 2): Resource leak (RESOURCE_LEAK)15. leaked_storage: Failing to save or free storage allocated by new
Coverage::SymbolInformation leaks it.
104     set[sym.name()] = *(new SymbolInformation);

```

**Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:55:40 GMT
2. **keywords:** Coverity added

**Comment 2**

1. **Ryan Long**, Fri, 04 Jun 2021 17:23:26 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 9527f65/rtems-tools:

```

DesiredSymbols?.cc: Fix resource leak
CID 1503018: Resource leak in load().
Closes #4421

```

**4422 - ReportsBase.cc: Resource leak error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4422">https://devel.rtems.org/ticket/4422</a> ( <a href="https://devel.rtems.org/ticket/4422">https://devel.rtems.org/ticket/4422</a> )
<b>Id</b>	4422
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 16:50:30
<b>Modified</b>	4 June 2021 17:23:28
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1503711: Resource leak in WriteSummaryReport?().

```

548     fprintf(
549         report,
550         "Percentage branch paths covered : %4.4g\n",
551         100.0 - percentageBranches
552     );
553 }
CID 1503711 (#1 of 1): Resource leak (RESOURCE_LEAK)34. leaked_storage: Variable report going out of scope leaks the storage it
points to.
554 }
555

```

**Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:56:04 GMT
2. **keywords:** Coverity added

**Comment 2**

1. **Ryan Long**, Fri, 04 Jun 2021 17:23:28 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 52780608/rtems-tools:

```

ReportsBase?.cc: Fix Resource leak

```

CID 1503711: Resource leak in WriteSummaryReport?().

Closes #4422

## 4423 - record-client.c: Unchecked return value error spotted by Coverity

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4423">https://devel.rtems.org/ticket/4423</a> ( <a href="https://devel.rtems.org/ticket/4423">https://devel.rtems.org/ticket/4423</a> )
<b>Id</b>	4423
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 19:14:04
<b>Modified</b>	30 September 2021 16:07:40
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

CID 1503011: Unchecked return value in resolve\_hold\_back().

```

191     for ( index = begin_index; index < per_cpu->item_index; ++index ) {
192         const rtems_record_item_64 *item;
193
194         item = &per_cpu->items[ index ];
195         CID 1503011 (#1 of 1): Unchecked return value (CHECKED_RETURN)12. check_return: Calling visit without checking return value (as is
done elsewhere 4 out of 5 times).
195         visit( ctx, item->event, item->data );

```

### Comment 1

1. **Ryan Long**, Tue, 18 May 2021 15:56:40 GMT
2. **keywords:** Coverity added

### Comment 2

1. **Ryan Long**, Thu, 30 Sep 2021 16:07:40 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 7c37893/rtems-tools:

```

record-client.c: Ignore return value from visit()
CID 1503011: Unchecked return value in resolve_hold_back().
Closes #4423

```

---

## 4424 - rtems-bin2c.c: Copy into fixed size buffer spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4424">https://devel.rtems.org/ticket/4424</a> ( <a href="https://devel.rtems.org/ticket/4424">https://devel.rtems.org/ticket/4424</a> )
<b>Id</b>	4424
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 20:57:47
<b>Modified</b>	29 September 2021 14:58:29
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1063892: Copy into fixed size buffer in process().

```

141 char *ifbasename;
142 ifbasename = basename(ifbasename_to_free);
143
CID 1063892 (#1 of 1): Copy into fixed size buffer (STRING_OVERFLOW)13. fixed_size_dest: You might overrun the 1025-character
fixed-size string buf by copying ifbasename without checking the length.
144 strcpy(buf, ifbasename);

```

**Comment 1**

1. **Ryan Long**, Tue, 18 May 2021 15:57:16 GMT
2. **keywords:** **Coverity** added

**Comment 2**

1. **Ryan Long**, Wed, 29 Sep 2021 14:58:29 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 05dab02/rtems-tools:

rtems-bin2c.c: Check length of buffer to be copied

CID 1063892: Copy into fixed size buffer in process().

Closes #4424

**4425 - GcovFunctionData.cc: Copy into fixed size buffer errors spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4425">https://devel.rtems.org/ticket/4425</a> ( <a href="https://devel.rtems.org/ticket/4425">https://devel.rtems.org/ticket/4425</a> )
<b>Id</b>	4425
<b>Reporter</b>	Ryan Long
<b>Created</b>	17 May 2021 21:51:03
<b>Modified</b>	16 December 2021 20:49:57
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1063892: Copy into fixed size buffer in addBlock().

```
CID 1399613 (#1 of 1): Copy into fixed size buffer (STRING_OVERFLOW)1. fixed_size_dest: You might overrun the 256-character fixed-size string block.sourceFileName by copying sourceFileName without checking the length.
  2. parameter_as_source: Note: This defect has an elevated risk because the source argument is a parameter of the current function.
184   strcpy (block.sourceFileName, sourceFileName);
```

CID 1399616: Copy into fixed size buffer in setBlockFileName().

```
CID 1399616 (#1 of 1): Copy into fixed size buffer (STRING_OVERFLOW)1. fixed_size_dest: You might overrun the 256-character fixed-size string block->sourceFileName by copying fileName without checking the length.
  2. parameter_as_source: Note: This defect has an elevated risk because the source argument is a parameter of the current function.
298   strcpy(block->sourceFileName, fileName);
```

### Comment 1

1. **Ryan Long**, Mon, 17 May 2021 21:57:02 GMT

Replying to Ryan Long:

CID 1063892: Copy into fixed size buffer in addBlock().

CID is actually 1399613

```
CID 1399613 (#1 of 1): Copy into fixed size buffer (STRING_OVERFLOW)1. fixed_size_dest: You might overrun the 256-character fixed-size string block.sourceFileName by copying sourceFileName without checking the length.
  2. parameter_as_source: Note: This defect has an elevated risk because the source argument is a parameter of the current function.
184   strcpy (block.sourceFileName, sourceFileName);
```

CID 1399616: Copy into fixed size buffer in setBlockFileName().

```
CID 1399616 (#1 of 1): Copy into fixed size buffer (STRING_OVERFLOW)1. fixed_size_dest: You might overrun the 256-character fixed-size string block->sourceFileName by copying fileName without checking the length.
  2. parameter_as_source: Note: This defect has an elevated risk because the source argument is a parameter of the current function.
298   strcpy(block->sourceFileName, fileName);
```

### Comment 2

1. **Ryan Long**, Tue, 18 May 2021 15:57:49 GMT

2. **keywords:** Coverity added

### Comment 3

1. **Ryan Long**, Thu, 16 Dec 2021 20:49:57 GMT

2. **status:** changed from **new** to **closed**

3. **resolution:** set to **fixed**

## 4426 - clock\_nanosleep() may use wrong clock for relative times

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4426">https://devel.rtems.org/ticket/4426</a> ( <a href="https://devel.rtems.org/ticket/4426">https://devel.rtems.org/ticket/4426</a> )
<b>Id</b>	4426
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	18 May 2021 11:09:45
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

For relative times, the clock identifier is not used to select the clock and instead always the CLOCK\_MONOTONIC is used. A side-effect is that sleep() and nanosleep() use the wrong clock (CLOCK\_MONOTONIC instead of CLOCK\_REALTIME).

### Comment 1

1. **Sebastian Huber**, Tue, 18 May 2021 11:55:05 GMT

2. **description:** modified (diff)

### Comment 2

1. **Sebastian Huber**, Tue, 18 May 2021 18:32:39 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 24c62932/rtems:

```
posix: Fix use of clock for relative times
Close #4426.
```

### Comment 3

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords**: **qualification** added

## 4427 - GcovData.cc: Dereference after null check error spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4427">https://devel.rtems.org/ticket/4427</a> ( <a href="https://devel.rtems.org/ticket/4427">https://devel.rtems.org/ticket/4427</a> )
<b>Id</b>	4427
<b>Reporter</b>	Ryan Long
<b>Created</b>	18 May 2021 16:19:41
<b>Modified</b>	4 August 2021 17:59:59
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1399597: Dereference after null check in readGcnoFile().

```
53 strcpy( gcnoFileName, fileName );
54 strcpy( gcdaFileName, fileName );
55 strcpy( textFileName, fileName );
56 strcpy( cFileName, fileName );
57 tempString = strstr( gcdaFileName, ".gcno" );
58 tempString2 = strstr( textFileName, ".gcno" );
59 tempString3 = strstr( cFileName, ".gcno" );
60
61 2. Condition tempString == NULL, taking true branch.
62 3. var compare_op: Comparing tempString to null implies that tempString might be null.
63 4. Condition tempString2 == NULL, taking false branch.
64 if ( (tempString == NULL) && (tempString2 == NULL) ){
65     fprintf(stderr, "ERROR: incorrect name of *.gcno file\n");
66 }
67 else
68 {
69     CID 1399597 (#1 of 1): Dereference after null check (FORWARD_NULL)5. var_deref_model: Passing null pointer tempString to strcpy,
which dereferences it.
70     strcpy( tempString, ".gcda");           // construct gcda file name
71     strcpy( tempString2, ".txt");           // construct report file name
72     strcpy( tempString3, ".c");           // construct source file name
73 }
```

### Comment 1

1. **Ryan Long**, Wed, 04 Aug 2021 17:59:59 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

## 4428 - ReportsBase.cc: Dereference after null check error spotted by Coverity



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4428">https://devel.rtems.org/ticket/4428</a> ( <a href="https://devel.rtems.org/ticket/4428">https://devel.rtems.org/ticket/4428</a> )
<b>Id</b>	4428
<b>Reporter</b>	Ryan Long
<b>Created</b>	18 May 2021 16:24:15
<b>Modified</b>	7 October 2021 14:29:59
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1503710: Dereference after null check in WriteAnnotatedReport?().

```

12. var_compare_op: Comparing info.uncoveredRanges to null implies that info.uncoveredRanges might be null.
13. Condition info.uncoveredBranches == NULL, taking false branch.
219   if ((info.uncoveredRanges == NULL) &&
220       (info.uncoveredBranches == NULL))
    5. Continuing loop.
    9. Continuing loop.
221   continue;
222
223   // If uncoveredRanges and uncoveredBranches are empty, then everything
224   // must have been covered for this symbol. Just skip it.
    CID 1503710 (#1 of 1): Dereference after null check (FORWARD_NULL)14. var_deref_model: Passing null pointer info.uncoveredRanges-
>set to empty, which dereferences it. [show details]
225   if ((info.uncoveredRanges->set.empty()) &&
226       (info.uncoveredBranches->set.empty()))
227   continue;

```

**Comment 1**

1. **Ryan Long**, Thu, 07 Oct 2021 14:29:59 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 7245050/rtems-tools:

```
ReportsBase?.cc: Add assert for member variables
```

The uncoveredRanges and uncoveredBranch member variables are allocated as a pair. They are both either NULL or not NULL. Coverity does not know this though, so this assert is added to ensure they are not NULL before being dereferenced.

CID 1503710: Dereference after null check

Closes #4428

**4430 - DesiredSymbols.cc: Uninitialized pointer read error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4430">https://devel.rtems.org/ticket/4430</a> ( <a href="https://devel.rtems.org/ticket/4430">https://devel.rtems.org/ticket/4430</a> )
<b>Id</b>	4430
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 May 2021 14:14:38
<b>Modified</b>	4 August 2021 18:04:04
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	Coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1503005: Uninitialized pointer read in load().

```

111     if (sym.type() == sym.st_func) {
      20. alloc fn: Calling operator new which returns uninitialized memory.
      CID 1503005 (#2 of 2): Uninitialized pointer read (UNINIT)21. uninitialized use in call: Using uninitialized value (new
Coverage::SymbolInformation).sourceFile when calling operator =. [show details]
112     set[sym.name()] = *(new SymbolInformation);

```

**Comment 1**

1. **Ryan Long**, Wed, 04 Aug 2021 18:04:04 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

**4432 - GcovFunctionData.cc: Uninitialized pointer field error spotted by coverity**

**Link** <https://devel.rtems.org/ticket/4432> (<https://devel.rtems.org/ticket/4432>)

**Id** 4432

**Reporter** Ryan Long

**Created** 19 May 2021 16:08:42

**Modified** 27 September 2021 22:18:28

**Owner** Ryan Long <ryan.long@...>

**Type** defect

**Component** tool

**Status** closed

**Resolution** fixed

**Version** 6

**Milestone** 6.1

**Priority** normal

**Severity** normal

**Keywords** Coverity

**Cc**

**Blocking**

**Blocked by**

**Description**

CID 1399640: Uninitialized pointer field in GcovFunctionData?().

```

20 GcovFunctionData::GcovFunctionData()
21 {
22     numberOfArcs = 0;
23     numberOfBlocks = 0;
24     coverageMap = NULL;
      2. uninitialized_member: Non-static class member id is not initialized in this constructor nor in any functions that it calls.
      4. uninitialized_member: Non-static class member checksum is not initialized in this constructor nor in any functions that it calls.
      6. uninitialized_member: Non-static class member firstLineNumber is not initialized in this constructor nor in any functions that it
calls.
      CID 1399640 (#1 of 1): Uninitialized pointer field (UNINIT_CTOR)8. uninitialized_member: Non-static class member symbolInfo is not
initialized in this constructor nor in any functions that it calls.
25 }

```

**Comment 1**

1. **Ryan Long**, Wed, 19 May 2021 16:09:58 GMT
2. **summary:** changed from **DesiredSymbols.h: Uninitialized pointer field error spotted by coverity** to **GcovFunctionData.cc: Uninitialized pointer field error spotted by coverity**

**Comment 2**

1. **Ryan Long**, Mon, 27 Sep 2021 22:18:28 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 247d39a/rtems-tools:

GcovFunctionData?.cc: Initialize member variables

CID 1399640: Uninitialized pointer field

Closes #4432

**4433 - DesiredSymbols.h: Uninitialized pointer field error spotted by coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4433">https://devel.rtems.org/ticket/4433</a> ( <a href="https://devel.rtems.org/ticket/4433">https://devel.rtems.org/ticket/4433</a> )
<b>Id</b>	4433
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 May 2021 16:13:54
<b>Modified</b>	27 September 2021 22:18:26
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399637: Uninitialized pointer field in SymbolInformation?().

```

176 SymbolInformation() :
177     baseAddress( 0 ),
178     uncoveredBranches( NULL ),
179     uncoveredRanges( NULL ),
180     unifiedCoverageMap( NULL )
181 {
182     CID 1399637 (#1 of 1): Uninitialized pointer field (UNINIT_CTOR)2.
  uninitialized in this constructor nor in any functions that it calls.
  }

```

**Comment 1**

1. **Ryan Long**, Mon, 27 Sep 2021 22:18:26 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 06a39db/rtems-tools:

```

DesiredSymbols?.h: Initialize symbolInfo
CID 1399627: Uninitialized pointer field
Closes #4433

```

**4434 - record-filter-zlib.cc: Uninitialized pointer field error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4434">https://devel.rtems.org/ticket/4434</a> ( <a href="https://devel.rtems.org/ticket/4434">https://devel.rtems.org/ticket/4434</a> )
<b>Id</b>	4434
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 May 2021 16:29:34
<b>Modified</b>	27 September 2021 22:18:30
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1503020: Uninitialized pointer field in ZlibFilter?().

```

36 ZlibFilter::ZlibFilter() : buffer_(65536)
37 {
  CID 1503013: Unchecked return value from library (CHECKED_RETURN) [select issue]
38 inflateInit(&stream);
  2. uninit_member: Non-static class member stream_.next_in is not initialized in this constructor nor in any functions that it calls.
  4. uninit_member: Non-static class member stream_.avail_in is not initialized in this constructor nor in any functions that it calls.
  6. uninit_member: Non-static class member stream_.total_in is not initialized in this constructor nor in any functions that it calls.
  8. uninit_member: Non-static class member stream_.next_out is not initialized in this constructor nor in any functions that it calls.
 10. uninit_member: Non-static class member stream_.avail_out is not initialized in this constructor nor in any functions that it calls.
 12. uninit_member: Non-static class member stream_.total_out is not initialized in this constructor nor in any functions that it calls.
 14. uninit_member: Non-static class member stream_.msg is not initialized in this constructor nor in any functions that it calls.
 16. uninit_member: Non-static class member stream_.zalloc is not initialized in this constructor nor in any functions that it calls.
 18. uninit_member: Non-static class member stream_.zfree is not initialized in this constructor nor in any functions that it calls.
 20. uninit_member: Non-static class member stream_.opaque is not initialized in this constructor nor in any functions that it calls.
 22. uninit_member: Non-static class member stream_.data_type is not initialized in this constructor nor in any functions that it calls.
 24. uninit_member: Non-static class member stream_.adler is not initialized in this constructor nor in any functions that it calls.
  CID 1503020 (#1 of 1): Uninitialized pointer field (UNINIT_CTOR) 26. uninit_member: Non-static class member stream_.reserved is not initialized in this constructor nor in any functions that it calls.
39)

```

**Comment 1**

1. **Ryan Long**, Mon, 27 Sep 2021 22:18:30 GMT
2. **owner:** set to **Ryan Long** <[ryan.long@...](mailto:ryan.long@...)>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 7b5dc22/rtems-tools:

```

record-filter-zlib.cc: Initialize stream_'s fields
CID 1503020: Uninitialized pointer field
Closes #4434

```

**4435 - Thread cancellation may produce ready threads with an active thread timer**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4435">https://devel.rtems.org/ticket/4435</a> ( <a href="https://devel.rtems.org/ticket/4435">https://devel.rtems.org/ticket/4435</a> )
<b>Id</b>	4435
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 May 2021 15:15:13
<b>Modified</b>	23 June 2021 07:07:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The `_Thread_Cancel()` (in contrast to `_Thread_Restart()` which uses a similar code block) may produce ready threads with an active timer in case the thread to cancel has its thread life protection enabled. The problem is this code block:

```

Priority_Control priority;
_Thread Add life change request( the_thread );
if ( _Thread_Is life change allowed( previous ) ) {
  _Thread_State_release( the_thread, &lock_context );
  _Thread_queue_Extract_with_proxy( the_thread );
  _Thread_Timer_remove( the_thread );
} else {
  _Thread_Clear_state_locked( the_thread, STATES_SUSPENDED );
  _Thread_State_release( the_thread, &lock_context );
}
priority = _Thread_Get_priority( executing );
_Thread_Raise_real_priority( the_thread, priority );
_Thread_Remove life change request( the_thread );

```

The life change request should only be added/removed if a life change is allowed (see `_Thread_Restart()`).

**Comment 1**

1. **Sebastian Huber**, Wed, 26 May 2021 12:41:24 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In ce6319a/rtems:

```
score: Fix _Thread_Cancel()
```

The `_Thread_Cancel()` (in contrast to `_Thread_Restart()` which used a similar code block) may have produced ready threads with an active timer in case the thread to cancel had its thread life protection enabled. The problem was this code block:

```
Priority_Control priority;
```

```
_Thread_Add_life_change_request( the_thread );
```

```
if ( _Thread_Is_life_change_allowed( previous ) ) {
```

```
    _Thread_State_release( the_thread, &lock_context );
```

```
    _Thread_queue_Extract_with_proxy( the_thread ); _Thread_Timer_remove( the_thread );
```

```
} else {
```

```
    _Thread_Clear_state_locked( the_thread, STATES_SUSPENDED ); _Thread_State_release( the_thread, &lock_context );
```

```
}
```

```
priority = _Thread_Get_priority( executing ); _Thread_Raise_real_priority( the_thread, priority );
_Thread_Remove_life_change_request( the_thread );
```

The life change request should only be added/removed if a life change is allowed (see `_Thread_Restart()`). Add `_Thread_Try_life_change_request()` and use it in `_Thread_Cancel()` and `_Thread_Restart()`.

Close #4435.

## Comment 2

1. **Sebastian Huber**, Wed, 23 Jun 2021 07:07:55 GMT
2. **keywords:** qualification added

## 4437 - powerpc/shared/sbrk.c: Do not reference errno

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4437">https://devel.rtems.org/ticket/4437</a> ( <a href="https://devel.rtems.org/ticket/4437">https://devel.rtems.org/ticket/4437</a> )
<b>Id</b>	4437
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 May 2021 21:24:50
<b>Modified</b>	16 December 2021 16:32:43
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

Using `errno` implicitly references the `newlib` reentrancy structure. Changing this eliminates one reason the reentrancy code may be pulled into `minimum.exe`.

## Comment 1

1. **Kinsey Moore**, Thu, 16 Dec 2021 16:32:43 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

This should have been closed by 402a206a1b1ff984b14c3321f0bc1340c4873147 but the close tag was malformed.

**4438 - powerpc/shared/irq/ppc-irq-legacy.c: Use rtems\_malloc() not malloc()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4438">https://devel.rtems.org/ticket/4438</a> ( <a href="https://devel.rtems.org/ticket/4438">https://devel.rtems.org/ticket/4438</a> )
<b>Id</b>	4438
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 May 2021 21:24:57
<b>Modified</b>	25 May 2021 13:33:50
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

malloc() is required to set errno which implicitly references the newlib reentrancy structure. Changing this eliminates one reason the reentrancy code may be pulled into minimum.exe.

**Comment 1**

1. **Joel Sherrill**, Tue, 25 May 2021 13:33:50 GMT
2. **owner:** set to **Joel Sherrill** <joel@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f9d59075/rtems:

```
ppc-irq-legacy.c: Use rtems_malloc() instead of malloc().
Closes #4438.
```

---

**4439 - Open of /dev/console should only be in SysInit List if Console Enabled**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4439">https://devel.rtems.org/ticket/4439</a> ( <a href="https://devel.rtems.org/ticket/4439">https://devel.rtems.org/ticket/4439</a> )
<b>Id</b>	4439
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 May 2021 21:28:46
<b>Modified</b>	25 May 2021 13:33:57
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The current code implicitly requires that the code to open /dev/console be included in the system initialization set anytime a dependency exists on the newlib reentrancy structure. This means that referencing errno pulls in at least open(), libio code, close(), atexit(), and unmount support.

This was shown to result in about 20K of text an 5K of data being included in powerpc/psim minimum.exe. A similar impact would happen on all BSPs.

**Comment 1**

1. **Joel Sherrill**, Tue, 25 May 2021 13:33:57 GMT
2. **owner:** set to **Joel Sherrill** <joel@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 76d5722b/rtems:

sysinit: Do not open console when just referencing reentrancy structure.

This change eliminates a system initialization dependency which resulted in an application without a file system or console referencing `errno` being forced to include the code to `open(/dev/console)`, `close()`, `atexit()`, and the unmount infrastructure.

Closes #4439.

---

## **4442 - CID 1399721: Copy into fixed size buffer**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4442">https://devel.rtems.org/ticket/4442</a> ( <a href="https://devel.rtems.org/ticket/4442">https://devel.rtems.org/ticket/4442</a> )
<b>Id</b>	4442
<b>Reporter</b>	Harrison Gerber
<b>Created</b>	26 May 2021 17:52:45
<b>Modified</b>	26 May 2021 22:45:46
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	normal
<b>Keywords</b>	coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

In `pci_cfg_print_device`: A source buffer of statically unknown size is copied into a fixed-size destination buffer (CWE-120)

### **Comment 1**

1. **Gedare Bloom**, Wed, 26 May 2021 18:10:12 GMT
2. **status**: changed from **new** to **accepted**
3. **severity**: changed from **minor** to **normal**
4. **component**: changed from **admin** to **lib**
5. **owner**: set to **Gedare Bloom**
6. **milestone**: set to **6.1**
7. **keywords**: **coverity** added

### **Comment 2**

1. **Harrison Edward Gerber**, Wed, 26 May 2021 22:45:46 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In `e2011dc/rtems`:

```
cpukit/libpci: fix potential buffer overflow in pci_cfg_print_code.c
```

See also CID 1399721

Closes #4442

---

## **4444 - CID 1399727: Copy into fixed size buffer**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4444">https://devel.rtems.org/ticket/4444</a> ( <a href="https://devel.rtems.org/ticket/4444">https://devel.rtems.org/ticket/4444</a> )
<b>Id</b>	4444
<b>Reporter</b>	Harrison Gerber
<b>Created</b>	26 May 2021 22:21:33
<b>Modified</b>	28 May 2021 22:00:54
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In rtems\_monitor\_line\_editor: A source buffer of statically unknown size is copied into a fixed-size destination buffer (CWE-120)

NOTE: Issue is more regarding source/dest overlapping with use of strcpy: needs change to use memory copy for overlapping source/dest

**Comment 1**

1. **Harrison Edward Gerber**, Fri, 28 May 2021 22:00:54 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 6a56fd9/rtems:

```
cpukit/libmisc/monitor: Fix src/dest overlap of strcpy in mon-editor.c
```

See also CID 1399727

Closes #4444

---

**4445 - CID 1468684: Uninitialized scalar variable**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4445">https://devel.rtems.org/ticket/4445</a> ( <a href="https://devel.rtems.org/ticket/4445">https://devel.rtems.org/ticket/4445</a> )
<b>Id</b>	4445
<b>Reporter</b>	Harrison Gerber
<b>Created</b>	26 May 2021 23:20:54
<b>Modified</b>	2 June 2021 15:31:59
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In tcp\_remote\_connect: Use of an uninitialized variable (CWE-457)

**Comment 1**

1. **Harrison Edward Gerber**, Wed, 02 Jun 2021 15:31:59 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 9429115c/rtems:

```
cpukit/libdebugger: Fix for sockaddr_in not being initialized
```

See also CID 1468684

Closes #4445

---



**4448 - covoar reports uncovered ranges of size 1**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4448">https://devel.rtems.org/ticket/4448</a> ( <a href="https://devel.rtems.org/ticket/4448">https://devel.rtems.org/ticket/4448</a> )
<b>Id</b>	4448
<b>Reporter</b>	Alex White
<b>Created</b>	2 June 2021 14:15:25
<b>Modified</b>	4 June 2021 19:25:14
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	coverage, covoar
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The uncovered range reports produced by covoar for the ARM architecture contain ranges of size 1. When clicked, they link to instructions that appears to be covered.

This should be fixed to remove these erroneous ranges.

**Comment 1**

1. **Alex White**, Wed, 02 Jun 2021 14:15:35 GMT
2. **owner:** set to **Alex White**
3. **status:** changed from **new** to **accepted**

**Comment 2**

1. **Alex White**, Fri, 04 Jun 2021 19:25:14 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In c17664f/rtems-tools:

```
covoar: Fix single-byte uncovered ranges
```

```
This fixes a bug where covoar reports uncovered ranges of size 1. When a NOP instruction is encountered at the end of a function, the remaining non-instruction bytes are marked as executed. The loop that marks the remaining bytes as executed was not considering the last address of the function.
```

```
Closes #4448
```

---

**4451 - DesiredSymbols: Implement move assignment operator**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4451">https://devel.rtems.org/ticket/4451</a> ( <a href="https://devel.rtems.org/ticket/4451">https://devel.rtems.org/ticket/4451</a> )
<b>Id</b>	4451
<b>Reporter</b>	Ryan Long
<b>Created</b>	8 June 2021 13:49:28
<b>Modified</b>	16 September 2021 17:30:05
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1505133: Missing move assignment operator for SymbolInformation? class.

```
128 */
CID 1505133 (#1 of 1): Missing move assignment operator (MISSING_MOVE_ASSIGNMENT)missing_move_assignment: Class
Coverage::SymbolInformation may benefit from adding a move assignment operator. See other events which show the copy assignment
operator being applied to rvalues, where a move assignment may be faster.
129 class SymbolInformation {
```

**Comment 1**

1. **Ryan Long**, Thu, 16 Sep 2021 17:30:05 GMT
  2. **status**: changed from **new** to **closed**
  3. **resolution**: set to **wontfix**
- 

**4453 - Global vs Local Attribute Unclear for SMP/Distributed MP**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4453">https://devel.rtems.org/ticket/4453</a> ( <a href="https://devel.rtems.org/ticket/4453">https://devel.rtems.org/ticket/4453</a> )
<b>Id</b>	4453
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	9 June 2021 18:31:46
<b>Modified</b>	7 December 2022 18:22:01
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The description for global vs local attributes on objects do not make it clear whether they apply to SMP or distributed multiprocessing configuration. This applies to at least the `rtems_task_create` description but likely needs to be addressed in the description in every create with global/local and in the SMP section.

**Comment 1**

1. **Sebastian Huber**, Thu, 10 Jun 2021 13:28:04 GMT

In the `rtems_task_create()` description we have:

The task has a local or global scope in a multiprocessing network (this attribute does not refer to SMP systems). The scope is selected by the mutually exclusive `RTEMS_LOCAL` and `RTEMS_GLOBAL` attributes.

Maybe we should add local scope and global scope glossary terms. Maybe we should replace scope with something more specific.

**Comment 2**

1. **Chris Johns**, Tue, 29 Nov 2022 23:43:13 GMT
2. **owner**: set to **Joel Sherrill**
3. **status**: changed from **new** to **assigned**

**Comment 3**

1. **Joel Sherrill**, Wed, 07 Dec 2022 18:22:01 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 32de9ff/rtems-docs:

c-user: Add Local vs Global to Key Concepts Chapter

Add multiple new index entries and cite them where `RTEMS_LOCAL` and `RTEMS_GLOBAL` are cited.

Closes #4453.

---

**4454 - bsp/i386: TSC calibration inaccurate**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4454">https://devel.rtems.org/ticket/4454</a> ( <a href="https://devel.rtems.org/ticket/4454">https://devel.rtems.org/ticket/4454</a> )
<b>Id</b>	4454
<b>Reporter</b>	Jan Sommer
<b>Created</b>	11 June 2021 06:31:44
<b>Modified</b>	6 January 2022 08:35:21
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	i386 clock
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The current implementation of the TSC calibration during startup yields inaccurate results.

There are 2 issues:

## 1. Rounding error:

The `calibrate_tsc` function calibrates for 1s by waiting for `rtems_clock_get_ticks_per_second()` ticks via the PIT.

The PIT has a frequency of 1193182 Hz. For a rtems tick of 1ms this yields 1193. Waiting for 1s means then waiting for 1193000 PIT ticks (instead of the full 1193182).

For a 1 GHz TSC clock this would yield already ~150 kHz less then the correct TSC frequency.

## 2. Waiting for the first loop at begin of timer period

```
for (i = rtems_clock_get_ticks_per_second() * pc386_isr_per_tick;
     i != 0; --i) {
    /* We know we've just completed a tick when timer goes from low to high */
    then_lsb = then_msb = 0xff;
    do {
        READ_8254(now_lsb, now_msb);
        if ((then_msb < now_msb) ||
            ((then_msb == now_msb) && (then_lsb < now_lsb)))
            break;
        then_lsb = now_lsb;
        then_msb = now_msb;
    } while (1);
}
```

This can yield deviations of several MHz for the TSC frequency.

For example, for a tested CPU with a TSC frequency of 19167.1 MHz yields a calibration result of 1912.3 MHz.

## Proposed solution

- Just wait 1193182 PIT ticks for 1 s instead of a number of rtems ticks
- Use the raw timer value instead of waiting for clock ticks.

**Comment 1**

1. **Joel Sherrill**, Fri, 17 Dec 2021 17:21:14 GMT

2. **component**: changed from **admin** to **bsps**

Any progress on this?

**Comment 2**

1. **Jan Sommer**, Thu, 06 Jan 2022 08:35:02 GMT

Seems I created this ticket twice by accident. It is a duplicate of #4455 which was fixed by this commit <https://git.rtems.org/rtems/commit/?id=93f96455957a943f1a4c17655a09612a93a34bf4>.

**Comment 3**

1. **Jan Sommer**, Thu, 06 Jan 2022 08:35:21 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **duplicate**

**4455 - bsp/i386: TSC calibration inaccurate**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4455">https://devel.rtems.org/ticket/4455</a> ( <a href="https://devel.rtems.org/ticket/4455">https://devel.rtems.org/ticket/4455</a> )
<b>Id</b>	4455
<b>Reporter</b>	Jan Sommer
<b>Created</b>	11 June 2021 06:31:54
<b>Modified</b>	21 June 2021 08:11:43
<b>Owner</b>	Jan Sommer
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	i386 clock
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The current implementation of the TSC calibration during startup yields inaccurate results.

There are 2 issues:

## 1. Rounding error:

The `calibrate_tsc` function calibrates for 1s by waiting for `rtems_clock_get_ticks_per_second()` ticks via the PIT.

The PIT has a frequency of 1193182 Hz. For a rtems tick of 1ms this yields 1193. Waiting for 1s means then waiting for 1193000 PIT ticks (instead of the full 1193182).

For a 1 GHz TSC clock this would yield already ~150 kHz less then the correct TSC frequency.

## 2. Waiting for the first loop at begin of timer period

```
for (i = rtems_clock_get_ticks_per_second() * pc386_isr_per_tick;
     i != 0; --i) {
  /* We know we've just completed a tick when timer goes from low to high */
  then_lsb = then_msb = 0xff;
  do {
    READ_8254(now_lsb, now_msb);
    if ((then_msb < now_msb) ||
        ((then_msb == now_msb) && (then_lsb < now_lsb)))
      break;
    then_lsb = now_lsb;
    then_msb = now_msb;
  } while (1);
}
```

This can yield deviations of several MHz for the TSC frequency.

For example, for a tested CPU with a TSC frequency of 19167.1 MHz yields a calibration result of 1912.3 MHz.

## Proposed solution

- Just wait 1193182 PIT ticks for 1 s instead of a number of rtems ticks
- Use the raw timer value instead of waiting for clock ticks.

**Comment 1**

1. **Jan Sommer**, Fri, 11 Jun 2021 06:32:17 GMT
2. **owner:** set to **Jan Sommer**
3. **status:** changed from **new** to **accepted**

**Comment 2**

1. **Jan Sommer**, Mon, 21 Jun 2021 08:11:43 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 93f9645/rtems:

```
bsps/i386: Update calibration of TSC to be more accurate
```

```
Closes #4455
```

**4458 - Simplify trap table initialization**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4458">https://devel.rtems.org/ticket/4458</a> ( <a href="https://devel.rtems.org/ticket/4458">https://devel.rtems.org/ticket/4458</a> )
<b>Id</b>	4458
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	18 June 2021 13:57:12
<b>Modified</b>	15 June 2023 17:43:50
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Currently, the trap table is statically initialized (see start.S). Unexpected traps end up in system error mode. Later during startup most traps are changed to jump to `_ISR_Handler()`. This is a side-effect of `bsp_spurious_initialize()`. The used functions for this dynamic initialization are a bit complex and need cache manager directives which involve all online processors. This should be simplified to cover only basic requirements.

- The `_ISR_Vector_table` should be initialized by `_CPU_Initialize_vectors()` to a new default handler `_SPARC_ISR_handler_default()` which just invokes `_Terminate()`.
- The traps associated with external interrupts (0x11 up to including 0x1f) should be statically initialized in start.S to jump to `_ISR_Handler()`.
- Standard synchronous exceptions such as
  - 0x01 instruction access exception
  - 0x02 illegal instruction
  - 0x03 privileged instruction
  - 0x04 fp disabled
  - 0x07 memory address not aligned
  - 0x08 fp exception
  - 0x09 data access exception
  - 0x0A tag overflow
  - 0x24 cp\_disabled
  - 0x28 cp\_exception

should also be statically initialize to jump to `_ISR_Handler()` to invoke the fatal error handler.

If software needs to change the default initialization, then it can use `set_vector()` or alternatives on demand.

**Comment 1**

1. **Sebastian Huber**, Fri, 18 Jun 2021 15:20:54 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Sebastian Huber**, Fri, 18 Jun 2021 15:22:45 GMT
2. **description:** modified (diff)

**Comment 3**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:27 GMT

In 7a140e2/rtems:

```
bsps/sparc: Add a symbol for each trap table entry
```

This makes it easier to review start.o and set break points to trap table entries. This change was checked by inspecting the trap table in start.o with objdump.

Update #4458.

**Comment 4**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:30 GMT

In 955c045b/rtems:

```
sparc: Move ISR handler install routines
```

Move `_CPU_ISR_install_raw_handler()` and `_CPU_ISR_install_vector()` to separate files. The goal is to make their use optional.

Update #4458. Update #4459.

**Comment 5**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:37 GMT

In 5c30e3d3/rtems:

bsps/sparc: Use `rtems_interrupt_handler_install()`

Avoid using `set_vector()` which depends on `_ISR_Vector_table()`. Prepare for a statically initialized trap table.

Update #4458.

#### **Comment 6**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:40 GMT

In b9d5f516/rtems:

sparc: Move FP frame offset defines to `cpuimpl.h`

This makes them usable in multiple files.

Update #4458.

#### **Comment 7**

1. **Sebastian Huber**, Thu, 24 Jun 2021 10:30:47 GMT

In be96cb43/rtems:

sparc: Simplify trap table initialization

Move `_ISR_Handler()` to a separate file since it is now only used if a handler is installed by `_CPU_ISR_install_raw_handler()`.

Statically initialize the traps for external interrupts to use the new `_SPARC_interrupt_trap()` which directly dispatches the interrupt handlers installed by `rtems_interrupt_handler_install()` via the BSP-provided `_SPARC_interrupt_dispatch()`.

Since the trap table is now fully statically initialized, there is no longer a dependency on the Cache Manager in the default configuration.

Update #4458.

#### **Comment 8**

1. **Sebastian Huber**, Thu, 12 Aug 2021 12:49:04 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

The trap table is now statically initialized.

#### **Comment 9**

1. **Sebastian Huber**, Thu, 15 Jun 2023 17:43:50 GMT

In 97a4b306/rtems:

bsp/leon2: Include missing header file

Update #4458.

---

## **4460 - CID 1437647: Explicit null dereferenced**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4460">https://devel.rtems.org/ticket/4460</a> ( <a href="https://devel.rtems.org/ticket/4460">https://devel.rtems.org/ticket/4460</a> )
<b>Id</b>	4460
<b>Reporter</b>	Harrison Gerber
<b>Created</b>	22 June 2021 19:57:20
<b>Modified</b>	31 October 2022 15:00:24
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

A null pointer dereference will occur.

In `rtems_fdt_unload`: Dereference of an explicit null value (CWE-476)

#### Comment 1

1. **Kinsey Moore**, Mon, 03 Oct 2022 18:13:47 GMT

In 05461aa4/rtems:

```
cpukit/fdt: Free index before container
```

```
Ensure that the index is released before the structure containing it is freed and NULled.
```

```
Updates #4460
```

#### Comment 2

1. **Kinsey Moore**, Mon, 03 Oct 2022 18:14:06 GMT

In 3af84c1/rtems:

```
cpukit/fdt: Free index before container
```

```
Ensure that the index is released before the structure containing it is freed and NULled.
```

```
Updates #4460
```

#### Comment 3

1. **Gedare Bloom**, Mon, 31 Oct 2022 14:54:26 GMT
2. **milestone**: changed from **6.1** to **7.1**

#### Comment 4

1. **Gedare Bloom**, Mon, 31 Oct 2022 15:00:24 GMT
  2. **status**: changed from **assigned** to **closed**
  3. **resolution**: set to **fixed**
  4. **milestone**: changed from **7.1** to **6.1**
- 

### 4461 - glib: Register system console as `"/dev/console"`

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4461">https://devel.rtems.org/ticket/4461</a> ( <a href="https://devel.rtems.org/ticket/4461">https://devel.rtems.org/ticket/4461</a> )
<b>Id</b>	4461
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	24 June 2021 06:25:53
<b>Modified</b>	24 June 2021 06:54:02
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The driver manager console driver did not register the system console as "/dev/console" this resulted in some test failures (for example spconsole01.exe).

**Comment 1**

1. **Sebastian Huber**, Thu, 24 Jun 2021 06:54:02 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 499a89b/rtems:

```
glibc: Register system console as /dev/console
Close #4461.
```

---

**4462 - CID 1437638: Logically dead code**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4462">https://devel.rtems.org/ticket/4462</a> ( <a href="https://devel.rtems.org/ticket/4462">https://devel.rtems.org/ticket/4462</a> )
<b>Id</b>	4462
<b>Reporter</b>	Harrison Gerber
<b>Created</b>	28 June 2021 23:48:06
<b>Modified</b>	31 October 2022 15:02:09
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In rtems-fdt.c:

The indicated dead code may have performed some action; that action will never occur.

In rtems\_fdt\_init\_index: Code can never be reached because of a logical contradiction (CWE-561)

```
159 entries = calloc(num_entries, sizeof(rtems_fdt_index_entry));
    cond_notnull: Condition entries, taking true branch. Now the value of entries is not NULL.
160 if (!entries)
161 {
162     return -RTEMS_FDT_ERR_NO_MEMORY;
163 }
164
165 names = calloc(1, total_name_memory);
    notnull: At condition entries, the value of entries cannot be NULL.
    dead_error_condition: The condition !entries cannot be true.
166 if (!entries)
167 {
CID 1437638 (#1 of 1): Logically dead code (DEADCODE)
dead_error_begin: Execution cannot reach this statement: free(entries);.
168     free(entries);
169     return -RTEMS_FDT_ERR_NO_MEMORY;
170 }
```

---

**Comment 1**



1. **Joel Sherrill**, Tue, 29 Jun 2021 00:31:27 GMT

Shouldn't it be freeing the first variable allocated -- names?

#### Comment 2

1. **Kinsey Moore**, Mon, 03 Oct 2022 18:13:45 GMT

In cab00c70/rtems:

```
cpukit/fdt: Check correct allocation
```

The second allocation check was mistakenly rechecking the first allocation. It now checks the correct allocation and ensures that names is not NULL.

Updates #4462

#### Comment 3

1. **Kinsey Moore**, Mon, 03 Oct 2022 18:14:04 GMT

In 584f5bc9/rtems:

```
cpukit/fdt: Check correct allocation
```

The second allocation check was mistakenly rechecking the first allocation. It now checks the correct allocation and ensures that names is not NULL.

Updates #4462

#### Comment 4

1. **Gedare Bloom**, Mon, 31 Oct 2022 15:02:09 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

### 4463 - rtems\_condition\_variable\_signal() is implemented as a broadcast

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4463">https://devel.rtems.org/ticket/4463</a> ( <a href="https://devel.rtems.org/ticket/4463">https://devel.rtems.org/ticket/4463</a> )
<b>Id</b>	4463
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	1 July 2021 11:20:43
<b>Modified</b>	1 July 2021 11:58:44
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

rtems\_condition\_variable\_signal() should use \_Condition\_Signal().

#### Comment 1

1. **Sebastian Huber**, Thu, 01 Jul 2021 11:58:44 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 737e18d/rtems:

```
rtems: Do not broadcast to signal a condition var
```

Close #4463.

### **4468 - waf build system does not generate the same hsnonts.h**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4468">https://devel.rtems.org/ticket/4468</a> ( <a href="https://devel.rtems.org/ticket/4468">https://devel.rtems.org/ticket/4468</a> )
<b>Id</b>	4468
<b>Reporter</b>	Chris Johns
<b>Created</b>	14 July 2021 04:28:20
<b>Modified</b>	30 August 2021 09:03:04
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	normal
<b>Keywords</b>	wafblocker
<b>Cc</b>	
<b>Blocking</b>	4081
<b>Blocked by</b>	

## Description

Building with autoconf and the command line of:

```
$ ../rtems.git/configure --target=powerpc-rtems6 --enable-rtemsbsp=mvme2307
```

gives:

```
$ grep BSP_CONSOLE_BAUD `find . -name bspopts.h`
#define BSP_CONSOLE_BAUD 9600
```

Building with waf and a config of ...

```
[DEFAULT]
BUILD_TESTS = True
RTEMS_POSIX_API = True
[powerpc/mvme2307]
```

gives:

```
$ grep BSP_CONSOLE_BAUD `find . -name bspopts.h`
#define BSP_CONSOLE_BAUD 115200
```

The default should be 9600 and the motorola\_powerpc BSP is listed in the options under 9600. Something is broken in the waf BSP opts handling.

## Comment 1

1. **Chris Johns**, Wed, 14 Jul 2021 04:44:57 GMT

The options code is not being passed the variant, it is passed the BSP ....

```
def default_value(self, variant):
    value = self.data["default"]
    for default in self.data["default-by-variant"]:
        print('[ ] %s %r' % (variant, default), OptionItem.is_variant(default["variants"], variant))
        if OptionItem.is_variant(default["variants"], variant):
```

gives:

```
] powerpc/mvme2307 {'value': 9600, 'variants': ['m68k/m5484FireEngine', 'powerpc/hsc_cm01', 'powerpc/beatnik', 'powerpc/haleakala', 'powerpc/motorola powerpc', 'powerpc/mvme3100', 'powerpc/mvme5500']} False
```

## Comment 2

1. **Chris Johns**, Wed, 14 Jul 2021 05:01:02 GMT

The optconsolebaud.yml file lists powerpc/motorola\_powerpc as a variant and it is a family. The ability to specify a family for default is something I think is needed. I do not like needing to list all BSPs is something we should require we do?

Are BSPs that INHERIT supported?

I wonder how you take a family given the variant?

## Comment 3

1. **Chris Johns**, Wed, 14 Jul 2021 06:38:28 GMT

Hmmm it seems the options are all required to have a default-by-variant. I am not sure if this is by design and for a reason, a hang over from the path to these spec files or it could be optional?

I will make it optional and I will make default-by-family optional.

## Comment 4

1. **Chris Johns**, Thu, 15 Jul 2021 00:03:15 GMT

2. **owner:** set to **Chris Johns <chrisj@...>**

3. **status:** changed from **new** to **closed**

**4. resolution: set to fixed**

In 6f2aa8ad/rtems:

```
build: Use BSP family for options
Optionally add support for 'default-by-family' to allow
option to be set by a family and so all related BSPs
Close #4468
```

**Comment 5**

1. **Sebastian Huber**, Thu, 15 Jul 2021 06:07:50 GMT

In 6107148/rtems:

```
build: Add missing default-by-family
Update #4468.
```

**Comment 6**

1. **Sebastian Huber**, Thu, 15 Jul 2021 06:07:54 GMT

In b6092cb/rtems:

```
build: Fix bsp_defaults command
Update #4468.
```

**Comment 7**

1. **Sebastian Huber**, Thu, 15 Jul 2021 06:10:06 GMT

In 6c1928c/rtems:

```
build: Prefer variant default value over family
Update #4468.
```

**Comment 8**

1. **Sebastian Huber**, Wed, 18 Aug 2021 09:26:43 GMT

In ebdfa24b/rtems:

```
build: Merge default-by-family into by-variant
Prefix the BSP family name with "bsps/" to make it distinct to the BSP variant names.
Update #4468.
```

**Comment 9**

1. **Sebastian Huber**, Mon, 30 Aug 2021 09:03:04 GMT

In d223ec9/rtems-docs:

```
eng: Document use of BSP family for defaults
Update #4468.
```

---

**4469 - rtems-exeinfo.cpp: Not restoring ostream format errors spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4469">https://devel.rtems.org/ticket/4469</a> ( <a href="https://devel.rtems.org/ticket/4469">https://devel.rtems.org/ticket/4469</a> )
<b>Id</b>	4469
<b>Reporter</b>	Ryan Long
<b>Created</b>	15 July 2021 14:46:52
<b>Modified</b>	13 August 2021 19:55:51
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1503006: Not restoring ostream format in output\_compilation\_unit().

```

185. format_changed: left changes the format state of std::cout for category adjustfield.
478     std::cout << " | "
479     << std::setw (source_max + 1) << std::left
480     << rld::path::basename (s.source);

```

CID 1503007: Not restoring ostream format in output\_tls().

```

11. format_changed: right changes the format state of std::cout for category adjustfield.
12. format_changed: hex changes the format state of std::cout for category basefield.
13. format_changed: setfill changes the format state of std::cout for category fill.
14. format_restored: dec changes the format state of std::cout for category basefield.
15. format_restored: setfill changes the format state of std::cout for category fill.
704     std::cout << "    data size : " << tls_data_size->value () << std::endl
705     << "    bss size : " << tls_bss_size->value () << std::endl
706     << "    alignment : " << tls_alignment->value () << std::endl
707     << std::right << std::hex << std::setfill ('0')
708     << "    data addr : 0x" << std::setw (8) << tls_data_begin->value ()
709     << std::endl
710     << std::dec << std::setfill (' ')
711     << std::endl;

```

### Comment 1

1. **Ryan Long**, Tue, 27 Jul 2021 18:42:06 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In e146927/rtems-tools:

rtems-exeinfo.cpp: Restore ostream format

CID 1503006: Not restoring ostream format CID 1503007: Not restoring ostream format

Used a variable to store the format of the ostream before any changes, and copied what was originally there back into the stream before returning from the function.

Closes #4469

### Comment 2

1. **Ryan Long**, Thu, 29 Jul 2021 14:43:57 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

### Comment 3

1. **Ryan Long**, Fri, 13 Aug 2021 19:55:51 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

## 4470 - CoverageMapBase.cc: Not restoring ostream format error spotted by Coverity

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4470">https://devel.rtems.org/ticket/4470</a> ( <a href="https://devel.rtems.org/ticket/4470">https://devel.rtems.org/ticket/4470</a> )
<b>Id</b>	4470
<b>Reporter</b>	Ryan Long
<b>Created</b>	15 July 2021 14:49:11
<b>Modified</b>	13 August 2021 19:56:40
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

CID 1503022: Not restoring ostream format in dump().

```
1. format_changed: hex changes the format state of out for category basefield.
2. format_changed: setfill changes the format state of out for category fill.
78 out << std::hex << std::setfill('0')
79 << "Address range: low = " << std::setw(8) << lowAddress
80 << " high = " << std::setw(8) << highAddress
81 << std::endl;
```

#### Comment 1

1. **Ryan Long**, Tue, 27 Jul 2021 18:42:08 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In d417918/rtems-tools:

```
CoverageMapBase?.cc: Restore ostream format
```

```
CID 1503022: Not restoring ostream format
```

```
Save format of stream before changing it, and change it back before returning.
```

```
Closes #4470
```

#### Comment 2

1. **Ryan Long**, Thu, 29 Jul 2021 14:43:37 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

#### Comment 3

1. **Ryan Long**, Fri, 13 Aug 2021 19:56:40 GMT
  2. **status:** changed from **reopened** to **closed**
  3. **resolution:** set to **fixed**
- 

### **4471 - ReportsHtml.cc: Not restoring ostream format error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4471">https://devel.rtems.org/ticket/4471</a> ( <a href="https://devel.rtems.org/ticket/4471">https://devel.rtems.org/ticket/4471</a> )
<b>Id</b>	4471
<b>Reporter</b>	Ryan Long
<b>Created</b>	15 July 2021 14:50:47
<b>Modified</b>	13 August 2021 19:57:26
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1505939: Not restoring ostream format in PutSymbolSummaryLine?().

```

5. format_changed: fixed changes the format state of report for category floatfield.
6. format_changed: setprecision changes the format state of report for category precision.
782     report << ""
783         << std::fixed << std::setprecision( 2 )
784         << ( symbolInfo.stats.uncoveredInstructions * 100.0 ) /
785             symbolInfo.stats.sizeInInstructions
786     << "" << std::endl;

```

**Comment 1**

1. **Ryan Long**, Tue, 27 Jul 2021 18:42:11 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f7887ec/rtems-tools:

```

ReportsHtml?.cc: Restore ostream format
CID 1505939: Not restoring ostream format
Save format of stream before changing it, and change it back before returning.
Closes #4471

```

**Comment 2**

1. **Ryan Long**, Thu, 29 Jul 2021 14:43:09 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

**Comment 3**

1. **Ryan Long**, Fri, 13 Aug 2021 19:57:26 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

**4472 - ReportsText.cc: Not restoring ostream format error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4472">https://devel.rtems.org/ticket/4472</a> ( <a href="https://devel.rtems.org/ticket/4472">https://devel.rtems.org/ticket/4472</a> )
<b>Id</b>	4472
<b>Reporter</b>	Ryan Long
<b>Created</b>	15 July 2021 14:52:45
<b>Modified</b>	13 August 2021 19:02:01
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1505940: Not restoring ostream format in PutSymbolSummaryLine?().

```

5. format_changed: fixed changes the format state of report for category floatfield.
6. format_changed: setprecision changes the format state of report for category precision.
231 report << "===== " << std::endl
232 << "Symbol : "
233 << symbolName << std::endl
234 << "Total Size in Bytes : "
235 << symbolInfo.stats.sizeInBytes << std::endl
236 << "Total Size in Instructions : "
237 << symbolInfo.stats.sizeInInstructions << std::endl
238 << "Total number Branches : "
239 << symbolInfo.stats.branchesNotExecuted +
240 symbolInfo.stats.branchesExecuted
241 << std::endl
242 << "Total Always Taken : "
243 << symbolInfo.stats.branchesAlwaysTaken << std::endl
244 << "Total Never Taken : "
245 << symbolInfo.stats.branchesNeverTaken << std::endl
246 << std::fixed << std::setprecision( 2 )
247 << "Percentage Uncovered Instructions : "
248 << uncoveredInstructions << std::endl
249 << "Percentage Uncovered Bytes : "
250 << uncoveredBytes << std::endl;

```

**Comment 1**

1. **Ryan Long**, Tue, 27 Jul 2021 18:42:13 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In df484a5/rtems-tools:

```
ReportsText?.cc: Restore ostream format
```

```
CID 1505940: Not restoring ostream format
```

```
Save format of stream before changing it, and change it back before returning.
```

```
Closes #4472
```

**Comment 2**

1. **Ryan Long**, Thu, 29 Jul 2021 14:42:40 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

**Comment 3**

1. **Ryan Long**, Fri, 13 Aug 2021 19:02:01 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 632414d/rtems-tools:

```
ReportsText?.cc: Add ostream_guard
```

```
CID 1505940: Not restoring ostream format
```

```
Closes #4472
```

**4473 - AddressToLineMapper.h: Pointer to local outside scope error spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4473">https://devel.rtems.org/ticket/4473</a> ( <a href="https://devel.rtems.org/ticket/4473">https://devel.rtems.org/ticket/4473</a> )
<b>Id</b>	4473
<b>Reporter</b>	Alex White
<b>Created</b>	16 July 2021 17:58:03
<b>Modified</b>	20 July 2021 18:27:12
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1505281: Pointer to local outside scope

```

SourceLine()
28 : address(0),
CID 1505281 (#1 of 1): Pointer to local outside scope (RETURN_LOCAL)
1. escape_local addr: Returning, through this->path_, the address of stack variable .
29   path_("unknown"),
30   line_num(-1),
31   is_end_sequence(true)
32 {
33   2. return: Returning here.
33 }
```

**Comment 1**

1. **Alex White**, Fri, 16 Jul 2021 17:58:23 GMT
2. **owner:** set to **Alex White**
3. **status:** changed from **new** to **accepted**

**Comment 2**

1. **Alex White**, Tue, 20 Jul 2021 18:27:12 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 2380886/rtems-tools:

```
AddressToLineMapper?.h: Remove pointer to temporary string
```

```
CID 1505281: Pointer to local outside scope
```

```
Closes #4473
```

---

**4475 - Add NFSv4 client support to libbsd**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4475">https://devel.rtems.org/ticket/4475</a> ( <a href="https://devel.rtems.org/ticket/4475">https://devel.rtems.org/ticket/4475</a> )
<b>Id</b>	4475
<b>Reporter</b>	Chris Johns
<b>Created</b>	19 July 2021 08:57:15
<b>Modified</b>	8 June 2022 13:11:44
<b>Owner</b>	Chris Johns
<b>Type</b>	task
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	nfs-v4
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add NFSv4 client support to libbsd. The client support is part of kernel and provides support for a range of the NFS protocol version including version 4.

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



The task is made of the following:

- Update the locks and locking to support the lock manager. VFS requires this be supported
- Add support for the FreeBSD Virtual File System (VFS)
- Add the kernel RPC implementation
- Add NFS client support

VFS is built around the FB's file structure and file descriptor structure. These need to be supported. The file struct and file descriptor form the basis for all fd based interactions with the FB kernel code such as files, devices and sockets.

LibIO and FB fd

The FB fd and file support clashes with the existing libio implementations used for things like socket, kqueue and select. The work to port the VFS requires:

- socket, kqueue, select support FB fd support. This is closer to the kernel. No direct libio access
- Provide an interface to libio mapping the iop descriptors to FB descriptors.

This approach nests the FB file descriptors inside the libio support. This is not optimal in terms of some activities but the hot paths in the code should not see a significant change in performance. Some paths like open are not optimal because the RTEMS file system op handlers imply a specific implementation that does not match up well with the FB namei interface. The long term approach is to look at libio and the handlers and consider allowing closer integration of FB's fd support.

BIO and Paging

The bio layer is required for VFS. No paging support other than the calls needed to have VFS link are provided. No VM paging is need and none of that code need be ported.

System Calls

Collect all the syscall functionality exported to RTEMS into a single place. Currently the calls are spread around the code and this:

- Does not centralize the code
- Add a lot of code to FB being ported

FreeBSD's initialization creates the initial process called proc0. Add support to create proc0 and let all thread' reference it. This allow the creds to be managed, kernel trace to work and it removes a number of changes that do not need to be made.

File Descriptor Reuse

The libio functionality of cycling across the fd range rather than reusing lower fd numbers is not compatible with the select call. Not reusing fd numbers once closed until the range as been used provides some protection against bugs where a user does not cleanly handle the fd they own however this is not compatible with FB and makes supporting select harder.

The select interface should not be used on RTEMS and users should be encourages to use threads for concurrent IO or kqueue. The means select may exist for legacy code porting reasons however the cycling fd count reduces how well the code ported will actually work. For example port a piece of select code, open a socket and use, it may work. Then open and close a file 64 times then run the same code. It will fail.

FB fd's are reused.

RPC

The legacy NFSv2 client the the NFSv4 cannot be built at the same time.

The kernel RPC and the user land RPC cannot exist in the same build. I have not looked extensively into this but I was seeing clashes with headers for the same types but different contents. The legacy NFSv2 client uses the user land RPC code while the kernel NFSv4 uses the kernel's RPC.

Module support is already in libbsd to handle the separate building of each piece.

Security

NFSv4 provides a number of extra security features. The code will be ported is possible but little or no security tested is planned at this point in time.

Testing

The NFSv4 stack will be tested against Linux and FreeBSD servers.

### Comment 1

1. **Chris Johns**, Tue, 20 Jul 2021 07:36:52 GMT
2. **description:** modified (diff)

### Comment 2

1. **Joel Sherrill**, Tue, 20 Jul 2021 14:51:34 GMT
2. **summary:** changed from **Add NFSv4 client support to libbds** to **Add NFSv4 client support to libbsd**

### Comment 3

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:16 GMT

In 59f652fe/rtems-libbsd:

```
Implement portable kernel symbol namespace tool
The script's use of sort proved to not be portable No need to check the commits as symbols are only added
Regenerated kernel header to reset the sort order
Update #4475
```

### Comment 4

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:19 GMT

In f700edc/rtems-libbsd:

waf: Fix clashing symbols in the user land symbols  
Update #4475

#### **Comment 5**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:21 GMT

In 5ef23a2/rtems-libbsd:

sys/netinet/libalias: Fix symbols clashes  
Update #4475

#### **Comment 6**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:24 GMT

In 974742d/rtems-libbsd:

kern-symbols: Add symbols from the everything build set  
Update #4475

#### **Comment 7**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:27 GMT

In 684cf3c/rtems-libbsd:

rtemsbsd: Add FrreBSD's clang-format style  
Update #4475

#### **Comment 8**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:29 GMT

In 2a01430/rtems-libbsd:

rtemsbsd: Catch timeout overflows  
Update #4475

#### **Comment 9**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:32 GMT

In e1ca99b/rtems-libbsd:

testsuite: Optionally allow all command in a shell  
Update #4475

#### **Comment 10**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:35 GMT

In 46a15fa/rtems-libbsd:

sys/kern: Add lockmgr support  
See man lockmgr Implement the lock\_object and move the RTEMS mutex to that object Add debug support to track the locks with gdb  
Update #4475

#### **Comment 11**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:38 GMT

In 761fd693/rtems-libbsd:

kern: Import kern\_prot.c fnd kern\_resource.c for proc0

Update #4475

#### **Comment 12**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:40 GMT

In c7427fc/rtems-libbsd:

```
kern: Add a proc0
Provides the thread's proc pointer and with that access to creds
Update #4475
```

#### **Comment 13**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:43 GMT

In 9800a0f/rtems-libbsd:

```
kern: Import kern_ktr.c
Update #4475
```

#### **Comment 14**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:46 GMT

In e56b5cb/rtems-libbsd:

```
kern: Add kernel trace support (KTR)
Update #4475
```

#### **Comment 15**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:48 GMT

In 1739d74/rtems-libbsd:

```
freebsd/sys: Import VFS support
Update #4475
```

#### **Comment 16**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:51 GMT

In ac4db4c/rtems-libbsd:

```
rtemsbsd: Remove DHCP init wrapper
Object files cannot config init and resided in libbsd.a
Update #4475
```

#### **Comment 17**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:53 GMT

In 6514d56/rtems-libbsd:

```
sys/kern: Add VFS support
Refactor the libio interface Move syscalls into an rtemsbsd location Provide a root directory mount point
Update #4475
```

#### **Comment 18**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:56 GMT

In 3da45ae/rtems-libbsd:

```
freebsd/sys: Import RPC and XDR support
Update #4475
```

**Comment 19**

1. **Chris Johns**, Thu, 02 Sep 2021 02:43:59 GMT

In c6dbc96/rtems-libbsd:

```
kern/sys: Add the kernel RPC and XDR support
Updates #4475
```

**Comment 20**

1. **Chris Johns**, Thu, 02 Sep 2021 02:44:01 GMT

In 6138f24/rtems-libbsd:

```
kern/sys: Import NFS and NFS file system client
Update #4475
```

**Comment 21**

1. **Chris Johns**, Thu, 02 Sep 2021 02:44:04 GMT

In 882425f/rtems-libbsd:

```
kern/sys: Add NFSv4 client
Update #4475
```

**Comment 22**

1. **Chris Johns**, Thu, 02 Sep 2021 02:44:07 GMT

In 7e282d2/rtems-libbsd:

```
rtemsbsd/nfs: Add support to mount NFSv2
NFSv2 requires userland RPC calls to determine the version of
NFS and the FH. This is passed to the kernel. Port more libc/rpc.
Update #4475
```

**Comment 23**

1. **Chris Johns**, Fri, 24 Sep 2021 00:00:06 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

**Comment 24**

1. **Sebastian Huber**, Wed, 08 Jun 2022 13:11:44 GMT

In dba9346/rtems-libbsd:

```
uma_core.c: Fix use of uninitialized variable
Update #4475.
```

---

**4482 - Document kernel character I/O support in Classic API Guide**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4482">https://devel.rtems.org/ticket/4482</a> ( <a href="https://devel.rtems.org/ticket/4482">https://devel.rtems.org/ticket/4482</a> )
<b>Id</b>	4482
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	30 July 2021 06:44:20
<b>Modified</b>	3 August 2021 08:40:04
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Directives like `printk()` are available for a long time. Document them in the Classic API Guide.

**Comment 1**

1. **Sebastian Huber**, Mon, 02 Aug 2021 05:15:51 GMT

In d999f865/rtems:

```
rtems: Generate
Change license to BSD-2-Clause according to file histories and documentation re-licensing agreement.
Place the group into the I/O Manager group. Add all source files to the group.
Update #3899. Update #3993. Update #4482.
```

**Comment 2**

1. **Sebastian Huber**, Tue, 03 Aug 2021 08:40:04 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In efb8e7c/rtems-docs:

```
c-user: Add "Kernel Character I/O Support" chapter
Close #4482.
```

**4483 - GcovData.cc: Not restoring ostream format error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4483">https://devel.rtems.org/ticket/4483</a> ( <a href="https://devel.rtems.org/ticket/4483">https://devel.rtems.org/ticket/4483</a> )
<b>Id</b>	4483
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 August 2021 18:08:56
<b>Modified</b>	13 August 2021 19:01:57
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1506202: Not restoring ostream format

```
3. format changed: hex changes the format state of std::cerr for category basefield.
407     std::cerr << "File is not a valid *.gcno output (magic: 0x"
408     << std::hex << std::setw( 4 ) << preamble->magic
409     << ")" << std::endl;
CID 1506202 (#1 of 1): Not restoring ostream format (STREAM_FORMAT_STATE)4. end_of_path: Changing format state of stream
std::cerr for category basefield without later restoring it.
```

**Comment 1**

1. **Ryan Long**, Fri, 13 Aug 2021 19:01:57 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 415a2b6/rtems-tools:

```
GcovData?.cc: Add ostream_guard
```

```
CID 1506202: Not restoring ostream format
```

```
Closes #4483
```

**4484 - GcovFunctionData.cc: Not restoring ostream format error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4484">https://devel.rtems.org/ticket/4484</a> ( <a href="https://devel.rtems.org/ticket/4484">https://devel.rtems.org/ticket/4484</a> )
<b>Id</b>	4484
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 August 2021 18:14:25
<b>Modified</b>	13 August 2021 19:01:59
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1506205: Not restoring ostream format

```
1. format changed: hex changes the format state of textFile for category basefield.
360   texTFile << " > BLOCK " << std::setw( 3 ) << block->id
361       << " from " << block->sourceFileName << std::endl
362       << "   -counter: " << std::setw( 5 ) << block->counter << std::endl
363       << "   -flags: 0x" << std::hex << block->flags << std::endl
364       << "   -lines: ";
```

**Comment 1**

1. **Ryan Long**, Fri, 13 Aug 2021 19:01:59 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In dc5e1fc/rtems-tools:

```
GcovFunctionData?.cc: Add ostream_guard
```

```
CID 1506205: Not restoring ostream format
```

```
Closes #4484
```

**4485 - GcovData.cc: Out-of-bounds acces errors spotted by Coverity**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4485">https://devel.rtems.org/ticket/4485</a> ( <a href="https://devel.rtems.org/ticket/4485">https://devel.rtems.org/ticket/4485</a> )
<b>Id</b>	4485
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 August 2021 18:22:36
<b>Modified</b>	20 August 2021 17:47:01
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1506208: Out-of-bounds access

```

CID 1506208 (#1 of 1): Out-of-bounds access (OVERRUN)2. overrun-buffer-arg: Overrunning struct type _ZN4Gcovl3gcov_preambleE of 12
bytes by passing it to a function which accesses it at byte offset 47 using argument 48L.
132  gcdaFile.write( (char *) &preamble , 4 * sizeof( preamble ) );
133  if ( gcdaFile.fail() ) {
134      std::cerr << "Error while writing gcda preamble to a file "
135              << gcdaFileName << std::endl;
136  }

```

CID 1506209: Out-of-bounds access

```

CID 1506209 (#1 of 1): Out-of-bounds access (OVERRUN)1. overrun-buffer-arg: Overrunning buffer pointed to by (char *)&preamble of 8
bytes by passing it to a function which accesses it at byte offset 47 using argument 48L.
400  gcovFile.read( (char *) &preamble , 4 * sizeof( gcov_preamble ) );
401  if ( gcovFile.gcount() != 4 * sizeof( gcov_preamble ) ) {
402      std::cerr << "Error while reading file preamble" << std::endl;
403      return -1;
404  }

```

**Comment 1**

1. **Ryan Long**, Fri, 20 Aug 2021 17:47:01 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 0ab060f/rtems-tools:

GcovData?.cc: Fix out-of-bounds access errors

Adjusted number of bytes to be read, removed length variable

CID 1506208: Out-of-bounds access CID 1506209: Out-of-bounds access

Closes #4485

**4486 - TraceWriterQEMU.cc: String not null terminated issue spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4486">https://devel.rtems.org/ticket/4486</a> ( <a href="https://devel.rtems.org/ticket/4486">https://devel.rtems.org/ticket/4486</a> )
<b>Id</b>	4486
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 August 2021 18:31:34
<b>Modified</b>	20 August 2021 17:47:03
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1506203: String not null terminated

```

CID 1506203 (#1 of 1): String not null terminated (STRING_NULL)6. string_null: Passing unterminated string header.magic to operator
<<, which expects a null-terminated string. [Note: The source code implementation of the function has been overridden by a builtin
model.]
124     std::cerr << "magic = " << header.magic << std::endl
125     << "version = " << header.version << std::endl
126     << "kind = " << header.kind << std::endl
127     << "sizeof target_pc = " << header.sizeof target_pc << std::endl
128     << "big_endian = " << header.big_endian << std::endl
129     << std::hex << std::setfill('0')
130     << "machine = " << std::setw(2) << header.machine[0]
131     << ':' << header.machine[1]
132     << std::dec << std::setfill(' ')
133     << std::endl;

```

**Comment 1**

1. **Ryan Long**, Fri, 20 Aug 2021 17:47:03 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f316d16/rtems-tools:

```
TraceWriterQEMU.cc: Remove unterminated string
```

```
Replaced header.magic with QEMU_TRACE_MAGIC to get rid of "String not null terminated" Coverity issue.
```

```
CID 1506203: String not null terminated
```

```
Closes #4486
```

**4487 - GcovData.cc: Uninitialized scalar field spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4487">https://devel.rtems.org/ticket/4487</a> ( <a href="https://devel.rtems.org/ticket/4487">https://devel.rtems.org/ticket/4487</a> )
<b>Id</b>	4487
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 August 2021 18:39:53
<b>Modified</b>	1 September 2021 15:31:05
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1506206: Uninitialized scalar field

```

22 GcovData::GcovData( Coverage::DesiredSymbols& symbolsToAnalyze ):
23     numberOfFunctions( 0 ),
24     symbolsToAnalyze_m( symbolsToAnalyze )
25 {
26     2. uninitialized_member: Non-static class member gcnoPreamble.magic is not initialized in this constructor nor in any functions that it
calls.
27     4. uninitialized_member: Non-static class member gcnoPreamble.version is not initialized in this constructor nor in any functions that
it calls.
28     CID 1506206 (#1 of 1): Uninitialized scalar field (UNINIT_CTOR)6. uninitialized_member: Non-static class member gcnoPreamble.timestamp
is not initialized in this constructor nor in any functions that it calls.
29 }

```

**Comment 1**

1. **Ryan Long**, Wed, 01 Sep 2021 15:31:05 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 7ccbcd89/rtems-tools:

```
GcovData?.cc: Initialize gcnoPreamble
```

```
CID 1506206: Uninitialized scalar field
```

```
Closes #4487
```



**4488 - TraceWriterQEMU.cc: Uninitialized scalar variable issue spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4488">https://devel.rtems.org/ticket/4488</a> ( <a href="https://devel.rtems.org/ticket/4488">https://devel.rtems.org/ticket/4488</a> )
<b>Id</b>	4488
<b>Reporter</b>	Ryan Long
<b>Created</b>	4 August 2021 18:55:42
<b>Modified</b>	27 September 2021 22:18:24
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1506204: Uninitialized scalar variable

```

115   header.machine[1] = 0; // XXX ??
      CID 1506204 (#1 of 1): Uninitialized scalar variable (UNINIT)4.  uninit_use_in_call: Using uninitialized value header.  Field
header._pad is uninitialized when calling fwrite.
116   status = ::fwrite( &header, sizeof(trace_header), 1, traceFile );

```

**Comment 1**

1. **Ryan Long**, Mon, 27 Sep 2021 22:18:24 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 70088f6/rtems-tools:

```

TraceWriterQEMU.cc: Initialize header._pad
CID 1506204: Uninitialized scalar variable
Closes #4488

```

**4489 - waf configure's --rtems-config and build create an error**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4489">https://devel.rtems.org/ticket/4489</a> ( <a href="https://devel.rtems.org/ticket/4489">https://devel.rtems.org/ticket/4489</a> )
<b>Id</b>	4489
<b>Reporter</b>	Chris Johns
<b>Created</b>	5 August 2021 07:30:27
<b>Modified</b>	29 November 2022 23:47:23
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Waf allows distclean, configure, build and install on a single command line however adding --rtems-config to the configure stage generates this error:

```
The --rtems-config command line option is not allowed in the build command
```

This is error is incorrect.

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 23:47:23 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **wontfix**

I am closing this as it will not be fixed for now. It is not right in the normal context of waf command lines but it is a corner case to fix.

Please reopen if this is important.

## 4490 - rtems\_partition\_return\_buffer() wrongly accepts buffers which are exactly at the buffer area end

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4490">https://devel.rtems.org/ticket/4490</a> ( <a href="https://devel.rtems.org/ticket/4490">https://devel.rtems.org/ticket/4490</a> )
<b>Id</b>	4490
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 August 2021 10:41:25
<b>Modified</b>	12 August 2021 12:26:28
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The range checking in `rtems_partition_return_buffer()` is wrong.

### Comment 1

1. **Sebastian Huber**, Thu, 12 Aug 2021 12:25:43 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 9399e12c/rtems:

```
rtems: Fix rtems_partition_return_buffer()
```

```
The rtems_partition_return_buffer() wrongly accepted which were exactly at the buffer area end. Use the buffer area limit address for the range checking.
```

```
Close #4490.
```

### Comment 2

1. **Sebastian Huber**, Thu, 12 Aug 2021 12:26:28 GMT
2. **keywords**: **qualification** added

## 4491 - TraceWriterQEMU.cc: Buffer not null terminated issue spotted by Coverity

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4491">https://devel.rtems.org/ticket/4491</a> ( <a href="https://devel.rtems.org/ticket/4491">https://devel.rtems.org/ticket/4491</a> )
<b>Id</b>	4491
<b>Reporter</b>	Ryan Long
<b>Created</b>	10 August 2021 14:57:35
<b>Modified</b>	27 September 2021 22:18:21
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

CID 1506207: Buffer not null terminated

```
CID 1506207 (#1 of 1): Buffer not null terminated (BUFFER_SIZE)3. buffer_size: Calling strncpy with a source string whose length (12 chars) is greater than or equal to the size argument (12) will fail to null-terminate header.magic.
109 strncpy( header.magic, QEMU TRACE MAGIC, sizeof(header.magic) );
```

**Comment 1**

1. **Ryan Long**, Mon, 27 Sep 2021 22:18:21 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In a06f48a/rtems-tools:

TraceWriterQEMU.cc: Change strncpy to memcpy

CID 1506207: Buffer not null terminated

Closes #4491

**4492 - ObjdumpProcessor.cc: Uninitialized pointer field**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4492">https://devel.rtems.org/ticket/4492</a> ( <a href="https://devel.rtems.org/ticket/4492">https://devel.rtems.org/ticket/4492</a> )
<b>Id</b>	4492
<b>Reporter</b>	Ryan Long
<b>Created</b>	11 August 2021 18:37:57
<b>Modified</b>	30 September 2021 13:10:54
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1506210: Uninitialized pointer field

```

125 ObjdumpProcessor::ObjdumpProcessor(
126     DesiredSymbols& symbolsToAnalyze,
127     std::shared_ptr& targetInfo
128 ): symbolsToAnalyze_m( symbolsToAnalyze ),
129     targetInfo_m( targetInfo )
130 {
131     CID 1506210 (#1 of 1): Uninitialized pointer field (UNINIT_CTOR)2. uninitialized_member: Non-static class member inputBuffer_m is not
132     initialized in this constructor nor in any functions that it calls.
133 }

```

**Comment 1**

1. **Ryan Long**, Thu, 30 Sep 2021 13:10:54 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

**4499 - rtems-exeinfo.cpp: Uninitialized scalar field error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4499">https://devel.rtems.org/ticket/4499</a> ( <a href="https://devel.rtems.org/ticket/4499">https://devel.rtems.org/ticket/4499</a> )
<b>Id</b>	4499
<b>Reporter</b>	Ryan Long
<b>Created</b>	18 August 2021 13:40:17
<b>Modified</b>	1 September 2021 15:31:02
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

## CID 1471637: Uninitialized scalar field

```

211     section::section (const section& orig)
212         : sec (orig.sec),
213         data (orig.data)
214     {
CID 1471637 (#1 of 1): Uninitialized scalar field (UNINIT_CTOR)2.  uninit_member: Non-static class member byteorder is not
initialized in this constructor nor in any functions that it calls.
215     }

```

**Comment 1**

1. **Ryan Long**, Wed, 01 Sep 2021 15:31:02 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 1d4edfb/rtems-tools:

```

rtems-exeinfo.cpp: Initialize byteorder
CID 1471637: Uninitialized scalar field
Closes #4499

```

**4500 - rld-dwarf.cpp: Uninitialized scalar field**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4500">https://devel.rtems.org/ticket/4500</a> ( <a href="https://devel.rtems.org/ticket/4500">https://devel.rtems.org/ticket/4500</a> )
<b>Id</b>	4500
<b>Reporter</b>	Ryan Long
<b>Created</b>	18 August 2021 15:12:11
<b>Modified</b>	1 September 2021 15:31:07
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

## CID 1503019: Uninitialized scalar field

```

677     function::function (file& debug, debug_info_entry& die)
678         : debug (debug),
679         machine_code_ (false),
680         external_ (false),
681         declaration_ (false),
682         inline_ (DW_INL_not_inlined),
683         entry_pc_ (0),
684         has_entry_pc_ (false),
685         pc_low_ (0),
686         pc_high_ (0),
687         ranges_ (debug),
688         call_line_ (0)
CID 1503019 (#1 of 1): Uninitialized scalar field (UNINIT_CTOR)14.  uninit_member: Non-static class member prototyped_ is not
initialized in this constructor nor in any functions that it calls.

```

**Comment 1**

1. **Ryan Long**, Wed, 18 Aug 2021 15:14:11 GMT

CID 1503021: Uninitialized scalar field

```

817     function::function (const function& orig)
818     : debug (orig.debug),
819       machine_code_ (orig.machine_code_),
820       external_ (orig.external_),
821       declaration_ (orig.declafation_),
822       inline_ (orig.inline_),
823       entry_pc_ (orig.entry_pc_),
824       has_entry_pc_ (orig.has_entry_pc_),
825       pc_low_ (orig.pc_low_),
826       pc_high_ (orig.pc_high_),
827       ranges_ (orig.ranges_),
828       name_ (orig.name_),
829       linkage_name_ (orig.linkage_name_),
830       call_file_ (orig.call_file_),
831       call_line_ (orig.call_line_)
832   {
833       2. unittest member: Non-static class member prototyped is not initialized in this constructor nor in any functions that it calls.
      CID 1503021 (#1 of 1): Uninitialized scalar field (UNINIT_CTOR)4. unittest member: Non-static class member decl_line_ is not
      initialized in this constructor nor in any functions that it calls.
833   }

```

**Comment 2**

1. **Ryan Long**, Wed, 01 Sep 2021 15:31:07 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 2cf693a/rtems-tools:

```

rld-dwarf.cpp: Initialize member variables
Initialize member variables not listed.
CID 1503019: Uninitialized scalar field.
Closes #4500

```

**4501 - TraceConverter.cc: Uncaught exception issue spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4501">https://devel.rtems.org/ticket/4501</a> ( <a href="https://devel.rtems.org/ticket/4501">https://devel.rtems.org/ticket/4501</a> )
<b>Id</b>	4501
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 August 2021 19:21:36
<b>Modified</b>	15 December 2021 16:35:20
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1471639: Uncaught exception

```

CID 1471639 (#1-9 of 9): Uncaught exception (UNCAUGHT_EXCEPT)root_function: In function main(int, char **) an exception of type
rld::error is thrown and never caught.
.
.
.
fun_call_w exception: Called function throws an exception of type rld::error. [show details]
144     executableInfo = new Coverage::ExecutableInfo(
145         executable,
146         "",
147         false,
148         symbolsToAnalyze
149     );

```

**Comment 1**

1. **Ryan Long**, Fri, 08 Oct 2021 13:58:46 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 234c19e/rtems-tools:

TraceConverter?.cc: Add catch for exception

CID 1471639: Uncaught exception

Closes #4501

#### Comment 2

1. **Ryan Long**, Fri, 08 Oct 2021 19:17:21 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

#### Comment 3

1. **Ryan Long**, Wed, 13 Oct 2021 17:05:08 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 958aa5b/rtems-tools:

TraceConverter?.cc: Add catch for exception

CID 1471639: Add catch for exception

Closes #4501

#### Comment 4

1. **Ryan Long**, Mon, 18 Oct 2021 15:32:48 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

#### Comment 5

1. **Ryan Long**, Thu, 04 Nov 2021 15:43:20 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In d1df4f6/rtems-tools:

TraceConverter?.cc: Add catch for exception

CID 1471639: Add catch for exception

Closes #4501

#### Comment 6

1. **Ryan Long**, Mon, 15 Nov 2021 20:13:41 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

#### Comment 7

1. **Ryan Long**, Tue, 30 Nov 2021 16:00:21 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 59ca889/rtems-tools:

TraceConverter?.cc: Add final catch for exceptions

CID 1471639: Add catch for exception

Closes #4501

#### Comment 8

1. **Ryan Long**, Mon, 13 Dec 2021 13:34:03 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

**Comment 9**

1. **Ryan Long**, Wed, 15 Dec 2021 16:35:20 GMT
2. **status**: changed from **reopened** to **closed**
3. **resolution**: set to **fixed**

In c9aefbb/rtems-tools:

```
TraceConverter?.cc: Fix Uncaught exception issue
CID 1471639: Uncaught exception
Closes #4501
```

**4502 - rld-rap.cpp: Uncaught exception issue spotted by Coverity**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4502">https://devel.rtems.org/ticket/4502</a> ( <a href="https://devel.rtems.org/ticket/4502">https://devel.rtems.org/ticket/4502</a> )
<b>Id</b>	4502
<b>Reporter</b>	Ryan Long
<b>Created</b>	19 August 2021 19:26:56
<b>Modified</b>	8 October 2021 13:58:49
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

CID 1471643: Uncaught exception

```
CID 1471643 (#1 of 1): Uncaught exception (UNCAUGHT_EXCEPT)exn_spec_violation: An exception of type rld::error is thrown but the
throw list noexcept doesn't allow it to be thrown. This will cause a call to unexpected() which usually calls terminate().
724   section_merge::~~section_merge ()
725   {
726     if (rld::verbose () >= RLD_VERBOSE_FULL_DEBUG)
727       fun_call w exception: Called function throws an exception of type rld::error. [show details]
728         std::cout << "rap:section-merge: " << sec.name
729           << " size=" << sec.size ()
730           << " offset=" << sec.offset
731           << " " << obj.obj.name ().full () << std::endl;
731   }
```

**Comment 1**

1. **Ryan Long**, Fri, 08 Oct 2021 13:58:49 GMT
2. **owner**: set to **Ryan Long** <ryan.long@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 5519a63/rtems-tools:

```
rld-rapp.cpp: Add catch for exception
CID 1471643: Uncaught exception
Closes #4502
```

**4506 - posix\_devctl() should return the errno directly not -1 and set errno**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4506">https://devel.rtems.org/ticket/4506</a> ( <a href="https://devel.rtems.org/ticket/4506">https://devel.rtems.org/ticket/4506</a> )
<b>Id</b>	4506
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	20 August 2021 19:24:23
<b>Modified</b>	20 September 2021 18:37:56
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The RTEMS implementation of `posix_devctl()` from POSIX 1003.26 does not return error codes as required by the standard.

"Upon successful completion, `posix_devctl()` shall return zero; otherwise an error number shall be returned to indicate the error. The value returned via the `dev_info_ptr` argument is driver dependent."

It should return the `errno` value and not -1 and set the `errno` variable. The current behavior is wrong but understandable because the implementation is a wrapper for `close()` and `ioctl()` which do set `errno` and return -1.

**Comment 1**

1. **Joel Sherrill**, Sat, 21 Aug 2021 19:25:36 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Ryan Long**, Mon, 20 Sep 2021 18:37:56 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 3951d4d/rtems:

```
pxcdevctl: Adjust for standard
```

```
pxsdevctl is supposed to return the value in errno. Before, it was returning -1 and setting errno. Changed the tests to reflect these changes. Added code from RRADE's posix_devctl.c.
```

```
Closes #4506
```

**4507 - mount call retruns error number and it should return -1**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4507">https://devel.rtems.org/ticket/4507</a> ( <a href="https://devel.rtems.org/ticket/4507">https://devel.rtems.org/ticket/4507</a> )
<b>Id</b>	4507
<b>Reporter</b>	Chris Johns
<b>Created</b>	28 August 2021 08:04:31
<b>Modified</b>	23 September 2021 23:57:21
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	mount libcsupport
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The mount call should return -1 for an any error with the `errno` set. Some paths in the mount do this and others so not.

The implementation needs to be changed to only return -1 when there is an error.



**Comment 1**

1. **Joel Sherrill**, Sat, 28 Aug 2021 22:31:05 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Chris Johns**, Thu, 23 Sep 2021 23:57:21 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **wontfix**
4. **description:** modified (diff)

The current behavior is correct. The NFS mounter is not correct.

**4508 - rtems\_message\_queue\_receive(): flush() does not release waiting tasks**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4508">https://devel.rtems.org/ticket/4508</a> ( <a href="https://devel.rtems.org/ticket/4508">https://devel.rtems.org/ticket/4508</a> )
<b>Id</b>	4508
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	30 August 2021 14:21:12
<b>Modified</b>	16 September 2021 07:37:35
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	trivial
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The `RTEMS Classic API Guide` <https://docs.rtems.org/branches/master/c-user/index.html> in `__Message Manager__` → `__Directives__` → section 14.4.8 `rtems_message_queue_receive()` says:

RTEMS\_UNSATISFIED:

The queue was flushed while the calling task was waiting to receive a message.

Yet, when I tested it, this does not happen. A waiting task is not released from the message queue when calling `rtems_message_queue_flush()`. Moreover, I did not find any sign in the source code of `rtems_message_queue_flush()` which look liked it would dequeue waiting threads. (In contrast `rtems_message_queue_delete()` does!) Furthermore, there is no other hint in the documentation of either function that `flush()` would kick out waiting receivers.

I may misinterpret the documentation above or oversee something in the code. Yet, I believe the text I cited above is a mistake in the documentation and should simply be removed.

How to reproduce/How I tested:

```
# I created a message queue and a second task with a higher priority than the first one.
# I made the second task wait on the message empty queue by calling rtems_message_queue_receive().
# Mean while the first task called rtems_message_queue_flush() on the empty queue.
# Result: The second task does still wait on the queue after rtems_message_queue_flush() returned. It does __not__ return with RTEMS_UNSATISFIED.
```

The debug output of my test looks like (the worker task is not released by `rtems_message_queue_flush()` but afterwards by a timeout of 3 ticks):

```
P:574:0:UI1/Valid/Valid/Valid/Flushed/Local/Fifo/Timeout/Empty/Nop:tc-message-receive.c:1316
L:#### rtems_message_queue_construct() with
L:####   .maximum_pending_messages = 3
L:####   .maximum_message_size = 5
L:####   .storage_size = 72
L:####   .storage_free = 0
L:####   .attributes = 0 (LOCAL=0, FIFO=0, PRIORITY=4)
L:#### rtems_task_restart BEFORE
L:#### rtems_message_queue_receive(option_set=0, timeout_param=3) BEGIN
L:#### rtems_task_restart AFTER
L:#### rtems_message_queue_flush() BEFORE
L:#### rtems_message_queue_flush() AFTER
L:#### WaitForWorker wait ticks BEFORE
L:#### rtems_message_queue_receive() END status = 6 (0=RTEMS_SUCCESSFUL, 13=RTEMS_UNSATISFIED, 6=RTEMS_TIMEOUT)
L:#### WorkerTask send event
L:#### WaitForWorker wait ticks AFTER
F:586:0:UI1/Valid/Valid/Valid/Flushed/Local/Fifo/Timeout/Empty/Nop:tc-message-receive.c:1004:RTEMS_TIMEOUT == RTEMS_UNSATISFIED
F:587:0:UI1/Valid/Valid/Valid/Flushed/Local/Fifo/Timeout/Empty/Nop:tc-message-receive.c:1043:3 == 0
L:#### rtems_message_queue_delete()
```

For the records:

```
RTEMS_VERSION = 6.0.0
remote origin = git://git.rtems.org/sebh/rtems.git /* The HASH is also in git://git.rtems.org/rtems.git */
commit HEAD = bb77a82f619752ba147c317d982ac47f56f4afec config.ini =
```

```
[arm/realview_pbx_a9_qemu]
RTEMS_DEBUG = True
RTEMS_NETWORKING = True
RTEMS_POSIX_API = True
RTEMS_SMP = True
BUILD_TESTS = True
```

```
NEWLIB_VERSION = 3.2.0
SOURCE_BUILDER = Set Builder, 6 (f12dee02d52d)
GCC_VERSION = arm-rtems6-gcc (GCC) 10.3.1 20210409 (RTEMS 6, RSB c938bd7cbe16bd03d3b382f2d7cfee6a86aa9424, Newlib 0c0f3df)
BINUTILS_VERSION = GNU ld (GNU Binutils) 2.36.1.20210409
```

**Comment 1**

1. **Frank Kuehndel**, Tue, 14 Sep 2021 15:19:16 GMT
2. **keywords:** **qualification** added

**Comment 2**

1. **Sebastian Huber**, Thu, 16 Sep 2021 07:34:37 GMT

In dbb7c956/rtems:

```
rtems: Fix message manager documentation
Correct the description of the count parameter of rtems_message_queue_flush().
Update #4508.
```

**Comment 3**

1. **Sebastian Huber**, Thu, 16 Sep 2021 07:37:35 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 7afc7a0/rtems-docs:

```
rtems: Fix message manager documentation
Correct the description of the count parameter of rtems_message_queue_flush().
Close #4508.
```

**4509 - Message queue priority discipline is broken in SMP configurations**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4509">https://devel.rtems.org/ticket/4509</a> ( <a href="https://devel.rtems.org/ticket/4509">https://devel.rtems.org/ticket/4509</a> )
<b>Id</b>	4509
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	31 August 2021 08:18:18
<b>Modified</b>	2 September 2021 05:51:53
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The message queue handler uses the thread queue extract operation to dequeue a receiver thread. This is wrong in SMP configurations since the extract thread queue operation does not ensure FIFO fairness across schedulers. The thread queue surrender operation should be used instead.

**Comment 1**

1. **Sebastian Huber**, Thu, 02 Sep 2021 05:48:07 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In d9249c9/rtems:

score: Fix blocking message queue receive

In order to ensure FIFO fairness across schedulers, the thread queue surrender operation must be used to dequeue a thread from the thread queue. The thread queue extract operation is intended for timeouts.

Add `_Thread_queue_Resume()` which may be used to make extracted or surrendered threads ready again.

Remove the now unused `_Thread_queue_Extract_critical()` function.

Close #4509.

## Comment 2

1. **Sebastian Huber**, Thu, 02 Sep 2021 05:51:53 GMT
2. **keywords: qualification** added

## 4510 - Fix ILP32 multilib variant in newlib for AArch64

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4510">https://devel.rtems.org/ticket/4510</a> ( <a href="https://devel.rtems.org/ticket/4510">https://devel.rtems.org/ticket/4510</a> )
<b>Id</b>	4510
<b>Reporter</b>	Ryan Long
<b>Created</b>	31 August 2021 20:01:54
<b>Modified</b>	22 November 2023 06:12:50
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

This flag is needed to force the generation of AArch64 assembly from C sources instead of using the hand-optimized code in newlib. The existing hand-optimized code has bugs for ILP32. There are multiple technical options to address this and lots of discussion:

- Update newlib from upstream ARM source code
- Add `-DPREFER_SIZE_OVER_SPEED` and always use C versions on aarch64
- Fix existing code

## Attachments:

1. **Ryan Long, Fri, 03 Sep 2021 12:31:34 GMT**  
**attach:** set to [0001-configure.host-Add-DPREFER\\_SIZE\\_OVER\\_SPEED.patch](https://devel.rtems.org/ticket/4510/0001-configure.host-Add-DPREFER_SIZE_OVER_SPEED.patch) ([https://devel.rtems.org/ticket/4510/0001-configure.host-Add-DPREFER\\_SIZE\\_OVER\\_SPEED.patch](https://devel.rtems.org/ticket/4510/0001-configure.host-Add-DPREFER_SIZE_OVER_SPEED.patch))
2. **Ryan Long, Fri, 10 Sep 2021 21:42:33 GMT**  
**attach:** set to [0001-aarch64-Add-ILP32-ABI-support-in-assembly.patch](https://devel.rtems.org/ticket/4510/0001-aarch64-Add-ILP32-ABI-support-in-assembly.patch) (<https://devel.rtems.org/ticket/4510/0001-aarch64-Add-ILP32-ABI-support-in-assembly.patch>)
3. **Kinsey Moore, Thu, 17 Mar 2022 21:17:26 GMT**  
**attach:** set to [0001-aarch64-Add-ILP32-ABI-support-in-assembly-v2.patch](https://devel.rtems.org/ticket/4510/0001-aarch64-Add-ILP32-ABI-support-in-assembly-v2.patch) (<https://devel.rtems.org/ticket/4510/0001-aarch64-Add-ILP32-ABI-support-in-assembly-v2.patch>)

## Comment 1

1. **Ryan Long**, Fri, 03 Sep 2021 16:36:21 GMT

This patch is only temporary. It will be removed once it is fixed upstream.

## Comment 2

1. **Chris Johns**, Tue, 07 Sep 2021 22:56:37 GMT

Who is fixing the upstream?

I have not been following newlib so is there a link to the discussion about this?

## Comment 3

1. **Ryan Long**, Wed, 08 Sep 2021 13:25:42 GMT

Replying to Chris Johns:

Who is fixing the upstream?

Kinsey has already gotten a fix merged with ARM. Newlib hasn't pulled those changes in yet though.

I have not been following newlib so is there a link to the discussion about this?

Here are the links to the discussions

<https://sourceware.org/pipermail/newlib/2020/017781.html> <https://sourceware.org/pipermail/newlib/2020/018169.html>  
<https://sourceware.org/pipermail/newlib/2020/018197.html>

#### Comment 4

1. **Chris Johns**, Thu, 09 Sep 2021 08:28:12 GMT

As discussed on devel@ the ILP32 support should be fixed or patched in newlib and we should not cause an performance regressions for LP64 targets.

#### Comment 5

1. **Joel Sherrill**, Thu, 09 Sep 2021 13:42:54 GMT

2. **description:** modified (diff)

3. **summary:** changed from **Add -DPREFER\_SIZE\_OVER\_SPEED for AArch64 builds** to **Fix ILP32 multilib variant in newlib for AArch64**

#### Comment 6

1. **Ryan Long**, Mon, 20 Sep 2021 20:37:49 GMT

In 0e54d58/rtems-source-builder:

```
rtems-gcc-10-newlib-head.cfg: Add newlib patch
```

Adds patch to add sanitation to the padding of bits and size\_t types for AArch64 tools builds with newlib. These changes have been made in ARM, but newlib has yet to pull them. This can be removed once newlib has pulled the code.

Updates #4510

#### Comment 7

1. **Ryan Long**, Mon, 20 Sep 2021 20:37:52 GMT

In 3950b1e/rtems-source-builder:

```
rtems-gcc-head-newlib-head.cfg: Add newlib patch
```

Adds patch to add sanitation to the padding of bits and size\_t types for AArch64 tools builds with newlib. These changes have been made in ARM, but newlib has yet to pull them. This can be removed once newlib has pulled the code.

Updates #4510

#### Comment 8

1. **Kinsey Moore**, Thu, 16 Dec 2021 15:56:03 GMT

2. **status:** changed from **new** to **closed**

3. **resolution:** set to **fixed**

This has been verified as fixed thanks to Ryan's patches.

#### Comment 9

1. **Kinsey Moore**, Thu, 17 Mar 2022 21:53:24 GMT

2. **status:** changed from **closed** to **reopened**

3. **resolution:** **fixed** deleted

Reopening this since it needs to be tracked until the patch is merged with newlib from the upstream optimized-routines repo.

#### Comment 10

1. **Chris Johns**, Tue, 29 Nov 2022 23:04:24 GMT

2. **version:** changed from **6** to **7**

3. **milestone:** changed from **6.1** to **7.1**

Moved until ARM adds a correct patch to newlib.

#### Comment 11

1. **Sebastian Huber**, Thu, 27 Jul 2023 15:01:56 GMT

2. **owner:** set to **Sebastian Huber**

3. **status:** changed from **reopened** to **assigned**
4. **version:** changed from **7** to **6**
5. **milestone:** changed from **7.1** to **6.1**

I guess you can wait forever if you want ARM to get this fixed. There are open issues in the ARM code:

<https://github.com/ARM-software/optimized-routines/issues/56>

<https://github.com/ARM-software/optimized-routines/pull/57>

#### Comment 12

1. **Kinsey Moore**, Thu, 27 Jul 2023 15:11:38 GMT

I've actually had some luck getting changes into optimized-routines. The hard part is getting them merged into newlib.

#### Comment 13

1. **Sebastian Huber**, Thu, 27 Jul 2023 15:12:55 GMT

I prepared some patches for Newlib, however, there is this open issue with the notes.

#### Comment 14

1. **Sebastian Huber**, Wed, 22 Nov 2023 06:12:50 GMT

In 07be298/rtems-source-builder:

```
6/7: Update Newlib
```

```
Pick up fixes for ARM/optimized-routines and the memory reclamation at thread exit.
```

```
Update #4510. Update #4967.
```

## 4511 - Count of postponed jobs is not set to zero for a newly created rate-monotonic period object

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4511">https://devel.rtems.org/ticket/4511</a> ( <a href="https://devel.rtems.org/ticket/4511">https://devel.rtems.org/ticket/4511</a> )
<b>Id</b>	4511
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	9 September 2021 13:00:32
<b>Modified</b>	6 October 2021 06:50:11
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

`rtems_rate_monotonic_get_status()` returns an arbitrary number for the count of postponed jobs if it is called for a newly created period object. The count of postponed jobs should be cleared to zero at object creation.

#### Comment 1

1. **Sebastian Huber**, Thu, 09 Sep 2021 13:07:17 GMT
2. **keywords:** **qualification** added

#### Comment 2

1. **Sebastian Huber**, Thu, 09 Sep 2021 13:08:09 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 82a61af/rtems:

```
rtems: Initialize count of postponed jobs
```

```
The rtems_rate_monotonic_get_status() directive returns an arbitrary number for the count of postponed jobs if it is called for a newly
```

created period object. Set the count of postponed jobs to zero during object creation.

Close #4511.

### Comment 3

1. **Sebastian Huber**, Wed, 06 Oct 2021 06:50:11 GMT

In 38c2147/rtems:

```
rtems: Set postponed jobs in rate-monotonic cancel
```

```
Set the postponed jobs count to zero in rtems_rate_monotonic_cancel() so that rtems_rate_monotonic_get_status() returns a consistent status for inactive periods.
```

```
Update #4511.
```

---

## 4513 - Document parts of the Cache Manager in the Classic API Guide

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4513">https://devel.rtems.org/ticket/4513</a> ( <a href="https://devel.rtems.org/ticket/4513">https://devel.rtems.org/ticket/4513</a> )
<b>Id</b>	4513
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 September 2021 08:29:13
<b>Modified</b>	16 September 2021 07:43:08
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The Cache Manager directives are available via . Document most of them in the Classic API Guide.

### Comment 1

1. **Sebastian Huber**, Thu, 16 Sep 2021 07:43:08 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

The documentation was updated.

---

## 4517 - Build failures for MacOS

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4517">https://devel.rtems.org/ticket/4517</a> ( <a href="https://devel.rtems.org/ticket/4517">https://devel.rtems.org/ticket/4517</a> )
<b>Id</b>	4517
<b>Reporter</b>	Chris Johns
<b>Created</b>	20 September 2021 00:15:33
<b>Modified</b>	29 November 2022 23:41:56
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

This ticket is a collection of the following archs that fail to build:

- bfin
- lm32
- mips

- or1k
- powerpc
- v850

**bfin**

```
../../../../sourceware-mirror-binutils-gdb-7ab567f/sim/bfin/dv-bfin_dma.c:124:35: error: implicitly declaring library function 'abs'
with type 'int (int)' [-Werror,-Wimplicit-function-declaration]
  if (dma->ele size != (unsigned) abs (dma->x modify))
```

**lm32**

```
../../../../sourceware-mirror-binutils-gdb-7ab567f/sim/lm32/dv-lm32cpu.c:151:8: error: implicit declaration of function
'lm32bf_h_csr_get' is invalid in C99 [-Werror,-Wimplicit-function-declaration]
  im = lm32bf_h_csr_get (cpu, LM32_CSR_IM);
```

**mip**

```
../../../../sourceware-mirror-binutils-gdb-7ab567f/sim/mips/cpl.c:495:7: error: implicitly declaring library function 'abort' with type
'void (void) __attribute__
```

**or1k**

```
../../../../sourceware-mirror-binutils-gdb-7ab567f/sim/or1k/./common/cgen-trace.c:213:6: error: implicitly declaring library function
'abort' with type 'void (void) __attribute__((noreturn))' [-Werror,-Wimplicit-function-declaration]
  abort ();
```

**powerpc**

```
semantics.c:42:7: error: implicit declaration of function 'tree_find_property' is invalid in C99 [-Werror,-Wimplicit-function-
declaration]
  if (tree_find_property(root, "/options/mpc860c0"))
```

**v850**

```
../../../../sourceware-mirror-binutils-gdb-7ab567f/sim/v850/simops.c:1651:6: error: implicit declaration of function 'free' is invalid
in C99 [-Werror,-Wimplicit-function-declaration]
  free (path);
```

**Comment 1**

1. **Chris Johns**, Mon, 20 Sep 2021 07:54:33 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Chris Johns**, Mon, 20 Sep 2021 07:55:01 GMT
2. **description:** modified (diff)

**Comment 3**

1. **Chris Johns**, Tue, 29 Nov 2022 23:41:56 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **wontfix**

There may be issues. Reopen if a specific build is needed.

**4518 - RTEMS and LibBSD both provide competing pipe() interfaces**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4518">https://devel.rtems.org/ticket/4518</a> ( <a href="https://devel.rtems.org/ticket/4518">https://devel.rtems.org/ticket/4518</a> )
<b>Id</b>	4518
<b>Reporter</b>	Chris Johns
<b>Created</b>	23 September 2021 05:29:15
<b>Modified</b>	24 September 2021 00:07:33
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

RTEMS provides a pipe() call in cpukit/libfs/src/pipe/pipe.c and LibBSD also provides a call in rtemsbsd/rtems/rtems-bsd-syscall-api.c. We should not have competing interfaces.

The selection of the version you get depends on the link order and the linker version. The RTEMS 6 linker seems to have a different preference to RTEMS 5. Apart from this fragility LibBSD should not be providing this interface.

A LibBSD pipe() is problematic for a number of reasons and so I am going to remove the call from it.

If LibBSD support is needed it needs to be via a file system op handles like all other file system interfaces for descriptor based access. I will not be adding this support.

The removal of pipe() from LibBSD removes the kqueue support for pipes. See the test selectpollkqueue01. If this support is needed please contact the RTEMS developers.

#### Comment 1

1. **Chris Johns**, Thu, 23 Sep 2021 05:32:50 GMT
2. **description:** modified (diff)

#### Comment 2

1. **Chris Johns**, Thu, 23 Sep 2021 05:34:24 GMT
2. **description:** modified (diff)

#### Comment 3

1. **Chris Johns**, Thu, 23 Sep 2021 09:16:00 GMT
2. **description:** modified (diff)

#### Comment 4

1. **Chris Johns**, Fri, 24 Sep 2021 00:03:48 GMT
2. **description:** modified (diff)
3. **summary:** changed from **RTEMS and LibBSD both provide pipe()** to **RTEMS and LibBSD both provide competing pipe() interfaces**

#### Comment 5

1. **Chris Johns**, Fri, 24 Sep 2021 00:06:48 GMT

The removal of pipe() from LibBSD does effect the kqueue support but it also lets the RTEMS version get linked in and do it's work. Pipe for libio descriptors and libmisc/redirector work nicely well before LibBSD is initialised and this is important in some applications. Especially ones that capture the console early to implement a dmesg type of support.

I am happy to see a file op added for pipe however I view RTEMS as having priority over the same call signature in LibBSD if there is a clash and there is.

I have an app that crashes because of this. I have no idea why on RTEMS 5 the RTEMS one is linked in and the same app and build system now results the LibBSD one. Having 2 interfaces is wrong.

#### Comment 6

1. **Chris Johns**, Fri, 24 Sep 2021 00:07:33 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 2e5f808/rtems-libbsd:

```
rtemsbsd/syscalls: Remove pipe()
This call is provided by RTEMS and that is preferred
Closes #4518
```

---

## 4519 - record-main-ltng.cc: Out-of-bounds access

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4519">https://devel.rtems.org/ticket/4519</a> ( <a href="https://devel.rtems.org/ticket/4519">https://devel.rtems.org/ticket/4519</a> )
<b>Id</b>	4519
<b>Reporter</b>	Ryan Long
<b>Created</b>	30 September 2021 19:55:28
<b>Modified</b>	7 October 2021 14:25:10
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



CID 1503017: Out-of-bounds access in CopyThreadName?().

```

1. Condition api_index < 3, taking false branch.
298 if (api_index < THREAD_API_COUNT) {
299     name = thread_names_[api_index][GetObjIndexOfID(item.data)];
300 } else {
2. alias: Assigning: name = kEmptyThreadName. name now points to byte 0 of kEmptyThreadName (which consists of 3 bytes).
301     name = kEmptyThreadName;
302 }
303
CID 1503017 (#1 of 1): Out-of-bounds access (OVERRUN)3. overrun-buffer-arg: Overrunning buffer pointed to by name of 3 bytes by
passing it to a function which accesses it at byte offset 15 using argument 16UL.
304 std::memcpy(dst, name, THREAD_NAME_SIZE);

```

#### Comment 1

1. **Ryan Long**, Thu, 07 Oct 2021 14:25:10 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 83b3d58/rtems-tools:

```

record-main-lttng.cc: Change size of empty string
CID 1503017: Out-of-bounds access in CopyThreadName?().
Change size of kEmptyThreadName from THREAD_API_COUNT to THREAD_NAME_SIZE.
Closes #4519

```

## 4522 - Optimize red-black tree insert/extract

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4522">https://devel.rtems.org/ticket/4522</a> ( <a href="https://devel.rtems.org/ticket/4522">https://devel.rtems.org/ticket/4522</a> )
<b>Id</b>	4522
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 October 2021 14:16:32
<b>Modified</b>	7 October 2021 19:39:19
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	tool/newlib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

Code coverage analysis of the red-black tree insert/extract operations defined in showed that the macros contain dead code. To fix this simplify some expressions and add specialized rotations:

<https://sourceware.org/pipermail/newlib/2021/018599.html>

#### Comment 1

1. **Sebastian Huber**, Thu, 07 Oct 2021 19:39:19 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 889cf95/rtems-source-builder:

```

Update newlib to fetch optimizations
Close #4522.

```

## 4524 - Re-add lost capability for custom stack allocator to allocate IDLE thread stacks

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4524">https://devel.rtems.org/ticket/4524</a> ( <a href="https://devel.rtems.org/ticket/4524">https://devel.rtems.org/ticket/4524</a> )
<b>Id</b>	4524
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 October 2021 22:21:23
<b>Modified</b>	2 May 2023 08:12:16
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

The move to statically allocate the stacks for the IDLE threads resulted in the loss of the capability for a custom stack allocator to be able to allocate the idle threads' stacks. This occurred close to the 5 branching point and is addressed for the 5 branch by #4520. This ticket is for the master (6).

#### Comment 1

1. **Joel Sherrill**, Mon, 11 Oct 2021 13:39:59 GMT
2. **owner:** set to **Joel Sherrill** <joel@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 822ebb4c/rtems:

```
Add support for IDLE Thread stack allocator
```

```
Add a stack allocator hook specifically for allocation of IDLE thread stacks. This allows the user to decide if IDLE thread stacks are statically allocated or handled by the same custom allocator mechanism as other thread stacks.
```

```
Closes #4524.
```

#### Comment 2

1. **Joel Sherrill**, Tue, 12 Oct 2021 18:44:34 GMT

In df5be4c/rtems-docs:

```
task-stack-alloc.rst: Add CONFIGURE_TASK_STACK_FROM_ALLOCATOR
```

```
Updates #4524.
```

#### Comment 3

1. **Sebastian Huber**, Mon, 25 Oct 2021 06:00:27 GMT

In 9be97a3/rtems:

```
score: Optimize default idle task stack allocator
```

```
Update #4524.
```

#### Comment 4

1. **Sebastian Huber**, Mon, 25 Oct 2021 06:00:37 GMT

In f1723d12/rtems:

```
rtems: Regenerate for IDLE task allocator option
```

```
Update #4524.
```

#### Comment 5

1. **Sebastian Huber**, Mon, 25 Oct 2021 06:10:52 GMT

In 46dbb6d/rtems-docs:

c-user: Regenerate for IDLE task allocator option  
Update #4524.

#### Comment 6

1. **Sebastian Huber**, Wed, 23 Feb 2022 08:29:13 GMT

In 2f8be4b/rtems-docs:

c-user: Document CONFIGURE\_SCHEDULER\_TABLE\_ENTRIES  
Update #4524.

#### Comment 7

1. **Sebastian Huber**, Wed, 23 Feb 2022 14:30:15 GMT

The last commit does not belong to this ticket. It references the wrong ticket number.

#### Comment 8

1. **Sebastian Huber**, Fri, 14 Oct 2022 09:41:45 GMT

In 2846b17/rtems:

config: Changeable size for IDLE stack allocator

Allow the IDLE stack allocator to change the stack size. This can be used by applications with a very dynamic thread-local storage size to adjust the thread storage area of the IDLE tasks dynamically.

Update #4524.

#### Comment 9

1. **Sebastian Huber**, Fri, 14 Oct 2022 09:42:01 GMT

In 45ee958/rtems:

config: Add CONFIGURE\_IDLE\_TASK\_STORAGE\_SIZE

By default, allocate the IDLE task storage areas from the RTEMS Workspace. This avoids having to estimate the thread-local storage size in the default configuration.

Add the application configuration option CONFIGURE\_IDLE\_TASK\_STORAGE\_SIZE to request a static allocation of the task storage area for IDLE tasks.

Update #3835. Update #4524.

#### Comment 10

1. **Sebastian Huber**, Fri, 14 Oct 2022 09:42:03 GMT

In 64fbaaa/rtems:

score: INTERNAL\_ERROR\_IDLE\_THREAD\_STACK\_TOO\_SMALL

Ensure that the IDLE storage allocator did allocate a sufficiently large area.

Update #3835. Update #4524.

#### Comment 11

1. **Sebastian Huber**, Tue, 02 May 2023 08:12:16 GMT

2. **keywords: qualification** added

---

## **4525 - rtems-tld.cpp: Logically dead code error spotted by Coverity**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4525">https://devel.rtems.org/ticket/4525</a> ( <a href="https://devel.rtems.org/ticket/4525">https://devel.rtems.org/ticket/4525</a> )
<b>Id</b>	4525
<b>Reporter</b>	Ryan Long
<b>Created</b>	8 October 2021 17:23:48
<b>Modified</b>	12 October 2021 14:40:44
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

CID 1399595: Logically dead code in generate\_traces().

```

1263         if (sig.has_ret () && !generator_.ret_trace.empty ())
1264         {
1265             if (ds_added)
1266                 ds += " + ";
1267             else
1268                 ds added = true;
1269         const: At condition drs_added, the value of drs_added must be equal to 0.
1270         dead_error_condition: The condition drs_added cannot be true.
1271         if (drs_added)
1272             CID 1399595 (#1 of 1): Logically dead code (DEADCODE)dead_error_line: Execution cannot reach this statement: drs += " + ";.
1273             drs += " + ";
1274             else
1275                 drs_added = true;
1276             ds += "sizeof(" + sig.ret + ')';
1277             drs += "sizeof(" + sig.ret + ')';
1278         }

```

**Comment 1**

1. **Ryan Long**, Tue, 12 Oct 2021 14:40:44 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 0acb4d0/rtems-tools:

```

rtems-tld.cpp: Remove logically dead code
CID 1399595: Logically dead code in generate_traces().
Closes #4525

```

**4527 - Add new directives to get all time values provided by the timehands**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4527">https://devel.rtems.org/ticket/4527</a> ( <a href="https://devel.rtems.org/ticket/4527">https://devel.rtems.org/ticket/4527</a> )
<b>Id</b>	4527
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 October 2021 14:01:01
<b>Modified</b>	19 November 2021 08:54:28
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Add directives for all time values provided by the timehands to the Clock Manager.

**Comment 1**

1. **Sebastian Huber**, Wed, 17 Nov 2021 08:11:55 GMT

In cbcfb6/rtems:

rtems: Add new clock manager directives

Update #4527.

## Comment 2

1. **Sebastian Huber**, Fri, 19 Nov 2021 08:54:28 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 38ec48d/rtems-docs:

c-user: Document new clock manager directives

Add new clock manager directives to get all times provided by the timehands.

Close #4527.

## 4528 - rate monotonic: reset of CPU usage time not always detected

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4528">https://devel.rtems.org/ticket/4528</a> ( <a href="https://devel.rtems.org/ticket/4528">https://devel.rtems.org/ticket/4528</a> )
<b>Id</b>	4528
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	11 October 2021 18:03:13
<b>Modified</b>	25 October 2021 16:01:04
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	trivial
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

`rtems_rate_monotonic_get_statistics()` and `rtems_rate_monotonic_get_status()` must detect whether the used CPU time was reset during a period (`rtems_cpu_usage_reset()`). This is achieved by storing the CPU usage time counter value when the period is started. To detect whether there was a reset, the CPU usage time value from the period start and the current value are compared. If the current value is lower than the one from the start there was a reset.

The bug is that when the current CPU usage time value is greater than the value at the start, a reset may still have occurred.

For example, when the period starts the used CPU time is at 1000 and 1000 is stored. Then the CPU time counter is resetted - so it is 0. Assume the period thread does some work and the CPU usage time is at 100 when `rtems_rate_monotonic_get_status()` is called. In this case the current code detects the reset and returns correctly `RTEMS_NOT_DEFINED`. Yet, when more CPU usage time passes without `rtems_rate_monotonic_period()` being called - lets say the used CPU time is at 1200 - and `rtems_rate_monotonic_get_status()` is called, the stored value (1000) is smaller than the current one (1200) so the reset is not detected.

This bug has been found with a test which manipulates the time directly. I doubt this bug is very relevant in practice. It requires that there are periods with long intervals and much CPU load and that either the system is shortly started or `rtems_cpu_usage_reset()` is used frequently.

The background:

The Classic API guide <https://docs.rtems.org/branches/master/c-user/rate-monotonic/directives.html#rtems-rate-monotonic-get-status> says for `rtems_rate_monotonic_get_status()`:

`RTEMS_NOT_DEFINED`: There was no status available due to a reset of the processor time usage of the owner task of the period.

The directive `rtems_cpu_usage_reset()` sets `the_thread->cpu_time_used` 0 in line 43 of `cpukit/libmisc/cpuuse/cpuusagereset.c`.

The detection whether there was an reset or not is done in file `cpukit/rtems/src/ratemonperiod.c` line 56 in function `_Rate_monotonic_Get_status()`:

```
[...]
/*
 * Determine cpu usage since period initiated.
 */
Thread_Get_CPU_time_used( owning_thread, &used );
/*
 * The cpu usage info was reset while executing. Can't
 * determine a status.
 */
if ( _Timestamp_Less_than( &used, &the_period->cpu_usage_period_initiated ) )
    return false;
[...]
```

The directive `rtems_rate_monotonic_get_statistics()` is affected indirectly because collecting its data is skipped when there was a reset. `cpukit/rtems/src/ratemonperiod.c` line 149 in function `_Rate_monotonic_Update_statistics()` (which in turn calls the above code).

For the records:

```
RTEMS_VERSION = 6.0.0
remote origin = git://git.rtems.org/sebh/rtems.git
commit HEAD = 1df2666ca1d73807a338e0d209ed1f42f67f00a9 (HEAD, origin/qual-43)
config.ini =
  [arm/realview_pbx_a9_qemu]
  RTEMS_DEBUG = True
  RTEMS_NETWORKING = True
  RTEMS_POSIX_API = True
  RTEMS_SMP = True
  BUILD_SAMPLES = False
  BUILD_VALIDATIONTESTS = True
  BUILD_UNITTESTS = True
NEWLIB_VERSION = 3.2.0
SOURCE_BUILDER = Set Builder, 6 (f12dee02d52d)
GCC_VERSION = arm-rtems6-gcc (GCC) 10.3.1 20210409 (RTEMS 6, RSB c938bd7cbe16bd03d3b382f2d7cf6ee6a86aa9424, Newlib 0c0f3df)
BINUTILS_VERSION = GNU ld (GNU Binutils) 2.36.1.20210409
```

### Comment 1

1. **Sebastian Huber**, Tue, 12 Oct 2021 06:22:08 GMT
2. **keywords:** qualification added
3. **status:** changed from **assigned** to **accepted**
4. **milestone:** changed from **Indefinite** to **6.1**

### Comment 2

1. **Sebastian Huber**, Mon, 25 Oct 2021 06:00:31 GMT

In 0221da5f/rtems:

```
rtems: Fix rate monotonic statistics
```

The rate monotonic period statistics were affected by `rtems_cpu_usage_reset()`. The logic to detect and work around a CPU usage reset was broken.

The `Thread_Contol::cpu_time_used` is changed to contain the processor time used throughout the entire lifetime of the thread. The new member `Thread_Contol::cpu_time_used_at_last_reset` is added to contain the processor time used at the time of the last reset through `rtems_cpu_usage_reset()`. This decouples the resets of the CPU usage and the rate monotonic period statistics.

Update #4528.

### Comment 3

1. **Sebastian Huber**, Mon, 25 Oct 2021 06:10:54 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In feb4687/rtems-docs:

```
c-user: rtems_rate_monotonic_get_status()
```

Mention that resetting the processor usage time of tasks has no impact on the period status and statistics.

Remove no longer relevant `RTEMS_NOT_DEFINED` error status.

Close #4528.

### Comment 4

1. **Sebastian Huber**, Mon, 25 Oct 2021 06:12:52 GMT

In 24922d0/rtems:

```
rtems: rtems_rate_monotonic_get_status()
```

Mention that resetting the processor usage time of tasks has no impact on the period status and statistics.

Remove no longer relevant `RTEMS_NOT_DEFINED` error status.

Update #4528.

### Comment 5

1. **Sebastian Huber**, Mon, 25 Oct 2021 16:01:04 GMT

In 75c133bd/rtems:

```
sptestsp/sp69: Remove test case
```

This error condition no longer exists.

Update #4528.

**4531 - Data corruption in SMP schedulers**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4531">https://devel.rtems.org/ticket/4531</a> ( <a href="https://devel.rtems.org/ticket/4531">https://devel.rtems.org/ticket/4531</a> )
<b>Id</b>	4531
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 October 2021 05:32:12
<b>Modified</b>	23 November 2021 13:36:27
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	critical
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Certain operations involving sticky thread queues, thread to processor affinity changes, priority updates, or thread pinning lead to data corruption in SMP schedulers, in particular the default SMP scheduler (SMP EDF).

**Comment 1**

1. **Sebastian Huber**, Wed, 20 Oct 2021 05:37:48 GMT
2. **severity**: changed from **normal** to **critical**

**Comment 2**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:06 GMT

In 577262a7/rtems:

```
score: Add red-black tree append/prepend
These functions are a faster alternative to _RbTree_Insert_inline() if it is known that the new node is the maximum/minimum node.
Update #4531.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:10 GMT

In 45e942d/rtems:

```
score: Rename _Scheduler_Set_idle_thread()
Rename _Scheduler_Set_idle_thread() in _Scheduler_Node_set_idle_user() and move it to .
Update #4531.
```

**Comment 4**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:13 GMT

In 7ae4f569/rtems:

```
score: Not set CPU in _Scheduler_Use_idle_thread()
Do not set the CPU of the idle thread in _Scheduler_Use_idle_thread(). This helps to use _Scheduler_Try_to_schedule_node() under more
general conditions in the future, for example in case the owner and user of a node are not the same.
Update #4531.
```

**Comment 5**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:17 GMT

In f0f60a1/rtems:

```
score: Change _Scheduler_Try_to_schedule_node()
Add the victim node as parameter instead of the idle thread.
```

Update #4531.

**Comment 6**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:20 GMT

In bd55f69/rtems:

```
score: Simplify _Scheduler_Exchange_idle_thread()
Remove superfluous idle parameter.
Update #4531.
```

**Comment 7**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:24 GMT

In e787091/rtems:

```
score: Add missing idle thread releases
Update #4531.
```

**Comment 8**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:28 GMT

In 81659420/rtems:

```
score: Add missing idle thread exchanges
Update #4531.
```

**Comment 9**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:31 GMT

In 6286a40/rtems:

```
score: Scheduler insert after move

Insert nodes after moving the second node to reduce the items in the data structure for the insert operation. This also avoids having two nodes for the same processor inserted into the scheduled chain.
Update #4531.
```

**Comment 10**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:35 GMT

In 757a1096/rtems:

```
score: Remove return value from enqueue scheduled
The return value was unused. Remove it.
Update #4531.
```

**Comment 11**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:38 GMT

In a53229bb/rtems:

```
score: Use extract from scheduled callbacks
Use the extract from scheduled callback provided by the scheduler implementation in the SMP scheduler framework.
Update #4531.
```

**Comment 12**1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:42 GMT



In 9d3e8212/rtems:

score: Rework affine ready queue handling

Rework the handling of the affine ready queue for the EDF SMP scheduler. Do the queue handling in the node insert, move, and extract operations. Remove the queue handling from `_Scheduler_EDF_SMP_Allocate_processor()`.

Update #4531.

### **Comment 13**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:45 GMT

In 75527ef3/rtems:

score: Optimize SMP EDF move to ready operation

If a node is moved from the scheduled chain to the ready queue, then we know that it is the highest priority ready node. So, it can be prepended to the ready queue without doing any comparisons.

Update #4531.

### **Comment 14**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:49 GMT

In 3781709/rtems:

score: Add SMP scheduler idle exchange callback

Update #4531.

### **Comment 15**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:56 GMT

In ff20bc9/rtems:

score: Rework idle handling in SMP schedulers

This patch fixes an issue with the idle thread handling in the SMP scheduler framework used for the MrsP locking protocol. The approach to use a simple chain of unused idle threads is broken for schedulers which support thread to processor affinity. The reason is that the thread to processor affinity introduces another ordering indicator which may under certain conditions lead to a reordering of idle threads in the scheduled chain. This reordering is not propagated to the chain of unused idle threads. This could lead to use an idle thread for a sticky scheduler node which is already in use. This locks up the system in infinite loops in the thread context switch procedure.

To fix this, the SMP scheduler implementations must now provide callbacks to get and release an unused idle thread.

Update #4531.

### **Comment 16**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:09 GMT

In dcd8b93/rtems:

score: Move `_Scheduler_Block_node()`

Move `_Scheduler_Block_node()` into `_Scheduler_SMP_Block()`. This simplifies the code and makes it easier to review.

Update #4531.

### **Comment 17**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:13 GMT

In c6362f6/rtems:

score: Move `_Scheduler_Unblock_node()`

Move `_Scheduler_Unblock_node()` into `_Scheduler_SMP_Unblock()`. This simplifies the code and makes it easier to review.

Update #4531.

### **Comment 18**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:16 GMT

In d0434b88/rtems:

score: Remove victim thread from CPU allocation  
Update #4531.

**Comment 19**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:20 GMT

In 4d90289e/rtems:

score: `_Scheduler_SMP_Schedule_highest_ready()`

Simplify callers of `_Scheduler_SMP_Schedule_highest_ready()`. Move the node state change and the extraction from scheduled into `_Scheduler_SMP_Schedule_highest_ready()`. Move the idle thread release to the caller which have more information about the presence of an idle thread.

Update #4531.

**Comment 20**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:23 GMT

In fc64e837/rtems:

score: Rework ask for help requests

Process ask for help requests on the current processor. This avoids using inter-processor interrupts to make the system behaviour a bit more predictable.

Update #4531.

**Comment 21**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:27 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 6443c9d/rtems:

score: Fix assertion in SMP scheduler framework

Properly assert that the scheduled chain is not empty. Fix formatting.

Close #4531.

**4532 - Priority inversion issues with MrsP locking protocol implementation**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4532">https://devel.rtems.org/ticket/4532</a> ( <a href="https://devel.rtems.org/ticket/4532">https://devel.rtems.org/ticket/4532</a> )
<b>Id</b>	4532
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 October 2021 05:37:11
<b>Modified</b>	23 November 2021 13:35:53
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	critical
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

While a thread is scheduled on a helping scheduler, while it does not own a MrsP semaphore, if it obtains a MrsP semaphore, then no scheduler node using an idle thread and the ceiling priority of the semaphore is unblocked for the home scheduler. This could lead to priority inversion issues and is not in line with the MrsP protocol.

**Comment 1**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:53 GMT

2. **status**: changed from **assigned** to **closed**

**3. resolution: set to fixed**

In 3d6ebde1/rtems:

score: Add SMP scheduler make/clean sticky

This patch fixes the following broken behaviour:

While a thread is scheduled on a helping scheduler, while it does not own a MrsP semaphore, if it obtains a MrsP semaphore, then no scheduler node using an idle thread and the ceiling priority of the semaphore is unblocked for the home scheduler.

This could lead to priority inversion issues and is not in line with the MrsP protocol.

Introduce two new scheduler operations which are only enabled if RTEMS\_SMP is defined. The operations are used to make the scheduler node of the home scheduler sticky and to clean the sticky property. This helps to keep the sticky handing out of the frequently used priority update operation.

Close #4532.

**4533 - libdebugger should only build for archs with a backend**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4533">https://devel.rtems.org/ticket/4533</a> ( <a href="https://devel.rtems.org/ticket/4533">https://devel.rtems.org/ticket/4533</a> )
<b>Id</b>	4533
<b>Reporter</b>	Chris Johns
<b>Created</b>	21 October 2021 02:04:25
<b>Modified</b>	25 October 2021 02:55:00
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Libdebugger has limited backend support however the generic parts are bring built for all architectures and libdebugger.a is being install however it will never link because of the missing backend support.

LibBSD has been fixed to correctly detect libdebugger.a and enable the test. This now fails to build.

**Comment 1**

1. **Chris Johns**, Mon, 25 Oct 2021 02:55:00 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3f0ad2b/rtems:

spec/libdebugger: Only enable for supported architectures

Closes #4533

**4534 - SMP EDF scheduler violates priority group ordering**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4534">https://devel.rtems.org/ticket/4534</a> ( <a href="https://devel.rtems.org/ticket/4534">https://devel.rtems.org/ticket/4534</a> )
<b>Id</b>	4534
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	27 October 2021 07:40:13
<b>Modified</b>	23 November 2021 13:36:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The SMP EDF scheduler supports one-to-one and one-to-all thread to processor affinities. The one-to-one thread to processor affinity introduces a constraint on the ordering of threads. The implementation uses one ready queue for threads which have a one-to-all affinity and one for each one-to-one affinity group. To order threads across the ready queues, a generation number is used. However, the approach to update the generation number each time a thread is inserted into a ready queue is wrong. The generation number need to be updated only in the enqueue and enqueue scheduled operations where an insert priority is available. The scheduled chain needs to take the generation number into account.

An example scenario which shows the bug is this. Let T be a high priority task affine to processor X. Let A be a lower priority task affine to processor X. Let B be a lower priority task with no affinity to a particular processor which executes on processor Y. Let B be in the same priority group than A and after A. Let T set the affinity to all processors. Now A (higher priority relative to B) should execute on X and T (high priority) should execute on Y.

**Comment 1**

1. **Sebastian Huber**, Wed, 27 Oct 2021 08:04:06 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:35:59 GMT

In 6d20f0c5/rtems:

```
score: Add node to insert to Chain_Node_order
This allows to use additional members of the nodes for comparision.
Update #4534.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:03 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In b9990b8d/rtems:

```
score: Fix SMP EDF priority group ordering

The SMP EDF scheduler supports one-to-one and one-to-all thread to processor affinities. The one-to-one thread to processor affinity introduces a constraint on the ordering of threads. The implementation uses one ready queue for threads which have a one-to-all affinity and one for each one-to-one affinity group. To order threads across the ready queues, a generation number is used. However, the approach to update the generation number each time a thread is inserted into a ready queue was wrong. The generation number needs to be updated only in the enqueue and enqueue scheduled operations where an insert priority is available. The scheduled chain needs to take the generation number into account.

An example scenario which shows the bug is this. Let T be a high priority task affine to processor X. Let A be a lower priority task affine to processor X. Let B be a lower priority task with no affinity to a particular processor which executes on processor Y. Let B be in the same priority group than A and after A. Let T set the affinity to all processors. Now A (higher priority relative to B) should execute on X and T (high priority) should execute on Y.

Close #4534.
```

**4543 - cannot build multiprocessor application on eclipse**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4543">https://devel.rtems.org/ticket/4543</a> ( <a href="https://devel.rtems.org/ticket/4543">https://devel.rtems.org/ticket/4543</a> )
<b>Id</b>	4543
<b>Reporter</b>	mohamedosama94
<b>Created</b>	3 November 2021 14:22:44
<b>Modified</b>	16 December 2021 15:38:53
<b>Owner</b>	
<b>Type</b>	task
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	worksforme
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	critical
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

Hi,

hope my mail finds you well, i have an issue as i am using rtems6 for zinq a53\_lp64 i downloaded the source and installed the toolchain aarch64-rtems6 and i built the bsp successfully by using waf and i used the qemu to run the test samples exe files successfully , so i installed the eclipse and added rtems plugin to it and i built the sample rtems example successfully but when i try to build an application task has test\_begin() or test\_end() the make is uncomplete and error (.text.Init+0x50): relocation truncated to fit: R\_AARCH64\_CALL26 against undefined symbol `rtems\_test\_begin' always appear i tried open declaration and i found the reference prototype  
int rtems\_test\_begin(const char\* name, const RTEMS\_TEST\_STATE state);

on test-info.h so eclipse refuse to build as cannot see the source code of the function and this also for rtems\_test\_end so what i have to do to make the eclipse build the rtems-application, kindly check the logs

```
/home/mohamed/quick-starts/rtems/6/lib/gcc/aarch64-rtems6/10.3.1/../../../../aarch64-rtems6/bin/ld: o-optimize/init.o: in function `Init':
/home/mohamed/eclipse-ground/rtems/rtems-app__init.c:64: undefined reference to `rtems_test_begin'
/home/mohamed/eclipse-ground/rtems/rtems-app__init.c:64:(.text.Init+0x50): relocation truncated to fit: R_AARCH64_CALL26 against undefined symbol `rtems_test_begin'
/home/mohamed/quick-starts/rtems/6/lib/gcc/aarch64-rtems6/10.3.1/../../../../aarch64-rtems6/bin/ld: /home/mohamed/eclipse-ground/rtems/rtems-app__init.c:66: undefined reference to `locked_print_initialize'
/home/mohamed/eclipse-ground/rtems/rtems-app__init.c:66:(.text.Init+0x54): relocation truncated to fit: R_AARCH64_CALL26 against undefined symbol `locked_print_initialize'
/home/mohamed/quick-starts/rtems/6/lib/gcc/aarch64-rtems6/10.3.1/../../../../aarch64-rtems6/bin/ld: o-optimize/init.o: in function `success':
/home/mohamed/eclipse-ground/rtems/rtems-app__init.c:31: undefined reference to `rtems_test_end'
/home/mohamed/eclipse-ground/rtems/rtems-app__init.c:31:(.text.Init+0x5c): relocation truncated to fit: R_AARCH64_CALL26 against undefined symbol `rtems_test_end'
/home/mohamed/quick-starts/rtems/6/lib/gcc/aarch64-rtems6/10.3.1/../../../../aarch64-rtems6/bin/ld: /home/mohamed/eclipse-ground/rtems/rtems-app__init.c:32: undefined reference to `rtems_test_exit'
/home/mohamed/eclipse-ground/rtems/rtems-app__init.c:32:(.text.Init+0x64): relocation truncated to fit: R_AARCH64_CALL26 against undefined symbol `rtems_test_exit'
/home/mohamed/quick-starts/rtems/6/lib/gcc/aarch64-rtems6/10.3.1/../../../../aarch64-rtems6/bin/ld: o-optimize/init.o: (.rodata._User_extensions.Initial_extensions+0x80): undefined reference to `rtems_test_fatal_extension'
collect2: error: Td returned 1 exit status
```

best regards,  
Mohamed

## Comment 1

1. **Joel Sherrill**, Wed, 03 Nov 2021 16:11:38 GMT

Those symbols are part of the RTEMS test support and would not have been included in whatever test directory you copied. They may be in a test support library. I don't know if it is installed.

I hope you mean SMP and not multiprocessor. Those are different configurations in RTEMS terminology.

Which test did you copy?

## Comment 2

1. **mohamedosama94**, Thu, 04 Nov 2021 10:43:20 GMT

Replying to Joel Sherrill:

Those symbols are part of the RTEMS test support and would not have been included in whatever test directory you copied. They may be in a test support library. I don't know if it is installed.

I hope you mean SMP and not multiprocessor. Those are different configurations in RTEMS terminology.

Which test did you copy?

Dear Joel Sherrill,

thanks for your reply, yes I mean SMP, and this issue happens when I use any test suites samples that have test\_begin() and test\_end() functions like: "base\_mp" test, "base\_sp" test but test like "hello" that doesn't have these functions build normally on eclipse so how can I install the support library and make the eclipse can reach them

## Comment 3

1. **Joel Sherrill**, Thu, 04 Nov 2021 13:29:30 GMT

Replace `test_begin()` and `test_end()` with a print to denote beginning and end of the test.

`base_mp` is for the distributed multiprocessing model in RTEMS. You want to build with SMP not multiprocessing (confusing I know). And I don't think there is an SMP sample. You may have to look at one of the tests `smptest` directory. These all use test support functions also but `smpschedaffinity01` and `smpschedaffinity01` are not large and show how to do affinity. `smpthreadpin01` shows pinning but is a bit more complicated than just demonstrating that a collection of threads were properly assigned to the desired core.

#### Comment 4

1. **Joel Sherrill**, Thu, 16 Dec 2021 15:38:53 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **worksforme**

## 4544 - The last processor must not be removed if it is owned by a helping scheduler

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4544">https://devel.rtems.org/ticket/4544</a> ( <a href="https://devel.rtems.org/ticket/4544">https://devel.rtems.org/ticket/4544</a> )
<b>Id</b>	4544
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 November 2021 09:44:53
<b>Modified</b>	23 November 2021 13:49:07
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

The following error condition is currently not checked by `rtems_scheduler_remove_processor()`: While an attempt is made to remove a processor from a scheduler, while the processor is the only processor owned by the scheduler, if a thread exists which uses the scheduler as a helping scheduler, then shall not be removed.

The reason is that ask for help requests and withdraw node requests are processed asynchronously in any order. An ask for help request carried out on a scheduler without a processor is undefined behaviour.

#### Comment 1

1. **Sebastian Huber**, Wed, 10 Nov 2021 08:21:56 GMT
2. **description**: modified (diff)
3. **summary**: changed from **Incorrect state change in processor removal of SMP scheduler** to **The last processor must not be removed if it is owned by a helping scheduler**

#### Comment 2

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:30 GMT

In c69a70a/rtems:

```
rtems: Fix rtems_scheduler_remove_processor()
Return an error status for the following error condition in rtems_scheduler_remove_processor():
While an attempt is made to remove a processor from a scheduler, while the processor is the only processor owned by the scheduler, if a thread exists which uses the scheduler as a helping scheduler, then the processor shall not be removed.
The reason is that ask for help requests and withdraw node requests are processed asynchronously in any order. An ask for help request carried out on a scheduler without a processor is undefined behaviour.
Update error status description.
Update #4544.
```

#### Comment 3

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:49:07 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 513b90d/rtems-docs:

```
c-user: rtems_scheduler_remove_processor()
```

Update error status description.

Close #4544.

## **4545 - The SMP EDF scheduler can only support more restricted affinity sets of a thread**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4545">https://devel.rtems.org/ticket/4545</a> ( <a href="https://devel.rtems.org/ticket/4545">https://devel.rtems.org/ticket/4545</a> )
<b>Id</b>	4545
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 November 2021 08:27:34
<b>Modified</b>	23 November 2021 13:36:33
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

The SMP EDF scheduler supports a one-to-one and one-to-all thread to processor affinity. Currently it accepts affinity sets which are a proper subset of the online processors containing at least two processors owned by the scheduler. In this case it sets a one-to-one thread to processor affinity. This leads to undefined behaviour if a processor is removed since the higher level check in `rtems_scheduler_remove_processor()` does not account for this implementation detail.

### **Comment 1**

1. **Sebastian Huber**, Wed, 10 Nov 2021 08:29:06 GMT
2. **description:** modified (diff)
3. **summary:** changed from **The SMP EDF scheduler has to better check the affinity set of a thread** to **The SMP EDF scheduler can only support more restricted affinity sets of a thread**

### **Comment 2**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:33 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 834a86fe/rtems:

```
score: Restrict affinity for EDF SMP scheduler
```

```
The SMP EDF scheduler supports a one-to-one and one-to-all thread to processor affinity. It accepted affinity sets which are a proper subset of the online processor containing at least two processors owned by the scheduler. In this case it used a one-to-one thread to processor affinity. This leads to undefined behaviour if a processor is removed since the higher level check in rtems_scheduler_remove_processor() does not account for this implementation detail.
```

```
Restrict the affinity set accepted by the SMP EDF scheduler to all online processors, or exactly one processor owned by the scheduler. Close #4545.
```

## **4546 - A thread restart does not update the priority of related threads**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4546">https://devel.rtems.org/ticket/4546</a> ( <a href="https://devel.rtems.org/ticket/4546">https://devel.rtems.org/ticket/4546</a> )
<b>Id</b>	4546
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 November 2021 17:00:55
<b>Modified</b>	23 November 2021 13:36:54
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Consider the following scenario. Let a high priority task H wait on a priority inheritance mutex M owned by a low priority task L. Restart task H. This should remove the priority inherited by H from L. This is currently not the case.

**Comment 1**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:37 GMT

In cd791039/rtems:

```
score: Remove thread timer earlier
```

The earlier we remove the thread timer the less likely is a superfluous thread timeout processing.

Update #4546.

**Comment 2**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:40 GMT

In 50aef135/rtems:

```
score: Add _Thread_MP_Extract_proxy()
```

Remove `_Thread_queue_Extract_with_proxy()` and move the proxy extraction to `_Thread_MP_Extract_proxy()`. Move similar code blocks of the previous caller of `_Thread_queue_Extract_with_proxy()` to helper functions.

Update #4546.

**Comment 3**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:44 GMT

In e429e97/rtems:

```
score: Simplify thread wait state handling
```

Remove the `THREAD_WAIT_STATE_READY_AGAIN` and simply use the initial value to indicate that a thread does not wait on something. Rename `THREAD_WAIT_FLAGS_INITIAL` to `THREAD_WAIT_STATE_READY`. This change is necessary so that `_Thread_Continue()` can be called for threads which never waited on something (for example dormant threads).

Update #4546.

**Comment 4**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:47 GMT

In 2e56aab/rtems:

```
score: Move _Thread_queue_Extract()
```

Move `_Thread_queue_Extract()` since this function is not used by the core services (threads, semaphores, mutexes, message queues).

Update #4546.

**Comment 5**

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:51 GMT

In 3b6e263a/rtems:



```
score: _Thread_queue_Surrender_no_priority()
Simplify _Thread_queue_Surrender_no_priority() and use _Thread_queue_Resume().
Update #4546.
```

### Comment 6

1. **Sebastian Huber**, Tue, 23 Nov 2021 13:36:54 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 5468464/rtems:

```
score: Properly continue the thread during restart
```

The `_Thread_queue_Extract()` does not deal with potential priority updates and the SMP locking protocol handling. Use `_Thread_queue_Continue()`. For the POSIX signals processing this is currently probably unnecessary, however, the use case is similar to the `restart` so use the same approach.

```
Close #4546.
```

## 4547 - dtc build failure on msys2 - all rtems6 target tools fail to build on Windows 10

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4547">https://devel.rtems.org/ticket/4547</a> ( <a href="https://devel.rtems.org/ticket/4547">https://devel.rtems.org/ticket/4547</a> )
<b>Id</b>	4547
<b>Reporter</b>	kgardas
<b>Created</b>	11 November 2021 21:08:30
<b>Modified</b>	17 February 2024 05:15:05
<b>Owner</b>	kgardas
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SoC, ecosystem, small, msys2
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

```
I'm testing RSB git source updated 2021-11-10 and it fails on freshly installed msys2/windows 10 platform with:
karel@DESKTOP-755H9VE MINGW64 /c/r/rtems-source-builder/rtems
$ ./source-builder/sb-check
RTEMS Source Builder - Check, 6 (efa44e47a7d2 modified)
Environment is ok
```

```
karel@DESKTOP-755H9VE MINGW64 /c/r/rtems-source-builder/rtems
$ ./source-builder/sb-set-builder --prefix=/c/r/r 6/rtems-sparc
RTEMS Source Builder - Set Builder, 6 (efa44e47a7d2 modified)
Build Set: 6/rtems-sparc
config: devel/dtc-1.6.0-1.cfg
package: dtc-1.6.0-x86_64-w64-mingw32-1
building: dtc-1.6.0-x86_64-w64-mingw32-1
error: building d1xwm1
Build FAILED
```

See error report: [rsb-report-dtc-1.6.0-x86\\_64-w64-mingw32-1.txt](#)

```
error: building d1xwm1
Build Set: Time 0:00:28.232196
Build FAILED
```

```
karel@DESKTOP-755H9VE MINGW64 /c/r/rtems-source-builder/rtems
$
the problem report is attached.
```

Joel adds: dtc does not build on msys2. It requires `fnmatch.h` which is not present. Alternative fixes include finding an alternative for `fnmatch` on msys2, providing an implementation to be used on msys2, or adding `gnulib` which is a portability package to our RSB packages on msys2.

Also there may be other tickets for the same issue.

Possible Mentors: Karel Gardas  
Skills: C  
Difficulty: Medium

### Attachments:

- 1 **kgardas**, Thu, 11 Nov 2021 21:09:20 GMT  
**attach:** set to [rsb-report-dtc-1.6.0-x86\\_64-w64-mingw32-1.txt](https://devel.rtems.org/ticket/4547/rsb-report-dtc-1.6.0-x86_64-w64-mingw32-1.txt) ([https://devel.rtems.org/ticket/4547/rsb-report-dtc-1.6.0-x86\\_64-w64-mingw32-1.txt](https://devel.rtems.org/ticket/4547/rsb-report-dtc-1.6.0-x86_64-w64-mingw32-1.txt))

**Comment 1**

1. **Joel Sherrill**, Wed, 02 Feb 2022 14:23:22 GMT
2. **keywords: SoC** added
3. **milestone: set to 6.1**

Adding SoC as a ticket because I think this is a possible small SoC project. Possible solutions include adding gnulib to the RSB bset for msys2 or modifying dtc to use other APIs for this functionality.

**Comment 2**

1. **Gedare Bloom**, Fri, 04 Feb 2022 18:53:18 GMT
2. **keywords: ecosystem small** added

**Comment 3**

1. **Joel Sherrill**, Fri, 04 Feb 2022 20:05:29 GMT
2. **keywords: msys2** added
3. **description: modified (diff)**
4. **summary: changed from RSB can't build rtems-sparc target tools on Windows 10. to dtc build failure on msys2 - all rtems6 target tools fail to build on Windows 10**

**Comment 4**

1. **Joel Sherrill**, Fri, 25 Feb 2022 21:15:50 GMT
2. **description: modified (diff)**

**Comment 5**

1. **Chris Johns**, Tue, 29 Nov 2022 23:48:28 GMT
- status update?

**Comment 6**

1. **Gedare Bloom**, Sat, 17 Feb 2024 05:15:05 GMT
2. **owner: set to kgardas**
3. **status: changed from new to assigned**

**4548 - Add RTEMS version option to waf configure**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4548">https://devel.rtems.org/ticket/4548</a> ( <a href="https://devel.rtems.org/ticket/4548">https://devel.rtems.org/ticket/4548</a> )
<b>Id</b>	4548
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 November 2021 23:00:52
<b>Modified</b>	18 March 2022 13:48:30
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	enhancement
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

We need a way to override the default release for testing. This is a developer option and is not for production. A waf option is considered the best way to manage this.

**Comment 1**

1. **Sebastian Huber**, Sat, 13 Nov 2021 13:53:19 GMT

This enhancement should be solved in a more general setting. What we need is the ability for maintainers to alter build system variables which a user should not be able to change.

What we could do is using an `_` prefix for internal build system variables which may be changed by the `config.ini` file if an `--rtems-maintainer-mode` option is given at the `configure` command line.

An alternative would be a `get-option` option action (similar to `set-value`) which uses a command line specified value if it is available. We could also add this feature to `set-value`.

### Comment 2

1. **Chris Johns**, Sun, 14 Nov 2021 02:56:59 GMT

I think maintainer experiments should be done with spec file changes on feature branches. My concern about a generic method from the command line, INI file or any other method is the testable dependencies it exposes. I feel what we have and where we are at is a good compromise between the web of options we had with `__autoconf's__` `configure` and the ever present complexity of build and BSP options we have to have.

I agree the implementation of how to manage this should follow reasonable design paths but I think the type of action needed has to be explicit with `wscript` or spec file changes.

I have added a call named `item_set_action_value()` that takes a path and value. The value needs to be of a type and nature that matches the action. The code to set the major version from the command line is:

```
if conf.options.rtems_version is not None:
    item set action value(conf, '/cpukit/optvermaj/set-value', conf.options.rtems version)
```

I think a path to address an item is a suitable abstraction. This version value update happens before the items are processed by `configure` which is important.

### Comment 3

1. **Sebastian Huber**, Wed, 17 Nov 2021 08:12:02 GMT

In `a0650f5f/rtems`:

```
build: Support command line specified options
Update #4548.
```

### Comment 4

1. **Sebastian Huber**, Wed, 17 Nov 2021 08:12:05 GMT

In `f06dd3e/rtems`:

```
build: Optional RTEMS_MAJOR via command line
Update #4548.
```

### Comment 5

1. **Sebastian Huber**, Wed, 17 Nov 2021 08:12:09 GMT

In `c1395ca0/rtems`:

```
build: Add --rtems-version command line option
Update #4548.
```

### Comment 6

1. **Joel Sherrill**, Fri, 17 Dec 2021 17:22:19 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **fixed**

Closing. This is in the tree now.

### Comment 7

1. **Sebastian Huber**, Tue, 11 Jan 2022 15:47:42 GMT

2. **owner**: set to **Sebastian Huber** <[sebastian.huber@...](mailto:sebastian.huber@...)>

In `fa1c18e/rtems-docs`:

```
eng: Document get-string-command-line action
Close #4548.
```

### Comment 8

1. **Sebastian Huber**, Tue, 11 Jan 2022 15:56:22 GMT

In 1ba0f41/rtems-docs:

eng: Document get-string-command-line action

Update #4548.

**Comment 9**1. **Sebastian Huber**, Fri, 18 Mar 2022 13:48:30 GMT

In 1a5991e/rtems:

build: Apply command line options to all variants

Update #4548.

**4550 - Add --rtems-version to rtems-test**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4550">https://devel.rtems.org/ticket/4550</a> ( <a href="https://devel.rtems.org/ticket/4550">https://devel.rtems.org/ticket/4550</a> )
<b>Id</b>	4550
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	19 November 2021 22:02:13
<b>Modified</b>	16 December 2021 20:34:35
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	rtems-test
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The rtems-test does not have a way to override the RTEMS version. This results in some tools defaulting to rtems6 when you want to test with the rtems7 version.

**Comment 1**

1. **Kinsey Moore**, Thu, 16 Dec 2021 20:34:35 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **duplicate**

This is a duplicate of #3671

**4551 - Workaround for GRLIB-TN-0011 required for sparc/leon3 BSPs in SMP configuration**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4551">https://devel.rtems.org/ticket/4551</a> ( <a href="https://devel.rtems.org/ticket/4551">https://devel.rtems.org/ticket/4551</a> )
<b>Id</b>	4551
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	23 November 2021 15:26:55
<b>Modified</b>	26 November 2021 09:38:20
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The check script tn-0011.tcl reported the following affected code block in cpu\_asm.S:

```
sparc-rtems6-objdump -d build/sparc/gr712rc/testsuites/validation/ts-validation-0.exe | tn-0011.tcl
INFO: Scanning utility for
INFO: GRLIB-TN-0011 - LEON3/FT AHB Lock Release during Atomic Operation
INFO: Script revision: 3 (20180412)
INFO:
INFO: Scanning objdump -d output on standard input...
0x400ad5f8 : seqa
INFO: 400ad5f8:      c2 7a 60 58      swap [ %o1 + 0x58 ], %g1
INFO: 400ad5fc:      80 a0 60 00      cmp %g1, 0
INFO: 400ad600:      12 80 00 14      bne 400ad650
INFO:
INFO: Error locations found: 1
```

**Comment 1**

1. **Sebastian Huber**, Fri, 26 Nov 2021 09:38:20 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In bdcc814/rtems:

```
sparc: Add workaround for GRLIB-TN-0011
```

Affected components are the GR712RC, UT699, UT699E, UT700, and LEON3FT-RTAX. Strictly, the workaround is only necessary if the MMU is enabled. Use FIX\_LEON3FT\_B2BST to enable the workaround. This is not 100% appropriate, but the best thing we can use to enable the workaround.

```
Close #4551.
```

**4556 - rtems\_shell\_main\_mmove problem**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4556">https://devel.rtems.org/ticket/4556</a> ( <a href="https://devel.rtems.org/ticket/4556">https://devel.rtems.org/ticket/4556</a> )
<b>Id</b>	4556
<b>Reporter</b>	chenjin_zhong
<b>Created</b>	2 December 2021 14:03:20
<b>Modified</b>	23 December 2022 18:56:38
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Hi, I think `__mmove__` command in shell means that the memory can be overlapped when copy happens. but I find that when implementing this function, the `__memcpy__` is used in RTEMS4.13/RTEMS5.1. Should the `__memcpy__` be replaced with `__mmove__`? The src code is listed as follows.

```
static int rtems_shell_main_mmove(
{
    int argc,
    char *argv[]

}

unsigned long tmp;
void *src;
void *dst;
size_t length;

if ( argc < 4 ) {
    fprintf(stderr,"%s: too few arguments\n", argv[0]);
    return -1;
}

/*
```

- Convert arguments into numbers

```

if ( rtems_string_to_pointer(argv[1], &dst, NULL) ) {
    printf( "Destination argument (%s) is not a number\n", argv[1] );
    return -1;
}

```

```

if ( rtems_string_to_pointer(argv[2], &src, NULL) ) {
    printf( "Source argument (%s) is not a number\n", argv[2] );
    return -1;
}

```

```

if ( rtems_string_to_unsigned_long(argv[3], &tmp, NULL, 0) ) {
    printf( "Length argument (%s) is not a number\n", argv[3] );
    return -1;
}
length = (size_t) tmp;

```

```

/*

```

- Now copy the memory.

```

__memcpy(dst, src, length);

```

```

return 0;

```

```

}

```

#### Comment 1

1. **Chris Johns**, Thu, 10 Nov 2022 00:44:36 GMT
2. **version**: changed from **5** to **6**
3. **milestone**: changed from **5.1** to **6.1**

#### Comment 2

1. **Chris Johns**, Tue, 29 Nov 2022 23:49:11 GMT
2. **owner**: set to **Chris Johns**
3. **status**: changed from **new** to **assigned**

#### Comment 3

1. **zack leung**, Fri, 23 Dec 2022 18:56:38 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 4523c713/rtems:

```

rtems_shell_main_mmove problem
--0000000000006acec205efd38cd6 Content-Type: text/plain; charset="UTF-8"
Closes #4556

```

## 4557 - medit problem in RTEMS6 (was 4.11/5.1)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4557">https://devel.rtems.org/ticket/4557</a> ( <a href="https://devel.rtems.org/ticket/4557">https://devel.rtems.org/ticket/4557</a> )
<b>Id</b>	4557
<b>Reporter</b>	chenjin_zhong
<b>Created</b>	2 December 2021 14:41:23
<b>Modified</b>	15 February 2023 21:00:22
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

Hi, I find when open medit editor in shell console, and then input `__CTRL+E/CTRL+X__` instructions in medit, the selected text cannot be cut. I review the code in `main_medit` file. First, when I input `__CTRL+E__` instruction, the function `select_toggle` is executed and selects the text. Second, when I input `__CTRL+X__`, the function `cut_selection` copies the selected text to clipboard, but after copy, the selected text is non-selected. Therefore, the `erase_selection` in `cut_selection` cannot take effect. the src code is listed as follows. I suggest that remove `__select_toggle__` in `__copy_selection__` function. and add after `__copy_selection__`. the code frament is marked in bold.

```
static void select_toggle(struct editor *ed) {
```

```
    ed->selecting = ed->selecting ? 0 : 1;
    update_selection(ed, ed->selecting);
    adjust(ed);
```

```
}
```

```
static void cut_selection(struct editor *ed) {
```

```
    copy_selection(ed);
    erase_selection(ed);
    select_toggle(ed);
```

```
}
```

```
static void copy_selection(struct editor *ed) {
```

```
    int selstart, selend;
    if (!get_selection(ed, &selstart, &selend)) return;
    ed->env->clipsize = selend - selstart;
    ed->env->clipboard = (unsigned char *) realloc(ed->env->clipboard, ed->env->clipsize);
    if (!ed->env->clipboard) return;
    copy(ed, ed->env->clipboard, selstart, ed->env->clipsize);
    select_toggle(ed);
```

```
}
```

```
__case ctrl('c'): copy_selection(ed); select_toggle; break;__
```

## Comment 1

1. **Joel Sherrill**, Thu, 02 Dec 2021 15:50:20 GMT

First I think you mean `main_edit.c` ([https://github.com/RTEMS/rtems/blob/master/cpukit/libmisc/shell/main\\_edit.c](https://github.com/RTEMS/rtems/blob/master/cpukit/libmisc/shell/main_edit.c))

Did you observe this on real hardware or a simulator? It is possible that the communications program (with hardware) or simulator is grabbing some characters.

It is also possible this is a bug. If this is the case, the code originated from <https://github.com/ringgaard/sanos/tree/master/src/utls/edit>. If it is a bug, we would like to work with the upstream to get it fixed and then update the code in RTEMS.

The code at the original repository can be compiled natively and you can check the behavior on that. The RTEMS derived version probably can be compiled similarly if that didn't get broken in the merge. Please try to follow up and let's see what is needed.

## Comment 2

1. **chenjin\_zhong**, Sun, 05 Dec 2021 13:34:32 GMT

Thank you! I have observed this on real hardware. then, I have checked <https://github.com/ringgaard/sanos/tree/master/src/utls/edit>. This Bug has been fixed. the code fragment is listed as follows. The `erase_selection` function is called by the `cut_selection` function and is able to delete selected characters.

```
void copy_selection(struct editor *ed) {
```

```
    int selstart, selend; if (!get_selection(ed, &selstart, &selend)) return; ed->env->clipsize = selend - selstart; ed->env->clipboard = (unsigned char *)
    realloc(ed->env->clipboard, ed->env->clipsize); if (!ed->env->clipboard) return; copy(ed, ed->env->clipboard, selstart, ed->env->clipsize);
```

```
}
```

```
void cut_selection(struct editor *ed) {
```

```
copy_selection(ed); erase_selection(ed);
```

```
}
```

**Comment 3**

1. **Chris Johns**, Thu, 10 Nov 2022 00:45:58 GMT
2. **summary**: changed from **medit problem in RTEMS4.11/5.1** to **medit problem in RTEMS6 (was 4.11/5.1)**
3. **version**: set to **6**
4. **milestone**: changed from **5.1** to **6.1**

This should check in 6.

**Comment 4**

1. **Chris Johns**, Tue, 29 Nov 2022 23:49:49 GMT
2. **owner**: set to **Chris Johns**
3. **status**: changed from **new** to **assigned**

**Comment 5**

1. **zack**, Wed, 15 Feb 2023 21:00:22 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 809e34e5/rtems:

```
libmisc/shell/main_edit.c: User cannot cut using ctrl e and x
Closes #4557
```

**4560 - Use thread-local storage for Newlib reentrancy objects**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4560">https://devel.rtems.org/ticket/4560</a> ( <a href="https://devel.rtems.org/ticket/4560">https://devel.rtems.org/ticket/4560</a> )
<b>Id</b>	4560
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	3 December 2021 09:04:00
<b>Modified</b>	11 October 2023 09:29:56
<b>Owner</b>	Sebastian Huber
<b>Type</b>	project
<b>Component</b>	tool/newlib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SoC, newlib, executive, large, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	4672

**Description**

Problem

The state of the art architectures supported by RTEMS have all efficient support for thread-local storage (MIPS has issues with thread-local storage, however, is MIPS state of the art?).

Newlib currently uses a huge object of type `struct _reent` to store thread-specific data. This object is returned by `__getreent()`. It is related to the `__DYNAMIC_REENT__` Newlib configuration option which is always defined for RTEMS.

The reentrancy structure contains `errno` and also the standard input, output, and error file streams. This means that if an application only uses `errno` it has a dependency on the file stream support event if it does not use it. This is an issue for lower end targets and the pre-qualification of RTEMS.

Solution

One approach to disentangle the dependencies introduced by `struct _reent` is to get rid of this structure and replace the individual members of the structure with thread-local objects. For example, instead of

```
struct _reent {
  int _errno;
  __FILE * _stdin;
  __FILE * _stdout;
  __FILE * _stderr;
};
```

use



```
Thread_local int _errno;
Thread_local FILE * _stdin;
Thread_local FILE * _stdout;
Thread_local FILE * _stderr;
```

Newlib already has access macros for the struct `_reent` members, for example:

```
#define _REENT_SIGNGAM(ptr) ((ptr)->_new._reent._gamma_signgam)
#define _REENT_RAND_NEXT(ptr) ((ptr)->_new._reent._rand_next)
#define _REENT_RAND48_SEED(ptr) ((ptr)->_new._reent._r48._seed)
#define _REENT_RAND48_MULT(ptr) ((ptr)->_new._reent._r48._mult)
#define _REENT_RAND48_ADD(ptr) ((ptr)->_new._reent._r48._add)
```

#### How-to Implement

The member access macros are incomplete. The first step is to use the Newlib configuration for RTEMS as is and rename all struct `_reent` members, for example add an `TEMPORARY` prefix to all member names, `_errno` to `TEMPORARY_errno`. Then add member access macros until Newlib builds again. Install this Newlib and check that RTEMS and libbsd compiles. Run the RTEMS and libbsd test suites to check for regressions.

In a second step to this for the `_REENT_SMALL` configuration of Newlib.

The third step is to add a new Newlib configuration option, for example `_REENT_THREAD_LOCAL` which turns the struct `_reent` members into thread-local objects with corresponding "member" access macros. Define `_REENT` to `NULL`.

#### Skills

C and assembly

#### Difficulty

This is a large (350-hour) project of hard difficulty.

#### Attachments:

---

1. **Sebastian Huber, Mon, 08 Aug 2022 11:00:15 GMT**

**attach:** set to [gcc-10-RTEMS-Use-local-exec-TLS-model-by-default.patch](https://devel.rtems.org/ticket/4560/gcc-10-RTEMS-Use-local-exec-TLS-model-by-default.patch) (<https://devel.rtems.org/ticket/4560/gcc-10-RTEMS-Use-local-exec-TLS-model-by-default.patch>)

2. **Sebastian Huber, Mon, 08 Aug 2022 11:00:32 GMT**

**attach:** set to [gcc-12-RTEMS-Use-local-exec-TLS-model-by-default.patch](https://devel.rtems.org/ticket/4560/gcc-12-RTEMS-Use-local-exec-TLS-model-by-default.patch) (<https://devel.rtems.org/ticket/4560/gcc-12-RTEMS-Use-local-exec-TLS-model-by-default.patch>)

---

#### Comment 1

1. **Joel Sherrill, Fri, 03 Dec 2021 17:29:59 GMT**

One issue with this is that TLS is not supported on all architectures. We would either have to have two methods (current and TLS) to do this or fix TLS everywhere.

#### Comment 2

1. **Sebastian Huber, Fri, 03 Dec 2021 19:20:33 GMT**

I am not sure what the Newlib maintainer say if we try to add a third reentrancy approach. I guess for backward compatibility they want to keep the existing methods anyway.

#### Comment 3

1. **Joel Sherrill, Fri, 03 Dec 2021 20:07:52 GMT**

2. **keywords:** SoC newlib added

#### Comment 4

1. **Chris Johns, Mon, 06 Dec 2021 08:19:37 GMT**

I would like to see libdl support for TLS added to RTEMS.

#### Comment 5

1. **Sebastian Huber, Fri, 28 Jan 2022 07:35:58 GMT**

In b519e50/rtems:

```
sptestests: Avoid a dependency on errno
```

Avoid a dependency on `errno` which might be a thread-local object. The tests `sp01`, `spstkalloc02`, and `sptls03` assume that no thread-local storage object is present.

```
Update #4560.
```

#### Comment 6

1. **Sebastian Huber, Fri, 28 Jan 2022 07:38:25 GMT**

Related discussion on libc-coord:

<https://www.openwall.com/lists/libc-coord/2022/01/21/1>

**Comment 7**

1. **Gedare Bloom**, Fri, 04 Feb 2022 18:54:45 GMT
2. **keywords: executive** added

**Comment 8**

1. **Gedare Bloom**, Fri, 25 Feb 2022 18:27:59 GMT
2. **keywords: large** added
3. **description:** modified (diff)

**Comment 9**

1. **Sebastian Huber**, Wed, 29 Jun 2022 09:04:57 GMT
2. **version:** changed from 7 to 6
3. **milestone:** changed from 7.1 to 6.1

**Comment 10**

1. **Sebastian Huber**, Wed, 29 Jun 2022 09:13:44 GMT
2. **blockedby:** set to 4672

**Comment 11**

1. **Matt Joyce**, Thu, 21 Jul 2022 05:15:04 GMT

In 57a569e/rtems:

```
sptestests: Disable Newlib reentrancy
Update #4560.
```

**Comment 12**

1. **Matt Joyce**, Thu, 21 Jul 2022 05:15:06 GMT

In 6d4b390/rtems:

```
Support _REENT_THREAD_LOCAL Newlib configuration
```

```
In case the Newlib REENT_THREAD_LOCAL configuration option is enabled, the struct _reent is not defined (there is only a forward declaration in ). Instead, the usual members of struct _reent are available as dedicated thread-local storage objects.
```

```
Update #4560.
```

**Comment 13**

1. **Sebastian Huber**, Thu, 21 Jul 2022 08:25:04 GMT

In ae6e598/rtems-source-builder:

```
6/7: Update Newlib
```

```
This makes the --enable-newlib-reent-thread-local (_REENT_THREAD_LOCAL_STORAGE) Newlib configuration option available.
```

```
Update #4560.
```

**Comment 14**

1. **Sebastian Huber**, Thu, 21 Jul 2022 08:25:05 GMT

In 958de50/rtems-source-builder:

```
newlib: Support --with/without-newlib-tls
```

```
This RSB option defines if the --enable-newlib-reent-thread-local (_REENT_THREAD_LOCAL_STORAGE) Newlib configuration option is used or not.
```

```
Update #4560.
```

**Comment 15**

1. **Sebastian Huber**, Thu, 21 Jul 2022 08:25:06 GMT

In f4f5d43/rtems-source-builder:

6/7: Use TLS in Newlib for some targets by default

Use the `--enable-newlib-reent-thread-local` (`_REENT_THREAD_LOCAL_STORAGE`) Newlib configuration option on the `aarch64`, `arm`, `nios2`, `powerpc`, `riscv`, and `sparc` targets by default.

Update #4560.

#### **Comment 16**

1. **Sebastian Huber**, Mon, 08 Aug 2022 18:23:20 GMT

In eea3793/rtems-source-builder:

6: Use local-exec TLS model by default

Update #4560.

#### **Comment 17**

1. **Sebastian Huber**, Fri, 09 Sep 2022 05:32:55 GMT

In 91e8654/rtems-docs:

user: Document RSB `--with/without-newlib-tls`

Update #4560.

#### **Comment 18**

1. **Sebastian Huber**, Fri, 14 Oct 2022 09:41:39 GMT

In b9212e2/rtems:

sptls01: Disable file system and Newlib reentrancy

Update #4560.

#### **Comment 19**

1. **Chris Johns**, Tue, 29 Nov 2022 22:38:23 GMT

Are we able to close this ticket?

#### **Comment 20**

1. **Sebastian Huber**, Wed, 30 Nov 2022 08:59:07 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

Yes, I recently were able to integrate the final patch for GCC 13. A follow up activity is #4765.

#### **Comment 21**

1. **Sebastian Huber**, Wed, 26 Apr 2023 05:14:33 GMT

In 908efe4/rtems-source-builder:

7: Use TLS in Newlib for m68k by default

Update #4560.

#### **Comment 22**

1. **Sebastian Huber**, Wed, 11 Oct 2023 09:29:56 GMT

2. **keywords**: **qualification** added

---

## **4566 - Atomic store does not use the order parameter for C++**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4566">https://devel.rtems.org/ticket/4566</a> ( <a href="https://devel.rtems.org/ticket/4566">https://devel.rtems.org/ticket/4566</a> )
<b>Id</b>	4566
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	7 December 2021 11:06:56
<b>Modified</b>	7 December 2021 11:25:05
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SMP, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This could result in invalid inline code for the SMP ticket locks if used from C++.

**Comment 1**

1. **Sebastian Huber**, Tue, 07 Dec 2021 11:07:12 GMT
2. **keywords: SMP qualification** added

**Comment 2**

1. **Sebastian Huber**, Tue, 07 Dec 2021 11:25:05 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 69d643f7/rtems:

```
score: Fix atomic stores for C++
```

```
Close #4566.
```

---

**4569 - aarch64 cache support does not provide rtems\_cache\_disable\_data()**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4569">https://devel.rtems.org/ticket/4569</a> ( <a href="https://devel.rtems.org/ticket/4569">https://devel.rtems.org/ticket/4569</a> )
<b>Id</b>	4569
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 December 2021 13:52:44
<b>Modified</b>	12 December 2021 17:58:14
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The aarch64 cache support defines:

```
bsps/aarch64/shared/cache/cache.c:#define CPU_CACHE_SUPPORT_PROVIDES_DISABLE_DATA
```

However, it does not provide `rtems_cache_disable_data()`.

**Comment 1**

1. **Kinsey Moore**, Fri, 10 Dec 2021 15:31:20 GMT

You are correct, while the AArch64 cache code provides `_CPU_cache_disable_data()`, it does not provide `rtems_cache_disable_data()`. I'll submit a patch to remove this define since the existing support via `_CPU_cache_disable_data` should be sufficient given that `CPU_DATA_CACHE_ALIGNMENT` is defined.

**Comment 2**

1. **Kinsey Moore**, Sun, 12 Dec 2021 17:58:14 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 68b0db35/rtems:

```
bsps/aarch64: Remove erroneous cache feature
```

The AArch64 cache implementation does not define `rtems_cache_disable_data()`, but declares that it does via `CPU_CACHE_SUPPORT_PROVIDES_DISABLE_DATA`. The existing implementation of `_CPU_cache_disable_data()` is sufficient to enable this functionality without the erroneous cache feature flag.

Closes #4569

## **4572 - Improve Clarity for New Clock Manager Directives**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4572">https://devel.rtems.org/ticket/4572</a> ( <a href="https://devel.rtems.org/ticket/4572">https://devel.rtems.org/ticket/4572</a> )
<b>Id</b>	4572
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	15 December 2021 22:27:35
<b>Modified</b>	26 January 2022 18:36:34
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

Looking through the Clock Manager at the new APIs, I noticed that there is nothing about what `bintime` and `sbintime` are in the "Time and Date Data Structures" section. Explaining what these time representations are is needed.

`struct timeval` and `timespec` are also not described in "Time and Data Data Structures" but this may be OK since they are from C and/or POSIX.

There is no discussion of what coarse is versus the non-coarse and what this means in practice.

There is no background on what the various clock sources are.

There may be other similar typos but `rtems_clock_get_monotonic()` describes its sole argument as being of the wrong type.

Without some background on the various time formats, sources, and terminology, the distinction between these APIs and their intended uses is impossible to figure out.

### **Comment 1**

1. **Sebastian Huber**, Thu, 16 Dec 2021 06:41:56 GMT

In 732d8bc/rtems-docs:

```
c-user: Fix Clock Manager parameter descriptions
```

Update #4572.

### **Comment 2**

1. **Sebastian Huber**, Thu, 16 Dec 2021 07:16:25 GMT
2. **keywords**: **qualification** added
3. **status**: changed from **assigned** to **accepted**

### **Comment 3**

1. **Sebastian Huber**, Thu, 16 Dec 2021 14:38:16 GMT

In 786b89a/rtems-docs:

```
c-user: Clarify time formats
```

Update #4572.

### **Comment 4**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Sebastian Huber**, Wed, 22 Dec 2021 07:11:55 GMT

In d404771/rtems:

```
rtems: Fix Clock Manager parameter descriptions
Update #4572.
```

#### **Comment 5**

1. **Sebastian Huber**, Tue, 11 Jan 2022 08:19:52 GMT

In e77e04d/rtems-docs:

```
c-user: Clarify Clock Manager dependencies
Update #4572.
```

#### **Comment 6**

1. **Sebastian Huber**, Wed, 26 Jan 2022 13:27:01 GMT

Joel, please close this issue or complain.

#### **Comment 7**

1. **Joel Sherrill**, Wed, 26 Jan 2022 18:36:34 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

I think it covers the concepts now.

## **4581 - Add AArch64 to Tier 1 BSPs**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4581">https://devel.rtems.org/ticket/4581</a> ( <a href="https://devel.rtems.org/ticket/4581">https://devel.rtems.org/ticket/4581</a> )
<b>Id</b>	4581
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	18 January 2022 16:08:13
<b>Modified</b>	25 January 2022 23:44:37
<b>Owner</b>	Kinsey Moore <kinsey.moore@...>
<b>Type</b>	task
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

I finally got around to producing an emailed test run on the Avnet ZU3EG development board. The test results are available here

#### **Comment 1**

1. **Kinsey Moore**, Wed, 19 Jan 2022 17:53:07 GMT
2. **owner**: set to **Kinsey Moore** <kinsey.moore@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In e0f9f8f/rtems-tools:

```
tiers: Add AArch64 to tier 1
Hardware test results have recently been posted for AArch64.
Closes #4581
```

#### **Comment 2**

1. **Joel Sherrill**, Tue, 25 Jan 2022 23:44:37 GMT

In 91a58af/rtems-tools:

```
rtems-bsps-tiers.ini: Move appropriate aarch64 BSPs to Tier 1 and 2
This also resulted in finding some BSPs listed which were no longer in the RTEMS source.
Updates #4581.
```

## **4583 - rtems-bsp-builder: Do not vary on network**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4583">https://devel.rtems.org/ticket/4583</a> ( <a href="https://devel.rtems.org/ticket/4583">https://devel.rtems.org/ticket/4583</a> )
<b>Id</b>	4583
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	20 January 2022 16:04:49
<b>Modified</b>	25 January 2022 23:44:33
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

With the network stack removed from the rtems.git repository, there is no need to build BSPs with and without networking. This should be removed. It should reduce the number of BSP build configurations in a run.

### **Comment 1**

1. **Joel Sherrill**, Thu, 20 Jan 2022 18:01:44 GMT
2. **owner:** changed from **Chris Johns** to **Joel Sherrill**

I'll take a swing at this while testing the tier updates.

### **Comment 2**

1. **Joel Sherrill**, Tue, 25 Jan 2022 23:44:33 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 519acfb/rtems-tools:

```
rtems-bsps-arm.ini, config/rtems-bsps.ini: Remove build variance on network
With the legacy TCP/IP stack no longer in rtems.git, there is nothing to turn on/off with regards to BSPs or the stack itself. Removing
this significantly reduces the number of configurations built.
Closes #4583.
```

## **4585 - Multiple Prototype Issues/Mismatches in rtems-examples from trace linker**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4585">https://devel.rtems.org/ticket/4585</a> ( <a href="https://devel.rtems.org/ticket/4585">https://devel.rtems.org/ticket/4585</a> )
<b>Id</b>	4585
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	24 January 2022 22:38:14
<b>Modified</b>	26 January 2022 18:29:01
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

This is some of the build failures in rtems-examples if the BSP has POSIX turned on:

```
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: hello-test.c:185:199: error: expected declaration specifiers or '...' before
'Thread_CPU_budget_algorithm_callout'
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: 185 | bool __wrap_Thread_Initialize(Objects_Information* a1, Thread_Control*
a2, const Scheduler_Control* a3, void* a4, size_t a5, bool a6, Priority_Control a7, bool a8, Thread_CPU_budget_algorithms a9,
Thread_CPU_budget_algorithm_callout a10, uint32_t a11, Objects_Name a12)
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: |
^~~~~~
error: compiling wrapper: Compiler error
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: hello-deep.c:1296:6: error: conflicting types for '_Thread_Start'
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: 1296 | bool _Thread_Start(Thread_Control* a1, const Thread_Entry_information*
a2, ISR_lock_Context* a3);
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: | ^~~~~~
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: In file included from hello-deep.c:30:
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: /home/joel/rtems-class/bsp-install/aarch64-
rtems6/xilinx_zynqmp_lp64_qemu/lib/include/rtems/score/threadimpl.h:279:16: note: previous declaration of '_Thread_Start' was here
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: 279 | Status_Control Thread_Start(
/home/joel/rtems-class/tools/bin/aarch64-rtems6-gcc: | Status_Control Thread_Start(
error: compiling wrapper: Compiler error
```

### Comment 1

1. Joel Sherrill, Wed, 26 Jan 2022 18:29:01 GMT
2. **owner:** set to Joel Sherrill <joel@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 75689781/rtems-tools:

```
linkers/rtems-score/thread*.ini: Remove symbols no longer present.
```

```
Close #4585.
```

## 4588 - RTEMS Stack Checker Report Bad Access When Not Enabled

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4588">https://devel.rtems.org/ticket/4588</a> ( <a href="https://devel.rtems.org/ticket/4588">https://devel.rtems.org/ticket/4588</a> )
<b>Id</b>	4588
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	26 January 2022 20:40:58
<b>Modified</b>	27 January 2022 18:59:40
<b>Owner</b>	Kinsey Moore <kinsey.moore@...>
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The RTEMS stack checker reporting function can be called without the stack checker infrastructure being enabled. This causes a bad access to 0x0 because the static interrupt stack checker data remains null instead of being initialized by `rtems_stack_checker_begin_extension`. The actual failure occurs in `Stack_check_Find_high_water_mark` while searching for `U32_PATTERN`.

This was found when the trailing D was left off of the `CONFIGURE_STACK_CHECKER_ENABLED` define in a test program.



Comment 1

1. **Kinsey Moore**, Thu, 27 Jan 2022 18:59:40 GMT
2. **owner**: set to **Kinsey Moore** <kinsey.moore@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In b539af8/rtems:

cpukit: Prevent error with disabled stack checker

When the stack checker is not enabled, the stack checker reporting function can still be called. This prevents that call from performing a null memory access in trying to find the high water mark if the stack checker was never initialized.

This also introduces a test to ensure this call does not cause a crash.

Closes #4588

4607 - support for SATA/AHCI drives

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4607">https://devel.rtems.org/ticket/4607</a> ( <a href="https://devel.rtems.org/ticket/4607">https://devel.rtems.org/ticket/4607</a> )
<b>Reporter</b>	ostyche
<b>Created</b>	11 February 2022 03:44:37
<b>Modified</b>	28 July 2022 06:40:44
<b>Owner</b>	
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	SATA
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Added support for SATA/AHCI drives. The relevant file path is \cpukit\sata\  
The files involved in the question were uploaded by git user ostyche who created a branch at 10:55 am on February 11, 2022

Comment 1

1. **Joel Sherrill**, Thu, 10 Mar 2022 16:33:46 GMT
2. **type**: changed from **defect** to **enhancement**
3. **version**: **4.11** deleted
4. **component**: changed from **admin** to **bsps**
5. **milestone**: changed from **5.1** to **6.1**

Can you provide a URL? If this was a pull on github, then it would be appreciated to get the patches submitted via the devel@ mailing list.

Comment 2

1. **Sebastian Huber**, Thu, 28 Jul 2022 06:40:44 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**

SATA support should be added through LibBSD.

4613 - Deprecate sparc64 port in rtems6 and remove in rtems7

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4613">https://devel.rtems.org/ticket/4613</a> ( <a href="https://devel.rtems.org/ticket/4613">https://devel.rtems.org/ticket/4613</a> )
<b>Id</b>	4613
<b>Reporter</b>	Gedare Bloom
<b>Created</b>	16 February 2022 20:17:36
<b>Modified</b>	9 February 2023 15:58:51
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	arch/sparc64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This port is no longer maintained. No one has been testing it and it does not appear to have any users.

Deprecate for RTEMS 6.x  
Remove in RTEMS 7.x

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:41:24 GMT

Please update <https://git.rtems.org/rtems-release/tree/rtems-notes-6.md> then close this ticket. please make a new ticket for the actual removal.

**Comment 2**

1. **Joel Sherrill**, Thu, 09 Feb 2023 15:58:51 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

<https://git.rtems.org/rtems-release/commit/?id=11aa44e068fe133ce088070cb1f5882b775a3e56>

---

**4614 - Deprecate sh port in rtems6 and remove in rtems7**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4614">https://devel.rtems.org/ticket/4614</a> ( <a href="https://devel.rtems.org/ticket/4614">https://devel.rtems.org/ticket/4614</a> )
<b>Id</b>	4614
<b>Reporter</b>	Gedare Bloom
<b>Created</b>	16 February 2022 20:18:11
<b>Modified</b>	9 February 2023 15:58:28
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	arch/sh
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This port is no longer maintained. No one has been testing it and it does not appear to have any users.

Deprecate for RTEMS 6.x  
Remove in RTEMS 7.x

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:42:33 GMT

Please update <https://git.rtems.org/rtems-release/tree/rtems-notes-6.md> then close this ticket. please make a new ticket for the actual removal.

**Comment 2**

1. **Joel Sherrill**, Thu, 09 Feb 2023 15:58:28 GMT
2. **status**: changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

<https://git.rtems.org/rtems-release/commit/?id=dffcad2c38d8328a66efda6a421aa7e39226afa3>

---

**4615 - Deprecate v850 port in rtems6 and remove in rtems7**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4615">https://devel.rtems.org/ticket/4615</a> ( <a href="https://devel.rtems.org/ticket/4615">https://devel.rtems.org/ticket/4615</a> )
<b>Id</b>	4615
<b>Reporter</b>	Gedare Bloom
<b>Created</b>	16 February 2022 20:19:06
<b>Modified</b>	9 February 2023 15:59:20
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	arch/v850
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This port is no longer maintained. No one has been testing it and it does not appear to have any users.

Deprecate for RTEMS 6.x  
Remove in RTEMS 7.x

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 22:42:43 GMT

Please update <https://git.rtems.org/rtems-release/tree/rtems-notes-6.md> then close this ticket. please make a new ticket for the actual removal.

**Comment 2**

1. **Joel Sherrill**, Thu, 09 Feb 2023 15:59:20 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

<https://git.rtems.org/rtems-release/commit/?id=d35d32f82182fd71bade181a09fbc9576d60116e>

---

**4617 - Potential non-monotonic CLOCK\_MONOTONIC**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4617">https://devel.rtems.org/ticket/4617</a> ( <a href="https://devel.rtems.org/ticket/4617">https://devel.rtems.org/ticket/4617</a> )
<b>Id</b>	4617
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	23 February 2022 08:52:16
<b>Modified</b>	23 February 2022 08:53:07
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The RTEMS timecounter implementation could lead to a non-monotonic CLOCK\_MONOTONIC if the clock interrupt is delayed for more than one second.

**Comment 1**

1. **Sebastian Huber**, Wed, 23 Feb 2022 08:53:07 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

This bug was fixed by 870cf9695f688c06743dd7fe8a7113e0cb5e3607.

---

## **4619 - riscv/rv32iac: minimum sample test fails to build**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4619">https://devel.rtems.org/ticket/4619</a> ( <a href="https://devel.rtems.org/ticket/4619">https://devel.rtems.org/ticket/4619</a> )
<b>Id</b>	4619
<b>Reporter</b>	Ryan Long
<b>Created</b>	23 February 2022 16:53:41
<b>Modified</b>	29 November 2022 23:52:49
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	worksforme
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	Hesham Almatary
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

This issue was found while investigating #4618. The specifics of the error are listed there.

### Comment 1

1. **Chris Johns**, Tue, 29 Nov 2022 23:52:49 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **worksforme**

BSP builder is showing this as working.

---

## **4627 - Multitasking start is broken on SMP targets which do not restore the interrupt state during context switching**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4627">https://devel.rtems.org/ticket/4627</a> ( <a href="https://devel.rtems.org/ticket/4627">https://devel.rtems.org/ticket/4627</a> )
<b>Id</b>	4627
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	8 March 2022 08:22:44
<b>Modified</b>	9 March 2022 20:01:37
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The current SMP multitasking start assumed that the initial heir thread of a processor starts execution in `_Thread_Handler()` which sets the interrupt state explicitly by `_ISR_Set_level()`. Under certain timing conditions processors may perform an initial context switch to a thread which already executes its thread body. In this case, interrupts are disabled after the context switch on targets which do not save/restore the interrupt state during a context switch (for example arm and riscv).

### Comment 1

1. **Sebastian Huber**, Tue, 08 Mar 2022 08:37:38 GMT

In b08ba92/rtems:

```
smptests/smpstart01: New test program
Update #4627.
```

### Comment 2

1. **Sebastian Huber**, Wed, 09 Mar 2022 20:01:37 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 32f0f11/rtems:

SMP: Fix start multitasking for some targets

The previous SMP multitasking start assumed that the initial heir thread of a processor starts execution in `_Thread_Handler()`. The `_Thread_Handler()` sets the interrupt state explicitly by `_ISR_Set_level()` before it calls the thread entry. Under certain timing conditions, processors may perform an initial context switch to a thread which already executes its thread body (see `smptests/smpstart01`). In this case, interrupts are disabled after the context switch on targets which do not save/restore the interrupt state during a context switch (aarch64, arm, and riscv).

Close #4627.

## **4629 - shell: Potential stack corruption in rtems\_shell\_init()**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4629">https://devel.rtems.org/ticket/4629</a> ( <a href="https://devel.rtems.org/ticket/4629">https://devel.rtems.org/ticket/4629</a> )
<b>Id</b>	4629
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 March 2022 06:11:06
<b>Modified</b>	18 March 2022 07:06:49
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The `rtems_shell_init()` passes the address of a stack variable (`exit_code`) to `rtems_shell_run()`. If `wait == false`, then the stack variable goes out of scope but may be accessed by the created shell thread.

### Comment 1

1. **Sebastian Huber**, Tue, 15 Mar 2022 06:11:35 GMT
2. **description**: modified (diff)

### Comment 2

1. **Sebastian Huber**, Fri, 18 Mar 2022 07:06:49 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In b837c83/rtems:

shell: Avoid potential stack corruption

The `rtems_shell_init()` passed the address of a stack variable (`exit_code`) to `rtems_shell_run()`. If `wait == false`, then the stack variable goes out of scope but may be accessed by the created shell thread.

The `rtems_shell_script()` was affected by the same problem.

Close #4629.

## **4631 - RSB fails to build gdb with Python 3.10 (and newer)**

Link	<a href="https://devel.rtems.org/ticket/4631">https://devel.rtems.org/ticket/4631</a> ( <a href="https://devel.rtems.org/ticket/4631">https://devel.rtems.org/ticket/4631</a> )
Id	4631
Reporter	Frank Kuehndel
Created	18 March 2022 12:09:33
Modified	26 April 2022 23:12:34
Owner	Chris Johns
Type	defect
Component	tool/gdb
Status	closed
Resolution	fixed
Version	6
Milestone	6.1
Priority	normal
Severity	normal
Keywords	
Cc	
Blocking	
Blocked by	

## Description

The rtems-source-builder fails to build the tools in a Fedora 35 container. I am building ARM for RTEMS 6 and get this error message:

```
config: tools/rtems-gdb-11.2.cfg
error: shell macro failed: /home/minna/src/rtems-source-builder/source-builder/sb/rtems-build-dep -c gcc -l : 2: error: no library
(-l) provided
Build Set: Time 0:00:33.396165
```

The same error appears for other architectures like AARCH64, POWERPC, RISC-V on Fedora 35. The source for this error is in file source-builder/config/gdb-common-1.cfg in line 118:

```
104 %ifnos darwin
105 %if %{host_ldflags} == %{nil}
106 %define gdb-host-libs %{nil}
107 %else
108 %define gdb-host-libs -L '%{host_ldflags}'
109 %endif
110 %if %{gdb-python-config} != %{nil}
111 %define gdb-python-lib-filter awk 'BEGIN{FS=" "}/python/{for(i=1;i 112 %if %{gdb-python-ver-mm} < 3.8
113 %define gdb-python-config-lib-check-flags --ldflags
114 %else
115 %define gdb-python-config-lib-check-flags --ldflags --embed
116 %endif
117 %define gdb-python-config-libs %{gdb-python-config} %{gdb-python-config-lib-check-flags} | %{gdb-python-lib-filter})
118 %define gdb-python-lib-check %{_smdir}/sb/rtems-build-dep -c %{_cc} %{gdb-host-libs} -l %{gdb-python-config-libs})
119 %else
120 %define gdb-python-lib-check %{_smdir}/sb/rtems-build-dep -c %{_cc} %{gdb-host-libs} -l %{gdb-python-ver-lib})
121 %endif
122 %if %{gdb-python-lib-check} == not-found && !%{ _rsb_getting_source}
123 %error "gdb: python: library file not found: %{gdb-python-ver-lib}, please install"
124 %endif
125 %endif
```

Some values of involved variables:

```
gdb-python-ver-mm = 3.10
gdb-python-config = /usr/bin/python3-config
gdb-python-config-lib-check-flags = --ldflags
gdb-python-lib-filter = awk 'BEGIN{FS=" "}/python/{for(i=1;igdb-python-config-libs = ''
```

The trouble is that gdb-python-config-libs is empty when line 118 gets called. It is empty because there is no python-library in the output of this call on Fedora 35:

```
$ /usr/bin/python3-config --ldflags
-L/usr/lib64 -lcrypt -ldl -lm -lm
```

Just to compare, on OpenSUSE 15.3 the same call returns (note the -lpython3.6m):

```
$ /usr/bin/python3-config --ldflags
-L/usr/lib64 -lpython3.6m -lpthread -ldl -lutil -lm -Xlinker -export-dynamic
```

Commenting out line 118 makes the build go through smoothly but I would prefer a permanent fix.

- Would be skipping line 118 when gdb-python-config-libs is empty be an appropriate solution?
- Is the "real" error in line 112? (%if 3.10 < 3.8 evaluates unexpectedly to true)
- Would the "error" in line 123 print out the correct library name?
- Does the whole check make sense when python3-config is obviously installed (both the command and the library are "usually" in the same pythonX-devel package)?

Notes:

- On Fedora 35 /usr/lib64/libpython3.10.so exists.
- On Fedora 35 adding --embed provides the library:

```
$ /usr/bin/python3-config --ldflags --embed
-L/usr/lib64 -lpython3.10 -lcrypt -ldl -lm -lm
```

For the records:

Command:

```
~/source-builder/sb-set-builder --rtems-version 6 --prefix /opt/rtems/6 --with_cxx --with_fortran --with_objc --jobs=12 --log
~/sb-set-builder.log 6/rtems-arm
```

```
RTEMS rtems-source-builder git: 6fe98f91d94bbf965bc0e78015585ff8823d17bd RTEMS: 6
Target architecture: ARM
Host architecture: x86_64
Host Kernel: 5.3.18-150300.59.49-default OS: Fedora Linux 35 (Container Image)
Container image base: docker.io/library/fedora:latest Python version in container: 3.10.2
Test date: 2022-03-18T11:02:10+01:00 rtems-source-builder/source-builder/sb-check log:
```

```
RTEMS Source Builder - Check, 6 (6fe98f91d94b modified)
warning: exe: absolute exe found in path: (_chown) /usr/sbin/chown
warning: exe: absolute exe found in path: (_install_info) /usr/bin/install-info
Environment is ok
```

**Comment 1**

1. **Frank Kuehndel**, Mon, 21 Mar 2022 14:31:11 GMT
2. **summary:** changed from **RSB fails to build gdb on Fedora 35** to **RSB fails to build gdb with Python 3.10 (and newer)**

**Comment 2**

1. **kgardas**, Thu, 21 Apr 2022 07:42:35 GMT
2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **assigned**

**Comment 3**

1. **Chris Johns**, Tue, 26 Apr 2022 23:12:33 GMT

In 4c3708f/rtems-source-builder:

```
sb: %if checks are numeric if the left and right values are numbers
If the left and right values are numbers make the check numeric.
Update #4631
```

**Comment 4**

1. **Chris Johns**, Tue, 26 Apr 2022 23:12:34 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 70f302e/rtems-source-builder:

```
gdb: Split python's version into major/minor and check for embed option
Closes #4631
```

**4632 - Error in rtems/thread.hpp with GCC 12**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4632">https://devel.rtems.org/ticket/4632</a> ( <a href="https://devel.rtems.org/ticket/4632">https://devel.rtems.org/ticket/4632</a> )
<b>Id</b>	4632
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	18 March 2022 13:59:22
<b>Modified</b>	19 March 2022 09:24:02
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

There is a compile error with GCC 12:

```
In file included from /home/EB/sebastian_h/src/rtems/cpukit/librtemscxx/thread.cpp:35:
/home/EB/sebastian_h/src/rtems/cpukit/include/rtems/thread.hpp:449:14: error: redefinition of default argument for 'class'
 449 |         class = thread::enable_if_attributes>
      |         ^~~~~
/home/EB/sebastian_h/src/rtems/cpukit/include/rtems/thread.hpp:312:17: note: original definition appeared here
 312 |         class = enable_if_attributes>
      |         ^~~~~
```

**Comment 1**

1. **Sebastian Huber**, Sat, 19 Mar 2022 09:24:02 GMT
2. **status:** changed from **assigned** to **closed**

3. **resolution: set to fixed**

In 7fe3c62/rtems:

```
thread.hpp: Fix redefinition of default argument
A default argument shall be defined only once.
Close #4632.
```

**4634 - Fix hash for glib-2.48**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4634">https://devel.rtems.org/ticket/4634</a> ( <a href="https://devel.rtems.org/ticket/4634">https://devel.rtems.org/ticket/4634</a> )
<b>Id</b>	4634
<b>Reporter</b>	Ryan Long
<b>Created</b>	24 March 2022 15:15:31
<b>Modified</b>	23 January 2023 20:49:08
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The hash needs updated in order for glib to be built. This is currently preventing

**Attachments:**

- 
- Ryan Long, Thu, 24 Mar 2022 15:16:13 GMT**  
**attach:** set to 0001-devel-glib-2.48-Update-hash.patch (<https://devel.rtems.org/ticket/4634/0001-devel-glib-2.48-Update-hash.patch>)
  - Ryan Long, Thu, 24 Mar 2022 20:51:50 GMT**  
**attach:** set to 566e1d61a500267c7849ad0b2552feec9c9a29a6\_patch ([https://devel.rtems.org/ticket/4634/566e1d61a500267c7849ad0b2552feec9c9a29a6\\_patch](https://devel.rtems.org/ticket/4634/566e1d61a500267c7849ad0b2552feec9c9a29a6_patch))
- 

**Comment 1**

- Ryan Long, Thu, 24 Mar 2022 20:49:58 GMT**

This is currently preventing QEMU from being built. The hash of the patch changed for some unknown reason. Therefore, we are going to store a copy of that patch here so that it doesn't change. This patch will then be pulled down and applied in place of where it was originally done. The hash of the patch will still have to be updated, but hopefully this will prevent it from happening again.

**Comment 2**

- Ryan Long, Fri, 25 Mar 2022 19:01:59 GMT**

In 49e3dac/rtems-source-builder:

```
devel/glib-2.48: Update hash and patch
Changes patch to be pulled from an RTEMS ticket and updated the hash of the patch.
Updates #4634
```

**Comment 3**

- Chris Johns, Tue, 29 Nov 2022 23:53:25 GMT**

Status update?

**Comment 4**

- Joel Sherrill, Wed, 28 Dec 2022 17:45:56 GMT**

Looks like it got committed with "updates" not "closes"

**Comment 5**

- Gedare Bloom, Mon, 23 Jan 2023 20:49:08 GMT**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



2. **status:** changed from **new** to **closed**
  3. **resolution:** set to **fixed**
- 

## 4635 - untar on JFFS slow down

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4635">https://devel.rtems.org/ticket/4635</a> ( <a href="https://devel.rtems.org/ticket/4635">https://devel.rtems.org/ticket/4635</a> )
<b>Id</b>	4635
<b>Reporter</b>	Chris Johns
<b>Created</b>	29 March 2022 05:27:34
<b>Modified</b>	5 April 2022 21:52:37
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	fs/jffs2
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Using untar on JFFS is slower on rtems 6 compared to 4.11. The application writes files to the flash disk from an in memory tarfile and the difference is easy to see for 10M or so of files.

I reviewed the changes to JFFS in rtems 6 and they look OK so it is not a regression the libfs. I also timed the flash driver and it is the same on 6 as 4.11.

I noticed on 6 there is a lot more blocks being written at the flash driver level compared to 4.11. Looking at untar I see the block size written is 512 bytes and with compression this results in a lot of small blocks. Changing the untar block write size to 8K speeds returns the performance.

I am not sure why there are more blocks on 6. A guess is the compression is better, which is nice. I will not look into this any more than changing untar to use 8K blocks.

### Comment 1

1. **Chris Johns**, Tue, 05 Apr 2022 21:52:37 GMT
2. **owner:** set to **Chris Johns <chrisj@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 500e6963/rtems:

```
libmisc/untar: Use a larger block size to read and write files
A larger block size lets files systems work better. On JFFS
a 512 byte compressed block means lots of small flash updates
Closes #4635
```

---

## 4639 - Error in imfs memfile when device is full

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4639">https://devel.rtems.org/ticket/4639</a> ( <a href="https://devel.rtems.org/ticket/4639">https://devel.rtems.org/ticket/4639</a> )
<b>Id</b>	4639
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	4 April 2022 13:31:12
<b>Modified</b>	7 April 2022 08:27:37
<b>Owner</b>	Christian Mauderer
<b>Type</b>	defect
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Cloned from #4638:

The problem from #2353 still exists in 5 and 6:

Original description:

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

From the reporter (Круглов Сергей):

- First bug I detect with attempt write file to full device (zero empty blocks).
- And after I send too many files, disk overflow and system not responding (receive and write to disk have high priority). A test, and found block=0, after -- = too big value.
- In imfs\_memfile.c

function IMFS\_memfile\_extend  
block declared: unsigned int block, and after block— work incorrect (if block = 0).  
for ( ; block>=old\_blocks ; block-- ) {

```
IMFS_memfile_remove_block( memfile, block );
```

```
}  
Must be declare int block;
```

#### Comment 1

1. **Christian Mauderer**, Thu, 07 Apr 2022 08:27:37 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 43119193/rtems:

imfs: Fix index underrun when extending empty file

Currently the following sequence causes a endless loop when extending an IMFS file:  
Create a file with zero length and close it. Make sure nearly no allocatable memory is left. Open the file and write enough data into it that more than the remaining memory will be used.  
In that case when extending the IMFS file, the file currently need zero blocks. If allocating enough new blocks fails, the already allocated new blocks will be freed again.

The comparison of block>=old\_blocks that has been used prior to this patch compared two unsigned numbers. If old\_blocks was zero, the comparison of these two numbers always evaluated to true.

This patch frees the last block in a separate step to avoid this problem.

Fixes #4639

## 4641 - x86\_64 elf\_machdep header file missing body

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4641">https://devel.rtems.org/ticket/4641</a> ( <a href="https://devel.rtems.org/ticket/4641">https://devel.rtems.org/ticket/4641</a> )
<b>Id</b>	4641
<b>Reporter</b>	Ryan Long
<b>Created</b>	7 April 2022 12:59:03
<b>Modified</b>	8 April 2022 13:25:41
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	arch/x86_64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The elf\_machdep header file is missing the body under cpukit/score/cpu/x86\_64/include/machine.

Joel found the code that needed to be put in at [http://cvsweb.netbsd.org/bsdweb.cgi/src/sys/arch/amd64/include/elf\\_machdep.h](http://cvsweb.netbsd.org/bsdweb.cgi/src/sys/arch/amd64/include/elf_machdep.h).

#### Comment 1

1. **Ryan Long**, Fri, 08 Apr 2022 13:25:41 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 5efcd021/rtems:

x86\_64/elf\_machdep.h: Replace stub with NetBSD version

The other ports included that architecture's version of this file from NetBSD. This patch follows that pattern.

closes #4641

**4644 - wkspc "failed allocations" increase with heap protection enabled (cloned)**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4644">https://devel.rtems.org/ticket/4644</a> ( <a href="https://devel.rtems.org/ticket/4644">https://devel.rtems.org/ticket/4644</a> )
<b>Id</b>	4644
<b>Reporter</b>	Matthew J Fletcher
<b>Created</b>	28 April 2022 06:52:10
<b>Modified</b>	28 April 2022 07:13:22
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	low
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	joel@...
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4643:

Investigating the "Total number of failed allocations:" from the wkspc cmd i see that;

```
/* Statistics */
++stats->failed_allocs;
```

Are incremented when `_Heap_Allocate_aligned_with_boundary` fails, however it seems this will routinely fail due to;

`_Heap_Protection_free_all_delayed_blocks` seemingly on purpose creating an impossibly large allocation.

```
uintptr_t large = 0
```

- (uintptr\_t) HEAP\_BLOCK\_HEADER\_SIZE
- (uintptr\_t) HEAP\_ALLOC\_BONUS
- (uintptr\_t) 1;

```
void *p = _Heap_Allocate( heap, large );
```

This makes it difficult to place a breakpoint on `failed_allocs` to investigate true low memory situations with heap protection enabled.

**Comment 1**

1. **Sebastian Huber**, Thu, 28 Apr 2022 07:13:22 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 8b18037f/rtems:

```
heap: Fix heap statistics with protection enabled
Close #4644.
```

**4646 - Control buildsets using the --with-`&#42` command line option**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4646">https://devel.rtems.org/ticket/4646</a> ( <a href="https://devel.rtems.org/ticket/4646">https://devel.rtems.org/ticket/4646</a> )
<b>Id</b>	4646
<b>Reporter</b>	Chris Johns
<b>Created</b>	5 May 2022 01:03:50
<b>Modified</b>	5 May 2022 22:03:49
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The following thread has raise an important issue on how we can test newer versions of tools. This ticket is about providing a solution:

<https://lists.rtems.org/pipermail/devel/2022-May/071458.html>

The solution is allow users to specific a tool set on the command line for a build of tools. The standard option is `--with-*`. For example a command line could be:

```
../source-builder/sb-set-builder \
  --prefix=/opt/rtems/6 \
  --log=arm.txt \
  --with-rtems-gcc=tools/rtems-gcc-head-newlib-head \
  6/rtems-arm
```

The buildset logic is to be changed to expand macros for buildset file names and to add a new buildset specific keyword `%defineifnot`. The tools default file becomes:

```
#
# Default tools configuration.
#
#include 6/rtems-base.bset
#
# Default RTEMS build. Override on the command line to the
# the RSB. For example to test the latest versino of gcc use:
#
# --with-rtems-gcc=tools/rtems-gcc-head-newlib-head
#
#defineifnot with_rtems_dtc      devel/dtc-1.6.1-1
#defineifnot with_rtems_expat   devel/expat-2.4.8-1
#defineifnot with_rtems_gmp     devel/gmp-6.2.1
#defineifnot with_rtems_gdb     tools/rtems-gdb-11.2
#defineifnot with_rtems_binutils tools/rtems-binutils-2.38
#defineifnot with_rtems_gcc     tools/rtems-gcc-10-newlib-head
#defineifnot with_rtems_tools   tools/rtems-tools-6
#
# Build gdb first to raise the Python install error as early as
# possible.  GDB needs expat so it needs to be built before.
#
%{with_rtems_dtc}
%{with_rtems_expat}
%{with_rtems_gmp}
%{with_rtems_gdb}
%{with_rtems_binutils}
%{with_rtems_gcc}
%{with_rtems_tools}
```

This approach lets cron based CI flows configure a build with the latest gcc, binutils etc so they can always be tested as a workflow.

The new keyword lets a define in a nested buildset file override a command line value. That may be needed.

**Comment 1**

1. **Chris Johns**, Thu, 05 May 2022 22:03:49 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 7d80719/rtems-source-builder:

```
sb/setbuilder: Control buildsets using the --with-* command line option
Expand macros in buildset file names Add support to buildsets for %defineifnot Update 6 and 7 to support command line build overrides
Closes #4646
```

**4648 - Documentation Needs to Use Version Variables not Hard-Coded Numbers**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4648">https://devel.rtems.org/ticket/4648</a> ( <a href="https://devel.rtems.org/ticket/4648">https://devel.rtems.org/ticket/4648</a> )
<b>Id</b>	4648
<b>Reporter</b>	Chris Johns
<b>Created</b>	8 May 2022 11:11:42
<b>Modified</b>	22 June 2023 21:57:22
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	user manual doc
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

This ticket is to track all the documentation changes for the RTEMS 6 releases.

**Comment 1**

1. **Chris Johns**, Sun, 08 May 2022 11:18:31 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

Update the build system to support substitution in areas of the text with:

@rtems-version@ @rtems-ver-major@ @rtems-ver-minor@ @rtems-ver-revision@

The support allows the source to contain in any area:

```
$ sparc-rtems@rtems-ver-major@gdb app.exe
```

#### **Comment 2**

1. **Chris Johns**, Sun, 08 May 2022 11:20:39 GMT

Topaz Hypervisor Guest

Update to waf configure

<https://docs.rtems.org/branches/master/user/bsps/bsps-powerpc.html#topaz-hypervisor-guest>

#### **Comment 3**

1. **Chris Johns**, Sun, 08 May 2022 11:22:58 GMT

RISC-V

No configure command line with waf.

<https://docs.rtems.org/branches/master/user/bsps/bsps-riscv.html#build-configuration-options>

#### **Comment 4**

1. **Chris Johns**, Sun, 08 May 2022 11:25:57 GMT

x86\_64

Configure options

[https://docs.rtems.org/branches/master/user/bsps/bsps-x86\\_64.html#build-configuration-options](https://docs.rtems.org/branches/master/user/bsps/bsps-x86_64.html#build-configuration-options)

#### **Comment 5**

1. **Chris Johns**, Mon, 09 May 2022 11:45:45 GMT

The use of `.. include::` in the nested `index.rst` files breaks the parsing of Sphinx. I have discovered the read in source that passes through the source-read hook is not in the some of the generated HTML pages. I cannot tell if this is a bug in Sphinx, the theme or something else but using the `.. toctree::` works.

We need to change the use includes and update the README.txt.

#### **Comment 6**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:01:23 GMT
2. **summary**: changed from **User manual documentation updates** to **User manual documentation updates for RTEMS 6 release**

#### **Comment 7**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:56:19 GMT

We need to use this extension:

<https://github.com/adamtheturtle/sphinx-substitution-extensions>

And then a documentation working session to switch the hard-coded versions and lengthy version specific output. Also remove the current hacked [per Chris :) ] solution.

#### **Comment 8**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:57:22 GMT
2. **summary**: changed from **User manual documentation updates for RTEMS 6 release** to **Documentation Needs to Use Version Variables not Hard-Coded Numbers**

---

## **4650 - tcpdump: Fix dumping to file and reading from file (cloned)**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4650">https://devel.rtems.org/ticket/4650</a> ( <a href="https://devel.rtems.org/ticket/4650">https://devel.rtems.org/ticket/4650</a> )
<b>Id</b>	4650
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2022 06:44:34
<b>Modified</b>	12 May 2022 05:44:39
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

Cloned from #4649:

When dumping to file, the file needs to be closed at program exit. When reading from file, we do not need the loop monitor. Do not use signals, since they are not cleaned up at program exit.

#### Comment 1

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:43 GMT

In a4c3d74/rtems-libbsd:

```
tcpdump01: New test
Update #4650.
```

#### Comment 2

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:44 GMT

In 7bc7bae/rtems-libbsd:

```
Add program destructor support
Update #4650.
```

#### Comment 3

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:46 GMT

In bd2201b/rtems-libbsd:

```
tcpdump: Make loop monitor cooperative
This helps a bit if the fgetc() is non-blocking.
Update #4650.
```

#### Comment 4

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:47 GMT

In face369/rtems-libbsd:

```
tcpdump: Use rtems_task_exit()
Update #4650.
```

#### Comment 5

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:49 GMT

In 869cb1a/rtems-libbsd:

```
tcpdump: Close pcap dumper at program exit
Update #4650.
```

**Comment 6**

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:50 GMT

In 70c9ac2/rtems-libbsd:

```
tcpdump: No loop monitor if reading from file
Update #4650.
```

**Comment 7**

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:51 GMT

In 45dfdc1/rtems-libbsd:

```
tcpdump: Ensure loop monitor termination
Update #4650.
```

**Comment 8**

1. **Sebastian Huber**, Thu, 12 May 2022 05:41:53 GMT

In 584dd8d/rtems-libbsd:

```
tcpdump: Do not use signals and chroot
Update #4650.
```

**Comment 9**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:15 GMT

In 544ba25/rtems-libbsd:

```
tcpdump01: New test
Update #4650.
```

**Comment 10**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:19 GMT

In c621252/rtems-libbsd:

```
Add program destructor support
Update #4650.
```

**Comment 11**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:22 GMT

In 479b4de/rtems-libbsd:

```
tcpdump: Make loop monitor cooperative
This helps a bit if the fgetc() is non-blocking.
Update #4650.
```

**Comment 12**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:26 GMT

In 6fb7134/rtems-libbsd:

```
tcpdump: Use rtems_task_exit()
Update #4650.
```

**Comment 13**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:29 GMT

In 011f489/rtems-libbsd:

```
tcpdump: Close pcap dumper at program exit
Update #4650.
```

**Comment 14**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:33 GMT

In c9b44ba/rtems-libbsd:

```
tcpdump: No loop monitor if reading from file
Update #4650.
```

**Comment 15**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:36 GMT

In 32ebbd3/rtems-libbsd:

```
tcpdump: Ensure loop monitor termination
Update #4650.
```

**Comment 16**

1. **Sebastian Huber**, Thu, 12 May 2022 05:44:39 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 5ad77a9/rtems-libbsd:

```
tcpdump: Do not use signals and chroot
Close #4650.
```

**4652 - if\_atsam: Fix checksum offload, add multicast and VLAN support (cloned)**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4652">https://devel.rtems.org/ticket/4652</a> ( <a href="https://devel.rtems.org/ticket/4652">https://devel.rtems.org/ticket/4652</a> )
<b>Id</b>	4652
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2022 06:48:48
<b>Modified</b>	1 June 2022 07:53:46
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4651:

The if\_atsam network interface driver has several issues. Do not disable the FCS if the checksum offload is disabled. Make sure the interface capabilities are enabled. Add multicast and VLAN support. Use the interface transmit method instead of the interface start approach. Correct a potential receive starvation error. Fix the interface up/down.

**Comment 1**

1. **Sebastian Huber**, Wed, 11 May 2022 13:53:53 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



In 2556c4c/rtems-libbsd:

```
if_atsam: Fix warnings
Update #4652.
```

### **Comment 2**

1. **Sebastian Huber**, Wed, 11 May 2022 13:53:54 GMT

In 7e082f6/rtems-libbsd:

```
if_atsam: Enable all capabilities
Update #4652.
```

### **Comment 3**

1. **Sebastian Huber**, Wed, 11 May 2022 13:53:55 GMT

In adda3a5/rtems-libbsd:

```
if_atsam: Do not disable the Ethernet CRC
The Ethernet CRC and padding must be always generated by the MAC.
Update #4652.
```

### **Comment 4**

1. **Sebastian Huber**, Wed, 11 May 2022 13:53:57 GMT

In 975916a/rtems-libbsd:

```
if_atsam: Fix interrupt setup
The interrupt is enabled by rtems_interrupt_handler_install().
Update #4652.
```

### **Comment 5**

1. **Sebastian Huber**, Wed, 11 May 2022 13:53:58 GMT

In 1230011/rtems-libbsd:

```
if_atsam: Fix start/stop of interface
Update #4652.
```

### **Comment 6**

1. **Sebastian Huber**, Wed, 11 May 2022 13:53:59 GMT

In c944cb9/rtems-libbsd:

```
if_atsam: Add multicast support
Update #4652.
```

### **Comment 7**

1. **Sebastian Huber**, Wed, 11 May 2022 13:54:01 GMT

In 2cb974f/rtems-libbsd:

```
if_atsam: Optimize transmit
Use the transmit interface handler to avoid a transmit task/interrupt. Use a compile-time constant for the transmit DMA descriptor count to simplify calculations.
Update #4652.
```

### **Comment 8**

1. **Sebastian Huber**, Wed, 11 May 2022 13:54:02 GMT

In 967613f/rtems-libbsd:

```
if_atsam: Optimize receive
```

Do not use the interface mutex in the receive loop. Avoid multiple reads of DMA descriptor words. Use a compile-time constant for the receive DMA descriptor count to simplify calculations.

```
Update #4652.
```

#### **Comment 9**

1. **Sebastian Huber**, Wed, 11 May 2022 13:54:03 GMT

In 821bcb7/rtems-libbsd:

```
if_atsam: Support IFCAP_VLAN_HWTAGGING
```

This is required to enable checksum offload for vlan interfaces.

```
Update #4652.
```

#### **Comment 10**

1. **Sebastian Huber**, Wed, 11 May 2022 13:54:05 GMT

In 989675e/rtems-libbsd:

```
if_atsam: Do not use rtems_bsdnet_newproc()
```

```
Update #4652.
```

#### **Comment 11**

1. **Sebastian Huber**, Wed, 11 May 2022 13:54:06 GMT

In 4ad0961/rtems-libbsd:

```
if_atsam: Support transmit bpf
```

```
Update #4652.
```

#### **Comment 12**

1. **Sebastian Huber**, Wed, 11 May 2022 13:54:07 GMT

In e992d45/rtems-libbsd:

```
if_atsam: Fix interface stop
```

```
Update #4652.
```

#### **Comment 13**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:46 GMT

In 73c764a/rtems-libbsd:

```
if_atsam: Fix warnings
```

```
Update #4652.
```

#### **Comment 14**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:48 GMT

In c58bb60/rtems-libbsd:

```
if_atsam: Enable all capabilities
```

```
Update #4652.
```

#### **Comment 15**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:49 GMT

In 5b62a8b/rtems-libbsd:

```
if_atsam: Do not disable the Ethernet CRC
The Ethernet CRC and padding must be always generated by the MAC.
Update #4652.
```

#### **Comment 16**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:50 GMT

In 339ba3d/rtems-libbsd:

```
if_atsam: Fix interrupt setup
The interrupt is enabled by rtems_interrupt_handler_install().
Update #4652.
```

#### **Comment 17**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:51 GMT

In f4efcbf/rtems-libbsd:

```
if_atsam: Fix start/stop of interface
Update #4652.
```

#### **Comment 18**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:53 GMT

In 3150b37/rtems-libbsd:

```
if_atsam: Add multicast support
Update #4652.
```

#### **Comment 19**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:54 GMT

In 6be24bd/rtems-libbsd:

```
if_atsam: Optimize transmit
Use the transmit interface handler to avoid a transmit task/interrupt. Use a compile-time constant for the transmit DMA descriptor count to simplify calculations.
Update #4652.
```

#### **Comment 20**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:55 GMT

In 62fc2b6/rtems-libbsd:

```
if_atsam: Optimize receive
Do not use the interface mutex in the receive loop. Avoid multiple reads of DMA descriptor words. Use a compile-time constant for the receive DMA descriptor count to simplify calculations.
Update #4652.
```

#### **Comment 21**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:56 GMT

In 202502a/rtems-libbsd:

```
if_atsam: Support IFCAP_VLAN_HWTAGGING
This is required to enable checksum offload for vlan interfaces.
```

Update #4652.

#### **Comment 22**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:58 GMT

In 5c4ac7a/rtems-libbsd:

```
if_atsam: Do not use rtems_bsdnet_newproc()
```

Update #4652.

#### **Comment 23**

1. **Sebastian Huber**, Wed, 11 May 2022 14:01:59 GMT

In 8039d70/rtems-libbsd:

```
if_atsam: Support transmit bpf
```

Update #4652.

#### **Comment 24**

1. **Sebastian Huber**, Wed, 11 May 2022 14:02:00 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 38e1610/rtems-libbsd:

```
if_atsam: Fix interface stop
```

Close #4652.

#### **Comment 25**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:52:38 GMT

In 07e2820/rtems-libbsd:

```
if_atsam: Allow stats reset via sysctl
```

Update #4652.

#### **Comment 26**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:52:39 GMT

In 683bae9/rtems-libbsd:

```
if_atsam: Add register sysctls
```

Update #4652.

#### **Comment 27**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:52:40 GMT

In bd56cb2/rtems-libbsd:

```
if_atsam: Add tx/rx desc sysctls
```

Update #4652.

#### **Comment 28**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:52:42 GMT

In 8588e95/rtems-libbsd:

if\_atsam: Shorten sysctl names

Update #4652.

### **Comment 29**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:52:43 GMT

In 61f646d/rtems-libbsd:

if\_atsam: Recover from receive freezes

Under unknown conditions the receive path ended up in a frozen state. In this state, the DMA and driver descriptor head were equal and all receive descriptors had the used bit set. So, the DMA was unable to store received frames. However, the receive daemon was never woken up to refill the receive buffers. It seems that the RXUBR interrupt can be used to recover from this state.

Update #4652.

### **Comment 30**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:53:41 GMT

In 5650e92/rtems-libbsd:

if\_atsam: Allow stats reset via sysctl

Update #4652.

### **Comment 31**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:53:42 GMT

In eb58e82/rtems-libbsd:

if\_atsam: Add register sysctls

Update #4652.

### **Comment 32**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:53:43 GMT

In 1ed12b8/rtems-libbsd:

if\_atsam: Add tx/rx desc sysctls

Update #4652.

### **Comment 33**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:53:45 GMT

In eea3f0e/rtems-libbsd:

if\_atsam: Shorten sysctl names

Update #4652.

### **Comment 34**

1. **Sebastian Huber**, Wed, 01 Jun 2022 07:53:46 GMT

In 9e87868/rtems-libbsd:

if\_atsam: Recover from receive freezes

Under unknown conditions the receive path ended up in a frozen state. In this state, the DMA and driver descriptor head were equal and all receive descriptors had the used bit set. So, the DMA was unable to store received frames. However, the receive daemon was never woken up to refill the receive buffers. It seems that the RXUBR interrupt can be used to recover from this state.

Update #4652.

---

## **4654 - pfctl: Fix global state initialization (cloned)**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4654">https://devel.rtems.org/ticket/4654</a> ( <a href="https://devel.rtems.org/ticket/4654">https://devel.rtems.org/ticket/4654</a> )
<b>Id</b>	4654
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 May 2022 11:37:24
<b>Modified</b>	13 May 2022 06:53:13
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

Cloned from #4653:

The last update introduced a static variable in `get_query_socket()` which was not initialized.

#### Comment 1

1. **Sebastian Huber**, Wed, 11 May 2022 13:17:11 GMT

In c9696eb/rtems-libbsd:

```
pf02: Fix shell environmnet initialization
Update #4654.
```

#### Comment 2

1. **Sebastian Huber**, Wed, 11 May 2022 13:17:13 GMT

In 435b298/rtems-libbsd:

```
pfctl: Fix global state initialization
Update #4654.
```

#### Comment 3

1. **Sebastian Huber**, Wed, 11 May 2022 13:19:09 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 211c5ed/rtems-libbsd:

```
pf02: Fix shell environmnet initialization
Close #4654.
```

#### Comment 4

1. **Sebastian Huber**, Fri, 13 May 2022 06:53:13 GMT

In ae635eb/rtems-libbsd:

```
pfctl: Fix global state initialization
Update #4654.
```

---

### **4656 - sync() whould synchronize all file descriptors (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4656">https://devel.rtems.org/ticket/4656</a> ( <a href="https://devel.rtems.org/ticket/4656">https://devel.rtems.org/ticket/4656</a> )
<b>Id</b>	4656
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	13 May 2022 10:58:51
<b>Modified</b>	17 May 2022 13:20:31
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Cloned from #4655:

According to POSIX

<https://pubs.opengroup.org/onlinepubs/9699919799/functions/sync.html>

we have

```
The sync() function shall cause all information in memory that updates file systems to be scheduled for writing out to all file systems.
```

Currently, the RTEMS sync() implementation synchronizes only the file descriptors associated with a FILE object. This should be changed to call fsync() and fdatasync() for all file descriptors.

### Comment 1

1. **Sebastian Huber**, Tue, 17 May 2022 13:20:31 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3ccfb583/rtems:

```
Synchronize all file descriptors in sync()
```

```
Synchronize all file descriptors and not just the ones associated with a FILE object.
```

```
Close #4656.
```

## 4658 - Fix build issue with riscv sample test

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4658">https://devel.rtems.org/ticket/4658</a> ( <a href="https://devel.rtems.org/ticket/4658">https://devel.rtems.org/ticket/4658</a> )
<b>Id</b>	4658
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 May 2022 17:40:10
<b>Modified</b>	29 November 2022 23:55:04
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	arch/riscv
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

When trying to build the minimum sample test for any RISC-V BSP, the following error occurs.

```
start.o: in function .L0:
/home/tester/rtems-cron-6/rtems/build/riscv/rv32i/../../../../bsps/riscv/shared/start/start.S:84:(.bsp_start_text+0x2c): relocation truncated to fit: R_RISCV_GPREL_I against symbol 'bsp_section_bss_size' defined in *ABS* section in /home/tester/rtems-cron-6/rtems/build/riscv/rv32i/testsuites/samples/minimum.exe
collect2: error: ld returned 1 exit status
```

### Comment 1

1. **Sebastian Huber**, Wed, 18 May 2022 06:26:58 GMT

<file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html>

I cannot reproduce this issue on my development machines. It could be an issue in the linker. I would run the linker in GDB and try to debug it to figure out what is going on.

### Comment 2

1. **Sebastian Huber**, Fri, 28 Oct 2022 11:53:25 GMT

In 89ba2a98/rtems:

```
bsps/riscv: Workaround for sporadic linker issues

Disable the linker relaxation in start.S to work around an issue described here:
https://mail.gnu.org/archive/html/bug-binutils/2021-03/msg00164.html

The real issue is probably in the linker command file or the linker itself.

Update #4658.
```

### Comment 3

1. **Sebastian Huber**, Fri, 04 Nov 2022 12:50:15 GMT

In b4ffaa7c/rtems:

```
bsps/riscv: Use start data for object

Maybe this helps to ensure that the object is properly aligned.

Update #4658.
```

### Comment 4

1. **Chris Johns**, Tue, 29 Nov 2022 23:55:04 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **fixed**

## 4661 - GCC 12 generates wrong code

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4661">https://devel.rtems.org/ticket/4661</a> ( <a href="https://devel.rtems.org/ticket/4661">https://devel.rtems.org/ticket/4661</a> )
<b>Id</b>	4661
<b>Reporter</b>	Chris Johns
<b>Created</b>	8 June 2022 03:45:09
<b>Modified</b>	19 July 2022 06:02:18
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	tool/gcc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Calling `exit()` in a C++ application results in `std::terminate()` being called.

The `std::ios_base::Init::~~Init()` destructor flushes `std::cout`, `std::cerr` and `std::clog`. The flush of `std::cerr` results in `terminate` being called.

The `ios_base` class uses a sentry to check the state. The code in it's destructor is:

```
if (bool( M os.flags() & ios_base::unitbuf) && !uncaught_exception())
```

The `std::cerr` object has `ios_base::unitbuf` set so `uncaught_exception()` is called. This call gets the `cxg` globals:

```
cxg eh_globals *globals = cxg get_globals ();
```

The `__cxg_get_globals()` checks if the `ec_globals` init object:

```
static eh_globals init init;
```

to see if it is still valid and the state is:

```
(gdb) p /x init
$2 = {
  _M_key = 0x13010001,
  _M_init = 0x1
}
```



However the static destructor has run and the POSIX key has been deleted. This results in `std::terminate()` being called.

The code for the destructor on ARM is:

```
006562e0 <__eh_globals_init::~__eh_globals_init()>:
6562e0: 7903      ldrb    r3, [r0, #4]
6562e2: b510     push   {r4, lr}
6562e4: 4604     mov    r4, r0
6562e6: b90b     cbnz   r3, 6562ec <__eh_globals_init::~__eh_globals_init()+0xc>
6562e8: 4620     mov    r0, r4
6562ea: bd10     pop    {r4, pc}
6562ec: 6800     ldr    r0, [r0, #0]
6562ee: f04d fe6b  bl     6a3fc8
6562f2: 4620     mov    r0, r4
6562f4: bd10     pop    {r4, pc}
```

and for aarch64 it is:

```
0000000010222c30 <__eh_globals_init::~__eh_globals_init()>:
10222c30: 39401001  ldrb   w1, [x0, #4]
10222c34: 35000041  cbnz   w1, 10222c3c <__eh_globals_init::~__eh_globals_init()+0xc>
10222c38: d65f03c0  ret
10222c3c: a9bf7bfd  stp    x29, x30, [sp, #-16]!
10222c40: 910003fd  mov    x29, sp
return pthread_key_delete (__key);
10222c44: 59400000  ldr    w0, [x0]
10222c48: 94008806  bl     10244c60
10222c4c: a8c17bfd  ldp    x29, x30, [sp], #16
10222c50: d65f03c0  ret
```

The `_M_init` boolean is not set to false.

### Comment 1

1. **Chris Johns**, Wed, 08 Jun 2022 05:13:41 GMT

[https://gcc.gnu.org/bugzilla/show\\_bug.cgi?id=105880](https://gcc.gnu.org/bugzilla/show_bug.cgi?id=105880)

### Comment 2

1. **Chris Johns**, Thu, 09 Jun 2022 02:21:00 GMT

In 80aea6a/rtems:

testsuite/libtests: Add `exit03` to test `exit()` with C++

Updates #4661

### Comment 3

1. **Chris Johns**, Tue, 19 Jul 2022 06:02:18 GMT

2. **owner:** set to **Chris Johns <chrisj@...>**

3. **status:** changed from **new** to **closed**

4. **resolution:** set to **fixed**

In a2bda89/rtems-source-builder:

gcc12/libstdc++: Fix lifetime bugs for non-TLS `eh_globals`  
This is the fix from PR105880:

<https://gcc.gnu.org/bugzilla/attachment.cgi?id=53103>

Closes #4661

## 4662 - Fix GCC 12 warnings

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4662">https://devel.rtems.org/ticket/4662</a> ( <a href="https://devel.rtems.org/ticket/4662">https://devel.rtems.org/ticket/4662</a> )
<b>Id</b>	4662
<b>Reporter</b>	Chris Johns
<b>Created</b>	8 June 2022 04:12:05
<b>Modified</b>	31 October 2023 11:48:22
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/gcc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	highest
<b>Severity</b>	blocker
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The move to GCC 12 has resulted in an increase in the number of warning. This ticket covers fixing these warning.

**Comment 1**

1. **Chris Johns**, Mon, 13 Jun 2022 22:22:46 GMT

In 66dc06e/rtems:

(The changeset message doesn't reference this ticket)

**Comment 2**

1. **Chris Johns**, Wed, 15 Jun 2022 02:56:27 GMT

In 5262b9c/rtems:

```
score/cpu: Silence ARM and AARCH64 GCC 12 false trigger array warning
```

The false trigger is covered in:

```
https://gcc.gnu.org/bugzilla/show_bug.cgi?id=99578
```

GCC 11 and 12 has been patched for constant pointer casts above 4K. This code casts a constant pointer within the first 4K page. As a result the patch disables the warning.

Updates #4662

**Comment 3**

1. **Chris Johns**, Wed, 15 Jun 2022 02:56:30 GMT

In 0cf0914/rtems:

```
cpukit: Change _COMPILING_NEWLIB to _LIBC for helper functions decls
```

Updates #4662

**Comment 4**

1. **Chris Johns**, Mon, 20 Jun 2022 00:39:36 GMT

The rtems/test.h code has a few warnings that are confusing:

```
In file included from ../../../../testsuites/libtests/ttest01/test-leak.c:1:
../../../../cpukit/include/rtems/test.h: In function 'T_case_body_missing_free':
../../../../cpukit/include/rtems/test.h:225:9: warning: 'p' may be used uninitialized [-Wmaybe-uninitialized]
 225 |         T_check_not_null(&T_check_instance, a);
      |         ^~~~~~
../../../../cpukit/include/rtems/test.h:219:6: note: by argument 2 of type 'const void *' to 'T_check_not_null' declared here
 219 | void T_check_not_null(const T_check_context_msg *, const void *);
      |         ^~~~~~
```

There are some more. Why does the code have tabs? It makes it difficult to update.

**Comment 5**

1. **Chris Johns**, Mon, 20 Jun 2022 01:19:56 GMT

The warning in comment:4 looks similar to:

```
[3173/4451] Compiling testsuites/psxtests/psxkey07/init.c
../../../../testsuites/psxtests/psxkey07/init.c: In function 'Test_Thread':
../../../../testsuites/psxtests/psxkey07/init.c:59:8: warning: 'value_p' may be used uninitialized [-Wmaybe-uninitialized]
 59 |     sc = pthread_setspecific( Key, value_p );
      |     ^~~~~~
In file included from ../../../../testsuites/psxtests/psxkey07/init.c:34:
/opt/work/rtems/6/arm-rtems6/include/pthread.h:309:9: note: by argument 2 of type 'const void *' to 'pthread_setspecific' declared here
 309 | int pthread_setspecific (pthread_key_t __key, const void *__value);
      |     ^~~~~~
```

The code is also similar to the comment:4 test case:

```
int *value_p, *value_p2;
value_p = malloc( sizeof( int ) );
rtems_test_assert(value_p != NULL);
```

Note, I added the NULL assert. Is this a false trigger for gcc 12 or something related to the malloc decl?

**Comment 6**

1. **Chris Johns**, Mon, 20 Jun 2022 01:30:06 GMT

There are a number of validation warnings. This is the bug notice of these warning as per the header.

**Comment 7**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. Chris Johns, Wed, 03 Aug 2022 07:18:28 GMT

I would prefer not to have to touch this trail:

```
../../../../cpukit/score/src/percpudata.c: In function '_Per_CPU_Data_initialize':
../../../../cpukit/score/src/percpudata.c:88:7: warning: 'memcpy' offset 0 is out of the bounds [0, 0] of object
'_Linker_set__Per_CPU_Data_begin' with type 'char[0]' [-Warray-bounds]
  88 |     memcpy( cpu->data, RTEMS_LINKER_SET_BEGIN( _Per_CPU_Data ), size);
      |     ^~~~~~
In file included from ../../../../cpukit/include/rtems/score/percpudata.h:41,
      from ../../../../cpukit/score/src/percpudata.c:41:
../../../../cpukit/include/rtems/linkersets.h:38:3: note: '_Linker_set__Per_CPU_Data_begin' declared here
  38 |     Linker_set_##set##_begin
      |     ^~~~~~
../../../../cpukit/include/rtems/linkersets.h:95:39: note: in expansion of macro 'RTEMS_LINKER_SET_BEGIN'
  95 |     RTEMS_LINKER_SET_ALIGN( type ) type RTEMS_LINKER_SET_BEGIN( set )[ 0 ] \
      |     ^~~~~~
../../../../cpukit/score/src/percpudata.c:49:1: note: in expansion of macro 'RTEMS_LINKER_RWSET'
  49 | RTEMS_LINKER_RWSET(
      |     ^~~~~~
```

Built with config.ini:

```
[DEFAULT]
RTEMS_DEBUG = True
RTEMS_POSIX_API = True
[arm/xilinx_zynq_a9_qemu]
RTEMS_SMP = True
BUILD_TESTS = True
```

## Comment 8

1. Chris Johns, Wed, 03 Aug 2022 07:44:09 GMT

This warning looks like a bug in our heap allocator:

```
../../../../testsuites/libtests/malloctest/init.c: In function 'test_early_malloc':
../../../../testsuites/libtests/malloctest/init.c:1531:7: warning: pointer 'q' used after 'free' [-Wuse-after-free]
  1531 |     r = realloc( q, 128 );
      |     ^
1531 |     r = realloc( q, 128 );
      |     ^~~~~~
| rtems_test_assert( r == q );
|-----F1 libio.h 12% (110,15) Git-master (C++//1 Abbrev) [ruru] -----
|
| * defined state even if no root file system was mounted.
../../../../testsuites/libtests/malloctest/init.c:1529:3: note: call to 'free' here
  1529 |     free( q );
      |     ^~~~~~
| rtems_test_assert( s != NULL );
|extern rtems_filesystem_global_location_t rtems_filesystem_global_location_null;
|
|
```

The pointer q has been free so I am wondering if the realloc works because the same block in the heap is allocated?

## Comment 9

1. Chris Johns, Wed, 03 Aug 2022 10:18:25 GMT

I think this warning is due to the pointer being captured in a static const variable:

```
In file included from ../../../../testsuites/libtests/ttest01/test-leak.c:1:
../../../../cpukit/include/rtems/test.h: In function 'T_case_body_missing_free':
../../../../cpukit/include/rtems/test.h:225:9: warning: 'p' may be used uninitialized [-Wmaybe-uninitialized]
  225 |     T_check_not_null(&T_check_instance, a);
      |     ^~~~~~
../../../../cpukit/include/rtems/test.h:219:6: note: by argument 2 of type 'const void *' to 'T_check_not_null' declared here
  219 | void T_check_not_null(const T_check_context_msg *, const void *);
      |     ^~~~~~
```

It should be OK so I am wondering if this is a false warning?

## Comment 10

1. Chris Johns, Wed, 03 Aug 2022 10:24:17 GMT

Replying to Chris Johns:

I think this warning is due to the pointer being captured in a static const variable:

The pointer is not part of the static const data.

## Comment 11

1. Chris Johns, Thu, 04 Aug 2022 21:48:31 GMT

In 46131ce0/rtems:

```
libdl: Fix warnings on 64bit architectures
Updates #4662
```

**Comment 12**

1. **Chris Johns**, Thu, 04 Aug 2022 21:48:34 GMT

In c36d608/rtems:

```
testsuite: Fix warnings
Updates #4662
```

**Comment 13**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:14 GMT

In ec7d6c0/rtems:

```
threads.h: Add pragmas to get rid of gcc 12 errors
Updates #4662
```

**Comment 14**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:17 GMT

In f9302067/rtems:

```
linkersets.h: Fix gcc 12 warning
Changing the offset from 0 to 1 got rid of a warning stating that offset 0 is out of bounds.
Updates #4662
```

**Comment 15**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:19 GMT

In df3fa4e0/rtems:

```
interr.h: Fix gcc 12 warning
The warning that this fixes states that "ISO C restricts enumerator values to range of 'int'."
Updates #4662
```

**Comment 16**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:21 GMT

In c55bd160/rtems:

```
percpu.h: Add pragma for gcc 12 warning
Updates #4662
```

**Comment 17**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:23 GMT

In 5b875915/rtems:

```
schedulerpriority.h: Fix gcc 12 warning
Changed the size of the array to 1 to get rid of the warning.
Updates #4662
```

**Comment 18**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:26 GMT

In 9e228978/rtems:

```
test.h: Add pragma for gcc 12 warning
```

**Comment 19**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:28 GMT

In b092ad57/rtems:

cpu.h: Fix gcc 12 warnings

Added two pragmas to address, and changed the value of AARCH64\_EXCEPTION\_MAKE\_ENUM\_64\_BIT to INT\_MAX because the old value was not in range of an int.

Updates #4662

**Comment 20**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:30 GMT

In dc0dccc/rtems:

dl09/dl-load.c: Fix gcc 12 warning

Changed format of size\_t variable being printed.

Updates #4662

**Comment 21**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:33 GMT

In a447b9b3/rtems:

malloctest/init.c: Added pragmas to address gcc 12 warnings

Updates #4662

**Comment 22**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:35 GMT

In 978022ee/rtems:

ttest01/test-checks.c: Initialize variables

These uninitialized variables were causing warnings to be generated.

Updates #4662

**Comment 23**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:37 GMT

In f60f349/rtems:

psxclock/init.c: Change print format for warning

Updates #4662

**Comment 24**

1. **Ryan Long**, Fri, 19 Aug 2022 20:46:39 GMT

In f045b9d/rtems:

psxkey07/init.c: Add pragma for gcc 12 warning

Updates #4662

**Comment 25**

1. **Sebastian Huber**, Tue, 30 Aug 2022 04:50:29 GMT

In c226990/rtems:

score: Do not expose to

The header file should not unnecessarily include standard C header files. The and header includes were removed in 2017.

Update #4662.

#### **Comment 26**

1. **Sebastian Huber**, Tue, 30 Aug 2022 05:32:54 GMT

In 44b3bc65/rtems:

validation: Fix use of uninitialized variables

Update #4662.

#### **Comment 27**

1. **Sebastian Huber**, Tue, 30 Aug 2022 13:11:48 GMT

In c1453c6/rtems-central:

spec: Fix warnings in validation code

Update #4662.

#### **Comment 28**

1. **Sebastian Huber**, Wed, 31 Aug 2022 11:12:58 GMT

In 1be6dc18/rtems:

libtest: Fix warnings without a pragma

It seems that recent GCC versions expect that functions with a "const type \*" parameter will read from the referenced location.

Update #4662.

#### **Comment 29**

1. **Sebastian Huber**, Wed, 31 Aug 2022 11:13:00 GMT

In dad6d322/rtems:

Fix pedantic warnings without a storage increase

Use RTEMS\_ZERO\_LENGTH\_ARRAY for flexible array member.

Update #4662.

#### **Comment 30**

1. **Sebastian Huber**, Fri, 09 Sep 2022 05:59:44 GMT

In 8d32b988/rtems:

validation: Fix integer type warning

Update #4662.

#### **Comment 31**

1. **Chris Johns**, Tue, 29 Nov 2022 23:55:39 GMT
2. **priority**: changed from **normal** to **highest**

#### **Comment 32**

1. **Joel Sherrill**, Fri, 27 Jan 2023 23:37:14 GMT

Filed #4833 for warnings in grlib/pci/grpci2dma.c which will require some insight to resolve properly. They look simple to fix for the \_\_RIGHT\_\_ person.

#### **Comment 33**

1. **Joel Sherrill**, Mon, 30 Jan 2023 16:28:57 GMT

In 29a3ad1b/rtems:

```
glibc: Fix snprintf() overflow warnings from gcc 12
Updates #4662.
```

#### **Comment 34**

1. **Zhongjie Zhu**, Tue, 07 Feb 2023 16:30:27 GMT

In ebb9e8c/rtems:

```
score: Fix maybe uninitialized warning
```

There are different cases for `_ISR_lock_ISR_disable()` and `_ISR_lock_ISR_enable()` in the case `RTEMS_SMP` is defined or `RTEMS_PROFILING` is defined, so remove the related Code.

```
../../../../cpukit/include/rtems/score/threaddispatch.h: In function '_Thread_Dispatch_disable':
../../../../cpukit/include/rtems/score/threaddispatch.h:231:14: warning: 'lock_context' may be used uninitialized [-Wmaybe-uninitialized]
```

```
231 |   cpu_self = _Thread_Dispatch_disable_critical( &lock_context );
```

```
| ~
```

```
../../../../cpukit/include/rtems/score/threaddispatch.h:210:32: note: by argument 1 of type 'const ISR_lock_Context *' to
'_Thread_Dispatch_disable_critical' declared here
```

```
210 | static inline Per_CPU_Control *_Thread_Dispatch_disable_critical(
```

```
|
```

```
../../../../cpukit/include/rtems/score/threaddispatch.h:225:21: note: 'lock_context' declared here
```

```
225 |   ISR_lock_Context lock_context;
```

```
| ~
```

```
Update #4662.
```

#### **Comment 35**

1. **Joel Sherrill**, Thu, 22 Jun 2023 20:55:25 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

Looks like most, if not all, have been resolved.

#### **Comment 36**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:48:22 GMT
2. **keywords:** **qualification** added

## **4666 - TFTP: Implement block and window size options**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4666">https://devel.rtems.org/ticket/4666</a> ( <a href="https://devel.rtems.org/ticket/4666">https://devel.rtems.org/ticket/4666</a> )
<b>Id</b>	4666
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	21 June 2022 07:25:19
<b>Modified</b>	18 January 2024 16:36:42
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Support the following TFTP options:

- RFC 2347 TFTP Option Extension
- RFC 2348 TFTP Blocksize Option
- RFC 7440 TFTP Windowsize Option

**Comment 1**

1. **Frank Kühndel**, Tue, 21 Jun 2022 07:46:13 GMT

In c044f050/rtems:

```
TFTPFS: Cleanup: Remove spaces at lines ends
Update #4666.
```

**Comment 2**

1. **Frank Kühndel**, Tue, 21 Jun 2022 07:46:16 GMT

In 679e7f10/rtems:

```
TFTPFS: Implement block and window size options
The original file cpukit/libfs/src/ftpfs/tftpDriver.c is split into two:
tftpfs.c - This file contains the code from tftpDriver.c
```

```
related to file system operations such as mount(), open(), read(), and so on.
```

```
tftpDriver.c - In the original file remains only the code related
```

```
to networking. This code implements the Trivial File Transfer Protocol (TFTP).
```

```
Moreover, the code is extended to support
RFC 2347 TFTP Option Extension RFC 2348 TFTP Blocksize Option RFC 7440 TFTP Windowsize Option
Update #4666.
```

**Comment 3**

1. **Frank Kühndel**, Tue, 21 Jun 2022 07:46:18 GMT

In 3e2b4ec/rtems:

```
TFTPFS: Add tests
Update #4666.
```

**Comment 4**

1. **Sebastian Huber**, Tue, 21 Jun 2022 14:06:17 GMT

In e38d4f7/rtems:

```
TFTPFS: Reduce test configuration
Update #4666.
```



**Comment 5**

1. **Sebastian Huber**, Tue, 21 Jun 2022 14:06:19 GMT

In 085f363/rtems:

```
TFTPFs: Fix test configuration for FP targets
The test uses snprintf().
Update #4666.
```

**Comment 6**

1. **Chris Johns**, Tue, 29 Nov 2022 22:50:21 GMT

Has this task been completed?

**Comment 7**

1. **Joel Sherrill**, Fri, 10 Feb 2023 13:51:58 GMT

Pinging again. Has this task been completed? If so, please close. If not, will it be done by 6.1?

**Comment 8**

1. **Frank Kuhndel**, Mon, 27 Feb 2023 16:21:32 GMT

All three RFCs have been implemented and the tests are also present and working. One additional patch was needed to provide a missing diagram for the documentation:

<https://lists.rtems.org/pipermail/devel/2022-October/073561.html>

Moreover, Coverity issues were fixed later on, see #4718.

This work on TFTP is completed and this ticket can be closed.

**Comment 9**

1. **Frank Kuhndel**, Mon, 27 Feb 2023 16:22:47 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

**Comment 10**

1. **Sebastian Huber**, Thu, 18 Jan 2024 16:36:42 GMT

In 3626fe8/rtems:

```
fstests/tftpf: Fix build dependency
Update #4666.
```

**4667 - include/sys/\_bitset.h defines struct bitset, pollutes namespace**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4667">https://devel.rtems.org/ticket/4667</a> ( <a href="https://devel.rtems.org/ticket/4667">https://devel.rtems.org/ticket/4667</a> )
<b>Id</b>	4667
<b>Reporter</b>	Alexandre Oliva
<b>Created</b>	22 June 2022 04:10:04
<b>Modified</b>	31 October 2023 11:48:40
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	tool/newlib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

sys/\_bitset.h gets indirectly (\*) included by sys/types.h, and should thus define only names that C and C++ standards reserve for the implementation. However, the line:

```
BITSET_DEFINE(bitset, 1);
```

expands to a definition of struct bitset in the global namespace.

Some of GCC's libstdc++ tests were failing on aarch64-rtems6.0 because of the naming ambiguity that arises. <https://gcc.gnu.org/pipermail/gcc-patches/2022-June/596918.html>

It would be best if user programs didn't have to resort to such trickery. In C++, it's not so hard; in C, it can be trickier.

I have not checked whether this struct bitset is actually used for any purpose on aarch64-rtems, or whether it's present on other ports. Maybe it could just be removed or renamed? Maybe upstream (FreeBSD?) would consider dropping it?

(\*) sys/types.h includes sys/\_pthreadtypes.h includes sys/cpuset.h includes sys/\_cpuset.h includes sys/\_bitset.h

#### Comment 1

1. **Sebastian Huber**, Wed, 22 Jun 2022 06:53:40 GMT

It seems the namespace pollution is already fixed in FreeBSD. We have to add the FreeBSD patches to Newlib.

#### Comment 2

1. **Sebastian Huber**, Wed, 22 Jun 2022 08:23:03 GMT
2. **owner**: set to **Sebastian Huber**
3. **status**: changed from **new** to **accepted**

#### Comment 3

1. **Sebastian Huber**, Wed, 22 Jun 2022 08:23:24 GMT
2. **component**: changed from **arch/aarch64** to **tool/newlib**

#### Comment 4

1. **Sebastian Huber**, Fri, 24 Jun 2022 05:32:25 GMT

In 89e910f1/rtems:

```
spcpuset01: Account for API changes
Update #4667.
```

#### Comment 5

1. **Sebastian Huber**, Fri, 24 Jun 2022 05:32:27 GMT

In a76988c/rtems:

```
score: Remove unused _Processor_mask_Nand()
Update #4667.
```

#### Comment 6

1. **Sebastian Huber**, Fri, 24 Jun 2022 05:32:29 GMT

In ba56e239/rtems:

```
score: Account for API changes
Update #4667.
```

#### Comment 7

1. **Sebastian Huber**, Fri, 24 Jun 2022 09:47:44 GMT
2. **status**: changed from **accepted** to **closed**
3. **resolution**: set to **fixed**

In 5295c711/rtems-source-builder:

```
6/7: Update Newlib
```

This Newlib update fixes a namespace pollution issue with .

Close #4667.

#### **Comment 8**

1. **Sebastian Huber**, Thu, 30 Jun 2022 15:33:56 GMT

In 9a88b07/rtems-libbsd:

user-space: Request FreeBSD bitset API

This is required for recent Newlib versions.

Update #4667.

#### **Comment 9**

1. **Sebastian Huber**, Thu, 30 Jun 2022 15:34:20 GMT

In f009252/rtems-libbsd:

user-space: Request FreeBSD bitset API

This is required for recent Newlib versions.

Update #4667.

#### **Comment 10**

1. **Sebastian Huber**, Fri, 01 Jul 2022 12:34:37 GMT

In c8f49c2/rtems-source-builder:

6/7: Update Newlib

This Newlib update fixes a FreeBSD kernel space issue with .

Update #4667.

#### **Comment 11**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:48:40 GMT

2. **keywords: qualification** added

### **4668 - Use thread-local storage in libstdc++**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4668">https://devel.rtems.org/ticket/4668</a> ( <a href="https://devel.rtems.org/ticket/4668">https://devel.rtems.org/ticket/4668</a> )
<b>Id</b>	4668
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	22 June 2022 05:56:28
<b>Modified</b>	11 October 2023 09:30:13
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	tool/gcc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	4672

#### **Description**

Fix the libstdc++ configuration so that TLS is used on targets with TLS support. Using TLS is more robust against shortages of system resources which lead to unexpected behaviour.

#### **Attachments:**

**1 Sebastian Huber, Wed, 22 Jun 2022 05:57:29 GMT**

**attach:** set to [v2-0001-Enable-some-features-for-RTEMS-in-libstdc.patch](https://devel.rtems.org/ticket/4668/v2-0001-Enable-some-features-for-RTEMS-in-libstdc.patch) (<https://devel.rtems.org/ticket/4668/v2-0001-Enable-some-features-for-RTEMS-in-libstdc.patch>)

**2 Sebastian Huber, Mon, 08 Aug 2022 10:53:13 GMT**

**attach:** set to [gcc-10-RTEMS-Enable-some-features-in-libstdc.patch](https://devel.rtems.org/ticket/4668/gcc-10-RTEMS-Enable-some-features-in-libstdc.patch) (<https://devel.rtems.org/ticket/4668/gcc-10-RTEMS-Enable-some-features-in-libstdc.patch>)

**3 Sebastian Huber, Mon, 08 Aug 2022 10:53:33 GMT**

**attach:** set to [gcc-12-RTEMS-Enable-some-features-in-libstdc.patch](https://devel.rtems.org/ticket/4668/gcc-12-RTEMS-Enable-some-features-in-libstdc.patch) (<https://devel.rtems.org/ticket/4668/gcc-12-RTEMS-Enable-some-features-in-libstdc.patch>)

**Comment 1**

1. **Sebastian Huber**, Fri, 01 Jul 2022 09:52:49 GMT

2. **blockedby:** set to **4672**

**Comment 2**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:03:20 GMT

In d07d6498/rtems:

```
samples/cdtest: Test exceptions during system init
```

```
Update #4668. Update #4672.
```

**Comment 3**

1. **Sebastian Huber**, Wed, 17 Aug 2022 04:55:33 GMT

In 4fd9fbd/rtems-source-builder:

```
6: Enable some libstdc++ features
```

```
Enable TLS support for all RTEMS targets except bfin, lm32, m68k, mips, moxie, orlk, and v850. For all RTEMS targets, define HAVE_ALIGNED_ALLOC, HAVE_AT_QUICK_EXIT, HAVE_LINK, HAVE_QUICK_EXIT, HAVE_READLINK, HAVE_SETENV, HAVE_SLEEP, HAVE_STRERROR_L, HAVE_SYMLINK, HAVE_TRUNCATE, and HAVE_USLEEP.
```

```
Update #4668.
```

**Comment 4**

1. **Sebastian Huber**, Thu, 08 Sep 2022 05:24:43 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

Integrated in GCC master branch and RSB for GCC 10 and 12 as patches.

**Comment 5**

1. **Sebastian Huber**, Wed, 11 Oct 2023 09:30:13 GMT

2. **keywords:** **qualification** added

**4669 - clock\_nanosleep() uses the wrong clock to determine the start time point**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4669">https://devel.rtems.org/ticket/4669</a> ( <a href="https://devel.rtems.org/ticket/4669">https://devel.rtems.org/ticket/4669</a> )
<b>Id</b>	4669
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	22 June 2022 08:51:14
<b>Modified</b>	26 July 2022 08:45:46
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	oliva@...
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

See gcc-patches mailing list:

```

On 22/06/2022 08:22, Sebastian Huber wrote:
> On 22/06/2022 08:01, Alexandre Oliva via Gcc-patches wrote:
>>
>> On rtems under qemu, the frequently-interrupted nanosleep ends up
>> sleeping shorter than expected, by a margin of less than 0,3%.
>>
>> I figured failing the library test over a system (emulator?) bug is
>> undesirable, so I put in some tolerance for the drift.
>>
>> Regstrapped on x86_64-linux-gnu, also tested with a cross to
>> aarch64-rtems6. OK to install?
>>
>> PS: I see nothing wrong with the implementation of clock_nanosleep (used
>> by nanosleep) on rtems6 that could cause it to wake up too early. I
>> suspect some artifact of the emulation environment.
>>
>>
>> for libstdc++-v3/ChangeLog
>>
>> * testsuite/30_threads/this_thread/60421.cc: Tolerate a
>> slightly early wakeup.
>> ---
>> .../testsuite/30_threads/this_thread/60421.cc      |      3 +-
>> 1 file changed, 2 insertions(+), 1 deletion(-)
>>
>> diff --git a/libstdc++-v3/testsuite/30_threads/this_thread/60421.cc b/libstdc++-v3/testsuite/30_threads/this_thread/60421.cc
>> index 12dbecalcc492..f3a5af453c4ad 100644
>> --- a/libstdc++-v3/testsuite/30_threads/this_thread/60421.cc
>> +++ b/libstdc++-v3/testsuite/30_threads/this_thread/60421.cc
>> @@ -51,9 +51,10 @@ test02()
>>     std::thread t([&result, &sleeping] {
>>         auto start = std::chrono::system_clock::now();
>>         auto time = std::chrono::seconds(3);
>> +     auto tolerance = std::chrono::milliseconds(10);
>>         sleeping = true;
>>         std::this_thread::sleep_for(time);
>> -     result = std::chrono::system_clock::now() >= (start + time);
>> +     result = std::chrono::system_clock::now() + tolerance >= (start + time);
>>         sleeping = false;
>>     });
>>     while (!sleeping)
>
> This looks like a bug in RTEMS or the BSP for the test platform. I would first investigate this and then change the test which
> looks all right to me.
> This is a problem in RTEMS. RTEMS uses the FreeBSD timecounters to maintain CLOCK_REALTIME and provides two methods to get the time
> in a coarse and fine resolution. The std::chrono::system_clock::now() uses the fine resolution (higher overhead). The
> clock_nanosleep() uses the coarse resolution which may give a time before now().

```

#### **Comment 1**

1. **Alexandre Oliva**, Thu, 23 Jun 2022 07:04:18 GMT
2. **cc: oliva@...** added

#### **Comment 2**

1. **Sebastian Huber**, Thu, 23 Jun 2022 07:14:50 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In cd50bea/rtems:

score: Use right clock for threadq timeouts

Use CLOCK\_REALTIME and CLOCK\_MONOTONIC for relative thread queue timeouts instead of CLOCK\_REALTIME\_COARSE and CLOCK\_MONOTONIC\_COARSE. This fixes an issue with clock\_nanosleep() in combination with clock\_gettime().

Close #4669.

#### **Comment 3**

1. **Sebastian Huber**, Thu, 23 Jun 2022 07:38:39 GMT

In 8c8ee47/rtems-central:

spec: Adjust clock\_nanosleep() test case

Update #4669.

#### **Comment 4**

1. **Sebastian Huber**, Tue, 26 Jul 2022 08:45:46 GMT
2. **keywords:** **qualification** added

## **4670 - Add option to build RTEMS with coverage instrumentation**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4670">https://devel.rtems.org/ticket/4670</a> ( <a href="https://devel.rtems.org/ticket/4670">https://devel.rtems.org/ticket/4670</a> )
<b>Id</b>	4670
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	28 June 2022 06:38:31
<b>Modified</b>	8 September 2022 06:27:10
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	4671
<b>Blocked by</b>	4196

**Description**

Add build options to build RTEMS with coverage instrumentation. Dump the gcov information after each test.

**Comment 1**

1. **Sebastian Huber**, Tue, 28 Jun 2022 06:38:43 GMT
2. **blockedby**: set to **4196**

**Comment 2**

1. **Sebastian Huber**, Tue, 28 Jun 2022 06:40:50 GMT
2. **blocking**: set to **4671**

**Comment 3**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:24:59 GMT

In 857fb17/rtems:

```
build: Add more flags to BuildItemContext?
```

Add cppflags, cflags, and cxxflags to BuildItemContext?. This allows to propagate the flags from parent items to child items.

Update #4670.

**Comment 4**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:03 GMT

In 4aeebae/rtems:

```
build: Fix identifier pattern
```

Allow upper case characters in identifiers.

Update #4670.

**Comment 5**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:06 GMT

In 0bb7b84/rtems:

```
build: Improve value substitution
```

The waf build system uses lists for tool flags. The build items may use variable substitution. Add the ability to use the variable substitution in lists. For example:

```
MORE_FLAGS = ['-more', '-flags']
```

```
flags:
```

```
-some-flag ${MORE_FLAGS}
```

Before this change, the `${MORE_FLAGS}` was substituted to `"-more -flags"`. This would be passed by waf as a single command line argument to the tool.

After this change, the `${MORE_FLAGS}` list extends the flags list:

```
flags = ['-some-flag', '-more', '-flags']
```

This list extension is performed if a list element consists of exactly one variable.

Update #4670.

**Comment 6**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:08 GMT

In 42da08d/rtems:

build: Add cppflags, cflags, cxxflags to groups

Propagate the group defined cppflags, cflags, and cxxflags from parent groups to child items through the build item context.

Update #4670.

**Comment 7**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:10 GMT

In a0aaa39/rtems:

build: Fix optimization flags definition order

OPTIMIZATION\_FLAGS must be defined before /build/bsp/bspopts is processed.

Update #4670.

**Comment 8**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:12 GMT

In a13047c/rtems:

build: Allow separate optimization flags

Allow separate optimization flags for the BSP, cpukit, and tests. For example, the BSP and cpukit may be built without optimization if coverage instrumentation is enabled, however, the tests may still use optimization.

Update #4670.

**Comment 9**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:15 GMT

In 2bc233fe/rtems:

gcov: Add fork(), etc. gcov wrappers

The compiler wraps fork(), etc. system calls if coverage generation is enabled. These functions must be provided by the system. For RTEMS, they just return an error status.

Update #4670.

**Comment 10**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:17 GMT

In 4f87edb/rtems:

gcov: Add functions to dump the gcov information

Update #4670.

**Comment 11**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:19 GMT

In 7452f67d/rtems:

gcov: Add wrapper to dump the gcov info

Update #4670.

**Comment 12**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:25:22 GMT

In 5c13a96/rtems:

build: Add RTEMS\_GCOV\_COVERAGE option

Update #4670.

#### **Comment 13**

1. **Sebastian Huber**, Tue, 05 Jul 2022 07:19:33 GMT

In f048c15/rtems-central:

spec: Update due to API changes

Update #4670.

#### **Comment 14**

1. **Sebastian Huber**, Wed, 20 Jul 2022 06:38:48 GMT

In 329a1ccf/rtems:

build: Add missing cxxflags

Update #4670.

#### **Comment 15**

1. **Sebastian Huber**, Thu, 04 Aug 2022 17:29:39 GMT

In 52b7a58/rtems:

build: Install

Update #4670.

#### **Comment 16**

1. **Sebastian Huber**, Thu, 08 Sep 2022 06:26:43 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In c33cca3/rtems-docs:

eng: Document new build item attributes

Close #4670.

#### **Comment 17**

1. **Sebastian Huber**, Thu, 08 Sep 2022 06:27:10 GMT

In 5ee830f/rtems-central:

spec: Add attributes to build items

Update #4670.

---

## **4672 - Thread-local storage should be usable once an idle thread exists**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4672">https://devel.rtems.org/ticket/4672</a> ( <a href="https://devel.rtems.org/ticket/4672">https://devel.rtems.org/ticket/4672</a> )
<b>Id</b>	4672
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	29 June 2022 09:13:44
<b>Modified</b>	11 October 2023 09:29:39
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	4560, 4668
<b>Blocked by</b>	

---

**Description**

At some point during system initialization the idle threads are created. Afterwards the boot processor basically executes within the context of an idle thread with thread dispatching disabled. On some architectures, the thread-local storage state must be applied to processor registers. Add a new CPU port function to do this: `_CPU_Use_thread_local_storage( Context_Control *executing )`.

**Comment 1**

1. **Sebastian Huber**, Fri, 01 Jul 2022 09:52:49 GMT
2. **blocking**: changed from **4560** to **4560, 4668**

**Comment 2**

1. **Sebastian Huber**, Mon, 04 Jul 2022 06:03:20 GMT

In d07d6498/rtems:

```
samples/cdtest: Test exceptions during system init
Update #4668. Update #4672.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 05 Jul 2022 05:38:53 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 03e4d1e9/rtems:

```
score: Add _CPU_Use_thread_local_storage()
```

At some point during system initialization, the idle threads are created. Afterwards, the boot processor basically executes within the context of an idle thread with thread dispatching disabled. On some architectures, the thread-local storage area of the associated thread must be set in dedicated processor registers. Add the new CPU port function to do this:

```
void _CPU_Use_thread_local_storage( const Context_Control *context )
Close #4672.
```

**Comment 4**

1. **Sebastian Huber**, Wed, 11 Oct 2023 09:29:39 GMT
  2. **keywords**: **qualification** added
- 

**4673 - Runtime loader exported symbols address size not consistent**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4673">https://devel.rtems.org/ticket/4673</a> ( <a href="https://devel.rtems.org/ticket/4673">https://devel.rtems.org/ticket/4673</a> )
<b>Id</b>	4673
<b>Reporter</b>	Ryan Long
<b>Created</b>	30 June 2022 20:42:09
<b>Modified</b>	29 July 2022 13:25:02
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

In `rtl-sym.c`, where the exported symbols table is read in `rtems_rtl_symbol_global_add`, the addresses are expected to be of size `sizeof(unsigned long)`. This works fine for most architectures because most of them evaluate to 4. For `Aarch64` however, this evaluates to 8.

**Comment 1**

1. **Ryan Long**, Fri, 29 Jul 2022 13:17:44 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In `ace7db9/rtems-tools`:

```
rtems-syms.cpp: Change check to pointer size
Changed from a RISC-V specific value being in the conditional to a check for the size of the architecture's pointer.
Closes #4673
```

**Comment 2**

1. **Ryan Long**, Fri, 29 Jul 2022 13:25:02 GMT

In `1c6ac88/rtems`:

```
cpukit/libdl/rtl-sym.c: Fix increment of variable

In rtems_rtl_symbol_global_add() the loop that gets to the end of the symbol table used "unsigned long" to increment the index for the table. For most architectures this resulted in 4, but with AArch64, it results in 8. This resulted in the symbols being read in wrong. Changing this to void* along with changing the RISC-V specific code for 8 byte pointers in rtems-tools to work independent of the architecture.

Updates #4673 Closes #4682
```

**4675 - sleep should be a thread cancellation point**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4675">https://devel.rtems.org/ticket/4675</a> ( <a href="https://devel.rtems.org/ticket/4675">https://devel.rtems.org/ticket/4675</a> )
<b>Id</b>	4675
<b>Reporter</b>	Alexandre Oliva
<b>Created</b>	7 July 2022 10:17:28
<b>Modified</b>	22 June 2023 20:52:53
<b>Owner</b>	Kinsey Moore
<b>Type</b>	defect
<b>Component</b>	posix
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

GCC has worked around, in the `libstdc++` test suite, the fact that `nanosleep` (as well as `sleep` and `clock_nanosleep`) should be thread cancellation points, per POSIX, but RTEMS may want to make them so. <https://gcc.gnu.org/pipermail/gcc-patches/2022-June/597003.html>

(I haven't checked that other functions that should be thread cancellation points are, I only noticed that this one wasn't, and decided to file this ticket because for other issues in which I explicitly identified RTEMS I got a request to do so)

**Comment 1**

1. **Sebastian Huber**, Thu, 07 Jul 2022 12:40:48 GMT
2. **component**: changed from **admin** to **posix**

Thanks for reporting the issue. I think we have currently no cancellation points in RTEMS at all. I think this is intentional, so I would mark this bug as WONTFIX.

**Comment 2**

1. **Joel Sherrill**, Sat, 18 Mar 2023 17:43:07 GMT

Do you have a test to show something isn't right? `sleep()` and `nanosleep()` ultimately call `clock_nanosleep()` and the requested blocking state is "STATES\_WAITING\_FOR\_TIME | STATES\_INTERRUPTIBLE\_BY\_SIGNAL"

<https://git.rtems.org/rtems/tree/cpukit/posix/src/clocknanosleep.c#n77>

RTEMS state bits consist of the type of object is being blocked on and attributes such as interruptible. It has been this way for a LONG time.

As a random thought, if you don't build RTEMS with POSIX enabled, then POSIX signals are disabled and then this likely wouldn't work.

**Comment 3**

1. **Joel Sherrill**, Sat, 18 Mar 2023 17:43:24 GMT
2. **milestone**: set to **6.1**

**Comment 4**

1. **Alexandre Oliva**, Sat, 22 Apr 2023 05:32:10 GMT

The unpatched `libstdc++` testcase is a test that shows the problem. An explicit `pthread_testcancel` shouldn't be needed. Functions that are cancellation points should (as-if) call it implicitly.

**Comment 5**

1. **Joel Sherrill**, Thu, 22 Jun 2023 20:52:53 GMT
2. **owner**: set to **Kinsey Moore**
3. **status**: changed from **new** to **assigned**

**4677 - incorrect handling of "inactive\_per\_block" from "Objects\_Information" structure (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4677">https://devel.rtems.org/ticket/4677</a> ( <a href="https://devel.rtems.org/ticket/4677">https://devel.rtems.org/ticket/4677</a> )
<b>Id</b>	4677
<b>Reporter</b>	Adrian Varlan
<b>Created</b>	13 July 2022 06:10:51
<b>Modified</b>	31 October 2023 11:49:16
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification, CONFIGURE_UNLIMITED_OBJECTS inactive_per_block
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4676:

The `inactive_per_block` for block 1 is not handled correctly. For the first object in the second block, the `inactive_per_block` value is not decremented. As a consequence, the block might be deleted when the second to last object from block 1 is deleted. This is only valid when the application is configured with "CONFIGURE\_UNLIMITED\_OBJECTS".

The reason is the following:

in function `__Objects_Activate_unlimited` from "objectimpl.h"

```
block = __Objects_Get_index( the_object->id ) - OBJECTS_INDEX_MINIMUM;
```

```

if ( block > objects_per_block ) {
    block /= objects_per_block;
}

information->inactive_per_block[ block ]--;
information->inactive--;
}

```

in a block with 8 objects per block, when creating the 9th object, `_Objects_Get_index( the_object->id )` returns 9. Therefore, "block" will be 8 (9 - 1). The next "if" will not be taken (8 > 8 ? No) and the `inactive_per_block` will not be decremented to 7 and remains at 8. This means that block 1 is a candidate for "`_Objects_Shrink_information`" function although object id 9 is still valid.

Steps to reproduce:

-assuming 8 objects per allocation block  
-using semaphores as objects

- create 17 "RTEMS\_SIMPLE\_BINARY\_SEMAPHORE" semaphore objects id's 1 -> 17.
- delete semaphores 11, 12, 13, 14, 15, 16, 17 (order is important)
- lock semaphore 9
- delete semaphore 10 -> at this point, block 1 is freed although semaphore 9 is still active
- unlock semaphore 9 -> this can lead to errors. In my case due to the free the semaphore object was altered and changed from a "SEMAPHORE\_VARIANT\_SIMPLE\_BINARY" to "SEMAPHORE\_VARIANT\_MUTEX\_INHERIT\_PRIORITY" resulting in a return value of "RTEMS\_NOT\_OWNER\_OF\_RESOURCE".

Simple fix:

the condition for the "if" should be ">=" instead of ">".

### Comment 1

1. **Sebastian Huber**, Mon, 18 Jul 2022 07:27:45 GMT

In e094261/rtems:

score: Fix `_Objects_Active_count()`

With unlimited objects the object maximum may be larger than the sum of active and inactive objects.

Update #4677.

### Comment 2

1. **Sebastian Huber**, Mon, 18 Jul 2022 07:27:47 GMT

In 3bb79aab/rtems:

spunlimited01: New test

Update #4677.

### Comment 3

1. **Sebastian Huber**, Mon, 18 Jul 2022 07:27:50 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 12a03bea/rtems:

score: Fix unlimited objects support

Commit 21275b58a5a69c3c838082ffc8a7a3641f32ea9a ("score: Static `Objects_Information` initialization") introduced an off-by-one error in the maintenance of inactive objects.

Close #4677.

### Comment 4

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:49:16 GMT
2. **keywords:** **qualification** added

## 4678 - System initialization time increased compared to RTEMS 4.11

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4678">https://devel.rtems.org/ticket/4678</a> ( <a href="https://devel.rtems.org/ticket/4678">https://devel.rtems.org/ticket/4678</a> )
<b>Id</b>	4678
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 July 2022 06:24:41
<b>Modified</b>	31 October 2023 11:49:33
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Since RTEMS 5, the objects based on Objects\_Control are statically allocated in the .bss sections. The zero-initialization is unnecessary since each object is fully initialized after allocation by an object-specific initialization routine. The memory for objects is statically allocated or allocated from the workspace if the unlimited objects configuration option is used. Workspace memory is uninitialized by default. Optimize the static allocation to place the object controls, local tables, and thread queue heads into a .noinit section.

The longer system initialization time compared to RTEMS 4.11 may lead to hardware watchdog problems.

**Comment 1**

1. **Sebastian Huber**, Fri, 15 Jul 2022 06:26:19 GMT
2. **description**: modified (diff)

**Comment 2**

1. **Sebastian Huber**, Fri, 15 Jul 2022 08:42:56 GMT

In 5ed00353/rtems:

```
bsps: Sort .noinit* sections
```

Sort the .noinit\* input sections by name first, then by alignment if two sections have the same name. This allows the placement of begin/end symbols to initialize some areas with a special value.

Update #4678.

**Comment 3**

1. **Sebastian Huber**, Fri, 15 Jul 2022 08:42:58 GMT

In 4b911a75/rtems:

```
score: Place object controls into .noinit sections
```

Place the statically allocated object control blocks, local tables, and thread queue heads into the dedicated .noinit input sections. The output section is not zero initialized. Placing these elements into the .noinit section reduces the system initialization time by decreasing the .bss section size.

It may improve the cache efficiency since the mostly read local tables are placed in a contiguous memory area.

Update #4678.

**Comment 4**

1. **Sebastian Huber**, Fri, 15 Jul 2022 08:43:01 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 1bf878f7/rtems:

```
score: Extend memory dirty/zero actions
```

Dirty or zero also the part of the .noinit section used by RTEMS.

Close #4678.

**Comment 5**

1. **Sebastian Huber**, Mon, 18 Jul 2022 13:45:02 GMT

In 0e5f4c5/rtems:

spsysinit01: Account for use of .noinit section

The objects control blocks cannot be used to check the pre-initialization state since they are allocated in a .noinit section.

Update #4678.

#### **Comment 6**

1. **Sebastian Huber**, Wed, 20 Jul 2022 06:38:51 GMT

In 25ccc19/rtems:

bsps/riscv: Sort .noinit\* sections

Sort the .noinit\* input sections by name first, then by alignment if two sections have the same name. This allows the placement of begin/end symbols to initialize some areas with a special value.

Update #4678.

#### **Comment 7**

1. **Sebastian Huber**, Wed, 27 Jul 2022 06:51:59 GMT

In 2501c64b/rtems:

score: Fix objects local table initialization

The objects local table must be statically zero-initialized so that `_Objects_Get()` and `_Objects_Get_no_protection()` return NULL if no object is associated with the identifier.

Update #4678.

#### **Comment 8**

1. **Sebastian Huber**, Thu, 28 Jul 2022 06:50:25 GMT

In 6a65803/rtems:

score: Allow linker garbage collection

Place the object control blocks in dedicated sections to allow a linker garbage collection.

Update #4678.

#### **Comment 9**

1. **Sebastian Huber**, Mon, 01 Aug 2022 07:07:39 GMT

In 4d77f725/rtems:

sp54: Fix test case

Since commit 6a6580331df3e09516d50f37d4dd5fd57825c08a, the local table is zero-initialized. Use an initial object control block instead.

Update #4678.

#### **Comment 10**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:49:33 GMT
2. **keywords: qualification** added

---

## **4679 - Use priority inheritance for thread join**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4679">https://devel.rtems.org/ticket/4679</a> ( <a href="https://devel.rtems.org/ticket/4679">https://devel.rtems.org/ticket/4679</a> )
<b>Id</b>	4679
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 July 2022 06:40:24
<b>Modified</b>	2 May 2023 08:18:35
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Threads may join the thread termination of another thread using the `pthread_join()` or `rtems_task_delete()` directives. Currently, the thread cancel operation uses a special case priority boosting mechanism:

```
static void _Thread_Raise_real_priority(
  Thread_Control *the_thread,
  Priority_Control priority
)
{
  Thread_queue_Context queue_context;
  _Thread_queue_Context_initialize( &queue_context );
  _Thread_queue_Context_clear_priority_updates( &queue_context );
  _Thread_Wait_acquire( the_thread, &queue_context );
  if ( priority < the_thread->Real_priority.priority ) {
    _Thread_Priority_change(
      the_thread,
      &the_thread->Real_priority,
      priority,
      PRIORITY_GROUP_LAST,
      &queue_context
    );
  }
  _Thread_Wait_release( the_thread, &queue_context );
  _Thread_Priority_update( &queue_context );
}
```

The problem is that this approach is not transitive, it does not account for priority adjustments of the calling task while waiting for the join, clustered scheduling is not supported, and deadlocks are not detected. All these problems are fixed by using a priority inheritance thread queue for the join operation.

**Comment 1**

1. **Sebastian Huber**, Tue, 19 Jul 2022 06:44:07 GMT
2. **description:** modified (diff)

**Comment 2**

1. **Sebastian Huber**, Thu, 28 Jul 2022 05:36:09 GMT

In 81fd510/rtems-docs:

```
c-user: Document task life states
Update #4679.
```

**Comment 3**

1. **Sebastian Huber**, Thu, 28 Jul 2022 05:36:11 GMT

In f4377b4/rtems-docs:

```
c-user: Document new rtems_task_delete() behaviour
Update #4679.
```

**Comment 4**

1. **Sebastian Huber**, Thu, 28 Jul 2022 05:45:19 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 31036f1d/rtems:

```
score: Use priority inheritance for thread join
```

Threads may join the thread termination of another thread using the `pthread_join()` or `rtems_task_delete()` directives. The thread cancel operation used a special case priority boosting mechanism implemented by `_Thread_Raise_real_priority()`. The problem was that this approach

is not transitive, does not account for priority adjustments of the calling task while waiting for the join, does not support clustered scheduling, and does not detect deadlocks. All these problems are fixed by using a priority inheritance thread queue for the join operation.

Close #4679.

#### Comment 5

1. **Sebastian Huber**, Tue, 02 May 2023 08:18:35 GMT
2. **keywords:** qualification added

## 4680 - POSIX tasks cancelled through `rtems_task_delete()` should have an exit value of `PTHREAD_CANCELED`

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4680">https://devel.rtems.org/ticket/4680</a> ( <a href="https://devel.rtems.org/ticket/4680">https://devel.rtems.org/ticket/4680</a> )
<b>Id</b>	4680
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	19 July 2022 08:23:19
<b>Modified</b>	2 May 2023 08:18:20
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The `rtems_task_delete()` directive is basically just a combined `pthread_cancel()` and `pthread_join()`. In addition, it removes the `PTHREAD_DETACHED` state. The exit value returned by `pthread_join()` of threads cancelled by `rtems_task_delete()` should reflect this by getting a `PTHREAD_CANCELED` value and not `NULL`.

#### Comment 1

1. **Sebastian Huber**, Thu, 28 Jul 2022 05:45:21 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 8a864bc6/rtems:

```
score: Use PTHREAD_CANCELED for _Thread_Cancel()
```

The `rtems_task_delete()` directive is basically just a combined `pthread_cancel()` and `pthread_join()`. In addition, it removes the `PTHREAD_DETACHED` state. The exit value returned by `pthread_join()` of threads cancelled by `rtems_task_delete()` should reflect this by getting a `PTHREAD_CANCELED` value instead of `NULL` which could be a normal exit value.

Close #4680.

#### Comment 2

1. **Sebastian Huber**, Tue, 02 May 2023 08:18:20 GMT
2. **keywords:** qualification added

## 4682 - Add AArch64 support to libdl



---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4682">https://devel.rtems.org/ticket/4682</a> ( <a href="https://devel.rtems.org/ticket/4682">https://devel.rtems.org/ticket/4682</a> )
<b>Id</b>	4682
<b>Reporter</b>	Ryan Long
<b>Created</b>	20 July 2022 21:12:13
<b>Modified</b>	29 July 2022 13:25:02
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

Add AArch64 support to libdl using NetBSD code as necessary.

#### Comment 1

1. **Ryan Long**, Fri, 29 Jul 2022 13:24:52 GMT

In ad94dc3/rtems:

```
sys/exec_elf.h: Bring in newer file
Updated this file with the newer version in NetBSD.
Updates #4682
```

#### Comment 2

1. **Ryan Long**, Fri, 29 Jul 2022 13:24:54 GMT

In f6432156/rtems:

```
libdl/rtl-elf.h: Fix aarch64 define
The aarch64 define was incorrect. This was causing the libdl tests to not work correctly.
Updates #4682
```

#### Comment 3

1. **Ryan Long**, Fri, 29 Jul 2022 13:24:57 GMT

In 0bd6514a/rtems:

```
cpukit/libdl: Add support for AArch64
rtl-mdreloc-aarch64.c and elf_machdep.h came from NetBSD.
Updates #4682
```

#### Comment 4

1. **Ryan Long**, Fri, 29 Jul 2022 13:24:59 GMT

In 2ea37e8/rtems:

```
libtests/dl*: Bump up the size of CONFIGURE_INIT_TASK_STACK_SIZE
Updates #4682
```

#### Comment 5

1. **Ryan Long**, Fri, 29 Jul 2022 13:25:02 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 1c6ac88/rtems:

cpukit/libddl/rtl-sym.c: Fix increment of variable

In rtems\_rtl\_symbol\_global\_add() the loop that gets to the end of the symbol table used "unsigned long" to increment the index for the table. For most architectures this resulted in 4, but with AArch64, it results in 8. This resulted in the symbols being read in wrong. Changing this to void\* along with changing the RISC-V specific code for 8 byte pointers in rtems-tools to work independent of the architecture.

Updates #4673 Closes #4682

## **4684 - Support Versal DDRMC0 regions 0 and 1**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4684">https://devel.rtems.org/ticket/4684</a> ( <a href="https://devel.rtems.org/ticket/4684">https://devel.rtems.org/ticket/4684</a> )
<b>Id</b>	4684
<b>Reporter</b>	Chris Johns
<b>Created</b>	22 July 2022 06:04:41
<b>Modified</b>	27 July 2022 23:00:10
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

The Versal's DDRMC0 supports region 0 and 1. Region 0's base address defaults to 0x000000000000 and can be up to 2G in length. If the hardware has more than 2G of DDR memory it is placed in region 1 and its default base address is 0x008000000000 placing it in the A64 address space.

Add support so the user defined memory length BSP\_XILINX\_VERSAL\_RAM\_LENGTH spans region 0 and 1.

Extend the heap with the region 1 memory.

### **Comment 1**

1. **Chris Johns**, Wed, 27 Jul 2022 23:00:07 GMT

In b868d0a/rtems:

```
bsp/aarch64: Make the unexpected sections origin address 64bit
```

Update #4684

### **Comment 2**

1. **Chris Johns**, Wed, 27 Jul 2022 23:00:10 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 51ffa21/rtems:

```
aarch64/versal: Support DDRMC0 region 0 and 1
Support DDRMC0 region 0 up to 2G in size Support DDRMC0 region 1 with DDR memory greater than 2G
up to the DDRMC0 max amount Extend the heap with region 1's memory
Closes #4684
```

## **4686 - Refactor shared code in Arm and AArch64**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4686">https://devel.rtems.org/ticket/4686</a> ( <a href="https://devel.rtems.org/ticket/4686">https://devel.rtems.org/ticket/4686</a> )
<b>Id</b>	4686
<b>Reporter</b>	Ryan Long
<b>Created</b>	26 July 2022 16:08:14
<b>Modified</b>	8 August 2022 16:53:46
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

rtl-mdreloc-arm.c and rtl-mdreloc-aarch64.c share code. The shared code should be pulled out and included into each file.

**Comment 1**

1. **Ryan Long**, Mon, 08 Aug 2022 16:53:46 GMT
2. **owner:** set to **Ryan Long** <ryan.long@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 5500232/rtems:

```
libdl: Refactor shared code in ARM and AArch64

rtl-mdreloc-arm.c was used as the basis for rtl-mdreloc-aarch64.c. This lead to some code being shared by the two files. The code was
consolidated into rtl-unwind-arm.c.

Closes #4686
```

---

**4689 - mips/jmr3904 Massive Number of Test Failures**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4689">https://devel.rtems.org/ticket/4689</a> ( <a href="https://devel.rtems.org/ticket/4689">https://devel.rtems.org/ticket/4689</a> )
<b>Id</b>	4689
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 July 2022 16:26:45
<b>Modified</b>	27 October 2022 22:00:45
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	arch/mips
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

jmr3904 last had a good test run in January 2022 (now July). Since then, there has not been one in which more than 1 test pass and I suspect that's because the one doesn't expect output.

<https://lists.rtems.org/pipermail/build/2022-January/030809.html>

This has been tracked down to a gdb simulator bug which has been reported as:

[https://sourceware.org/bugzilla/show\\_bug.cgi?id=29439](https://sourceware.org/bugzilla/show_bug.cgi?id=29439)

Many details follow in the comments.

**Attachments:**

- 
- 1 **Joel Sherrill**, Mon, 01 Aug 2022 19:35:18 GMT  
**attach:** set to [hello.exe.xz](https://devel.rtems.org/ticket/4689/hello.exe.xz) (<https://devel.rtems.org/ticket/4689/hello.exe.xz>)
- 

**Comment 1**

1. Joel Sherrill, Sat, 30 Jul 2022 18:21:29 GMT
2. **summary:** changed from **mips/jmr3904 Massive Number of Test Failures** to **mips/jmr3904 Massive Number of Test Failures**

**Comment 2**

1. Joel Sherrill, Sat, 30 Jul 2022 21:13:04 GMT

I checked with the gdb 8 used with RTEMS 5 and the hello.exe runs. The same executable fails to run with the gdb 11.2 used with RTEMS 6 or the gdb 13 used with RTEMS 7.

I will try to narrow it down some more before reporting to the gdb mailing list. At least it doesn't look like something broken in RTEMS itself.

**Comment 3**

1. Sebastian Huber, Mon, 01 Aug 2022 07:57:50 GMT

This looks like a GDB or other tool issue. Maybe a sign extension bug:

```
objdump -h build/mips/jmr3904/testsuites/samples/ticker.exe
build/mips/jmr3904/testsuites/samples/ticker.exe:      file format elf32-tradbigmips
Sections:
Idx Name          Size      VMA           LMA           File off  Algn
 0 .text          000115a0  88000000  88000000  00001000  2**4
CONTENTS, ALLOC, LOAD, READONLY, CODE
 1 .rtemsroset    00000070  880115a0  880115a0  000125a0  2**2
CONTENTS, ALLOC, LOAD, READONLY, DATA
 2 .init          00000048  88011610  88011610  00012610  2**0
CONTENTS, ALLOC, LOAD, READONLY, CODE
 3 .fini          00000030  88011658  88011658  00012658  2**0
CONTENTS, ALLOC, LOAD, READONLY, CODE
 4 .ctors         00000008  88011688  88011688  00012688  2**2
CONTENTS, ALLOC, LOAD, DATA
 5 .dtors         00000008  88011690  88011690  00012690  2**2
CONTENTS, ALLOC, LOAD, DATA
 6 .rdata         00002030  880116a0  880116a0  000126a0  2**4
CONTENTS, ALLOC, LOAD, READONLY, DATA
 7 .MIPS.abiflags 00000018  880136d0  880136d0  000146d0  2**3
CONTENTS, ALLOC, LOAD, READONLY, DATA, LINK_ONCE_SAME_SIZE
 8 .data          000005c0  880136e8  880136e8  000146e8  2**3
CONTENTS, ALLOC, LOAD, DATA
 9 .bss           00001410  88013cb0  88013cb0  00014ca8  2**4
ALLOC
10 .noinit        00001310  880150c0  880150c0  00014ca8  2**3
ALLOC
11 .rtemsstack   00004000  880163d0  880163d0  00014ca8  2**4
ALLOC
12 .debug_aranges 00002958  00000000  00000000  00014ca8  2**3
CONTENTS, READONLY, DEBUGGING, OCTETS
13 .debug_info    00109cb1  00000000  00000000  00017600  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
14 .debug_abbrev  00023397  00000000  00000000  001212b1  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
15 .debug_line    0003dc56  00000000  00000000  00144648  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
16 .debug_frame   000048f4  00000000  00000000  001822a0  2**2
CONTENTS, READONLY, DEBUGGING, OCTETS
17 .debug_str     0001160c  00000000  00000000  00186b94  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
18 .gnu.attributes 00000010  00000000  00000000  001981a0  2**0
CONTENTS, READONLY
19 .comment       00000063  00000000  00000000  001981b0  2**0
CONTENTS, READONLY
20 .debug_line_str 000001be  00000000  00000000  00198213  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
21 .debug_loclists 00022d89  00000000  00000000  001983d1  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
22 .debug_rnglists 0000605d  00000000  00000000  001bb15a  2**0
CONTENTS, READONLY, DEBUGGING, OCTETS
~/src/rtems (master) > /opt/rtems/6/bin/mipstx39-rtems6-gdb build/mips/jmr3904/testsuites/samples/ticker.exe
GNU gdb (GDB) 11.2
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "--host=x86_64-linux-gnu --target=mipstx39-rtems6".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<http://www.gnu.org/software/gdb/bugs.html>
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/manual/>>
For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from build/mips/jmr3904/testsuites/samples/ticker.exe...
(gdb) tar sim
Connected to the simulator.
(gdb) load
Loading section .text, size 0x115a0 lma ffffffff88000000
Loading section .rtemsroset, size 0x70 lma ffffffff880115a0
Loading section .init, size 0x48 lma ffffffff88011610
Loading section .fini, size 0x30 lma ffffffff88011658
Loading section .ctors, size 0x8 lma ffffffff88011688
Loading section .dtors, size 0x8 lma ffffffff88011690
Loading section .rdata, size 0x2030 lma ffffffff880116a0
Loading section .MIPS.abiflags, size 0x18 lma ffffffff880136d0
Loading section .data, size 0x5c0 lma ffffffff880136e8
Start address ffffffff88000004
Transfer rate: 648448 bits in <1 sec.
(gdb) r
Starting program: /tmp/sh/b-rtems/mips/jmr3904/testsuites/samples/ticker.exe
mips-core: 4 byte read to unmapped address 0xffffffff88000004 at 0xffffffff88000004
Program received signal SIGBUS, Bus error.
_start () at /home/EB/sebastian_h/src/rtems/bSPS/mips/jmr3904/start/start.S:57
57          bal     $L1
```

**Comment 4**

## 1. Joel Sherrill, Mon, 01 Aug 2022 19:32:17 GMT

I did a git bisect after narrowing down which release branches it worked on. That let me track it down to a commit based on git bisect. I will file a gdb ticket once I get my login working there again.

```
$ git bisect log git bisect start # good: [ce35d7163e779b1321058b22f005c70ce1524b25] Set GDB version number to 10.2. git bisect good
ce35d7163e779b1321058b22f005c70ce1524b25 # bad: [ef6ec3333e80e39ce207c6c5d5628bdd5402111d] Set GDB version number to 11.2. git bisect bad
ef6ec3333e80e39ce207c6c5d5628bdd5402111d # good: [8087c3fa8b5d695e3e29e69d70d0b35ec902ac59] Fix GDB build in infrun.c when configured with
unit tests disabled git bisect skip d3dacc0fafba473fd42fd3ca86fd3203db28ae8 # skip: [4d0d7d07d051308626f079fa6d1598fab445c7] Automatic date
update in version.in git bisect skip 8087c3fa8b5d695e3e29e69d70d0b35ec902ac59 # skip: [d3dacc0fafba473fd42fd3ca86fd3203db28ae8]
exp_uses_objfile to return bool git bisect skip 4d0d7d07d051308626f079fa6d1598fab445c7 # good: [a4eba6087d4cec81f8b41477b4da56ff87b88e91] Fix a
bug in the s390x linker when discarding all input files. git bisect good a4eba6087d4cec81f8b41477b4da56ff87b88e91 # good:
[546b77fe78bb366bbec3c708ac371e2f553bbdae] GDBserver remote packet support for memory tagging git bisect good
546b77fe78bb366bbec3c708ac371e2f553bbdae # good: [2e8adb6448c78fdb748c13c7859b68f3e7984c4d] Update config.sub and config.guess for MIPS R3
and R5 ISA support git bisect good 2e8adb6448c78fdb748c13c7859b68f3e7984c4d # bad: [50a6759f0f541ea965c7330bfbfe335cb8d66af8] Use
gdb::function_view in addrmap foreach git bisect bad 50a6759f0f541ea965c7330bfbfe335cb8d66af8 # good:
[c572c4580e774f1ec0115948d31dcf8a5b04878e] Automatic date update in version.in git bisect good c572c4580e774f1ec0115948d31dcf8a5b04878e #
good: [209f108f73888741bf31d03d35722b6e0b521ec8] sim: mn10300: tweak static inlines git bisect good 209f108f73888741bf31d03d35722b6e0b521ec8 #
bad: [57a922a59801a9e7684f9661a65fa2ed5833d65d] sim: move UNUSED before TYPE in SIM_ENDIAN_INLINE's definition git bisect bad
57a922a59801a9e7684f9661a65fa2ed5833d65d # good: [162c6aef1f3a96923e75f0b4ef430822d273465c] gas: fold symbol table entries generated for
.startof()/ .sizeof() git bisect good 162c6aef1f3a96923e75f0b4ef430822d273465c # good: [07490bf81d2fc91676eb71b77e07f80f20fc1b54] sim: unify
various library testing logic git bisect good 07490bf81d2fc91676eb71b77e07f80f20fc1b54 # bad: [ce3ec98acd2f344ae911de3f41dd2e3c6c68b141] sim: unify
gettext/intl probing logic git bisect bad ce3ec98acd2f344ae911de3f41dd2e3c6c68b141 # good: [c30420d82a0b743285cf8333f90ca85274632714] elf:
Update GNU_PROPERTY_UINT32_[AND]OR_XXX tests git bisect good c30420d82a0b743285cf8333f90ca85274632714 # bad:
[bc56166f66244a9e3abc62c7bc595a6f800f23b0] sim: unify toolchain dependency logic git bisect bad bc56166f66244a9e3abc62c7bc595a6f800f23b0
```

**Comment 5**

## 1. Joel Sherrill, Mon, 01 Aug 2022 19:38:10 GMT

FYI you can't run jmr3904 executables with just `__tar sim__`, you need to use `__tar sim --board=jmr3904__` in gdb or you can use the run command. Here's an example with an older gdb/run

```
$ ~/rtems-work/tools/5/bin/mipstx39-rtems5-run --board=jmr3904 /tmp/hello.exe
*** BEGIN OF TEST HELLO WORLD ***
....
```

**Comment 6**

## 1. Joel Sherrill, Tue, 02 Aug 2022 20:56:23 GMT

2. **description:** modified (diff)**Comment 7**

## 1. Joel Sherrill, Mon, 24 Oct 2022 13:38:27 GMT

Fix pushed to gdb repository and confirmed to work with ticker.exe.

**Comment 8**

## 1. Joel Sherrill, Thu, 27 Oct 2022 22:00:45 GMT

2. **owner:** set to Joel Sherrill <joel@...>3. **status:** changed from **new** to **closed**4. **resolution:** set to **fixed**

In cb8821e/rtems-source-builder:

```
Update mipstx39 gdb version to pick up fix to make simulator work
Closes #4689.
```

**4690 - CLOCK\_REALTIME thread queue not updated as part of clock\_settime call**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4690">https://devel.rtems.org/ticket/4690</a> ( <a href="https://devel.rtems.org/ticket/4690">https://devel.rtems.org/ticket/4690</a> )
<b>Id</b>	4690
<b>Reporter</b>	Chris Johns
<b>Created</b>	1 August 2022 04:22:51
<b>Modified</b>	5 August 2022 06:12:49
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Setting the CLOCK\_REALTIME clock using clock\_settime(CLOCK\_REALTIME, , ) clock does not update thread relative period entries on the watchdog timer queue.

A system's stability is effected if a user calls clock\_settime on the CLOCK\_REALTIME clock. The watchdog's REALTIME clock queue is references against the realtime clock and movement of the time means

The effected parts are:

- User C code that calls nanosleep, usleep, sleep or clock\_nanosleep(CLOCK\_REALTIME, , ).
- User C++ code that uses std::this\_thread::sleep\_for() as GCC uses the nanosleep() call.
- LibBSD uses CLOCK\_REALTIME.

The nanosleep call is explained in more detail in the clock\_nanosleep rational. The nanosleep clock must be CLOCK\_REALTIME. The clock\_settime standard says:

Setting the value of the CLOCK\_REALTIME clock via clock\_settime() shall have no effect on threads that are blocked waiting for a relative time service based upon this clock, including the nanosleep() function; nor on the expiration of relative timers based upon this clock. Consequently, these time services shall expire when the requested relative interval elapses, independently of the new or old value of the clock.

**Attachments:**

- 
- 1 **Chris Johns, Mon, 01 Aug 2022 08:07:48 GMT**  
**attach:** set to [init.c \(https://devel.rtems.org/ticket/4690/init.c\)](https://devel.rtems.org/ticket/4690/init.c)
- 

**Comment 1**

1. **Chris Johns, Mon, 01 Aug 2022 04:23:04 GMT**
2. **summary:** changed from **CLOCK\_REALTIME thread queue no updated as part of clock\_settime call** to **CLOCK\_REALTIME thread queue not updated as part of clock\_settime call**

**Comment 2**

1. **Chris Johns, Mon, 01 Aug 2022 06:56:47 GMT**

The attached test checks the times. It will show the failure however it does not pass the initial check because the expected ticks is not the actual ticks. The failure is:

```
Clock settime while sleeping: step=0
clock: nanosleep: sec=0 nsec=500000000 ticks=51 expected-ticks=50
../../../../testsuites/psxtests/psxclock/init.c: 120 ctx->ticks == ticks
```

Should the ticks the sleeper sees be 51 or 50?

**Comment 3**

1. **Chris Johns, Tue, 02 Aug 2022 00:53:45 GMT**

Replying to Chris Johns:

The attached test checks the times. It will show the failure however it does not pass the initial check because the expected ticks is not the actual ticks. The failure is:

```
Clock settime while sleeping: step=0
clock: nanosleep: sec=0 nsec=500000000 ticks=51 expected-ticks=50
../../../../testsuites/psxtests/psxclock/init.c: 120 ctx->ticks == ticks
```

Should the ticks the sleeper sees be 51 or 50?

<https://lists.rtems.org/pipermail/devel/2022-August/072735.html>

The extra 1 is needed.

**Comment 4**

1. **Sebastian Huber, Thu, 04 Aug 2022 05:47:27 GMT**

In c64c638/rtems:

```
posix: Fix relative CLOCK_REALTIME sleep
```

A relative CLOCK\_REALTIME time out shall not be affected by CLOCK\_REALTIME changes through clock\_settime(). Since our CLOCK\_REALTIME is basically just CLOCK\_MONOTONIC plus an offset, we can simply use the CLOCK\_MONOTONIC watchdog for relative CLOCK\_REALTIME time outs.

Update #4690.

**Comment 5**

1. **Sebastian Huber, Thu, 04 Aug 2022 05:50:25 GMT**
2. **keywords:** qualification added

**Comment 6**

1. **Sebastian Huber**, Thu, 04 Aug 2022 05:53:26 GMT

In 11121d0/rtems-central:

spec: Fix relative CLOCK\_REALTIME sleep

A relative CLOCK\_REALTIME time out shall not be affected by CLOCK\_REALTIME changes through clock\_settime(). Since our CLOCK\_REALTIME is basically just CLOCK\_MONOTONIC plus an offset, we can simply use the CLOCK\_MONOTONIC watchdog for relative CLOCK\_REALTIME time outs.

Update #4690.

**Comment 7**

1. **Chris Johns**, Thu, 04 Aug 2022 21:48:28 GMT

2. **owner:** set to **Chris Johns <chrisj@...>**

3. **status:** changed from **new** to **closed**

4. **resolution:** set to **fixed**

In 1a883b9/rtems:

testsuite/psxclock: Check setting realtime clock does not effect sleeping tasks

Closes #4690

**Comment 8**

1. **Sebastian Huber**, Fri, 05 Aug 2022 06:12:49 GMT

In c3c4525/rtems:

posix: Avoid dead code in clock\_nanosleep()

This issue was reported by Coverity Scan for RTEMS:

CID 1507760: Control flow issues (DEADCODE)

Closes #4690.

**4691 - Add support for FACE Technical Standard Restriction on POSIX Absolute Timers**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4691">https://devel.rtems.org/ticket/4691</a> ( <a href="https://devel.rtems.org/ticket/4691">https://devel.rtems.org/ticket/4691</a> )
<b>Id</b>	4691
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	1 August 2022 15:13:58
<b>Modified</b>	31 October 2023 11:49:58
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

## Overview

Most of the time, the FACE Technical Standard (<https://opengroup.org/face>) defines a subset (e.g. profile) of a standard. It currently includes four profiles of the POSIX 1003.1-2008 standard with a few optional features like multiple processes and IPV6. However, in one case, it defines an error case for something POSIX defines as required behavior. This ticket is intended to track adding support for an application being able to configure whether it wants the POSIX behavior or that defined by the FACE Technical Standard.

## FACE Technical Standard Requirements

POSIX allows for setting a timer on CLOCK\_REALTIME[1] while the FACE Technical Standard defines this as an error. This behavior and deviation from POSIX has been in the FACE Technical Standard since the beginning and was present in Edition 1.0[2]. This is the language from Edition 1.0 of the FACE Technical Standard which was written in the tone of a white paper rather than as a set of requirements:

3.9.4 Time Management

Partial support for the POSIX CLOCK\_REALTIME, which permits a calendar-based clock time to be set that becomes available to all partitions. Due to safety and security-related considerations in the POSIX definitions of this clock's behavior, the configuration data will specify which partitions (preferably one partition) have permissions to set (using the clock\_settime API) this clock. All partitions may have access to read this clock, but an error will be returned for any partition that attempts to set an alarm based on this clock that is based on absolute time (setting of an alarm based on a relative time is supported). Partitions authorized to set the calendar time will also be authorized to set the time zone value that is visible to all other partitions.

Subsequent editions of the FACE Technical Standard have fine-tuned the language and made requirements clearer with simpler direct "shall" statements.

Also, although the term OSS UoC was defined in Edition 1.0, the requirements now use this acronym for Operating System Segment Unit of Conformance to refer to the operating system and foundational services. Other types of segments are defined for applications, communications, and device management. In Edition 3.1[3], the language has the same intent as Edition 1.0 but the requirements are stated in a more direct and clearer manner.

#### 4.1.1.3 OSS POSIX Clock Requirements

An OSS UoC provides support for POSIX clocks.

- An OSS UoC shall support the POSIX Monotonic Clock option (CLOCK\_MONOTONIC), including setting absolute and relative timers on this clock.
- An OSS UoC shall support clock read-access based POSIX CLOCK\_REALTIME clock (calendar-based clock time).
- An OSS UoC shall support setting a relative timer-based POSIX CLOCK\_REALTIME clock (calendar-based clock time).
- An OSS UoC shall support clock time write access for POSIX CLOCK\_REALTIME clock value under the constraint that configuration data specifies the partition is authorized to set the clock time (using the clock\_settime() API).

Note: The time value set by one partition becomes visible to all other partitions. The timezone value set by one POSIX process using the tzset() or setenv() APIs is local to that POSIX process.

- An OSS UoC shall return an error when a software component attempts to set an absolute timer on the POSIX CLOCK\_REALTIME clock.

Note: The behavior is necessary (e.g., to prevent backwards and forwards shifts in sequential timers) due to the setting of POSIX\_CLOCK\_REALTIME clock impacting all partitions.

The use of the word "partition" is intentional because the FACE Technical Standard includes ARINC 653 and POSIX standards. ARINC 653 defines a time and space partitioned real-time environment. POSIX or ARINC 653 applications can be hosted in a partition. In three of the four profiles, ARINC 653 is required while in the fourth it is optional. RTEMS can be hosted in an ARINC 653 partition using a paravirtualized configuration with a BSP that adapts it to the environment.

The requirement being addressed by this ticket is (5) since RTEMS currently meets the other requirements. (5) contradicts the POSIX standard and modifying RTEMS to not support absolute POSIX timers is not an acceptable option.

#### Proposed Solution

The proposed solution is to add a confdefs.h configure option that enables this behavior when the OSS UoC (e.g. operating system) must provide FACE conformant behavior. When not defined, the POSIX behavior will be in effect.

This will require additions to the confdefs.h family of headers, adding a test, and updating documentation.

#### References

- [1] POSIX timer\_create - [https://pubs.opengroup.org/onlinepubs/9699919799/functions/timer\\_create.html](https://pubs.opengroup.org/onlinepubs/9699919799/functions/timer_create.html)
- [2] FACE Technical Standard, Edition 1.0. January 2012. <https://publications.opengroup.org/c122>.
- [3] FACE Technical Standard, Edition 3.1. July 2020. <https://publications.opengroup.org/c207>.

#### Comment 1

1. **Chris Johns**, Tue, 02 Aug 2022 01:24:38 GMT

What structure and naming convention do you propose for confdefs.h?

Could I configure the following to get all FACE related configures enabled:

```
#define CONFIGURE_FACE
```

?

#### Comment 2

1. **Joel Sherrill**, Wed, 10 Aug 2022 19:07:27 GMT

In 4b04589b/rtems:

```
Add support for CONFIGURE_POSIX_TIMERS_FACE_BEHAVIOR
```

This adds the configure option CONFIGURE\_POSIX\_TIMERS\_FACE\_BEHAVIOR which allows the application to choose whether to have the POSIX timer\_create() function follow the behavior defined by POSIX or the FACE Technical Standard.

```
Updates #4691.
```

#### Comment 3

1. **Duc Doan**, Thu, 11 Aug 2022 05:46:29 GMT

In c655c72d/rtems:

```
build/cpukit: Add confdefs/face.h to install rule
```

```
Updates #4691
```

#### Comment 4

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



1. **Joel Sherrill**, Thu, 11 Aug 2022 18:01:47 GMT

In 996d18c/rtems:

```
psxtimer_face01: Improve coverage and documentation
Updates #4691.
```

#### **Comment 5**

1. **Sebastian Huber**, Wed, 31 Aug 2022 11:09:53 GMT

In b3d2e3fe/rtems:

```
config: Include on demand
Updates #4691.
```

#### **Comment 6**

1. **Joel Sherrill**, Mon, 05 Sep 2022 06:47:03 GMT

In b1fd623/rtems-central:

```
Add POSIX Timer FACE Behavior Configuration
Updates #4691.
```

#### **Comment 7**

1. **Sebastian Huber**, Mon, 05 Sep 2022 06:47:04 GMT

In 1a5be0d/rtems-central:

```
spec: Add glossary link
Updates #4691.
```

#### **Comment 8**

1. **Sebastian Huber**, Mon, 05 Sep 2022 06:48:21 GMT

In b06ec5b6/rtems:

```
config: Document CONFIGURE_POSIX_TIMERS_FACE_BEHAVIOR
Update #4691.
```

#### **Comment 9**

1. **Joel Sherrill**, Mon, 05 Sep 2022 06:53:06 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 4f9e9e5/rtems-docs:

```
c-user/config/face.rst: New file -- add CONFIGURE_POSIX_TIMERS_FACE_BEHAVIOR
Closes #4691.
```

#### **Comment 10**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:49:58 GMT

2. **keywords**: **qualification** added

---

## **4693 - Remove ILP32 aarch64/xilinx\_versal\_&#42 BSPs**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4693">https://devel.rtems.org/ticket/4693</a> ( <a href="https://devel.rtems.org/ticket/4693">https://devel.rtems.org/ticket/4693</a> )
<b>Id</b>	4693
<b>Reporter</b>	Chris Johns
<b>Created</b>	2 August 2022 02:45:54
<b>Modified</b>	22 August 2022 21:51:43
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The BSPs:

- aarch64/xilinx\_versal\_ilp32\_qemu
- aarch64/xilinx\_versal\_ilp32\_vck190

support ILP32 addressing and the Versal has default memory regions above the 4G address boundary. There is value in supporting ILP32 if there is not practical use for it.

If a use case is identified they can be added back.

**Comment 1**

1. **Chris Johns**, Sun, 21 Aug 2022 23:40:09 GMT

I will rename the aarch64/xilinx\_versal\_ilp64\_qemu to aarch64/xilinx\_versal\_qemu and aarch64/xilinx\_versal\_ilp64\_vck190 to aarch64/xilinx\_versal\_vck190

**Comment 2**

1. **Chris Johns**, Sun, 21 Aug 2022 23:43:02 GMT

I will add aarch64/xilinx\_versal\_aiedge as a generic BSP. The AI Edge series product range Xilinx Versal has the same scalar processors on all variants.

**Comment 3**

1. **Chris Johns**, Mon, 22 Aug 2022 21:51:43 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In dee5ea81/rtems:

```
bsps/xilinx/versal: Remove IPL32 BSPs, add aiedge and change defaults
Versal has IO mapped to the upper 64bit address space and
needs full 64bit addresses. Add xilinx_versal_aiedge for custom hardware Make the hardware settings the defaults and qemu as variants
Closes #4693
```

---

**4694 - sptests/sp37 fails to compile if RTEMS\_SMP is not defined**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4694">https://devel.rtems.org/ticket/4694</a> ( <a href="https://devel.rtems.org/ticket/4694">https://devel.rtems.org/ticket/4694</a> )
<b>Id</b>	4694
<b>Reporter</b>	Lucian-Raul Silistru
<b>Created</b>	2 August 2022 14:47:10
<b>Modified</b>	8 August 2022 09:59:01
<b>Owner</b>	joel@...
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Issue seems to be caused by lines 191-193 and 207 in testsuites/sptests/sp37/init.c

- name is undefined
- `_ISR_lock_Initialize` is "(void)name"

In file included from `../../../../../../../../RTEMS/cpukit/include/rtems/rtems/intr.h:70`,

```
from ../../../../../../RTEMS/cpukit/include/rtems.h:69,
from ../../../../../../RTEMS/bsps/include/bsp/default-initial-extension.h:40,
from ../../../../../../RTEMS/bsps/myriad2/ma2x8x/include/bsp.h:27,
from ../../../../../../RTEMS/testsuites/support/include/tmacros.h:41,
from ../../../../../../RTEMS/testsuites/sptests/sp37/system.h:35,
from ../../../../../../RTEMS/testsuites/sptests/sp37/init.c:41:
```

`../../../../../../../../RTEMS/testsuites/sptests/sp37/init.c`: In function 'test\_isr\_locks':  
`../../../../../../../../RTEMS/testsuites/sptests/sp37/init.c:207:42: error: 'name' undeclared (first use in this function)`

```
207 | _ISR_lock_Initialize( &container.lock, name );
```

```
|~
```

`../../../../../../../../RTEMS/cpukit/include/rtems/score/isrlock.h:202:12: note: in definition of macro '_ISR_lock_Initialize'`

```
202 | (void) _name
```

```
|
```

`../../../../../../../../RTEMS/testsuites/sptests/sp37/init.c:207:42: note: each undeclared identifier is reported only once for each function it appears in`

```
207 | _ISR_lock_Initialize( &container.lock, name );
```

```
|~
```

`../../../../../../../../RTEMS/cpukit/include/rtems/score/isrlock.h:202:12: note: in definition of macro '_ISR_lock_Initialize'`

```
202 | (void) _name
```

```
|
```

### **Comment 1**

1. **Joel Sherrill**, Tue, 02 Aug 2022 17:51:36 GMT

This report appears to be against an architecture and BSP (myriad2/ma2x8x) that are not in the RTEMS.org source base. I have built two other non-SMP BSPs this week (mips and powerpc) and the weekly BSP build sweeps would also catch a general or BSP specific build issue.

The ISR method definitions are part of the architecture port. My guess is that you are dropping the architecture and BSP code into a git clone from rtems.org and that the myriad2/ma2x8x code is not up to date.

### **Comment 2**

1. **Lucian-Raul Silistru**, Wed, 03 Aug 2022 16:05:16 GMT

Thanks for confirmation that it should work.

Figured it was cherrypick from an older version that broke it for us. Once removed we don't see the issue anymore.

### **Comment 3**

1. **Lucian-Raul Silistru**, Mon, 08 Aug 2022 09:59:01 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **invalid**

## **4695 - Automatic version numbers in the documentation**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4695">https://devel.rtems.org/ticket/4695</a> ( <a href="https://devel.rtems.org/ticket/4695">https://devel.rtems.org/ticket/4695</a> )
<b>Id</b>	4695
<b>Reporter</b>	Chris Johns
<b>Created</b>	3 August 2022 03:42:50
<b>Modified</b>	19 December 2023 20:41:52
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

There is no easy means to add the current version number to the documentation using the Sphinx. The supported directives and variables are fine in the documentation however they are not applied in the code blocks.

Provide a means to support a version number that can be used in the documentation and code blocks.

We should also review the documentation code blocks and find ways to include content that does not vary from version to version.

**Comment 1**

1. **Chris Johns**, Thu, 04 Aug 2022 21:50:09 GMT

In c935a2c/rtems-docs:

```
building: Add support for an RTEMS version number
Support using a version number for RTEMS documentation
Updates #4695
```

**Comment 2**

1. **Chris Johns**, Thu, 04 Aug 2022 21:50:11 GMT

In e551cc7/rtems-docs:

```
versions: Update aarch64
Updates #4695
```

**Comment 3**

1. **Chris Johns**, Thu, 04 Aug 2022 21:50:12 GMT

In f028448/rtems-docs:

```
versions: Update arm
Updates #4695
```

**Comment 4**

1. **Chris Johns**, Thu, 04 Aug 2022 21:50:14 GMT

In 3859073/rtems-docs:

```
versions: Update microblaze, powerpc, riscv and x86_64
Updates #4695
```

**Comment 5**

1. **Chris Johns**, Thu, 04 Aug 2022 21:50:15 GMT

In 1d6dcf8/rtems-docs:

```
versions: Update user manual
Updates #4695
```

**Comment 6**

1. **Chris Johns**, Tue, 29 Nov 2022 22:50:56 GMT
2. **severity**: changed from **normal** to **blocker**

We need to complete this to make a 6.1 release.

**Comment 7**

1. **Chris Johns**, Tue, 29 Nov 2022 22:52:11 GMT
2. **priority**: changed from **normal** to **high**

**Comment 8**

1. **Chris Johns**, Tue, 19 Dec 2023 20:41:52 GMT

In e4a0de6/rtems-docs:

```
user: Automatic version number fixes
Updates #4695
```

**4697 - Documentation for libbsd Configure options**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4697">https://devel.rtems.org/ticket/4697</a> ( <a href="https://devel.rtems.org/ticket/4697">https://devel.rtems.org/ticket/4697</a> )
<b>Id</b>	4697
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	4 August 2022 20:43:26
<b>Modified</b>	29 November 2022 23:59:46
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	documentation, libbsd
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

libbsd appears to have some options to configure it similar to confdefs.h. We need user facing documentation on those options.

**Comment 1**

1. **Chris Johns**, Tue, 29 Nov 2022 23:59:46 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **invalid**

There are options in the README in LibBSD.

**4700 - Fix instances of "is" operator used with literals**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4700">https://devel.rtems.org/ticket/4700</a> ( <a href="https://devel.rtems.org/ticket/4700">https://devel.rtems.org/ticket/4700</a> )
<b>Id</b>	4700
<b>Reporter</b>	Ryan Long
<b>Created</b>	11 August 2022 18:45:34
<b>Modified</b>	12 August 2022 14:18:07
<b>Owner</b>	Ryan Long <ryan.long@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Python 3.8 introduced new warnings when using the "is" operator when comparing literals.

**Comment 1**

1. **Ryan Long**, Thu, 11 Aug 2022 18:53:29 GMT
2. **summary:** changed from **Fix instances of "is" operator used with literals** to **Fix instances of "is" operator used with literals**

**Comment 2**

1. **Ryan Long**, Fri, 12 Aug 2022 14:18:07 GMT
2. **owner:** set to **Ryan Long <ryan.long@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f3d9c87/rtems-tools:

```
rtemstoolkit: Fix conditions using "is" with literals
Fix warnings that come from python 3.8 about using the "is" operator with string literals.
Closes #4700
```

**4701 - Relocatable write data is placed in read-only region on some BSPs**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4701">https://devel.rtems.org/ticket/4701</a> ( <a href="https://devel.rtems.org/ticket/4701">https://devel.rtems.org/ticket/4701</a> )
<b>Id</b>	4701
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	12 August 2022 08:01:22
<b>Modified</b>	12 August 2022 08:02:07
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The .data.rel.ro\* linker input section pattern accidentally matches with writeable data those symbol name starts with "ro".

**Comment 1**

1. **Sebastian Huber**, Fri, 12 Aug 2022 08:02:07 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 21a36ed1/rtems:

bsps: Fix .data.rel.ro placement

The .data.rel.ro\* linker input section pattern accidentally matches with writeable data those symbol name starts with "ro".

Close #4701.

## 4702 - Fix warnings for indexing past array bounds (primarily validation tests)

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4702">https://devel.rtems.org/ticket/4702</a> ( <a href="https://devel.rtems.org/ticket/4702">https://devel.rtems.org/ticket/4702</a> )
<b>Id</b>	4702
<b>Reporter</b>	Ryan Long
<b>Created</b>	15 August 2022 19:39:21
<b>Modified</b>	22 June 2023 22:20:58
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Building for AArch64 it looks like most of the warnings are for indexing past the end of an array. Most are from the validation tests, but a few aren't. Hopefully they all have the same fix.

I attached the log file of the warnings.

### Attachments:

- 
- 1 **Ryan Long, Mon, 15 Aug 2022 19:40:54 GMT**  
attach: set to [errors2.txt](https://devel.rtems.org/ticket/4702/errors2.txt) (<https://devel.rtems.org/ticket/4702/errors2.txt>)

### Comment 1

- 1. **Joel Sherrill, Mon, 15 Aug 2022 20:08:18 GMT**

Per [https://bugzilla.redhat.com/show\\_bug.cgi?id=2047439](https://bugzilla.redhat.com/show_bug.cgi?id=2047439), do [0] arrays need to change to [1]?

### Comment 2

- 1. **Ryan Long, Tue, 16 Aug 2022 16:46:06 GMT**

Replying to Ryan Long:

Building for AArch64 it looks like most of the warnings are for indexing past the end of an array. Most are from the validation tests, but a few aren't. Hopefully they all have the same fix.

I forgot to add the BSP when I submitted this. I've been building RTEMS for xilinx\_zynqmp\_lp64\_qemu on AArch64.

### Comment 3

- 1. **Sebastian Huber, Wed, 31 Aug 2022 11:13:02 GMT**

In b1072f5/rtems:

```
validation: Ignore array bounds warnings
```

Update #4702.

### Comment 4

- 1. **Sebastian Huber, Mon, 05 Sep 2022 06:47:06 GMT**

In 654b3ee/rtems-central:

```
spec: Ignore array bounds warnings
```

Update #4702.

**Comment 5**

1. **Sebastian Huber**, Mon, 05 Sep 2022 06:48:23 GMT

In 9e9ce43d/rtems:

validation: Regenerate

Update #4702.

**Comment 6**

1. **Sebastian Huber**, Mon, 12 Sep 2022 07:27:54 GMT

In 4fdf79c/rtems:

score: Prevent an out of bounds warning

Update #4702.

**Comment 7**

1. **Chris Johns**, Tue, 29 Nov 2022 22:53:27 GMT

Can this be closed?

**Comment 8**

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:20:58 GMT

This will be closed before 6. If you wish to continue this before 7, clone.

**4703 - NetSNMP 5.7.2.1 Patch**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4703">https://devel.rtems.org/ticket/4703</a> ( <a href="https://devel.rtems.org/ticket/4703">https://devel.rtems.org/ticket/4703</a> )
<b>Id</b>	4703
<b>Reporter</b>	Chris Johns
<b>Created</b>	16 August 2022 06:22:40
<b>Modified</b>	16 August 2022 06:24:06
<b>Owner</b>	Chris Johns
<b>Type</b>	task
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

This ticket is a place holder for the NetSNMP patch moving it out of the rtems-tools repo.

**Attachments:**

1. **Chris Johns**, Tue, 16 Aug 2022 06:23:53 GMT  
**attach:** set to [rtems-net-snmp-5.7.2.1-20140623\\_patch](https://devel.rtems.org/ticket/4703/rtems-net-snmp-5.7.2.1-20140623_patch) ([https://devel.rtems.org/ticket/4703/rtems-net-snmp-5.7.2.1-20140623\\_patch](https://devel.rtems.org/ticket/4703/rtems-net-snmp-5.7.2.1-20140623_patch))

**Comment 1**

1. **Chris Johns**, Tue, 16 Aug 2022 06:24:06 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

**4705 - Installed header clean up**



---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4705">https://devel.rtems.org/ticket/4705</a> ( <a href="https://devel.rtems.org/ticket/4705">https://devel.rtems.org/ticket/4705</a> )
<b>Id</b>	4705
<b>Reporter</b>	Chris Johns
<b>Created</b>	19 August 2022 04:48:33
<b>Modified</b>	29 November 2022 22:52:49
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

A number of headers are installed when they should not or are not installed.

#### Comment 1

1. **Chris Johns**, Sun, 21 Aug 2022 23:30:10 GMT

In e49a1c9b/rtems:

```
spec/bsps: Do not install tm27.h
Updates #4705
```

#### Comment 2

1. **Chris Johns**, Sun, 21 Aug 2022 23:30:12 GMT

In bb09755/rtems:

```
spec/bsps/aarch64: Install ELF machine types for libdl
Updates #4705
```

#### Comment 3

1. **Chris Johns**, Sun, 21 Aug 2022 23:30:15 GMT

In eae542c0/rtems:

```
spec/librtemscpu: Fix installed headers
pci.h is only for sparc keyimpl.h is not referenced and so not needed
Updates #4705
```

#### Comment 4

1. **Chris Johns**, Tue, 29 Nov 2022 22:52:49 GMT
  2. **status**: changed from **assigned** to **closed**
  3. **resolution**: set to **fixed**
- 

## 4706 - Installed header break C++



In a329579/rtems:

cpukit/include: Fix including in C++

UPdates #4706

**Comment 5**

1. **Sebastian Huber**, Mon, 29 Aug 2022 07:05:55 GMT

In 23b42f7/rtems:

score: Fix format

Update #4706.

**Comment 6**

1. **Sebastian Huber**, Mon, 29 Aug 2022 07:10:17 GMT

In 9b16f24/rtems:

score: Fix format

Update #4706.

**Comment 7**

1. **Chris Johns**, Tue, 29 Nov 2022 22:53:46 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

**Comment 8**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:51:59 GMT
2. **keywords:** **qualification** added

**4710 - RSB does not expand dir type macros correctly**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4710">https://devel.rtems.org/ticket/4710</a> ( <a href="https://devel.rtems.org/ticket/4710">https://devel.rtems.org/ticket/4710</a> )
<b>Id</b>	4710
<b>Reporter</b>	Chris Johns
<b>Created</b>	28 August 2022 22:34:02
<b>Modified</b>	9 September 2022 01:32:29
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The expansion of the dir type macros is not done correctly. Macro replacement only appends the file part to the last element of a path list. For example:

```
%{mydir}/abc.cfg
```

with a path of:

```
%define mydir x:y:z
```

results in:

```
x:y:z/abc.cfg
```

The config load code handles this but it is wrong. The expansion of dir type macro variables should handle path separators (:) so you get:

```
x/abc.cfg:y/abc.cfg:z.abc.cfg
```

This has not been a problem in the RSB because the `_configdir` has only had two elements and the last one only ever had subdirectories.

**Comment 1**

1. **Chris Johns**, Fri, 09 Sep 2022 01:32:29 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 18b4507/rtems-source-builder:

```
sb/config: Correctly handle multiple config paths
Add rtems/config to the config directories searched to better
support deployment Correctly expand the configdir and path searches
Close #4710
```

**4712 - powerpc: Add AltiVec VRSAGE support**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4712">https://devel.rtems.org/ticket/4712</a> ( <a href="https://devel.rtems.org/ticket/4712">https://devel.rtems.org/ticket/4712</a> )
<b>Id</b>	4712
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	1 September 2022 08:09:42
<b>Modified</b>	8 September 2022 13:45:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/powerpc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The VRSAGE feature of the AltiVec unit can be used to reduce the amount of AltiVec registers which need to be saved/restored during interrupt processing and context switches.

**Comment 1**

1. **Sebastian Huber**, Thu, 08 Sep 2022 13:21:34 GMT

In be84706/rtems-source-builder:

```
6: Update GCC 10 and 12
Update #4712.
```

**Comment 2**

1. **Sebastian Huber**, Thu, 08 Sep 2022 13:45:01 GMT

In d907c22/rtems:

```
powerpc: Add support for VRSAGE
```

The VRSAGE feature of the AltiVec unit can be used to reduce the amount of AltiVec registers which need to be saved/restored during interrupt processing and context switches.

In order to use the VRSAGE optimization a corresponding multilib (-mvrsave) is required, see GCC configuration. The -mvrsave option must be added to the ABI\_FLAGS of the BSP.

```
Currently only the -mcpu=e6500 based QorIQ BSP support this optimization.
Update #4712.
```

**Comment 3**

1. **Sebastian Huber**, Thu, 08 Sep 2022 13:45:03 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 52d566c/rtems:

```
bsp/qorIQ: Enable VRSAGE optimization
```

Close #4712.

---

## **4713 - Make pthread\_atfork follow FACE Technical Standard Behavior for Single Process Environments**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4713">https://devel.rtems.org/ticket/4713</a> ( <a href="https://devel.rtems.org/ticket/4713">https://devel.rtems.org/ticket/4713</a> )
<b>Id</b>	4713
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	2 September 2022 16:38:18
<b>Modified</b>	6 September 2022 22:22:09
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	posix
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

The POSIX specification for pthread\_atfork() does not address the behavior when in a single process environment. The RTEMS implementation was an arbitrary decision on our part with no basis from the wider POSIX community. The FACE Technical Standard includes profiles without multiple process support and has defined the behavior for this method as follows:

When multiple POSIX processes are supported, pthread\_atfork(), the functionality is per the POSIX standard. When multiple POSIX processes are not supported, pthread\_atfork() should return 0. The provision to support only a single process is not addressed in the POSIX standard.

The RTEMS implementation currently returns ENOSYS instead of 0.

This ticket is to track the change to RTEMS and the documentation.

### **Comment 1**

1. **Joel Sherrill**, Tue, 06 Sep 2022 21:59:42 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In dbba9430/rtems:

```
pthread_atfork(): Change to behavior from FACE Technical Standard  
Closes #4713.
```

### **Comment 2**

1. **Joel Sherrill**, Tue, 06 Sep 2022 22:22:09 GMT

In 8741d2c/rtems-docs:

```
posix-users/process_creation_and_execution.rst: Update pthread_atfork()  
Updates #4713.
```

---

## **4714 - Use waf for LwIP walk sources**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4714">https://devel.rtems.org/ticket/4714</a> ( <a href="https://devel.rtems.org/ticket/4714">https://devel.rtems.org/ticket/4714</a> )
<b>Id</b>	4714
<b>Reporter</b>	Chris Johns
<b>Created</b>	4 September 2022 23:00:35
<b>Modified</b>	30 November 2022 00:06:58
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	network/lwip
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The lwip.py support has a call to walk the source tree for source files. Waf supports glob'ing of sources so why not use that?

This ticket is to remove the walk.

### Comment 1

1. **Chris Johns**, Sun, 04 Sep 2022 23:01:12 GMT
2. **description:** modified (diff)

### Comment 2

1. **Kinsey Moore**, Wed, 30 Nov 2022 00:06:58 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

This was resolved with commit e02d02e2ce29379c2d4bfb15bd5b101e9bd58e8 to rtems-lwip.

## 4718 - Coverity issues in cpukit/libfs/src/ftpfs/tftpDriver.c

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4718">https://devel.rtems.org/ticket/4718</a> ( <a href="https://devel.rtems.org/ticket/4718">https://devel.rtems.org/ticket/4718</a> )
<b>Id</b>	4718
<b>Reporter</b>	Frank Kuehndel
<b>Created</b>	16 September 2022 16:47:28
<b>Modified</b>	2 December 2022 15:18:54
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	fs
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	lowest
<b>Severity</b>	trivial
<b>Keywords</b>	coverity
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Coverity indicates the following issues in cpukit/libfs/src/ftpfs/tftpDriver.c:

\_\_CID 1506523\_\_ (#1 of 1):

Unchecked return value from library (CHECKED\_RETURN)

• check\_return: Calling sendto(tp->socket, send\_buf, plen, 0, (struct sockaddr \*)&tp->farAddress, 16U) without checking return value. This library function may fail and return an error code.

```

727     sendto (
728         tp->socket,
729         send_buf,
730         plen,
731         0,
732         (struct sockaddr *) &tp->farAddress,
733         sizeof (tp->farAddress)
734     );

```

\_\_CID 1506522\_\_ (#1 of 1):

Unchecked return value from library (CHECKED\_RETURN)

- `check_return`: Calling `sendto(tp->socket, (char *)&msg, len, 0, (struct sockaddr *)to, 16U)` without checking return value. This library function may fail and return an error code.

```
529 sendto (tp->socket, (char *)&msg, len, 0, (struct sockaddr *)to, sizeof *to);
```

\_\_CID 1437618\_\_ (#1 of 3):

Unchecked return value from library (CHECKED\_RETURN)

- `check_return`: Calling `setsockopt(tp->socket, 65535, 4102, &tv, 16U)` without checking return value. This library function may fail and return an error code.

```
594 setsockopt (tp->socket, SOL_SOCKET, SO_RCVTIMEO, &tv, sizeof tv);
```

\_\_CID 1437618\_\_ (#2 of 3):

Unchecked return value from library (CHECKED\_RETURN)

- `check_return`: Calling `setsockopt(tp->socket, 65535, 4102, &tv, 16U)` without checking return value. This library function may fail and return an error code.

```
555 setsockopt (tp->socket, SOL_SOCKET, SO_RCVTIMEO, &tv, sizeof tv);
```

\_\_CID 1437618\_\_ (#3 of 3):

Unchecked return value from library (CHECKED\_RETURN)

- `check_return`: Calling `setsockopt(tp->socket, 65535, 4102, &tv, 16U)` without checking return value. This library function may fail and return an error code.

```
559 setsockopt (tp->socket, SOL_SOCKET, SO_RCVTIMEO, &tv, sizeof tv);
```

### Comment 1

1. **Frank Kühndel**, Fri, 02 Dec 2022 15:18:54 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 997ba1d9/rtems:

```
tftpDriver.c: Fix Coverity issues
```

```
CID 1506523: Unchecked return value from library (CHECKED_RETURN) CID 1506522: Unchecked return value from library (CHECKED_RETURN) CID 1437618: Unchecked return value from library (CHECKED_RETURN)
```

```
Close #4718
```

## 4724 - Git commit message format instructions

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4724">https://devel.rtems.org/ticket/4724</a> ( <a href="https://devel.rtems.org/ticket/4724">https://devel.rtems.org/ticket/4724</a> )
<b>Id</b>	4724
<b>Reporter</b>	Chris Johns
<b>Created</b>	26 September 2022 01:48:26
<b>Modified</b>	14 December 2022 23:26:53
<b>Owner</b>	Joel Sherrill
<b>Type</b>	task
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The Eng docs Creating A Patch references the Wiki. The content should be in the manual.

Note lots of git related bits are in the Eng manual and still on the Wiki so which is correct?

### Comment 1

1. **Chris Johns**, Tue, 29 Nov 2022 22:58:51 GMT

Add the how to make a commit to the Making Changes section of the Eng manual.

### Comment 2

1. **Joel Sherrill**, Tue, 13 Dec 2022 22:43:41 GMT

2. **summary:** changed from **Git commit message format instructions** to **Git commit message format instructions**

### Comment 3

1. **Joel Sherrill**, Wed, 14 Dec 2022 23:26:53 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In a3d7dd1/rtems-docs:

(The changeset message doesn't reference this ticket)

## 4726 - RSB decode exception stops build

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4726">https://devel.rtems.org/ticket/4726</a> ( <a href="https://devel.rtems.org/ticket/4726">https://devel.rtems.org/ticket/4726</a> )
<b>Id</b>	4726
<b>Reporter</b>	Chris Johns
<b>Created</b>	26 September 2022 05:38:51
<b>Modified</b>	30 September 2022 21:07:04
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	admin
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Building in a Rocky VM on FB 12 with 5 I got:

```
Traceback (most recent call last):
  File "/usr/lib64/python3.9/threading.py", line 973, in _bootstrap_inner
    self.run()
  File "/usr/lib64/python3.9/threading.py", line 910, in run
    self._target(*self._args, **self._kwargs)
  File "/opt/work/chris/rtems/rsb/rtems-source-builder.git/source-builder/sb/execute.py", line 204, in _readthread
    data = data.decode(sys.stdout.encoding)
UnicodeDecodeError: 'utf-8' codec can't decode byte 0xe2 in position 4095: unexpected end of data
```

If the data is corrupted or broken things stop. Fix to attempt to keep going.

This issue also effect rtems-tools.

### Comment 1

1. **Frank Kuhndel**, Thu, 29 Sep 2022 09:18:56 GMT

I have seen similar errors in special build environments. These two are from March 2022, RSB for RTEMS 6 (note the slight difference in the error message in the last line):

```
GIT BUILD HEAD: 4cdec141b1320a1e5a04b898e13e04c43ec233c3 ubuntu-nios2
DevTools: Build #124 ubuntu-nios2 (Mar 9, 2022, 12:38:59)
building: nios2-rtems6-gcc-0f001dd-newlib-85f2dca-x86_64-linux-gnu-1
21:08:10 Exception in thread _stderr[]:
21:08:10 Traceback (most recent call last):
21:08:10   File "/usr/lib/python3.8/threading.py", line 932, in _bootstrap_inner
21:08:10     self.run()
21:08:10   File "/usr/lib/python3.8/threading.py", line 870, in run
21:08:10     self._target(*self._args, **self._kwargs)
21:08:10   File "/home/minna/src/rtems-source-builder/source-builder/sb/execute.py", line 204, in _readthread
21:08:10     data = data.decode(sys.stdout.encoding)
21:08:10 UnicodeDecodeError: 'utf-8' codec can't decode byte 0xe2 in position 4095: unexpected end of data
```

```
GIT HEAD="6fe98f91d94bbf965bc0e78015585ff8823d17bd
BUILD ACTUAL RSB_OPTIONS="--with ada --with cxx --with objc --jobs=12"
building: v850-rtems6-gcc-0f001dd-newlib-d88cbd0-x86_64-linux-gnu-1
18:55:36 Exception in thread _stderr[]:
18:55:36 Traceback (most recent call last):
18:55:36   File "/usr/lib/python3.8/threading.py", line 932, in _bootstrap_inner
18:55:36     self.run()
18:55:36   File "/usr/lib/python3.8/threading.py", line 870, in run
18:55:36     self._target(*self._args, **self._kwargs)
18:55:36   File "/home/minna/src/rtems-source-builder/source-builder/sb/execute.py", line 204, in _readthread
18:55:36     data = data.decode(sys.stdout.encoding)
18:55:36 UnicodeDecodeError: 'utf-8' codec can't decode bytes in position 4094-4095: unexpected end of data
```

Setting the `__locale__` to any "only-one-byte-unicode" linke LANG=en\_US.iso885915 when invoking the source-builder avoids the error.

There is most likely no error in the input data but the loop decoding it has probably a bug. Unicode code points encoded in UTF-8 can be up to 4 bytes long. The input data is read by source-builder/sb/execute.py in blocks of 4096 bytes. I guess it cuts through a multi-byte code point with the first byte(s) at the end of the current block and the rest of the bytes in the beginning of the next block. Note that the error always points to the end of the block position 4095 or position 4094-4095. Moreover, byte 0xe2 indicates that this is not the last byte of the code point (0xe2 is the first byte of a 3 byte code point?).

I know in Linux there exist some GNU Unicode decoding function which keeps a state between consecutive calls. This function is intended for use in cases where not the complete text can be decoded at once. I guess there is such a function for Python too. An alternative may be to read and decode the input in one large piece.



**Comment 2**

1. **Chris Johns**, Thu, 29 Sep 2022 09:26:56 GMT

Thanks for input and feedback. I agree with what you are saying.

The input can be in hundreds of mega so that is not practical to hold it until the end. This code is a performance hot spot so what happens needs to be kept as simple as possible.

Would you be able to make a buffer of data I could test solution with?

**Comment 3**

1. **Chris Johns**, Thu, 29 Sep 2022 09:34:21 GMT

It looks like using Python codecs with streaming is the way to handle this.

Again thank you for the insights in how the data is handled.

**Comment 4**

1. **Frank Kuehndel**, Thu, 29 Sep 2022 10:00:33 GMT

I case this helps, this script

1) writes 4093 spaces (note the field with is 4094) 2) a single "A" character 3) A 4 byte unicode 4) A new line

```
env LANG=en_US.UTF-8 printf '%4094c\U0001F0A1\n' A >file.txt
```

You can visualize it:

```
$ wc file.txt
 1      1 4099 file.txt
$ hexdump -C file.txt
00000000  20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20  |          |
*
00000ff0  20 20 20 20 20 20 20 20 20 20 20 20 20 41 f0 9f  |          A..|
00001000  82 a1 0a                                     |...|
00001003
```

**Comment 5**

1. **Chris Johns**, Thu, 29 Sep 2022 10:22:52 GMT

Thanks. I have a patch I am testing. It uses the `codecs.getincrementaldecoder()` factory function to create a decoder that hold state across decodes.

**Comment 6**

1. **Chris Johns**, Thu, 29 Sep 2022 10:23:27 GMT

2. **description:** modified (diff)

**Comment 7**

1. **Chris Johns**, Thu, 29 Sep 2022 10:46:08 GMT

I am testing with this code:

```
import codecs
import sys
bad = True
if bad:
    data = ''
    with open('file.txt', 'rb') as f:
        while True:
            block = f.read(4096)
            data += block.decode(sys.stdout.encoding)
            if len(block) < 4096:
                break
    print(len(data), len(block))
else:
    decoder = codecs.getincrementaldecoder(sys.stdout.encoding)()
    data = ''
    with open('file.txt', 'rb') as f:
        while True:
            block = f.read(4096)
            data += decoder.decode(block)
            if len(block) < 4096:
                break
    print(len(data), len(block))
```

and I cannot generate a failure with `bad = True`.

**Comment 8**

1. **Frank Kuehndel**, Thu, 29 Sep 2022 11:05:33 GMT

When I paste your code in `f.py` with `bad = True` I get the error:

```
$ python f.py
Traceback (most recent call last):
  File "f.py", line 9, in
    data += block.decode(sys.stdout.encoding)
  File "/usr/lib64/python2.7/encodings/utf_8.py", line 16, in decode
    return codecs.utf_8_decode(input, errors, True)
UnicodeDecodeError: 'utf8' codec can't decode bytes in position 4094-4095: unexpected end of data
```

with bad = False it works:

```
$ python f.py
(4096, 3)
```

I tested on an OpenSUSE 15.4, file.txt produced by the line from comment 4. locale prints

```
$ locale
LANG=en_US.UTF-8
LC_CTYPE="en_US.UTF-8"
LC_NUMERIC="en_US.UTF-8"
LC_TIME="en_US.UTF-8"
LC_COLLATE=POSIX
LC_MONETARY="en_US.UTF-8"
LC_MESSAGES="en_US.UTF-8"
LC_PAPER="en_US.UTF-8"
LC_NAME="en_US.UTF-8"
LC_ADDRESS="en_US.UTF-8"
LC_TELEPHONE="en_US.UTF-8"
LC_MEASUREMENT="en_US.UTF-8"
LC_IDENTIFICATION="en_US.UTF-8"
LC_ALL=
```

### Comment 9

1. **Chris Johns**, Thu, 29 Sep 2022 11:12:41 GMT

Thanks for testing. I think the patch I posted to the devel list should fix this. If you could be so kind and review the patch I would appreciate it.

### Comment 10

1. **Chris Johns**, Thu, 29 Sep 2022 20:56:03 GMT

In d7fb57f/rtems-source-builder:

```
sb/execute: Use a decoder that maintains state across blocks
Update #4726
```

### Comment 11

1. **Chris Johns**, Fri, 30 Sep 2022 02:27:15 GMT

The change has broken a dry-run. There is no stdout and so no encoder. The incremental decoder needs an encoding.

### Comment 12

1. **Chris Johns**, Fri, 30 Sep 2022 21:07:04 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In e04c841/rtems-source-builder:

```
sb/execute: Fix incremental decoder with --dry-run
Closes #4726
```

---

## 4729 - Add 64bit address support to RTEMS FDT

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4729">https://devel.rtems.org/ticket/4729</a> ( <a href="https://devel.rtems.org/ticket/4729">https://devel.rtems.org/ticket/4729</a> )
<b>Id</b>	4729
<b>Reporter</b>	Chris Johns
<b>Created</b>	29 September 2022 05:35:06
<b>Modified</b>	27 November 2022 22:53:29
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

RTEMS's FDT wrapper does not handle the reg property correctly. Update to handle 64bit register addresses.

**Comment 1**

1. **Chris Johns**, Thu, 06 Oct 2022 04:33:38 GMT

The calls `rtems_fdt_prop_map` and `rtems_fdt_get_value` change to return a table `uintptr_t` values.

**Comment 2**

1. **Chris Johns**, Mon, 10 Oct 2022 00:30:12 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 40eb58f/rtems:

```
libmisc/rtems-fdt: Update to support 64bit addresses
Add support to get the parent address and size cells Provide support to get a reg prop address map Change getting a set of properties
to uintptr_t Improve the debug mode of the ls command to print all props
Closes #4729
```

**Comment 3**

1. **Chris Johns**, Tue, 11 Oct 2022 01:40:36 GMT

In fe104e39/rtems:

```
libmisc/rtems-fdt: Fix missing error string
Coverity CID 1515930 issue
Updates #4729
```

**Comment 4**

1. **Chris Johns**, Fri, 14 Oct 2022 02:33:37 GMT

In 580a3a6/rtems:

```
libmisc/rtems-fdt: Fix return error values
Updates #4729
```

**Comment 5**

1. **Chris Johns**, Sun, 27 Nov 2022 22:53:29 GMT

In 408dbeb/rtems:

```
libmisc/rtems-fdt: Support prop map items up to the size of uintptr_t
Updates #4729
```

---

**4730 - rtems-source-builder doesn't generate tar archives for all packages any more**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4730">https://devel.rtems.org/ticket/4730</a> ( <a href="https://devel.rtems.org/ticket/4730">https://devel.rtems.org/ticket/4730</a> )
<b>Id</b>	4730
<b>Reporter</b>	Christian Mauderer
<b>Created</b>	29 September 2022 07:49:53
<b>Modified</b>	30 September 2022 21:07:06
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Like discussed in the following mailing list thread, the rtems-source-builder doesn't generate tar archives for all packages anymore:

<https://lists.rtems.org/pipermail/devel/2022-September/073369.html>

All RTEMS tools build sets 6/rtems-\* work fine except for 6/rtems-microblaze. devel/qemu and devel/dtc do not generate a tar archive. If the patch

<https://git.rtems.org/rtems-source-builder/commit?id=6205068c5a429e9ee1b471f4c8a3a119bb6757b2>

is reverted, the tar files are generated just like before.

**Comment 1**

1. **Chris Johns**, Thu, 29 Sep 2022 11:40:47 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 336f15c/rtems-source-builder:

```
sb/set-builder: Fix staging and tar file generation with a single config build
Closes #4730
```

**Comment 2**

1. **Chris Johns**, Fri, 30 Sep 2022 02:25:24 GMT
2. **version:** set to **6**
3. **milestone:** set to **6.1**

This has broken staging for multiple packages in a top level buildset.

**Comment 3**

1. **Chris Johns**, Fri, 30 Sep 2022 20:23:01 GMT
2. **status:** changed from **closed** to **reopened**
3. **resolution:** **fixed** deleted

The RSB is now not installing packages or internally staging them.

**Comment 4**

1. **Chris Johns**, Fri, 30 Sep 2022 21:07:06 GMT
2. **status:** changed from **reopened** to **closed**
3. **resolution:** set to **fixed**

In 953b839/rtems-source-builder:

```
sb/set-bulder: Fix installing builds when a single buildset
Always stage a build install if installable and outter most buildset instance
Closes #4730
```

**4732 - Set top in RSB version.py**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4732">https://devel.rtems.org/ticket/4732</a> ( <a href="https://devel.rtems.org/ticket/4732">https://devel.rtems.org/ticket/4732</a> )
<b>Id</b>	4732
<b>Reporter</b>	Chris Johns
<b>Created</b>	29 September 2022 08:15:17
<b>Modified</b>	29 September 2022 23:06:09
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Setting the top lets the code be used in deployment to get the version of the RSB being used. An RSB version lets a user track the exact tools being built and version numbers reported by the tools can match the packaged build, eg an rpm name and version info.

**Comment 1**

1. **Chris Johns**, Thu, 29 Sep 2022 23:06:09 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

<https://git.rtems.org/rtems-source-builder/commit/?id=cfed1659a297cb0f95a03e053345962097aa02bf>

---

**4736 - RISC-V - ISR\_stack allocation and usage by harts > CONFIGURE\_MAXIMUM\_PROCESSORS**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4736">https://devel.rtems.org/ticket/4736</a> ( <a href="https://devel.rtems.org/ticket/4736">https://devel.rtems.org/ticket/4736</a> )
<b>Id</b>	4736
<b>Reporter</b>	Lucian-Raul Silistru
<b>Created</b>	5 October 2022 15:38:19
<b>Modified</b>	22 June 2023 21:07:55
<b>Owner</b>	Hesham Almatary
<b>Type</b>	defect
<b>Component</b>	arch/riscv
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

When running SMP with CONFIGURE\_MAXIMUM\_PROCESSORS < total number of harts, the unused harts that start will allocate interrupt stacks from the sections following `.rtemsstack`. 16 bytes are used (written) while parking the core in `_CPU_Thread_Idle_body`.

Unallocated `_Per_CPU_Information` is also used but only for pointer math - this seems to work out fine.

It does seem like practically, with the default linkcmds, unless the cores are held/delayed by a debugger, they would never end up writing in memory before that memory is used - `.rtemsstack` is followed by `.work`.

Is this intended/known behaviour?

**Comment 1**

1. **Sebastian Huber**, Fri, 07 Oct 2022 05:06:16 GMT

This is a bug. The arm start.S does not have this issue for example.

**Comment 2**

1. **Sebastian Huber**, Fri, 07 Oct 2022 05:07:44 GMT
2. **milestone**: set to **6.1**

**Comment 3**

1. **Chris Johns**, Wed, 30 Nov 2022 00:03:38 GMT

Status update?

**Comment 4**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:00:39 GMT
2. **owner:** set to **Hesham Almatary**
3. **status:** changed from **new** to **assigned**

Hesham.. can you please take a shot at this?

**Comment 5**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:07:55 GMT
2. **summary:** changed from **ISR\_stack allocation and usage by harts > CONFIGURE\_MAXIMUM\_PROCESSORS** to **RISC-V - ISR\_stack allocation and usage by harts > CONFIGURE\_MAXIMUM\_PROCESSORS**

**4741 - Fix GCC PR 107248**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4741">https://devel.rtems.org/ticket/4741</a> ( <a href="https://devel.rtems.org/ticket/4741">https://devel.rtems.org/ticket/4741</a> )
<b>Id</b>	4741
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	14 October 2022 13:04:19
<b>Modified</b>	15 October 2022 08:19:58
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

[https://gcc.gnu.org/bugzilla/show\\_bug.cgi?id=107248](https://gcc.gnu.org/bugzilla/show_bug.cgi?id=107248)

**Comment 1**

1. **Sebastian Huber**, Sat, 15 Oct 2022 08:19:57 GMT

In 36a3d88/rtems-source-builder:

```
6: Update GCC 10 and 12
```

```
Update #4741.
```

**Comment 2**

1. **Sebastian Huber**, Sat, 15 Oct 2022 08:19:58 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In e24641b/rtems-source-builder:

```
7: Update Binutils, GDB, and GCC
```

```
Close #4741.
```

**4744 - libdebugger arm backend does not single step**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4744">https://devel.rtems.org/ticket/4744</a> ( <a href="https://devel.rtems.org/ticket/4744">https://devel.rtems.org/ticket/4744</a> )
<b>Id</b>	4744
<b>Reporter</b>	Chris Johns
<b>Created</b>	25 October 2022 03:11:26
<b>Modified</b>	30 October 2022 20:52:30
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/debugger
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Single stepping with the ARM backend does not cleanly step instructions.

**Comment 1**

1. **Chris Johns**, Sun, 30 Oct 2022 20:52:30 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 18b1a591/rtems:

```
cpukit/libdebugger: Fix stepping on ARM architectures
```

```
Closes #4744
```

---

**4746 - Armv7-M SysTick clock driver uses off by one reload value**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4746">https://devel.rtems.org/ticket/4746</a> ( <a href="https://devel.rtems.org/ticket/4746">https://devel.rtems.org/ticket/4746</a> )
<b>Id</b>	4746
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	26 October 2022 09:31:03
<b>Modified</b>	26 October 2022 09:36:01
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	4.11
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description****Comment 1**

1. **Dariusz Sabala**, Wed, 26 Oct 2022 09:36:01 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 1eae6f2/rtems:

```
bsps/arm: fix Cortex-M7 systick reload value
see ARM DUI 0646C Arm Cortex-M7 Devices Generic User Guide
"The RELOAD value is calculated according to its use.
For example, to generate a multi-shot timer with a period
of N processor clock cycles, use a RELOAD value of N-1.
If the SysTick? interrupt is required every 100 clock pulses,
set RELOAD to 99." see routines used in CMSIS project for reference
Close #4746.
```

---

**4750 - Linker discards RTEMS\_SYSCALL\_ITEM object**

**4750 - Linker discards RTEMS\_SYSINIT\_ITEM object**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4750">https://devel.rtems.org/ticket/4750</a> ( <a href="https://devel.rtems.org/ticket/4750">https://devel.rtems.org/ticket/4750</a> )
<b>Id</b>	4750
<b>Reporter</b>	dsa93
<b>Created</b>	4 November 2022 13:40:35
<b>Modified</b>	7 November 2022 15:00:32
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Hi

I am developing device driver in custom BSP in RTEMS.  
I applied my BSP on top of master branch.

My driver code looks like this:

```
/* driver logic in "static" functions (omitted) */
void custom_driver_init(void);
RTEMS_SYSINIT_ITEM(
  custom_driver_init,
  RTEMS_SYSINIT_DEVICE_DRIVERS,
  RTEMS_SYSINIT_ORDER_SEVENTH
);
```

It is discarded by linker. custom\_driver\_init is never called. I discovered hack how to make linker not discard this: if I put at least one extern linkage function and call it in other file then linker dont discard "custom\_driver\_init"

```
/* driver logic in "static" functions (omitted) */
/* Call this function for example from main function */
int workaraound(void) {
  return 5;
}
void custom_driver_init(void);
RTEMS_SYSINIT_ITEM(
  custom_driver_init,
  RTEMS_SYSINIT_DEVICE_DRIVERS,
  RTEMS_SYSINIT_ORDER_SEVENTH
);
```

Driver file compilation arguments:

```
-MMD,
-Wall,
-Wmissing-prototypes,
-Wimplicit-function-declaration,
-Wstrict-prototypes,
-Wnested-externs,
-O2,
-g,
-fdata-sections,
-ffunction-sections,
-mthumb,
-mcpu=cortex-m7,
-mfpu=fpv5-d16,
-mfloat-abi=hard,
-save-temps,
-Icpukit/include,
-I../../../../cpukit/include,
-Icpukit/score/cpu/arm/include,
-I../../../../cpukit/score/cpu/arm/include,
-IbSPS/include,
-I../../../../bSPS/include,
-IbSPS/arm/include,
-I../../../../bSPS/arm/include,
../../../../bSPS/arm/someplatform/console/console.c,
-c,
-DHAVE_CONFIG_H=1,
-DBOARD_MAINCK_FREQ_HZ=10000000
```

Application linkage files

```
/home/dsa/rtems/rsb-6/bin/arm-rtems6-gcc
-g
-mthumb
-mcpu=cortex-m7
-mfpu=fpv5-d16
-mfloat-abi=hard
-DBOARD_MAINCK_FREQ_HZ=10000000
-I/home/dsa/arm-rtems6/someplatform/lib/include
-B/home/dsa/arm-rtems6/someplatform/lib
-qrtems
-Wl,--gc-sections
-Wl,-Map=ecu-app.map,--print-memory-usage,--cref
CMakeFiles/ecu-app.dir/src/main.c.obj
-o ecu-app.elf
-lrtemsbsp
-lrtemscpu
```

I tried to research this topic and I am not sure if there is a way to prevent this optimisation, so I decided to post it here. I can provide you some more details or perform some tests



**Comment 1**

1. **Sebastian Huber**, Mon, 07 Nov 2022 15:00:08 GMT

If it is discarded through the linker garbage collection, then you probably use a custom linker command file which doesn't have the KEEP() directive.

If it is not linked in at all, then your application has no reference to the driver or you didn't add the driver to the objects list of the executable link.

Questions like this should be discussed on the mailing list.

**Comment 2**

1. **Sebastian Huber**, Mon, 07 Nov 2022 15:00:32 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **invalid**

**4751 - chmod problem in shell of RTEMS 6**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4751">https://devel.rtems.org/ticket/4751</a> ( <a href="https://devel.rtems.org/ticket/4751">https://devel.rtems.org/ticket/4751</a> )
<b>Id</b>	4751
<b>Reporter</b>	chenjin_zhong
<b>Created</b>	10 November 2022 00:49:30
<b>Modified</b>	26 December 2022 19:37:09
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4558:

Hi, I find one problem in rtems\_shell\_main\_chmod function. the usage of this instruction is described as "chmod 0777 n1 n2... #change filemode", .the src code is listed as follows. the bold part should be replaced with `__chmod(argv[n], mode)`?

```
static int rtems_shell_main_chmod(
  int argc,
  char *argv[]
)
{
  int          n;
  mode_t      mode;
  unsigned long tmp;
  if (argc < 2) {
    fprintf(stderr, "%s: too few arguments\n", argv[0]);
    return -1;
  }
  /*
   * Convert arguments into numbers
   */
  if ( rtems_string_to_unsigned_long(argv[1], &tmp, NULL, 0) ) {
    printf("Mode argument (%s) is not a number\n", argv[1] );
    return -1;
  }
  mode = (mode_t) (tmp & 0777);
  /*
   * Now change the files modes
   */
  for (n=2 ; n < argc ; n++)
    chmod(argv[n++], mode); /* <<<< here */
  return 0;
}
```

**Comment 1**

1. **Chris Johns**, Wed, 30 Nov 2022 00:05:18 GMT

2. **owner**: set to **Chris Johns**

3. **status**: changed from **new** to **assigned**

**Comment 2**

1. **zack leung**, Mon, 26 Dec 2022 19:37:09 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In c8c713c/rtems:

rtems\_shell\_main\_chmod: Correct argument indexing  
Closes #4751

---

## 4756 - Docs build system does not build singlehtml (cloned)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4756">https://devel.rtems.org/ticket/4756</a> ( <a href="https://devel.rtems.org/ticket/4756">https://devel.rtems.org/ticket/4756</a> )
<b>Id</b>	4756
<b>Reporter</b>	Chris Johns
<b>Created</b>	10 November 2022 22:05:05
<b>Modified</b>	6 December 2022 21:20:46
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Cloned from #4755:  
The configure logic does not handle the inliner detection correctly.

### Comment 1

1. **Chris Johns**, Wed, 30 Nov 2022 00:05:43 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

### Comment 2

1. **Chris Johns**, Tue, 06 Dec 2022 21:20:46 GMT
2. **owner**: set to **Chris Johns <chrisj@...>**

In 8f5f371/rtems-docs:

```
waf: Handle the enable options for singlehtml and ditaa/puml
Close #4756
```

---

## 4759 - TLS support is broken for ARMv6

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4759">https://devel.rtems.org/ticket/4759</a> ( <a href="https://devel.rtems.org/ticket/4759">https://devel.rtems.org/ticket/4759</a> )
<b>Id</b>	4759
<b>Reporter</b>	jkillelea
<b>Created</b>	14 November 2022 00:31:55
<b>Modified</b>	3 January 2023 07:53:06
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

I have found two possible memory exceptions under rtems\_shell\_init when running on the raspberry pi 1 BSP.

First, a possible null pointer dereference from getpwuid\_r(0, &pwd, NULL, 0, &pwd\_res); in rtems\_shell\_init\_once. The NULL pointer is never checked before it is used as a backing buffer for pwd.

Second, usage of stdin, stdout, and stderr cause memory exceptions in rtems\_shell\_run when used, for example shell\_env->parent\_stdin = stdin;.

#### Attachments:

1 **jkillelea**, Mon, 14 Nov 2022 00:32:43 GMT

**attach:** set to [getpwuid\\_r\\_patch.txt \(https://devel.rtems.org/ticket/4759/getpwuid\\_r\\_patch.txt\)](https://devel.rtems.org/ticket/4759/getpwuid_r_patch.txt)

#### Comment 1

1. **Chris Johns**, Wed, 30 Nov 2022 00:10:13 GMT
2. **component:** changed from **admin** to **shell**

#### Comment 2

1. **jkillelea**, Sun, 11 Dec 2022 15:06:45 GMT

It appears that raspberry pi does not support `_Thread_Local` attributes. Rebuilding GCC with the flag `--without_newlib_tls` seems to fix most errors. The null pointer error in `getpwuid_r` is actually ok, it's the call to set errno later in the function that causes failures.

#### Comment 3

1. **Sebastian Huber**, Thu, 15 Dec 2022 07:18:06 GMT

What happens if you run the `sptls01`, `sptls02`, and `sptls03` tests on this BSP?

After a tool update, did you recompile everything?

#### Comment 4

1. **jkillelea**, Sun, 18 Dec 2022 18:03:05 GMT

I recompiled everything with the same `--without_newlib_tls` flag, yes. That seemed to fix most issues. Certain miscellaneous packages fail to compile, but the kernel, BSP, and libbsd all work. I can reach an interactive terminal inside qemu now, and can reach the terminal prompt over serial on real hardware (unclear why I can't type yet, but that feels unrelated).

#### Comment 5

1. **Sebastian Huber**, Mon, 19 Dec 2022 06:43:45 GMT

Disabling the Newlib TLS configuration is really not a long term option. We should figure out why the TLS support is broken on this BSP. What happens if you run the `sptls01`, `sptls02`, and `sptls03` tests on this BSP?

#### Comment 6

1. **jkillelea**, Mon, 26 Dec 2022 23:22:52 GMT

```
Hi there, sorry for the delay. Here's the result of running each test on real hardware.
` * BEGIN OF TEST SPTLS 1 * * TEST VERSION:
6.0.0.240987228f7f7bab90c20efb8d219e26cf5f51c5 * TEST STATE: EXPECTED_PASS * TEST BUILD: RTEMS_POSIX_API * TEST TOOLS:
12.2.1 20221121 (RTEMS 6, RSB 65f83cf973d6f1f8974ea1818e653753b83eaea8, Newlib b9898fc)
```

```
__ * FATAL __ fatal source: 9 (RTEMS_FATAL_SOURCE_EXCEPTION)
```

```
R0 = 0x0000007b R8 = 0x770e8bde R1 = 0x0000000a R9 = 0x5f4cdb15 R2 = 0x00000001 R10 = 0xe38f3ff7 R3 = 0x0024c068 R11 = 0xb1bc579f R4 =
0x00000000 R12 = 0x01010101 R5 = 0x0000007b SP = 0x00303998 R6 = 0x00000008 LR = 0x00200600 R7 = 0x002001e8 PC = 0x0020059c CPSR =
0x600001d3 VEC = 0x00000004 RTEMS version: 6.0.0.240987228f7f7bab90c20efb8d219e26cf5f51c5 RTEMS tools: 12.2.1 20221121 (RTEMS 6, RSB
65f83cf973d6f1f8974ea1818e653753b83eaea8, Newlib b9898fc) executing thread ID: 0x09010001 executing th
```

```
` * BEGIN OF TEST SPTLS 2 * * TEST VERSION: 6.0.0.240987228f7f7bab90c20efb8d219e26cf5f51c5 * TEST STATE: EXPECTED_PASS *
TEST BUILD: RTEMS_POSIX_API * TEST TOOLS: 12.2.1 20221121 (RTEMS 6, RSB 65f83cf973d6f1f8974ea1818e653753b83eaea8, Newlib b9898fc)
A::globalCounter() = 0
```

```
__ * FATAL __ fatal source: 9 (RTEMS_FATAL_SOURCE_EXCEPTION)
```

```
R0 = 0x00000017 R8 = 0x00000000 R1 = 0x0000000a R9 = 0x00000000 R2 = 0x00003008 R10 = 0x00000000 R3 = 0x00000000 R11 = 0x00000000 R4 =
0x00226158 R12 = 0x00000000 R5 = 0x00302888 SP = 0x0030b290 R6 = 0x00000000 LR = 0x002006ac R7 = 0x00000000 PC = 0x00200ff0 CPSR =
0x20000153 VEC = 0x00000004 RTEMS version: 6.0.0.240987228f7f7bab90c20efb8d219e26cf5f51c5 RTEMS tools: 12.2.1 20221121 (RTEMS 6, RSB
65f83cf973d6f1f8974ea1818e653753b83eaea8, Newlib b9898fc) executing thread ID: 0x0a010001 executing th
```

```
` * BEGIN OF TEST SPTLS 3 * * TEST VERSION: 6.0.0.240987228f7f7bab90c20efb8d219e26cf5f51c5 * TEST STATE: EXPECTED_PASS *
TEST BUILD: RTEMS_POSIX_API * TEST TOOLS: 12.2.1 20221121 (RTEMS 6, RSB 65f83cf973d6f1f8974ea1818e653753b83eaea8, Newlib b9898fc)
```

```
__ * END OF TEST SPTLS 3 __
```

```
[ RTEMS shutdown ]`
```

GCC was compiled via rsb using the flag `--without_newlib_tls`, but the kernel was built from source. Couldn't find where to use the same flag for that.

#### Comment 7

1. **Sebastian Huber**, Tue, 03 Jan 2023 07:49:36 GMT
2. **owner:** set to **Sebastian Huber <sebastian.huber@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In f8cb1f48/rtems:

arm: Enable thread ID register for ARMv6  
Close #4759.

### **Comment 8**

1. **Sebastian Huber**, Tue, 03 Jan 2023 07:53:06 GMT
  2. **component**: changed from **shell** to **arch/arm**
  3. **summary**: changed from **RPi: crashes when shell starts** to **TLS support is broken for ARMv6**
- 

## **4760 - RSB fatal error on missing hash checksums**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4760">https://devel.rtems.org/ticket/4760</a> ( <a href="https://devel.rtems.org/ticket/4760">https://devel.rtems.org/ticket/4760</a> )
<b>Id</b>	4760
<b>Reporter</b>	Chris Johns
<b>Created</b>	15 November 2022 02:25:19
<b>Modified</b>	22 June 2023 21:17:53
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	reopened
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	high
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

The time has come to raise a fatal error if a hash is missing rather than a warning. This will stop missing checksums being present when releasing. It also makes it simpler to test releases for no missing checksums.

### **Comment 1**

1. **Joel Sherrill**, Thu, 09 Feb 2023 20:56:06 GMT  
Hasn't this been implemented?

### **Comment 2**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:14:45 GMT
  2. **status**: changed from **assigned** to **closed**
  3. **resolution**: set to **duplicate**
- Dupe of #4857

### **Comment 3**

1. **Chris Johns**, Thu, 22 Jun 2023 21:17:53 GMT
  2. **status**: changed from **closed** to **reopened**
  3. **resolution**: **duplicate** deleted
- Please check and then confirm before closing
- 

## **4762 - Add Versal SDHCI Arasan driver to libbsd**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4762">https://devel.rtems.org/ticket/4762</a> ( <a href="https://devel.rtems.org/ticket/4762">https://devel.rtems.org/ticket/4762</a> )
<b>Id</b>	4762
<b>Reporter</b>	Aaron N
<b>Created</b>	21 November 2022 22:22:47
<b>Modified</b>	22 November 2022 02:40:47
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Added support for SD card slots in libbsd for the Versal. Tested on VCK190.

**Attachments:**

- 
- Aaron N, Mon, 21 Nov 2022 22:26:26 GMT**  
**attach:** set to [0001-rtemsbsd-versal-Add-SDHCI-Driver-support.patch](https://devel.rtems.org/ticket/4762/0001-rtemsbsd-versal-Add-SDHCI-Driver-support.patch) (<https://devel.rtems.org/ticket/4762/0001-rtemsbsd-versal-Add-SDHCI-Driver-support.patch>)
  - Aaron N, Tue, 22 Nov 2022 01:35:29 GMT**  
**attach:** set to [0001-rtemsbsd-versal-Add-SDHCI-Driver-support-v2.patch](https://devel.rtems.org/ticket/4762/0001-rtemsbsd-versal-Add-SDHCI-Driver-support-v2.patch) (<https://devel.rtems.org/ticket/4762/0001-rtemsbsd-versal-Add-SDHCI-Driver-support-v2.patch>)
  - Aaron N, Tue, 22 Nov 2022 01:40:02 GMT**  
**attach:** set to [0001-rtemsbsd-versal-Add-SDHCI-Driver-support-v3.patch](https://devel.rtems.org/ticket/4762/0001-rtemsbsd-versal-Add-SDHCI-Driver-support-v3.patch) (<https://devel.rtems.org/ticket/4762/0001-rtemsbsd-versal-Add-SDHCI-Driver-support-v3.patch>)
  - Aaron N, Tue, 22 Nov 2022 01:47:04 GMT**  
**attach:** set to [v4-0001-rtemsbsd-versal-Add-SDHCI-Driver-support.patch](https://devel.rtems.org/ticket/4762/v4-0001-rtemsbsd-versal-Add-SDHCI-Driver-support.patch) (<https://devel.rtems.org/ticket/4762/v4-0001-rtemsbsd-versal-Add-SDHCI-Driver-support.patch>)
  - Aaron N, Tue, 22 Nov 2022 02:08:44 GMT**  
**attach:** set to [0001-rtems-versal-Updated-mmu-to-include-mapping-for-SDHC.patch](https://devel.rtems.org/ticket/4762/0001-rtems-versal-Updated-mmu-to-include-mapping-for-SDHC.patch) (<https://devel.rtems.org/ticket/4762/0001-rtems-versal-Updated-mmu-to-include-mapping-for-SDHC.patch>)
- 

**Comment 1**

- Aaron N, Mon, 21 Nov 2022 22:23:16 GMT**
- type:** changed from **defect** to **enhancement**

**Comment 2**

- Kinsey Moore, Tue, 22 Nov 2022 00:58:45 GMT**

The patch looks good to me.

**Comment 3**

- Kinsey Moore, Tue, 22 Nov 2022 01:16:11 GMT**

My only comment beyond that is that I should have renamed the existing Arasan base define and reused it instead of making RTEMS\_BSD\_DRIVER\_XILINX\_ZYNQMP\_SDHCI in rtems-bsd-nexus-bus.h when I added the driver to the ZynqMP platform.

**Comment 4**

- Kinsey Moore, Tue, 22 Nov 2022 01:20:30 GMT**

If you feel like fixing that, you could combine the existing RTEMS\_BSD\_DRIVER\_XILINX\_ZYNQMP\_SDHCI and RTEMS\_BSD\_DRIVER\_XILINX\_ZYNQ\_SDHCI along with RTEMS\_BSD\_DRIVER\_XILINX\_VERSAL\_SDHCI added in this patch into a single reused RTEMS\_BSD\_DRIVER\_ARASAN\_SDHCI.

**Comment 5**

- Aaron N, Tue, 22 Nov 2022 01:40:51 GMT**

Added your suggestion in, v3 has the name you suggested. Thanks.

**Comment 6**

- Kinsey Moore, Tue, 22 Nov 2022 01:43:41 GMT**

The v3 patch looks great, thanks!

**Comment 7**

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Aaron N**, Tue, 22 Nov 2022 02:09:14 GMT

Attached patch for MMU to map SDHCI devices for the Versal.

#### Comment 8

1. **Kinsey Moore**, Tue, 22 Nov 2022 02:10:26 GMT

That looks good as well.

#### Comment 9

1. **Aaron Nyholm**, Tue, 22 Nov 2022 02:39:24 GMT

In c5fa19e/rtems:

```
rtems/versal: Updated mmu to include mapping for SDHCI devices on versal
Tested on VCK190
Updates #4762
```

#### Comment 10

1. **Aaron Nyholm**, Tue, 22 Nov 2022 02:40:47 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In a39a6a2/rtems-libbsd:

```
rtemsbsd/versal: Add SDHCI Driver support
Tested on VCK190
Closes #4762
```

---

## 4763 - Detect terminal size

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4763">https://devel.rtems.org/ticket/4763</a> ( <a href="https://devel.rtems.org/ticket/4763">https://devel.rtems.org/ticket/4763</a> )
<b>Id</b>	4763
<b>Reporter</b>	Chris Johns
<b>Created</b>	22 November 2022 09:07:57
<b>Modified</b>	22 November 2022 19:49:00
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

Add support to set the rows and columns in the shell. RTEMS does not have a full tty system and does not carry terminfo so implement a shell based approach to let some commands manage the terminal size.

Update the edit command to support the terminal size.

Fix the help lines.

#### Comment 1

1. **Chris Johns**, Tue, 22 Nov 2022 19:49:00 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In 8425e67/rtems:

```
libmisc/shell: Support terminal size as env variables
```

## **4766 - Classic API User Guide Index has Functions without Parentheses**

---

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4766">https://devel.rtems.org/ticket/4766</a> ( <a href="https://devel.rtems.org/ticket/4766">https://devel.rtems.org/ticket/4766</a> )
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 November 2022 15:45:45
<b>Modified</b>	30 November 2022 23:26:07
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

Some index entries in the Classic API Users Guide has some method names without parentheses like `rtems_clock_get` instead of `rtems_clock_get()` which is used most of the time. Fix to improve consistency.

### **Comment 1**

1. **Joel Sherrill**, Wed, 30 Nov 2022 23:26:07 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In aaba6e5/rtems-docs:

```
c-user/*: Add trailing parentheses on methods in index which were missing it
Closes #4766.
```

---

## **4767 - Add rtems-lwip to release packages**

---

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4767">https://devel.rtems.org/ticket/4767</a> ( <a href="https://devel.rtems.org/ticket/4767">https://devel.rtems.org/ticket/4767</a> )
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 November 2022 20:56:56
<b>Modified</b>	4 January 2023 22:39:43
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	tool
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

The rtems-lwip repository is young but mature enough now to include in the release package. Please add it.

This should primarily related to the rtems-release repository.

### **Comment 1**

1. **Joel Sherrill**, Wed, 04 Jan 2023 22:39:43 GMT
  2. **description**: modified (diff)
- 

## **4768 - Use tarballs for stable versions development tools**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4768">https://devel.rtems.org/ticket/4768</a> ( <a href="https://devel.rtems.org/ticket/4768">https://devel.rtems.org/ticket/4768</a> )
<b>Id</b>	4768
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	30 November 2022 21:00:46
<b>Modified</b>	3 July 2023 21:54:59
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	reopened
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	4921

---

#### Description

Currently many of the individual tools in the development toolchain are using specified in the RSB using git hashes and not release versions. This is an issue for stable tool versions (e.g. 6) and release branches. Using git hashes is necessary for picking up bug fixes in some cases and should likely be the preference for the forward leaning tools (e.g. 7) but released versions with patches should be given preference.

Note: Newlib is acknowledged as likely always being a hash.

#### Comment 1

1. **Chris Johns**, Wed, 30 Nov 2022 21:02:25 GMT

I agree with this. Should the Eng doco be updated to reflect this as a policy?

#### Comment 2

1. **Joel Sherrill**, Mon, 20 Feb 2023 20:43:23 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **workforme**

Confirming that the RSB lists all tools as released versions except rtems-tools and newlib. See <https://git.rtems.org/rtems-source-builder/tree/rtems/config/6/rtems-default.bset> for details.

#### Comment 3

1. **Chris Johns**, Mon, 06 Mar 2023 03:40:26 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution**: **workforme** deleted

I am reopening this ticket. The severity is blocker and if a release is not to use upstream released tarball files we need a clear reason why.

The RSB is not using GCC released sources and the current `rtems/config/tools/rtems-gcc-10-newlib-head.cfg` shows this.

If you look at the 5.3 sources you will see gcc tarballs are used, eg `gcc-9.3.0.tar.xz`. As things are an RTEMS 6 release will end up with a file called `gnu-mirror-gcc-92b44cf.tar.gz`.

Where is the repo this comes from?

The name `gnu-mirror-gcc` is confusing unless you understand what is going on?

How do you track the integrity of the repo used once you manage to find it?

I think we should be using a GCC release tarball of code in releases.

#### Comment 4

1. **Chris Johns**, Mon, 03 Jul 2023 21:54:59 GMT
  2. **blockedby**: set to **4921**
- 

## **4769 - config: Add CONFIGURE\_RECORD\_INTERRUPTS\_ENABLED**



<b>Link</b>	<a href="https://devel.rtems.org/ticket/4769">https://devel.rtems.org/ticket/4769</a> ( <a href="https://devel.rtems.org/ticket/4769">https://devel.rtems.org/ticket/4769</a> )
<b>Id</b>	4769
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	1 December 2022 11:36:04
<b>Modified</b>	3 January 2023 14:51:55
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	config
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

```

/**
 * @brief This configuration option is a boolean feature define.
 *
 * In case
 *
 * * this configuration option is defined
 * * and #CONFIGURE_RECORD_PER_PROCESSOR_ITEMS is properly defined,
 * * then the interrupt event recording is enabled.
 *
 * @par Default Configuration
 * If this configuration option is undefined, then the described feature is not
 * enabled.
 *
 * @par Notes
 * The interrupt event recording generates interrupt entry and exit events when
 * interrupt entries are dispatched.
 */
#define CONFIGURE_RECORD_INTERRUPTS_ENABLED

```

### Comment 1

1. **Sebastian Huber**, Fri, 02 Dec 2022 09:13:28 GMT

In 71d1acd/rtems:

bsps/irq: Rename handler in dispatch table

The name handler table was a bit misleading after the last rework. Rename it to distach table. Update the documentation accordingly.

Update #4769.

### Comment 2

1. **Sebastian Huber**, Fri, 02 Dec 2022 09:13:31 GMT

In 0d5e41a/rtems:

bsps/irq: Add bsp\_interrupt\_get\_dispatch\_table\_slot()

Update #4769.

### Comment 3

1. **Sebastian Huber**, Fri, 02 Dec 2022 09:13:33 GMT

In c46fbb9/rtems:

config: Add CONFIGURE\_RECORD\_INTERRUPTS\_ENABLED

This enables the tracing of interrupt entry/exit events through an application configuration option. The interrupt processing can be viewed with Trace Compass using rtems-record-logging from the RTEMS Tools.

Update #4769.

### Comment 4

1. **Sebastian Huber**, Fri, 02 Dec 2022 09:14:41 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 47e1f6e/rtems-docs:

Document CONFIGURE\_RECORD\_INTERRUPTS\_ENABLED  
Close #4769.

**Comment 5**

1. **Sebastian Huber**, Fri, 02 Dec 2022 09:26:31 GMT

In 492c2d4/rtems-central:

spec: Specify CONFIGURE\_RECORD\_INTERRUPTS\_ENABLED  
Update #4769.

**Comment 6**

1. **Sebastian Huber**, Tue, 03 Jan 2023 14:51:55 GMT

In 074e287/rtems-central:

spec: Rename interrupt handler in dispatch table  
Update #4769.

**4771 - Versal UART issues**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4771">https://devel.rtems.org/ticket/4771</a> ( <a href="https://devel.rtems.org/ticket/4771">https://devel.rtems.org/ticket/4771</a> )
<b>Id</b>	4771
<b>Reporter</b>	Chris Johns
<b>Created</b>	5 December 2022 04:57:52
<b>Modified</b>	17 May 2023 04:23:43
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The Versal polled mode it broken when building. The disable all interrupt call is not built in polled mode.

The UART interrupt mode behaves differently with a small stand alone app than a full app with libbsd. A full application with libbsd seems to behave while the small app exhibit the "not tx interrupt on FIFO load" issue.

**Attachments:**

1 **Aaron N**, Mon, 05 Dec 2022 22:28:42 GMT

**attach:** set to [0001-aarch64-versal-Fix-uart-interrupt-issues.patch](https://devel.rtems.org/ticket/4771/0001-aarch64-versal-Fix-uart-interrupt-issues.patch) (<https://devel.rtems.org/ticket/4771/0001-aarch64-versal-Fix-uart-interrupt-issues.patch>)

---

**Comment 1**

1. **Chris Johns**, Thu, 09 Feb 2023 02:27:13 GMT

The UART IP is based on the standard ARM IP however Xilinx have finally reported to me the interrupts are not the same as the ARM IP. There is weird issue around needing to prime the FIFO to half plus one to generate the first TX interrupt.

Xilinx has confirmed this will not change across the range of ACAP devices.

The main issue this raises is using the UART for a specialized protocol and not a terminal where sending a number of carriage returns is harmless.

**Comment 2**

1. **Aaron N**, Wed, 17 May 2023 04:23:43 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

---

**4772 - Remove use of interval from rtems\_task\_wake\_after() documentation**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4772">https://devel.rtems.org/ticket/4772</a> ( <a href="https://devel.rtems.org/ticket/4772">https://devel.rtems.org/ticket/4772</a> )
<b>Id</b>	4772
<b>Reporter</b>	Chris Johns
<b>Created</b>	6 December 2022 22:35:30
<b>Modified</b>	20 July 2023 12:43:36
<b>Owner</b>	Kinsey Moore
<b>Type</b>	enhancement
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The Classic API documentation for `rtems_task_wake_after()` refers to an `__interval__` while the call accepts ticks. The exact interval is not known because the period of time to next tick is not known when the call is made.

- Clarify the wording
- Recommend new applications use the POSIX based calls `nanosleep()` and `clock_nanosleep()` for applications that have intervals in a time base rather than system ticks.

The Gemini, Verify the fidelity of RTEMS System Tick issue provides some back ground to this change.

**Comment 1**

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:03:49 GMT

This is requested as an outcome of RTEMS System Tick Resolution (#30) from NSF NOIRLab / Gemini. This is about verifying the fidelity of RTEMS System Tick. A recent test of our `systemTickTest` tool inside `GemUtils?` is discussed here.

[https://gitlab.com/nsf-noirlab/gemini/rtsw/epics-base/epics-base/uploads/3ef07e7417e9e14903de65fd91c8417f/EPICS\\_Task\\_Sleep-CCJ.pdf](https://gitlab.com/nsf-noirlab/gemini/rtsw/epics-base/epics-base/uploads/3ef07e7417e9e14903de65fd91c8417f/EPICS_Task_Sleep-CCJ.pdf)

The intent is to be clear it is "number of ticks" and not an arbitrarily precise "interval". Now that RTEMS can have nanosecond granularity this distinction becomes important.

**Comment 2**

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:04:43 GMT
2. **owner:** set to **Kinsey Moore**
3. **status:** changed from **new** to **assigned**

**Comment 3**

1. **Kinsey Moore**, Thu, 06 Jul 2023 18:40:05 GMT

In 981ba2d/rtems-docs:

```
c-user: Update references to rtems_task_wake_after
```

```
rtems_task_wake_after takes a parameter in terms of a count of clock ticks and not a measure in a subunit of seconds. This updates documentation to reflect that. This also makes obvious the caveat about the first tick wait not being a whole tick and points the user at a replacement for better accuracy.
```

```
Updates #4772
```

**Comment 4**

1. **Kinsey Moore**, Thu, 13 Jul 2023 20:15:22 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

**Comment 5**

1. **Kinsey Moore**, Thu, 20 Jul 2023 09:06:02 GMT

In 20fc133/rtems-central:

```
spec/wake-after: Update references to intervals
```

```
rtems_task_wake_after takes a parameter in terms of a count of clock ticks and not a measure in a subunit of seconds. This updates documentation to reflect that and recommends clock_nanosleep() for applications requiring sleep for a time-based duration instead of a count of clock ticks.
```

Updates #4772

### **Comment 6**

1. **Sebastian Huber**, Thu, 20 Jul 2023 09:06:29 GMT

In be789ee/rtems-docs:

c-user: Update copyright and use glossary terms

Updates #4772.

### **Comment 7**

1. **Kinsey Moore**, Thu, 20 Jul 2023 09:09:35 GMT

In 21429f6/rtems:

rtems: Update references to rtems\_task\_wake\_after

rtems task\_wake\_after takes a parameter in terms of a count of clock ticks and not a measure in a subunit of seconds. This updates documentation to reflect that. This also makes obvious the caveat about the first tick wait not being a whole tick and points the user at a replacement for better accuracy.

Updates #4772

### **Comment 8**

1. **Sebastian Huber**, Thu, 20 Jul 2023 12:41:48 GMT

In 63a5c19/rtems-docs:

c-user: Fix typo

Updates #4772.

### **Comment 9**

1. **Sebastian Huber**, Thu, 20 Jul 2023 12:43:36 GMT

In 4935659/rtems:

rtems: Fix typo

Update #4772.

---

## **4775 - RISC-V: Default RV64 BSPs to medany**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4775">https://devel.rtems.org/ticket/4775</a> ( <a href="https://devel.rtems.org/ticket/4775">https://devel.rtems.org/ticket/4775</a> )
<b>Id</b>	4775
<b>Reporter</b>	Hesham Almatary
<b>Created</b>	17 December 2022 16:43:37
<b>Modified</b>	2 March 2023 13:51:34
<b>Owner</b>	Hesham Almatary <hesham.almatary@...>
<b>Type</b>	enhancement
<b>Component</b>	arch/riscv
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	Sebastian Huber Joel Sherrill
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

Currently generic RISC-V BSPs (riscv/riscv) that start with rv64 and not rv64\_medany will start at 0x70000000. This adds high maintenance overhead and deviates from almost all other RISC-V-based OSes and baremetal program that start at 0x80000000. Further, testing now has to account for an extra parameter (medany or not) that doubles the number of BSPs need to be tested.

It would be ideal to reduce maintenance efforts by defaulting all RV64 BSPs to medany and make them start at 0x80000000 to run on both QEMU and Spike. Those that need other cmodels or start addresses could be customised (e.g., rv64imac would default to medany but rv64imac\_medlow won't).

**Attachments:**

---

**1 Hesham Almatary, Sat, 17 Dec 2022 16:44:20 GMT****attach:** set to [0001-Add-RTEMS-rv32-medany-support\\_patch \(https://devel.rtems.org/ticket/4775/0001-Add-RTEMS-rv32-medany-support\\_patch\)](https://devel.rtems.org/ticket/4775/0001-Add-RTEMS-rv32-medany-support_patch)

---

**Comment 1**

1. **Chris Johns**, Sat, 17 Dec 2022 21:36:18 GMT
2. **version:** set to **6**
3. **component:** changed from **admin** to **arch/riscv**
4. **milestone:** set to **6.1**

I have assigned this ticket to 6. Please move if not for 6.1.

**Comment 2**

1. **Hesham Almatary**, Wed, 21 Dec 2022 12:35:09 GMT
2. **description:** modified (diff)
3. **summary:** changed from **RISC-V: Default BSPs to medany** to **RISC-V: Default RV64 BSPs to medany**

**Comment 3**

1. **Hesham Almatary**, Fri, 23 Dec 2022 09:07:51 GMT

In dd28005/rtems:

```
spec/build/riscv: Default rv64* BSPs to medany cmodel

Currently generic RISC-V BSPs (riscv/riscv) that start with rv64 and not rv64*_medany will start at 0x70000000. This adds high
maintenance overhead and deviates from almost all other RISC-V-based OSes and baremetal programs that start at 0x80000000. Further,
testing now has to account for an extra parameter (medany or not) that doubles the number of BSPs need to be tested.

This commit defaults all RV64 BSPs to use medany code model to allow starting all BSPs at 0x80000000. BSPs that require different code
models and/or start addresses are custom and need to add their own entries.

Updates #4775
```

**Comment 4**

1. **Hesham Almatary**, Fri, 23 Dec 2022 09:07:54 GMT

In a430dd4/rtems:

```
spec/build/riscv: Start all riscv/riscv BSPs at 0x80000000

To follow other RISC-V-based OSes conventions. Delete generic BSPs that start at 0x70000000 as BSPs are now medany by default.

Updates #4775
```

**Comment 5**

1. **Hesham Almatary**, Mon, 09 Jan 2023 18:11:06 GMT
2. **owner:** set to **Hesham Almatary <hesham.almatary@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 6794f01/rtems-docs:

```
Docs: RISC-V Update rv64* BSPs to medany and 0x80000000 start address

Closes #4775
```

**Comment 6**

1. **Hesham Almatary**, Wed, 08 Feb 2023 07:13:22 GMT

In a735d42/rtems-tools:

```
RISC-V Default rv64* BSPs to medany and 0x80000000 start address

To run on both QEMU and Spike

Updates #4775
```

**Comment 7**

1. **Hesham Almatary**, Wed, 08 Feb 2023 07:13:23 GMT

In 7ee62e9/rtems-tools:

RISC-V: Test rv32i and rv32imafdc on QEMU

Updates #4775

**Comment 8**

1. **Sebastian Huber**, Thu, 02 Mar 2023 13:51:34 GMT

In 269562cf/rtems:

bsps/riscv: Use medany cmodel for 64-bit variants

Updates #4775.

**4778 - Deployed RSB does not find release version config**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4778">https://devel.rtems.org/ticket/4778</a> ( <a href="https://devel.rtems.org/ticket/4778">https://devel.rtems.org/ticket/4778</a> )
<b>Id</b>	4778
<b>Reporter</b>	Chris Johns
<b>Created</b>	18 December 2022 04:13:30
<b>Modified</b>	22 June 2023 22:05:43
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Cloned from #4777:

The RSB does not find the VERSION file when released.

**Comment 1**

1. **Chris Johns**, Sun, 18 Dec 2022 04:13:42 GMT

2. **summary**: changed from **Deployed RSB does not find release version config (cloned)** to **Deployed RSB does not find release version config**

**Comment 2**

1. **Chris Johns**, Thu, 22 Jun 2023 22:05:43 GMT

2. **status**: changed from **new** to **closed**

3. **resolution**: set to **fixed**

**4782 - Correct Issues in Rate Monotonic Manager Background Section**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4782">https://devel.rtems.org/ticket/4782</a> ( <a href="https://devel.rtems.org/ticket/4782">https://devel.rtems.org/ticket/4782</a> )
<b>Id</b>	4782
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	10 January 2023 15:10:34
<b>Modified</b>	17 January 2023 19:35:43
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Fix these issues:

- 11.2.5.1 last bullet is inverted logically. Non-periodic tasks must NOT displace periodic ones and should run in background at a logically lower priority.
- 11.2.5.4 - emphasis box needed on the second paragraph (after lead-in that ends with a colon)

**Comment 1**

1. **Joel Sherrill**, Tue, 17 Jan 2023 19:35:28 GMT

In f48f79d/rtems-docs:

c-user/rate-monotonic/background.rst: Correct logically inverted statement Also corrected a spot of formatting.

Closes #4782.

**Comment 2**

1. **Joel Sherrill**, Tue, 17 Jan 2023 19:35:43 GMT
  2. **status**: changed from **new** to **closed**
  3. **resolution**: set to **fixed**
- 

**4783 - Fix issues when compiling dtc with Cygwin**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4783">https://devel.rtems.org/ticket/4783</a> ( <a href="https://devel.rtems.org/ticket/4783">https://devel.rtems.org/ticket/4783</a> )
<b>Id</b>	4783
<b>Reporter</b>	Ryan Long
<b>Created</b>	16 January 2023 21:23:55
<b>Modified</b>	28 July 2023 13:51:26
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Currently, DTC is failing to build due to this check in checks.c. For some reason the argument into isxdigit is coming in as a char. I've brought it up to the maintainer, but he sees no reason to change it. Therefore, a patch is needed to get it to build.

```
1183 if (unitname[0] == '0' && isxdigit(unitname[1])) 1184 FAIL(c, dti, node, "unit name should not have leading 0s");
1185 }
```

**Attachments:**

1. **Ryan Long**, Mon, 16 Jan 2023 21:28:54 GMT  
**attach**: set to [0001-checks.c-Ensure-argument-is-an-integer.patch](https://devel.rtems.org/ticket/4783/0001-checks.c-Ensure-argument-is-an-integer.patch) (<https://devel.rtems.org/ticket/4783/0001-checks.c-Ensure-argument-is-an-integer.patch>)
  2. **Kinsey Moore**, Mon, 30 Jan 2023 17:11:39 GMT  
**attach**: set to [0001-checks.c-Ensure-argument-is-an-integer-v2.patch](https://devel.rtems.org/ticket/4783/0001-checks.c-Ensure-argument-is-an-integer-v2.patch) (<https://devel.rtems.org/ticket/4783/0001-checks.c-Ensure-argument-is-an-integer-v2.patch>)
-

**Comment 1**

1. **Sebastian Huber**, Tue, 17 Jan 2023 07:30:41 GMT

I can't find the associated thread on the DTC mailing list. Could you please provide a link?

**Comment 2**

1. **Joel Sherrill**, Fri, 20 Jan 2023 15:02:48 GMT

See <https://github.com/dgibson/dtc/issues/71> and I just posted. If you want to pile on, it would be appreciated. I don't think he sees the underlying issue.

Per <https://en.cppreference.com/w/c/string/byte/isxdigit>, the argument is an integer. GCC and LLVM warn for using a character as an array index and this is from the GCC manual.

```
-Wchar-subscripts
Warn if an array subscript has type char. This is a common cause of error, as programmers often forget that this type is signed on
some machines. This warning is enabled by -Wall.
```

**Comment 3**

1. **Kinsey Moore**, Mon, 30 Jan 2023 17:21:10 GMT

In afaeda7/rtems-source-builder:

```
dtc: Add patch to build for ticket 4783
```

```
This patch resolves a build error with dtc on cygwin until upstream adopts a fix.
```

**Comment 4**

1. **Sebastian Huber**, Tue, 25 Jul 2023 05:27:50 GMT

The patch makes no sense. You need an (unsigned char) cast. I added a comment to the dtc issue.

**Comment 5**

1. **Sebastian Huber**, Thu, 27 Jul 2023 11:09:59 GMT

See:

<https://github.com/dgibson/dtc/pull/105>

**Comment 6**

1. **Sebastian Huber**, Fri, 28 Jul 2023 13:51:08 GMT

Pull request was merged. The next release will fix the issue.

**Comment 7**

1. **Sebastian Huber**, Fri, 28 Jul 2023 13:51:26 GMT

2. **milestone**: changed from **Indefinite** to **6.1**

**4803 - Revert or Mark CAN API as experimental**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4803">https://devel.rtems.org/ticket/4803</a> ( <a href="https://devel.rtems.org/ticket/4803">https://devel.rtems.org/ticket/4803</a> )
<b>Id</b>	4803
<b>Reporter</b>	Gedare Bloom
<b>Created</b>	20 January 2023 22:37:10
<b>Modified</b>	27 July 2023 18:27:24
<b>Owner</b>	Gedare Bloom
<b>Type</b>	defect
<b>Component</b>	dev
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	karel@...
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**



The CAN API done in GSoC 2022 is not stable. There are some key deficiencies that need to be fixed, and they may cause the API to change. The API needs to be marked as experimental or reverted before it appears in a release.

**Comment 1**

1. **kgardas**, Sat, 21 Jan 2023 07:46:52 GMT
2. **cc: karel@...** added

**Comment 2**

1. **Gedare Bloom**, Thu, 27 Jul 2023 18:27:24 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In c1cad59/rtems:

Revert "cpukit/dev/can: Added CAN support"

This reverts commit cd91b37dce728b372f164355719a4e601e12e7b3.

Closes #4803.

**4818 - Incomplete Statement in "cpu->heir"**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4818">https://devel.rtems.org/ticket/4818</a> ( <a href="https://devel.rtems.org/ticket/4818">https://devel.rtems.org/ticket/4818</a> )
<b>Id</b>	4818
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	23 January 2023 11:42:22
<b>Modified</b>	24 January 2023 10:28:10
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

\_\_Description: \_\_ The assignment statement "cpu->heir = " is incomplete and missing a value and semicolon at the end. It is recommended to revise this statement to ensure the code is not broken by the missing semicolon.

The attached excel lists in a systematic way the sources where this issue applies.

\_\_Additional Notes: \_\_ This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-058.

\_\_File list (please check the attached excel for more information): \_\_ cpukit\score\src\threadcreateidle.c

**Attachments:**

- 1 **Daniel Páscoa, Mon, 23 Jan 2023 11:42:43 GMT**  
**attach:** set to [RTEMS-SMP-CODE-VER-058.xlsx](https://devel.rtems.org/ticket/4818/RTEMS-SMP-CODE-VER-058.xlsx) (<https://devel.rtems.org/ticket/4818/RTEMS-SMP-CODE-VER-058.xlsx>)

**Comment 1**

1. **Sebastian Huber**, Mon, 23 Jan 2023 13:06:26 GMT
2. **keywords:** **qualification** added

**Comment 2**

1. **Sebastian Huber**, Tue, 24 Jan 2023 10:26:25 GMT
2. **owner:** set to **Sebastian Huber** <sebastian.huber@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 9ecb73f/rtems:

score: Clarify code block

Do not use a chained assignment for code clarity.

Close #4818.

### Comment 3

1. **Sebastian Huber**, Tue, 24 Jan 2023 10:28:10 GMT
2. **version**: set to **6**
3. **component**: changed from **admin** to **score**
4. **milestone**: set to **6.1**

## 4820 - Hazardous cast

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4820">https://devel.rtems.org/ticket/4820</a> ( <a href="https://devel.rtems.org/ticket/4820">https://devel.rtems.org/ticket/4820</a> )
<b>Id</b>	4820
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	23 January 2023 11:45:27
<b>Modified</b>	24 January 2023 10:27:54
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Description: Converting a function pointer to a different type of pointer can lead to unpredictable and undefined behavior. It is important to note that attempting to convert a pointer to a function to a pointer of a different type of function is particularly dangerous and should be avoided.

The attached excel lists in a systematic way the sources where this issue applies.

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-079.

File list (please check the attached excel for more information): `__ bsp\shared\irq\irq-handler-iterate.c`  
`bsp\sparc\leon3\include\tm27.h`

### Attachments:

1. **Daniel Páscoa**, Mon, 23 Jan 2023 11:45:39 GMT  
**attach**: set to [RTEMS-SMP-CODE-VER-079.xlsx](https://devel.rtems.org/ticket/4820/RTEMS-SMP-CODE-VER-079.xlsx) (<https://devel.rtems.org/ticket/4820/RTEMS-SMP-CODE-VER-079.xlsx>)

### Comment 1

1. **Sebastian Huber**, Mon, 23 Jan 2023 13:06:26 GMT
2. **keywords**: **qualification** added

### Comment 2

1. **Sebastian Huber**, Tue, 24 Jan 2023 10:26:27 GMT
2. **owner**: set to **Sebastian Huber** <sebastian.huber@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 10ee41a8/rtems:

```
tm27: Avoid function pointer casts
```

```
Add TM27_USE_VECTOR_HANDLER to select the interrupt handler type used by the implementation.
```

Close #4820.

### Comment 3

1. **Sebastian Huber**, Tue, 24 Jan 2023 10:27:54 GMT
2. **version**: set to **6**
3. **component**: changed from **admin** to **test**

4. milestone: set to 6.1

## 4821 - Ubuntu Host Instructions Wrong

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4821">https://devel.rtems.org/ticket/4821</a> ( <a href="https://devel.rtems.org/ticket/4821">https://devel.rtems.org/ticket/4821</a> )
<b>Id</b>	4821
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	23 January 2023 23:41:33
<b>Modified</b>	25 January 2023 14:15:35
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The current instructions were reported to be as being broken in email. Filing a ticket to track.

So here is the quick start command line which is missing the work 'install' and some of the packages listed don't exist:  
<https://docs.rtems.org/branches/master/user/hosts/posix.html#xubuntu>

Here is the correct command line:

```
$ sudo apt install build-essential g++ gdb unzip pax bison flex texinfo python3-dev python-is-python3 libpython2-dev libncurses5-dev zlib1g-dev
ninja-build pkg-config
```

### Comment 1

1. **Joel Sherrill**, Wed, 25 Jan 2023 14:15:35 GMT
2. **owner:** set to **Joel Sherrill** <joel@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 68a44b2/rtems-docs:

```
user/hosts/posix.rst: Update Ubuntu instructions to 22.x
Closes #4821.
```

## 4822 - Function returning unchanged function input

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4822">https://devel.rtems.org/ticket/4822</a> ( <a href="https://devel.rtems.org/ticket/4822">https://devel.rtems.org/ticket/4822</a> )
<b>Id</b>	4822
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	24 January 2023 11:35:33
<b>Modified</b>	24 January 2023 18:24:52
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Description: These functions appear to be returning their input without making any changes. To improve their functionality, it is recommended to re-write them to return void.

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-057.

\_\_File: \_\_ cpukit\score\src\smc.c \_\_Function: \_\_ \_SMP\_Process\_message \_\_Line: \_\_ 284

#### Comment 1

1. **Sebastian Huber**, Tue, 24 Jan 2023 15:41:24 GMT
2. **owner**: set to **Sebastian Huber**
3. **status**: changed from **new** to **assigned**
4. **version**: set to **6**
5. **component**: changed from **admin** to **score**
6. **milestone**: set to **6.1**

#### Comment 2

1. **Sebastian Huber**, Tue, 24 Jan 2023 15:44:36 GMT
2. **keywords**: **qualification** added

#### Comment 3

1. **Sebastian Huber**, Tue, 24 Jan 2023 18:24:52 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 48f693a9/rtems:

```
score: Remove unused return value
```

```
Several SMP message processing functions returned a value. This value was always unused.
```

```
Close #4822.
```

## 4826 - Software Engineering Guide has broken Reference

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4826">https://devel.rtems.org/ticket/4826</a> ( <a href="https://devel.rtems.org/ticket/4826">https://devel.rtems.org/ticket/4826</a> )
<b>Id</b>	4826
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	27 January 2023 13:59:43
<b>Modified</b>	15 February 2023 20:33:57
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

Section 3, RTEMS Stakeholders, has a single paragraph which renders like this in the html at <https://docs.rtems.org/branches/master/eng/stakeholders.html>:

```
Please have a look at the Support and Contributing chapter of the ERROR: :r:url:`user`.
```

A bit of investigation shows that it is trying to link to <https://docs.rtems.org/branches/master/user/support/index.html>. That section appears to be there correctly.

Looking for documentation for the "r:url:" syntax, I could not find any on the net. I see 48 uses of "r:". I suspect but did not check that they all might be broken. What is "r:" and what makes it work?

#### Comment 1

1. **Joel Sherrill**, Fri, 27 Jan 2023 14:08:24 GMT
2. **owner**: set to **Chris Johns**
3. **status**: changed from **new** to **assigned**
4. **description**: modified (diff)

#### Comment 2

1. **Chris Johns**, Tue, 14 Feb 2023 22:17:00 GMT

You cannot have links like this to rolling released versions of the documentation in the documentation and it needs to be removed.

### Comment 3

1. **Chris Johns**, Tue, 14 Feb 2023 22:17:19 GMT

2. **owner**: changed from **Chris Johns** to **Joel Sherrill**

### Comment 4

1. **Sebastian Huber**, Wed, 15 Feb 2023 07:03:49 GMT

This `:_` stuff is implemented in `common/rtemsdomain.py`. It seems to be a Sphinx customization. It used to work at some point in time.

### Comment 5

1. **Chris Johns**, Wed, 15 Feb 2023 20:33:57 GMT

2. **owner**: changed from **Joel Sherrill** to **Chris Johns**

The domains could have been broken by me when I updated that code to handle the version number change.

I will take a look. My comment about URL links is related to references between different documents only. References in a document is supported.

Sorry for the confusion.

## 4828 - Macro defined but magic number used instead

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4828">https://devel.rtems.org/ticket/4828</a> ( <a href="https://devel.rtems.org/ticket/4828">https://devel.rtems.org/ticket/4828</a> )
<b>Id</b>	4828
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	27 January 2023 16:09:22
<b>Modified</b>	14 July 2023 10:01:06
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

**Description:** Each register has a dedicated SHIFT macro, however, it is not utilized in subsequent macro definitions where the shift operation is performed. To improve consistency and maintainability, consider incorporating the defined shift macro in the subsequent macro definitions instead of using hardcoded shift values.

**Additional Notes:** These findings are related to the fact that a bunch of macros like `AHBSTAT_AHBS_HMASTER_SHIFT` are defined and then are not used right in the next few lines.

```
#define AHBSTAT_AHBS_HMASTER_SHIFT 3
#define AHBSTAT_AHBS_HMASTER_MASK 0x78U
#define AHBSTAT_AHBS_HMASTER_GET( _reg ) \
```

```
(( _reg ) >> 3 ) & 0xfU )
```

```
#define AHBSTAT_AHBS_HMASTER( _val ) ( ( _val ) << 3 )
```

As stated, in every one of these files, "This file is part of the RTEMS quality process and was automatically generated". There are YAML files where these registers are defined and the Waf build system generates the header files automatically with the current configuration.

This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-013.

**File list:** `bsps/include/grlib/ahbstat-regs.h`  
`bsps/include/grlib/ahbtrace-regs.h`  
`bsps/include/grlib/apbuart-regs.h`  
`bsps/include/grlib/dsu4-regs.h`  
`bsps/include/grlib/ftmctrl-regs.h`  
`bsps/include/grlib/gptimer-regs.h`  
`bsps/include/grlib/gr1553b-regs.h`  
`bsps/include/grlib/gr740thsens-regs.h`  
`bsps/include/grlib/grcan-regs.h`  
`bsps/include/grlib/grclkgate-regs.h`  
`bsps/include/grlib/grcthgbt-regs.h`  
`bsps/include/grlib/grgpio-regs.h`  
`bsps/include/grlib/grgprbank-regs.h`  
`bsps/include/grlib/grgpreg-regs.h`  
`bsps/include/grlib/griommu-regs.h`  
`bsps/include/grlib/grpci2-regs.h`

```

bsps\include\glibc\grspw2-regs.h
bsps\include\glibc\grspwrouter-regs.h
bsps\include\glibc\irqamp-regs.h
bsps\include\glibc\l4stat-regs.h
bsps\include\glibc\memscrub-regs.h
bsps\include\glibc\l2cache-regs.h
bsps\include\glibc\mmctrl-regs.h
bsps\include\glibc\spictrl-regs.h
bsps\include\glibc\spwvnp-regs.h
bsps\include\glibc\spwvmap-regs.h

```

**Comment 1**

1. **Sebastian Huber**, Sat, 28 Jan 2023 17:24:25 GMT
2. **keywords:** **qualification** added
3. **owner:** set to **Needs Funding**
4. **version:** set to **6**
5. **status:** changed from **new** to **assigned**
6. **milestone:** set to **7.1**

**Comment 2**

1. **Sebastian Huber**, Tue, 31 Jan 2023 17:50:55 GMT

The files are generated, so changing the format would be easy. Is this the desired format?

```

#define AHBSTAT_AHBS_HMASTER_SHIFT 3
#define AHBSTAT_AHBS_HMASTER_MASK 0x78U`
#define AHBSTAT_AHBS_HMASTER_GET( _reg ) \
( ( (_reg) & AHBSTAT_AHBS_HMASTER_MASK ) >> AHBSTAT_AHBS_HMASTER_SHIFT )
#define AHBSTAT_AHBS_HMASTER( _val ) ( ( _val ) << AHBSTAT_AHBS_HMASTER_SHIFT )

```

It makes the lines longer and the files larger.

**Comment 3**

1. **Daniel Páscoa**, Wed, 08 Feb 2023 10:33:48 GMT

Hello! Yes, we think this format is better, despite being longer and more extensive; this way, the logic is clearer and unambiguous.

**Comment 4**

1. **Sebastian Huber**, Wed, 15 Mar 2023 07:30:30 GMT

In ea3eadf/rtems-central:

```

interface: Improve register bit field macros
Update #4828.

```

**Comment 5**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:52:16 GMT
2. **owner:** changed from **Needs Funding** to **Sebastian Huber**
3. **status:** changed from **assigned** to **accepted**
4. **type:** changed from **defect** to **enhancement**
5. **component:** changed from **admin** to **bsps**
6. **milestone:** changed from **7.1** to **6.1**

**Comment 6**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:06 GMT
2. **status:** changed from **accepted** to **closed**
3. **resolution:** set to **fixed**

In 2d71cba0/rtems:

```

bsps/glibc: Add generated headers
Close #4828.

```

**4832 - CLANG flagged error**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4832">https://devel.rtems.org/ticket/4832</a> ( <a href="https://devel.rtems.org/ticket/4832">https://devel.rtems.org/ticket/4832</a> )
<b>Id</b>	4832
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	27 January 2023 16:13:18
<b>Modified</b>	28 January 2023 16:43:22
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

Description: SPAMR/CLANG point out to a possible dereference to a null pointer. However, this issue has already been checked by the RTEMS team and flagged as false positive (see [rtems-6-sparc-gr740-smp-3/doc/paf/spamr/spamr.pdf](#) page 29). Yet, the justification sentence ends with "Why CLANG complains about a possible null pointer at this place in code and not everywhere or nowhere remains a mystery" which sounds awkward and lead us to think that a complete analysis as not been done on the error.

Looking at it now, "\_Chain\_Initialize\_one" is declared as static inline in a .h. That makes it public and so not all calls are controlled. Within the function, there is already an assert operation for one of the inputs. Now, one needs to add it also to the other one. Note that this assert is only active when compiler options RTEMS\_DEBUG or RTEMS\_STATIC\_ANALYSIS are used which shall remove the CLANG error and not influence the flight executable.

(Missions might do an early compilation with RTEMS\_DEGUG to spot any problem on this).

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-062.

File list: `_cpukit/include/rtems/score/chainimpl.h` (line 525)

### Comment 1

1. **Sebastian Huber**, Fri, 27 Jan 2023 19:27:51 GMT
2. **status**: changed from **new** to **closed**
3. **component**: changed from **admin** to **score**
4. **version**: set to **6**
5. **milestone**: set to **6.1**
6. **keywords**: **qualification** added
7. **resolution**: set to **wontfix**

Functions starting with an underscore are reserved for the RTEMS implementation and not a part of the API.

Adding an `_Assert(x != NULL)` to pointer parameters of internal functions in general makes no sense.

I reviewed the related clang analysis. The problem is that clang doesn't know that `_Scheduler_Count` is greater than zero.

### Comment 2

1. **Sebastian Huber**, Sat, 28 Jan 2023 16:43:22 GMT

In 45393975/rtems:

```
score: Help static analysis in thread init
```

```
Add an assert to _Thread_Initialize_scheduler_and_wait_nodes() which may help a static analyzer. Use a do/while loop since we have at least one scheduleF.
```

```
Update #4832.
```

## 4833 - `glib/pci/grpci2dma.c` Warnings Require Insight to Resolve Properly

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4833">https://devel.rtems.org/ticket/4833</a> ( <a href="https://devel.rtems.org/ticket/4833">https://devel.rtems.org/ticket/4833</a> )
<b>Id</b>	4833
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	27 January 2023 23:36:08
<b>Modified</b>	22 June 2023 21:21:20
<b>Owner</b>	Daniel Hellstrom
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

These are warnings which may be new from gcc 12. It will take someone more knowledgeable about this driver to fix it.

```

../../../../bsps/shared/grlib/pci/grpci2dma.c: In function 'grpci2dma_channel_list_remove':
../../../../bsps/shared/grlib/pci/grpci2dma.c:363:25: warning: 'curr_chan' may be used uninitialized [-Wmaybe-uninitialized]
   363 |         grpci2dma_channel_bd_set_next(curr_chan, new_first_chan);
       |         ^~~~~~
../../../../bsps/shared/grlib/pci/grpci2dma.c:351:41: note: 'curr_chan' was declared here
   351 |         struct grpci2_bd_chan * curr_chan;
       |         ^~~~~~
../../../../bsps/shared/grlib/pci/grpci2dma.c: In function 'grpci2dma_status':
../../../../bsps/shared/grlib/pci/grpci2dma.c:1769:16: warning: 'status' may be used uninitialized [-Wmaybe-uninitialized]
   1769 |         return status;
       |         ^~~~~~
../../../../bsps/shared/grlib/pci/grpci2dma.c:1756:13: note: 'status' was declared here
   1756 |         int status;
       |         ^~~~~~

```

**Comment 1**

1. Joel Sherrill, Thu, 22 Jun 2023 21:21:20 GMT

Daniel.. can someone from Gaisler look into this? Thanks.

**4834 - close\_editor problem of RTEMS4.13/5.1 (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4834">https://devel.rtems.org/ticket/4834</a> ( <a href="https://devel.rtems.org/ticket/4834">https://devel.rtems.org/ticket/4834</a> )
<b>Id</b>	4834
<b>Reporter</b>	chenjin_zhong
<b>Created</b>	30 January 2023 03:43:51
<b>Modified</b>	31 January 2023 05:17:32
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4564:

Hi, I find when close editor in shell console.some errors will occur. I check and analyse the source code of medit.c. the code fragment is listed as follows.

```

#if defined(rtems)
    case ctrl('w'): ed = ed->env->current; close_editor(ed); break;
#else
    case ctrl('w'): close_editor(ed); ed = ed->env->current; break;
#endif

```



```
static void close_editor(struct editor *ed) {
```

```
    struct env *env = ed->env;
    if (ed->dirty) {
```

```
        display_message(ed, "Close %s without saving changes (y/n)? ", ed->filename);
        if (!ask()) {
```

```
            ed->refresh = 1;
            return;
        }
```

```
    }
```

```
delete_editor(ed);
```

```
ed = env->current;
if (!ed) {
```

```
    ed = create_editor(env);
    new_file(ed, "");
```

```
    ed->refresh = 1;
}
```

```
static void delete_editor(struct editor *ed) {
```

```
    if (ed->next == ed) {
```

```
        ed->env->current = NULL;
```

```
    } else {
```

```
        ed->env->current = ed->prev;
```

```
    }
    ed->next->prev = ed->prev;
    ed->prev->next = ed->next;
    if (ed->start) free(ed->start);
```

```
    clear_undo(ed);
```

```
    __ free(ed); __
}
```

as seen above, if the macro `__rtems__` is defined, the `delete_editor` function will free `__ed__` pointer. Therefore, after the next loop, the `__ed__` is an invalid pointer. I have checked the code of <https://github.com/ringgaard/sanos/blob/master/src/utlils/edit/edit.c>. the code is as follows.

```
__ case ctrl('w'): close_editor(ed); ed = ed->env->current; break; __
```

#### Comment 1

1. **Chris Johns**, Tue, 31 Jan 2023 05:17:32 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3ad2789/rtems:

```
libmisc/shell/edit: Fix closing the editor
```

```
Closes #4834
```

#### **4835 - medit malloc problem of RTEMS (cloned)**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4835">https://devel.rtems.org/ticket/4835</a> ( <a href="https://devel.rtems.org/ticket/4835">https://devel.rtems.org/ticket/4835</a> )
<b>Id</b>	4835
<b>Reporter</b>	chenjin_zhong
<b>Created</b>	30 January 2023 03:46:07
<b>Modified</b>	31 January 2023 05:17:34
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	shell
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Cloned from #4565:

I find malloc function is called by move\_gap function in medit.c. The returned value does not check. At least 32KB of memory is allocated at each time, maybe more than. The returned value "start" should be check to avoid malloc failure. The move\_gap function should return immediately when malloc failure. the code fragment is listed as follows.

<pre>static void move_gap(struct editor *ed, int pos, int minsize) {</pre>	<pre>    int gapsize = ed-&gt;rest - ed-&gt;gap;     unsigned char *p = text_ptr(ed, pos);     if (minsize &lt; 0) minsize = 0;     if (minsize &lt;= gapsize) {</pre>
<pre>        if (p != ed-&gt;rest) {</pre>	<pre>            if (p &lt; ed-&gt;gap) {</pre>
<pre>                memmove(p + gapsize, p, ed-&gt;gap - p);</pre>	<pre>            } else {</pre>
<pre>                memmove(ed-&gt;gap, ed-&gt;rest, p - ed-&gt;rest);</pre>	<pre>            }             ed-&gt;gap = ed-&gt;start + pos;             ed-&gt;rest = ed-&gt;gap + gapsize;         }     } else {</pre>
<pre>        int newsize;         unsigned char *start;         unsigned char *gap;         unsigned char *rest;         unsigned char *end;</pre>	<pre>        if (gapsize + MINEXTEND &gt; minsize) minsize = gapsize + MINEXTEND;         newsize = (ed-&gt;end - ed-&gt;start) - gapsize + minsize; __ start = (unsigned char *) malloc(newsize); __ TODO check for out of memory         gap = start + pos;         rest = gap + minsize;         end = start + newsize; __</pre>
<pre>        if (p &lt; ed-&gt;gap) {</pre>	<pre>            memcpy(start, ed-&gt;start, pos);             memcpy(rest, p, ed-&gt;gap - p);             memcpy(end - (ed-&gt;end - ed-&gt;rest), ed-&gt;rest, ed-&gt;end - ed-&gt;rest);</pre>
<pre>        } else {</pre>	<pre>            memcpy(start, ed-&gt;start, ed-&gt;gap - ed-&gt;start);             memcpy(start + (ed-&gt;gap - ed-&gt;start), ed-&gt;rest, p - ed-&gt;rest);             memcpy(rest, p, ed-&gt;end - p);</pre>
<pre>        }     } }</pre>	<pre>    } }</pre>

```

    free(ed->start);
    ed->start = start;
    ed->gap = gap;
    ed->rest = rest;
    ed->end = end;
}

#ifdef DEBUG
    memset(ed->gap, 0, ed->rest - ed->gap);
#endif
}

```

**Comment 1**

1. **Chris Johns**, Tue, 31 Jan 2023 05:17:34 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In edea93c/rtems:

```

libmisc/shell/edit: Return if no memory in move_gap
Closes #4835

```

**4838 - Fix for UART interrupt on aarch64 Versal**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4838">https://devel.rtems.org/ticket/4838</a> ( <a href="https://devel.rtems.org/ticket/4838">https://devel.rtems.org/ticket/4838</a> )
<b>Id</b>	4838
<b>Reporter</b>	Aaron N
<b>Created</b>	5 February 2023 22:27:50
<b>Modified</b>	9 February 2023 13:13:15
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	arch/aarch64
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Fixed UART interrupts for Versal. Tested on VCK190.

**Attachments:**

1. **Aaron N, Sun, 05 Feb 2023 22:28:08 GMT**  
**attach:** set to [0001-aarch64-versal-Fix-uart-interrupt-issues.patch](https://devel.rtems.org/ticket/4838/0001-aarch64-versal-Fix-uart-interrupt-issues.patch) (<https://devel.rtems.org/ticket/4838/0001-aarch64-versal-Fix-uart-interrupt-issues.patch>)

**Comment 1**

1. **Aaron N**, Sun, 05 Feb 2023 23:56:20 GMT
2. **component:** changed from **admin** to **arch/aarch64**

**Comment 2**

1. **Joel Sherrill**, Mon, 06 Feb 2023 00:30:59 GMT
2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **assigned**
4. **milestone:** set to **6.1**

Assigning to Chris since this is his BSP

**Comment 3**

1. **Kinsey Moore**, Wed, 08 Feb 2023 20:35:42 GMT

Is this a duplicate of #4771?

**Comment 4**

1. **Chris Johns**, Thu, 09 Feb 2023 02:24:00 GMT

Replying to Kinsey Moore:

Is this a duplicate of #4771?

Yes I think it is. Aaron will know so lets see what he says?

**Comment 5**

1. **Aaron N**, Thu, 09 Feb 2023 10:16:02 GMT

Yeah it is a duplicate.

**Comment 6**

1. **Kinsey Moore**, Thu, 09 Feb 2023 13:13:15 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **duplicate**

**4842 - SPARC/glib - Registers definitions wrongly defined when there are reserved bits**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4842">https://devel.rtems.org/ticket/4842</a> ( <a href="https://devel.rtems.org/ticket/4842">https://devel.rtems.org/ticket/4842</a> )
<b>Id</b>	4842
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 February 2023 14:43:19
<b>Modified</b>	14 July 2023 10:01:28
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

With respect to RTEMS 6 (ESA-promoted RTEMS SMP Qualification Data Pack release 3), the following issues are observed:

File Lines Discrepancy `\include\glib\ftmctrl-regs.h` 84; 86; 88; 91; 96;98; 101; 106; 109; 115; 120; 123 According to table 365 of page 294 of the GR740 User Manual (v.2.50), the register addresses are incorrectly defined. `\include\glib\grgpio-regs.h` 225 According to table 406 of page 319 of the GR740 User Manual (v.2.50), the register address is incorrect; `\include\glib\dsu4-regs.h` 435 According to table 538 of page 403 of the GR740 User Manual (v.2.5), the register address is incorrect according to the table but it is correct according to the table description. `\include\glib\gr1553b-regs.h` 609 According to table 327 of page 259 of the GR740 User Manual (v.2.50), the register address is incorrect according to the table but it is correct according to the table description. `\include\glib\spwmp-regs.h` 151 According to table 213 of page 200 of the GR740 User Manual (v.2.5), the register address is incorrect according to the table but it is correct according to the table description. `\include\glib\spwrmap-regs.h` 575; 591; 715; 787; 809 According to tables 191, 192, 199, 201, 202, respectively (to each identified line) starting on page 192 of the GR740 User Manual (v.2.5), the register addresses are incorrect according to the table but are correct according to the table description.

It seems that the generation of these registers definitions leads to incorrect bit definitions whenever there are reserved bits specified in the Gaisler User Manual.

Can you please double-check these cases?

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-CODE-VER-014.

**Comment 1**

1. **Sebastian Huber**, Tue, 14 Feb 2023 16:27:14 GMT

The DSU4[ITCB0] ITPOINTER field seems to be correct in the description. See also the GRIP manual.

**Comment 2**

1. **Sebastian Huber**, Tue, 14 Feb 2023 16:27:36 GMT

2. **component**: changed from **admin** to **arch/sparc**

3. **milestone:** set to **6.1****Comment 3**

1. **Sebastian Huber**, Tue, 14 Feb 2023 17:50:59 GMT

The RTELM - GR1553B RT Event Log mask register should be clarified by Gaisler.

**Comment 4**

1. **Sebastian Huber**, Tue, 14 Feb 2023 19:16:08 GMT

With respect to the

Space Wire Plug-and-Play - Active Links Interrupt port mask (IPMASK) Port interrupt pending (PIP) Link running status (LRUNSTAT) the register block definitions are actually from the GRIP manual. In the latest version, up to 31 links are supported.

**Comment 5**

1. **Sebastian Huber**, Tue, 14 Feb 2023 19:28:41 GMT

To be check by Gaisler:

Space Wire Plug-and-Play - Device Vendor and Product ID Space Wire Plug-and-Play - Unit Vendor and Product ID

**Comment 6**

1. **Sebastian Huber**, Thu, 16 Feb 2023 08:06:11 GMT

In a7c2836/rtems-central:

```
spec: Fix FTMCTRL - MCFG1 bit fields
There was an off by one error in all bit fields. Add the R flag.
Update #4842.
```

**Comment 7**

1. **Sebastian Huber**, Thu, 16 Feb 2023 08:06:12 GMT

In 239d254/rtems-central:

```
spec: Fix GRGPIO - IRQMAP bit fields
Update #4842.
```

**Comment 8**

1. **Sebastian Huber**, Thu, 16 Feb 2023 08:06:13 GMT

In dd6f100/rtems-central:

```
spec: Fix SpaceWire? RMAP - Product ID
Update #4842.
```

**Comment 9**

1. **Sebastian Huber**, Thu, 16 Feb 2023 08:06:14 GMT

In 4fdeb56/rtems-central:

```
spec: Expand SpaceWire? port bit fields
Use the maximum width supported by the SpaceWire? standard even if this exceeds the configuration limits of a particular IP instance.
Update #4842.
```

**Comment 10**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:05:31 GMT

2. **owner:** set to **Sebastian Huber**

3. **status:** changed from **new** to **assigned**

4. **summary:** changed from **Registers definitions wrongly defined when there are reserved bits** to **SPARC/glib - Registers definitions wrongly file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html**

defined when there are reserved bits

#### **Comment 11**

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:30:42 GMT

This will be closed before 6. Please clone for 7 if continued.

#### **Comment 12**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:58:53 GMT

In d4c1301/rtems-central:

spec: Add GRCAN - CanTxIRQ

Update #4842.

#### **Comment 13**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:58:54 GMT

In b46ff7e/rtems-central:

spec: Expand GRCLKGATE register bit fields

Use the maximum width supported by the GRLIB even if this exceeds the configuration limits of a particular IP instance.

Update #4842.

#### **Comment 14**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:58:55 GMT

In 89b89fe/rtems-central:

spec: Move GR740-specific register blocks

Update #4842.

#### **Comment 15**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:58:57 GMT

In d6c4baf/rtems-central:

spec: Use GRLIB definition of GRSPW2

Update #4842.

#### **Comment 16**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:58:58 GMT

In d077161/rtems-central:

spec: Remove obsolete register block

This register block was an incomplete duplicate of spec:/dev/gplib/if/grspw2.

Update #4842.

#### **Comment 17**

1. **Sebastian Huber**, Fri, 14 Jul 2023 09:58:59 GMT

In 5771560/rtems-central:

spec: Use GRLIB definition of GRSPWROUTER

Rename item to match with GRLIB naming.

Update #4842.

**Comment 18**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:08 GMT

In e56cecf5/rtems:

bsps/grlib: Fix FTMCTRL - MCFG1 bit fields

There was an off by one error in all bit fields. Add the R flag.

Update #4842.

**Comment 19**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:10 GMT

In b7eb7d1f/rtems:

bsps/grlib: Fix GRGPIO - IRQMAP bit fields

Update #4842.

**Comment 20**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:12 GMT

In 7575890/rtems:

bsps/grlib: Fix SpaceWire? RMAP - Product ID

Update #4842.

**Comment 21**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:14 GMT

In fe232596/rtems:

bsps/grlib: Expand SpaceWire? port bit fields

Use the maximum width supported by the SpaceWire? standard even if this exceeds the configuration limits of a particular IP instance.

Update #4842.

**Comment 22**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:16 GMT

In 845422b/rtems:

bsps/grlib: Fix SPWTRDP register name

Update #4842.

**Comment 23**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:18 GMT

In e6427f1e/rtems:

bsps/grlib: Add GRCAN - CanTxIRQ

Update #4842.

**Comment 24**

1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:20 GMT

In 584be21/rtems:

bsps/grlib: Expand GRCLKGATE register bit fields

Use the maximum width supported by the GRLIB even if this exceeds the configuration limits of a particular IP instance.

Update #4842.

**Comment 25**1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:22 GMT

In cba956b/rtems:

bsps/grlib: Move GR740-specific registers  
Update #4842.

**Comment 26**1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:24 GMT

In 181d989/rtems:

bsps/grlib: Use GRLIB definition of GRSPW2  
Update #4842.

**Comment 27**1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:26 GMT

In 06f63154/rtems:

bsps/grlib: Remove obsolete header file  
This header file was an incomplete duplicate of .  
Update #4842.

**Comment 28**1. **Sebastian Huber**, Fri, 14 Jul 2023 10:01:28 GMT2. **status:** changed from **assigned** to **closed**3. **resolution:** set to **fixed**

In 49ad450/rtems:

bsps/grlib: Use GRLIB definition of GRSPWROUTER  
Rename parts to match with GRLIB naming.  
Close #4842.

**4843 - Output value not assigned**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4843">https://devel.rtems.org/ticket/4843</a> ( <a href="https://devel.rtems.org/ticket/4843">https://devel.rtems.org/ticket/4843</a> )
<b>Id</b>	4843
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 February 2023 14:44:48
<b>Modified</b>	10 February 2023 14:59:09
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The Software Document Design (starting on page 181) specifies that there should be two outputs, but the RTEMS\_UNSATISFIED is not returned by the function. The only failure detected may be due to the assert function, but the rtems\_status\_code isn't the returned value. Ensure all output values specified in the SDD are returned.

\_\_Additional Notes:\_\_ From code analysis and from objdumping the librtmsbsp.a library it can be observed that the asserts() currently do nothing: they are  
file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html



translated to `#define Assert( _e ) ( ( void ) 0 )` unless `RTEMS_DEBUG` or `RTEMS_STATIC_ANALYSIS` are defined, which in a release environment target are not defined. Since in the documentation it says that it can return `RTEMS_UNSATISFIED` or `RTEMS_SUCCESSFUL` either the documentation is wrong, or the code is not correctly implemented.

This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs ( <https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-CODE-VER-032.

\_\_ File list: \_\_ bsp\sparc\leon3\start\irq.c

```
bsp_interrupt_is_pending (line 106)
bsp_interrupt_raise (line 127)
bsp_interrupt_clear (line 185)
bsp_interrupt_vector_enable (line 270)
bsp_interrupt_vector_disable (line 299)
```

### Comment 1

1. **Sebastian Huber**, Fri, 10 Feb 2023 14:58:12 GMT
2. **owner:** set to **Sebastian Huber <sebastian.huber@...>**
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 519e288/rtems:

```
bsp/irq: Clarify interrupt vector operations
Clarify that the presence of error conditions is implementation-defined.
Close #4843.
```

### Comment 2

1. **Sebastian Huber**, Fri, 10 Feb 2023 14:59:09 GMT
2. **component:** changed from **admin** to **bsp**
3. **milestone:** set to **6.1**

## 4844 - Unchecked boundaries

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4844">https://devel.rtems.org/ticket/4844</a> ( <a href="https://devel.rtems.org/ticket/4844">https://devel.rtems.org/ticket/4844</a> )
<b>Id</b>	4844
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 February 2023 14:52:06
<b>Modified</b>	28 July 2023 14:51:27
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	score
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Consider checking for overflow situations and taking necessary actions in the three files designated below.

\_\_ Memory copy function accesses out-of-bound array element in file `cpukit/include/rtems/score/coremsgimpl.h` (line 469)\_\_

Additional Information:

The pointer to the structure that contains the buffer and the size is tested against `NULL`, but this finding refers to the fact that the argument size of is not validated against the maximum size of the destination and/or source buffer.

This function can be traced up to `rtems_message_queue_send` and `rtems_message_queue_receive` functions where the buffer, its size and maximum size for queue messages are provided by the user. In the RTEMS library at the moment of sending a message in the `_CORE_message_queue_Submit` function it is validated if the given size of the buffer is not above the user previously provided/configured maximum size, and returns an error if so. But it is up to the user to supply correct values. If the user tries to pass a buffer with 16 bytes, but indicates 32 bytes in the size there is no possible library validation that will detect an overflow situation. These cases must be detected by user code inspection/review.

\_\_ Out of bound memory access (access exceeds upper limit of memory block) in file `cpukit/include/rtems/score/mrpsimpl.h` (lines 120, 312, 315)\_\_

Additional Information:

There is a Global variable `const size_t Scheduler_Count = CONFIGURE_SCHEDULER_COUNT`; corresponding to the value configured statically depending of `RTEMS_ARRAY_SIZE( Scheduler_Table )`, which is the number of shedulers. Relevant source code for lines 312 and 315, which are OK:

```
scheduler_count = _Scheduler_Count;
for ( i = 0 ; i < Scheduler_Count ; ++i ) {
(...)
    scheduler_of_index = &_Scheduler_Table[ i ];
(...)
    mrsp->ceiling_priorities[ i ] =
```

Relevant source code for lines 120 and others, do not seem OK, because is not clear that the scheduler is always valid:

```
scheduler_index = _Scheduler_Get_index( scheduler ); // Note: translates to "return (uint32_t) (scheduler - &_Scheduler_Table[ 0 ]);"
return mrsp->ceiling_priorities[ scheduler_index ];
```

\_\_Returned pointer value points outside the original object (potential buffer overflow) for file cpukit\score\src\threadqops.c (line 294)\_\_

Consider checking for overflow situations and acting accordingly.

Additional Information:

The line 294 (the referred line is for version 3 of the QDP), from function `_Thread_queue_Priority_queue_by_index`:

```
return &heads->Priority[ scheduler_index ];
```

The priority field is declared as `Thread_queue_Priority_queue Priority[ RTEMS_ZERO_LENGTH_ARRAY ]`; which is a zero-length array...

Then in `threads.h` file a Struct is defined as

```
struct Thread_queue_Configured_heads {
    Thread_queue_Heads Heads;
    Thread_queue_Priority_queue Priority[ _CONFIGURE_SCHEDULER_COUNT ];
};
```

Which permits to access the zero-length array beyond the initial configuration of zero length (C99 permits it):

C99 6.7.2.1, §16: As a special case, the last element of a structure with more than one named member may have an incomplete array type; this is called a flexible array member.

But still, `scheduler_index` value is obtained by calling several other functions which extract information from a thread object in order to obtain and use the `scheduler_index` value in the `_Thread_queue_Priority_queue_by_index` function. It is not clear that that value is below `_CONFIGURE_SCHEDULER_COUNT` value.

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-CODE-VER-036.

### Comment 1

1. **Sebastian Huber**, Fri, 10 Feb 2023 07:16:22 GMT

These should have been three tickets and not just one.

The message send directives use the size as an output only parameter. If you change this to an input and output parameter, then you may break existing applications which do not set the size parameter to a proper value. The Semaphore Control Block size is defined by the application configuration:

```
#if CONFIGURE_MAXIMUM_SEMAPHORES > 0
SEMAPHORE_INFORMATION_DEFINE(
    CONFIGURE_MAXIMUM_SEMAPHORES,
    _CONFIGURE_SCHEDULER_COUNT
);
#endif
```

There are lots of other values in the Thread Control Block which have to be correct. Why should we add a check here specifically? We could add an `_Assert()`.

### Comment 2

1. **Sebastian Huber**, Thu, 23 Mar 2023 16:25:34 GMT

2. **owner**: set to **Sebastian Huber**

3. **status**: changed from **new** to **assigned**

4. **type**: changed from **defect** to **enhancement**

5. **component**: changed from **admin** to **score**

6. **milestone**: set to **6.1**

### Comment 3

1. **Daniel Páscoa**, Fri, 16 Jun 2023 14:28:50 GMT

1 >>> We agree that changing the function prototype for `rtems_message_queue_send`, `rtems_message_queue_receive`, `_CORE_message_queue_Insert` message and other functions in-between could break existing applications and may not be acceptable to do so. So, one suggests dismissing this point of the ticket.

2 >>> This point can be dismissed as it is now confirmed that necessary protections are already in place on the API entry point for `_MRSP_Get_priority` and `_MRSP_Set_priority`, which is the `rtems_semaphore_set_priority` (one can refer to the protections implemented by this function within code and/or ICD).

3 >>> Yes, appending the `_Assert( scheduler_index < _Scheduler_Count );` just before the concerned line will solve it. Thanks

### Comment 4

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:11:21 GMT

If there is an `_Assert()` implemented somewhere, please merge it and close if the rest of these are non-issues.

**Comment 5**

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:31:03 GMT

This will be closed before 6. Please clone for 7 if continued.

**Comment 6**

1. **Sebastian Huber**, Fri, 28 Jul 2023 14:50:34 GMT

In 6293fc4f/rtems:

```
score: Assert scheduler index validity
Update #4844.
```

**Comment 7**

1. **Sebastian Huber**, Fri, 28 Jul 2023 14:51:27 GMT

Daniel, please review the changes and close the ticket if everything is all right.

**4845 - Global variable declared/defined in the wrong file**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4845">https://devel.rtems.org/ticket/4845</a> ( <a href="https://devel.rtems.org/ticket/4845">https://devel.rtems.org/ticket/4845</a> )
<b>Id</b>	4845
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 February 2023 14:53:20
<b>Modified</b>	10 February 2023 15:01:47
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

This source file contains both declaration and definition of the variable. It is recommended to declare global variables in a header file and define them in separate source files. Please consider this best practice and move the declarations to a header file and corresponding definitions to respective source files.

Additional Notes: LEON3\_Boot\_Cpu is a global variable and only used by start.S file. And as such cannot be declared as static. Because is used in an assembly file there was no need to declare it as external. But the global variable is in fact declared and defined in same file.

This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-043.

File list: \_\_ bsp/sparc/leon3/start/bspstart.c (line 54)

**Comment 1**

1. **Sebastian Huber**, Fri, 10 Feb 2023 15:01:13 GMT

2. **owner:** set to **Sebastian Huber** <sebastian.huber@...>

3. **status:** changed from **new** to **closed**

4. **resolution:** set to **fixed**

In b993111/rtems:

```
bsp/leon3: Move SMP data to start.S
The LEON3_Boot_Cpu global object is only used by start.S. Move the definition of this object to start.S and use a local symbol
.lbootcpuindex for it.
Use a compare-and-swap instruction to assign the boot CPU. This allows a concurrent initialization.
Close #4845.
```

**Comment 2**

1. **Sebastian Huber**, Fri, 10 Feb 2023 15:01:47 GMT

2. **component:** changed from **admin** to **arch/sparc**

3. **milestone:** set to **6.1**

---

## 4847 - Goto statements

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4847">https://devel.rtems.org/ticket/4847</a> ( <a href="https://devel.rtems.org/ticket/4847">https://devel.rtems.org/ticket/4847</a> )
<b>Id</b>	4847
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 February 2023 14:56:10
<b>Modified</b>	14 February 2023 00:58:54
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The use of "goto" statements is strongly discouraged as it results in convoluted program logic, making it challenging to analyse and verify program correctness, particularly in loops. Instead, the "break" and "continue" statements provide alternatives to "goto" and should be utilized to simplify the code.

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-074.

File list: \_\_cpukit/score/src/threaddispatch.c (line 290)

### Comment 1

1. **Joel Sherrill**, Thu, 09 Feb 2023 15:05:11 GMT

Although cpukit/score/src/threaddispatch.c (line 290) is not right per the current source, on first examination, I think this goto can be a break. Leaving the label post\_switch is probably good for understanding purposes. And adding a comment at that point would probably be a good idea also.

FWIW this goto was not present in versions <= 4.10 but shows up in 4.11 and I think that it could have been a break back then also. The code looks similar.

### Comment 2

1. **Sebastian Huber**, Thu, 09 Feb 2023 18:44:59 GMT

2. **component:** changed from **admin** to **score**

Yes, it can be a break. I am not sure if the break improves the code clarity.

### Comment 3

1. **Joel Sherrill**, Thu, 09 Feb 2023 18:59:30 GMT

Looking at the older versions, there was not a loop around the dispatching activities. This was added because with SMP, the other cores could request a dispatch on a core while one was in process.

I'm fine with changing it to a break. I just think anytime you look at code, you should consider if more comments are necessary. I think the post\_switch label is acting as a minimal comment and the scenarios for looping more than once or exercising the break could be documented in the comments.

### Comment 4

1. **Sebastian Huber**, Fri, 10 Feb 2023 14:58:10 GMT

2. **owner:** set to **Sebastian Huber <sebastian.huber@...>**

3. **status:** changed from **new** to **closed**

4. **resolution:** set to **fixed**

In 22d845d5/rtems:

```
score: Replace goto with a break
```

```
The goto label was directly after the loop, so we can replace the goto with a break.
```

```
Close #4847.
```

### Comment 5

1. **Sebastian Huber**, Fri, 10 Feb 2023 14:58:45 GMT

2. **milestone:** set to **6.1**

**Comment 6**

1. **Chris Johns**, Tue, 14 Feb 2023 00:58:54 GMT

Has this ticket and review taken into account the discussion here?

<https://lists.rtems.org/pipermail/devel/2014-May/006723.html>

I have not seen a similar discussion?

**4850 - LEON3 - Variable not initialized in any file / missing #ifdefs**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4850">https://devel.rtems.org/ticket/4850</a> ( <a href="https://devel.rtems.org/ticket/4850">https://devel.rtems.org/ticket/4850</a> )
<b>Id</b>	4850
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	13 February 2023 12:59:06
<b>Modified</b>	28 July 2023 05:27:56
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Within `__bsps\sparc\leon3\include\bsp\leon3.h` (lines 207, 309)\_\_\_

The `*LEON3_IrqCtrl_Adev` and `*LEON3_Timer_Adev` are declared but not initialized in any file of the QDP.:

Please consider having these declared within the "else" blocks of the `"#if defined(LEON3_IRQAMP_BASE)"` where `*LEON3_IrqCtrl_Regs` and `*LEON3_Timer_Regs` are declared. \_\_\_

Additional Notes: \_\_\_ This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). Original ISVV reference for this issue is RTEMS-SMP-CODE-VER-041.

**Comment 1**

1. **Sebastian Huber**, Thu, 23 Mar 2023 16:22:58 GMT

2. **owner:** set to **Sebastian Huber**

3. **status:** changed from **new** to **assigned**

4. **component:** changed from **admin** to **arch/sparc**

5. **milestone:** set to **6.1**

**Comment 2**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:11:55 GMT

2. **summary:** changed from **Variable not initialized in any file / missing #ifdefs** to **LEON3 - Variable not initialized in any file / missing #ifdefs**

**Comment 3**

1. **Sebastian Huber**, Fri, 28 Jul 2023 05:27:56 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In c173f05/rtems:

```
bsp/leon3: Make declarations conditional
```

```
The LEON3_IrqCtrl_Adev object is only defined if LEON3_IRQAMP_BASE is not defined.
```

```
The LEON3_Timer_Adev object is only defined if LEON3_GPTIMER_BASE is not defined.
```

```
Close #4850.
```

**4855 - Input validity unchecked**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4855">https://devel.rtems.org/ticket/4855</a> ( <a href="https://devel.rtems.org/ticket/4855">https://devel.rtems.org/ticket/4855</a> )
<b>Id</b>	4855
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	13 February 2023 14:21:44
<b>Modified</b>	23 March 2023 16:21:24
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	unspecified
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

In a generic way, function inputs shall be checked for validity before being used.

When successive calls are done to different functions, one might argue that inputs are to be checked only once and then considered valid in other calls. Yet this has some pitfalls like:

- function inputs are not checked in a consistent way throughout all functions:
  - Each one has to constantly double-check in comments and/or callers if inputs are instead checked elsewhere in the call tree.
  - Even if for the moment no call tree leads to invalid input issues, future maintenance operations may add new calls without validity checks.

One can assume some exceptions can occur (e.g., when there is a considerable performance impact), but as long such cases are justified within the function's comments one can easily sort out those exceptions.

Bellow, there is a list of cases where input validity could be added:

- `bsp\include\bsp\irq-generic.h`: `bsp_interrupt_entry_load_first` function is called by `bsp_interrupt_handler_dispatch_unchecked` where the argument was already checked.
- `bsp\include\bsp\irq-generic.h`: `bsp_interrupt_handler_index` function is called by `bsp_interrupt_entry_load_first`, `bsp_interrupt_entry_remove`, `bsp_interrupt_spurious`, `bsp_interrupt_entry_find`, `bsp_interrupt_entry_install`, `rtems_interrupt_handler_iterate` functions. It was possible to trace in all of them a validation of the argument used in `bsp_interrupt_handler_index` before being called.
- `bsp\shared\irq\irq-default-handler.c`: `bsp_interrupt_handler_default` is only called by `bsp_interrupt_spurious` and `bsp_interrupt_handler_dispatch_unchecked` functions and it was possible to trace in all of them a validation of the argument used in `bsp_interrupt_handler_index` before being called.
- `bsp\shared\irq\irq-entry-remove.c`: the `*entry` argument of `bsp_interrupt_entry_do_remove` is actually tested and validated inside of that function. That function is also the only place where `bsp_interrupt_entry_remove` is called. The arguments `vector`, `*entry` and `previous_next` are all validated by a call to the `bsp_interrupt_entry_find` and subsequent code that is run prior to call `bsp_interrupt_entry_remove` function. `__`
- `bsp\shared\irq\irq-generic.c`: the `bsp_interrupt_spurious` function argument `vector` is tested before being called in `bsp_interrupt_handler_dispatch_unchecked` function.
- `bsp\shared\irq\irq-generic.c`: `bsp_interrupt_entry_install_first` function is called once by `bsp_interrupt_entry_install` function. The validation of the argument `vector` can be traceback to `rtems_interrupt_entry_install` function. The argument `*entry` is also passed by `bsp_interrupt_entry_install` function and explained in the previous paragraph.
- `bsp\shared\dev\clock\clockimpl.h`: in both functions (`void Clock_isr` and `rtems_isr Clock_isr`) declaration/definition (they are the same function, just declared differently depending of `#if defs`), both arguments are not used. Due to the evaluation of the internal `#if`, this functions are reduced to `Clock_driver_ticks += 1; _Timecounter_Tick();`
- `bsp\sparc\leon3\start\bsp\bspmp.c`: the `bsp_start_on_secondary_processor` function calls `_SMP_Start_multitasking_on_secondary_processor` with the same argument as it was called. This argument in that sub-function is used to get a value `cpu_index_self`, which itself is validated and checked if it is a proper value or not. Indirect validation.
- `bsp\sparc\leon3\start\bsp\bspmp.c`: the `_CPU_SMP_Send_interrupt` function is called in 3 different places: in one place (`_SMP_Request_shutdown` function in `smc.c` file) it is inside a for loop that is limited by `_SMP_Processor_configured_maximum`. This is OK. For the other 2 places (from `_SMP_Send_message` function in `smc.c` file and `_Thread_Dispatch_request` function in `threaddispatch.h` file) it is not clear that the argument of `_CPU_SMP_Send_interrupt` cannot be limited (when it should be limited at least to `_SMP_Processor_configured_maximum`).
- `bsp\sparc\leon3\start\bsp\bspmp.c`: `bsp_interrupt_get_attributes` function actually tests `vector` argument. But also there is only one call to this function which is from `rtems_interrupt_get_attributes` function in `irq-enable-disable.c` file where both arguments are tested prior call to `bsp_interrupt_get_attributes` function.
- `bsp\sparc\shared\start\bsp\bspgetworkarea.c`: `_SPARC_Memory_initialize` function receives its `*end_of_usable_ram` argument from the main function in `start.S` file. No validation is performed there. The argument is used to initialize a struct, which later on may be used for dynamically allocated memory. The referred pointer argument is never dereferenced, it is used as the end limit of the allocated memory position. It may make sense to test in this initialisation function if its value is above `&_Memory_Areas[0]`.
- `cpukit\libc\string\memset.c`: `memset` function is part of space qualification profile context, and the `void *<dst>` pointer is not tested against `NULL`.
- `cpukit\libc\string\memcpy.c`: `memcpy` function is part of space qualification profile context, and the `void *dst` and `void *src` pointers is not tested against `NULL`.
- `cpukit\posix\src\clock\nanosleep.c`: in function `clock_nanosleep` the `*rmtp` argument can be `NULL` if the user does not want to get the remain time, so there is no need to validate it. For the `*rqtp` (request) argument this should be validated if different than `NULL` and the `tv_nsec` field must be validated if between 0 and 999999999.
- `cpukit\rtems\src\clock\tod\toseconds.c`: the `_TOD_To_seconds` function is called by `_Timer_Fire_when` function from `timercreate.c` file, by `rtems_task_wake_when` function from `taskwakewhen.c` file and by `rtems_clock_set` function from `clockset.c` file. In all three cases the argument with which the `_TOD_To_seconds` function is called is validated with a call to `_TOD_Validate` function prior to the call.
- `cpukit\rtems\src\events\send.c`: the `_Event_Seize` function is called by two similar functions the `rtems_event_receive` from `eventreceive.c` file and `rtems_event_system_receive` from `systemeventreceive.c` file. The `*event_out` argument is validated prior the call; all other arguments are declared and defined in the caller functions prior to call the `_Event_Seize` function.

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-VAL-029.

## Comment 1

1. **Daniel Páscoa**, Mon, 13 Feb 2023 14:25:16 GMT

\_\_Correction: \_\_ The original ISVV reference for this issue is \_\_RTEMS-SMP-VER-029\_\_.

#### Comment 2

1. **Sebastian Huber**, Thu, 23 Mar 2023 16:21:24 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**
4. **component**: changed from **admin** to **unspecified**
5. **milestone**: set to **6.1**

For internal functions it is responsibility of the caller to ensure that arguments are valid.

The C library functions `memset()` and `memcpy()` are not required to check for NULL.

`clocknanosleep()` checks the mentioned error conditions. There are also test cases for them.

The `end_of_usable_ram` is provided by the boot loader. How can the BSP validate this?

## 4857 - RSB Recipe Missing %hash Does Not Fail

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4857">https://devel.rtems.org/ticket/4857</a> ( <a href="https://devel.rtems.org/ticket/4857">https://devel.rtems.org/ticket/4857</a> )
<b>Id</b>	4857
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	16 February 2023 22:34:10
<b>Modified</b>	30 June 2023 00:11:25
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	duplicate
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

If a recipe is missing a `%hash` command, it is reported as a warning. It would be preferable to have an error.

```
warning: gdb-readline8.2.patch: no hash found
```

From #4760 and copied as part of merging these tickets:

The time has come to raise a fatal error if a hash is missing rather than a warning. This will stop missing checksums being present when releasing. It also makes it simpler to test releases for no missing checksums.

#### Comment 1

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:15:04 GMT
2. **description**: modified (diff)

#### Comment 2

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:32:07 GMT

Please check and then confirm before closing

#### Comment 3

1. **Chris Johns**, Fri, 30 Jun 2023 00:11:15 GMT

This is being closed because #4760 makes any missing `%hash` cause a fatal error.

#### Comment 4

1. **Chris Johns**, Fri, 30 Jun 2023 00:11:25 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **duplicate**

## 4858 - GDB fails to build on any host with readline 8.2 or newer

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4858">https://devel.rtems.org/ticket/4858</a> ( <a href="https://devel.rtems.org/ticket/4858">https://devel.rtems.org/ticket/4858</a> )
<b>Id</b>	4858
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	16 February 2023 22:36:08
<b>Modified</b>	17 February 2023 20:12:44
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	tool/gdb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This showed up with gdb 11.2 building on Cygwin. The fix is already in the gdb git repository on the master but not gdb 12.x. This ticket tracks adding that to the RSB.

**Comment 1**

1. **Joel Sherrill**, Fri, 17 Feb 2023 20:12:44 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In e1d5d93/rtems-source-builder:

```
rtems-gdb-11.2.cfg: Add patch for hosts with readline 8.2
Get the fix from gdb git repo to fix build issue which showed up on Cygwin but was cross platform.
Closes #4858.
```

**4859 - Update gdb to 12.1**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4859">https://devel.rtems.org/ticket/4859</a> ( <a href="https://devel.rtems.org/ticket/4859">https://devel.rtems.org/ticket/4859</a> )
<b>Id</b>	4859
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	16 February 2023 22:39:01
<b>Modified</b>	17 February 2023 20:12:45
<b>Owner</b>	Joel Sherrill <joel@...>
<b>Type</b>	defect
<b>Component</b>	tool/gdb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

While investigating the build issue tracked as #4858, I tried bumping the gdb to 12.1 hoping it included the fix. But it did not. This bumps the default gdb to 12.1 with the same patch.

**Comment 1**

1. **Joel Sherrill**, Fri, 17 Feb 2023 20:12:45 GMT
2. **owner**: set to **Joel Sherrill** <joel@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In e3f4060/rtems-source-builder:

```
Update gdb to 12.1 including patch for hosts with readline 8.2
Issue for hosts with readline 8.2 also exists with gdb 12.1.
```



Closes #4859.

## 4860 - Waf Failure on CentOS 8 Stream

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4860">https://devel.rtems.org/ticket/4860</a> ( <a href="https://devel.rtems.org/ticket/4860">https://devel.rtems.org/ticket/4860</a> )
<b>Id</b>	4860
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	17 February 2023 15:37:03
<b>Modified</b>	20 February 2023 22:50:33
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	waf
<b>Cc</b>	Jeff Mayes
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Jeff Mayes reported (<https://lists.rtems.org/pipermail/devel/2023-February/074424.html>) that builds on the CentOS 8 Stream test host are failing with this:

```
Using rtems for RTEMS source
Testing: sparc erc32-sis
BSP to Build: erc32
Traceback (most recent call last):
  File "./waf", line 167, in
    from waflib import Scripting
  File "/home/tester/rtems-cron-6/rtems/.waf-2.0.20-36f5354d605298f6a89c09e0c7ef6c1d/waflib/Scripting.py", line 7, in
    from waflib import Utils,Configure,Logs,Options,ConfigSet,Context,Errors,Build,Node
  File "/home/tester/rtems-cron-6/rtems/.waf-2.0.20-36f5354d605298f6a89c09e0c7ef6c1d/waflib/Configure.py", line 6, in
    from waflib import ConfigSet,Utils,Options,Logs,Context,Build,Errors
  File "/home/tester/rtems-cron-6/rtems/.waf-2.0.20-36f5354d605298f6a89c09e0c7ef6c1d/waflib/Options.py", line 6, in
    from waflib import Logs,Utils,Context,Errors
  File "/home/tester/rtems-cron-6/rtems/.waf-2.0.20-36f5354d605298f6a89c09e0c7ef6c1d/waflib/Context.py", line 183
    raise Errors.WafError('Execution failure: %s'%str(e),ex=e),None,sys.exc_info()[2],None,sys.exc_info()[2])
SyntaxError: invalid syntax
FAILED: Unable to waf distclean rtems
```

In follow up emails, Chris Johns suggested updating waf which Jeff reported fixed the issue.

The action for this ticket is to update waf in the following repositories:

- rtems
- rtems-examples
- rtems-docs
- rtems-libbsd
- rtems-lwip
- rtems-net-legacy (OK -- already on latest waf)
- rtems-tools

### Comment 1

1. **Joel Sherrill**, Fri, 17 Feb 2023 20:32:35 GMT
2. **description:** modified (diff)

### Comment 2

1. **Joel Sherrill**, Mon, 20 Feb 2023 15:45:34 GMT

In 9b4aed1/rtems:

```
waf: Update to waf 2.0.25
```

Updates #4860

### Comment 3

1. **Joel Sherrill**, Mon, 20 Feb 2023 15:47:20 GMT

In b0fc22c/rtems-libbsd:

```
waf: Update to waf 2.0.25
```

Updates #4860

### Comment 4

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

1. **Joel Sherrill**, Mon, 20 Feb 2023 15:47:50 GMT

In 1aa4cb8/rtems-libbsd:

waf: Update to waf 2.0.25  
Updates #4860

#### Comment 5

1. **Joel Sherrill**, Mon, 20 Feb 2023 15:49:11 GMT

In 0b9bb40/rtems-tools:

waf: Update to waf 2..0.25  
Updates #4860

#### Comment 6

1. **Joel Sherrill**, Mon, 20 Feb 2023 17:43:45 GMT

In 2f7ebf7/rtems-docs:

waf: Update to waf 2.0.25  
Updates #4860

#### Comment 7

1. **Joel Sherrill**, Mon, 20 Feb 2023 22:50:33 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **fixed**

All repos should be updated to the latest waf. Closing.

---

### **4861 - "Single HTML" links on docs.rtems.org lead to empty pages**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4861">https://devel.rtems.org/ticket/4861</a> ( <a href="https://devel.rtems.org/ticket/4861">https://devel.rtems.org/ticket/4861</a> )
<b>Id</b>	4861
<b>Reporter</b>	Jens Schweikhardt
<b>Created</b>	17 February 2023 15:59:48
<b>Modified</b>	17 February 2023 16:11:18
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/website
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### **Description**

Point your browser to docs.rtems.org.

All the orange icon "HTML" links in the "Single HTML" columns lead to an empty page. The PDF links are ok.

#### Comment 1

1. **Joel Sherrill**, Fri, 17 Feb 2023 16:11:18 GMT
  2. **owner**: set to **Chris Johns**
  3. **status**: changed from **new** to **assigned**
  4. **milestone**: set to **6.1**
- 

### **4862 - score/ & bsp/s: Unused input parameters**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4862">https://devel.rtems.org/ticket/4862</a> ( <a href="https://devel.rtems.org/ticket/4862">https://devel.rtems.org/ticket/4862</a> )
<b>Id</b>	4862
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	23 February 2023 12:36:23
<b>Modified</b>	28 July 2023 14:55:19
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	unspecified
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The following functions list input parameters on their signature that seem not to be used:

```
File      Function      Line
-----
bsp\shared\cache\cacheimpl.hmp_cache_inst_inv_all 293
bsp\shared\dev\clock\clockimpl.hvoid Clock_isr130
bsp\shared\dev\clock\clockimpl.hrtems_isr Clock_isr134
bsp\shared\irq\irq-generic.cbsp_interrupt_allocate_handler_index62
bsp\sparc\leon3\start\bspclean.cbsp_fatal_extension70
cpukit\score\src\threadchangepriority.cstatic void Thread_Priority_action_change( ); 92
cpukit\score\src\threadq.c_Thread_queue_MP_callout_do_nothing157
cpukit\score\src\threadqenqueue.c_Thread_queue_Deadlock_fatal382
cpukit\score\src\threadqops.c_Thread_queue_FIFO_do_initialize137
cpukit\score\src\threadtimeout.c_Thread_queue_Add_timeout_ticks28
cpukit\score\src\threadrestart.c_Thread_Join_flush_filter84
cpukit\score\src\userextitrate.c_User_extensions_Thread_begin_visitor102
```

Could one please double-check if in each case the unused parameters can be safely removed from the function's signature? PS: The first functions are also implemented within .h files and perhaps could be moved to .c files.

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-CODE-VER-028.

**Comment 1**

1. **Sebastian Huber**, Thu, 23 Mar 2023 16:25:03 GMT
2. **owner:** set to **Sebastian Huber**
3. **status:** changed from **new** to **assigned**
4. **type:** changed from **defect** to **enhancement**
5. **component:** changed from **admin** to **unspecified**
6. **milestone:** set to **6.1**

**Comment 2**

1. **Sebastian Huber**, Wed, 05 Apr 2023 12:00:12 GMT

In 32fe5724/rtems:

```
bsp: Mark argument as unused
Update #4862.
```

**Comment 3**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:28:32 GMT

Could the actual parameter that isn't referenced be provided? This looks easy to resolve if there were complete information.

**Comment 4**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:29:22 GMT
2. **summary:** changed from **Unused input parameters** to **score/ & bsp/: Unused input parameters**

**Comment 5**

1. **Daniel Páscoa**, Fri, 23 Jun 2023 14:14:00 GMT

Most of the functions listed on the initial ticket description only have a single parameter.

Regarding the others, the information is included hereafter:

```
File      Function      Unused parameter(s)
-----
cpukit\score\src\threadchangepriority.c_Thread_Priority_action_change*priority_actions and *arg
cpukit\score\src\threadq.c_Thread_queue_MP_callout_do_nothing*the_proxy and mp_id
cpukit\score\src\threadqops.c_Thread_queue_FIFO_do_initialize*queue and *queue_context
cpukit\score\src\threadtimeout.c_Thread_queue_Add_timeout_ticksqueue*
cpukit\score\src\threadrestart.c_Thread_Join_flush_filter*queue
cpukit\score\src\userextitrate.c_User_extensions_Thread_begin_visitor*arg
```

**Comment 6**

1. **Sebastian Huber**, Tue, 18 Jul 2023 19:55:24 GMT

There are two obvious reasons, why some of these functions have unused parameters:

When functions are used through function pointers, then they may have unused parameters since other functions may need the parameter. Only if the parameter is unused in all functions associated with a function pointer, the parameter is really superfluous. API backwards compatibility.

Could you please remove these false positives from the list.

**Comment 7**

1. **Sebastian Huber**, Fri, 28 Jul 2023 14:55:19 GMT

In a41611a/rtems:

```
bsps/irq: Remove unused parameter
Update #4862.
```

**4863 - Operations evaluation order.**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4863">https://devel.rtems.org/ticket/4863</a> ( <a href="https://devel.rtems.org/ticket/4863">https://devel.rtems.org/ticket/4863</a> )
<b>Id</b>	4863
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	23 February 2023 12:37:47
<b>Modified</b>	26 April 2023 08:22:47
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Within cpukit\include\rtems\score\objectimpl.h line 545 one has:

if ( !the\_api the\_api > OBJECTS\_APIS\_LAST ) This shall be equivalent to “if ( !(the\_api) (the\_api > OBJECTS\_APIS\_LAST ))”, but at first glance, this is not always obvious to everyone and one might need to read further documentation to be fully sure of it.

We would suggest the parenthesis be added so that the code logic is straightforward. In this case, one would not call it an ‘excess’ as stated within the RTEMS SW Eng. Manual (“Avoid excess parentheses. Learn the operator precedence. rules.”).

Additional Notes: This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-CODE-VER-076.

**Comment 1**

1. **Daniel Páscoa**, Thu, 23 Feb 2023 14:30:55 GMT

The operators were interpreted as new lines. This is the correct description (with a white space between the operators):

Within cpukit\include\rtems\score\objectimpl.h line 545 one has:

if ( !the\_api || the\_api > OBJECTS\_APIS\_LAST ) This shall be equivalent to “if ( !(the\_api) || (the\_api > OBJECTS\_APIS\_LAST ))”, but at first glance, this is not always obvious to everyone and one might need to read further documentation to be fully sure of it.

**Comment 2**

1. **Joel Sherrill**, Thu, 23 Feb 2023 15:17:54 GMT

The code would be better written avoiding the use of compound expressions which will ease the testing when moving to higher design assurance levels which require MCDC style analysis. I would recommend trying to rewrite code to avoid compound expressions. This effectively can reduce testing to simpler decision/branch coverage. Here's my recommendation which also adds the braces which I am surprised didn't get flagged:

```
if ( !the_api ) {
    return false;
}
if ( the_api > OBJECTS_APIS_LAST )
    return false;
}
return true;
}
```

FWIW I don't think the code as written was hard to read or confusing. I wouldn't have changed based solely on that report. The rules of evaluation in C are clear enough that anyone confused by this shouldn't be touching this code anyway.

**Comment 3**

1. **Sebastian Huber**, Thu, 23 Mar 2023 15:22:20 GMT
2. **component**: changed from **admin** to **score**
3. **milestone**: set to **6.1**

**Comment 4**

1. **Sebastian Huber**, Wed, 26 Apr 2023 08:22:47 GMT
2. **owner**: set to **Sebastian Huber <sebastian.huber@...>**
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 6979b03/rtems:

```
score: Simplify _Objects_Is_api_valid()
Close #4863.
```

**4867 - Clean up rtems-lwip uLan directory**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4867">https://devel.rtems.org/ticket/4867</a> ( <a href="https://devel.rtems.org/ticket/4867">https://devel.rtems.org/ticket/4867</a> )
<b>Id</b>	4867
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	3 March 2023 14:35:49
<b>Modified</b>	3 July 2023 14:52:57
<b>Owner</b>	Kinsey Moore
<b>Type</b>	defect
<b>Component</b>	network/lwip
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The uLan directory in rtems-lwip was originally sourced from another project as documented in its ORIGIN.uLan file. This directory contains both some BSP-specific drivers as well as some of the core RTEMS/lwIP integration code in the form of sys\_arch.c/h.

Permission has been given by the authors of this upstream repository to relicense the code under the terms of the rtemslwip directory so as to remove references to "uLan" since this term is relatively unrelated to either project and just so happened to be the location of the source.  
<https://lists.rtems.org/pipermail/devel/2023-March/074525.html>

Core integration components should be rehomed under rtemslwip/common and BSP-specific code should be rehomed under rtemslwip in a BSP-specific directory or in a new root directory with appropriate LICENSE and ORIGIN files depending on its provenance.

**Comment 1**

1. **Joel Sherrill**, Thu, 22 Jun 2023 20:53:40 GMT
2. **owner**: set to **Kinsey Moore**
3. **status**: changed from **new** to **assigned**
4. **component**: changed from **admin** to **network/lwip**

**Comment 2**

1. **Kinsey Moore**, Mon, 03 Jul 2023 14:52:57 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In d0cb318/rtems-lwip:

```
Alter ownership of components in uLan
```

```
This commit breaks up the uLan directory and removes its ORIGIN and COPYING metadata in favor of this repository being the authoritative source of these sources as per the wishes of the originator of these files. More information can be found here:
https://lists.rtems.org/pipermail/devel/2023-March/074525.html
```

```
Closes #4867
```

**4869 - Add QSPI Flash Device API**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4869">https://devel.rtems.org/ticket/4869</a> ( <a href="https://devel.rtems.org/ticket/4869">https://devel.rtems.org/ticket/4869</a> )
<b>Id</b>	4869
<b>Reporter</b>	Aaron N
<b>Created</b>	6 March 2023 02:27:09
<b>Modified</b>	30 June 2023 00:13:22
<b>Owner</b>	chrisj@...
<b>Type</b>	enhancement
<b>Component</b>	dev/spi
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Add an API for qspi flash to create device node.

**Attachments:**

- 
- Aaron N, Mon, 06 Mar 2023 02:31:48 GMT**  
attach: set to [0003-cpukit-spi-Add-API-for-QSPI-Flash.patch](https://devel.rtems.org/ticket/4869/0003-cpukit-spi-Add-API-for-QSPI-Flash.patch) (<https://devel.rtems.org/ticket/4869/0003-cpukit-spi-Add-API-for-QSPI-Flash.patch>)
  - Aaron N, Mon, 06 Mar 2023 04:40:12 GMT**  
attach: set to [0006-dev-spi-Fixed-write-behaviour-for-qspi\\_flash.patch](https://devel.rtems.org/ticket/4869/0006-dev-spi-Fixed-write-behaviour-for-qspi_flash.patch) ([https://devel.rtems.org/ticket/4869/0006-dev-spi-Fixed-write-behaviour-for-qspi\\_flash.patch](https://devel.rtems.org/ticket/4869/0006-dev-spi-Fixed-write-behaviour-for-qspi_flash.patch))
  - Aaron N, Thu, 09 Mar 2023 00:33:35 GMT**  
attach: set to [0006-libmisc-shell-Add-spiflash-command.patch](https://devel.rtems.org/ticket/4869/0006-libmisc-shell-Add-spiflash-command.patch) (<https://devel.rtems.org/ticket/4869/0006-libmisc-shell-Add-spiflash-command.patch>)
  - Aaron N, Thu, 09 Mar 2023 03:13:33 GMT**  
attach: set to [0003-cpukit-spi-Add-API-for-SPI-Flash.patch](https://devel.rtems.org/ticket/4869/0003-cpukit-spi-Add-API-for-SPI-Flash.patch) (<https://devel.rtems.org/ticket/4869/0003-cpukit-spi-Add-API-for-SPI-Flash.patch>)
  - Aaron N, Wed, 15 Mar 2023 23:25:11 GMT**  
attach: set to [0003-cpukit-flash-Add-API-for-Flash-devices.patch](https://devel.rtems.org/ticket/4869/0003-cpukit-flash-Add-API-for-Flash-devices.patch) (<https://devel.rtems.org/ticket/4869/0003-cpukit-flash-Add-API-for-Flash-devices.patch>)
  - Aaron N, Wed, 15 Mar 2023 23:25:29 GMT**  
attach: set to [0006-libmisc-shell-Add-flashdev-command.patch](https://devel.rtems.org/ticket/4869/0006-libmisc-shell-Add-flashdev-command.patch) (<https://devel.rtems.org/ticket/4869/0006-libmisc-shell-Add-flashdev-command.patch>)
- 

**Comment 1**

- Chris Johns, Mon, 06 Mar 2023 02:41:29 GMT**

Thanks for this.

Should this be \_\_SPI Flash\_\_ or SPIFLASH? QSPI is quad SPI and there also exists octal and it would be good to have both supported?

**Comment 2**

- Chris Johns, Wed, 08 Mar 2023 00:30:06 GMT**

Can we please have an ioctl command that lets a user can set a region in the flash device access is limited to? It may be nice to make the read and write calls relative to a region's base address. By default a device open maps to the entire flash.

The use case is allowed shared access to the flash device. For example JFFS on a region and the ability to modified a boot area.

**Comment 3**

- Aaron N, Thu, 09 Mar 2023 00:31:19 GMT**

Renamed the API to spiflash to reflect it's use for more then QSPI flash. I have also added region set and unset to define a base and length for limited access. Offsets are relative to the base set.

**Comment 4**

- Aaron N, Wed, 15 Mar 2023 23:26:56 GMT**

Renamed to flashdev for wider compatibility and added type IOCTL.

**Comment 5**

- Joel Sherrill, Thu, 22 Jun 2023 21:20:13 GMT**

Can this be closed now?

**Comment 6**

- Chris Johns, Thu, 22 Jun 2023 21:22:37 GMT**

No, it is being worked on.

### Comment 7

1. **Chris Johns**, Fri, 30 Jun 2023 00:13:22 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

## 4870 - Add features for QSPI Flash on Xilinx Versal

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4870">https://devel.rtems.org/ticket/4870</a> ( <a href="https://devel.rtems.org/ticket/4870">https://devel.rtems.org/ticket/4870</a> )
<b>Id</b>	4870
<b>Reporter</b>	Aaron N
<b>Created</b>	6 March 2023 02:35:37
<b>Modified</b>	9 March 2023 00:32:51
<b>Owner</b>	chrisj@...
<b>Type</b>	enhancement
<b>Component</b>	arch/aarch64
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Adds bug fixes for code ported from Xilinx, adds ReadId? function for QSPI flash, adds wrapper to Xilinx driver to allow use of QSPI flash device API and ports JFFS2 driver from ZynqMP.

### Attachments:

- 1 **Aaron N, Mon, 06 Mar 2023 02:36:01 GMT**  
**attach**: set to [0001-bsps-Fix-xqspipsu-build-issues-on-versal.patch](https://devel.rtems.org/ticket/4870/0001-bsps-Fix-xqspipsu-build-issues-on-versal.patch) (<https://devel.rtems.org/ticket/4870/0001-bsps-Fix-xqspipsu-build-issues-on-versal.patch>)
- 2 **Aaron N, Mon, 06 Mar 2023 02:36:35 GMT**  
**attach**: set to [0002-bsps-Add-ReadId-command-Xilinx-GQSPI-flash-helper.patch](https://devel.rtems.org/ticket/4870/0002-bsps-Add-ReadId-command-Xilinx-GQSPI-flash-helper.patch) (<https://devel.rtems.org/ticket/4870/0002-bsps-Add-ReadId-command-Xilinx-GQSPI-flash-helper.patch>)
- 3 **Aaron N, Mon, 06 Mar 2023 02:38:28 GMT**  
**attach**: set to [0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.patch](https://devel.rtems.org/ticket/4870/0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.patch) (<https://devel.rtems.org/ticket/4870/0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.patch>)
- 4 **Aaron N, Mon, 06 Mar 2023 02:38:42 GMT**  
**attach**: set to [0005-aarch64-versal-Port-JFFS2-GQSPI-NOR-Driver-from-Zynq.patch](https://devel.rtems.org/ticket/4870/0005-aarch64-versal-Port-JFFS2-GQSPI-NOR-Driver-from-Zynq.patch) (<https://devel.rtems.org/ticket/4870/0005-aarch64-versal-Port-JFFS2-GQSPI-NOR-Driver-from-Zynq.patch>)
- 5 **Aaron N, Thu, 09 Mar 2023 00:31:59 GMT**  
**attach**: set to [0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.2.patch](https://devel.rtems.org/ticket/4870/0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.2.patch) (<https://devel.rtems.org/ticket/4870/0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.2.patch>)
- 6 **Aaron N, Wed, 15 Mar 2023 23:27:33 GMT**  
**attach**: set to [0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.3.patch](https://devel.rtems.org/ticket/4870/0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.3.patch) (<https://devel.rtems.org/ticket/4870/0004-aarch64-versal-Add-wrapper-for-Xilinx-GQSPI-for-QSPI.3.patch>)

### Comment 1

1. **Aaron N**, Thu, 09 Mar 2023 00:32:51 GMT  
Updated patch 4 to reflect changes to spiflash API begin renamed

## 4872 - GDB 13.1 does not build on FreeBSD 13.1

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4872">https://devel.rtems.org/ticket/4872</a> ( <a href="https://devel.rtems.org/ticket/4872">https://devel.rtems.org/ticket/4872</a> )
<b>Id</b>	4872
<b>Reporter</b>	Chris Johns
<b>Created</b>	9 March 2023 03:10:07
<b>Modified</b>	9 March 2023 23:38:51
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/gdb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

If the binutils package is installed GDB does not build.

See [https://sourceware.org/bugzilla/show\\_bug.cgi?id=30214](https://sourceware.org/bugzilla/show_bug.cgi?id=30214)

**Comment 1**

1. **Chris Johns**, Thu, 09 Mar 2023 23:38:51 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In e5abdec/rtems-source-builder:

```
6/gdb: fix building on FreeBSD 13.1
```

See [https://sourceware.org/bugzilla/show\\_bug.cgi?id=30214](https://sourceware.org/bugzilla/show_bug.cgi?id=30214)

Closes #4872

---

**4874 - Undefined behaviour**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4874">https://devel.rtems.org/ticket/4874</a> ( <a href="https://devel.rtems.org/ticket/4874">https://devel.rtems.org/ticket/4874</a> )
<b>Id</b>	4874
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 March 2023 12:37:19
<b>Modified</b>	9 March 2023 12:55:23
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	rtems
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

If one searches within SRSs or ICDs for 'undefined behaviour' one will find specifications/functions on which descriptions mention conditions that will lead to 'undefined behaviour', e.g.:

...

```
__spec:/rtems/clock/if/get-boot-time__
```

...

boot\_time is the pointer to a struct timespec object. The time elapsed since the Unix epoch at some time point during system initialization call will be stored in this object. Calling the directive with a pointer equal to NULL is undefined behaviour."

One created specific tests to further access the eventual impacts, for instance in the clock-related functions below:

```
spec:/rtems/clock/if/get-boot-time
```

```
spec:/rtems/clock/if/get-boot-time-bintime
```

```
spec:/rtems/clock/if/get-boot-time-timeval
```

```
spec:/rtems/clock/if/get-monotonic
```

```
spec:/rtems/clock/if/get-monotonic-bintime
```



spec:/rtems/clock/if/get-monotonic-coarse  
spec:/rtems/clock/if/get-monotonic-coarse-bintime  
spec:/rtems/clock/if/get-monotonic-coarse-timeval  
spec:/rtems/clock/if/get-monotonic-timeval  
spec:/rtems/clock/if/get-realtime  
spec:/rtems/clock/if/get-realtime-bintime  
spec:/rtems/clock/if/get-realtime-coarse  
spec:/rtems/clock/if/get-realtime-coarse-bintime  
spec:/rtems/clock/if/get-realtime-coarse-timeval  
spec:/rtems/clock/if/get-realtime-timeval

The outcome was:

There is no internal check for a NULL pointer in these functions, so when called with a null pointer argument there is unwanted behaviour for both the GR712rc and GR740; an attempt to access memory location 0.

For the GR712rc board this memory position is not mapped and causes a trap to be raised (this trap handler leads to unpredictable results, the workflow of the program is not recoverable). For the GR740 board the actual memory position is either read or written (the previous value being overridden with unpredictable results).

So, even if somehow this shall also be a user responsibility, shouldn't one adopt a safe approach to this and add input checking for these functions?

\_\_Additional Notes: \_\_

This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-REQ-VER-008 and RTEMS-SMP-VAL-005.

### Comment 1

1. **Sebastian Huber**, Thu, 09 Mar 2023 12:54:46 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **wontfix**

This was discussed on the RTEMS mailing list some time ago:

<https://lists.rtems.org/pipermail/devel/2021-November/069991.html>

Quite frankly, someone passing a NULL pointer to functions like `void rtems_clock_get_monotonic_bintime(struct bintime *time_point)` will also use the NULL pointer later. The next release of the pre-qualified RTEMS will probably contain the `clock_get()` function which performs these NULL pointer checks.

### Comment 2

1. **Sebastian Huber**, Thu, 09 Mar 2023 12:55:23 GMT
2. **keywords:** **qualification** added
3. **version:** set to **6**
4. **component:** changed from **admin** to **rtems**
5. **milestone:** set to **6.1**

---

## 4875 - LEON3FT - Power-down workaround

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4875">https://devel.rtems.org/ticket/4875</a> ( <a href="https://devel.rtems.org/ticket/4875">https://devel.rtems.org/ticket/4875</a> )
<b>Id</b>	4875
<b>Reporter</b>	Daniel Páscoa
<b>Created</b>	9 March 2023 12:42:53
<b>Modified</b>	22 June 2023 21:03:07
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/sparc
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Within `bsp/sparc/leon3/start\bspidle.S` there is the attached code snapshot, on which line 26 seems to contradict GR712RC board User Manual section 1.7.8 (Errata # 8 - LEON3FT Cache Controller: Incorrect Bus Access After Power-Down):

"1.7.8 LEON3FT Cache Controller: Incorrect Bus Access After Power-Down

A LEON with support for clock gating has one clock that is kept running and one clock that is gated off in power-down mode. Due to a design error, the gated clock was used for logic that keeps track of the state of the AMBA bus. Due to this error, the first instruction or data (whichever is first) access to the bus after leaving power-down might be performed incorrectly.

...  
 Note that the stack pointer or other cachable memory should never be used as the source operand, even if using ASI 1, since this may lead to faulty data being loaded into the data cache."

One has asked Gaisler's opinion and this has been the response: "The errata is perhaps a bit too strongly worded. There is a risk that the load instruction used in the workaround will lead to fetching in incorrect data that gets cached if the address is in a cacheable area but that in itself is not a problem. In order for that to propagate into a real problem there has to be a subsequent load from that address that hits in the Dcache and uses the invalid data before that cache line is either flushed or the data is overwritten by stores. If you know that the address (and the same cache line) will not be loaded from this does not happen. In this case it is reading from the stack of the idle task which is never read from once the idle task is running. So I do not see that this can create a real issue."

Either way, we wanted the RTEMS community to double-check that indeed there is not a real problem and eventually place additional comments on the code to better contextualize it w.r.t. the GR712RC User Manual errata # 8.

\_\_(Image attached)\_\_

\_\_Additional Notes:\_\_

This ticket was raised as an outcome of the Independent SW Verification and Validation (ISVV) for ESA-promoted RTEMS SMP Qualification Data Packs (<https://rtems-qual.io.esa.int>). The original ISVV reference for this issue is RTEMS-SMP-CODE-VER-073.

#### Attachments:

---

1 **Daniel Páscoa, Thu, 09 Mar 2023 12:43:34 GMT**

**attach:** set to [Screenshot 2023-03-09 125938.jpg \(https://devel.rtems.org/ticket/4875/Screenshot%202023-03-09%20125938.jpg\)](#)

---

#### Comment 1

1. **Sebastian Huber, Thu, 09 Mar 2023 13:01:31 GMT**

2. **type:** changed from **defect** to **enhancement**

3. **version:** set to **6**

4. **component:** changed from **admin** to **arch/sparc**

5. **milestone:** set to **6.1**

#### Comment 2

1. **Sebastian Huber, Wed, 15 Mar 2023 06:22:08 GMT**

2. **keywords:** **qualification** added

#### Comment 3

1. **Joel Sherrill, Thu, 22 Jun 2023 21:03:07 GMT**

2. **owner:** set to **Sebastian Huber**

3. **status:** changed from **new** to **assigned**

4. **summary:** changed from **Power-down workaround** to **LEON3FT - Power-down workaround**

---

## 4878 - sptests/spsysinit01 sem\_open call only has 3 parameters with O\_CREAT flag (cloned)

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4878">https://devel.rtems.org/ticket/4878</a> ( <a href="https://devel.rtems.org/ticket/4878">https://devel.rtems.org/ticket/4878</a> )
<b>Id</b>	4878
<b>Reporter</b>	Lucian-Raul Silistru
<b>Created</b>	13 March 2023 14:29:44
<b>Modified</b>	14 March 2023 06:43:33
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

#### Description

Cloned from #4877:

When calling `sem_open` with the `O_CREAT` flag the `sem_open` function requires 4 parameters. It will:  
`value = va_arg(args, unsigned int);`  
 so the "value" argument will be randomly chosen.

`sem_open` can fail if the random value is not a valid semaphore value, failing the test.

#### Comment 1

1. **Sebastian Huber**, Tue, 14 Mar 2023 06:43:33 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 377eae4/rtems:

```
spsysinit01: Fix sem_open() call

The O_CREAT flag requires a mode and initial value as third and fourth argument.

Close #4878.
```

## 4881 - powerpc gas and ld warnings

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4881">https://devel.rtems.org/ticket/4881</a> ( <a href="https://devel.rtems.org/ticket/4881">https://devel.rtems.org/ticket/4881</a> )
<b>Id</b>	4881
<b>Reporter</b>	Chris Johns
<b>Created</b>	21 March 2023 04:51:55
<b>Modified</b>	21 March 2023 21:55:03
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/binutils
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The upgraded binutils generates new warnings when linking executables:

```
/opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/../../../../powerpc-rtems6/bin/ld: warning: /opt/work/rtems/6-bsp/powerpc-rtems6/mvme2307/lib/vectors_entry.o: missing .note.GNU-stack section implies executable stack
/opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/../../../../powerpc-rtems6/bin/ld: NOTE: This behaviour is deprecated and will be removed in a future version of the linker
/opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/../../../../powerpc-rtems6/bin/ld: warning: /opt/work/chris/rtems/libbsd/rtems-libbsd.git/build/powerpc-rtems6-mvme2307-default/termios05.exe has a LOAD segment with RWX permissions
/opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/../../../../powerpc-rtems6/bin/ld: warning: /opt/work/chris/rtems/libbsd/rtems-libbsd.git/build/powerpc-rtems6-mvme2307-default/termios05.exe has a LOAD segment with RWX permissions
```

### Comment 1

1. **Chris Johns**, Tue, 21 Mar 2023 06:23:45 GMT

This article by Nick Clifton explains the changes in binutils-2.39:

<https://www.redhat.com/en/blog/linkers-warnings-about-executable-stacks-and-segments>

### Comment 2

1. **Chris Johns**, Tue, 21 Mar 2023 06:57:19 GMT

This diff removes the warning:

```
diff --git a/bsps/powerpc/shared/start/vectors_entry.S b/bsps/powerpc/shared/start/vectors_entry.S
index 07b17a48af..9140c55121 100644
--- a/bsps/powerpc/shared/start/vectors_entry.S
+++ b/bsps/powerpc/shared/start/vectors_entry.S
@@ -10,6 +10,7 @@
`#include `
    PUBLIC_VAR (__rtems_start)
+    .section .note.GNU-stack,"",@progbits
    .section .entry_point_section,"awx",@progbits
/*
 * Entry point information used by bootloader code
```

however it moves to another object file:

```
/opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/../../../../powerpc-rtems6/bin/ld: warning: /opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/m604/ecrtn.o: missing .note.GNU-stack section implies executable stack
/opt/work/6/lib/gcc/powerpc-rtems6/12.2.1/../../../../powerpc-rtems6/bin/ld: NOTE: This behaviour is deprecated and will be removed in a future version of the linker
```

This time it is in the gcc build object files.

### Comment 3

1. **Chris Johns**, Tue, 21 Mar 2023 09:26:15 GMT

The following removes the warnings:

```
[powerpc/mvme2307]
LINKFLAGS = -Wl,--no-warn-execstack -Wl,--no-warn-rwx-segments
```

I do not know how to add these options to the LINKFLAGS in the spec files.

#### **Comment 4**

1. **Chris Johns**, Tue, 21 Mar 2023 09:51:24 GMT

I will get the RSB to disable these warnings for RTEMS. This will mean we will not have to change anything and users will not see these warnings and be confused.

#### **Comment 5**

1. **Chris Johns**, Tue, 21 Mar 2023 10:50:55 GMT

2. **owner:** set to **Chris Johns**

3. **status:** changed from **new** to **assigned**

#### **Comment 6**

1. **Chris Johns**, Tue, 21 Mar 2023 21:55:03 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In f0e34ea/rtems-source-builder:

```
binutils: Disable stack exec and RWX section warnings
```

```
Binutils 2.39 and later enable by default warnings for executables with executable stack and RWX sections. Disable them.
```

```
Closes #4881
```

---

## **4882 - mvme2703 legacy network build failure**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4882">https://devel.rtems.org/ticket/4882</a> ( <a href="https://devel.rtems.org/ticket/4882">https://devel.rtems.org/ticket/4882</a> )
<b>Id</b>	4882
<b>Reporter</b>	Chris Johns
<b>Created</b>	21 March 2023 04:56:36
<b>Modified</b>	22 June 2023 22:05:14
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	network/legacy
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### **Description**

Building powerpc/mvme2703 BSP with the legacy networking fails with:

```

../../netinet/in.c: In function 'in_canforward':
../../netinet/in.c:117:13: warning: implicit declaration of function 'IN_CLASSA'; did you mean 'IN_BADCLASS'? [-Wimplicit-function-declaration]
 117 |         if (IN_CLASSA(i)) {
      |             ^~~~~~
      |             IN_BADCLASS
../../netinet/in.c:118:27: error: 'IN_CLASSA_NET' undeclared (first use in this function)
 118 |         net = i & IN_CLASSA_NET;
      |             ^~~~~~
../../netinet/in.c:118:27: note: each undeclared identifier is reported only once for each function it appears in
../../netinet/in.c:119:41: error: 'IN_LOOPBACKNET' undeclared (first use in this function); did you mean 'IN_LOOPBACK'?
 119 |         if (net == 0 || net == (IN_LOOPBACKNET << IN_CLASSA_NS_SHIFT))
      |                                 ^~~~~~
      |                                 IN_LOOPBACK
../../netinet/in.c:119:59: error: 'IN_CLASSA_NS_SHIFT' undeclared (first use in this function)
 119 |         if (net == 0 || net == (IN_LOOPBACKNET << IN_CLASSA_NS_SHIFT))
      |                                 ^~~~~~
../../netinet/in.c: In function 'in_ifinit':
../../netinet/in.c:495:34: error: 'IN_CLASSA_NET' undeclared (first use in this function)
 495 |         ia->ia_netmask = IN_CLASSA_NET;
      |                          ^~~~~~
../../netinet/in.c:496:18: warning: implicit declaration of function 'IN_CLASSB'; did you mean 'IN_BADCLASS'? [-Wimplicit-function-declaration]
 496 |         else if (IN_CLASSB(i))
      |                   ^~~~~~
      |                   IN_BADCLASS
../../netinet/in.c:497:34: error: 'IN_CLASSB_NET' undeclared (first use in this function)
 497 |         ia->ia_netmask = IN_CLASSB_NET;
      |                          ^~~~~~
../../netinet/in.c:499:34: error: 'IN_CLASSC_NET' undeclared (first use in this function)
 499 |         ia->ia_netmask = IN_CLASSC_NET;
      |                          ^~~~~~

```

**Comment 1**

1. Chris Johns, Tue, 21 Mar 2023 05:49:58 GMT

Also have:

```

[ 29/223] Compiling libtest/testbusy.c
../../libtest/testbusy.c: In function 'rtems_test_busy_cpu_usage':
../../libtest/testbusy.c:31:3: error: too many arguments to function '_Thread_Get_CPU_time_used'
 31 |     Thread_Get_CPU_time_used( executing, &start );
      |     ^~~~~~
In file included from ../../libtest/testbusy.c:21:
/opt/work/rtems/6-bsp/powerpc-rtems6/mvme2307/lib/include/rtems/score/threadimpl.h:1306:19: note: declared here
1306 | Timestamp_Control Thread_Get_CPU_time_used( Thread_Control *the_thread );
      |     ^~~~~~
../../libtest/testbusy.c:35:5: error: too many arguments to function '_Thread_Get_CPU_time_used'
 35 |     Thread_Get_CPU_time_used( executing, &now );
      |     ^~~~~~
/opt/work/rtems/6-bsp/powerpc-rtems6/mvme2307/lib/include/rtems/score/threadimpl.h:1306:19: note: declared here
1306 | Timestamp_Control Thread_Get_CPU_time_used( Thread_Control *the_thread );
      |     ^~~~~~

```

**Comment 2**

1. Chris Johns, Tue, 21 Mar 2023 05:57:40 GMT

There are a couple of issues. The headers installed with the tools requires `-DIN_HISTORICAL_NETS=1` on the command line and the score API for the CPU usage has changed.

**Comment 3**

1. Chris Johns, Thu, 22 Jun 2023 22:05:14 GMT
2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

**4884 - I2C default ioctl handler does not handle set clock**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4884">https://devel.rtems.org/ticket/4884</a> ( <a href="https://devel.rtems.org/ticket/4884">https://devel.rtems.org/ticket/4884</a> )
<b>Id</b>	4884
<b>Reporter</b>	Chris Johns
<b>Created</b>	22 March 2023 04:53:13
<b>Modified</b>	22 March 2023 05:26:40
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	dev/i2c
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The base struct for an I2C driver can set `set_clock_handler` so a user can change the I2C clock speed. The default `ioctl` handler does not check for the `I2C_BUS_SET_CLOCK` command and if the `set_clock_handler` is set calling it.

### Comment 1

1. **Chris Johns**, Wed, 22 Mar 2023 05:26:40 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **invalid**

Ah sorry I was looking at a device and not the bus.

## 4887 - RTEMS Net Legacy does not build as a package in the RSB

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4887">https://devel.rtems.org/ticket/4887</a> ( <a href="https://devel.rtems.org/ticket/4887">https://devel.rtems.org/ticket/4887</a> )
<b>Id</b>	4887
<b>Reporter</b>	Chris Johns
<b>Created</b>	23 March 2023 02:24:52
<b>Modified</b>	22 June 2023 22:35:02
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	network/legacy
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The waf support does not handle staged builds or the options `--rtems-tools` and `--rtems` at the same time. The build fails when reading the `rtemsbsp` static library because it will not be in the `PREFIX`.

Also the build script scans for `.c` and `.h` files. This is fragile. If someone copies in a C file for some reason it is picked up. The sources and headers need to be explicit in build script.

### Attachments:

- 1 **Chris Johns**, Mon, 27 Mar 2023 03:40:31 GMT  
attach: set to [r](https://devel.rtems.org/ticket/4887/r) (<https://devel.rtems.org/ticket/4887/r>)

### Comment 1

1. **Chris Johns**, Thu, 23 Mar 2023 21:20:31 GMT

I do not understand what the `bsp_drivers.py` use of `os.path.expanduser` is for? A build should not reference files outside the source tree unless there are options a user uses.

I am not following the `bsp_driver` code. Testing it I am seeing for `atsamv`:

```
arm/atsamv:
({'arm/atsamv': ['bsps/arm/atsamv/arm/atsamv/net', 'bsps/arm/atsamv/arm/atsamv/include']}, {'arm/atsamv': []})
```

There is `bsps/arm/atsam` but no `bsps/arm/atsamv` and `bsps/arm/atsamv/arm/atsamv/net` looks to be repeated. I am confused.

### Comment 2

1. **Chris Johns**, Fri, 24 Mar 2023 02:13:23 GMT

The BSP list does not handle aliases, for example the `powerpc/beatnik` has a number of aliased BSPs such as `powerpc/mvme2703`.

### Comment 3

1. **Chris Johns**, Mon, 27 Mar 2023 03:42:36 GMT

The attached file `r` is a list of headers that matched headers found in an installed `powerpc/mvme2307` build of RTEMS 5.3 with networking enabled.

The list is what needs to be installed. The existing build scans for files and installs them.

### Comment 4

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:15:45 GMT

Can this be closed now?

**Comment 5**

1. **Joel Sherrill**, Thu, 22 Jun 2023 22:35:02 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Chris says this is fixed.

---

**4889 - Remove file scanning from rtems-lwip**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4889">https://devel.rtems.org/ticket/4889</a> ( <a href="https://devel.rtems.org/ticket/4889">https://devel.rtems.org/ticket/4889</a> )
<b>Id</b>	4889
<b>Reporter</b>	Kinsey Moore
<b>Created</b>	24 March 2023 00:07:56
<b>Modified</b>	29 March 2023 16:26:35
<b>Owner</b>	Kinsey Moore <kinsey.moore@...>
<b>Type</b>	defect
<b>Component</b>	network/lwip
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

rtems-lwip currently scans a subset of directories for files. Since it already supports includes in its definition format, it should instead explicitly list all files to be compiled and support for directory scanning should be removed.

**Comment 1**

1. **Kinsey Moore**, Wed, 29 Mar 2023 16:26:35 GMT
2. **owner**: set to **Kinsey Moore <kinsey.moore@...>**
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 80197c5/rtems-lwip:

```
lwip.py: Remove directory scanning
This removes directory scanning from rtems-lwip for a more robust build system.
Closes #4889
```

---

**4892 - MacOS tools build failures on Ventura and M series processors**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4892">https://devel.rtems.org/ticket/4892</a> ( <a href="https://devel.rtems.org/ticket/4892">https://devel.rtems.org/ticket/4892</a> )
<b>Id</b>	4892
<b>Reporter</b>	Chris Johns
<b>Created</b>	26 March 2023 01:09:44
<b>Modified</b>	11 April 2023 22:09:58
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Building the tools with a recent MacOS such as Ventura failed because Apple has removed support for embedded python in programs. This means GDB does not build. The solution is to teach the RSB GDB support to use a build of Python from <https://www.python.org/>.

The RSB failed to build gcc on the M series processors on Ventura using Xcode 14.2. The build gcc crosscompiler (xgcc) crashes with sig faults. GCC does not bootstrap on ARM systems:

```
*** Configuration aarch64-apple-darwin22.3.0 not supported
```

Look at supporting Homebrew built gcc.

#### Attachments:

- 1 **Chris Johns, Mon, 27 Mar 2023 04:07:36 GMT**  
attach: set to [0001-darwin-Add-support-to-build-with-homebrew-is-present.patch](https://devel.rtems.org/ticket/4892/0001-darwin-Add-support-to-build-with-homebrew-is-present.patch) (https://devel.rtems.org/ticket/4892/0001-darwin-Add-support-to-build-with-homebrew-is-present.patch)
- 2 **Chris Johns, Mon, 27 Mar 2023 04:07:53 GMT**  
attach: set to [0002-dtc-Disable-warnings.patch](https://devel.rtems.org/ticket/4892/0002-dtc-Disable-warnings.patch) (https://devel.rtems.org/ticket/4892/0002-dtc-Disable-warnings.patch)
- 3 **Chris Johns, Mon, 27 Mar 2023 04:08:07 GMT**  
attach: set to [0003-gdb-Use-a-virtual-environment-if-present.patch](https://devel.rtems.org/ticket/4892/0003-gdb-Use-a-virtual-environment-if-present.patch) (https://devel.rtems.org/ticket/4892/0003-gdb-Use-a-virtual-environment-if-present.patch)
- 4 **Chris Johns, Mon, 27 Mar 2023 04:08:24 GMT**  
attach: set to [0004-gcc-12-Fix-libgcc-on-MacOS.patch](https://devel.rtems.org/ticket/4892/0004-gcc-12-Fix-libgcc-on-MacOS.patch) (https://devel.rtems.org/ticket/4892/0004-gcc-12-Fix-libgcc-on-MacOS.patch)
- 5 **Chris Johns, Tue, 04 Apr 2023 23:12:27 GMT**  
attach: set to [gcc-no-sig.diff](https://devel.rtems.org/ticket/4892/gcc-no-sig.diff) (https://devel.rtems.org/ticket/4892/gcc-no-sig.diff)

#### Comment 1

1. **Chris Johns, Sun, 26 Mar 2023 01:15:45 GMT**

Fix building libgcc on MacOS:

```
https://gcc.gnu.org/bugzilla/show_bug.cgi?id=109282
```

#### Comment 2

1. **Chris Johns, Mon, 27 Mar 2023 04:20:26 GMT**

I have attached the 4 patches I have for building on a recent MacOS.

You need:

Recent Xcode installed with the command line tools package. To install the package start Xcode and then click on the Xcode menu item followed by "Open Developer Tools", "More Developer Tools...". Find the command line tools package for the version of Xcode you are running and install. Install a recent Python 3 from <https://www.python.org/downloads/macos/> and install. From a terminal shell run:

```
% /Applications/Python\ 3.11/Update\ Shell\ Profile.command
```

To install the paths in your environment

Create a virtual environment and activate it:

```
% python3 -m venv rpy
% ../rpy/bin/activate
```

Optionally install Homebrew and set up the environment. Make sure one of gcc-12 through to gcc-9 packages is installed. Run a normal RSB build

\_\_Note:\_\_ Currently M2 Pro builds are failing with a segment fault. I have only one machine to test this on.

#### Comment 3

1. **kgardas, Tue, 28 Mar 2023 10:26:27 GMT**

Some things's fishy here. If we're talking about tools build by RSB as presented in HEAD, then I'm able to build those on Ventura. The point is to:

use hand build python3 use either more RAM or limit jobs

The common issue of segfaulting GCC seems to be caused by Ventura reworked memory management which seems to be very sensitive to available amount of RAM.

Using Ventura 13.2 here.

#### Comment 4

1. **kgardas, Tue, 28 Mar 2023 10:52:36 GMT**

OK, so sorry for noise here. What I wrote was applicable in the past. Now, while looking into the internal documentation for MacOS-based customer (which may become part of rtems doc, just don't know where to put it nor had a time to submit/merge) I see these asciidoc paragraphs:



```

==== Install RTEMS build requirements
Please note that this paragraph is written for macOS 13.2.1 (Ventura) and is
not directly applicable to Linux distributions and/or various BSDs.
We are using homebrew to install basic packages required to compile
RTEMS tools and packages. Let's start with the Homebrew installation first.
Open the shell window and run following command inside it.
----
% /bin/bash -c "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"
----
The command will ask for root access and will then also download not
only brew package manager, but also Apple's Xcode command line tools.
When this is done, you may choose to configure brew to be available on
your PATH by following 'Next steps' printed to the terminal by the
installation process.
When this is done, you may continue with using brew package manager to
install required packages for us. Please use following command in
order to do it.
----
% brew install xz python3 texinfo
----
In order to use python3 installed above with just a 'python' command
which is required by the RTEMS source builder (due to required support
for python2 on tools side) you will also need to create a symbolic
link python3 -> python like below:
----
% cd /opt/homebrew/bin
% ln -s python3 python
----

```

**Comment 5**

1. **kgardas**, Tue, 28 Mar 2023 12:59:14 GMT

I can confirm that I've built tools using RSB with last patch being:

```

commit f0e34eab8bf33b833a7d9d0b2bddd3b89f6d83cb (origin/master, origin/HEAD)
Author: Chris Johns
Date: Tue Mar 21 22:05:41 2023 +1100
    binutils: Disable stack exec and RWX section warnings
    Binutils 2.39 and later enable by default warnings for executables
    with executable stack and RWX sections. Disable them.
    Closes #4881

```

hour ago on my Ventura Mac Mini M1 software versions:

```

karel@mini rtems % sw_vers
ProductName:      macOS
ProductVersion:  13.2.1
BuildVersion:    22D68

```

just \*FINE\* and without any of your proposed patches!

So please do not destabilize stuff. macOS is enough PITA :-)

**Comment 6**

1. **Chris Johns**, Tue, 28 Mar 2023 21:10:46 GMT

Replying to kgardas:

OK, so sorry for noise here.

No problem.

What I wrote was applicable in the past. Now, while looking into the internal documentation for MacOS-based customer (which may become part of rtems doc, just don't know where to put it nor had a time to submit/merge) I see these asciidoc paragraphs:

I will update the User Manual once we have the patches attached to this ticket.

```

==== Install RTEMS build requirements
Please note that this paragraph is written for macOS 13.2.1 (Ventura) and is
not directly applicable to Linux distributions and/or various BSDs.
We are using homebrew to install basic packages required to compile
RTEMS tools and packages. Let's start with the Homebrew installation first.
Open the shell window and run following command inside it.
----
% /bin/bash -c "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"
----

```

Homebrew is optional in my view and not mandatory.

```

----
The command will ask for root access and will then also download not
only brew package manager, but also Apple's Xcode command line tools.
When this is done, you may choose to configure brew to be available on
your PATH by following 'Next steps' printed to the terminal by the
installation process.
When this is done, you may continue with using brew package manager to
install required packages for us. Please use following command in
order to do it.
----
% brew install xz python3 texinfo
----

```

Python from Homebrew is an option for python but that will be a per user choice. The end goal is building with Xcode and python.org. The texinfo package may be added like gsd has been. I am not sure we even need makeinfo any more.

```

----
In order to use python3 installed above with just a 'python' command
which is required by the RTEMS source builder (due to required support
for python2 on tools side) you will also need to create a symbolic
link python3 -> python like below:
----
% cd /opt/homebrew/bin
% ln -s python3 python
----

```

Adding a link is personal choice. I prefer we document using virtual environments.

### Comment 7

1. **Chris Johns**, Tue, 28 Mar 2023 21:13:47 GMT

Replying to kgardas:

I can confirm that I've built tools using RSB with last patch being:

```
commit f0e34eab8bf33b833a7d9d0b2bddd3b89f6d83cb (origin/master, origin/HEAD)
Author: Chris Johns
Date: Tue Mar 21 22:05:41 2023 +1100
    binutils: Disable stack exec and RWX section warnings
    Binutils 2.39 and later enable by default warnings for executables
    with executable stack and RWX sections. Disable them.
    Closes #4881
```

hour ago on my Ventura Mac Mini M1 software versions:

```
karel@mini rtems % sw_vers
ProductName:      macOS
ProductVersion:   13.2.1
BuildVersion:     22D68
```

just \*FINE\* and without any of your proposed patches!

So please do not destabilize stuff. macOS is enough PITA :-)

The patches are needed so I encourage you try them and comment before they are pushed. The RSB is active and it changes.

### Comment 8

1. **kgardas**, Tue, 28 Mar 2023 21:28:04 GMT

Hold on! You added patches. I described two ways how is it possible to build tool and yet you claim patches are needed when half of the patches try to deal with crashing of gcc on your Ventura.

Also you claim homebrew is optional yet you like to use it's gcc/g++ to build tools.

A bit contradicting.

Anyway, please make sure you are on the \*LATEST\* Ventura and not on the .0 release. If you update, you will see your gcc crashes may be gone for good. I reported that on devel@ few times already.

Yes, makeinfo is still required by RSB otherwise I would not install it.

Yes, if RSB build its own xz and python and whatever, it would be good.

### Comment 9

1. **Chris Johns**, Wed, 29 Mar 2023 05:57:47 GMT

Replying to kgardas:

Hold on! You added patches.

Indeed I did, please read the ticket. I clearly said this at the start of comment:2.

I described two ways how is it possible to build tool and yet you claim patches are needed when half of the patches try to deal with crashing of gcc on your Ventura.

The patches are not attempting to address the crashing. I have no idea what causes those. The patches address other issues. They are:

Using Python virtual env and cleaning up python support for MacOS. This lets a user install python from python.org. DTC did not build because of warnings treated as errors. No idea how you missed this is you are at the same level of updates as me. Libgcc uses sh and not \$(SHELL) in it's Makefile.in. I have not looked into why I got it but something is different in the set up or environment to trigger it. Add homebrew as a I wanted to try building xgcc with gcc rather than Xcode. It did not help so I am currently considering dropping that patch.

Also you claim homebrew is optional yet you like to use it's gcc/g++ to build tools.

I have not yet added Homebrew support. It is sitting in a patch. I would prefer not to have it part of the build. I have explained this on the devel list in the past.

A bit contradicting.

I did not and have not and I cannot understand why you need to talk to me like this. Can you please not?

Anyway, please make sure you are on the \*LATEST\* Ventura and not on the .0 release.

I am on the latest.

If you update, you will see your gcc crashes may be gone for good. I reported that on devel@ few times already.

They have not gone for me. I am on an M2 Pro and I think you are on an M1.

Yes, makeinfo is still required by RSB otherwise I would not install it.

The RSB checks but is it needed in any packages these days? It was added long ago when all projects built the docs by default using it. We do not build doc. If needed support should be added like gsd.

Yes, if RSB build its own xz and python and whatever, it would be good.

The RSB is written in python so building python would be difficult without it already being installed. Ah yes xz is another. I built that by hand and had forgotten.

## Comment 10

### 1. Chris Johns, Sun, 02 Apr 2023 23:29:15 GMT

Building on M2 Pro with Ventura 13.3 and Xcode Version 14.3 (14E222b) results in segmentation faults in cc1 and cc1plus. Inspecting the MacOS crash reports showed invalid accesses to the stack guard area of memory. A typical crash report is:

```
Exception Type:      EXC_BAD_ACCESS (SIGSEGV)
Exception Codes:    KERN_PROTECTION_FAILURE at 0x00000001699dbff0
Exception Codes:    0x0000000000000002, 0x00000001699dbff0
Termination Reason: Namespace SIGNAL, Code 11 Segmentation fault: 11
Terminating Process: exc handler [30551]
VM Region Info: 0x1699dbff0 is in 0x1699d8000-0x1699dc000; bytes after start: 16368 bytes before end: 15
REGION TYPE          START - END          [ VSIZE] PRT/MAX SHRMOD  REGION DETAIL
  MALLOC_MEDIUM (reserved)  147800000-148000000   [ 8192K] rw-/rwx SM=NUL  ... (unallocated)
  GAP OF 0x219d8000 BYTES
---> STACK GUARD        1699d8000-1699dc000   [ 16K] ---/rwx SM=NUL  ... for thread 0
  Stack                1699dc000-16d9d8000   [ 64.0M] rw-/rwx SM=PRV  thread 0
Thread 0 Crashed:: Dispatch queue: com.apple.main-thread
0  ccl                    0x10335d630  _gmpn_lshift + 208
1  ccl                    0x1033438c8  mpfr_mpn_exp + 684 (mpn_exp.c:151)
2  ???                    0x2db39f030  ???
Thread 0 crashed with ARM Thread State (64-bit):
  x0: 0x0000000000000000   x1: 0x00000001699dc010   x2: 0x0000000000000000   x3: 0x0000000000000001
  x4: 0x0000000000000000   x5: 0x0000000000000000   x6: 0x0000000000000000   x7: 0x0000000000000000
  x8: 0xfffffffffffffff   x9: 0x0000000000000007   x10: 0x0000000000000000  x11: 0x0000000000000000
  x12: 0x0000000000000000  x13: 0x0000000000000000  x14: 0x0000000000000001  x15: 0x00000000fffffff0
  x16: 0x00000001699dc170  x17: 0x0000000082eff7fb  x18: 0xfffffffffffffe00  x19: 0xfffffffffffff04
  x20: 0x0000000000000003  x21: 0x0000000000000003  x22: 0x000000016d9cf818  x23: 0x0000000000000005
  x24: 0xfffffffffffff08  x25: 0x0000000000000004  x26: 0x0000000000000012  x27: 0x000000016d9cf6c8
  x28: 0x000000016d9cf6e0  fp: 0x000000016d9cf7c0  lr: 0x00000001033438c8
  sp: 0x000000016d9cf6b0  pc: 0x000000010335d630  cpsr: 0x20001000
  far: 0x00000001699dbff0  esr: 0x92000007 (Data Abort) byte read Translation fault
Binary Images:
  0x102428000 - 0x10359bfff ccl (*) <72d6a4cf-055f-369c-89cb-4cbf48bff6cf> /Users/USER/*/ccl
  0x0 - 0xfffffffffffffff ??? (*) <00000000-0000-0000-0000-000000000000> ???
```

The FAR is in the stack guard area. The crashes are always in the MPFR library and relate to calls to GMP. The GMP tests pass. The MPFR built by gcc tests fail and a hand built MPFR tests pass.

The crash leaves the build so changing to the MPFR build directory lets you run the tests:

```
cd build/arm-rtems6-gcc-cf59d86-newlib-17ac400-arm64-apple-darwin22.4.0-1/build/mpfr
make check
```

The results are:

```
=====
Testsuite summary for MPFR 4.2.0
=====
# TOTAL: 197
# PASS: 97
# SKIP: 3
# XFAIL: 0
# FAIL: 97
# XPASS: 0
# ERROR: 0
```

The failures are all seg faults.

I upgraded to MPFR 4.2.0 as it does not need the fix-mac-arm64-mpfr-config.patch patch. Building by hand and referencing the gcc build GMP has the following results:

```
=====
Testsuite summary for MPFR 4.2.0
=====
# TOTAL: 197
# PASS: 194
# SKIP: 3
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
```

I provided the same configure command line used by gcc when it builds the library internally. There are no sig faults.

I ran the tests for GMP and there were no errors.

Close inspection of the build and the config.log reveals a difference. The gcc build has:

```
-DHAVE_GMPN_INVERT_LIMB=1 -DHAVE_GMPN_RSBLSH1_N=1
```

and they are not present when building by hand. The config.log shows:

```
configure:19315: checking for __gmpn_invert_limb
[.]
configure:19315: result: yes
```

The hand built MPFR has:

```
configure:19315: checking for __gmpn_invert_limb
[.]
configure:19315: result: no
```

This is the only difference I could see.

## Comment 11

### 1. Chris Johns, Tue, 04 Apr 2023 23:16:43 GMT

I have found a suitable work around for MacOS arm64 that stops the crashes. I tracked issue to GMP and the assembler accelerators it has for aarch64. That code seems to access memory outside the area allocated and MacOS 13.2/13.3 detects this on arm64. The crash depends on where the alloc call allocates memory in relation to the stack guard.

I used the simple patch attached to toplev.cc to stop GCC catching the seg fault signal. This lets MacOS capture the fault and generate a useful crash report.

After a crash I changed directory to the GCC build of MPFR and ran make check. The results failed as shown in comment:10.

Testing of builds of MPFR showed the issue in GMP and inspecting GMP configure --help showed --disable-assemble. Using this option results in the MPFR tests passing. I updated the GMP build to add this option on MacOS arm64.

This exposed a second issue. GCC was building GMP internally as the source was linked into the top level of GCC's sources. GMP is now built as a package because GDB also requires GMP. There is no point building it twice. Removing the GMP sources from the GCC build let GCC pick up the GMP package built and staged earlier in the build set with the work around configure option.

No bug report has been raised with the GMP or MPFR projects. If someone feels like doing that please do.

### Comment 12

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:27 GMT

In 344981a/rtems-source-builder:

```
dtc: Disable warnings
Updates #4892
```

### Comment 13

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:29 GMT

In 9919f12/rtems-source-builder:

```
gdb: Use a virtual environment if present
Detect and use a virtual environment if present Supports MacOS with python.org in a venv
Updates #4892
```

### Comment 14

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:30 GMT

In f3c5dbd/rtems-source-builder:

```
rtems/gcc: Do not build GMP in GCC, use the staged build
Do not build GMP when building GCC. GMP is now built
as a package for GDB. Building as a separate package
lets use control how it is built.
Updates #4892
```

### Comment 15

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:32 GMT

In 4358a03/rtems-source-builder:

```
devel/gmp: Disable assemble builds on MacOS AARCH64
Updates #4892
```

### Comment 16

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:33 GMT

In 235c12f/rtems-source-builder:

```
devel/mpfr: Update to 4.2.0 to support MacOS AARCH64
Use base64 checksums Change MPFR URL
Updates #4892
```

### Comment 17

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:35 GMT

In 05f6bef/rtems-source-builder:

```
devel/mpfr: Add MPFR as a package
This is a place holder incase we stop building MPFR in
GCC.
Updates #4892
```

**Comment 18**

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:37 GMT

In cf447af/rtems-source-builder:

```
rtems/mipsstx39: Update to GDB 13.1 and stage build GMP
Use a build set file to stage GMP as recent GDB
versions require GMP.
Update #4892
```

**Comment 19**

1. **Chris Johns**, Wed, 05 Apr 2023 22:33:38 GMT

In 024db7d/rtems-source-builder:

```
rtems/microblaze: Update to GDB 13.1
```

Note:

GCC does not build on MacOS 13.3 due to the specific version of GCC the Microblaze is using.

Updates #4892

**Comment 20**

1. **Chris Johns**, Tue, 11 Apr 2023 22:09:58 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

Karel has confirmed builds are working cleanly.

**4896 - Makefile.inc exported BSP include path not a system include path**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4896">https://devel.rtems.org/ticket/4896</a> ( <a href="https://devel.rtems.org/ticket/4896">https://devel.rtems.org/ticket/4896</a> )
<b>Id</b>	4896
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 April 2023 21:55:08
<b>Modified</b>	14 April 2023 20:07:10
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The BSP include path exported in the Makefile.inc set of files uses -I and that is not a system include. The RTEMS 5 and earlier autoconf build system provided a spec file using the -B option and that either added a system path or the spec file included a system path. Either way the BSP include path was added as a system include path and so the compiler placed it at the end of the include list.

The CPU\_DEFINES macro is part of CPPFLAGS exported by Makefile.inc and we cannot control how applications uses that variable so we need to make sure the BSP include path is exported as a system include path.

The issue was found with EPICS. EPICS installs a header file called link.h under its include path. RTEMS now provides a header file called link.h. The CPPFLAGS are before the EPICS include path so our link.h was seen before the EPICS one and that broken the build.

**Comment 1**

1. **Kinsey Moore**, Fri, 14 Apr 2023 20:07:10 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In 5a37722b/rtems:

spec/pkgconfig: Allow builds to override headers

This allows any builds targeting an installed RTEMS BSP to override headers in the installed BSP reliably, including headers previously installed by that or other builds. This includes applications, network stacks, libraries, and any other builds.

Closes #4896

## 4899 - BSP powerpc/qoriq\_e6500\_64 and powerpc/qoriq\_e6500\_32 fail to build

Link	<a href="https://devel.rtems.org/ticket/4899">https://devel.rtems.org/ticket/4899</a> ( <a href="https://devel.rtems.org/ticket/4899">https://devel.rtems.org/ticket/4899</a> )
Id	4899
Reporter	Chris Johns
Created	23 April 2023 22:29:25
Modified	22 June 2023 21:45:21
Owner	
Type	defect
Component	bsps
Status	closed
Resolution	fixed
Version	6
Milestone	6.1
Priority	normal
Severity	normal
Keywords	
Cc	
Blocking	
Blocked by	

### Description

```
[ 87/1471] Compiling bsp/powerpc/shared/vme/vmeTsi148.c
/tmp/ccc918.s: Assembler messages:
/tmp/ccc918.s:353: Error: unrecognized opcode: `eieio'
/tmp/ccc918.s:386: Error: unrecognized opcode: `eieio'
/tmp/ccc918.s:419: Error: unrecognized opcode: `eieio'
/tmp/ccc918.s:444: Error: unrecognized opcode: `eieio'
/tmp/ccc918.s:477: Error: unrecognized opcode: `eieio'
/tmp/ccc918.s:503: Error: unrecognized opcode: `eieio'
...
```

### Comment 1

#### 1. Sebastian Huber, Mon, 24 Apr 2023 08:40:54 GMT

I can't reproduce this issue:

```
Waf: Entering directory `/tmp/sh/b-rtems/powerpc/qoriq_core_0'
[ 87/1471] Compiling bsp/powerpc/shared/vme/vmeTsi148.c
Waf: Leaving directory `/tmp/sh/b-rtems/powerpc/qoriq_core_0'
'build powerpc/qoriq_core_0' finished successfully (0.626s)
Waf: Entering directory `/tmp/sh/b-rtems/powerpc/qoriq_core_1'
[ 87/1471] Compiling bsp/powerpc/shared/vme/vmeTsi148.c
Waf: Leaving directory `/tmp/sh/b-rtems/powerpc/qoriq_core_1'
'build powerpc/qoriq_core_1' finished successfully (0.598s)
Waf: Entering directory `/tmp/sh/b-rtems/powerpc/qoriq_e500'
[ 87/1471] Compiling bsp/powerpc/shared/vme/vmeTsi148.c
Waf: Leaving directory `/tmp/sh/b-rtems/powerpc/qoriq_e500'
'build powerpc/qoriq_e500' finished successfully (0.600s)
Waf: Entering directory `/tmp/sh/b-rtems/powerpc/qoriq_e6500_32'
[ 87/1471] Compiling bsp/powerpc/shared/vme/vmeTsi148.c
Waf: Leaving directory `/tmp/sh/b-rtems/powerpc/qoriq_e6500_32'
'build powerpc/qoriq_e6500_32' finished successfully (0.643s)
Waf: Entering directory `/tmp/sh/b-rtems/powerpc/qoriq_e6500_64'
[ 76/2031] Compiling bsp/powerpc/shared/vme/vmeTsi148.c
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148FindPciBase':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:466:16: warning: cast to pointer from integer of different size
[-Wint-to-pointer-cast]
 466 |         *pbase=(BERRegister*)((pci_ulong)BSP_PCI2LOCAL_ADDR(busaddr) & ~0xff);
      |         ^
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148InitInstance':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:493:33: warning: cast from pointer to integer of different size
[-Wpointer-to-int-cast]
 493 |         (unsigned int)base, irq);
      |         ^
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148ResetBusXX':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:553:9: warning: implicit declaration of function
'rtems_interrupt_disable'; did you mean 'rtems_interrupt_raise'? [-Wimplicit-function-declaration]
 553 |         rtems_interrupt_disable(flags);
      |         ^~~~~~
rtems_interrupt_raise
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:553:9: warning: nested extern declaration of
'rtems_interrupt_disable' [-Wnested-externs]
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:556:9: warning: implicit declaration of function
'rtems_interrupt_enable'; did you mean 'rtems_interrupt_raise'? [-Wimplicit-function-declaration]
 556 |         rtems_interrupt_enable(flags);
      |         ^~~~~~
rtems_interrupt_raise
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:556:9: warning: nested extern declaration of
'rtems_interrupt_enable' [-Wnested-externs]
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'tsiVMEISR':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1487:47: warning: cast from pointer to integer of different size
[-Wpointer-to-int-cast]
 1487 |     int pin = (int)arg;
      |             ^
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'connectIsr':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1598:21: warning: cast to pointer from integer of different size
[-Wint-to-pointer-cast]
 1598 |     xx.handle = (rtems_irq_hdl_param)slot;
      |                 ^
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'tsi_desc_setnxt':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:2401:56: warning: cast from pointer to integer of different size
```

```

[-Wpointer-to-int-cast]
2401 |         st_be32( &d->dnlal, BSP_LOCAL2PCI_ADDR((uint32_t)n) );
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:381:45: note: in definition of macro 'BSP_LOCAL2PCI_ADDR'
381 | #define BSP_LOCAL2PCI_ADDR(1)  (((uint32_t)1)+PCI_DRAM_OFFSET)
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148DmaListStartXX':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:381:35: warning: cast from pointer to integer of different size
[-Wpointer-to-int-cast]
381 | #define BSP_LOCAL2PCI_ADDR(1)  (((uint32_t)1)+PCI_DRAM_OFFSET)
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:337:111: note: in definition of macro 'TSI_WR'
337 | #define TSI_WR(base, reg, val)  out_be32((volatile uint32_t *) ((base) + (reg)/sizeof(*base)), val)
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:2495:64: note: in expansion of macro 'BSP_LOCAL2PCI_ADDR'
2495 |         TSI_WR(base, TSI_DNLAL_REG(channel), (uint32_t)BSP_LOCAL2PCI_ADDR(d));
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148ResetBusXX':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:553:9: warning: 'flags' is used uninitialized [-Wuninitialized]
553 |         rtems_interrupt_disable(flags);
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:550:15: note: 'flags' was declared here
550 | unsigned long flags;
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'intDoEnDis':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1862:9: warning: 'flags' may be used uninitialized [-Wmaybe-uninitialized]
1862 |         rtems_interrupt_disable(flags);
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1851:17: note: 'flags' was declared here
1851 | unsigned long  flags, v;
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148IntRoute':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1444:1: warning: 'flags' may be used uninitialized [-Wmaybe-uninitialized]
1444 | rtems_interrupt_disable(flags);
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1412:38: note: 'flags' was declared here
1412 | unsigned long  mask, shift, mapreg, flags, wire;
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148ISRGet':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1473:9: warning: 'flags' may be used uninitialized [-Wmaybe-uninitialized]
1473 |         rtems_interrupt_disable(flags);
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1463:19: note: 'flags' was declared here
1463 | unsigned long  flags;
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148InstallISR':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1810:17: warning: 'flags' may be used uninitialized [-Wmaybe-uninitialized]
1810 |         rtems_interrupt_disable(flags);
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1796:19: note: 'flags' was declared here
1796 | unsigned long  flags;
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c: In function 'vmeTsi148RemoveISR':
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1834:17: warning: 'flags' may be used uninitialized [-Wmaybe-uninitialized]
1834 |         rtems_interrupt_disable(flags);
/home/EB/sebastian_h/src/rtems/bsps/powerpc/shared/vme/vmeTsi148.c:1826:19: note: 'flags' was declared here
1826 | unsigned long  flags;
Waf: Leaving directory `/tmp/sh/b-rtems/powerpc/qoriq_e6500_64'

```

**Comment 2**

1. **Chris Johns**, Mon, 24 Apr 2023 09:13:31 GMT

I just tried and I am still see the error. I am using:

```

[DEFAULT]
BUILD_TESTS = False
RTEMS_DEBUG = True
[powerpc/qoriq_e6500_32]
[powerpc/qoriq_e6500_64]

ruru rtems.git $ /opt/work/rtems/6/bin/powerpc-rtems6-gcc --version
powerpc-rtems6-gcc (GCC) 12.2.1 20220908 (RTEMS 6, RSB c0edd80bcd27b3dad7ee7acf5ea129e81e6a6f64, Newlib 783133b)
Copyright (C) 2022 Free Software Foundation, Inc.
This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

```

**Comment 3**

1. **Sebastian Huber**, Mon, 24 Apr 2023 09:19:40 GMT

Very strange, I don't get this error with:

```

/opt/rtems/6/bin/powerpc-rtems6-gcc --version
powerpc-rtems6-gcc (GCC) 12.2.1 20230421 (RTEMS 6, RSB 21bf2f3d73e49006cb6fd45f064d6b045bc4ed07, Newlib da40bd6)
Copyright (C) 2022 Free Software Foundation, Inc.
This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

```

**Comment 4**

1. **Joel Sherrill**, Thu, 22 Jun 2023 21:03:58 GMT

Chris.. I thought this was resolved. Can we close?

**Comment 5**

1. **Chris Johns**, Thu, 22 Jun 2023 21:45:21 GMT

2. **status:** changed from **new** to **closed**
3. **resolution:** set to **fixed**

Building now

## 4900 - PowerPC score warnings in score headers

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4900">https://devel.rtems.org/ticket/4900</a> ( <a href="https://devel.rtems.org/ticket/4900">https://devel.rtems.org/ticket/4900</a> )
<b>Id</b>	4900
<b>Reporter</b>	Chris Johns
<b>Created</b>	23 April 2023 22:48:53
<b>Modified</b>	31 October 2023 11:52:51
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	highest
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Building a few of the PowerPC BSPs with `RTEMS_DEBUG = True` generates these warnings:

```
[ 319/1483] Compiling cpukit/score/cpu/powerpc/cpu.c
In file included from ../../../../cpukit/score/cpu/powerpc/include/rtems/score/cpu.h:59,
                 from ../../../../cpukit/score/cpu/powerpc/include/rtems/score/cpuimpl.h:42,
                 from ../../../../cpukit/score/cpu/powerpc/cpu.c:43:
../../../../cpukit/score/cpu/powerpc/cpu.c: In function '_CPU_Fatal_halt':
../../../../cpukit/include/rtems/score/basedefs.h:436:33: warning: implicit declaration of function '_Assert' [-Wimplicit-function-declaration]
 436 | #define _Assert_Unreachable() _Assert( 0 )
      |                               ^~~~~~
../../../../cpukit/include/rtems/score/basedefs.h:865:7: note: in expansion of macro '_Assert_Unreachable'
 865 |     _Assert_Unreachable(); \
      |     ^~~~~~
../../../../cpukit/score/cpu/powerpc/cpu.c:361:3: note: in expansion of macro 'RTEMS_UNREACHABLE'
 361 |     RTEMS_UNREACHABLE();
      |     ^~~~~~
../../../../cpukit/include/rtems/score/basedefs.h:436:33: warning: nested extern declaration of '_Assert' [-Wnested-externs]
 436 | #define _Assert_Unreachable() _Assert( 0 )
      |                               ^~~~~~
../../../../cpukit/include/rtems/score/basedefs.h:865:7: note: in expansion of macro '_Assert_Unreachable'
 865 |     _Assert_Unreachable(); \
      |     ^~~~~~
../../../../cpukit/score/cpu/powerpc/cpu.c:361:3: note: in expansion of macro 'RTEMS_UNREACHABLE'
 361 |     RTEMS_UNREACHABLE();
      |     ^~~~~~
```

The score headers `basedefs.h` header depends on `assert.h` and `assert.h` includes `basedefs.h` at its top.

I think this ticket should be set to blocker for the 6.1 release. We should resolve this and the warnings before we make a release.

### Comment 1

1. **Sebastian Huber**, Mon, 24 Apr 2023 08:15:52 GMT

Yes, there is a cyclic dependency. For `RTEMS_STATIC_ANALYSIS` we need `basedefs.h`. For `RTEMS_UNREACHABLE()` we need `_Assert()`.

I am not sure if the `RTEMS_STATIC_ANALYSIS` was really a good idea. It is currently just used in `assert.h`. Maybe we should remove it.

### Comment 2

1. **Chris Johns**, Mon, 24 Apr 2023 08:27:17 GMT

You are the best judge of this. Breaking the dependency would be good to see done.

### Comment 3

1. **Sebastian Huber**, Tue, 25 Apr 2023 06:02:19 GMT

In 9eb5dd3/rtems-central:

```
spec: Avoid cyclic header file dependencies

There was a cyclic dependency: For RTEMS_STATIC_ANALYSIS we needed basedefs.h in assert.h. For RTEMS_UNREACHABLE() we needed _Assert()
from assert.h in basedefs.h.

Fix this by introducing _Debug_Unreachable() in basedefs.h.

Add RTEMS_FUNCTION_NAME to basedefs.h and use it in basedefs.h and assert.h.

Update #4900.
```



**Comment 4**

1. **Sebastian Huber**, Tue, 25 Apr 2023 06:06:50 GMT
2. **owner:** set to **Sebastian Huber** <sebastian.huber@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In 863b26ee/rtems:

score: Avoid cyclic header file dependencies

There was a cyclic dependency: For RTEMS\_STATIC\_ANALYSIS we needed basedefs.h in assert.h. For RTEMS\_UNREACHABLE() we needed \_Assert() from assert.h in basedefs.h.

Fix this by introducing \_Debug\_Unreachable() in basedefs.h.

Add RTEMS\_FUNCTION\_NAME to basedefs.h and use it in basedefs.h and assert.h.

Close #4900.

**Comment 5**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:52:51 GMT
2. **keywords:** **qualification** added

**4901 - rtems\_task\_construct Documentation Missing Some Details**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4901">https://devel.rtems.org/ticket/4901</a> ( <a href="https://devel.rtems.org/ticket/4901">https://devel.rtems.org/ticket/4901</a> )
<b>Id</b>	4901
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	26 April 2023 14:31:48
<b>Modified</b>	19 May 2023 05:21:42
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The rtems\_task\_construct directive description has a couple of deficiencies:

- does not mention or link to RTEMS\_TASK\_STORAGE\_SIZE
- does not provide rtems\_task\_config and discuss the fields

It would be nice to discuss how each of the parameters to rtems\_task\_create is set/computed when using rtems\_task\_config.

I did not look but rtems\_message\_queue\_construct may have similar issues.

**Comment 1**

1. **Joel Sherrill**, Wed, 26 Apr 2023 14:32:05 GMT
2. **owner:** set to **Sebastian Huber**
3. **status:** changed from **new** to **assigned**

**Comment 2**

1. **Sebastian Huber**, Thu, 27 Apr 2023 05:57:24 GMT

Yes, this is definitely missing. One issue is that we have no documentation of the data structures in the Classic API Guide. They are only present in the Doxygen documentation. My plan is to improve the documentation generator in rtems-central to produce documentation for the data structures.

**Comment 3**

1. **Joel Sherrill**, Thu, 27 Apr 2023 11:43:15 GMT

It isn't just the data structure. That could be largely accounted for with a quick mention that rtems\_task\_config maps to the arguments to rtems\_task\_create. The problem is specifically stack\_size in create becomes storage\_size in construct and you have to use a macro on your desired stack\_size to fill in the structure. The dtor field is also missing info. You could get by with a bullet list on the structure parameters showing how they map or are used.

There is also nothing in rtems-examples which uses this.

#### Comment 4

1. **Sebastian Huber**, Thu, 27 Apr 2023 13:38:13 GMT

Most of the stuff is already covered in the Doxygen output:

<https://github.com/RTEMS/rtems/blob/master/cpukit/include/rtems/rtems/tasks.h#L107>

#### Comment 5

1. **Sebastian Huber**, Fri, 19 May 2023 05:21:42 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In e33eae1/rtems-docs:

```
c-user: Generate API type documentation
Close #4901.
```

---

## 4902 - Update zlib to version 1.2.13

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4902">https://devel.rtems.org/ticket/4902</a> ( <a href="https://devel.rtems.org/ticket/4902">https://devel.rtems.org/ticket/4902</a> )
<b>Id</b>	4902
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	5 May 2023 07:47:24
<b>Modified</b>	9 May 2023 12:56:31
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The last zlib update was more than ten years ago. Update it to the latest version. This includes security fixes.

#### Comment 1

1. **Sebastian Huber**, Fri, 05 May 2023 07:47:49 GMT
2. **summary**: changed from **Update zlib to latest version** to **Update zlib to version 1.2.13**

#### Comment 2

1. **Sebastian Huber**, Tue, 09 May 2023 12:56:31 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 1f00afc/rtems:

```
zlib: Update from 1.2.5 to 1.2.13
The updated files were extracted from:
https://www.zlib.net/zlib-1.2.13.tar.xz
The archive had an SHA-256 hash value of:
d14c38e313afc35a9a8760dadf26042f51ea0f5d154b0630a31da0540107fb98
Close #4902.
```

---

## 4905 - SuperCore \_TOD\_Adjust No Longer Referenced and Should be Removed

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4905">https://devel.rtems.org/ticket/4905</a> ( <a href="https://devel.rtems.org/ticket/4905">https://devel.rtems.org/ticket/4905</a> )
<b>Id</b>	4905
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	15 May 2023 13:39:34
<b>Modified</b>	16 May 2023 13:21:09
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Apparently with the rework of time handling, this method has become unused and should be removed.

**Comment 1**

1. **Joel Sherrill**, Mon, 15 May 2023 13:39:44 GMT
2. **owner:** set to **Joel Sherrill**
3. **status:** changed from **new** to **assigned**

**Comment 2**

1. **Joel Sherrill**, Tue, 16 May 2023 13:21:09 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 3f4454b/rtems:

```
_TOD_Adjust method is unused. Remove it.
```

```
Use of this method was likely eliminated during the rework to use FreeBSD bintime/sbintime.
```

```
Close #4905.
```

**4906 - libbsd not working on nucleo-h743ZI**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4906">https://devel.rtems.org/ticket/4906</a> ( <a href="https://devel.rtems.org/ticket/4906">https://devel.rtems.org/ticket/4906</a> )
<b>Id</b>	4906
<b>Reporter</b>	Ning Yang
<b>Created</b>	15 May 2023 17:42:30
<b>Modified</b>	22 June 2023 20:47:49
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	invalid
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	stm32h7
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

libbsd not working on nucleo-h743ZI.

I run the libbsd testsuit selectpollkqueue01.get a fatal.

The same fatal happened in my project.

```
* FATAL *
fatal source: 0 (INTERNAL_ERROR_CORE)
fatal code: 2 (INTERNAL_ERROR_TOO_LITTLE_WORKSPACE)
RTEMS version: 6.0.0.020163e5b7bb0b4363b57f37729b99becae9c629 RTEMS tools: 12.2.1 20230224 (RTEMS 6, RSB
f0e34eab8bf33b833a7d9d0b2bddd3b89f6d83cb, Newlib 17ac400)
executing
```

i used a sh to build libbsd

```
cd /home/yangn0/devel/rtems-arm/rtems-libbsd
./waf distclean
./waf configure --prefix=$HOME/devel/rtems-arm/tools/rtems/6 \
  --rtems-bsps=arm/nucleo-h743zi \
  --buildset=buildset/default.ini
./waf
./waf install
```

**Comment 1**

1. **Ning Yang**, Tue, 16 May 2023 06:44:17 GMT
2. **keywords:** `stm32h7` added
3. **component:** changed from `arch/arm` to `network/libbsd`

**Comment 2**

1. **Joel Sherrill**, Thu, 22 Jun 2023 20:47:17 GMT

The nucleo-h743ZI only has 1MB RAM. Although we don't have a hard line for the minimum RAM required for libbsd, this is well below the normal for use. We would recommend using lwip instead in such a low RAM environment. Please feel free to ask on [devel@](#) or Discord for help with that.

**Comment 3**

1. **Joel Sherrill**, Thu, 22 Jun 2023 20:47:49 GMT
2. **status:** changed from `new` to `closed`
3. **resolution:** set to `invalid`

There is nothing to fix in this situation. Closing.

**4909 - Multiple Protected Heap Functions are Unused**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4909">https://devel.rtems.org/ticket/4909</a> ( <a href="https://devel.rtems.org/ticket/4909">https://devel.rtems.org/ticket/4909</a> )
<b>Id</b>	4909
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	21 May 2023 11:54:39
<b>Modified</b>	31 October 2023 11:53:04
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The following functions are unused and should be removed:

- `_Protected_heap_Get_block_size`
- `_Protected_heap_Iterate`
- `_Protected_heap_Resize_block`

**Comment 1**

1. **Joel Sherrill**, Sun, 21 May 2023 11:54:45 GMT
2. **owner:** set to **Joel Sherrill**
3. **status:** changed from `new` to `assigned`

**Comment 2**

1. **Joel Sherrill**, Fri, 26 May 2023 14:52:35 GMT
2. **status:** changed from `assigned` to `closed`
3. **resolution:** set to `fixed`

In 63415655/rtems:

```
score/src/pheap*: Remove unreferenced methods
_Protected_heap_Get_block_size _Protected_heap_Iterate _Protected_heap_Resize_block
Closes #4909.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:53:04 GMT
2. **keywords:** qualification added

**4910 - RSB options for python selection**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4910">https://devel.rtems.org/ticket/4910</a> ( <a href="https://devel.rtems.org/ticket/4910">https://devel.rtems.org/ticket/4910</a> )
<b>Id</b>	4910
<b>Reporter</b>	Chris Johns
<b>Created</b>	23 May 2023 02:49:31
<b>Modified</b>	30 June 2023 00:14:15
<b>Owner</b>	Chris Johns
<b>Type</b>	enhancement
<b>Component</b>	tool/rsb
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

A recent change to the version of GDB means we need python3 development libraries installed as GDB will only build with Python3. To aid compatibility for older operating systems provide options to aid the selection of a suitable python. Add support for:

```
--with-python2 : command for Python2
```

```
--with-python3 : command for Python3
```

```
--with-python-version : command for a version of Python
```

For example:

```
--with-python-version=python3.6
```

**Comment 1**

1. **Chris Johns**, Fri, 30 Jun 2023 00:14:15 GMT

Joel, what do you think?

**4912 - Collect Compression Library Source in Single Place**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4912">https://devel.rtems.org/ticket/4912</a> ( <a href="https://devel.rtems.org/ticket/4912">https://devel.rtems.org/ticket/4912</a> )
<b>Id</b>	4912
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	26 May 2023 14:55:25
<b>Modified</b>	6 June 2023 13:49:01
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	zlib, xz, compression
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Currently zlib is in cpukit/ while xz is in cpukit/libmisc. The purpose of this ticket is to create cpukit/compression and move both to it. This ticket does not add, remove, or upgrade the existing source. It is intended to just document improving the organization.

**Comment 1**

1. **Joel Sherrill**, Fri, 26 May 2023 14:55:32 GMT
2. **owner**: set to **Joel Sherrill**
3. **status**: changed from **new** to **assigned**

**Comment 2**

1. **Joel Sherrill**, Tue, 06 Jun 2023 13:49:01 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In bb5dbff7/rtems:

```
Move various compression libraries into single subdirectory
This improves the organization of the cpukit.
Closes #4912.
```

**4913 - libbsd/ipsec-tools: Problems with more than 64 open files**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4913">https://devel.rtems.org/ticket/4913</a> ( <a href="https://devel.rtems.org/ticket/4913">https://devel.rtems.org/ticket/4913</a> )
<b>Id</b>	4913
<b>Reporter</b>	Christian Mauderer
<b>Created</b>	31 May 2023 05:56:47
<b>Modified</b>	31 May 2023 06:04:26
<b>Owner</b>	Christian Mauderer
<b>Type</b>	defect
<b>Component</b>	network/libbsd
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

IPSec with racoon doesn't work if there are more than 64 open file descriptors in the system.

**Comment 1**

1. **Christian Mauderer**, Wed, 31 May 2023 06:01:36 GMT

In dfb2144/rtems-libbsd:

```
ipsec-tools: Fix copying fd_set prior to select
The racoon session code copies an fd_set from one variable into another prior to calling select. That works well for simple structures.
In libbsd we have to allocate fd_sets instead of using fixed structures to avoid a problem with file numbers bigger than FD_SETSIZE. The
simple assignment didn't work in that case.
This patch makes sure that a memcpy is used instead.
Update #4913
```

**Comment 2**

1. **Christian Mauderer**, Wed, 31 May 2023 06:03:37 GMT

In 8ed211f/rtems-libbsd:

```
ipsec-tools: Fix copying fd_set prior to select
The racoon session code copies an fd_set from one variable into another prior to calling select. That works well for simple structures.
In libbsd we have to allocate fd_sets instead of using fixed structures to avoid a problem with file numbers bigger than FD_SETSIZE. The
simple assignment didn't work in that case.
This patch makes sure that a memcpy is used instead.
Update #4913
```

**Comment 3**

1. **Christian Mauderer**, Wed, 31 May 2023 06:04:26 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

## 4915 - Building sphinx 7.0.1 fails

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4915">https://devel.rtems.org/ticket/4915</a> ( <a href="https://devel.rtems.org/ticket/4915">https://devel.rtems.org/ticket/4915</a> )
<b>Id</b>	4915
<b>Reporter</b>	Andrew Butterfield
<b>Created</b>	7 June 2023 10:27:01
<b>Modified</b>	21 November 2023 13:35:58
<b>Owner</b>	Utkarsh Verma <utkarsh@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	sphinx, qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

I am trying to install sphinx on an Apple Silicon OSX machine. I've already done this successfully in the past on a similar machine.

This time, after following steps in the rtems-docs README.txt, I do `./waf`, it does some stuff and then:

```
[ 7/10] Compiling common/_static/favicon.ico
[ 8/10] Compiling common/_static/my-styles.css
[ 9/10] Compiling common/_static/logo.png
[10/10] Compiling common/_static/style.css
Theme error:
An error happened in rendering the page bld/index.
Reason: UndefinedError("'style' is undefined")
```

I'm using pip 22.2.1, Python 3.10.6 and pip3 installs sphinx 7.0.1

```
(sphinx) ab-rtems-docs% pip3 install sphinx
Requirement already satisfied: sphinx in ./sphinx/lib/python3.10/site-packages (7.0.1)
```

### Comment 1

1. **Utkarsh Verma**, Wed, 14 Jun 2023 05:25:08 GMT
2. **owner**: set to **Utkarsh Verma <utkarsh@...>**
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In 4c87f9b/rtems-docs:

```
eng: Fix builds for newer Sphinx versions (>=7)
```

The current Sphinx theme depends on the style parameter which got deprecated in v5.1 and finally got removed in v7. Now, the styles key should be preferred which is a list of stylesheets. This commit implements this change.

Closes #4915

### Comment 2

1. **Joel Sherrill**, Wed, 26 Jul 2023 18:38:09 GMT

In 13237ab/rtems-docs:

```
layout.html: Revert patch forcing Spinx to >= 6.0
```

Unfortunately, updating past Sphinx 5.x results in unordered bullet lists not formatting correctly as show in a screen capture attached to #4928. Revert this patch until the issue is resolved and output is reviewed for other potential issues.

```
From: Utkarsh Verma Date: Wed, 14 Jun 2023 05:36:26 +0000 Subject: [PATCH] eng: Fix builds for newer Sphinx versions (>=7)
```

```
The current Sphinx theme depends on the style parameter which got deprecated in v5.1 and finally got removed in v7. Now, the styles key should be preferred which is a list of stylesheets. This commit implements this change.
```

Updates #4915. Updates #4928.

**Comment 3**

1. **Joel Sherrill**, Wed, 26 Jul 2023 18:59:53 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution**: **fixed** deleted

My patch set was a work-around to not use  $\geq 6$ . This needs a permanent fix.

**Comment 4**

1. **Sebastian Huber**, Tue, 01 Aug 2023 07:20:04 GMT
2. **keywords**: **qualification** added

**Comment 5**

1. **Sebastian Huber**, Tue, 01 Aug 2023 07:20:53 GMT
2. **priority**: changed from **high** to **normal**
3. **status**: changed from **reopened** to **closed**
4. **resolution**: set to **wontfix**
5. **milestone**: changed from **Indefinite** to **6.1**

**Comment 6**

1. **Sebastian Huber**, Tue, 21 Nov 2023 13:35:58 GMT

In 027ed52/rtems-central:

```
requirements.txt: Set maximum Sphinx version
Update #4915. Update #4928.
```

**4920 - libdl does not support TLS**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4920">https://devel.rtems.org/ticket/4920</a> ( <a href="https://devel.rtems.org/ticket/4920">https://devel.rtems.org/ticket/4920</a> )
<b>Id</b>	4920
<b>Reporter</b>	Chris Johns
<b>Created</b>	22 June 2023 22:08:14
<b>Modified</b>	19 February 2024 03:48:28
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The symbol generator does not create the correct symbols for libdl to use. And libdl does not handle TLS symbols correctly.

There is not backend support for TLS in the arch code.

**Comment 1**

1. **Chris Johns**, Thu, 29 Jun 2023 23:29:57 GMT

We need to add support to din the TSL base for a thread for each architecture:

aarch64 arm bfin i386 lm32 m68k mips moxie powerpc riscv sparc v850 AARCH64

```
static void* rtems_rtl_tls_get_base (void) {
  intptr_t value;
  __asm__ volatile (
    "\"mrs %0, TPIDR_EL0\" : \"=&r\" ( value ) : : \"memory\"
  );",
  return value;
}
```

**Comment 2**



1. **Chris Johns**, Thu, 29 Jun 2023 23:30:46 GMT

Joel, we voted and you are best to do this as you have all arch tools built.

### **Comment 3**

1. **Chris Johns**, Sat, 12 Aug 2023 06:33:28 GMT

Test dl11 fails on arm with:

```
*** BEGIN OF TEST libdl (RTL) 11 ***
*** TEST VERSION: 6.0.0.10da3025186cadf2d78e34cf81cce02121069d44
*** TEST STATE: EXPECTED PASS
*** TEST BUILD: RTEMS DEBUG RTEMS POSIX_API
*** TEST TOOLS: 12.3.I 20230626 (RTEMS 6, RSB 8e568b2ca3489d6bfa48e1d29618ea9b48a5b408, Newlib 4c7d0df)
load: /dl11-o1.o
handle: 0x20e148 loaded
dlsym ptr call failed: ret value bad
```

and on aarch64 with:

```
*** BEGIN OF TEST libdl (RTL) 11 ***
*** TEST VERSION: 6.0.0.10da3025186cadf2d78e34cf81cce02121069d44
*** TEST STATE: EXPECTED PASS
*** TEST BUILD: RTEMS DEBUG RTEMS POSIX_API
*** TEST TOOLS: 12.3.I 20230626 (RTEMS 6, RSB 8e568b2ca3489d6bfa48e1d29618ea9b48a5b408, Newlib 4c7d0df)
load: /dl11-o1.o
handle: 0x40118610 has unresolved externals
dlsym ptr call failed: ret value bad
```

The ptr\_call asks for a function pointer to:

```
int *get_errno_ptr (void)
{
    return &errno;
}
```

and errno is a TLS variable.

### **Comment 4**

1. **Chris Johns**, Tue, 15 Aug 2023 05:55:47 GMT

I have posted a patch for the general changes need plus dl11 is working for the following architectures:

aarch64 arm powerpc sparc

### **Comment 5**

1. **Chris Johns**, Wed, 16 Aug 2023 00:52:12 GMT

Remaining archs are:

bfin i386 lm32 m68k mips moxie riscv v850

I do not know which of these archs support TLS.

### **Comment 6**

1. **Joel Sherrill**, Wed, 16 Aug 2023 14:36:40 GMT

The following table summarises the state of TLS support for each architecture listed previously. I based this on grep'ing for TLS in the score/cpu port directory and looking at generated assembly.

ArchitectureMechanismSupport in RTEMS bfin \_emutls\_get\_address() No i386 %gs register when not compiled for PIC Yes lm32 \_emutls\_get\_address() No m68k m68k\_read\_tp() Yes mips Illegal Instruction Exception No moxie \_emutls\_get\_address() No riscv %tp register Yes v850 \_emutls\_get\_address() No

Question: Some of the architectures have an implementation of tls\_get\_addr(). Could this be copied and used as \_emutls\_get\_addr()?

Question: Do we want to disable use of TLS in the tools for those we have no TLS support for? I think this is the safest option.

I used this program to see what GCC generates.

```
__thread int i;
int returni(void)
{
    return i;
}
```

Note: For the MIPS, see gcc/config/mips/mips.md for a description of the illegal instruction used.

### **Comment 7**

1. **Gedare Bloom**, Wed, 16 Aug 2023 20:09:24 GMT

v850 is slated for deprecation. quite likely so should any of the architectures that don't have TLS

### **Comment 8**

1. **Chris Johns**, Wed, 16 Aug 2023 23:59:05 GMT

Question: Do we want to disable use of TLS in the tools for those we have no TLS support for? I think this is the safest option.

The change is not adding the ability to load TLS variables. That is out of scope for this change. The regression is only for archs that support TLS and where newlib has been updated to use TLS for recent data. If this newlib has not been updated there is no regression so I do not think we need to disable archs.

\_\_Note\_\_:

If an arch supports TLS and newlib has not been updated and a user attempts to load a TLS variable an error is generated which is the same error as before. The `rtms_rtl_tls_get_base()` call needs to be present if the base image has TLS symbols. If it does not there should be no references.

#### **Comment 9**

1. **Chris Johns**, Wed, 16 Aug 2023 23:59:56 GMT

Question: Some of the architectures have an implementation of `tls_get_addr()`. Could this be copied and used as `emutls_get_addr()`?

If there is a call that can be made then it can be used.

#### **Comment 10**

1. **Chris Johns**, Thu, 17 Aug 2023 00:01:50 GMT

v850 is slated for deprecation. quite likely so should any of the architectures that don't have TLS

The `rtms_rtl_tls_get_base()` call can return NULL for this arch. An active user can update or ask to have the code updated. Is the compiler defined `__v850__`?

#### **Comment 11**

1. **Chris Johns**, Thu, 17 Aug 2023 01:55:52 GMT

Test results

This is the test results for the ones I can simulate using the v2 patch.

AARCH64

Failures:

dl06.exe dl09.exe ARM

Failures:

dl06.exe dl09.exe PowerPC

Failures:

dl06.exe dl09.exe SPARC

Expected Fail:

dl06.exe

#### **Comment 12**

1. **Chris Johns**, Mon, 21 Aug 2023 00:37:34 GMT

In aba4d3b/rtems-tools:

linker: Add TLS support to the symbol table generator

Updates #4920

#### **Comment 13**

1. **Chris Johns**, Mon, 21 Aug 2023 00:53:33 GMT

In 27da374/rtems:

libdl: Add support to import base image TLS symbols

This change requires an rtems-tools update for symbol generation.

Working architectures:

aarch64 arm powerpc sparc

No newlib TLS support but checked:

i386 m69k

Updates #4920

#### **Comment 14**

1. **Chris Johns**, Tue, 22 Aug 2023 01:34:55 GMT

In 0860f99/rtems-source-builder:

rtems/tools: Pick up the rtems-syms and rtems-test sis changes

Updates #4920

**Comment 15**1. **Kinsey Moore**, Mon, 28 Aug 2023 15:31:32 GMT

With the update from Chris above, that leaves these architectures to check:

bfin lm32 mips moxie riscv v850

**Comment 16**1. **Chris Johns**, Tue, 29 Aug 2023 01:24:19 GMT

I think v850 can be left if it builds as it is to be removed once we branch 6 for release. For the others knowing which has TLS support enabled would be a good start.

**Comment 17**1. **Sebastian Huber**, Mon, 18 Sep 2023 05:24:15 GMT

In 49a88a7/rtems:

```
score: Add _CPU_Get_TLS_thread_pointer()
Add _CPU_Get_TLS_thread_pointer() to get the thread pointer which is used to get the address of thread-local storage objects associated with a thread.
Update #4920.
```

**Comment 18**1. **Sebastian Huber**, Mon, 18 Sep 2023 05:24:17 GMT

In de25f012/rtems:

```
libdl: Use _CPU_Get_TLS_thread_pointer()
Update #4920.
```

**Comment 19**1. **Kinsey Moore**, Thu, 21 Sep 2023 21:53:37 GMT

Remaining items on the list here are:

bfin lm32 mips moxie

I'm building tools to check these.

**Comment 20**1. **Kinsey Moore**, Fri, 22 Sep 2023 17:42:33 GMT

For blackfin in sptls01.exe:

Retrieving the TLS space:

```
331c: ff e3 22 f5 CALL 0x1d60 <_emutls_get_address>; 3320: 20 32 P4 = R0;
```

Retrieving the value for the only TLS item in this test:

```
3322: 60 99 R0 = B[P4] (X); 3324: 00 43 R0 = R0.B (X);
```

Setting the value for the only TLS item in this test to 5:

```
3340: 28 60 R0 = 0x5 (X); /* R0=0x5( 5) */ 3342: 20 9b B[P4] = R0;
```

**Comment 21**1. **Kinsey Moore**, Fri, 22 Sep 2023 17:54:40 GMT

For LM32 in sptls01.exe:

Retrieving TLS space:

```
8000498: f8 00 24 2f calli 8009554
```

Retrieving the value:

```
80004a0: 40 22 00 00 lbu r2,(r1+0)
```

Storing the value:

```
80004cc: 31 81 00 00 sb (r12+0),r1 (there was a "mv r12,r1" in the interim)
```

### **Comment 22**

1. **Kinsey Moore**, Fri, 22 Sep 2023 18:13:43 GMT

For MIPS in sptls01.exe:

Retrieving TLS space: 80010334: 7c03e83b rdhwr v0,\$29

Retrieving value: 80010344: 90429000 lbu v0,-28672(v0) (negative value is a sign-extended 0x9000, significance not understood)

Storing value: 800106bc: 24030005 li v1,5 800106c0: a0439000 sb v1,-28672(v0)

### **Comment 23**

1. **Kinsey Moore**, Fri, 22 Sep 2023 18:18:30 GMT

For Moxie in sptls01.exe:

Retrieving TLS space:

```
2022: 03 00 00 00 jsra 1c4e 2026: 1c 4e
```

(return value stored in r0)

Retrieving value:

```
1e98: 1c 32 ld.b $r1, ($r0)
```

Storing value (TLS address moved to r10):

```
202a: 1b 20 00 00 ldi.b $r0, 0x5 202e: 00 05 2030: 1e c2 st.b ($r10), $r0
```

### **Comment 24**

1. **Sebastian Huber**, Wed, 18 Oct 2023 09:00:32 GMT

In a4e1b7f/rtems-tools:

```
linker: Fix typo in symbol table generator
```

```
Updates #4920.
```

### **Comment 25**

1. **Joel Sherrill**, Wed, 18 Oct 2023 12:37:56 GMT

The rdhwr instruction is undefined and should generate an exception. It is expected that the OS will provide the TLS code in that exception. See <https://www.linux-mips.org/wiki/NPTL> for some details.

I have hoped there was a way in GCC to switch to the generic subroutine call but I've never tripped across it. Perhaps something might be obvious if you search for that instruction in the mips specific GCC code.

Replying to Kinsey Moore:

For MIPS in sptls01.exe:

Retrieving TLS space: 80010334: 7c03e83b rdhwr v0,\$29

Retrieving value: 80010344: 90429000 lbu v0,-28672(v0) (negative value is a sign-extended 0x9000, significance not understood)

Storing value: 800106bc: 24030005 li v1,5 800106c0: a0439000 sb v1,-28672(v0)

### **Comment 26**

1. **Kinsey Moore**, Wed, 18 Oct 2023 13:17:45 GMT

The MIPS CPU port in RTEMS doesn't yet support it, but this would be a good application of RTEMS\_EXCEPTION\_EXTENSIONS to accommodate the existing mechanism.

Replying to Joel Sherrill:

The rdhwr instruction is undefined and should generate an exception. It is expected that the OS will provide the TLS code in that exception. See <https://www.linux-mips.org/wiki/NPTL> for some details.

I have hoped there was a way in GCC to switch to the generic subroutine call but I've never tripped across it. Perhaps something might be obvious if you search for that instruction in the mips specific GCC code.

#### Comment 27

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:53:20 GMT
2. **keywords:** `qualification` added

#### Comment 28

1. **Kinsey Moore**, Fri, 16 Feb 2024 01:04:49 GMT

It's on my tasklist to update this issue with the current status.

#### Comment 29

1. **Kinsey Moore**, Mon, 19 Feb 2024 03:48:28 GMT

Status update:

bfin, lm32, moxie: Generated code uses `emutls_get_address()` to get the TLS base address. This is not yet implemented by `_CPU_Get_TLS_thread_pointer()`.

mips: Generated code uses the `rdhwr` instruction. This instruction is not yet used by `_CPU_Get_TLS_thread_pointer()` and, even if it were, RTEMS does not support it. There is no known way to prevent `gcc` from using this instruction to retrieve the TLS base address. This requires emulation of this instruction by RTEMS kernel code, possibly using `RTEMS_EXCEPTION_EXENSIONS` which are not yet available for this platform. There are at least 3 subtasks required to get this working on mips:

usage of `rdhwr` in `_CPU_Get_TLS_thread_pointer()` implementation of `RTEMS_EXCEPTION_EXENSIONS` or equivalent usage of the above to emulate `rdhwr`

v850: Slated for removal as stated above, not considered.

or1k, sh, sparc64, x86\_64: These do not support dynamic loading and are not being considered for this ticket.

aarch64, arm, i386, m68k, microblaze, nios2, powerpc, riscv, sparc: `_CPU_Get_TLS_thread_pointer()` is implemented and expected to function correctly.

## 4921 - Tool versions for RTEMS 6.1 release

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4921">https://devel.rtems.org/ticket/4921</a> ( <a href="https://devel.rtems.org/ticket/4921">https://devel.rtems.org/ticket/4921</a> )
<b>Id</b>	4921
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	3 July 2023 07:11:02
<b>Modified</b>	28 November 2023 22:24:49
<b>Owner</b>	Chris Johns
<b>Type</b>	task
<b>Component</b>	tool/rsb
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	4768
<b>Blocked by</b>	

#### **Description**

- GCC 13.2
- Binutils 2.41
- GDB 13.2
- Newlib TBD

#### Comment 1

1. **Sebastian Huber**, Mon, 03 Jul 2023 07:11:47 GMT
2. **owner:** set to `chris.johns`
3. **status:** changed from `new` to `assigned`

#### Comment 2

1. **Sebastian Huber**, Mon, 03 Jul 2023 07:12:51 GMT
2. **owner:** changed from `chris.johns` to `Chris Johns`

**Comment 3**

1. **Chris Johns**, Mon, 03 Jul 2023 21:54:59 GMT
2. **blocking**: set to **4768**

**Comment 4**

1. **Sebastian Huber**, Tue, 25 Jul 2023 05:14:55 GMT

In fd3ab60/rtems-source-builder:

```
6: Use GDB 13.2
Prepare for RTEMS 6.1 release.
Update #4921.
```

**Comment 5**

1. **Sebastian Huber**, Tue, 25 Jul 2023 05:14:56 GMT

In 96b1140/rtems-source-builder:

```
6: Use libexpat 2.5.0
This version contains security fixes. Prepare for RTEMS 6.1 release.
Update #4921.
```

**Comment 6**

1. **Sebastian Huber**, Thu, 23 Nov 2023 06:25:26 GMT

In df69080/rtems-source-builder:

```
6: Use GCC 13.2
Prepare for RTEMS 6.1 release.
Update #4921.
```

**Comment 7**

1. **Sebastian Huber**, Thu, 23 Nov 2023 06:25:28 GMT

In d4d0850/rtems-source-builder:

```
6: Use Binutils 2.41
Prepare for RTEMS 6.1 release.
Update #4921.
```

**Comment 8**

1. **Chris Johns**, Tue, 28 Nov 2023 22:24:49 GMT

In 9e57632/rtems-source-builder:

```
6: Fix gcc-13 support for MacOS
Update #4921
```

---

**4923 - FPU context init/switch not working well on more than 2 tasks on Cortex-Mx/ARMv7-M platform**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4923">https://devel.rtems.org/ticket/4923</a> ( <a href="https://devel.rtems.org/ticket/4923">https://devel.rtems.org/ticket/4923</a> )
<b>Id</b>	4923
<b>Reporter</b>	kgardas
<b>Created</b>	7 July 2023 09:47:34
<b>Modified</b>	31 January 2024 18:30:49
<b>Owner</b>	Cedric Berger
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	accepted
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	major
<b>Keywords</b>	
<b>Cc</b>	cedric@...
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

While working on stm32h7 I've noted strange results from fpu calculations when several tasks are involved. I've minimized that to attach testcase. The testcase runs well on Xilinx/A9/Qemu and BeagleBone? White platforms (ARMv7-A), but fails by providing wrong output on ARMv7-M (STM32H757i-eval).

The core of the testcase is a comparison of power of two done on integer by shifting and by calling C pow function with using double. When there is discrepancy in comparison of those, error is signaled and counted. The output then prints number of test run/number of failures and this all for Init and 4 other tasks created. The first error in comparison is also signaled for every task where it happen by clear 'ERROR' message. The output from H7 looks like:

```
initializing...
main task infinite loop.
ERROR, computation failed in fpu_task_pow2
ERROR, computation failed in fpu_task_pow3
ERROR, computation failed in fpu_task_pow4
ERROR, computation failed in Init
INIT: 1000/1000, T1: 38985/0, T2: 39802/39802, T3: 39735/39735, T4: 39804/39804
INIT: 2000/1000, T1: 78030/0, T2: 79663/79663, T3: 79508/79508, T4: 79650/79650
INIT: 3000/1000, T1: 117100/0, T2: 119517/119517, T3: 119281/119281, T4: 119513/119513
INIT: 4000/2000, T1: 156138/0, T2: 159385/159385, T3: 159054/159054, T4: 159355/159355
INIT: 5000/2000, T1: 195198/0, T2: 199242/199242, T3: 198827/198827, T4: 199195/199195
INIT: 6000/2000, T1: 234238/0, T2: 239111/239111, T3: 238599/238599, T4: 239054/239054
INIT: 7000/2000, T1: 273278/0, T2: 278961/278961, T3: 278372/278372, T4: 278903/278903
INIT: 8000/2000, T1: 312315/0, T2: 318807/318807, T3: 318145/318145, T4: 318740/318740
INIT: 9000/2000, T1: 351353/0, T2: 358628/358628, T3: 357918/357918, T4: 358600/358600
INIT: 10000/2000, T1: 390393/0, T2: 398463/398463, T3: 397691/397691, T4: 398444/398444
INIT: 11000/2000, T1: 429431/0, T2: 438302/438302, T3: 437464/437464, T4: 438279/438279
INIT: 12000/2000, T1: 468470/0, T2: 478152/478152, T3: 477236/477236, T4: 478123/478123
INIT: 13000/2000, T1: 507506/0, T2: 518006/518006, T3: 517009/517009, T4: 517961/517961
...
```

as you can see computation is always good (0 error) on T1 task while it is always bad on T2, T3, T4 tasks. Sometimes it is even bad on Init task.

Expected output from BeagleBone? looks:

```
initializing...
main task infinite loop.
INIT: 1000/0, T1: 8028/0, T2: 8042/0, T3: 8043/0, T4: 8043/0
INIT: 2000/0, T1: 16053/0, T2: 16084/0, T3: 16084/0, T4: 16085/0
INIT: 3000/0, T1: 24076/0, T2: 24125/0, T3: 24125/0, T4: 24126/0
INIT: 4000/0, T1: 32097/0, T2: 32163/0, T3: 32165/0, T4: 32167/0
INIT: 5000/0, T1: 40120/0, T2: 40204/0, T3: 40207/0, T4: 40208/0
...
```

The idea here is that task context initialization or switch is not working well on v7-M platform.

## Attachments:

- kgardas, Fri, 07 Jul 2023 09:48:03 GMT**  
attach: set to [init.c](https://devel.rtems.org/ticket/4923/init.c) (<https://devel.rtems.org/ticket/4923/init.c>)
- kgardas, Fri, 07 Jul 2023 10:19:26 GMT**  
attach: set to [init.2.c](https://devel.rtems.org/ticket/4923/init.2.c) (<https://devel.rtems.org/ticket/4923/init.2.c>)
- Cedric Berger, Tue, 06 Feb 2024 15:04:10 GMT**  
attach: set to [bug-1-make-paranoia-test-fail\\_patch](https://devel.rtems.org/ticket/4923/bug-1-make-paranoia-test-fail_patch) ([https://devel.rtems.org/ticket/4923/bug-1-make-paranoia-test-fail\\_patch](https://devel.rtems.org/ticket/4923/bug-1-make-paranoia-test-fail_patch))
- Cedric Berger, Tue, 06 Feb 2024 15:04:50 GMT**  
attach: set to [fix-1-save-and-restore-fpscr\\_patch](https://devel.rtems.org/ticket/4923/fix-1-save-and-restore-fpscr_patch) ([https://devel.rtems.org/ticket/4923/fix-1-save-and-restore-fpscr\\_patch](https://devel.rtems.org/ticket/4923/fix-1-save-and-restore-fpscr_patch))
- Cedric Berger, Tue, 06 Feb 2024 15:05:30 GMT**  
attach: set to [fix-2-clean-initial-thread-frame\\_patch](https://devel.rtems.org/ticket/4923/fix-2-clean-initial-thread-frame_patch) ([https://devel.rtems.org/ticket/4923/fix-2-clean-initial-thread-frame\\_patch](https://devel.rtems.org/ticket/4923/fix-2-clean-initial-thread-frame_patch))

## Comment 1

- kgardas, Fri, 07 Jul 2023 10:23:37 GMT**

Testing on nucleo-h743zi (most close to original platform of stm32h743-eval I have here) reveals same results as from stm32h757i-eval: (although to get failure on Init takes more time)

```

initializing...
main task infinite loop.
ERROR, computation failed in fpu_task_pow2
ERROR, computation failed in fpu_task_pow3
ERROR, computation failed in fpu_task_pow4
INIT: 1000/0, T1: 15085/0, T2: 15336/15336, T3: 15351/15351, T4: 15356/15356
INIT: 2000/0, T1: 30162/0, T2: 30685/30685, T3: 30716/30716, T4: 30727/30727
INIT: 3000/0, T1: 45239/0, T2: 46035/46035, T3: 46080/46080, T4: 46098/46098
INIT: 4000/0, T1: 60318/0, T2: 61384/61384, T3: 61429/61429, T4: 61468/61468
INIT: 5000/0, T1: 75419/0, T2: 76733/76733, T3: 76794/76794, T4: 76839/76839
INIT: 6000/0, T1: 90496/0, T2: 92082/92082, T3: 92159/92159, T4: 92210/92210
INIT: 7000/0, T1: 105575/0, T2: 107432/107432, T3: 107524/107524, T4: 107581/107581
INIT: 8000/0, T1: 120650/0, T2: 122799/122799, T3: 122888/122888, T4: 122952/122952
INIT: 9000/0, T1: 135725/0, T2: 138167/138167, T3: 138252/138252, T4: 138322/138322
INIT: 10000/0, T1: 150799/0, T2: 153535/153535, T3: 153617/153617, T4: 153693/153693
INIT: 11000/0, T1: 165874/0, T2: 168903/168903, T3: 168981/168981, T4: 169064/169064
INIT: 12000/0, T1: 180947/0, T2: 184253/184253, T3: 184346/184346, T4: 184435/184435
INIT: 13000/0, T1: 196021/0, T2: 199621/199621, T3: 199711/199711, T4: 199805/199805
INIT: 14000/0, T1: 211114/0, T2: 214989/214989, T3: 215075/215075, T4: 215176/215176
INIT: 15000/0, T1: 226187/0, T2: 230357/230357, T3: 230440/230440, T4: 230547/230547
INIT: 16000/0, T1: 241261/0, T2: 245726/245726, T3: 245805/245805, T4: 245918/245918
INIT: 17000/0, T1: 256335/0, T2: 261094/261094, T3: 261169/261169, T4: 261289/261289
INIT: 18000/0, T1: 271409/0, T2: 276463/276463, T3: 276534/276534, T4: 276659/276659
ERROR, computation failed in Init
INIT: 19000/1000, T1: 286484/0, T2: 291832/291832, T3: 291899/291899, T4: 292030/292030
INIT: 20000/1000, T1: 301565/0, T2: 307199/307199, T3: 307264/307264, T4: 307398/307398
INIT: 21000/1000, T1: 316637/0, T2: 322550/322550, T3: 322628/322628, T4: 322765/322765

```

**Comment 2**

1. **Sebastian Huber**, Fri, 07 Jul 2023 13:15:38 GMT

Does the spcontext01 check the floating-point registers on this BSP and what is the outcome of this test?

**Comment 3**

1. **kgardas**, Fri, 07 Jul 2023 13:25:38 GMT

Here is the output of spcontext01 on nucleo-h743zi:

```

*** BEGIN OF TEST SPCONTEXT 1 ***
*** TEST VERSION: 6.0.0.6264b14804bbe21f13d4691160b45e208286abaa
*** TEST STATE: EXPECTED_PASS
*** TEST BUILD:
*** TEST TOOLS: 12.2.1 20230224 (RTEMS 6, RSB 7153c2f1dcfb83b154b976298699c26e793a33dd, Newlib 17ac400)
Test configuration N N N... done
Test configuration N N F... done
Test configuration N F N... done
Test configuration N F F... done
Test configuration F N N... done
Test configuration F N F... done
Test configuration F F N... done
Test configuration F F F... done
*** END OF TEST SPCONTEXT 1 ***
[ RTEMS shutdown ]
RTEMS version: 6.0.0.6264b14804bbe21f13d4691160b45e208286abaa
RTEMS tools: 12.2.1 20230224 (RTEMS 6, RSB 7153c2f1dcfb83b154b976298699c26e793a33dd, Newlib 17ac400)
executing thread ID: 0x0a010001
executing thread name: UI1

```

Let me know if there is anything I should test here. I have some spare time at my disposal, but I'd need to be kicked into the right direction. Currently studding Cortex-M lazy stacking and context switching and RTEMS book is ordered as a backup and will be here probably next week. I'll also provide few registers dumps for your information...

**Comment 4**

1. **Sebastian Huber**, Fri, 07 Jul 2023 14:05:26 GMT

Maybe we don't save a status register related to the FPU.

**Comment 5**

1. **Joel Sherrill**, Fri, 07 Jul 2023 14:19:47 GMT

Maybe the FPU context isn't properly initialized for this CPU variant. The first context switch restore is handled special in `_Thread_Handler`. Easy enough to break there and see what is actually being restored. If it's wrong, then that's the culprit.

**Comment 6**

1. **kgardas**, Fri, 07 Jul 2023 14:48:04 GMT

Ad `_Thread_Handler` breakpoint:



```
(gdb) b _Thread_Handler
Breakpoint 1 at 0x8003748: file ../../cpukit/include/rtems/score/percpu.h, line 719.
Note: automatically using hardware breakpoints for read-only addresses.
(gdb) c
Continuing.
Breakpoint 1, _Thread_Handler ()
  at ../../cpukit/include/rtems/score/percpu.h:719
719     return cpu->executing;
(gdb) where
#0  _Thread_Handler () at ../../cpukit/include/rtems/score/percpu.h:719
#1  0x08003748 in _Thread_Get (id=, lock_context=0x0)
  at ../../cpukit/score/src/threadget.c:63
Backtrace stopped: previous frame identical to this frame (corrupt stack?)
(gdb) c
Continuing.
Breakpoint 1, _Thread_Handler ()
  at ../../cpukit/include/rtems/score/percpu.h:719
719     return cpu->executing;
(gdb) c
Continuing.
Breakpoint 1, _Thread_Handler ()
  at ../../cpukit/include/rtems/score/percpu.h:719
719     return cpu->executing;
(gdb) c
Continuing.
Breakpoint 1, _Thread_Handler ()
  at ../../cpukit/include/rtems/score/percpu.h:719
719     return cpu->executing;
```

this looks like some macro executing:

```
static inline struct _Thread_Control *_Per_CPU_Get_executing(
  const Per_CPU_Control *cpu
)
{
  return cpu->executing;
}
```

### Comment 7

1. **Sebastian Huber**, Thu, 13 Jul 2023 12:32:33 GMT

We were able to reproduce the issue. It is a problem in the FPU context save/restore during interrupt processing. Under certain conditions, the FPU context is restored from an uninitialized frame which could enable the flush-to-zero configuration. I am currently quite busy. I will add it to my TODO list, but it could be September/October?.

### Comment 8

1. **kgardas**, Thu, 13 Jul 2023 12:43:11 GMT

Sebastian, thanks a lot for the information. Could you give me as much information as possible with regarding to the issue as there is a high chance I find some time to deal it again before your available timeframe. For example I'm curious is it related to FPU lazy stack saving which is used and enforced by the RTEMS code? Knowing all information about it from you, will certainly help with possible fixing of the issue on our side. Thanks a lot!

### Comment 9

1. **Sebastian Huber**, Thu, 13 Jul 2023 13:23:33 GMT

The FPU context corruption happens in `_ARMV7M_Pendable_service_call()`. Somehow the FPU context is not restored from the right frame position in certain cases. It is not clear, why this error doesn't show up in the `spcontext01` test.

### Comment 10

1. **kgardas**, Thu, 27 Jul 2023 18:45:22 GMT

I consider this issue to be release critical as it affects one of major platforms (ARMv7-M) and makes FPU computation unreliable/unpredictable there. Hence switching milestone to 6.1. Please discuss if you do not think so.

### Comment 11

1. **kgardas**, Thu, 27 Jul 2023 18:45:55 GMT
2. **milestone**: set to **6.1**

### Comment 12

1. **Cedric Berger**, Wed, 31 Jan 2024 18:28:00 GMT
2. **cc**: **cedric@...** added

### Comment 13

1. **Cedric Berger**, Wed, 31 Jan 2024 18:30:49 GMT
2. **owner**: set to **Cedric Berger**
3. **status**: changed from **new** to **accepted**
4. **version**: set to **6**

I will try to work on that in February.

## 4924 - Add Regulator Helper to RTEMS

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4924">https://devel.rtems.org/ticket/4924</a> ( <a href="https://devel.rtems.org/ticket/4924">https://devel.rtems.org/ticket/4924</a> )
<b>Id</b>	4924
<b>Reporter</b>	Joel Sherrill
<b>Created</b>	7 July 2023 20:31:03
<b>Modified</b>	16 August 2023 15:10:43
<b>Owner</b>	Joel Sherrill
<b>Type</b>	enhancement
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

This is to add the Regulator Helper. This will include the regulator itself, a test with full coverage, an example for rtems-examples, and a chapter in the Classic API Guide.

The regulator is designed to sit logically between two entities -- a source and a destination, where it limits the traffic sent to the destination to prevent it from being flooded with messages from the source. This can be used to accommodate bursty input from a source and meter it out to a destination.

### Comment 1

1. **Joel Sherrill**, Fri, 07 Jul 2023 20:31:10 GMT
2. **owner:** set to **Joel Sherrill**
3. **status:** changed from **new** to **assigned**

### Comment 2

1. **z.ling111**, Sun, 09 Jul 2023 01:12:13 GMT

Hello joel interested in working on this ticket would like some more info.

### Comment 3

1. **Joel Sherrill**, Sun, 09 Jul 2023 14:57:23 GMT

The code was posted to devel@ for review Friday. Documentation will follow soon. The most helpful thing would be to review this code. Beyond this help is needed to address tickets with a 6.1 target.

### Comment 4

1. **Joel Sherrill**, Fri, 11 Aug 2023 18:21:24 GMT

In fd69308/rtems:

```
Add the Regulator Interface and test
```

```
Updates #4924.
```

```
The Regulator is an application support class which is used to deal with the scenario where there is a bursty input source which needs to be metered out to a destination sink. The maximum size of bursts needs to be known and the delivery method must be configured to deliver messages at a rate that allows the traffic to not overflow.
```

### Comment 5

1. **Joel Sherrill**, Wed, 16 Aug 2023 15:10:43 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

Chapter added to the Classic API Guide and an example added to rtems-examples without having the ticket tagged:

```
https://git.rtems.org/rtems-docs/commit?id=7bd117cb00b68e5cb89aa8c237a813730876817e https://git.rtems.org/rtems-examples/commit?id=d11f57cff6621fefac1d1bca5d013b8c79171cc7
```

This can now be closed.

---

## 4925 - Deal with GR740 errata: Level-2 Cache Issues H1 2023 (GRLIB-TN-0021)

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4925">https://devel.rtems.org/ticket/4925</a> ( <a href="https://devel.rtems.org/ticket/4925">https://devel.rtems.org/ticket/4925</a> )
<b>Id</b>	4925
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	12 July 2023 04:21:04
<b>Modified</b>	12 July 2023 04:21:04
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/sparc
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Evaluate, document, implement workarounds and validate the workarounds for the GR740 errata: Level-2 Cache Issues H1 2023 (GRLIB-TN-0021):

<https://gaisler.com/doc/antn/GRLIB-TN-0021.pdf>

---

**4929 - RTEMS tools installs into \$PREFIX/share/rtems and not \$PREFIX/share/rtems6**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4929">https://devel.rtems.org/ticket/4929</a> ( <a href="https://devel.rtems.org/ticket/4929">https://devel.rtems.org/ticket/4929</a> )
<b>Id</b>	4929
<b>Reporter</b>	Chris Johns
<b>Created</b>	19 July 2023 21:17:53
<b>Modified</b>	19 July 2023 21:17:53
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

Should these path be aligned?

At the moment it creates confusion if the user enters the wrong prefix when building RTEMS.

---

**4931 - User manual RSB BSP build examples need updating**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4931">https://devel.rtems.org/ticket/4931</a> ( <a href="https://devel.rtems.org/ticket/4931">https://devel.rtems.org/ticket/4931</a> )
<b>Id</b>	4931
<b>Reporter</b>	Chris Johns
<b>Created</b>	25 July 2023 02:33:00
<b>Modified</b>	25 July 2023 02:33:00
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description****4934 - Update STM32 H7 HAL/LL drivers code**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4934">https://devel.rtems.org/ticket/4934</a> ( <a href="https://devel.rtems.org/ticket/4934">https://devel.rtems.org/ticket/4934</a> )
<b>Id</b>	4934
<b>Reporter</b>	kgardas
<b>Created</b>	27 July 2023 18:32:22
<b>Modified</b>	2 August 2023 08:26:14
<b>Owner</b>	kgardas
<b>Type</b>	task
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Hello,

patch series for updating STM32 H7 HAL/LL drivers code is ready for review already here: <https://github.com/karelv/rtems/tree/stm32h7-hal-update-2023-07>.

The code was tested on both M7 and M4 cores on stm32h747i-disco board and shows that update does not cause any new failures/regressions.

The patch series was already submitted for review on devel@ here: <https://lists.rtems.org/pipermail/devel/2023-July/075880.html>

**Comment 1**

1. **kgardas**, Wed, 02 Aug 2023 08:26:14 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

New HAL code was merged into the tree on July 31 2023. Hence closing.

**4935 - 7/rtems-mips get source fails**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4935">https://devel.rtems.org/ticket/4935</a> ( <a href="https://devel.rtems.org/ticket/4935">https://devel.rtems.org/ticket/4935</a> )
<b>Id</b>	4935
<b>Reporter</b>	Chris Johns
<b>Created</b>	30 July 2023 22:56:21
<b>Modified</b>	20 November 2023 17:08:59
<b>Owner</b>	joel
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	highest
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Getting sources for 7/rtems-mips fails with:

```
error: 7/rtems-mips.bset:6: cannot find file: tools/rtems-mipstx39-gdb-head
```

Release candidates for 6 get the 7 sources because the 6-rc? are made from master.

**Comment 1**

1. **Chris Johns**, Sun, 30 Jul 2023 22:58:41 GMT

To test run this command (<https://git.rtems.org/rtems-release/tree/rtems-release-sources#n139>):

```
../source-builder/sb-get-sources --stop-on-error
```

**Comment 2**

1. **Chris Johns**, Sun, 03 Sep 2023 05:39:22 GMT

I will point the 7 MIPS gdb to the 6 version. I have no idea about this architecture and tools and no one has picked the issue up.

Also this is present:

<file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html>

```
warning: 0001-gcc-config-aarch64-rtems.h-Define--USE-INIT-FINI-.patch: no hash found
warning: 0001-microblaze-Define--ELF--for-RTEMS-target.patch: no hash found
```

I need to see why an error was not generated. No hash should be a hard error.

### Comment 3

1. **Chris Johns**, Fri, 17 Nov 2023 03:18:22 GMT
2. **owner:** set to **joel**
3. **status:** changed from **new** to **assigned**

This is still present and making a release candidate breaks:

```
] Created: 6.1-rc1/rtems-6.1-rc1-release-notes.html 6.1-rc1/rtems-6.1-rc1-release-notes.pdf
] Collect tools sources
] RTEMS Release Sources, v6.1-rc1
] Package: rtems-source-builder
] Release: 6.1-rc1
tar Jxf ../rtems-source-builder-6.1-rc1.tar.xz
./source-builder/sb-get-sources
RTEMS Source Builder - Get Sources, 6.1-rc1
error: 7/rtems-mips.bset:6: cannot find file: tools/rtems-mipstx39-gdb-head
Build FAILED
```

### Comment 4

1. **Joel Sherrill**, Mon, 20 Nov 2023 17:08:59 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In ae81810/rtems-source-builder:

```
rtems-mipstx39-gdb-head.bset: Add missing file
```

```
This configuration file was missing for the mipstx39 gdb build for the head/7 tools.
```

```
Closes #4935.
```

## 4940 - Fix cache support for ARM926EJ-S processor

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4940">https://devel.rtems.org/ticket/4940</a> ( <a href="https://devel.rtems.org/ticket/4940">https://devel.rtems.org/ticket/4940</a> )
<b>Id</b>	4940
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	10 August 2023 06:10:15
<b>Modified</b>	10 August 2023 06:11:28
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/arm
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

Fix the CP15 cache support so that it works on ARMv5T processors such as the ARM926EJ-S. This processor has different cache maintenance operations compared to ARMv6 processors such as the ARM1176JZF-S. The current support leads to undefined instruction exceptions.

### Comment 1

1. **Sebastian Huber**, Thu, 10 Aug 2023 06:11:28 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In ffec9f96/rtems:

```
arm: Fix cache support for ARM926EJ-S
```

```
The ARM926EJ-S is an ARMv5T architecture processor and lacks some features of ARMv6 processors such as the ARM1176JZF-S.
```

```
Close #4940.
```

## 4942 - Regulator warnings

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4942">https://devel.rtems.org/ticket/4942</a> ( <a href="https://devel.rtems.org/ticket/4942">https://devel.rtems.org/ticket/4942</a> )
<b>Id</b>	4942
<b>Reporter</b>	Chris Johns
<b>Created</b>	11 August 2023 22:30:59
<b>Modified</b>	15 August 2023 14:09:09
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The recently added regulator has warnings on aarch64/xilinx\_zynqmp\_lp64\_qemu:

```

../../../../cpukit/libmisc/regulator/regulator.c: In function 'rtems_regulator_get_statistics':
../../../../cpukit/libmisc/regulator/regulator.c:656:3: warning: implicit declaration of function 'memset' [-Wimplicit-function-declaration]
  656 |     memset(statistics, 0, sizeof(rtems_regulator_statistics));
      |     ^~~~~~
../../../../cpukit/libmisc/regulator/regulator.c:40:1: note: include '' or provide a declaration of 'memset'
   39 | #include
      | +++ |+#include
   40 |
../../../../cpukit/libmisc/regulator/regulator.c:656:3: warning: incompatible implicit declaration of built-in function 'memset' [-Wbuiltin-declaration-mismatch]
  656 |     memset(statistics, 0, sizeof(rtems_regulator_statistics));
      |     ^~~~~~
../../../../cpukit/libmisc/regulator/regulator.c:656:3: note: include '' or provide a declaration of 'memset'

```

**Comment 1**

1. **z.ling111**, Sun, 13 Aug 2023 00:51:08 GMT

Is there a way to compile libmisc I added the .h file but i didn't see it compile when i ran ./waf is there an option to compile libmisc?

**Comment 2**

1. **Joel Sherrill**, Sun, 13 Aug 2023 04:46:16 GMT

Replying to z.ling111:

Is there a way to compile libmisc I added the .h file but i didn't see it compile when i ran ./waf is there an option to compile libmisc?

libmisc is built all the time. Nothing special. Post the patch once you compile and run the tests.

**Comment 3**

1. **zack**, Tue, 15 Aug 2023 14:09:09 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 7b33aa26/rtems:

```

Address Regulator warning for no prototype for memset()
Closes #4942.

```

**4943 - ARM unwind register is not being hooked**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4943">https://devel.rtems.org/ticket/4943</a> ( <a href="https://devel.rtems.org/ticket/4943">https://devel.rtems.org/ticket/4943</a> )
<b>Id</b>	4943
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 August 2023 01:53:26
<b>Modified</b>	14 August 2023 01:05:25
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The ARM unwind support is not working and dl05 is failing on aarch64.  
The support uses `__gnu_Unwind_Find_exidx` and it is not being called.  
I have not tested arm but the support is shared between arm and aarch64.

**Comment 1**

1. **Chris Johns**, Sat, 12 Aug 2023 05:59:41 GMT

The aarch64 architecture can use the DWARF 2 exception support. This is an improvement over the specific ARM support. Switching the unwind support to `rtems_rtl_elf_unwind_dw2_*` functions results in dl05 passing.

**Comment 2**

1. **Chris Johns**, Sat, 12 Aug 2023 06:30:02 GMT
2. **owner**: set to **Chris Johns**
3. **status**: changed from **new** to **assigned**

**Comment 3**

1. **Chris Johns**, Mon, 14 Aug 2023 01:05:25 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In 663e0dae/rtems:

```
cpukit/libdl: AARCH64 unwind uses DWARF 2 tables
Closes #4943
```

**4944 - libdl test dl09 fails on arm and aarch64**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4944">https://devel.rtems.org/ticket/4944</a> ( <a href="https://devel.rtems.org/ticket/4944">https://devel.rtems.org/ticket/4944</a> )
<b>Id</b>	4944
<b>Reporter</b>	Chris Johns
<b>Created</b>	12 August 2023 06:26:29
<b>Modified</b>	28 August 2023 01:19:04
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The test crashes on arm and fails on aarch64 with:

```

-----
Run: 3
Test source (link in strstr): testsuites/libtests/dl09/dl-load.c
Allocation size: 33554432
load: /dl09-o1.o
handle: 0x4811d650: unresolved externals
handle: 0x4811d650 loaded
space alloc: /dl09-o1.o: 33554432: 0x40118940
load: /dl09-o2.o
handle: 0x421191f0: unresolved externals
handle: 0x421191f0 loaded
space alloc: /dl09-o2.o: 33554432: 0x4c1225b0
load: /dl09-o3.o
kobj_reloc: Relocation 0x40045820 too far from 0x4e122f48 (base+0x18) for 26bit word
dlopen failed: (null)
/opt/work/chris/rtems/kernel/rtems.git/testsuites/libtests/dl09/dl-load.c: 168 o->handle != NULL
[ RTEMS shutdown ]
RTEMS version: 6.0.0.10da3025186cadf2d78e34cf81cce02121069d44
RTEMS tools: 12.3.1 20230626 (RTEMS 6, RSB 8e568b2ca3489d6bfa48e1d29618ea9b48a5b408, Newlib 4c7d0df)
executing thread ID: 0x0a010001
executing thread name: UI1

```

**Comment 1**

1. **Chris Johns**, Tue, 15 Aug 2023 02:51:10 GMT

It also fails on powerpc.

**Comment 2**

1. **Chris Johns**, Fri, 18 Aug 2023 23:54:04 GMT

The dl091 test allocates large blocks of memory between loading object files to move the object's text base address out of the range of any relative addressing instructions to symbols in the base image forcing the use of trampolines.

On aarch64 the failure is the trampoline memory is out of range to the text memory so the relocations to the trampoline memory cannot be fixed up. The allocated trampoline memory is not colocated to the allocated text memory when it should be. The overflow is:

```
rtl: JUMP26/PC26/CALL: insn=0x4e123208 where=0x4e123208 target=0xfffffffff1f24898 raddr=0x40047aa0 parsing=0
```

The target value is the relative offset and is -201367832. The instruction to fix up is located at 0x4e123208. The trampoline allocation is:

```

rtl: tramp:elf: tramps: 14 count:14 total:14
rtl: tramp:elf: slots: 14 (224)
rtl: alloc: new: OBJECT addr=0x421190f0 size=224

```

If trace is enabled for the test a set of commands are run at the end of each pass to report the state of some things such as the heap. The heap state is returned by the malloc\_info() call and that call causes the test to pass (see #4946). Something happens in the heap to bring the allocated memory closer together.

The intent of the original design was to have a trampoline table appended to one end of the text area of the object file's memory. This means the maximum size of code that can be loaded is half the relative instruction offset size. A review of the code shows the trampoline memory is being heap allocated as a separate block. I cannot remember why it is implemented this way. Effort was spent determining how to handle the allocation because the relocation records need to be parsed to determine the amount of memory to append to the text area and this means the relocation records are processed twice slowing loading down. The double processing of the relocation records was considered a suitable compromise to solve the problem. Parsing was added however the number of relocations is not being used when allocating the text area of memory.

I think the text area needs to be extended to hold the trampoline memory. I am not sure if the text size reported should be the object file's text size or the size with the trampoline memory. I suppose it is text type memory so it should be included. It will make the change simpler.

**Comment 3**

1. **Chris Johns**, Sat, 19 Aug 2023 00:04:35 GMT

I now see the complicating factor and the reason the memory is a separate allocation.

The trampoline memory is sized to allocate space for each unresolved symbol an object file has. When loading an object file you do not know if an unresolved symbol will need a trampoline to reach the symbol.

**Comment 4**

1. **Chris Johns**, Thu, 24 Aug 2023 06:16:08 GMT

I have added allocator resize support to libdl. The object file memory is resized if there are any trampolines found when the relocation records are parsed. The sizing determines the amount of trampoline memory needed and the tramp\_size is added to the text\_size resizing the text section.

The order of allocations has been changed so text is last and so lower the probability resizing moves the text\_base address. In the output from dl09 you can see 120 bytes of trampoline memory is being added onto the text section:

```

rtl: alloc: resize: READ_WRITE prev-addr=0x4e132610 addr=0x4e132610 size=8
rtl: alloc: resize: READ_WRITE prev-addr=0x4e132670 addr=0x4e132670 size=32
rtl: alloc: resize: READ prev-addr=0x4e1326e0 addr=0x4e1326e0 size=328
rtl: alloc: resize: READ_EXEC prev-addr=0x4e132870 addr=0x4e132870 size=472
rtl: resize sect: text - b:0x4e132870 s:472 a:4
rtl: resize sect: tramp - b:0x4e1329d0 s:120 a:8
rtl: resize sect: const - b:0x4e1326e0 s:328 a:8
rtl: resize sect: eh - b:0 s:0 a:0
rtl: resize sect: data - b:0x4e132610 s:8 a:0
rtl: resize sect: bss - b:0x4e132670 s:32 a:8

```

The changes will handle a section moving when resizing.

The dl09 test now passes for aarch64 with and without trace being turned on.

**Comment 5**

1. **Chris Johns**, Sat, 26 Aug 2023 23:05:18 GMT



Test results with the changes to fix dl09 for arm/lilnx\_zynq\_a9\_qemu:

```

Passed:          9
Failed:          1
User Input:      1
Expected Fail:   0
Indeterminate:   0
Benchmark:       0
Timeout:         0
Test too long:   0
Invalid:         0
Wrong Version:   0
Wrong Build:     0
Wrong Tools:     0
Wrong Header:    0
-----
Total:          11
Failures:
  dl06.exe
User Input:
  dll10.exe

```

and for aarch64/xilinx\_zynqmp\_lp64\_qemu:

```

Passed:          9
Failed:          1
User Input:      1
Expected Fail:   0
Indeterminate:   0
Benchmark:       0
Timeout:         0
Test too long:   0
Invalid:         0
Wrong Version:   0
Wrong Build:     0
Wrong Tools:     0
Wrong Header:    0
-----
Total:          11
Failures:
  dl06.exe
User Input:
  dll10.exe

```

### Comment 6

1. **Chris Johns**, Mon, 28 Aug 2023 01:19:01 GMT

In dcc6409/rtems:

```
spec/testsuite/dl: Fix optimization flags
```

```
Updates #4944
```

### Comment 7

1. **Chris Johns**, Mon, 28 Aug 2023 01:19:04 GMT
2. **owner:** set to **Chris Johns** <chrisj@...>
3. **status:** changed from **new** to **closed**
4. **resolution:** set to **fixed**

In b9f11607/rtems:

```
libdl: Realloc text memory if there are trampolines
Add resize to the allocator interface Rework the trampoline variables in the obj struct
to make better sense of what is happening
Closes #4944
```

## 4945 - rtems-test SIS support is broken

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4945">https://devel.rtems.org/ticket/4945</a> ( <a href="https://devel.rtems.org/ticket/4945">https://devel.rtems.org/ticket/4945</a> )
<b>Id</b>	4945
<b>Reporter</b>	Chris Johns
<b>Created</b>	17 August 2023 01:50:40
<b>Modified</b>	21 August 2023 00:37:35
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The sis BSP is using gdb and I am not sure gdb supports the SIS simulator any more?

And sis-run is broken with the stand alone sis tool we now use. The -a option is not supported.

**Comment 1**

1. **Chris Johns**, Thu, 17 Aug 2023 01:51:01 GMT
2. **owner:** changed from **joel@...** to **Chris Johns**
3. **status:** changed from **new** to **assigned**

**Comment 2**

1. **Chris Johns**, Mon, 21 Aug 2023 00:37:35 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 349bbd9/rtems-tools:

```
tester/sis: Use the RTEMS SIS command
Make sis and sis-run the same as there is no SIS support in gdb anymore.
Closes #4945
```

**4947 - Testsuite libtest tests not built with optimise or debug flags**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4947">https://devel.rtems.org/ticket/4947</a> ( <a href="https://devel.rtems.org/ticket/4947">https://devel.rtems.org/ticket/4947</a> )
<b>Id</b>	4947
<b>Reporter</b>	Chris Johns
<b>Created</b>	24 August 2023 23:27:22
<b>Modified</b>	12 September 2023 07:27:42
<b>Owner</b>	Sebastian Huber <sebastian.huber@...>
<b>Type</b>	defect
<b>Component</b>	build
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The tests are being built with the optimize or debug options for:

- aarch64/xilinx\_zynqmp\_lp64\_qemu
- arm/xilinx\_zynq\_a9\_qemu

The build is:

```
09:44:14 runner '/opt/work/rtems/6/bin/arm-rtems6-gcc
-MMD -Wall -Wmissing-prototypes -Wimplicit-function-declaration
-Wstrict-prototypes -Wnested-externs -march=armv7-a -mthumb
-mfpu=neon -mfloat-abi=hard -mtune=cortex-a9 -DHAVE_CONFIG_H=1
-Icpukit/include -I../..../cpukit/include -Icpukit/score/cpu/arm/include
-I../..../cpukit/score/cpu/arm/include -Ibsps/include
-I../..../bsps/include -Ibsps/arm/include -I../..../bsps/arm/include
-Ibsps/arm/xilinx-zynq/include -I../..../bsps/arm/xilinx-zynq/include
-Itestsuites/support/include -I../..../testsuites/support/include
-Itestsuites/libtests/dl09 -I../..../testsuites/libtests/dl09
-c /opt/work/chris/rtems/kernel/rtems.git/testsuites/libtests/dl09/dl-load.c
-o testsuites/libtests/dl09/dl-load.o'
```

while a cpukit file is:

```
09:45:00 runner ['/opt/work/rtems/6/bin/arm-rtems6-gcc',
'-MMD', '-Wall', '-Wmissing-prototypes', '-Wimplicit-function-declaration',
'-Wstrict-prototypes', '-Wnested-externs', '-march=armv7-a',
'-mthumb', '-mfpu=neon', '-mfloat-abi=hard', '-mtune=cortex-a9',
'-O2', '-g', '-fdata-sections', '-ffunction-sections',
'-Icpukit/include', '-I../..../cpukit/include',
'-Icpukit/score/cpu/arm/include',
'-I../..../cpukit/score/cpu/arm/include',
'../..../cpukit/libdl/rtl-elf.c',
'-c', '-o/opt/work/chris/rtems/kernel/rtems.git/build/arm/xilinx_zynq_a9_qemu/cpukit/libdl/rtl-elf.c.59.o',
'-DHAVE_CONFIG_H=1']
```

**Comment 1**

1. **Chris Johns**, Thu, 24 Aug 2023 23:48:52 GMT

The tests use the TEST\_OPTIMIZATION\_FLAGS which is defined in the BSP and based on OPTIMIZATION\_FLAGS. This does not seem to be working.

#### Comment 2

1. **Chris Johns**, Thu, 24 Aug 2023 23:49:26 GMT
2. **severity**: changed from **normal** to **blocker**

#### Comment 3

1. **Chris Johns**, Fri, 25 Aug 2023 23:28:06 GMT

The issue is the tests are not being linked with the right or complete set of flags.

The optimization flags contain -g and given -g does not change the generated code it is questionable if this option should be here or a debug flags settings or even forced on as an invariant default.

The simplest solution at this point in time is to add \${TEST\_OPTIMIZATION\_FLAGS} to the ldflags in the grp.yml for the testsuite.

Adding TEST\_OPTIMIZATION\_FLAGS to the linker flags has the benefit of linking with -fdata-sections and -ffunction-sections and given we are building all the code with those options the tests are not truly testing the build a user sees.

There is a fragility around having the separate sections flags in optimization flag set. If someone adjusts the -O level they need to carry the other flags over. Is the separate sections important enough now that it needs its own setting to avoid simple mistakes?

#### Comment 4

1. **Chris Johns**, Fri, 25 Aug 2023 23:49:15 GMT

The test dl09 does not build dl-load.o with the TEST\_OPTIMIZATION\_FLAGS flags. Updating the dl09.yml spec's cflags to have TEST\_OPTIMIZATION\_FLAGS works but adding that same to the ldflags breaks the build because the substitution does not happen.

It seems cflags does not pick up the top level grp.yml setting while ldflags does. I have no idea why it is like this.

#### Comment 5

1. **Sebastian Huber**, Tue, 12 Sep 2023 07:27:42 GMT
2. **owner**: set to **Sebastian Huber** <sebastian.huber@...>
3. **status**: changed from **new** to **closed**
4. **resolution**: set to **fixed**

In d2d1fa18/rtems:

```
build: Use build context for custom commands
Revert duplicated listing of TEST_OPTIMIZATION_FLAGS.
Close #4947.
```

## 4950 - libdl test dl07 fails on PowerPC

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4950">https://devel.rtems.org/ticket/4950</a> ( <a href="https://devel.rtems.org/ticket/4950">https://devel.rtems.org/ticket/4950</a> )
<b>Id</b>	4950
<b>Reporter</b>	Chris Johns
<b>Created</b>	28 August 2023 01:25:22
<b>Modified</b>	29 August 2023 01:21:58
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib/dl
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

The libdl test dl07 fails on PowerPC (psim) with:

```
rtl: alloc: del: READ_WRITE addr=0x91ca8
*** FATAL ***
fatal source: 13 (RTEMS FATAL SOURCE HEAP)
heap error: heap=0x7e6d0 blocK=0x91cdC reason=HEAP_ERROR_BROKEN_PROTECTOR(0)=[0x91ce0,0,0,0]
RTEMS version: 6.0.0.b9f11607b1731bc5f2391653cd8f4ebe48ba278e
RTEMS tools: 12.3.1 20230626 (RTEMS 6, RSB 8e568b2ca3489d6bfa48e1d29618ea9b48a5b408, Newlib 4c7d0df)
executing thread ID: 0x0a010001
executing thread name: UI1
```

The issue is the .bss section size is too small for the sections present. The bug has been triggered by the separate section support now being used in the test suite.

#### Comment 1

1. **Chris Johns**, Mon, 28 Aug 2023 06:31:02 GMT

The change to use separate data and text sections exposed a bug in how symbols and section alignment are handled when locating the symbols. The issues are:

The base address of a section may not be aligned to the required alignment. The location support on PowerPC included SDATA symbols in respective data section processing while not being included in the size calculation. This pushed the symbols out past the end of the allocated memory.

#### Comment 2

1. **Chris Johns**, Tue, 29 Aug 2023 01:21:58 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In ac6de5a3/rtems:

```
cpukit/libdl: Correctly account for section alignments
Add the section alignment to the size as the allocator may not
provide correctly aligned memory Only include symbols in the section when locating symbols. The
powerpc was incorrectly adding SDATA BSS symbols to the BSS offset
overrunning the section
Closes #4950
```

## 4951 - rtems-tools fail on FreeBSD to get number of cores

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4951">https://devel.rtems.org/ticket/4951</a> ( <a href="https://devel.rtems.org/ticket/4951">https://devel.rtems.org/ticket/4951</a> )
<b>Id</b>	4951
<b>Reporter</b>	Chris Johns
<b>Created</b>	28 August 2023 04:52:14
<b>Modified</b>	3 September 2023 05:27:49
<b>Owner</b>	Chris Johns <chrisj@...>
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

```
$ ./waf test
Waf: Entering directory `/opt/work/chris/rtems/tools/rtems-tools.git/build'
Test python rtemstoolkit.check : fail
Test python3 rtemstoolkit.check : fail
Test python rtemstoolkit.config : fail
Test python3 rtemstoolkit.config : fail
Test python rtemstoolkit.configuration : pass
Test python3 rtemstoolkit.configuration : pass
Test python rtemstoolkit.error : pass
Test python3 rtemstoolkit.error : pass
Test python rtemstoolkit.execute : fail
Test python3 rtemstoolkit.execute : fail
Test python rtemstoolkit.git : fail
Test python3 rtemstoolkit.git : fail
Test python rtemstoolkit.host : fail
Test python3 rtemstoolkit.host : fail
Test python rtemstoolkit.log : pass
Test python3 rtemstoolkit.log : pass
Test python rtemstoolkit.macros : pass
Test python3 rtemstoolkit.macros : pass
Test python rtemstoolkit.mailer : fail
Test python3 rtemstoolkit.mailer : fail
Test python rtemstoolkit.options : fail
Test python3 rtemstoolkit.options : fail
Test python rtemstoolkit.path : pass
Test python3 rtemstoolkit.path : pass
Test python rtemstoolkit.reraise : pass
Test python3 rtemstoolkit.reraise : pass
Test python rtemstoolkit.rtems : pass
Test python3 rtemstoolkit.rtems : pass
Test python rtemstoolkit.stacktraces : pass
Test python3 rtemstoolkit.stacktraces : pass
Test python rtemstoolkit.textbox : pass
Test python3 rtemstoolkit.textbox : pass
Test python rtemstoolkit.version : fail
Test python3 rtemstoolkit.version : fail
Test failures
```

#### Comment 1

1. **Chris Johns**, Mon, 28 Aug 2023 04:55:22 GMT
2. **status**: changed from **new** to **closed**
3. **resolution**: set to **wontfix**
4. **summary**: changed from **rtems-tools unit tests fail on FreeBSD** to **rtems-tools fail on FreeBSD to get number of cores**

The unit tests pass. I had a typo in a change I was testing. I have changed the ticket to track the original problem:

```
$ python -m rtemstoolkit.host
Python's OS name: posix
Name      : freebsd
Windows   : No
]]]] ['/sbin/sysctl', 'hw.ncpu']
***** 1 usage: sysctl [-bdehlnooqtTwx] [ -B ] [-f filename] name[=value] ...
        sysctl [-bdehlnooqtTwx] [ -B ] -a
```

The execute command is failing.

#### Comment 2

1. **Chris Johns**, Mon, 28 Aug 2023 04:55:42 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution**: **wontfix** deleted

#### Comment 3

1. **Chris Johns**, Tue, 29 Aug 2023 01:20:30 GMT
2. **owner**: set to **Chris Johns <chrisj@...>**
3. **status**: changed from **reopened** to **closed**
4. **resolution**: set to **fixed**

In 3ea0c24/rtems-tools:

```
rtemstoolkit: Fix shell execution
```

The fixes to parse the command along with the pipe options broke a simple shell command such as '/sbin/sysctl hw.ncpu' on FreeBSD. This patch fixes the shell command by passing a string for the various options.

The unit test has been updated to catch errors and report them.

Closes #4951

#### Comment 4

1. **Chris Johns**, Tue, 29 Aug 2023 03:50:08 GMT

In 9ca9576/rtems-source-builder:

```
rtems/tools: Shell execute fixes
```

Updates #4951

#### Comment 5

1. **Chris Johns**, Sun, 03 Sep 2023 05:27:49 GMT

In 35c7320/rtems-source-builder:

```
rtems/tools: Execute use of shlex.join fix for python < 3.8
```

Updates #4951

---

## 4953 - Use of symbol addresses for arbitrary values may not work for some code models

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4953">https://devel.rtems.org/ticket/4953</a> ( <a href="https://devel.rtems.org/ticket/4953">https://devel.rtems.org/ticket/4953</a> )
<b>Id</b>	4953
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	12 September 2023 13:48:38
<b>Modified</b>	24 November 2023 07:15:12
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	score
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

## Description

The `_ISR_Stack_size` is defined by the application configuration like this:

```

/**
 * @ingroup RTEMSAPIBaseDefs
 *
 * @brief Defines a global symbol with the name and value.
 *
 * @param _name is the user defined name of the symbol. The name shall be a
 * valid designator. On the name a macro expansion is performed and
 * afterwards it is stringified.
 *
 * @param _value is the value of the symbol. On the value a macro expansion is
 * performed and afterwards it is stringified. It shall expand to an integer
 * expression understood by the assembler.
 *
 * This macro shall be placed at file scope.
 */
#if defined( USER_LABEL_PREFIX )
#define RTEMS_DEFINE_GLOBAL_SYMBOL( _name, _value ) \
    asm( \
        "\t.globl " RTEMS_XSTRING( RTEMS_SYMBOL_NAME( _name ) ) \
        "\n\t.set " RTEMS_XSTRING( RTEMS_SYMBOL_NAME( _name ) ) \
        ", " RTEMS_STRING( _value ) "\n" \
    )
#else
#define RTEMS_DEFINE_GLOBAL_SYMBOL( _name, _value )
#endif
RTEMS_DEFINE_GLOBAL_SYMBOL(
    _ISR_Stack_size,
    CONFIGURE_INTERRUPT_STACK_SIZE
);

```

Firstly, the `RTEMS_DEFINE_GLOBAL_SYMBOL()` is broken. It should depend on `GNUC` and not `USER_LABEL_PREFIX`.

Secondly, setting a symbol to an arbitrary absolute address may not work with all code models, see:

<https://sourceware.org/pipermail/binutils/2023-September/129448.html>

The `_ISR_Stack_size` should be changed to point to the end of the ISR stack of processor 0:

```

RTEMS_DEFINE_GLOBAL_SYMBOL(
    _ISR_Stack_0_end,
    RTEMS_SYMBOL_NAME( _ISR_Stack_area_begin )
    + CONFIGURE_INTERRUPT_STACK_SIZE
);

```

The tests for `RTEMS_DEFINE_GLOBAL_SYMBOL()` should be changed to use values relative to another symbol.

## Comment 1

1. **Sebastian Huber**, Wed, 13 Sep 2023 05:28:52 GMT

In 0add2d2/rtems:

```

score: Fix RTEMS_DEFINE_GLOBAL_SYMBOL()

The availability of a proper RTEMS_DEFINE_GLOBAL_SYMBOL() implementation depends on asm() and thus GNUC.

Clarify documentation.

Update #4953.

```

## Comment 2

1. **Sebastian Huber**, Wed, 13 Sep 2023 05:28:54 GMT

In d7a6e80/rtems:

```

tests: Improve RTEMS_DEFINE_GLOBAL_SYMBOL() tests

Use a symbol value relative to an existing symbol address to make the test work on more code models.

Update #4953.

```

**Comment 3**

1. **Sebastian Huber**, Wed, 13 Sep 2023 05:44:16 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

Since the start files are written in assembly, they can use the right instructions to load an arbitrary absolute address. A review of the uses of `_ISR_Stack_size` showed that there is actually no issue right now. Adjusting the tests for `RTEMS_DEFINE_GLOBAL_SYMBOL()` should be enough.

**Comment 4**

1. **Sebastian Huber**, Wed, 13 Sep 2023 08:52:29 GMT
2. **status**: changed from **closed** to **reopened**
3. **resolution**: **fixed** deleted

The `spconfig01` test fails on aarch64 with:

```
testsuites/sptestes/spconfig01/init.c: 89 rtems configuration get_interrupt_stack_size() == CPU STACK MINIMUM SIZE
```

The `rtems_configuration_get_interrupt_stack_size()` needs to be fixed.

**Comment 5**

1. **Sebastian Huber**, Wed, 13 Sep 2023 08:57:43 GMT
2. **summary**: changed from `__Definition of _ISR_Stack_size may not work for some code models` to **Use of symbol addresses for arbitrary values may not work for some code models**

The use of `_TLS_BSS_size` and `_TLS_Data_begin` may also not work on some code models. I really wonder why the TLS related tests pass on aarch64.

**Comment 6**

1. **Sebastian Huber**, Wed, 13 Sep 2023 09:02:33 GMT

There are also issues with `_TLS_Size` and `_TLS_Alignment`.

**Comment 7**

1. **Sebastian Huber**, Thu, 14 Sep 2023 12:01:15 GMT

In 5f8415b/rtems:

```
validation: Add RTEMS_DEFINE_GLOBAL_SYMBOL() test
Update #4953.
```

**Comment 8**

1. **Sebastian Huber**, Mon, 18 Sep 2023 05:24:10 GMT

In 206bbeb/rtems:

```
score: Fix TLS support for some code models

Store symbols with an arbitrary absolute address such as _TLS_Size, _TLS_Alignment, _TLS_Data_size, and _TLS_BSS_size in an object to
avoid issues with some code models.

Update #4953.
```

**Comment 9**

1. **Sebastian Huber**, Mon, 18 Sep 2023 05:24:12 GMT

In 2111497/rtems:

```
rtems: rtems_configuration_get_interrupt_stack_size()

Fix rtems_configuration_get_interrupt_stack_size() for some code models.

The _ISR_Stack_size symbol has an arbitrary absolute address and may not be representable in the code model used by the compiler.

Update #4953.
```

**Comment 10**

1. **Sebastian Huber**, Fri, 24 Nov 2023 07:15:12 GMT
2. **status**: changed from **reopened** to **closed**

3. **resolution:** set to **fixed**

## **4954 - sparc: Simplify the clock driver and CPU counter support**

---

<b>Link Id</b>	<a href="https://devel.rtems.org/ticket/4954">https://devel.rtems.org/ticket/4954</a> ( <a href="https://devel.rtems.org/ticket/4954">https://devel.rtems.org/ticket/4954</a> )
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 September 2023 08:39:53
<b>Modified</b>	20 October 2023 12:50:44
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### **Description**

Unfortunately, most SPARC SoCs? supported by RTEMS lack a proper free-running counter. The only exception are the GR712RC and the GR740. For the pre-qualified GR712RC BSP, the current implementation is too complicated. Make the fall back to a free-running GPTIMER mandatory for the leon3 BSP family to simplify things. For the GR712RC use the DSU time tag counter.

### **Comment 1**

1. **Sebastian Huber**, Fri, 15 Sep 2023 16:02:59 GMT
2. **description:** modified (diff)

### **Comment 2**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:45 GMT

In 8fe0fc4/rtems:

```
bsps/leon3: Optional IRQ(A)MP timestamp support
This is necessary to run the tests on SIS with profiling enabled.
Update #4954.
```

### **Comment 3**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:47 GMT

In b6dc4b4/rtems:

```
sparc: Move CPU counter implementation
Enable a BSP-specific CPU counter implementation.
Update #4954.
```

### **Comment 4**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:49 GMT

In 3f03a6d/rtems:

```
bsps/leon3: Make GPTIMER fall back mandatory
Using the auto reload counter which generates the clock ticks for the timecounter or CPU counter is quite difficult and only works in uniprocessor configurations.
Update #4954.
```

### **Comment 5**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:51 GMT

In ff533cec/rtems:



bsps/leon3: Simplify clock and CPU counter

Share the timecounter instance between the clock and the CPU counter. This greatly simplifies the clock driver since we have to do the device selection only in one place, the CPU counter support.

Update #4954.

#### **Comment 6**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:53 GMT

In abb2f8b/rtems:

bsps/leon3: Use custom CPU counter implementation

Merge the timecounter and CPU counter support for the leon3 BSP family. Remove now unused functions from the CPU counter support of the erc32 and leon3 BSPs.

Update #4954.

#### **Comment 7**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:55 GMT

In 8266a8a3/rtems:

bsps/leon3: Move code blocks

Move code blocks to simplify C preprocessor usage.

Update #4954.

#### **Comment 8**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:57 GMT

In ffa29bac/rtems:

bsps/leon3: Statically initialize get timecount

Update #4954.

#### **Comment 9**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:56:59 GMT

In 601b84c7/rtems:

bsps/leon3: leon3\_counter\_use\_irqamp\_timestamp()

Simplify leon3\_counter\_use\_irqamp\_timestamp().

Update #4954.

#### **Comment 10**

1. **Sebastian Huber**, Fri, 20 Oct 2023 08:57:01 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 958d517/rtems:

bsps/leon3: Use DSU time tag for GR712RC

Close #4954.

#### **Comment 11**

1. **Sebastian Huber**, Fri, 20 Oct 2023 12:50:44 GMT

In 36b935f1/rtems:

sparc: Fix move of CPU counter implementation

This fixes a build error with RTEMS\_PROFILING enabled.

**4955 - sparc: Potential stack corruption in uniprocessor configurations during start multitasking**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4955">https://devel.rtems.org/ticket/4955</a> ( <a href="https://devel.rtems.org/ticket/4955">https://devel.rtems.org/ticket/4955</a> )
<b>Id</b>	4955
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	20 September 2023 06:54:57
<b>Modified</b>	12 October 2023 14:07:59
<b>Owner</b>	Sebastian Huber
<b>Type</b>	defect
<b>Component</b>	arch/sparc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	critical
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The system initialization uses the interrupt stack. A first level interrupt shall never interrupt a context which uses the interrupt stack. Such a use would lead to stack corruption and undefined system behaviour. Unfortunately, in uniprocessor configurations this is the case right now. Multiprocessing is started using `_CPU_Context_restore()`. The caller of this function (`_Thread_Start_multitasking()`) uses the interrupt stack. Later we have in `cpukit/score/cpu/sparc/cpu_asm.S`:

```

mov    %g1, %psr                ! restore status register and
                                ! **** ENABLE TRAPS ****
ld     [%o1 + G5_OFFSET], %g5    ! restore the global registers
ld     [%o1 + G7_OFFSET], %g7
! Load thread specific ISR dispatch prevention flag
ld     [%o1 + ISR_DISPATCH_DISABLE_STACK_OFFSET], %o2
! Store it to memory later to use the cycles
ldd    [%o1 + L0_OFFSET], %i0    ! restore the local registers
ldd    [%o1 + L2_OFFSET], %i2
ldd    [%o1 + L4_OFFSET], %i4
ldd    [%o1 + L6_OFFSET], %i6
! Now restore thread specific ISR dispatch prevention flag
st     %o2, [%g6 + PER_CPU_ISR_DISPATCH_DISABLE]
ldd    [%o1 + I0_OFFSET], %i0    ! restore the input registers
ldd    [%o1 + I2_OFFSET], %i2
ldd    [%o1 + I4_OFFSET], %i4
ldd    [%o1 + I6_FP_OFFSET], %i6
ldd    [%o1 + O6_SP_OFFSET], %o6 ! restore the output registers

```

Between the `ENABLE TRAPS` and the restore of the output registers, we still use the stack of the caller and interrupts may be enabled. If an interrupt happens in this code block, the interrupt stack is concurrently used which may lead to a crash.

**Comment 1**

1. **Sebastian Huber**, Tue, 26 Sep 2023 05:50:21 GMT

In a9862623/rtems:

```

validation: Check stack of interrupted context

Check the stack of the interrupted context during the multitasking start.

Update #4955.

```

**Comment 2**

1. **Sebastian Huber**, Thu, 12 Oct 2023 11:53:39 GMT

2. **status**: changed from **assigned** to **closed**

3. **resolution**: set to **fixed**

In 1c36971d/rtems:

```

sparc: Fix stack corruption

Fix a potential stack corruption in uniprocessor configurations during start multitasking.

```

The system initialization uses the interrupt stack. A first level interrupt shall never interrupt a context which uses the interrupt stack. Such a use would lead to stack corruption and undefined system behaviour. Unfortunately, in uniprocessor configurations this was the case. Multiprocessing is started using `_CPU_Context_restore()`. The caller of this function (`_Thread_Start_multitasking()`) uses the interrupt stack. Later we have in `cpukit/score/Cpu/sparc/cpu_asm.S`:

```

mov    %g1, %psr                ! restore status register and
                                ! ____ ENABLE TRAPS ____

```

```
ld [%o1 + G5_OFFSET], %g5 ! restore the global registers ld [%o1 + G7_OFFSET], %g7
```

```
! Load thread specific ISR dispatch prevention flag ld [%o1 + ISR_DISPATCH_DISABLE_STACK_OFFSET], %o2 ! Store it to memory later to use the cycles
```

```
ldd [%o1 + L0_OFFSET], %l0 ! restore the local registers ldd [%o1 + L2_OFFSET], %l2 ldd [%o1 + L4_OFFSET], %l4
ldd [%o1 + L6_OFFSET], %l6
```

```
! Now restore thread specific ISR dispatch prevention flag st %o2, [%g6 + PER_CPU_ISR_DISPATCH_DISABLE]
```

```
ldd [%o1 + I0_OFFSET], %i0 ! restore the input registers ldd [%o1 + I2_OFFSET], %i2 ldd [%o1 + I4_OFFSET], %i4
ldd [%o1 + I6_FP_OFFSET], %i6
```

```
ldd [%o1 + O6_SP_OFFSET], %o6 ! restore the output registers
```

Between the ENABLE TRAPS and the restore of the output registers, we still use the stack of the caller and interrupts may be enabled. If an interrupt happens in this code block, the interrupt stack is concurrently used which may lead to a crash.

Fix this by adding a new function `_SPARC_Start_multiprocessing()` for uniprocessor configurations. This function first sets the stack pointer to use the stack of the heir thread.

Close #4955.

### Comment 3

1. **Sebastian Huber**, Thu, 12 Oct 2023 14:07:59 GMT

In 43b74b14/rtems:

validation: Support powerpc in test case

Update #4955.

## 4956 - Deadlock caused by locking inversion in JFFS2

**Link** <https://devel.rtems.org/ticket/4956> (<https://devel.rtems.org/ticket/4956>)

**Id** 4956

**Reporter** Kinsey Moore

**Created** 20 September 2023 16:58:43

**Modified** 16 February 2024 00:35:11

**Owner** Kinsey Moore

**Type** defect

**Component** admin

**Status** assigned

**Resolution**

**Version**

**Milestone** 6.1

**Priority** normal

**Severity** normal

**Keywords**

**Cc**

**Blocking**

**Blocked by**

### Description

When the code for delayed writes was added to support JFFS2 on NAND, it introduced a possible locking inversion when managing the delayed write work queue.

This has been partially addressed by fa85760c99a72b8186c70c896b98efe0d7cde2b6, but there are other issues with this code that need to be addressed as well.

First is that when not compiling with RTEMS\_DEBUG, nodes are not automatically set as off the chain upon extraction and this behavior is depended upon.

Second is that protected (ISR-locked) chain calls are used when they are not necessary due to already being locked.

Third is that the bug fixed by the referenced commit needs a test that verifies the fix.

### Comment 1

1. **z.ling111**, Tue, 26 Sep 2023 00:41:07 GMT

Hey i'm interested working on this ticket would the nodes be set off only if

```
#if defined(RTEMS_DEBUG) is true? I can't find other functions that call this so i can't confirm. I think i'm going to try to work on the first part.
```

**Comment 2**

1. **Kinsey Moore**, Tue, 26 Sep 2023 13:16:46 GMT

Hey, thanks for the interest. I actually have a patch on the mailing list that just got approved for fixing this, so it should be going into the codebase shortly. I still need to write a test that produces the original issue, though.

**Comment 3**

1. **Kinsey Moore**, Tue, 26 Sep 2023 13:38:00 GMT

In 99c637f/rtems:

```
cpukit/jffs2: Avoid use of off-chain semantics
```

This reworks the JFFS2 delayed work queue to avoid use of on-chain/off-chain semantics since they vary in behavior under RTEMS\_DEBUG and are not guaranteed to be safe to use in SMP systems. This adds all delayed work structs to the chain on FS init and does not remove them until unmount.

Updates #4956

**Comment 4**

1. **Kinsey Moore**, Fri, 16 Feb 2024 00:35:11 GMT
2. **owner:** set to **Kinsey Moore**
3. **status:** changed from **new** to **assigned**

**4957 - spstdc17 warnings building i386/pc686**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4957">https://devel.rtems.org/ticket/4957</a> ( <a href="https://devel.rtems.org/ticket/4957">https://devel.rtems.org/ticket/4957</a> )
<b>Id</b>	4957
<b>Reporter</b>	Chris Johns
<b>Created</b>	4 October 2023 01:49:08
<b>Modified</b>	18 October 2023 05:17:50
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This test has these warnings:

```
[4070/4522] Compiling testsuites/sptests/spstdc17/init.c
In file included from ../../../../cpukit/include/rtems/rtems/intr.h:73,
                 from ../../../../cpukit/include/rtems.h:69,
                 from ../../../../testsuites/sptests/spstdc17/init.c:32:
../../../../cpukit/include/rtems/score/isrlock.h:72:9: warning: struct has no members [-Wpedantic]
   72 | typedef struct {
      |         ^~~~~~
In file included from ../../../../cpukit/include/rtems/scheduler.h:40,
                 from ../../../../cpukit/include/rtems/confdefs/scheduler.h:65,
                 from ../../../../cpukit/include/rtems/confdefs/threads.h:49,
                 from ../../../../cpukit/include/rtems/confdefs/inittask.h:56,
                 from ../../../../cpukit/include/rtems/confdefs.h:68,
                 from ../../../../testsuites/sptests/spstdc17/init.c:57:
../../../../cpukit/include/rtems/score/scheduler.h:318:16: warning: struct has no members [-Wpedantic]
  318 | typedef struct Scheduler_Context {
      |         ^~~~~~~~~~~~~~~~~~~~~~
```

**Comment 1**

1. **Chris Johns**, Wed, 04 Oct 2023 01:50:08 GMT
2. **owner:** **joel@...** deleted
3. **status:** changed from **new** to **assigned**

**Comment 2**

1. **z.ling111**, Tue, 17 Oct 2023 00:30:19 GMT

deleted comment

**Comment 3**

1. **z.ling111**, Wed, 18 Oct 2023 01:42:13 GMT

Does removing the precompiler defines affect how gcc sees struts? right now i removed the defines to fix this issue

```
typedef struct {
```

```
SMP_lock_Control Lock;
```

```
} ISR_lock_Control;
```

for example removing the #defines gives me this compiler error? do you have any suggestions?

```
../../../../cpukit/include/rtems/score/isrlock.h:73:3: error: unknown type name 'SMP_lock_Control'
```

```
73 | SMP_lock_Control Lock;
```

```
|~
```

smplock.h is defined above

**Comment 4**

1. **Joel Sherrill**, Wed, 18 Oct 2023 02:44:14 GMT

It has a single field which is smp specific. When built for uniprocessor, the structure ends up with no fields which is the problem. I am guessing that all code that uses this should be smp only and the structure not present.

**Comment 5**

1. **Sebastian Huber**, Wed, 18 Oct 2023 05:17:50 GMT

Through typedefs this structure is part of the API. We could add a dummy member to the API visible structure for uniprocessor configurations if we really want to fix warnings like this. Internally, we need more #ifdefs to avoid using the lock control.

**4959 - rtems-test tftp does not a session timeout**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4959">https://devel.rtems.org/ticket/4959</a> ( <a href="https://devel.rtems.org/ticket/4959">https://devel.rtems.org/ticket/4959</a> )
<b>Id</b>	4959
<b>Reporter</b>	Chris Johns
<b>Created</b>	5 October 2023 05:23:48
<b>Modified</b>	18 December 2023 05:30:16
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The TFTP server has a timeout for session that are running however there is no timeout on the listen state. A target could fail to create a session. Add a session timeout.

**Comment 1**

1. **Chris Johns**, Tue, 07 Nov 2023 21:07:44 GMT

2. **status:** changed from **assigned** to **closed**

3. **resolution:** set to **fixed**

In a22b396/rtems-tools:

```
tester/tftp: Add a session timeout
Fix listener done state Finish open with the state as finished
Closes #4959
```

**Comment 2**

1. **Chris Johns**, Mon, 18 Dec 2023 05:30:16 GMT

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

In 384acf1/rtems-tools:

```
tester/console: Fix restart regx check
```

The fix to the TFTP timeout has a simple bug.

Updates #4959

## 4960 - User manual test documentation update

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4960">https://devel.rtems.org/ticket/4960</a> ( <a href="https://devel.rtems.org/ticket/4960">https://devel.rtems.org/ticket/4960</a> )
<b>Id</b>	4960
<b>Reporter</b>	Chris Johns
<b>Created</b>	7 October 2023 04:04:07
<b>Modified</b>	7 October 2023 04:04:07
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The Testing chapter of the User Manual needs to be update for RTEMS 6.

## 4961 - Document and test CONFIGURE\_JFFS2\_DELAYED\_WRITE\_TASK\_PRIORITY

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4961">https://devel.rtems.org/ticket/4961</a> ( <a href="https://devel.rtems.org/ticket/4961">https://devel.rtems.org/ticket/4961</a> )
<b>Id</b>	4961
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	11 October 2023 05:18:58
<b>Modified</b>	16 February 2024 00:35:28
<b>Owner</b>	Kinsey Moore
<b>Type</b>	defect
<b>Component</b>	fs/jffs2
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

The CONFIGURE\_JFFS2\_DELAYED\_WRITE\_TASK\_PRIORITY application configuration option should be documented according to:

<https://docs.rtems.org/branches/master/eng/req/howto.html#application-configuration-options>

There should be a test program for this option.

### Comment 1

1. **Sebastian Huber**, Tue, 31 Oct 2023 11:53:58 GMT
2. **keywords: qualification** added

### Comment 2

1. **Sebastian Huber**, Tue, 19 Dec 2023 07:01:26 GMT

In a901ca3/rtems:

```
doxygen: CONFIGURE_JFFS2_DELAYED_WRITE_TASK_PRIORITY
```

```
Document CONFIGURE_JFFS2_DELAYED_WRITE_TASK_PRIORITY.
```

**Comment 3**

1. **Sebastian Huber**, Tue, 19 Dec 2023 07:27:49 GMT

In ddf2b03/rtems-docs:

```
c-user: CONFIGURE_JFFS2_DELAYED_WRITE_TASK_PRIORITY
Document CONFIGURE_JFFS2_DELAYED_WRITE_TASK_PRIORITY.
Update #4961.
```

**Comment 4**

1. **Kinsey Moore**, Tue, 19 Dec 2023 07:28:57 GMT

In 8bfd9ce/rtems-central:

```
spec: Add JFFS2 delayed write task priority
This adds the configuration option used to select the JFFS2 delayed write task priority to be used when operating on NAND flash.
Updates #4961
```

**Comment 5**

1. **Kinsey Moore**, Fri, 16 Feb 2024 00:35:28 GMT
2. **owner**: set to **Kinsey Moore**
3. **status**: changed from **new** to **assigned**

**4962 - MicroBlaze BSPs modify carry flag before MSR is saved**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4962">https://devel.rtems.org/ticket/4962</a> ( <a href="https://devel.rtems.org/ticket/4962">https://devel.rtems.org/ticket/4962</a> )
<b>Id</b>	4962
<b>Reporter</b>	Alex White
<b>Created</b>	23 October 2023 14:09:39
<b>Modified</b>	23 October 2023 18:49:22
<b>Owner</b>	Alex White
<b>Type</b>	defect
<b>Component</b>	bsps
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The interrupt handler for the MicroBlaze? BSPs defined in bsp/microblaze/microblaze\_fpga/start/\_interrupt\_handler.S saves one register to the stack, R5, before jumping to the architecture \_ISR\_Handler. This is because R5 is used to pass the interrupt source if it is known. To indicate an unknown interrupt source, it uses the following instruction:

```
addi r5, r0, 0xFF
```

The addi instruction modifies the carry flag in MSR. This is a problem because MSR has not been saved to the stack yet. It is saved in \_ISR\_Handler.

This went unnoticed because it manifests itself in subtle ways. It requires that an interrupt happen somewhere between an instruction that modifies the carry flag and an instruction that uses the modified carry flag.

To resolve this issue, the entire interrupt frame should be saved as the first step of \_interrupt\_handler rather than in \_ISR\_Handler. It should also be made very clear that saving the stack frame is handled by the BSP rather than the architecture-specific \_ISR\_Handler.

**Comment 1**

1. **Alex White**, Mon, 23 Oct 2023 18:49:22 GMT
2. **owner**: set to **Alex White**
3. **status**: changed from **new** to **assigned**

**4967 - strtouf leaks memory**

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4967">https://devel.rtems.org/ticket/4967</a> ( <a href="https://devel.rtems.org/ticket/4967">https://devel.rtems.org/ticket/4967</a> )
<b>Id</b>	4967
<b>Reporter</b>	Chris Johns
<b>Created</b>	15 November 2023 04:07:59
<b>Modified</b>	16 February 2024 01:01:37
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool/newlib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

The libc call strtrof leaks memory when a thread exits if strtrof has been made within the context of the thread. The code uses Balloc and Bfree to obtain pieces of memory it uses. The memory is recycled using newlib reent TLS variables. The `_reclaim_reent()` does not clean up `_REENT_MP_P5S`.

**Attachments:**

- 
- Chris Johns, Wed, 15 Nov 2023 04:08:39 GMT**  
attach: set to [libc-strtof-init.c](https://devel.rtems.org/ticket/4967/libc-strtof-init.c) (<https://devel.rtems.org/ticket/4967/libc-strtof-init.c>)
  - Chris Johns, Wed, 15 Nov 2023 04:32:48 GMT**  
attach: set to [0001-Reclaim-REENT\\_MP\\_P5S-in-reclaim\\_reent.patch](https://devel.rtems.org/ticket/4967/0001-Reclaim-REENT_MP_P5S-in-reclaim_reent.patch) ([https://devel.rtems.org/ticket/4967/0001-Reclaim-REENT\\_MP\\_P5S-in-reclaim\\_reent.patch](https://devel.rtems.org/ticket/4967/0001-Reclaim-REENT_MP_P5S-in-reclaim_reent.patch))
- 

**Comment 1**

- Sebastian Huber, Wed, 22 Nov 2023 06:12:50 GMT**

In 07be298/rtems-source-builder:

6/7: Update Newlib

Pick up fixes for ARM/optimized-routines and the memory reclamation at thread exit.

Update #4510. Update #4967.

**Comment 2**

- Chris Johns, Fri, 16 Feb 2024 01:01:37 GMT**
  - status:** changed from **new** to **closed**
  - resolution:** set to **fixed**
- 

**4968 - Python 3.12 fix escape sequences and remove SafeConfigParser**


---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4968">https://devel.rtems.org/ticket/4968</a> ( <a href="https://devel.rtems.org/ticket/4968">https://devel.rtems.org/ticket/4968</a> )
<b>Id</b>	4968
<b>Reporter</b>	Chris Johns
<b>Created</b>	20 November 2023 22:12:42
<b>Modified</b>	22 November 2023 20:59:58
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

**Description**

This breaks version.py in:

- rtems-tools
- rtems-docs



- rtems\_waf

Also update any escape sequences that are not correctly escaped or are a regx expressions (prefix with r).

### Comment 1

1. **Chris Johns**, Tue, 21 Nov 2023 20:47:51 GMT

In 63396e2/rtems-source-builder:

```
sb: Fix Python 3.12 safeConfigParser and invalid escape sequences
Updates #4968
```

### Comment 2

1. **Chris Johns**, Tue, 21 Nov 2023 21:29:36 GMT

In 75ffa67/rtems-tools:

```
python: Updates for Python 3.12
Change SafeConfigParser? to ConfigParser? Fix escape sequences in strings
Updates #4968
```

### Comment 3

1. **Chris Johns**, Wed, 22 Nov 2023 02:52:25 GMT
2. **summary:** changed from **Python 3.12 does not have SafeConfigParser** to **Python 3.12 fix escape sequences and remove SafeConfigParser**

### Comment 4

1. **Chris Johns**, Wed, 22 Nov 2023 20:59:58 GMT

In 72c11fa/rtems:

```
waf: Fix Python 3.12 escape sequences
Updates #4968
```

## 4969 - Update libibery sources in rtems-tools

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4969">https://devel.rtems.org/ticket/4969</a> ( <a href="https://devel.rtems.org/ticket/4969">https://devel.rtems.org/ticket/4969</a> )
<b>Id</b>	4969
<b>Reporter</b>	Chris Johns
<b>Created</b>	21 November 2023 04:56:37
<b>Modified</b>	23 November 2023 22:36:13
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### **Description**

MacOS is removing vfork. Update to gcc latest sources and use POSIX spawn support.  
Update all files.

### Comment 1

1. **Chris Johns**, Tue, 21 Nov 2023 21:29:38 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In a4b312e/rtems-tools:

rtemstoolkit/libierty: Update to gcc latest  
 Use POSIX spawn support for MacOS  
 Closes #4969

### Comment 2

1. **Chris Johns**, Thu, 23 Nov 2023 22:36:13 GMT

In b7bb493/rtems-source-builder:

rtems/rtems-tools: Update with C++17 and Python 3.12 fixes  
 Updates #4969 Updates #4970

---

## 4970 - Fix C++ 17 deprecated functionality in rtems-tools

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4970">https://devel.rtems.org/ticket/4970</a> ( <a href="https://devel.rtems.org/ticket/4970">https://devel.rtems.org/ticket/4970</a> )
<b>Id</b>	4970
<b>Reporter</b>	Chris Johns
<b>Created</b>	22 November 2023 00:54:22
<b>Modified</b>	23 November 2023 22:36:13
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The C++ code uses functionality deprecated in c++17. Update and resolve.

### Comment 1

1. **Chris Johns**, Wed, 22 Nov 2023 00:56:42 GMT
2. **summary:** changed from **Fix C++ 17 depreciated funtionalty** to **Fix C++ 17 depreciated funtionalty in rtrems-tools**

Add the repo to the subject

### Comment 2

1. **Chris Johns**, Wed, 22 Nov 2023 21:01:55 GMT

In 00af5a6/rtems-tools:

rtemstoolkit: Update SimpleIni? to latest  
 The resolves C++17 warnings.  
 Updates #4970

### Comment 3

1. **Chris Johns**, Wed, 22 Nov 2023 21:01:56 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In f408c0f/rtems-tools:

rtemstoolkit, linkers: Fix C++17 warnings  
 Closes #4970

### Comment 4

1. **Joel Sherrill**, Thu, 23 Nov 2023 16:11:17 GMT

2. **summary:** changed from **Fix C++ 17 deprecated funtionality in rtems-tools** to **Fix C++ 17 deprecated functionality in rtems-tools**

Fix spelling in title

#### Comment 5

1. **Chris Johns**, Thu, 23 Nov 2023 22:36:13 GMT

In b7bb493/rtems-source-builder:

```
rtems/rtems-tools: Update with C++17 and Python 3.12 fixes
Updates #4969 Updates #4970
```

## 4971 - Report that nested validation test cases did run

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4971">https://devel.rtems.org/ticket/4971</a> ( <a href="https://devel.rtems.org/ticket/4971">https://devel.rtems.org/ticket/4971</a> )
<b>Id</b>	4971
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	22 November 2023 13:50:41
<b>Modified</b>	28 November 2023 13:03:40
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	test
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	qualification
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

Some validation test cases use parameterized nested test cases. For example, the `rtems_semaphore_obtain()` test uses a parameterized test case to seize a mutex. The nested mutex seize test case uses a parameterized thread queue enqueue test case. Currently, there is no indication that these nested test cases did actually run. Some of these nested test cases run in a tight loop, so printing a hint on every run could lead to a massive amount of test output.

Add test case remarks to the RTEMS Test Framework which may be used to give such an indication.

#### Comment 1

1. **Sebastian Huber**, Tue, 28 Nov 2023 13:03:37 GMT

In d586b3c/rtems:

```
libtest: Add T_add_remark()
This can be used to report that nested test cases did run in a test case.
Update #4971.
```

#### Comment 2

1. **Sebastian Huber**, Tue, 28 Nov 2023 13:03:40 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 528f0e1/rtems:

```
validation: Add nested test case remarks
Close #4971.
```

## 4973 - Add RSB options to control a specific python

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4973">https://devel.rtems.org/ticket/4973</a> ( <a href="https://devel.rtems.org/ticket/4973">https://devel.rtems.org/ticket/4973</a> )
<b>Id</b>	4973
<b>Reporter</b>	Chris Johns
<b>Created</b>	29 November 2023 03:18:18
<b>Modified</b>	6 December 2023 21:50:45
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

Older hosts can have varying installations of pythons. Provide a means to set a version found in your path with:

- --with-python2
- --with-python3
- --with-python-version

#### Comment 1

1. **Chris Johns**, Wed, 06 Dec 2023 21:50:45 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In a970057/rtems-source-builder:

```
gdb: Add options to control the python version
```

The options are:

```
--with-python2 --with-python3 --with-python-version
```

Closes #4973

## 4974 - rtems-tools buid failed with '--host=x86\_64-w64-mingw32'

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4974">https://devel.rtems.org/ticket/4974</a> ( <a href="https://devel.rtems.org/ticket/4974">https://devel.rtems.org/ticket/4974</a> )
<b>Id</b>	4974
<b>Reporter</b>	zhengxiaojun
<b>Created</b>	30 November 2023 06:30:04
<b>Modified</b>	30 November 2023 06:33:40
<b>Owner</b>	
<b>Type</b>	defect
<b>Component</b>	tool
<b>Status</b>	new
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

rtems-tools build failed with "--host=x86\_64-w64-mingw32" after the commit <https://git.rtems.org/rtems-tools/commit/?id=a4b312ee4f3d8c93ab0d45d568879069e7ac7d7a> 'writeargv' is undefined. add libierty/argv.c will solve this problem.

#### Attachments:

1. **zhengxiaojun**, Thu, 30 Nov 2023 06:31:44 GMT  
**attach:** set to [0001-add-libierty-argv.c-for-mingw32-build.patch](https://devel.rtems.org/ticket/4974/0001-add-libierty-argv.c-for-mingw32-build.patch) (<https://devel.rtems.org/ticket/4974/0001-add-libierty-argv.c-for-mingw32-build.patch>)

#### Comment 1

1. **zhengxiaojun**, Thu, 30 Nov 2023 06:33:40 GMT

argv.c file of patch is from gcc13.2

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

## 4975 - Terminal row/col probe timeout too fast

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4975">https://devel.rtems.org/ticket/4975</a> ( <a href="https://devel.rtems.org/ticket/4975">https://devel.rtems.org/ticket/4975</a> )
<b>Id</b>	4975
<b>Reporter</b>	Chris Johns
<b>Created</b>	5 December 2023 02:33:10
<b>Modified</b>	13 December 2023 20:22:30
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The timeout is too fast if the terminal and the target hardware are on different continents.

### Comment 1

1. **Chris Johns**, Wed, 13 Dec 2023 20:22:30 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 7260887/rtems:

```
libmisc/shell: Work around tmux bug in row and column
Extend the timeout to 150 msec for long remote sessions Improve the performance of the detection
Closes #4975 Closes #4977
```

---

## 4977 - tmux bug swaps lines and columns

---

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4977">https://devel.rtems.org/ticket/4977</a> ( <a href="https://devel.rtems.org/ticket/4977">https://devel.rtems.org/ticket/4977</a> )
<b>Id</b>	4977
<b>Reporter</b>	Chris Johns
<b>Created</b>	11 December 2023 06:11:30
<b>Modified</b>	13 December 2023 20:22:30
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	lib
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

A tmux bug which is fixed but not released swaps the columns and rows fields:

<https://github.com/tmux/tmux/issues/3457>

Given it will be a while before this enters downstream packages provide a work around.

also improve response time to the query. At the moment a 50 msec delay is imposed and it does not have to be there.

### Comment 1

1. **Chris Johns**, Wed, 13 Dec 2023 20:22:30 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **fixed**

In 7260887/rtems:

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

libmisc/shell: Work around tmux bug in row and column  
 Extend the timeout to 150 msec for long remote sessions Improve the performance of the detection  
 Closes #4975 Closes #4977

## 4980 - Build documentation using sphinx 7.2

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4980">https://devel.rtems.org/ticket/4980</a> ( <a href="https://devel.rtems.org/ticket/4980">https://devel.rtems.org/ticket/4980</a> )
<b>Id</b>	4980
<b>Reporter</b>	Chris Johns
<b>Created</b>	19 December 2023 00:29:30
<b>Modified</b>	19 December 2023 20:41:50
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	doc
<b>Status</b>	closed
<b>Resolution</b>	fixed
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

- Set no max version
- Fix the layout to support versions later than 5.9

I have no idea when the breakage happened and if other versions are effected.

### Comment 1

1. **Chris Johns**, Tue, 19 Dec 2023 01:02:27 GMT

I have tested a patch with versions:

sphinx sphinxcontrib.bibtex 7.2 2.6.1 6.1.3 2.4.2 5.3.0 2.4.2

### Comment 2

1. **Chris Johns**, Tue, 19 Dec 2023 20:41:50 GMT
2. **status**: changed from **assigned** to **closed**
3. **resolution**: set to **fixed**

In e31a0b2/rtems-docs:

```
sphinx/style: Fix building with the latest sphinx
```

```
Tested on sphinx 7.2, 6.1.3 AND 5.3.0
```

```
Closes #4980
```

## 4982 - Add support for TMS570LC4357 for the arm/tms570 BSP

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4982">https://devel.rtems.org/ticket/4982</a> ( <a href="https://devel.rtems.org/ticket/4982">https://devel.rtems.org/ticket/4982</a> )
<b>Id</b>	4982
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	15 January 2024 09:31:59
<b>Modified</b>	1 February 2024 06:57:06
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	arch/arm
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

### Description

file:///opt/work/chris/rtems/releasing/rtems-release.git/6.1-rc2/ws-rtems-release-notes/rtems-6.1-rc2-release-notes.html

Add support for TMS570LC4357 chip variant using the TMS570LS43x Hercules Development Kit from TI.

#### **Comment 1**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:36:50 GMT

In 7427caa/rtems:

```
bsps/arm: Use shared empty bsp_start_hook_0()  
Update #4982.
```

#### **Comment 2**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:36:52 GMT

In 222c989/rtems:

```
bsp/tms570: Remove empty  
Update #4982.
```

#### **Comment 3**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:36:54 GMT

In 72ec63e7/rtems:

```
bsp/tms570: Remove empty  
Update #4982.
```

#### **Comment 4**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:36:56 GMT

In 58521f1/rtems:

```
bsp/tms570: Remove empty  
Update #4982.
```

#### **Comment 5**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:36:58 GMT

In 8e8b9bc0/rtems:

```
bsp/tms570: Relicense to BSD-2-Clause  
Change license to BSD-2-Clause according to file history and contributor agreements. Add Doxygen file comments.  
Update #3053. Update #3707. Update #4982.
```

#### **Comment 6**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:00 GMT

In 600bd565/rtems:

```
bsp/tms570: Use new pin define  
Update #4982.
```

#### **Comment 7**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:02 GMT

In 2110125/rtems:

```
bsp/tms570: Add bsp_restart()  
Update #4982.
```

**Comment 8**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:05 GMT

In 8240cae/rtems:

```
bsp/tms570: Rename tms570_initialize_and_clear()
Rename tms570_initialize_and_clear() in tms570_pom_initialize_and_clear().
Update #4982.
```

**Comment 9**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:07 GMT

In 849210f/rtems:

```
bsp/tms570: Fix bsp_reset()
Update #4982.
```

**Comment 10**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:09 GMT

In 27e0abb/rtems:

```
bsp/tms570: Avoid errno for debug console
Update #4982.
```

**Comment 11**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:11 GMT

In a6482eb/rtems:

```
bsp/tms570: Implement set/get interrupt priority
Update #4982.
```

**Comment 12**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:13 GMT

In 8753604e/rtems:

```
bsp/tms570: Implement interrupt is enabled/pending
Update #4982.
```

**Comment 13**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:15 GMT

In cf01329e/rtems:

```
bsp/tms570: Avoid spurious interrupts
Update #4982.
```

**Comment 14**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:17 GMT

In df067e5/rtems:

```
bsp/tms570: Add TM27 support
Update #4982.
```



**Comment 15**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:20 GMT

In 1dae4f95/rtems:

```
bsp/tms570: Remove obsolete build option
Update #4982.
```

**Comment 16**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:21 GMT

In 285d1a4/rtems:

```
bsp/tms570: Avoid vector overlay memory region
Reserve the space in a section. This makes it possible to use a common memory region definition.
Update #4982.
```

**Comment 17**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:23 GMT

In 1b7a8af5/rtems:

```
bsp/tms570: Add variant enable to build
Update #4982.
```

**Comment 18**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:26 GMT

In 437da01/rtems:

```
bsp/tms570: Add linkcmds.memory
Remove obsolete tms570ls3137_hdk_with_loader BSP variant. With the new memory origin/size build options this variant is no longer required.
Update #4982.
```

**Comment 19**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:28 GMT

In eb97cd1/rtems:

```
bsp/tms570: Add TMS570LC4357 BSP variants
Update #4982.
```

**Comment 20**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:30 GMT

In 36192165/rtems:

```
bsp/tms570: Fix PBIST clock enable
Bit 1 of the PACT is reserved (writes have no effect).
Update #4982.
```

**Comment 21**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:32 GMT

In 048d81a0/rtems:

```
bsp/tms570: Add TMS570LC4357 PBIST support
```

Update #4982.

#### **Comment 22**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:34 GMT

In 8569f01/rtems:

bsp/tms570: Enable hardware init for some variants  
Update #4982.

#### **Comment 23**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:36 GMT

In b995211/rtems:

bsp/tms570: Add tms570\_pbist\_run\_and\_check()  
Update #4982.

#### **Comment 24**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:38 GMT

In 39fd4b1/rtems:

bsp/tms570: Remove double pin configuration  
Do not set pins to the default function before the actual setting is applied. If a pin setting needs to be done in a certain order, then this should be done explicitly through multiple calls to tms570\_bsp\_pinmmr\_config().  
Update #4982.

#### **Comment 25**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:41 GMT

In 4f6fa974/rtems:

bsp/tms570: Add TMS570LC4357 pin config support  
Update #4982.

#### **Comment 26**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:43 GMT

In c14efe49/rtems:

bsp/tms570: Add TMS570LC4357 power support  
Update #4982.

#### **Comment 27**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:45 GMT

In eeaa318/rtems:

bsp/tms570: Simplify expression  
Update #4982.

#### **Comment 28**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:47 GMT

In 4d9c9c52/rtems:

bsp/tms570: Conditionalize TMS570LS3137 errata

Update #4982.

#### **Comment 29**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:49 GMT

In 75dd824/rtems:

bsp/tms570: Add errata SSWF021#45 handling

Update #4982.

#### **Comment 30**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:51 GMT

In 2bbacdb/rtems:

bsp/tms570: TMS570LC4x Errata DEVICE#60

Update #4982.

#### **Comment 31**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:53 GMT

In ec79400/rtems:

bsp/tms570: Add HCLKCNTL register

Update #4982.

#### **Comment 32**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:37:55 GMT

In b99013e/rtems:

bsp/tms570: Remove reset source handling

Do not clear SYSESR and let the application handle the reset source.

Update #4982.

#### **Comment 33**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:37:58 GMT

In f7530be/rtems:

bsp/tms570: Honor DBGRST for TMS570LC4357

Update #4982.

#### **Comment 34**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:00 GMT

In 23ba8d2c/rtems:

bsp/tms570: Use asm code for tms570\_memory\_init()

Make sure that we do not use the stack for this function.

Update #4982.

#### **Comment 35**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:02 GMT

In 2db0844/rtems:

bsp/tms570: Initialize SRAM on demand

Update #4982.

### **Comment 36**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:04 GMT

In 3f75b58/rtems:

bsp/tms570: The TMS570LC4357 has no TCRAM modules

Update #4982.

### **Comment 37**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:06 GMT

In e963447/rtems:

bsp/tms570: Add header guards

Update #4982.

### **Comment 38**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:08 GMT

In d4c6def/rtems:

bsp/tms570: Use shared bsp\_start\_hook\_1()

Update #4982.

### **Comment 39**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:10 GMT

In 663bedd/rtems:

bsp/tms570: Use bsp\_start\_copy\_sections\_compact()

There is no need to relocate the text and read-only data.

Update #4982.

### **Comment 40**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:12 GMT

In 5a2f64cf/rtems:

bsp/tms570: Initialize and enable caches on demand

Update #4982.

### **Comment 41**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:14 GMT

In 65831d7/rtems:

bsp/tms570: Optimize tms570\_debug\_console\_out()

Reduce number of interrupt disable/enable actions.

Update #4982.

### **Comment 42**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:38:16 GMT

In 53cbe748/rtems:

```
bsp/tms570: Initialize MPU
Update #4982.
```

**Comment 43**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:38:18 GMT

In b300b967/rtems:

```
bsp/tms570: Board-specific tms570_pll_init()
Update #4982.
```

**Comment 44**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:38:20 GMT

In 42e013a/rtems:

```
bsp/tms570: Board-specific tms570_map_clock_init()
Update #4982.
```

**Comment 45**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:38:23 GMT

In 87be7eab/rtems:

```
bsp/tms570: Board-specific tms570_pinmux_init()
Update #4982.
```

**Comment 46**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:38:25 GMT

In 449d836/rtems:

```
bsp/tms570: Board-specific tms570_emif_sdram_init()
Update #4982.
```

**Comment 47**

1. **Tyler Miller**, Mon, 15 Jan 2024 09:38:27 GMT

In b47c818/rtems:

```
bsp/tms570: Update README
Update #4982.
```

**Comment 48**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:29 GMT

In 9a961eec/rtems:

```
bsp/tms570: Remove unused BSP options
Update #4982.
```

**Comment 49**

1. **Sebastian Huber**, Mon, 15 Jan 2024 09:38:31 GMT

In df37864/rtems:

```
bsp/tms570: Use TMS570_OSCILLATOR_MAIN
```

This option replaces BSP\_OSCILATOR\_CLOCK. It may be used in PLL setup calculations.

Update #4982.

### Comment 50

1. **Sebastian Huber**, Thu, 25 Jan 2024 07:17:19 GMT

In 9fdaa4e/rtems-tools:

config: Update BSPs

Update #4982.

### Comment 51

1. **Adrien Chardon**, Thu, 01 Feb 2024 06:57:06 GMT

In b1fdf75/rtems:

bsp/tms570: Fix console receive interrupts

tms570\_sci\_interrupt\_handler() is called when an RX interrupt fires. It checks in the register FLR, the RXRDY bit (Receiver ready flag - indicate that the SCTRDR contains new data). If it is set, it calls tms570\_sci\_read\_received\_chars().

tms570\_sci\_read\_received\_chars() checks the register RD against 0. If it is non zero, it returns 1 to indicate that one byte was read.

In the old behavior, if it is zero, the function returns 0 to indicate that no data was read.

The new behavior is to not silently drop 0x00 bytes. Ignoring 0x00 bytes is fine when working with printable text (which, I assume, is how this driver was tested), but as soon as the UART is used in non canonical (raw) mode, with potentially 0x00 bytes, these bytes will be silently dropped, causing issues in the data/protocol layer above.

Update #4982.

---

## 4986 - Improve CONFIGURE\_TICKS\_PER\_TIMESLICE configuration and documentation

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4986">https://devel.rtems.org/ticket/4986</a> ( <a href="https://devel.rtems.org/ticket/4986">https://devel.rtems.org/ticket/4986</a> )
<b>Id</b>	4986
<b>Reporter</b>	Sebastian Huber
<b>Created</b>	31 January 2024 07:13:03
<b>Modified</b>	31 January 2024 07:13:03
<b>Owner</b>	Sebastian Huber
<b>Type</b>	enhancement
<b>Component</b>	config
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

---

### Description

The documentation allows a value of zero for CONFIGURE\_TICKS\_PER\_TIMESLICE. This should be changed to make zero an invalid value and it should be rejected by an #error configuration error.

---

## 4991 - RSB source and patch checksum updates

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4991">https://devel.rtems.org/ticket/4991</a> ( <a href="https://devel.rtems.org/ticket/4991">https://devel.rtems.org/ticket/4991</a> )
<b>Id</b>	4991
<b>Reporter</b>	Chris Johns
<b>Created</b>	16 February 2024 06:51:10
<b>Modified</b>	20 February 2024 00:58:30
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/rsb
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	normal
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

Downloaded files in the RSB are reporting checksum errors. This ticket is to cover the updates to correct this for the RTEMS 6 release.

**Comment 1**

1. **Chris Johns**, Sun, 18 Feb 2024 23:44:09 GMT

In ee02d32/rtems-source-builder:

```
gcc: gcc-4.9-1.cfg Make-lang patch checksum error
Updates #4991
```

**Comment 2**

1. **Chris Johns**, Tue, 20 Feb 2024 00:58:30 GMT

In 07ba8d5/rtems-source-builder:

```
rtems: Checksum fixes
Updates #4991
```

**4993 - Increase FD\_SIZE to 256**

<b>Link</b>	<a href="https://devel.rtems.org/ticket/4993">https://devel.rtems.org/ticket/4993</a> ( <a href="https://devel.rtems.org/ticket/4993">https://devel.rtems.org/ticket/4993</a> )
<b>Id</b>	4993
<b>Reporter</b>	Chris Johns
<b>Created</b>	19 February 2024 22:38:06
<b>Modified</b>	19 February 2024 22:38:17
<b>Owner</b>	Chris Johns
<b>Type</b>	defect
<b>Component</b>	tool/newlib
<b>Status</b>	assigned
<b>Resolution</b>	
<b>Version</b>	6
<b>Milestone</b>	6.1
<b>Priority</b>	highest
<b>Severity</b>	blocker
<b>Keywords</b>	
<b>Cc</b>	
<b>Blocking</b>	
<b>Blocked by</b>	

**Description**

The default for FD\_SIZE in newlib is 64. This is proving to be too small for EPICS applications. EPICS limits the number of descriptors here for RTEMS 6 builds. The comment in EPICS base is:

```
/* Note: The select() system call can only be used with the first FD_SETSIZE
 * File Descriptors (newlib default is 64). Beginning RTEMS 5.1, FDs are
 * allocated sequentially. So changing this CONFIGURE parameter such
 * that CONFIGURE_MAXIMUM_FILE_DESCRIPTOR >= FD_SETSIZE will likely
 * cause applications making select() calls to fault at some point.
 *
 * IOC core components (libca and RSRV) do not make select() calls.
 *
 * Applications and driver code using poll() or other socket
 * multiplexers do not share this limitation.
 *
 * cf. https://github.com/epics-base/epics-base/issues/300
 */
```

Increasing FD\_SIZE to 256 will increase the set but 64 is too small for RTEMS and we do not need 1024 that systems like FreeBSD have.

#### Comment 1

1. **Chris Johns**, Mon, 19 Feb 2024 22:38:17 GMT
2. **owner:** set to **Chris Johns**
3. **status:** changed from **new** to **assigned**

## 550 - fcntl() fails to put a non-blocking socket into blocking mode

<b>Link</b>	<a href="https://devel.rtems.org/ticket/550">https://devel.rtems.org/ticket/550</a> ( <a href="https://devel.rtems.org/ticket/550">https://devel.rtems.org/ticket/550</a> )
<b>Id</b>	550
<b>Reporter</b>	Thomas Rauscher
<b>Created</b>	16 January 2004 11:47:00
<b>Modified</b>	29 November 2022 21:47:15
<b>Owner</b>	Joel Sherrill
<b>Type</b>	defect
<b>Component</b>	network/legacy
<b>Status</b>	closed
<b>Resolution</b>	wontfix
<b>Version</b>	4.5
<b>Milestone</b>	6.1
<b>Priority</b>	normal
<b>Severity</b>	major
<b>Keywords</b>	
<b>Cc</b>	bugs@... joel.sherrill@...
<b>Blocking</b>	
<b>Blocked by</b>	

#### Description

A socket cannot be put into blocking mode using fcntl() once it has been put into non-blocking mode.

ioctl() is working fine, so the problem is not in the IP stack.

The problem occurs in real life with the GoAhead? webserver on high-latency connections as its non-blocking write socket remains non-blocking and a web page can be truncated when websDone() is called.

In newlib (1.10, 1.11) there are several non-blocking flags. The following is defined in sys/fcntl.h

```
#define _FNBIO 0x1000 /* non blocking I/O (sys5 style) */
#define _FNONBLOCK 0x4000 /* non blocking I/O (POSIX style) */
...
#define _FNDELAY _FNONBLOCK /* non blocking I/O (4.2 style) */
/* O_NDELAY _FNDELAY set in include/fcntl.h */
/* O_NDELAY _FNBIO set in 5include/fcntl.h */
#define O_NONBLOCK _FNONBLOCK
```

So O\_NDELAY is never defined. sys/fcntl.h is not patched by the rtems-newlib patch.

In RTEMS, libio.c and libio\_.h both contain the following code

```
#if ! defined(O_NDELAY)
# if defined(solaris2)
# define O_NDELAY O_NONBLOCK
# elif defined(RTEMS_NEWLIB)
# define O_NDELAY _FNBIO
# endif
#endif
```

As O\_NDELAY is undefined and RTEMS\_NEWLIB is defined, O\_NDELAY is defined to 0x1000.

Thus, using O\_NONBLOCK in fcntl() (this was suggested in the mailing list some time ago) doesn't seem to work.

Release:  
RTEMS-4.5

Environment:  
rtems-4.5.0, newlib-1.10 or newlib-1.11

#### Attachments:

- 1 **Thomas Rauscher, Sun, 03 Dec 2006 13:31:12 GMT**  
**attach:** set to [socketblock.c](https://devel.rtems.org/ticket/550/socketblock.c) (<https://devel.rtems.org/ticket/550/socketblock.c>)

#### Comment 1

1. **Joel Sherrill**, Fri, 16 Jan 2004 18:01:54 GMT
2. **status:** changed from **assigned** to **waiting**

State-Changed-From-To: open->feedback State-Changed-Why: Thomas ... does this happen in 4.6 or the current source?



I don't see this problem in the current code. At this point, no further releases from the 4.5 branch are planned so I am prone to close any bug report against it.

#### Comment 2

1. **Gedare Bloom**, Sat, 22 Nov 2014 14:23:02 GMT
2. **description:** modified (diff)
3. **milestone:** changed from **2** to **4.9.5**

#### Comment 3

1. **Gedare Bloom**, Sat, 22 Nov 2014 14:24:39 GMT
2. **owner:** changed from **Eric Norum** to **Joel Sherrill**

#### Comment 4

1. **Joel Sherrill**, Sun, 23 Nov 2014 18:52:45 GMT

I am hacking together a test but I believe this does happen in the current source. It looks like `so_ioctl(fd, FIONBIO, [O_NONBLOCK]~O_NONBLOCK)` needs to be called. We have the `ioctl_h` handler but should we make the call if networking is enabled?

#### Comment 5

1. **Joel Sherrill**, Sun, 23 Nov 2014 18:56:06 GMT

NOTE that FIONBIO is not defined in newlib -- only in the network stack so that makes for some trouble. I suppose we could modify `rtems_syscalls.c` to handle `F_SETFD`.

#### Comment 6

1. **Joel Sherrill**, Thu, 12 Feb 2015 17:46:49 GMT
2. **description:** modified (diff)
3. **milestone:** changed from **4.9.5** to **5.0**

This is a known issue with many RTOS'. The FACE (<http://www.opengroup.org/face>) standard has specifically had to add requirements so this behavior is required of RTOSes conforming to the FACE POSIX Profiles. The `ioctl()` interface is not in POSIX and `fcntl()` is the only way to set non-blocking in a pure POSIX environment.

I pushed this milestone to 5.0 because:

this is a long-standing issue. it is technically beyond the POSIX standard itself. it will need to be addressed with the current IPV4 stack, the new IPV4/IPV6 stack and LWIP if we are to support that. this needs test code. this needs a design that can work with multiple network stacks.

#### Comment 7

1. **Sebastian Huber**, Thu, 09 Nov 2017 06:26:42 GMT
2. **milestone:** changed from **5.0** to **6.1**

Milestone renamed

#### Comment 8

1. **Chris Johns**, Tue, 29 Nov 2022 21:47:15 GMT
2. **status:** changed from **assigned** to **closed**
3. **resolution:** set to **wontfix**

The fd handling has evolved and now we have libbsd. If this is still a problem please reopen.